

Water Resources Data for New Hampshire and Vermont, 2000

By M.F. Coakley, Chandlee Keirstead, R.O. Brown, and R.G. Kiah

INTRODUCTION

The Water Resources Division of the U.S. Geological Survey, in cooperation with State agencies, obtains a large amount of data pertaining to the water resources of New Hampshire and Vermont each water year. These data, accumulated during many water years, constitute a valuable data base for developing an improved understanding of the water resources of the States. To make these data readily available to interested parties outside the U.S. Geological Survey, the data are published annually in this report series entitled "Water Resources Data-New Hampshire and Vermont."

This report series includes records of stage, discharge, and water quality of streams; contents of lakes and reservoirs; and water levels of ground-water wells. This volume contains records for water discharge at 76 gaging stations; stage records for 5 lakes; month end contents for 2 lakes and reservoirs; and water levels at 28 observation wells. Also included are data for 43 crest-stage partial record stations. Locations of these sites are shown in figures 1 and 2. Additional water data were collected at various sites not involved in the systematic data-collection program and are published under miscellaneous discharge measurements and under Supplemental National Water-quality Assessment Data for Gaging Stations in New Hampshire and Vermont. The data in this report represent that part of the National Water Data System collected by the U.S. Geological Survey and cooperating State and Federal agencies in New Hampshire and Vermont.

This series of annual reports for New Hampshire and Vermont began with the 1961 water year with a

report that contained only data relating to the quantities of surface water and published as "Water Resources data for Massachusetts, New Hampshire, Rhode Island, and Vermont." For the 1964 water year, a similar report was introduced that contained only data relating to water quality. Beginning with the 1975 water year, the report format was changed to present, in one volume, data on quantities of surface water, quality of surface and ground water, and ground-water levels.

Prior to introduction of this series and for several water years concurrent with it, water-resources data for New Hampshire and Vermont were published in U.S. Geological Survey Water-Supply Papers. Data on stream discharge and stage and on lake or reservoir contents and stage, through September 1960, were published annually under the title "Surface-Water Supply of the United States, Parts 1A and 1B." For the 1961 through 1970 water years, the data were published in two 5-year reports. Data on chemical quality, temperature, and suspended sediment for the 1941 through 1970 water years were published annually under the title "Quality of Surface Waters of the United States," and water levels for the 1939 through 1974 water years were published under the title "Ground-Water Levels in the United States." The above mentioned Water-Supply Papers may be consulted in the libraries of the principal cities of the United States and may be purchased from U.S. Geological Survey, Branch of Information Services, Federal Center, Box 25286, Denver, Colorado 80225.

Publications similar to this report are published annually by the U.S. Geological Survey for all States. These official reports have an identification number



Figure 1. Location of surface-water data-collection sites.




Figure 2. Location of ground-water data-collection sites.

consisting of the two-letter State abbreviation, the last two digits of the water year, and the volume number. For example, this volume is identified as "U.S. Geological Survey Water-Data Report NH-VT-00-1." For archiving and general distribution, the reports for 1971-74 water years also are identified as water-data reports. These water-data reports are for sale in paper copy or in microfiche by the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161. Real-time and historical data from the surface-water network, as well as information about individual sites, are available through the world wide web at:

http://nh.water.usgs.gov/rt-cgi/gen_tbl_pg

<http://waterdata.usgs.gov/nwis-w/US/>

Additional information, including current prices, for ordering specific reports may be obtained from the District Office at the address given on the back of the title page or by telephone (603) 226-7800.

COOPERATION

The U.S. Geological Survey and organizations of the States of New Hampshire and Vermont have had cooperative agreements for the systematic collection of surface-water records since the early 1900's, and for groundwater records since the mid 60's. Organizations that assisted in collecting the data in this report through cooperative agreements with the U.S. Geological Survey are:

New Hampshire Department of Environmental Services,
Robert W. Varney, Commissioner

Vermont Department of Environmental Conservation,
Canute Dalmasse, Commissioner

City of Keene,
Patrick MacQueen, City Manager

City of Rochester,
Gary Stenhouse, City Manager

Assistance in the form of funds or services was provided by the Corps of Engineers, U.S. Army, in the collection of records for 20 gaging stations published in this report. Organizations supplying data are acknowledged in the station descriptions.

The following organizations contributed funds and services through the requirements of the Federal Energy Regulatory Commission:

Green Mountain Power Company

Citizens Utilities Company

On waters adjacent to the international boundary, certain gaging stations are maintained by the United States (or Canada) under agreement with Canada (or the United States), and the records are obtained and compiled in a manner equally acceptable to both countries. These stations are designated as "international gaging stations."

SUMMARY OF HYDROLOGIC CONDITIONS

Streamflow

Runoff for the 2000 water year was above-normal throughout much of New Hampshire and Vermont except southern and central New Hampshire. The Piscataqua and Merrimack River Basins were in the normal range (below normal refers to the lower quartile of record, above normal refers to the upper quartile of record, and normal refers to the two middle quartiles). The basis of the above-normal, normal, and below-normal ranges is a 30-year reference period (October 1961 through September 1990).

The 2000 monthly and annual mean discharges and the monthly and annual median discharges for the reference period of 1961-90 are shown in figure 3 for stations on the Pemigewasset River at Plymouth, New Hampshire, and Dog River at Northfield Falls, Vermont. These stations recorded 2000 water-year runoff of 128 and 112 percent of median (compared to 102 percent a year ago for each site) and were used with other stations as indicators of monthly runoff across both states.

The 2000 water year began with most of New Hampshire and Vermont experiencing above-normal runoff. Runoff declined to normal or just above-normal for the winter period before rising to above-normal levels with the spring snowmelt and greater than normal precipitation. As the snowpack melted in the southern and eastern basins (Hudson, Merrimack, Saco, and Piscataquog) in April and May, runoff dropped to normal ranges. Continued snowmelt in the high reaches of the St. Lawrence, Connecticut, and Androscoggin River Basins kept runoff levels above-normal through May. Summer runoff for most of New Hampshire and Vermont was normal except for the Hudson River Basin, which experienced above-normal runoff throughout the




Figure 3. Comparison of discharge at two long-term index gaging stations during the 2000 water year with median discharge for period 1961-90.

summer. Southwestern New Hampshire and central Vermont and New Hampshire also had above-normal runoff for parts of the summer. The following table is a summary of mean runoff for a number of sites.

Station No.	Record length (years)	Mean runoff in 2000 water year		
		Mean ft ³ /s	Percent of median	Range
01054000	87	3,177	131	above-normal
01064500	97	1,022	110	normal
01073500	67	291	104	normal
01076500	97	1,493	112	normal
01078000	83	149	106	normal
01092000	64	5,933	120	normal
01138500	51	6,086	125	above-normal
01152500	73	472	117	normal
01154500	59	11,250	120	above-normal
01161000	92	799	111	normal
01334000	70	276	126	above-normal
04282500	98	1,281	124	above-normal
04287000	66	154	128	above-normal
04292500	72	1,576	130	above-normal
04293500	81	1,250	137	above-normal
04296000	49	251	130	above-normal

Additional statistics for each gaging station in this report are provided in the tables of daily mean discharges. Monthly flow hydrographs from the network are also available through the world wide web at:

<http://nh.water.usgs.gov/WaterData/curr.htm>

<http://vt.water.usgs.gov/WaterData/curr.htm>

Floods and Droughts

Annual peak discharges at streamflow-gaging stations were recorded during the months of March, April, May, and July across the two States. The recurrence intervals of annual peak discharges at

most gaging stations were less than 5-years (peaks having a 1 in 5 chance of being equaled or exceeded in any given year) and ranged from less than 2-year to greater than a 5-year recurrence interval throughout the water year.

Minimum streamflows occurred during the late summer month of September for most of New Hampshire and Vermont. Minimum streamflows in the Hudson River Basin were observed in July. Runoff generally declined to about 50 to 96-percent flow duration (percentage of time daily flows will be equaled or exceeded) across both States.

Reservoir Storage

The total combined usable storage of 5 major reservoirs in both States is 22,436 million cubic feet. At the beginning of the water year, the actual usable storage from these reservoirs was 18,319 million cubic feet or 82 percent of capacity. Average reservoir storage remained at 80 percent of capacity through November, then followed a steady seasonal decline to a minimum capacity for the water year of 54 percent by the end of January. Average reservoir storage then increased to a maximum average capacity of 91 percent for the water year by the end of July and finally declined seasonally to a capacity of 67 percent at the end of September, which is a combined usable storage of 15,388 million cubic feet.

Ground-Water Levels

The ground-water observation-well network in New Hampshire consisted of 26 wells, and, in Vermont, 2 wells during the 2000 water year. Funding for the remaining network of Vermont wells was terminated at the end of the 1995 water year. Most wells are of small diameter and located in sandy material.

The monthly conditions summarized below are based on levels from selected representative wells across New Hampshire. The terms used below are defined as follows; **below-normal** refers to the lower quartile of ranked, monthly ground-water level readings, **above-normal** refers to the upper quartile, and **normal** refers to the two middle quartiles.

Ground-water conditions in New Hampshire were generally in the normal range from October

through December. January and February were predominantly below-normal with significant winter conditions keeping any ground-water recharge to a minimum. Ground-water conditions for the spring months of March through May were generally normal. Flows during June through September were generally normal but punctuated by isolated pockets of above- and/or below-normal conditions probably corresponding to effects of isolated, summer-time rain events.

Listed below are the monthly ground-water conditions for New Hampshire, summarized by general trends and exceptions.

October Ground-water levels were **normal**, except for the extreme southwestern part of the state, the lower Merrimack River valley, the sea-coast region, and the northern third of the state, which were **above-normal**.

November Ground-water levels were **normal**, except for the northeastern quarter of the state and a small pocket around the lower Contoocook River valley, which were **above-normal**.

December Ground-water levels were **normal**.

January Ground-water levels were **below-normal**, except for a swath through central New Hampshire from the middle Connecticut River valley to the seacoast and for the Upper Ammonoosuc and Israel River valleys, which were **normal**.

February Ground-water levels were **normal**, except for southeastern parts of the state (the seacoast region extending west to parts of the lower Merrimack River valley and north to parts of the Lake's region) and the region north of the White Mountains, which were **below-normal**.

March Ground-water levels were **normal**, except for the Israel River valley and parts of the Upper Ammonoosuc River valley in northern New Hampshire, which were **below-normal**.

April Ground-water levels were **normal**, except for parts of the Lamprey, Cocheco, and Salmon Falls River valleys in southeastern New Hampshire and the Ashuelot River valley in southwestern New Hampshire, which were **above-normal**.

May Ground-water levels were **normal**, except for lower and middle parts of the Connecticut River valley in western New Hampshire, which were **above-normal**.

June Ground-water levels were **normal**, except for the extreme southern part of the state along the Massachusetts border and parts of the Warner, Blackwater, Smith, and Mascoma River valleys, which were **above-normal**, and except for parts of the Piscataqua and

Merrymeeting River valleys in southeastern New Hampshire and for parts of the Israel, Upper Ammonoosuc, and Androscoggin River valleys in northern New Hampshire, which were **below-normal**.

July

Ground-water levels were **normal**, except for the Warner, Blackwater, Cold, and Ashuelot River valleys in the southwestern part of the State, which were **above-normal**, and except for the Androscoggin and extreme upper Connecticut River valleys in northern New Hampshire, which were **below-normal**.

August

Ground-water levels were **normal**, except for the southwestern part of the State (including the Sugar, Ashuelot, and Contoocook River valleys), which was **above-normal**, and except for a swath through the northern White Mountains region (including the Ammonoosuc and Androscoggin River valleys), which was **below-normal**.

September Ground-water levels were **normal**, except for northern New Hampshire (the White Mountain and North Country regions combined) and the Salmon Falls River valley, which were **below-normal**, and for southwestern New Hampshire (including the Contoocook, Piscataquog, Souhegan, and lower Ashuelot River valleys), which were **above-normal**.

New monthly lows (the lowest water level recorded for a given month) were recorded at the following wells during the 2000 water year:

Deerfield (DDW 46) in Feb.

Errol (ETW 1) in Oct. and Feb.

Lancaster (LCW 1) in June.

Lisbon (LLW 19) in Jan., Feb., Aug., and Sep. (this also set a new low water level for period of record).

Newport (NPW 3) in Mar.

Newport (NPW 6) in Mar.

Shelburne (SJW 2) in Aug.

New monthly highs (the highest water level recorded for a given month) were recorded at the following wells during the 2000 water year:

Barnstead (BAW 10) in May.

Colebrook (CTW 73) in Oct. (this also set a new high water level for period of record) and Nov.

Enfield (ENW-30) in May.

Lisbon (LLW 19) in May.

Nashua (NAW 218) in Apr.

Newport (NPW 3) in Aug.

Shelburne (SJW 2) in Apr.

Hydrographs for each of the ground-water-station records contained in this report provide additional information on water-level trends. Monthly conditions data from the network are also available through the world wide web at:

<http://nh.water.usgs.gov/WaterData/curr.htm>

SPECIAL NETWORKS AND PROGRAMS

The National Water-Quality Assessment (NAWQA) Program of the U.S. Geological Survey is a long-term program with goals to describe the status and trends of water-quality conditions for a large, representative part of the Nation's ground- and surface-water resources; provide an improved understanding of the primary natural and human factors affecting these observed conditions and trends; and provide information that supports development and evaluation of management, regulatory, and monitoring decisions by other agencies.

Assessment activities are being conducted in 53 study units (major watersheds and aquifer systems) that represent a wide range of environmental settings nationwide and that account for a large percentage of the Nation's water use. A wide array of chemical constituents will be measured in ground water, surface water, streambed sediments, and fish tissues. The coordinated application of comparative hydrologic studies at a wide range of spatial and temporal scales will provide information for decision making by water-resources managers and a foundation for aggregation and comparison of findings to address water-quality issues of regional and national interest.

Communication and coordination between USGS personnel and other local, State, and Federal interests are critical components of the NAWQA Program. Each study unit has a local liaison committee consisting of representatives from key Federal, State, and local water resources agencies, Indian nations, and universities in the study unit. Liaison committees typically meet annually to discuss their information needs, monitoring plans and progress, desired information products, and opportunities to collaborate efforts among the agencies.

The New England Coastal Basins (NECB) NAWQA study unit encompasses 23,000 square

miles in western and central Maine, eastern New Hampshire, eastern Massachusetts, most of Rhode Island, and a small part of eastern Connecticut. In WY 2000, the NECB NAWQA study collected water samples from 11 stream sites and 17 ground water wells (fig. 4). Data from these sites are presented in the Miscellaneous Surface-Water Quality and Miscellaneous Ground-Water Quality sections of this report.

Additional information about the NAWQA Program is available through the world wide web at:

http://wwwrvares.er.usgs.gov/nawqa/nawqa_home.html

EXPLANATION OF THE RECORDS

The surface-water and ground-water records published in this report are for the 2000 water year that began October 1, 1999, and ended September 30, 2000. A calendar of the water year is provided on the inside of the front cover. The records contain streamflow data, stage and content data for lakes and reservoirs, water-quality data for surface water, and ground-water-level data.

The locations of the stations and wells where the data were collected are shown in figures 1 and 2. The following sections of the introductory text are presented to provide users with a more detailed explanation of how the hydrologic data published in this report were collected, analyzed, computed, and arranged for presentation.

Station Identification Numbers

Each data station, whether streamgage or well, in this report is assigned a unique identification number. The number usually is assigned when a station is first established and is retained for that station indefinitely. The systems used by the U.S. Geological Survey to assign identification numbers for surface-water stations and for ground-water well sites differ, but both are based on geographic location. The "downstream-order" system is used for surface-water stations and the "latitude-longitude" system is used for wells.




Figure 4. Location of surface- and ground-water quality data-collection sites for the National Water Quality Assessment (NAWQA) program.

Downstream Order System

Since October 1, 1950, the order of listing hydrologic-station records in U.S. Geological Survey reports is in a downstream direction along the main stream. All stations on a tributary entering upstream from a mainstream station are listed before that station. A station on a tributary that enters between two mainstream stations is listed between them. A similar order is followed in listing stations on first rank, second rank, and other ranks of tributaries. The rank of any tributary with respect to the stream to which it is immediately tributary is indicated by an indentation in the "List of Stations" in the front of this report. Each indentation represents one rank. This downstream order and system of identification shows which stations are on tributaries between any two stations and the rank of the tributary on which each station is situated.

The station-identification number is assigned according to downstream order. In assigning station numbers, no distinction is made between continuous-record stations and other types of stations; therefore, the station number for a continuous-record station indicates downstream-order position in a list made up of all types of stations. Gaps are left in the series of numbers to allow for new stations that may be established; hence, the numbers are not consecutive. The complete station number (usually eight digits, but sometimes nine or more if needed) appears just to the left of the station name. The first two digits indicate the Part number (formerly used in Water-Supply Papers to designate major river systems) and the last six or more digits indicate the downstream order within the Part. For example, in the station number 01076500, "01" is the Part number for "North Atlantic Slope Basins" and "076500" is the downstream order number.

Latitude-Longitude System

The identification numbers for wells are assigned according to the grid system of latitude and longitude. The number consists of 15 digits. The first six digits denote the degrees, minutes, and seconds of latitude, the next seven digits denote degrees, minutes, and seconds of longitude, and the last two digits (assigned sequentially) identify the wells or other sites within a 1-second grid. This site-identification number, once assigned, is a pure




Figure 5. System for numbering wells and miscellaneous sites (latitude and longitude).

number and has no locational significance. In the rare instance where the initial determination of latitude and longitude is found to be in error, the station will retain its initial identification number; however, its true latitude and longitude will be listed in the LOCATION paragraph of the station description. (See figure 5.)

A local well number is also used in this report. The local well number consists of a 2-letter code for the town in which the well is located followed by a "W" signifying that it is a well, and a sequential number. The local number is used to identify the location of observation wells on figure 2.

Records of Stage and Water Discharge

Records of stage and water discharge may be complete or partial. Complete records of discharge are those obtained using a continuous stage-recording device through which either instantaneous or mean daily discharges may be computed for any time, or any period of time, during the period of record. Complete records of lake or reservoir content, similarly, are those for which stage or content may be computed or estimated with reasonable accuracy for any time, or period of time.

They may be obtained using a continuous stage-recording device, but need not be. Because daily mean discharges and end-of-day contents

commonly are published for such stations, they are referred to as "daily stations."

By contrast, partial records are obtained through discrete measurements with/without using a continuous stage-recording device and pertain only to a few flow characteristics, or perhaps only one. The nature of the partial record is indicated by table titles such as "Crest-stage partial records," or "Low-flow partial records." Records of miscellaneous discharge measurements or of measurements from special studies, such as low-flow seepage studies, may be considered as partial records, but they are presented separately in this report. Location of all complete-record stations for which data are given in this report are shown in figure 1. Some streamflow data from the network, as well as information for individual sites, are available through the world wide web at:

<http://nh.water.usgs.gov/WaterData/WaterDataPage.htm>

Data Collection and Computation

The data obtained at a complete-record gaging station on a stream or canal consist of a continuous record of stage, individual measurements of discharge throughout a range of stages, and notations regarding factors that may affect the relationships between stage and discharge. These data, together with supplemental information, such as weather records, are used to compute daily discharges. The data obtained at a complete-record gaging station on a lake or reservoir consist of a record of stage and of notations regarding factors that may affect the relationship between stage and lake content. These data are used with stage-area and stage-capacity curves or tables to compute water-surface areas and lake storage.

Continuous records of stage are obtained with digital recorders that punch stage values on paper tapes at selected time intervals or with electronic data loggers which collect, store, and transmit data via satellite. Measurements of discharge are made with current meters using methods adopted by the U.S. Geological Survey as a result of experience accumulated since 1880. These methods are described in standard textbooks, Water-Supply Paper 2175, and the U.S. Geological Survey Techniques of Water-Resources Investigations (TWRI's), Book 3, Chapter A1 through A19 and Book 8, Chapters A2 and B2. The methods are consistent with the

American Society for Testing and Materials (ASTM) standards and generally follow the standards of the International Organization for standards (ISO).

In computing discharge records, results of individual measurements are plotted against the corresponding stages, and stage-discharge relation curves are then constructed. From these curves, rating tables indicating the approximate discharge for any stage within the range of the measurements are prepared. If it is necessary to define extremes of discharge outside the range of the current-meter measurements, the curves are extended using (1) logarithmic plotting; (2) velocity-area studies; (3) results of indirect measurements of peak discharge, such as slope-area or contracted-opening measurements, and computations of flow over dams or weirs; or (4) step-backwater techniques.

Daily mean discharge is computed by applying the daily mean stage (gage height) to the stage-discharge rating table or by applying each recorded stage in the day to the rating table and computing the mean from the sum of the individual discharges. If the stage-discharge relation is subject to change because of frequent or continual change in the physical features that form the control, the daily mean discharge is determined by the shifting-control method, in which correction factors based on the individual discharge measurements and notes of the personnel making the measurements are applied to the gage heights before the discharges are determined from the curves or tables. This shifting-control method also is used if the stage-discharge relation is changed temporarily because of aquatic growth or debris on the control. For some stations, formation of ice in the winter may so obscure the stage-discharge relations that daily mean discharges must be estimated from other information such as temperature and precipitation records, notes of observations, and records for other stations in the same or nearby basins for comparable periods.

At some stream-gaging stations, the stage-discharge relation is affected by the backwater from reservoirs, tributary streams, or other sources. This necessitates the use of the slope method in which the slope or fall in a reach of the stream is a factor in computing discharge. The slope or fall is obtained by means of an auxiliary gage set at some distance from the base gage. At some stations the

stage-discharge relation is affected by changing stage; at these stations the rate of change in stage is used as a factor in computing discharge.

At some gaging stations, acoustic velocity meter (AVM) systems are used to compute discharge. The AVM system measures the stream's velocity at one or more paths in the cross section. Coefficients are developed to relate this path velocity to the mean velocity in the cross section. Because the AVM sensors are fixed in position, the adjustment coefficients generally vary with stage. Cross-sectional area curves are developed to relate stage, recorded as noted above, to cross section area. Discharge is computed by multiplying path velocity by the appropriate stage related coefficient and area.

In computing records of lake or reservoir contents, it is necessary to have available surveys, curves, or tables defining the relationship of stage and content. The application of stage to the stage-content curves or tables gives the contents from which daily, monthly, or yearly changes are determined. If the stage-content relation changes because of deposition of sediment in a lake or reservoir, periodic resurveys may be necessary to redefine the relation. Even when this is done, the contents computed may become increasingly in error as the lapsed time since the last survey increases. Discharges over lake or reservoir spillways are computed from stage-discharge relations much as other stream discharges are computed.

For some gaging stations, there are periods when no gage-height record is obtained, or the recorded gage height is so faulty that it cannot be used to compute daily discharge or contents. This happens when the recorder stops or otherwise fails to operate properly, intakes are plugged, the float is frozen in the well, or for various other reasons. For such periods, the daily discharges are estimated from the recorded range in stage, previous or following record, discharge measurements, weather records, comparison with other station records from the same or nearby basins, and regression analysis. Likewise, daily contents may be estimated from operator's logs, previous or following record, inflow-outflow studies, and other information. Information explaining how estimated daily-discharge values are identified in station records is included in the next two sections, "Data Presentation" (REMARKS paragraph) and "Identifying Estimated Daily Discharge."

Data Presentation

Streamflow data in this report are presented in a new format that is considerably different from the format in data reports prior to the 1991 water year. The major changes are that statistical characteristics of discharge now appear in tabular summaries following the water-year data table and less information is provided in the text or station manuscript above the table. These changes represent the results of a pilot program to reformat the annual water-data report to meet current user needs and data preferences.

The records published for each continuous-record surface-water discharge station (gaging station) now consist of four parts, the manuscript or station description; the data table of daily mean values of discharge for the current water year with summary data; a tabular statistical summary of monthly mean flow data for a designated period, by water year; and a summary statistics table that includes statistical data of annual, daily, and instantaneous flows as well as data pertaining to annual runoff, 7-day low-flow minimums, and flow duration.

Station Manuscript

The manuscript provides, under various headings, descriptive information, such as station location; period of record; historical extremes outside the period of record; record accuracy; and other remarks pertinent to station operation and regulation. The following information, as appropriate, is provided with each continuous record of discharge or lake content. Comments to follow clarify information presented under the various headings of the station description.

LOCATION.--Information on locations is obtained from the most accurate maps available. The location of the gage with respect to the cultural and physical features in the vicinity and with respect to the reference place mentioned in the station name is given. River mileages, given for only a few stations, were determined by methods given in "River Mileage Measurement," Bulletin 14, Revision of October 1968, prepared by the Water Resources Council or were provided by the U.S. Army Corps of Engineers.

DRAINAGE AREA.--Drainage areas are measured using the most accurate maps available. Because the type of maps available varies from one drainage

basin to another, the accuracy of drainage areas likewise varies. Drainage areas are updated as better maps become available.

PERIOD OF RECORD.--This indicates the period for which there are published records for the station or for an equivalent station. An equivalent station is one that was in operation at a time that the present station was not and whose location was such that records from it can reasonably be considered equivalent with records from the present station.

REVISED RECORDS.--Because of new information, published records occasionally are found to be incorrect, and revisions are printed in later reports. Listed under this heading are all the reports in which revisions have been published for the station and the water years to which the revisions apply. If a revision did not include daily, monthly, or annual figures of discharge, that fact is noted after the year dates as follows: "(M)" means that only the instantaneous maximum discharge was revised; "(m)" that only the instantaneous minimum was revised; and "(P)" that only peak discharges were revised. If the drainage area has been revised, the report in which the most recently revised figure was first published is given.

GAGE.--The type of gage in current use, the datum of the current gage referred to sea level (see glossary), and a condensed history of the types, locations and datums of previous gages are given under this heading.

REMARKS.--All periods of estimated daily discharge will either be identified by date in this paragraph of the station description for water-discharge stations or flagged in the daily discharge table. (See next section, "Identifying Estimated Daily Discharge.") If a REMARKS paragraph is used to identify estimated record, the paragraph will begin with this information presented as the first entry. The paragraph is also used to present information relative to the accuracy of the records, to special methods of computation, and to conditions that affect natural flow at the station. In addition, information may be presented pertaining to average discharge data for the period of record; to extremes data for the period of record and the current year; and, possibly, to other pertinent items. For reservoir stations, information is given on the dam forming the reservoir, the capacity, outlet works and spillway, and purpose and use of the reservoir.

COOPERATION.--Records provided by a cooperating organization or obtained for the U.S. Geological Survey by a cooperating organization are identified here.

EXTREMES OUTSIDE PERIOD OF RECORD.--Included here is information concerning major floods or unusually low flows that occurred outside the stated period of record. The information may or may not have been obtained by the U.S. Geological Survey.

REVISIONS.--If a critical error in published records is discovered, a revision is included in the first report published following discovery of the error.

Although rare, occasionally the records of a discontinued gaging station may need revision. Because, for these stations, there would be no current or, possibly, future station manuscript published to document the revision in a "Revised Records" entry, users of data for these stations who obtained the record from previously published data reports may wish to contact the District Office (address given on the back of the title page of this report) to determine if the published records were ever revised after the station was discontinued. Of course, if the data for a discontinued station were obtained by computer retrieval, the data would be current and there would be no need to check because any published revision of data is always accompanied by revision of the corresponding data in computer storage.

Manuscript information for lake or reservoir stations differs from that for stream stations in the nature of the "Remarks" and in the inclusion of a skeleton stage-capacity table when daily contents are given.

Headings for AVERAGE DISCHARGE, EXTREMES FOR PERIOD OF RECORD, AND EXTREMES FOR CURRENT YEAR have been deleted and the information contained in these paragraphs, except for the listing of secondary instantaneous peak discharges in the EXTREMES FOR CURRENT YEAR paragraph, is now presented in the tabular summaries following the discharge table or in the REMARKS paragraph, as appropriate. No changes have been made to the data presentations of lake contents.

Data Table of Daily Mean Values

The daily table of discharge records for stream-gaging stations gives mean discharge for

each day of the water year. In the monthly summary for the table, the line headed "TOTAL" gives the sum of the daily figures for each month; the line headed "MEAN" gives the average flow in cubic feet per second for the month; and the lines headed "MAX" and "MIN" give the maximum and minimum daily mean discharges, respectively, for each month. Discharge for the month also is usually expressed in cubic feet per second per square mile (line headed "CFSM"); or in inches (line headed "IN."); or in acre-feet (line headed "AC-FT"). Figures for cubic feet per second per square mile and runoff in inches or in acre-feet may be omitted if there is extensive regulation or diversion or if the drainage area includes large noncontributing areas. At some stations monthly and (or) yearly observed discharges are adjusted for reservoir storage or diversion, or diversion data or reservoir contents are given. These figures are identified by a symbol and corresponding footnote.

Statistics of Monthly Mean Data

A tabular summary of the mean (line headed "MEAN"), maximum (line headed "MAX"), and minimum (line headed "MIN") of monthly mean flows for each month for a designated period is provided below the mean values table. The water years of the first occurrence of the maximum and minimum monthly flows are provided immediately below those figures. The designated period will be expressed as "FOR WATER YEARS _ - _, BY WATER YEAR (WY)," and will list the first and last water years of the range of years selected from the PERIOD OF RECORD paragraph in the station manuscript. It will consist of all of the station record within the specified water years, inclusive, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript.

Summary Statistics

A table titled "SUMMARY STATISTICS" follows the statistics of monthly mean data tabulation. This table consists of four columns, with the first column containing the line headings of the statistics being reported. The table provides a statistical summary of yearly, daily, and instantaneous flows, not only for

the current water year but also for the previous calendar year and for a designated period, as appropriate. The designated period selected, "WATER YEARS _ - _," will consist of all of the station record within the specified water years, inclusive, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript. All of the calculations for the statistical characteristics designated ANNUAL (See line headings below.), except for the "ANNUAL 7-DAY MINIMUM" statistic, are calculated for the designated period using complete water years. The other statistical characteristics may be calculated using partial water years.

The date or water year, as appropriate, of the first occurrence of each statistic reporting extreme values of discharge is provided adjacent to the statistic. Repeated occurrences may be noted in the REMARKS paragraph of the manuscript or in footnotes. Because the designated period may not be the same as the station period of record published in the manuscript, occasionally the dates of occurrence listed for the daily and instantaneous extremes in the designated-period column may not be within the selected water years listed in the heading. When this occurs, it will be noted in the REMARKS paragraph or in footnotes. Selected streamflow duration curve statistics and runoff data are also given. Runoff data may be omitted if there is extensive regulation or diversion of flow in the drainage basin.

The following summary statistics data, as appropriate, are provided with each continuous record of discharge. Comments to follow clarify information presented under the various line headings of the summary statistics table.

ANNUAL TOTAL.--The sum of the daily mean values of discharge for the year. At some stations the annual total discharge is adjusted for reservoir storage or diversion. The adjusted figures are identified by a symbol and corresponding footnotes.

ANNUAL MEAN.--The arithmetic mean of the individual daily mean discharges for the year noted or for the designated period. At some stations the yearly mean discharge is adjusted for reservoir storage or diversion. The adjusted figures are identified by a symbol and corresponding footnotes.

HIGHEST ANNUAL MEAN.--The maximum annual mean discharge occurring for the designated period.

LOWEST ANNUAL MEAN.--The minimum annual mean discharge occurring for the designated period.

HIGHEST DAILY MEAN.--The maximum daily mean discharge for the year or for the designated period.

LOWEST DAILY MEAN.--The minimum daily mean discharge for the year or for the designated period.

ANNUAL 7-DAY MINIMUM.--The lowest mean discharge for 7 consecutive days for a calendar year or a water year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1-March 31). The date shown in the summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year low-flow statistic.)

INSTANTANEOUS PEAK FLOW.--The maximum instantaneous discharge occurring for the water year or for the designated period. Note that secondary instantaneous peak discharges above a selected base discharge are stored in District computer files for stations meeting certain criteria. Those discharge values may be obtained by writing to the District Office. (See address on back of title page of this report.)

INSTANTANEOUS PEAK STAGE.--The maximum instantaneous stage occurring for the water year or for the designated period. If the dates of occurrence for the instantaneous peak flow and instantaneous peak stage differ, the REMARKS paragraph in the manuscript or a footnote may be used to provide further information.

INSTANTANEOUS LOW FLOW.--The minimum instantaneous discharge occurring for the water year or for the designated period.

ANNUAL RUNOFF.--Indicates the total quantity of water in runoff for a drainage area for the year. Data reports may use any of the following units of measurement in presenting annual runoff data:

Acre-foot (AC-FT) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet or about 326,000 gallons or 1,233 cubic meters.

Cubic feet per second per square mile (CFSM) is the average number of cubic feet of water flowing per second from each square mile area drained, assuming the runoff is distributed uniformly in time and area.

Inches (INCHES) indicates the depth to which the drainage area would be covered if all of the runoff for a given time period were uniformly distributed on it.

10 PERCENT EXCEEDS.--The discharge that has been exceeded 10 percent of the time for the designated period.

50 PERCENT EXCEEDS.--The discharge that has been exceeded 50 percent of the time for the designated period.

90 PERCENT EXCEEDS.--The discharge that has been exceeded 90 percent of the time for the designated period.

Data collected at partial-record stations follow the information for continuous-record sites. Data for partial-record discharge stations are presented in two tables. The first is a table of annual maximum stage and discharge at crest-stage stations, and the second is a table of discharge measurements at low-flow partial-record stations. The tables of partial-record stations are followed by a listing of discharge measurements made at sites other than continuous-record or partial-record stations. These measurements are generally made in times of drought or flood to give better areal coverage to those events. Those measurements and others collected for some special reason are called measurements at miscellaneous sites.

Identifying Estimated Daily Discharge

Estimated daily-discharge values published in the water-discharge tables of annual State data reports are identified either by flagging individual daily values with the letter symbol "e" and printing a table footnote, "e - Estimated," or by listing the dates of the estimated record in the REMARKS paragraph of the station description.

Accuracy of the Records

The accuracy of streamflow records depends primarily on: (1) The stability of the stage-discharge relation or, if the control is unstable, the frequency of discharge measurements; and (2) the accuracy of measurements of stage, measurements of discharge, and interpretation of records.

The accuracy attributed to the records is indicated under "REMARKS." "Excellent" means that about 95 percent of the daily discharges are within 5 percent of their true values; "good," within

10 percent; and “fair,” within 15 percent. Records that do not meet the criteria mentioned are rated “poor.” Different accuracies may be attributed to different parts of a given record.

Daily mean discharges in this report are given to the nearest hundredth of a cubic foot per second for values less than 1 ft³/s; to the nearest tenth between 1.0 and 10 ft³/s; to whole numbers between 10 and 1,000 ft³/s; and to 3 significant figures for more than 1,000 ft³/s. The number of significant figures used is based solely on the magnitude of the discharge value. Discharges listed for partial-record stations and miscellaneous sites are generally shown to three significant figures.

Discharge at many stations, as indicated by the monthly mean, may not reflect natural runoff due to the effects of diversion, consumption, regulation by storage, increase or decrease in evaporation due to artificial causes, or to other factors. For such stations, figures of cubic feet per second per square mile and of runoff, in inches, are not published unless satisfactory adjustments can be made for diversions, for changes in contents of reservoirs, or for other changes incident to use and control. Evaporation from a reservoir is not included in the adjustments for changes in reservoir contents, unless it is so stated. Even at those stations where adjustments are made, large errors in computed runoff may occur if adjustments or losses are large in comparison with the observed discharge.

Other Records Available

Information used in the preparation of the records in this publication, such as discharge-measurement notes, gage-height records, temperature measurements, and rating tables is on file in the District Office. Also, most of the daily mean discharges are in computer-readable form and have been analyzed statistically. Information on the availability of the unpublished information or on the results of statistical analyses of the published records may be obtained from the New Hampshire-Vermont District Office at the address given on the back of the title page or by telephone (603) 226-7800.

Records of Surface-Water Quality

Records of surface-water quality ordinarily are obtained at or near stream-gaging stations because interpretation of records of surface-water quality

nearly always requires corresponding discharge data. Records of surface-water quality in this report may involve a variety of types of data and measurement frequencies.

Classification of Records

Water-quality data for surface-water sites are grouped into one of three classifications. A **continuing-record station** is a site where data are collected on a regularly scheduled basis. Frequency may be once or more times daily, weekly, monthly, or quarterly. A **partial-record station** is a site where limited water-quality data are collected systematically over a period of years. Frequency of sampling is usually less than quarterly. A **miscellaneous sampling site** is a location other than a continuing or partial-record station where random samples are collected to give better areal coverage to define water-quality conditions in the river basin.

A careful distinction needs to be made between “continuing **records**”, as used in this report, and “continuous **recordings**,” which refers to a continuous graph or a series of discrete values recorded at short intervals. Some records of water quality, such as temperature and specific conductance, may be obtained through continuous recordings; however, because of costs, most data are obtained only monthly or less frequently. In this report, continuing-record stations where data are collected on a continuous basis are referred to as **continuous-recording stations**. Locations of stations for which records on the quality of surface water appear in this report are shown in figure 1.

Arrangement of Records

Water-quality records collected at a surface-water daily record station are published immediately following that record, regardless of the frequency of sample collection. Station number and name are the same for both records. Where a surface-water daily record station is not available or where the water quality differs significantly from that at the nearby surface-water station, the continuing water-quality record is published with its own station number and name in the regular downstream-order sequence. Water-quality data for miscellaneous sampling sites appear in separate tables following the table of discharge measurements at miscellaneous sites.

Onsite Measurements and Sample Collection

In obtaining water-quality data, a major concern is to assure that the data obtained represent the in-situ quality of the water. To do this, certain measurements, such as water temperature, pH, alkalinity, dissolved oxygen, and specific conductance need to be made on-site when the samples are taken. To assure that measurements made in the laboratory also represent the in-situ water, carefully prescribed procedures need to be followed in collecting the samples, in treating the samples to prevent changes in quality pending analysis, and in shipping the samples to the laboratory.

Procedures for on-site measurements and for collecting, treating, and shipping samples are given in the TWRI Book 1, Chapter D2; Book 3, Chapter C2; and Book 5, Chapters A1, A3, and A4. These references are listed in the PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS section of this report. These methods are consistent with ASTM standards and generally follow ISO standards.

One sample can define adequately the water quality at a given time if the mixture of solutes throughout the stream cross section is homogeneous. However, the concentration of solutes at different locations in the cross section may vary widely with different rates of water discharge, depending on the source of material and the turbulence and mixing of the stream. Some streams must be sampled through several vertical sections to obtain a representative sample needed for an accurate mean concentration and for use in calculating load. All samples obtained for the National Water-Quality Assessment Program are usually obtained from at least several verticals. Whether samples are obtained from the centroid of flow or from several verticals depends on flow conditions and other factors which must be evaluated by the collector.

Water-quality data published in this report are considered to be the most representative values available for the stations listed. The values reported represent water-quality conditions at the time of sampling as much as possible, consistent with available sampling techniques and methods of analysis.

Water Temperature

Water temperatures are measured at all water-quality stations. Large streams have a small diurnal temperature change; shallow streams may have a daily range of several degrees and may follow closely the changes in air temperature. Some streams may be affected by waste-heat discharges. At stations where recording instruments are used, both mean, maximum, and minimum temperatures for each day are published.

Laboratory Measurements

Samples are analyzed locally for specific conductance, dissolved oxygen, pH, and temperature. All other samples were analyzed in the Geological Survey laboratory in Lakewood, Colorado. Methods used to analyze sediment samples and to compute sediment records are described in the TWRI Book 5, Chapter C1. Methods used by the U.S. Geological Survey laboratories are given in the TWRI Book 1, Chapter D2; Book 3, Chapter C2; and Book 5, Chapters A1, A3, A4, and A5. These methods are consistent with ASTM standards and generally follow ISO standards.

Data Presentation

For continuing-record stations, information pertinent to the history of station operation is provided in descriptive headings preceding the tabular data. These descriptive headings give details regarding location, drainage area, period of record, type of data available, instrumentation, general remarks, and extremes for parameters currently measured daily. Tables of water-quality data, including chemical, physical, biological, radiochemical data, and so forth, obtained at a frequency less than daily are presented first. Tables of "daily values" of specific conductance, pH, water temperature, and dissolved oxygen data from water-quality monitor recorders follow in sequence.

In the descriptive headings, if the location is identical to that of the discharge gaging station, neither the LOCATION nor the DRAINAGE AREA statements are repeated. The following information, as appropriate, is provided with each continuing-record station. Comments that follow clarify information presented under the various headings of the station description.

LOCATION.--See Data Presentation under "Records of Stage and Water Discharge;" same comments apply.

DRAINAGE AREA.--See Data Presentation under "Records of Stage and Water Discharge;" same comments apply.

PERIOD OF RECORD.--This indicates the periods for which there are published water-quality records for the station. The periods are shown separately for records of parameters measured daily or continuously and those measured less than daily. For those measured daily or continuously, periods of daily record are given for the parameters individually.

INSTRUMENTATION.--Information on instrumentation is given only if a water-quality monitor, or temperature recording device is in operation at a station.

REMARKS.--Remarks provide added information pertinent to the collection, analysis, or computation of the records.

EXTREMES.--Maximums and minimums are given only for parameters measured daily or more frequently. Extremes are provided for both the period of daily record and for the current water year. If a value from a miscellaneous measurement from outside the period of daily record has higher maximum or lower minimum, that value is reported in a descriptive heading for extremes outside the period of daily record.

REVISIONS.--If errors in published water-quality records are discovered after publication, appropriate updates are made to the Water-Quality File in the U.S. Geological Survey's computerized data system, WATSTORE, and subsequently by monthly transfer of update transactions to the U.S. Environmental Protection Agency's STORET system. Because the usual volume of updates makes it impractical to document individual changes in the State data-report series or elsewhere, potential users of U.S. Geological Survey water-quality data are encouraged to obtain all required data from the appropriate computer file to insure the most recent updates.

The surface-water-quality records for miscellaneous sampling sites are published in separate tables following the table of discharge measurements at miscellaneous sites. No descriptive statements are given for these records. Each station is published with its own station number and name in the regular downstream-order sequence.

Remark Codes

The following remark codes may appear with the water-quality data in this report:

PRINTED

OUTPUT

REMARK

<i>E</i>	<i>Estimated value.</i>
<i>></i>	<i>Actual value is known to be greater than the value shown.</i>
<i><</i>	<i>Actual value is known to be less than the value shown.</i>

Records of Ground-Water Levels

The national network of observation wells is intended to provide a sampling and historical record of ground-water level changes in the most important aquifers. Locations of observation wells from this network in New Hampshire and Vermont are shown in figure 2. Water levels measured from these 28 network wells are included in this report. Information about the availability of data in the water-level database may be obtained from the Chief, New Hampshire-Vermont District (see address on back of title page).

Data Collection and Computation

Measurements of water levels are made in many types of wells under varying conditions, but the methods of measurement are standardized to the extent possible. The equipment and measuring techniques used at each observation well ensure that measurements at each well are of consistent accuracy and reliability.

Tables of water-level data are presented by counties arranged in alphabetical order. The prime identification number for a given well is the 15-digit number that appears in the upper left corner of the table. The secondary identification number is the local well number, an alphanumeric number, derived from the municipality in which each well is located.

Water-level records are obtained from direct measurements with a steel or electric tape or from a water-stage recorder. The water-level measurements in this report are given in feet with reference to land-surface datum. Land-surface datum is a datum plane that is approximately at land surface at each well. If known, the elevation of the land-surface datum is given in the well description.

Water levels are reported to as many significant figures as can be justified by the local conditions. Accordingly, most measurements are reported to a hundredth of a foot, but one is given to five-hundredths of a foot.

Data Presentation

Each well record consists of three parts, the station description, the data table of water levels observed during the water year, and the hydrograph showing water level fluctuations during the most recent ten-year period. Hydrographs are based on end-of-month measurements or continuous data record (where available). The description of the well is presented first through use of descriptive headings preceding the tabular data. The comments to follow clarify information presented under the various headings.

LOCATION.--This paragraph follows the well-identification number and reports the latitude and longitude (given in degrees, minutes, and seconds); the hydrologic-unit number; the distance and direction from a geographic point of reference; and the owner's name.

AQUIFER.--This entry designates by name (if a name exists) and geologic age the aquifer(s) open to the well.

WELL CHARACTERISTICS.--This entry describes the well in terms of method of construction, use, diameter, depth and additional information such as casing breaks, collapsed screen, and other changes since construction.

DATUM.--This entry describes both the land-surface elevation at the well and the measuring point. The measuring point is described physically (such as top of collar, notch in top of casing, plug in pump base, and so on), and in relation to land surface (such as 1.3 ft above land-surface datum). The elevation of the land-surface datum is described in feet above (or below) sea level; it is reported with a precision depending on the method of determination.

PERIOD OF RECORD.--This entry indicates the period for which there are published records for the well. It reports the month and year of the start of publication of water-level records by the U.S. Geological Survey and the words "to current year" if the records are to be continued into the following year. Periods for which water-level records are available, but are not published by the U.S. Geological Survey, may be noted.

EXTREMES FOR PERIOD OF RECORD.--This entry contains the highest and lowest water levels of the period of published record, with respect to land-surface datum, and the dates of their occurrence.

Records of Ground-Water Quality

Water samples were collected from 17 domestic bedrock wells between October 1999 and September 2000 in the New Hampshire part of the New England Coastal Basins NAWQA study. Only one sample was collected from each well. These samples were collected as part of the NAWQA program to determine the occurrence and distribution of selected constituents in the ground waters of certain bedrock aquifer systems and analyzed for major ions, nutrients, trace elements, radon gas, radionuclides, 48 pesticide compounds, and 86 volatile organic compounds (VOCs).

Sampling protocols were followed to obtain and evaluate accurate water-quality data (Koterba and others, 1995). The sample line was connected to the faucet that is at the base of the pressure tank from inside the home. Water-quality samples were processed in the field and then shipped to the USGS National Water-Quality Laboratory in Lakewood, Colorado for analysis. Samples were analyzed locally (in the field) for alkalinity, specific conductance, dissolved oxygen, pH, temperature, ferrous iron, and sulfide.

Koterba, M.T., Wilde, F.D., and Lapham, W.W., 1995, Ground-water data-collection protocols and procedures for the National Water Quality Assessment program- Collection and documentation of water-quality samples and related data: U.S. Geological Survey Open-File Report 95-399, 113 p.

Analyses of pesticides in surface-water and ground-water samples (schedule 2001)

Selected surface-water and ground-water samples from the New England Coastal Basins NAWQA study were analyzed for pesticides on schedule 2001 during the 2000 water year. Sampling sites are shown in figure 4. This table lists the pesticides on the schedule, the unit of measure (micrograms per liter, $\mu\text{g/L}$), the U.S. Geological Survey National Water Information System parameter code, and the laboratory reporting level. **Only pesticides measured at or above the minimum reporting level for one or more samples are listed in the water-quality tables.**

SCHEDULE DESCRIPTION.--Pesticides in filtered water extracted on C-18 Solid Phase Extraction (SPE) cartridge and analyzed by Gas Chromatography/Mass Spectrometry (GC/MS).

SAMPLE REQUIREMENTS.--1 liter of water filtered through 0.7-micron glass-fiber depth filter, chilled at 4° C (packed in ice).

CONTAINER REQUIREMENTS.--1 liter baked amber glass bottle (GCC) from NWQL.

PCODE.--The USGS/EPA parameter code.

COMPOUND NAME.--IUPAC nomenclature.

COMMON NAME.--Common or trade name(s) for constituent.

LRL.--Laboratory reporting level.

PCode	Compound name (Common name)	LRL (µg/L)
49260	Acetochlor (Harness Plus, Surpass)	0.002
46342	Alachlor (Lasso, Bullet)	0.002
39632	Atrazine (Atrex, Atred)	0.001
04040	Atrazine, Deethyl- (Metabolite of Atrazine)	0.002
82686	Azinphos, Methyl- (Guthion, Gusathion)	0.001
82673	Benfluralin (Benefin, Balan)	0.002
04028	Butylate (Genate Plus, Suntan+)	0.002
82680	Carbaryl (Sevin, Denapan)	0.003
82674	Carbofuran (Furandan, Curaterr)	0.003
38933	Chlorpyrifos (Brodan, Dursban)	0.004
04041	Cyanazine (Bledex, Fortrol)	0.004
82682	DCPA (Dacthal, Chlorthal-dimethyl)	0.002
34653	DDE,p,p-	0.006
39572	Diazinon (Basudin, Diazatol)	0.002
39381	Dieldrin (Panoram D-31, Octalox)	0.001
82660	Diethylaniline (Metabolite of Alachlor)	0.003
82677	Disulfoton (Disyston, Frumin AL)	0.017
82668	EPTC (Eptam, Farmarox)	0.002
82663	Ethalfuralin (Sonalan, Curbit)	0.004
82672	Ethoprop (Mocap, Ethoprophos)	0.003
04095	Fonofos (Dyfonate, Capfos)	0.003
34253	HCH,alpha- (alpha-BHC, alpha-lindane)	0.002
39341	HCH,gamma- (Lindane, gamma-BHC)	0.004
82666	Linuron (Lorex, Linex)	0.002
39532	Malathion	0.005
39415	Metolachlor (Dual, Pennant)	0.002
82630	Metribuzin (Lexon, Sencor)	0.004
82671	Molinate (Ordram)	0.004
82684	Napropamide (Devrinol)	0.003
39542	Parathion, Ethyl- (Roethyl-P, Alkron)	0.004
82667	Parathion, Methyl- (Pennacp-M)	0.006
82669	Pebulate (Tillam, PEBL)	0.004
82683	Pendimethalin (Prowl, Stomp, Pre-M)	0.004
82687	Permethrin,cis- (Ambush, Astro)	0.005
82664	Phorate (Thimet, Granutox)	0.002
04037	Prometon (Pramitol, Princep)	0.018
82676	Pronamide (Kerb) (Propyzamid)	0.003
04024	Propachlor (Ramrod, Satecid)	0.007
82679	Propanil (Stampede, Stam)	0.004
82685	Propargite (Omite, Alkyl sulfite)	0.013

PCode	Compound name (Common name)	LRL (µg/L)
04035	Simazine (Princep, Caliber 91)	0.005
82670	Tebuthiuron (Spike, Tebusan)	0.010
82665	Terbacil (Sinbar)	0.007
82675	Terbufos (Counter, Contraven)	0.013
82681	Thiobencarb (Bolero, Saturn)	0.002
82678	Triallate (Avadex BW, Far-GO)	0.001
82661	Trifluralin (Treflan, Gowan)	0.002

Analyses of volatile organic compounds in ground-water samples (schedule 2020/2021)

Selected ground-water samples from the NECB NAWQA study were analyzed for volatile organic compounds (VOCs) in 2000. The National Water Quality Lab (NWQL) created a method for accurate determination of VOCs in water in the nanogram per liter range, schedules 2020/2021. The method is described in USGS Open-File Report 97-829 (Connor and others, 1998). Minor improvements to instrument operating conditions permits a data reporting strategy for measuring detected compounds extrapolated at less than the lowest calibration standard or measured at less than the reporting limit.

This table lists the volatile organic compounds on the schedule, the unit of measure (micrograms per liter (µg/L), the U.S. Geological Survey National Water Information System parameter code, the Union of Pure and Applied Chemistry (IUPAC) compound name, and the National Water Quality Laboratory compound name. Positive detections measured at less than the LRL are reported as estimated concentrations (E) to alert the data user to decreased confidence in accurate quantitation. Values for analytes in the 2020/2021 schedules are preceded by an "E" in the following situations:

1. When the calculated concentration is less than the lowest calibration standard. The analyte meets all identification criteria to be positively identified, but the amount detected is below where it can be reliably quantified.

2. If a sample is diluted for any reason. The method reporting level is multiplied by the dilution factor to obtain the adjusted method reporting level. Values below the lowest calibration standard, multiplied by the dilution factor are qualified with an "E". For example, a value of 0.19 in a 1:2 dilution is reported as E0.1.

3. If the set spike has recoveries out of the specified range (60-140 percent).

4. If the analyte is also detected in the set blank. If the value in the sample is less than five times the blank value and greater than the blank value plus the long term method detection limit, the value is preceded by an "E" to indicate that the analyte is positively identified but not positively quantified because the analyte was also detected in the blank.

Connor, B.F., Rose, D.L., Noriega, M.C., Murtagh, L.K., and Abney, S.R., 1998, Methods of analysis by the U.S. Geological Survey National Water Quality Laboratory—Determination of 86 volatile organic compounds in water by gas chromatography/mass spectrometry, including detections less than reporting limits: U.S. Geological Survey Open-File Report 97-829, 78 p.

SCHEDULE DESCRIPTION.--The sample water is actively purged with helium to extract the volatile organic compounds. The volatile compounds are trapped onto a sorbent trap, thermally desorbed, separated by a megabore gas chromatographic capillary column, and finally determined by a full scan quadropole mass spectrometer. Compound identification is confirmed by the gas chromatographic retention time and by the resultant mass spectrum, typically identified by three unique ions.

SAMPLE REQUIREMENTS.--Water collected in vials placed in stainless steel VOC sampler. Hydrochloric acid is used for preservation. Chilled at 4°C (packed in ice).

CONTAINER REQUIREMENTS.--40 milliliter baked amber septum glass vial, from OCALA Quality Water Service Unit.

PCODE.--The EPA/USGS parameter code.

COMPOUND NAME.--IUPAC nomenclature.

COMMON NAME.--NWQL nomenclature.

LRL.--Laboratory reporting level.

PCode	Compound name	Common name	LRL (µg/L)
77353	(1,1-Dimethylethyl) benzene	<i>tert</i> -butylbenzene	0.06
77223	(1-Methylethyl) benzene	Isopropylbenzene	0.032
77350	(1-Methylpropyl) benzene	<i>sec</i> -butylbenzene	0.032
34396	1,1,1,2,2,2-Hexachloroethane	Hexachloroethane	0.19
77562	1,1,1,2-Tetrachloroethane	1,1,2-tetrachloroethane	0.03
34506	1,1,1-Trichloroethane	1,1,1-trichloroethane	0.032

PCode	Compound name	Common name	LRL (µg/L)
34516	1,1,2,2-Tetrachloroethane	1,1,2,2-tetrachloroethane	0.09
77652	1,1,2-Trichloro-1,2,2-trifluoroethane	Freon-113	0.06
34511	1,1,2-Trichloroethane	1,1,2-trichloroethane	0.06
34496	1,1-Dichloroethane	1,1-dichloroethane	0.066
34501	1,1-Dichloroethene	1,1-dichloroethene	0.04
77168	1,1-Dichloropropene	1,1-dichloropropene	0.026
49999	1,2,3,4-Tetramethylbenzene	Preh-nitene	0.23
50000	1,2,3,5-Tetramethylbenzene	Isodurence	0.20
77613	1,2,3-Trichlorobenzene	1,2,3-trichlorobenzene	0.27
77443	1,2,3-Trichloropropane	1,2,3-trichloropropane	0.16
77221	1,2,3-Trimethylbenzene	1,2,3-trimethylbenzene	0.12
34551	1,2,4-Trichlorobenzene	1,2,4-trichlorobenzene	0.19
77222	1,2,4-Trimethylbenzene	1,2,4-trimethylbenzene	0.056
82625	1,2-Dibromo-3-chloropropane	1,2-dibromo-3-chloropropane (DBCP)	0.21
77651	1,2-Dibromoethane	1,2-dibromoethane	0.036
34536	1,2-Dichlorobenzene	1,2-dichlorobenzene	0.048
32103	1,2-Dichloroethane	1,2-dichloroethane	0.13
34541	1,2-Dichloropropane	1,2-dichloropropane	0.068
77135	1,2-Dimethylbenzene	<i>o</i> -xylene	0.038
85795	1,3 & 1,4-Dimethylbenzene	<i>m</i> & <i>p</i> -xylene	0.06
77226	1,3,5-Trimethylbenzene	1,3,5-trimethylbenzene	0.044
34566	1,3-Dichlorobenzene	1,3-dichlorobenzene	0.054
77173	1,3-Dichloropropane	1,3-dichloropropane	0.12
34571	1,4-Dichlorobenzene	1,4-dichlorobenzene	0.05
77275	1-Chloro-2-methylbenzene	2-chlorotoluene	0.042
77277	1-Chloro-4-methylbenzene	4-chlorotoluene	0.06
77356	1-Isopropyl-4-methylbenzene	<i>p</i> -Isopropyltoluene	0.07
77170	2,2-Dichloropropane	2,2-dichloropropane	0.05
81595	2-Butanone	Methyl-ethyl ketone	1.6
77220	2-Ethyltoluene	2-ethyl toluene	0.06
77103	2-Hexanone	2-hexanone	0.70
34215	2-Propenenitrile	Acrylonitrile	1.2
78109	3-Chloro-1-propene	3-chloro-1-propene	0.20
78133	4-Methyl-2-pentanone	Methyl isobutyl ketone	0.37
81552	Acetone	Acetone	7.0
34030	Benzene	Benzene	0.035
81555	Bromobenzene	Bromobenzene	0.036
77297	Bromochloromethane	Bromochloromethane	0.044
32101	Bromodichloromethane	Bromodichloromethane	0.048
50002	Bromoethene	Vinyl Bromide	0.10
34413	Bromomethane	Methyl bromide	0.26
77041	Carbon disulfide	Carbon Disulfide	0.07
34301	Chlorobenzene	Chlorobenzene	0.028
34311	Chloroethane	Chloroethane	0.12

PCode	Compound name	Common name	LRL (µg/L)
39175	Chloroethene	Vinyl Chloride	0.11
34418	Chloromethane	Methyl chloride	0.50
77093	<i>cis</i> -1,2-Dichloroethene	<i>cis</i> -1,2-dichloroethene	0.038
34704	<i>cis</i> -1,3-Dichloropropene	<i>cis</i> -1,3-dichloropropene	0.09
32105	Dibromochloromethane	Dibromochloromethane	0.18
30217	Dibromomethane	Dibromomethane	0.05
34668	Dichlorodifluoromethane	Dichlorodifluoromethane	0.27
34423	Dichloromethane	Methylene Chloride	0.38
81576	Diethyl ether	Diethyl ether	0.17
81577	Di isopropyl	Ether	0.10
77128	Ethenylbenzene	Styrene	0.042
73570	Ethyl methacrylate	Ethyl Methacrylate	0.18
50004	Ethyl <i>tert</i> -butyl ether	Ethyl- <i>t</i> -butyl ether (ETBE)	0.054
34371	Ethylbenzene	Ethylbenzene	0.03
39702	Hexachlorobutadiene	Hexachlorobutadiene	0.14
77424	Iodomethane	Methyl iodide	0.12
49991	Methyl acrylate	Methyl Acrylate	1.4
81593	Methyl acrylonitrile	Methyl Acrylonitrile	0.6
81597	Methyl methacrylate	Methyl Methacrylate	0.35
78032	Methyl <i>tert</i> -butyl ether	Methyl- <i>t</i> -butyl ether (MTBE)	0.17
34010	Methylbenzene	Toluene	0.05
77342	<i>n</i> -Butylbenzene	<i>n</i> -butylbenzene	0.19
77224	<i>n</i> -Propylbenzene	<i>n</i> -propylbenzene	0.042
34696	Naphthalene	Naphthalene	0.25
50005	<i>tert</i> -Amyl methyl ether	<i>tert</i> -amyl methyl ether (TAME)	0.11
34475	Tetrachloroethene	Tetrachloroethene	0.10
32102	Tetrachloromethane	Carbon tetrachloride	0.06
81607	Tetrahydrofuran	Tetrahydrofuran	2.2
34546	<i>trans</i> -1,2-Dichloroethene	<i>trans</i> -1,2-dichloroethene	0.032
34699	<i>trans</i> -1,3-Dichloropropene	<i>trans</i> -1,3-dichloropropene	0.09
73547	<i>trans</i> -1,4-Dichloro-2-butene	<i>trans</i> -1,4-dichloro-2-butene	0.70
32104	Tribromomethane	Bromoform	0.06
39180	Trichloroethene	Trichloroethene	0.038
34488	Trichlorofluoromethane	Trichlorofluoromethane	0.09
32106	Trichloromethane	Chloroform	0.052

ACCESS TO USGS WATER DATA

The U.S. Geological Survey is the principal Federal water-data agency and, as such, collects and disseminates about 70 percent of the water data currently being used by numerous State, local, private, and other Federal agencies to develop and

manage our water resources. As part of the U.S. Geological Survey's program of releasing water data to the public, a large-scale computerized system was developed for the storage and retrieval of water data collected through its activities. The National Water Data Storage and Retrieval System (WATSTORE) was established in 1972 to provide an effective and efficient means for the processing and maintenance of water data collected through the activities of the U.S. Geological Survey and to facilitate release of the data to the public. As of December 1996, WATSTORE was retired. It has been replaced by National Water Information System (NWIS) and incorporates many of the features of WATSTORE. The historic daily-mean and peak-flow discharge data (final) from NWIS can be accessed through the world wide web (www) via the address:

<http://water.usgs.gov>

Provisional current (monthly) conditions and real time (telemetry) information for New Hampshire and Vermont can be obtained at the following www addresses:

<http://nh.water.usgs.gov>

<http://vt.water.usgs.gov>

http://nh.water.usgs.gov/rt-cgi/gen_tbl_pg

<http://nh.water.usgs.gov/WaterData/curr.htm>

Information about the availability of other provisional, specific types of data or products, and user charges, can be obtained locally from each of the Water Resources Division District Offices (See address on the back of the title page.)

DEFINITION OF TERMS

Terms related to streamflow, water-quality, and other hydrologic data, as used in this report, are defined below. See also table for converting English units to International System (SI) Units on the inside of the back cover.

Acre-foot (AC-FT, acre-ft) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet, 325,851 gallons, or 1,233 cubic meters.

Algae are mostly aquatic single-celled, colonial, or multicelled plants containing chlorophyll and lacking roots, stems, and leaves.

Alkalinity is the capacity of solutes in an aqueous system to neutralize acid. This term designates titration of a "filtered" sample.

Annual runoff is the total quantity of water in runoff for a drainage area for the year. Data reports may use any of the following units of measurement in presenting annual runoff data.

Cubic foot per second per square mile [CFSM, (ft³/s)/mi²] is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming the runoff is distributed uniformly in time and area.

Inch (IN., in.) as used in this report, refers to the depth to which the drainage area would be covered with water if all of the runoff for a given time period were uniformly distributed on it.

Base flow is flow in a channel sustained by ground-water discharge in the absence of direct runoff.

Bed material is the sediment mixture of which a streambed, lake, pond, reservoir, or estuary bottom is composed.

Biomass is the amount of living matter present at any given time, expressed as mass per unit area or volume of habitat.

Ash mass is the mass or amount of residue present after the residue from the dry mass determination has been ashed in a muffle furnace at a temperature of 500°C for 1 hour. Ash mass of zooplankton and phytoplankton is expressed in grams per cubic meter (g/m³), and periphyton and benthic organisms in grams per square meter (g/m²).

Dry mass refers to the mass of residue present after drying in an oven at 105°C for zooplankton and periphyton, until the mass remains unchanged. This mass represents the total organic matter, ash, and sediment in the sample. Dry mass is expressed in the same units as ash mass.

Bottom material: See “Bed material.”

Chlorophyll refers to the green pigments of plants. Chlorophyll a and b are the two most common green pigments in plants.

Confined aquifer is a term used to describe an aquifer containing water between two relatively impermeable boundaries. The water level in a well tapping a confined aquifer stands above the top of the confined aquifer and can be higher or lower than the water table that may be present in the material above it. In some cases the water level can rise above the ground surface, yielding a flowing well.

Contents is the volume of water in a reservoir or lake. Unless otherwise indicated, volume is computed on the basis of a level pool and does not include bank storage.

Continuous-record station is a site that meets either of the following conditions:

1. Stage or streamflow are recorded at some interval on a continuous basis. The recording interval is usually 15 minutes, but may be less or more frequent.
2. Water-quality, sediment, or other hydrologic measurements are recorded at least daily.

Control designates a feature in the channel downstream from a gaging station that physically influences the water-surface elevation and thereby determines the stage-discharge relation at the station. This feature may be a constriction of the channel, a bedrock outcrop, a gravel bar, an artificial structure, or a uniform cross section over a long reach of the channel.

Control structure as used in this report is a structure on a stream or canal that is used to regulate the flow or stage of the stream or to prevent the intrusion of saltwater.

Cubic foot per second (CFS, ft³/s) is the rate of discharge representing a volume of 1 cubic foot passing a given point in 1 second. It is equivalent to approximately 7.48 gallons per second, 448.8 gallons per minute, or 0.02832 cubic meters per second.

Cubic foot per second-day (CFS-DAY, Cfs-day, [(ft³/s)/d]) is the volume of water represented by a flow of 1 cubic foot per second for 24 hours. It is equivalent to 86,400 cubic feet, 1.9835 acre-feet, 646,317 gallons, or 2,447 cubic meters.

Daily record is a summary of streamflow, sediment, or water-quality values computed from data collected with sufficient frequency to obtain reliable estimates of daily mean values.

Daily record station is a site for which daily records of streamflow, sediment, or water-quality values are computed.

Datum, as used in this report, is an elevation above mean sea level to which all gage height readings are referenced.

Diel is of or pertaining to a 24-hour period of time; a regular daily cycle.

Discharge, or flow, is the volume of water (or more broadly, volume of fluid including solid- and dissolved-phase material), that passes a given point in a given period of time.

Annual 7-day minimum is the lowest mean discharge for 7 consecutive days in a year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1-March 31). The date shown in the

summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year low-flow statistic.)

Instantaneous discharge is the discharge at a particular instant of time.

Mean discharge (MEAN) is the arithmetic mean of individual daily mean discharges during a specific period.

Dissolved refers to that material in a representative water sample that passes through a 0.45-micrometer membrane filter. This is a convenient operational definition used by Federal agencies that collect water data. Determinations of “dissolved” constituents are made on subsamples of the filtrate.

Dissolved oxygen (DO) content of water in equilibrium with air is a function of atmospheric pressure, temperature, and dissolved-solids concentration of the water. The ability of water to retain oxygen decreases with increasing temperature or dissolved solids, with small temperature changes having the more significant offset. Photosynthesis and respiration may cause diurnal variations in dissolved-oxygen concentration in water from some streams.

Dissolved-solids concentration of water is determined either analytically by the “residue-on-evaporation” method, or mathematically by totaling the concentrations of individual constituents reported in a comprehensive chemical analysis. During that analytical determination of dissolved solids, the bicarbonate (generally a major dissolved component of water) is converted to carbonate. Therefore, in the mathematical calculation of dissolved-solids concentration, the bicarbonate value, in milligrams per liter, is multiplied by 0.4926 to reflect the change. Alternatively, alkalinity concentration (as mg/L CaCO₃) can be converted to carbonate concentration by multiplying by 0.60.

Drainage area of a site on a stream is that area, measured in a horizontal plane, that has a common outlet at the site for its surface runoff. Figures of drainage area given herein include all closed basins, or noncontributing areas, within the area unless otherwise specified.

Drainage basin is a part of the Earth’s surface that is occupied by a drainage system with a common outlet for its surface runoff (see “Drainage area”).

Dry weight refers to the weight of animal tissue after it has been dried in an oven at 65°C until a constant weight is achieved. Dry weight represents total organic and inorganic matter in the tissue.

Flow-duration percentiles are values on a scale of 100 that indicate the percentage of time for which a flow is not

exceeded. For example, the 90th percentile of river flow is greater than or equal to 90 percent of all recorded flow rates.

Gage datum is the elevation of the zero point of the reference gage from which gage height is determined as compared to sea level (see “Datum”). This elevation is established by a system of levels from known benchmarks, by approximation from topographic maps, or by geographical positioning system.

Gage height (G.H.) is the water-surface elevation referenced to the gage datum. Gage height is often used interchangeably with the more general term “stage,” although gage height is more appropriate when used with a reading on a gage.

Gaging station is a site on a stream, canal, lake, or reservoir where systematic observations of stage, discharge, or other hydrologic data are obtained. When used in connection with a discharge record, the term is applied only to those gaging stations where a continuous record of discharge is computed.

Ground-water level is the elevation of the water table or another potentiometric surface at a particular location.

Hardness of water is a physical-chemical characteristic that is commonly recognized by the increased quantity of soap required to produce lather. It is attributable to the presence of alkaline earths (principally calcium and magnesium) and is expressed as the equivalent concentration of calcium carbonate (CaCO₃).

High tide is the maximum height reached by each rising tide. The high-high and low-high tides are the higher and lower of the two high tides, respectively, of each tidal day. See NOAA web site:
<http://www.co-ops.nos.noaa.gov/tideglos.html>

Hydrologic benchmark station is one that provides hydrologic data for a basin in which the hydrologic regimen will likely be governed solely by natural conditions. Data collected at a benchmark station may be used to separate effects of natural from human-induced changes in other basins that have been developed and in which the physiography, climate, and geology are similar to those in the undeveloped benchmark basin.

Hydrologic unit is a geographic area representing part or all of a surface drainage basin or distinct hydrologic feature as defined by the former Office of Water Data Coordination and delineated on the State Hydrologic Unit Maps by the U.S. Geological Survey. Each hydrologic unit is identified by an 8-digit number.

Land-surface datum (lsd) is a datum plane that is approximately at land surface at each ground-water observation well.

Low tide is the minimum height reached by each falling tide. The high-low and low-low tides are the higher and lower of the two low tides, respectively, of each tidal day.

See NOAA web site:

<http://www.co-ops.nos.noaa.gov/tideglos.html>

Measuring point (MP) is an arbitrary permanent reference point from which the distance to water surface in a well is measured to obtain water level.

Micrograms per gram (UG/G, $\mu\text{g/g}$) is a unit expressing the concentration of a chemical constituent as the mass (micrograms) of the element per unit mass (gram) of material analyzed.

Micrograms per kilogram (UG/KG, $\mu\text{g/kg}$) is a unit expressing the concentration of a chemical constituent as the mass (micrograms) of the constituent per unit mass (kilogram) of the material analyzed. One microgram per kilogram is equivalent to 1 part per billion.

Micrograms per liter (UG/L, $\mu\text{g/L}$) is a unit expressing the concentration of chemical constituents in water as mass (micrograms) of constituent per unit volume (liter) of water. One thousand micrograms per liter is equivalent to 1 milligram per liter.

Microsiemens per centimeter (US/CM, $\mu\text{S/cm}$) is a unit expressing the amount of electrical conductivity of a solution as measured between opposite faces of a centimeter cube of solution at a specified temperature. Siemens is the International System of Units nomenclature. It is synonymous with mhos and is the reciprocal of resistance in ohms.

Milligrams per liter (MG/L, mg/L) is a unit for expressing the concentration of chemical constituents in water as the mass (milligrams) of constituent per unit volume (liter) of water. Concentration of suspended sediment also is expressed in mg/L and is based on the mass of dry sediment per liter of water-sediment mixture.

Miscellaneous site, or miscellaneous station, is a site where streamflow, sediment, and/or water-quality data are collected once, or more often on a random or discontinuous basis.

Nanograms per liter (NG/L, ng/L) is a unit expressing the concentration of chemical constituents in solution as mass (nanograms) of solute per unit volume (liter) of water. One million nanograms per liter is equivalent to 1 milligram per liter.

National Geodetic Vertical Datum of 1929 (NGVD of 1929) is a geodetic datum derived from a general adjustment of the first order level nets of the United States and Canada. It was formerly called "Sea Level Datum of 1929" or "mean sea level" in this series of reports. Although the datum was derived from the average sea level over a period of many years at 26 tide stations along the Atlantic, Gulf of Mexico, and Pacific Coasts, it does not necessarily represent local mean sea level at any particular place.

See NOAA web site:

<http://www.ngs.noaa.gov/faq.shtml#WhatVD29VD88>

Nephelometric turbidity unit (NTU) is the measurement for reporting turbidity that is based on use of a standard suspension of Formazin. Turbidity measured in NTU uses nephelometric methods that depend on passing specific light of a specific wavelength through the sample.

Open or screened interval is the length of unscreened opening or of well screen through which water enters a well, in feet below land surface.

Organic carbon (OC) is a measure of organic matter present in aqueous solution, suspension, or bottom sediments. May be reported as dissolved organic carbon (DOC), suspended organic carbon (SOC), or total organic carbon (TOC).

Organochlorine compounds are any chemicals that contain carbon and chlorine. Organochlorine compounds that are important in investigations of water, sediment, and biological quality include certain pesticides and industrial compounds.

Parameter Code is a 5-digit number used in the U.S. Geological Survey computerized data system, National Water Information System (NWIS), to uniquely identify a specific constituent or property.

Partial-record station is a site where discrete measurements of one or more hydrologic parameters are obtained over a period of time without continuous data being recorded or computed. A common example is a crest-stage gage partial-record station at which only peak stages and flows are recorded.

Particle size is the diameter, in millimeters (mm), of a particle determined by sieve or sedimentation methods. The sedimentation method utilizes the principle of Stokes Law to calculate sediment particle sizes. Sedimentation methods (pipet, bottom-withdrawal tube, visual-accumulation tube, Sedigraph) determine fall diameter of particles in either distilled water (chemically dispersed) or in native water (the river water at the time and point of sampling).

Particle-size classification used in this report agrees with the recommendation made by the American Geophysical Union Subcommittee on Sediment Terminology. The classification is as follows:

Classification	Size (mm)	Method of analysis
Clay	0.00024 - 0.004	Sedimentation
Silt	0.004 - 0.062	Sedimentation
Sand	0.062 - 2.0	Sedimentation/sieve
Gravel	2.0 - 64.0	Sieve

The particle-size distributions given in this report are not necessarily representative of all particles in transport in the stream. Most of the organic matter is removed, and the sample is subjected to mechanical and chemical dispersion before analysis in distilled water. Chemical dispersion is not used for native water analysis.

Percent composition or percent of total is a unit for expressing the ratio of a particular part of a sample or population to the total sample or population, in terms of types, numbers, weight, or volume.

Periodic station is a site where stage, discharge, sediment, chemical, or other hydrologic measurements are made one or more times during a year, but at a frequency insufficient to develop a daily record.

Periphyton is the assemblage of microorganisms attached to and living upon submerged solid surfaces. While primarily consisting of algae, they also include bacteria, fungi, protozoa, rotifers, and other small organisms. Periphyton are useful indicators of water quality.

Pesticides are chemical compounds used to control undesirable organisms. Major categories of pesticides include insecticides, miticides, fungicides, herbicides, and rodenticides.

pH of water is the negative logarithm of the hydrogen-ion activity. Solutions with pH less than 7 are termed "acidic," and solutions with a pH greater than 7 are termed "basic." Solutions with a pH of 7 are neutral. The presence and concentration of many dissolved chemical constituents found in water are, in part, influenced by the hydrogen-ion activity of water. Biological processes including growth, distribution of organisms, and toxicity of the water to organisms are also influenced, in part, by the hydrogen-ion activity of water.

Picocurie (PC, pCi) is one trillionth (1×10^{-12}) of the amount of radioactivity represented by a curie (Ci). A curie is the amount of radioactivity that yields 3.7×10^{10} radioac-

tive disintegrations per second. A picocurie yields 2.22 dpm (disintegrations per minute).

Plankton is the community of suspended, floating, or weakly swimming organisms that live in the open water of lakes and rivers. Concentrations are expressed as a number of cells per milliliter (cells/mL of sample).

Phytoplankton is the plant part of the plankton. They are usually microscopic, and their movement is subject to the water currents. Phytoplankton growth is dependent upon solar radiation and nutrient substances. Because they are able to incorporate as well as release materials to the surrounding water, the phytoplankton have a profound effect upon the quality of the water. They are the primary food producers in the aquatic environment and are commonly known as algae.

Radioisotopes are isotopic forms of an element that exhibit radioactivity. Isotopes are varieties of a chemical element that differ in atomic weight, but are very nearly alike in chemical properties. The difference arises because the atoms of the isotopic forms of an element differ in the number of neutrons in the nucleus; for example, ordinary chlorine is a mixture of isotopes having atomic weights of 35 and 37, and the natural mixture has an atomic weight of about 35.453. Many of the elements similarly exist as mixtures of isotopes, and a great many new isotopes have been produced in the operation of nuclear devices such as the cyclotron. There are 275 isotopes of the 81 stable elements, in addition to more than 800 radioactive isotopes.

Recurrence interval, also referred to as return period, is the average time, usually expressed in years, between occurrences of hydrologic events of a specified type (such as exceedances of a specified high flow or non-exceedance of a specified low flow). The terms "return period" and "recurrence interval" do not imply regular cyclic occurrence. The actual times between occurrences vary randomly, with most of the times being less than the average and a few being substantially greater than the average. For example, the 100-year flood is the flow rate that is exceeded by the annual maximum peak flow at intervals whose average length is 100 years (that is, once in 100 years, on average); almost two-thirds of all exceedances of the 100-year flood occur less than 100 years after the previous exceedance, half occur less than 70 years after the previous exceedance, and about one-eighth occur more than 200 years after the previous exceedance. Similarly, the 7-day 10-year low flow ($7Q_{10}$) is the flow rate below which the annual minimum 7-day-mean flow dips at intervals whose average length is 10 years (that is, once in 10 years, on average); almost two-thirds of the non-exceedances of the $7Q_{10}$ occur less than 10 years after the previous non-exceedance, half occur less than 7 years after, and about one-eighth occur more than 20 years after

the previous non-exceedance. The recurrence interval for annual events is the reciprocal of the annual probability of occurrence. Thus, the 100-year flood has a 1-percent chance of being exceeded by the maximum peak flow in any year, and there is a 10-percent chance in any year that the annual minimum 7-day-mean flow will be less than the $7Q_{10}$.

Replicate samples are a group of samples collected in a manner such that the samples are thought to be essentially identical in composition.

River mile is the distance of a point on a river measured in miles from the river's mouth along the low-water channel.

River mileage is the linear distance along the meandering path of a stream channel determined in accordance with Bulletin No. 14 (October 1968) of the Water Resources Council.

Runoff in inches (IN., in.) is the depth, in inches, to which the drainage area would be covered if all the runoff for a given time period were uniformly distributed on it.

Sea level refers to the National Geodetic Vertical Datum of 1929 (NGVD of 1929)—a geodetic datum derived from a general adjustment of the first-order level nets of the United States and Canada, formerly called Sea Level Datum of 1929.

See NOAA web site:

http://www.co-ops.nos.noaa.gov/glossary/gloss_n.html#NGVD

Sediment is solid material that is transported by, suspended in, or deposited from water. It originates mostly from disintegrated rocks; it also includes chemical and biochemical precipitates and decomposed organic material, such as humus. The quantity, characteristics, and cause of the occurrence of sediment in streams are influenced by environmental factors. Some major factors are degree of slope, length of slope, soil characteristics, land usage, and quantity and intensity of precipitation.

Bed load is the sediment that is transported in a stream by rolling, sliding, or skipping along or very close to the bed. In this report, bed load is considered to consist of particles in transit from the bed to an elevation equal to the top of the bed-load sampler nozzle (usually within 0.25 ft of the streambed).

Bed-load discharge (tons per day) is the quantity of sediment moving as bed load, reported as dry weight, that passes a cross section in a given time.

Suspended sediment is the sediment that is maintained in suspension by the upward components of turbulent currents or that exists in suspension as a colloid.

Seven-day 10-year low flow ($7Q_{10}$, $7Q_{10}$) is the minimum flow averaged over 7 consecutive days that is expected to occur on average, once in any 10-year period. The $7Q_{10}$ has a 10-percent chance of occurring in any given year.

Solute is any substance that is dissolved in water.

Specific conductance is a measure of the ability of a water to conduct an electrical current. It is expressed in microsiemens per centimeter at 25°C. Specific conductance is related to the type and concentration of ions in solution and can be used for approximating the dissolved-solids content of the water. Commonly, the concentration of dissolved solids (in milligrams per liter) is from 55 to 75 percent of the specific conductance (in microsiemens). This relation is not constant from stream to stream, and it may vary in the same source with changes in the composition of the water.

Stage: See "Gage height."

Stage-discharge relation is the relation between the water-surface elevation, termed stage (gage height), and the volume of water flowing in a channel per unit time.

Streamflow is the discharge that occurs in a natural channel. Although the term "discharge" can be applied to the flow of a canal, the word "streamflow" uniquely describes the discharge in a surface stream course. The term "streamflow" is more general than "runoff" as streamflow may be applied to discharge whether or not it is affected by diversion or regulation.

Surface area of a lake or impoundment is that area encompassed by the boundary of the lake or impoundment as shown on USGS topographic maps, or on other available maps or photographs. The computed surface areas reflect the water levels of the lakes or impoundments at the times when the information for the maps or photographs was obtained.

Synoptic Studies are short-term investigations of specific water-quality conditions during selected seasonal or hydrologic periods to provide improved spatial resolution for critical water-quality conditions. For the period and conditions sampled, they assess the spatial distribution of selected water-quality conditions in relation to causative factors, such as land use and contaminant sources.

Total is the total amount of a given constituent in a representative suspended-sediment sample, regardless of the constituent's physical or chemical form. This term is used only when the analytical procedure assures measurement of at least 95 percent of the constituent present in both the dissolved and suspended phases of the sample. A knowledge of the expected form of the constituent in the sample, as well as the analytical methodology used, is required to judge when

the results should be reported as “total.” (Note that the word “total” does double duty here, indicating both that the sample consists of a suspended-sediment mixture and that the analytical method determined all of the constituent in the sample.)

Total discharge is the quantity of a given constituent, measured as dry mass or volume, that passes a stream cross section per unit of time. When referring to constituents other than water, this term needs to be qualified, such as “total sediment discharge,” “total chloride discharge,” and so on.

Turbidity is a measurement of the collective optical properties of a water sample that cause light to be scattered and absorbed rather than transmitted in straight lines; the higher the intensity of scattered light, the higher the turbidity. Turbidity is expressed in nephelometric turbidity units (NTU) or Formazin turbidity units (FTU) depending on the method and equipment used.

Volatile organic compounds (VOC's) are organic compounds that can be isolated from the water phase of a sample by purging the water sample with inert gas, such as helium, and subsequently analyzed by gas chromatography. Many VOC's are manmade chemicals that are used and produced in the manufacture of paints, adhesives, petroleum products, pharmaceuticals, and refrigerants. They are often components of fuels, solvents, hydraulic fluids, paint thinners, and dry cleaning agents commonly used in urban settings. VOC contamination of drinking-water supplies is a human health concern because many are toxic and are known or suspected human carcinogens (U.S. Environmental Protection Agency, 1996).

Water level is the water-surface elevation or stage of the free surface of a body of water above or below any datum (see “Gage height”), or the surface of water standing in a well, usually indicative of the position of the water table or other potentiometric surface.

Water table is the surface of a ground-water body at which the water is at atmospheric pressure.

Water-table aquifer is an unconfined aquifer within which is found the water table.

Water year in U.S. Geological Survey reports dealing with surface-water supply is the 12-month period October 1 through September 30. The water year is designated by the calendar year in which it ends and which includes 9 of the 12 months. Thus, the year ending September 30, 1999, is called the “1999 water year.”

WDR is used as an abbreviation for “Water-Data Report” in the REVISED RECORDS paragraph to refer to State annual hydrologic-data reports. (WRD was used as an

abbreviation for “Water-Resources Data” in reports published prior to 1976.)

Well is an excavation (pit, hole, tunnel), generally cylindrical in form and often walled in, drilled, dug, driven, bored, or jetted into the ground to such a depth as to penetrate water-yielding geologic material and allow the water to flow or to be pumped to the surface.

Wet weight refers to the weight of animal tissue or other substance including its contained water.

WSP is used as an abbreviation for “Water-Supply Paper” in reference to previously published reports.

PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS

The U.S. Geological Survey publishes a series of manuals describing procedures for planning and conducting specialized work in water-resources investigations. The material is grouped under major subject headings called books and is further divided into sections and chapters. For example, Section A of Book 3 (Applications of Hydraulics) pertains to surface water. The chapter, the unit of publication, is limited to a narrow field of subject matter. This format permits flexibility in revision and publication as the need arises.

The reports listed below are for sale by the U.S. Geological Survey, Information Services, Box 25286, Federal Center, Denver, Colorado 80225 (authorized agent of the Superintendent of Documents, Government Printing Office). Prepayment is required. Remittance should be sent by check or money order payable to the “U.S. Geological Survey.” Prices are not included because they are subject to change. Current prices can be obtained by writing to the above address. When ordering or inquiring about prices for any of these publications, please give the title, book number, chapter number, and mention the “U.S. Geological Survey Techniques of Water-Resources Investigations.”

Book 1. Collection of Water Data by Direct Measurement

Section D. Water Quality

- 1-D1. *Water temperature—influential factors, field measurement, and data presentation*, by H.H. Stevens, Jr., J.F. Ficke, and G.F. Smoot: USGS-TWRI Book 1, Chapter D1. 1975. 65 pages.

- 1-D2. *Guidelines for collection and field analysis of ground-water samples for selected unstable constituents*, by W.W. Wood: USGS-TWRI Book 1, Chapter D2. 1976. 24 pages.

Book 2. Collection of Environmental Data

Section D. Surface Geophysical Methods

- 2-D1. *Application of surface geophysics to ground-water investigations*, by A.A.R. Zohdy, G.P. Eaton, and D.R. Mabey: USGS-TWRI Book 2, Chapter D1. 1974. 116 pages.
- 2-D2. *Application of seismic-refraction techniques to hydrologic studies*, by F.P. Haeni: USGS-TWRI Book 2, Chapter D2. 1988. 86 pages.

Section E. Subsurface Geophysical Methods

- 2-E1. *Application of borehole geophysics to water-resources investigations*, by W.S. Keys and L.M. MacCary: USGS-TWRI Book 2, Chapter E1. 1971. 126 pages.
- 2-E2. *Borehole geophysics applied to ground-water investigations*, by W.S. Keys: USGS-TWRI Book 2, Chapter E2. 1990. 150 pages.

Section F. Drilling and Sampling Methods

- 2-F1. *Application of drilling, coring, and sampling techniques to test holes and wells*, by Eugene Shuter and W.E. Teasdale: USGS-TWRI Book 2, Chapter F1. 1989. 97 pages.

Book 3. Applications of Hydraulics

Section A. Surface-Water Techniques

- 3-A1. *General field and office procedures for indirect discharge measurements*, by M.A. Benson and Tate Dalrymple: USGS-TWRI Book 3, Chapter A1. 1967. 30 pages.
- 3-A2. *Measurement of peak discharge by the slope-area method*, by Tate Dalrymple and M.A. Benson: USGS-TWRI Book 3, Chapter A2. 1967. 12 pages.
- 3-A3. *Measurement of peak discharge at culverts by indirect methods*, by G.L. Bodhaine: USGS-TWRI Book 3, Chapter A3. 1968. 60 pages.
- 3-A4. *Measurement of peak discharge at width contractions by indirect methods*, by H.F. Matthai: USGS-TWRI Book 3, Chapter A4. 1967. 44 pages.
- 3-A5. *Measurement of peak discharge at dams by indirect methods*, by Harry Hulsing: USGS-TWRI Book 3, Chapter A5. 1967. 29 pages.
- 3-A6. *General procedure for gaging streams*, by R.W. Carter and Jacob Davidian: USGS-TWRI Book 3, Chapter A6. 1968. 13 pages.
- 3-A7. *Stage measurement at gaging stations*, by T.J. Buchanan and W.P. Somers: USGS-TWRI Book 3, Chapter A7. 1968. 28 pages.
- 3-A8. *Discharge measurements at gaging stations*, by T.J. Buchanan and W.P. Somers: USGS-TWRI Book 3, Chapter A8. 1969. 65 pages.
- 3-A9. *Measurement of time of travel in streams by dye tracing*, by F.A. Kilpatrick and J.F. Wilson, Jr.: USGS-TWRI Book 3, Chapter A9. 1989. 27 pages.
- 3-A10. *Discharge ratings at gaging stations*, by E.J. Kennedy: USGS-TWRI Book 3, Chapter A10. 1984. 59 pages.
- 3-A11. *Measurement of discharge by the moving-boat method*, by G.F. Smoot and C.E. Novak: USGS-TWRI Book 3, Chapter A11. 1969. 22 pages.
- 3-A12. *Fluorometric procedures for dye tracing*, Revised, by J.F. Wilson, Jr., E.D. Cobb, and F.A. Kilpatrick: USGS-TWRI Book 3, Chapter A12. 1986. 41 pages.
- 3-A13. *Computation of continuous records of streamflow*, by E.J. Kennedy: USGS-TWRI Book 3, Chapter A13. 1983. 53 pages.
- 3-A14. *Use of flumes in measuring discharge*, by F.A. Kilpatrick and V.R. Schneider: USGS-TWRI Book 3, Chapter A14. 1983. 46 pages.
- 3-A15. *Computation of water-surface profiles in open channels*, by Jacob Davidian: USGS-TWRI Book 3, Chapter A15. 1984. 48 pages.
- 3-A16. *Measurement of discharge using tracers*, by F.A. Kilpatrick and E.D. Cobb: USGS-TWRI Book 3, Chapter A16. 1985. 52 pages.
- 3-A17. *Acoustic velocity meter systems*, by Antonius Laenen: USGS-TWRI Book 3, Chapter A17. 1985. 38 pages.
- 3-A18. *Determination of stream reaeration coefficients by use of tracers*, by F.A. Kilpatrick, R.E. Rathbun, Nobuhiro Yotsukura, G.W. Parker, and L.L. DeLong: USGS-TWRI Book 3, Chapter A18. 1989. 52 pages.

- 3-A19. *Levels at streamflow gaging stations*, by E.J. Kennedy: USGS-TWRI Book 3, Chapter A19. 1990. 31 pages.
- 3-A20. *Simulation of soluble waste transport and buildup in surface waters using tracers*, by F.A. Kilpatrick: USGS-TWRI Book 3, Chapter A20. 1993. 38 pages.
- 3-A21. *Stream-gaging cableways*, by C.R. Wagner: USGS-TWRI Book 3, Chapter A21. 1995. 56 pages.

Section B. Ground-Water Techniques

- 3-B1. *Aquifer-test design, observation, and data analysis*, by R.W. Stallman: USGS-TWRI Book 3, Chapter B1. 1971. 26 pages.
- 3-B2. *Introduction to ground-water hydraulics, a programmed text for self-instruction*, by G.D. Bennett: USGS-TWRI Book 3, Chapter B2. 1976. 172 pages.
- 3-B3. *Type curves for selected problems of flow to wells in confined aquifers*, by J.E. Reed: USGS-TWRI Book 3, Chapter B3. 1980. 106 pages.
- 3-B4. *Regression modeling of ground-water flow*, by R.L. Cooley and R.L. Naff: USGS-TWRI Book 3, Chapter B4. 1990. 232 pages.
- 3-B4. *Supplement 1. Regression modeling of ground-water flow -- Modifications to the computer code for nonlinear regression solution of steady-state ground-water flow problems*, by R.L. Cooley: USGS-TWRI Book 3, Chapter B4. 1993. 8 pages.
- 3-B5. *Definition of boundary and initial conditions in the analysis of saturated ground-water flow systems—An introduction*, by O.L. Franke, T.E. Reilly, and G.D. Bennett: USGS-TWRI Book 3, Chapter B5. 1987. 15 pages.
- 3-B6. *The principle of superposition and its application in ground-water hydraulics*, by T.E. Reilly, O.L. Franke, and G.D. Bennett: USGS-TWRI Book 3, Chapter B6. 1987. 28 pages.
- 3-B7. *Analytical solutions for one-, two-, and three-dimensional solute transport in ground-water systems with uniform flow*, by E.J. Wexler: USGS-TWRI Book 3, Chapter B7. 1992. 190 pages.

Section C. Sedimentation and Erosion Techniques

- 3-C1. *Fluvial sediment concepts*, by H.P. Guy: USGS-TWRI Book 3, Chapter C1. 1970. 55 pages.
- 3-C2. *Field methods for measurement of fluvial sediment*, by Thomas K. Edwards and

G. Douglas Glysson: USGS-TWRI Book 3, Chapter C2. 1988. 80 pages.

- 3-C3. *Computation of fluvial-sediment discharge*, by George Porterfield: USGS-TWRI Book 3, Chapter C3. 1972. 66 pages.

Book 4. Hydrologic Analysis and Interpretation

Section A. Statistical Analysis

- 4-A1. *Some statistical tools in hydrology*, by H.C. Riggs: USGS-TWRI Book 4, Chapter A1. 1968. 39 pages.
- 4-A2. *Frequency curves*, by H.C. Riggs: USGS-TWRI Book 4, Chapter A2. 1968. 15 pages.

Section B. Surface Water

- 4-B1. *Low-flow investigations*, by H.C. Riggs: USGS-TWRI Book 4, Chapter B1. 1972. 18 pages.
- 4-B2. *Storage analyses for water supply*, by H.C. Riggs and C.H. Hardison: USGS-TWRI Book 4, Chapter B2. 1973. 20 pages.
- 4-B3. *Regional analyses of streamflow characteristics*, by H.C. Riggs: USGS-TWRI Book 4, Chapter B3. 1973. 15 pages.

Section D. Interrelated Phases of the Hydrologic Cycle

- 4-D1. *Computation of rate and volume of stream depletion by wells*, by C.T. Jenkins: USGS-TWRI Book 4, Chapter D1. 1970. 17 pages.

Book 5. Laboratory Analysis

Section A. Water Analysis

- 5-A1. *Methods for determination of inorganic substances in water and fluvial sediments*, by M.J. Fishman and L.C. Friedman, editors: USGS-TWRI Book 5, Chapter A1. 1989. 545 pages.
- 5-A2. *Determination of minor elements in water by emission spectroscopy*, by P.R. Barnett and E.C. Mallory, Jr.: USGS-TWRI Book 5, Chapter A2. 1971. 31 pages.
- 5-A3. *Methods for the determination of organic substances in water and fluvial sediments*, edited by R.L. Wershaw, M.J. Fishman, R.R. Grabbe, and L.E. Lowe: USGS-TWRI Book 5, Chapter A3. 1987. 80 pages.
- 5-A4. *Methods for collection and analysis of aquatic biological and microbiological samples*, by L.J. Britton and P.E. Greeson, editors: USGS-TWRI Book 5, Chapter A4. 1989. 363 pages.

5-A5. *Methods for determination of radioactive substances in water and fluvial sediments*, by L.L. Thatcher, V.J. Janzer, and K.W. Edwards: USGS–TWRI Book 5, Chapter A5. 1977. 95 pages.

5-A6. *Quality assurance practices for the chemical and biological analyses of water and fluvial sediments*, by L.C. Friedman and D.E. Erdmann: USGS–TWRI Book 5, Chapter A6. 1982. 181 pages.

Section C. Sediment Analysis

5-C1. *Laboratory theory and methods for sediment analysis*, by H.P. Guy: USGS–TWRI Book 5, Chapter C1. 1969. 58 pages.

Book 6. Modeling Techniques

Section A. Ground Water

6-A1. *A modular three-dimensional finite-difference ground-water flow model*, by M.G. McDonald and A.W. Harbaugh: USGS–TWRI Book 6, Chapter A1. 1988. 586 pages.

6-A2. *Documentation of a computer program to simulate aquifer-system compaction using the modular finite-difference ground-water flow model*, by S.A. Leake and D.E. Prudic: USGS–TWRI Book 6, Chapter A2. 1991. 68 pages.

6-A3. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 1: Model Description and User's Manual*, by L.J. Torak: USGS–TWRI Book 6, Chapter A3. 1993. 136 pages.

6-A4. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 2: Derivation of finite-element equations and comparisons with analytical solutions*, by R.L. Cooley: USGS–TWRI Book 6, Chapter A4. 1992. 108 pages.

6-A5. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 3: Design philosophy and programming details*, by L.J. Torak: USGS–TWRI Book 6, Chapter A5, 1993. 243 pages.

6-A6. *A coupled surface-water and ground-water flow model (MODBRANCH) for simulation of stream-aquifer interaction*, by Eric D. Swain and Eliezer J. Wexler. 1996. 125 pages.

Book 7. Automated Data Processing and Computations

Section C. Computer Programs

7-C1. *Finite difference model for aquifer simulation in two dimensions with results of numerical experiments*, by P.C. Trescott, G.F. Pinder, and S.P. Larson: USGS–TWRI Book 7, Chapter C1. 1976. 116 pages.

7-C2. *Computer model of two-dimensional solute transport and dispersion in ground water*, by L.F. Konikow and J.D. Bredehoeft: USGS–TWRI Book 7, Chapter C2. 1978. 90 pages.

7-C3. *A model for simulation of flow in singular and interconnected channels*, by R.W. Schaffranek, R.A. Baltzer, and D.E. Goldberg: USGS–TWRI Book 7, Chapter C3. 1981. 110 pages.

Book 8. Instrumentation

Section A. Instruments for Measurement of Water Level

8-A1. *Methods of measuring water levels in deep wells*, by M.S. Garber and F.C. Koopman: USGS–TWRI Book 8, Chapter A1. 1968. 23 pages.

8-A2. *Installation and service manual for U.S. Geological Survey manometers*, by J.D. Craig: USGS–TWRI Book 8, Chapter A2. 1983. 57 pages.

Section B. Instruments for Measurement of Discharge

8-B2. *Calibration and maintenance of vertical-axis type current meters*, by G.F. Smoot and C.E. Novak: USGS–TWRI Book 8, Chapter B2. 1968. 15 pages.

Book 9. Handbooks for Water-Resources Investigations

Section A. National Field Manual for the Collection of Water-Quality Data

9-A1. *National Field Manual for the Collection of Water-Quality Data: Preparations for Water Sampling*, by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS–TWRI Book 9, Chapter A1. 1998. 47 p.

9-A2. *National Field Manual for the Collection of Water-Quality Data: Selection of Equipment for Water Sampling*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS–TWRI Book 9, Chapter A2. 1998. 94 p.

9-A3. *National Field Manual for the Collection of Water-Quality Data: Cleaning of Equipment for Water Sampling*, edited by F.D. Wilde,

- D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo:
USGS–TWRI Book 9, Chapter A3. 1998.
75 p.
- 9-A4. *National Field Manual for the Collection of Water-Quality Data: Collection of Water Samples*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS–TWRI Book 9, Chapter A4. 1999. 156 p.
- 9-A5. *National Field Manual for the Collection of Water-Quality Data: Processing of Water Samples*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS–TWRI Book 9, Chapter A5. 1999, 149 p.
- 9-A6. *National Field Manual for the Collection of Water-Quality Data: Field Measurements*, edited by F.D. Wilde and D.B. Radtke:
USGS–TWRI Book 9, Chapter A6. 1998.
Variously paginated.
- 9-A7. *National Field Manual for the Collection of Water-Quality Data: Biological Indicators*, by D.N. Myers and F.D. Wilde: USGS–TWRI Book 9, Chapter A7. 1997. 49 pages.
- 9-A8. *National Field Manual for the Collection of Water-Quality Data: Bottom-material samples*, by D.B. Radtke: USGS–TWRI Book 9, Chapter A8. 1998. 48 pages.
- 9-A9. *National Field Manual for the Collection of Water-Quality Data: Safety in Field Activities*, by S.L. Lane and R.G. Fay: USGS–TWRI Book 9, Chapter A9. 1998. 60 pages.