

# Bay Area Air Quality Management District

939 Ellis Street  
San Francisco, CA 94109  
(415) 771-6000

---

---

## Proposed Renewal of MAJOR FACILITY REVIEW PERMIT

Issued To:  
**Rexam Beverage Can Company**  
**Site #A1665**

**Site Address:**  
2433 Crocker Circle Drive  
Fairfield, CA 94533

**Mailing Address:**  
8770 W. Bryn Mawr Avenue, M.S. 04D  
Chicago, IL 60631-3542

**Responsible Official**  
Allan J. Bohner,  
Senior Vice President  
North America Manufacturing  
& Worldwide Engineering  
(773) 399-~~3389~~**3613**

**Facility Contact**  
~~Ronald J. Kanueh~~**Dave Rubick,**  
Plant Manager  
(707) 437-6645

---

---

<b>Type of Facility:</b>	Beverage Can Manufacturing	BAAQMD <b>Engineering</b> Permit
<b>Division Contact:</b>		
<b>Primary SIC:</b>	3411	Ted Hull
<b>Product:</b>	Coated and Decorated Aluminum Beverage Cans	

**ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT**

---

Jack P. Broadbent, Executive Officer/Air Pollution Control Officer

---

Date

## TABLE OF CONTENTS

I. STANDARD CONDITIONS .....	<del>323</del>
II. EQUIPMENT .....	<del>727</del>
III. GENERALLY APPLICABLE REQUIREMENTS .....	<del>10210</del>
IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS .....	<del>13213</del>
V. SCHEDULE OF COMPLIANCE .....	<del>29229</del>
VI. PERMIT CONDITIONS .....	<del>29229</del>
VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS .....	<del>35235</del>
VIII. TEST METHODS .....	<del>50250</del>
IX. REVISION HISTORY .....	<del>52252</del>
X. GLOSSARY .....	<del>53253</del>

## I. STANDARD CONDITIONS

### A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

- BAAQMD Regulation 1 - General Provisions and Definitions  
(as amended by the District Board on ~~10/7/985/2/01~~);
- SIP Regulation 1 - General Provisions and Definitions  
(as approved by EPA through ~~9/29/986/28/99~~);
- BAAQMD Regulation 2, Rule 1 - Permits, General Requirements  
(as amended by the District Board on ~~10/7/9812/21/04~~);
- SIP Regulation 2, Rule 1 - Permits, General Requirements  
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 2 - Permits, New Source Review  
(as amended by the District Board on ~~10/7/9812/21/04~~);
- SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration  
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking  
(as amended by the District Board on ~~10/7/9812/21/04~~); and
- SIP Regulation 2, Rule 4 - Permits, Emissions Banking  
(as approved by EPA through 1/26/99); and
- BAAQMD Regulation 2, Rule 6 – Permits, Major Facility Review  
(as amended by the District Board on 4/16/03).**

### B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit expires on ~~July 28, 2004~~. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than ~~January 28, 2004~~ and no earlier ~~July 28, 2003~~. **If a complete application for renewal has not been submitted in accordance with these deadlines, the facility may not operate after ~~July 28, 2004~~. If the permit renewal has not been issued by \_\_\_\_\_, but a complete application for renewal has been submitted in accordance with the above deadlines, the existing permit will continue in force until the District takes final action on the renewal application. (Regulation 2-6-307, 404.2, 407, & 409.6; MOP Volume II, Part 3, §4.2) (~~Regulation 2-6-307, 404.2, & 409.6; MOP Volume II, Part 3, §4.2~~)**
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)

## I. Standard Conditions

4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or **the filing** of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
6. This permit does not convey any property rights of any sort, nor any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
8. Any records required to be maintained pursuant to this permit ~~which~~**that** the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions **or the potential to emit** for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)
- 11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (Regulation 2-6-409.20; MOP Volume II, Part 3, §4.11)**

### C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

### D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment ~~which~~**that** is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

### E. Records

- 1. The permit holder must provide any information, records, and reports**

## I. Standard Conditions

- requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)**
2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of entry. (Regulation 2-6-501, ~~Regulation 3;~~ MOP Volume II, Part 3, §4.7)

### F. Monitoring Reports

**Reports of A**all required monitoring ~~reports~~ must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. **The reporting periods for this permit shall be June 1st through November 30th and December 1st through May 31st . Each report is due on the last day of the month after the end of the reporting period.** All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement  
Bay Area Air Quality Management District  
939 Ellis Street  
San Francisco, CA 94109  
Attn: Title V Reports

(Regulation 2-6-502, ~~Regulation 3;~~ MOP Volume II, Part 3, §4.7)

### G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. **The certification period will be December 1st through November 30th. The certification shall be submitted by December 31 of each year.** The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division  
USEPA, Region IX  
75 Hawthorne Street  
San Francisco, CA 94105  
Attention: Air-3

## I. Standard Conditions

(MOP Volume II, Part 3, §4.5 and 4.15)

### H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit ~~caused by conditions beyond the permit holder's reasonable control~~ by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. ~~Any variance granted by the Hearing Board from any term or condition of this permit which lasts longer than 90 days will be subject to EPA approval.~~ (MOP Volume II, Part 3, §4.8)
3. ~~Notwithstanding the foregoing,~~ The granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement unless the Major Facility Review Permit has been modified pursuant to Regulation 2, Rule 6. (MOP Volume II, Part 3, §4.8)

### I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

### J. Miscellaneous Conditions

**The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)**

## II. EQUIPMENT

**Table II A - Permitted Sources**

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. **The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301.**

S-#	Description	Make or Type	Model	Capacity
S-1	Roller Coater - Line 1	Rutherford	CB 1200	<del>1,200</del> <b>1,762</b> Cans Per Minute
S-2	Coater Oven - Line 1	Feco Pin, Natural Gas		3.6 MMBTU/hr
S-3	Printer - Line 1	Rutherford	CD 1200	<del>1,200</del> <b>1,762</b> CPM
S-4	Printer Oven - Line 1	Feco Pin, Natural Gas		3.6 MMBTU/hr
S-5	Spray Machines - Line 1	NCC	773.3	(6) x <del>225</del> <b>294</b> CPM
S-6	Bake Oven - Line 1	Feco Pin, Natural Gas		3.0 MMBTU/hr
S-7	Roller Coater - Line 2	Rutherford	CB 1200	<del>1,200</del> <b>1,762</b> CPM
S-8	Coater Oven - Line 2	Feco Pin, Natural Gas		3.6 MMBTU/hr
S-9	Printer - Line 2	Rutherford	CD 1200	<del>1,200</del> <b>1,762</b> CPM
S-10	Printer Oven - Line 2	Feco Pin, Natural Gas		3.6 MMBTU/hr
S-11	Spray Machines - Line 2	NCC	773.3	(6) x <del>225</del> <b>294</b> CPM
S-12	Bake Oven - Line 2	Feco Pin, Natural Gas		3.0 MMBTU/hr
S-13	Basecoat Bulk Tank	Fixed Roof		10,000 gallons
S-14	Overvarnish Bulk Tank	Fixed Roof		10,000 gallons
S-15	Inside Spray Bulk Tank	Fixed Roof		10,000 gallons
S-16	Scrap Collection System	BLO-APCO	185	1,000 lb/hr
S-17	Lime Silo	Lime Storage		10 tons/hr max <del>fill</del> <del>rate</del> <b>capacity</b>

## II. Equipment

**Table II B - Abatement Devices**

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A-1	Direct Flame Afterburner	2, 4, 5, 6, 8, 10, 11, 12	BAAQMD Condition #394; Parts 3,4,5,6,7	1,450 °F during all periods of operation	95%
A-1	Direct Flame Afterburner	1, 2, 3, 4,5, 6, 7, 8, 9, 10, 11, 12	Regulation 8-11-302	Required for coating usage not complying with 8-11-301	90%
A-1	Direct Flame Afterburner	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12	NSPS -Subpart WW	As needed	Achieve VOC emission standards of 60.492
A-2	Pulse Jet Baghouse	5, 11	Regulation 6-301, <del>6-310</del>	<del>As-needed</del>	Ringelmann #1 for <b>3 minutes in any hour; 0.15- gr/dscf</b>
<b>A-2</b>	<b>Pulse Jet Baghouse</b>	<b>5, 11</b>	<b>Regulation 6-310</b>		<b>0.15 gr/dscf</b>
A-3	Vapor Balance System	13	None	N/A	N/A
A-4	Vapor Balance System	14	None	N/A	N/A
A-5	Vapor Balance System	15	None	N/A	N/A
A-6	Scrap Cyclone	16	Regulation 6-301, <del>6-310</del>	<del>As-needed</del>	Ringelmann #1 for <b>3 minutes in any hour; 0.15- gr/dscf</b>
<b>A-6</b>	<b>Scrap Cyclone</b>	<b>16</b>	<b>Regulation 6-310</b>		<b>0.15 gr/dscf</b>



## II. Equipment

**Table II B - Abatement Devices**

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A-7	Oil Mist Collector	16	Regulation 6-301, <del>6-310</del>	<del>As-needed</del>	Ringelmann #1 for <b>3 minutes</b> in any hour; <del>0.15-</del> <del>gr/dscf</del>
<b>A-7</b>	<b>Oil Mist Collector</b>	<b>16</b>	<b>Regulation</b> <b>6-310</b>		<b>0.15 gr/dscf</b>
A-8	Lime Silo Baghouse	17	Regulation 6-301, <del>6-310</del>	<del>As-needed</del>	Ringelmann #1 for <b>3 minutes</b> in any hour; <del>0.15-</del> <del>gr/dscf</del>
<b>A-8</b>	<b>Lime Silo Baghouse</b>	<b>17</b>	<b>Regulation</b> <b>6-310</b>		<b>0.15 gr/dscf</b>

### III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements would not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit. **This section also contains provisions that may apply to temporary sources.**

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board **of Directors.**
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

~~Where an applicable requirement is a SIP requirement, the full language of the SIP requirement is included in Appendix A of this permit. The full language of SIP requirements is on EPA Region 9's website. The address is:~~  
**<http://yosemite.epa.gov/r9/r9sips.nsf/Casips?readform&state=California>**

**NOTE:**

~~There are differences between the current BAAQMD rule and the version of the rule in the SIP. For specific information, contact the District's Rule Development Section of the Enforcement Division. All sources must comply with both versions of the rule until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~  
**There are differences between the current BAAQMD rules and the versions of the rules in the SIP. All sources must comply with both versions of a rule until US EPA has reviewed and approved the District's revision of the regulation.**

**Table III  
Generally Applicable Requirements**

### III. Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions ( <del>10/7/98</del> 5/2/01)	N
SIP Regulation 1	General Provisions and Definitions ( <del>9/29/98</del> 6/28/99)	Y <sup>1</sup>
<b>BAAQMD Regulation 2, Rule 1</b>	<b>General Requirements (8/1/01)</b>	<b>N</b>
<b>BAAQMD 2-1-429</b>	<b>Federal Emissions Statement (6/7/95)</b>	<b>Y</b>
<b>SIP Regulation 2, Rule 1</b>	<b>General Requirements (1/26/99)</b>	<b>Y<sup>1</sup></b>
BAAQMD Regulation 5	Open Burning ( <del>11/2/94</del> 3/6/02)	Y
<b>SIP Regulation 5</b>	<b>Open Burning (9/4/98)</b>	<b>Y<sup>1</sup></b>
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y
<b>BAAQMD Regulation 8, Rule 2</b>	<b>Organic Compounds – Miscellaneous Operations (6/15/94)</b>	<b>Y</b>
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings ( <del>12/20/95</del> 11/21/01)	<del>Y</del> N
<b>BAAQMD Regulation 8, Rule 4</b>	<b>Organic Compounds - General Solvent and Surface Coating Operations (10/16/02)</b>	<b>Y</b>
<b>BAAQMD Regulation 8, Rule 16</b>	<b>Organic Compounds - Solvent Cleaning Operations (10/16/02)</b>	<b>Y</b>
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y <sup>1</sup>
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products ( <del>12/20/95</del> 7/17/02)	N
<b>SIP Regulation 8, Rule 51</b>	<b>Organic Compounds - Adhesive and Sealant Products (2/26/02)</b>	<b>Y<sup>1</sup></b>
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)	N
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide ( <del>7/8/99</del> 6/8/99)	Y <sup>1</sup>
<b>BAAQMD Regulation 11, Rule 1</b>	<b>Hazardous Pollutants - Lead (3/17/82)</b>	<b>N</b>
<b>SIP Regulation 11, Rule 1</b>	<b>Hazardous Pollutants – Lead (9/2/81)</b>	<b>Y<sup>1</sup></b>
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing ( <del>12/4/94</del> 10/7/98)	<del>Y</del> N
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	<del>Y</del> N
<b>SIP Regulation 12, Rule 4</b>	<b>Miscellaneous Standards of Performance - Sandblasting (9/2/81)</b>	<b>Y<sup>1</sup></b>

### III. Generally Applicable Requirements

**Table III  
Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
California Health and Safety Code Section 41750 et seq.	Portable Equipment	N
California Health and Safety Code Section 44300 et seq.	Air Toxics "Hot Spots" Information and Assessment Act of 1987	N
40 CFR Part 61, Subpart A	National Emission Standards for Hazardous Air Pollutants – General Provisions (5/28/03)	Y

1. This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved the District's revision of the regulation.

#### IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s):  
 The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors.
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP:  
 The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. ~~Additionally, where an applicable requirement is a SIP requirement, the full language of the SIP requirement is included in Appendix A of this permit. The full language of SIP requirements is on EPA Region 9's website. The address is:~~ <http://yosemite.epa.gov/r9/r9sips.nsf/Casips?readform&state=California>. All other text may be found in the regulations themselves.

**Table IV-A  
 Source-Specific Applicable Requirements  
 S-1, S-7: Roller Coaters, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Reporting requirement for periods of inoperation > 24 hours	Y	
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	N	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
1-523.5	Maintenance and calibration	N	

## IV. Source-Specific Applicable Requirements

**Table IV-A**  
**Source-Specific Applicable Requirements**  
**S-1, S-7: Roller Coaters, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>SIP</b> <b>Regulation 1</b>	<b>General Provisions and Definitions (6/28/99)</b>		
<b>1-523</b>	<b>Parametric Monitoring and Recordkeeping Procedures</b>	<b>Y<sup>1</sup></b>	
<b>1-523.3</b>	<b>Reports of Violations</b>	<b>Y<sup>1</sup></b>	
<b>BAAQMD</b> <b>Regulation 8,</b> <b>Rule 11</b>	<b>Organic Compounds – Metal Container, Closure And Coil Coating (11/19/97)</b>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>		
<del>8-11-301.3</del>	<del>—VOC Limit— Two Piece Can Basecoat</del>	<del>Y</del>	
8-11-302	Emission Control Device Requirement (alternative to coating limits)	Y	
<del>8-11-305</del>	<del>Alternate Emission Control Plan (optional)</del>	<del>Y</del>	
8-11-306	Surface Preparation and Cleanup Solvent	Y	
8-11-402	Operation and Maintenance Plan	Y	
8-11-501	Coating Records	Y	
8-11-504	Afterburner Temperature Monitoring (where applicable)	Y	
<b>NSPS</b> <b>Part 60</b>	<b>Standards of Performance for New Stationary Sources (12/23/71)</b>		
<b>Subpart A</b>	<b>General Provisions</b>	<b>Y</b>	
60.7	Notification and Record Keeping	Y	
60.8 (a)	Initial Performance Test	Y	
60.9	Availability of Information	Y	
60.11 (a)	Compliance with standards and maintenance requirements	Y	
60.12	Circumvention	Y	
60.13 (a)(b)(e)(f)(i)	Monitoring Requirements	Y	
<b>NSPS Subpart</b> <b>WW</b>	<b>Standards of Performance for the Beverage Can Surface Coating Industry (8/25/83)</b>		
60.492 (a)	VOC Limit – Two-Piece Can Exterior Basecoat	Y	
60.493 (b)	Monthly Performance Test	Y	
60.494	Monitoring of Operations	Y	
60.495	Reporting and Recordkeeping	Y	

#### IV. Source-Specific Applicable Requirements

**Table IV-A**  
**Source-Specific Applicable Requirements**  
**S-1, S-7: Roller Coaters, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.496	Test Methods and Procedures	Y	
<b>BAAQMD Cond #391</b>			
part 1	Facility VOC <b>and HAP</b> Limits [Cumulative Increase, <b>40 CFR 63.3480(b)</b> ]	Y	
part 12	Recordkeeping [Cumulative Increase, <b>Regulation 2-1-403</b> ]	Y	

**1** This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

**Table IV-B**  
**Source-Specific Applicable Requirements**  
**S-2, S-8: Coater Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 1</b>	<b>General Provisions and Definitions (5/2/01)</b>		
<b>1-523</b>	<b>Parametric Monitoring and Recordkeeping Procedures</b>	<b>N</b>	
<b>1-523.1</b>	<b>Reporting requirement for periods of inoperation &gt; 24 hours</b>	<b>Y</b>	
<b>1-523.2</b>	<b>Limit on duration of inoperation</b>	<b>Y</b>	
<b>1-523.3</b>	<b>Reporting requirement for violations of any applicable limits</b>	<b>N</b>	
<b>1-523.4</b>	<b>Records of inoperation, tests, calibrations, adjustments, &amp; maintenance</b>	<b>Y</b>	
<b>1-523.5</b>	<b>Maintenance and calibration</b>	<b>N</b>	
<b>SIP Regulation 1</b>	<b>General Provisions and Definitions (6/28/99)</b>		
<b>1-523</b>	<b>Parametric Monitoring and Recordkeeping Procedures</b>	<b>Y<sup>1</sup></b>	

#### IV. Source-Specific Applicable Requirements

**Table IV-B**  
**Source-Specific Applicable Requirements**  
**S-2, S-8: Coater Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<del>1-523.3</del>	<del>Reports of Violations</del>	<del>Y<sup>1</sup></del>	
<b>BAAQMD Regulation 8, Rule 11</b>	<b>Organic Compounds – Metal Container, Closure And Coil Coating (11/19/97)</b>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>		
<del>8-11-301.3</del>	<del>—VOC Limit—Two Piece Can Basecoat</del>	<del>Y</del>	
8-11-302	Emission Control Device Requirement (alternative to coating limits)	Y	
<del>8-11-305</del>	<del>Alternate Emission Control Plan (optional)</del>	<del>Y</del>	
8-11-402	Operation and Maintenance Plan	Y	
8-11-504	Afterburner Temperature Monitoring (where applicable)	Y	
<b>NSPS Part 60</b>	<b>Standards of Performance for New Stationary Sources (12/23/71)</b>		
<b>Subpart A</b>	<b>General Provisions</b>		
60.7	Notification and Record Keeping	Y	
60.8 (a)	Initial Performance Test	Y	
60.9	Availability of Information	Y	
60.11 (a)	Compliance with standards and maintenance requirements	Y	
60.12	Circumvention	Y	
60.13 (a)(b)(e)(f)(i)	Monitoring Requirements	Y	
<b>NSPS Subpart WW</b>	<b>Standards of Performance for the Beverage Can Surface Coating Industry (8/25/83)</b>		
60.492(a)	VOC Limits	Y	
60.493 (b)	Monthly Performance Test	Y	
60.494	Monitoring of Operations	Y	
60.495	Reporting and Recordkeeping	Y	
60.496	Test Methods and Procedures	Y	
<b>BAAQMD Cond #391</b>			



#### IV. Source-Specific Applicable Requirements

**Table IV-B**  
**Source-Specific Applicable Requirements**  
**S-2, S-8: Coater Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>part 1</b>	<b>Facility VOC and HAP Limits [Cumulative Increase, 40 CFR 63.3480(b)]</b>	<b>Y</b>	
part 2	Afterburner Requirement [BACT, Regulation 8-11-302]	Y	
part 3	Automatic Oven Shutdown when Airflow is Lost [BACT]	Y	
part 5	Afterburner VOC Control Efficiency [BACT]	Y	
part 6	Incinerator Temperature [BACT]	Y	
part 7	Incinerator Temperature Monitoring/Recording [BACT, Regulation 8-11-504]	Y	
part 8	Allowable temperature excursions [Regulation 2-1-403]	Y	
part 9	Allowable temperature excursion recordkeeping [Regulation 2-1-403]	Y	
part 10	Definition of temperature excursion [Regulation 2-1-403]	Y	
part 11	Incinerator Temperature Recordkeeping [BACT]	Y	
part 12	Recordkeeping [Cumulative Increase, <b>Regulation 2-1-403</b> ]	Y	

**1 This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.**

**Table IV-C**  
**Source-Specific Applicable Requirements**  
**S-3, S-9: Printers, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 1</b>	<b>General Provisions and Definitions (5/2/01)</b>		
<b>1-523</b>	<b>Parametric Monitoring and Recordkeeping Procedures</b>	<b>N</b>	
<b>1-523.1</b>	<b>Reporting requirement for periods of inoperation &gt; 24 hours</b>	<b>Y</b>	

## IV. Source-Specific Applicable Requirements

**Table IV-C**  
**Source-Specific Applicable Requirements**  
**S-3, S-9: Printers, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	N	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y <sup>1</sup>	
1-523.3	Reports of Violations	Y <sup>1</sup>	
BAAQMD Regulation 8, Rule 11	Organic Compounds – Metal Container, Closure And Coil Coating (11/19/97)		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>		
<del>8-11-301.3</del>	<del>—VOC Limit— Two Piece Can Overvarnish</del>	<del>Y</del>	
<del>8-11-301.10</del>	<del>—VOC Limit— Inks</del>	<del>N</del>	
8-11-302	Emission Control Device Requirement (alternative to coating limits)	Y	
<del>8-11-305</del>	<del>Alternative Emission Control Plan (optional)</del>	<del>Y</del>	
8-11-306	Surface Preparation and Cleanup Solvent	Y	
8-11-402	Operation and Maintenance Plan	Y	
8-11-501	Coating Records	Y	
8-11-504	Afterburner Temperature Monitoring (where applicable)	Y	
<del>SIP Regulation 8, Rule 11</del>	<del>Organic Compounds—Metal Container, Closure And Coil Coating (12/23/97)</del>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>	<del>Y<sup>1</sup></del>	
<del>8-11-301.9</del>	<del>VOC Limit— Inks</del>	<del>Y<sup>1</sup></del>	
NSPS Part 60	Standards of Performance for New Stationary Sources (12/23/71)		
Subpart A	General Provisions		
60.7	Notification and Record Keeping	Y	
60.8 (a)	Initial Performance Test	Y	

#### IV. Source-Specific Applicable Requirements

**Table IV-C**  
**Source-Specific Applicable Requirements**  
**S-3, S-9: Printers, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.9	Availability of Information	Y	
60.11 (a)	Compliance with standards and maintenance requirements	Y	
60.12	Circumvention	Y	
60.13 (a)(b)(e)(f)(i)	Monitoring Requirements	Y	
<b>NSPS Subpart WW</b>	<b>Standards of Performance for the Beverage Can Surface Coating Industry (8/25/83)</b>		
60.492 (b)	VOC Limit – Two-Piece Can Clear Basecoat and Overvarnish	Y	
60.493 (b)	Monthly Performance Test	Y	
60.494	Monitoring of Operations	Y	
60.495	Reporting and Recordkeeping	Y	
60.496	Test Methods and Procedures	Y	
<b>BAAQMD Cond #391</b>			
part 1	Facility VOC <b>and HAP</b> Limits [Cumulative Increase, <b>40 CFR 63.3480(b)</b> ]	Y	
part 12	Recordkeeping [Cumulative Increase, <b>Regulation 2-1-403</b> ]	Y	

**1** This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

**Table IV-D**  
**Source-Specific Applicable Requirements**  
**S-4, S-10: Printer Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 1</b>	<b>General Provisions and Definitions (5/2/01)</b>		

#### IV. Source-Specific Applicable Requirements

**Table IV-D**  
**Source-Specific Applicable Requirements**  
**S-4, S-10: Printer Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Reporting requirement for periods of inoperation > 24 hours	Y	
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	N	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y <sup>1</sup>	
1-523.3	Reports of Violations	Y <sup>1</sup>	
BAAQMD Regulation 8, Rule 11	Organic Compounds – Metal Container, Closure And Coil Coating (11/19/97)		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>		
<del>8-11-301.3</del>	<del>—VOC Limit—Two Piece Can Overvarnish</del>	<del>Y</del>	
<del>8-11-301.10</del>	<del>—VOC Limit—Inks</del>	<del>N</del>	
8-11-302	Emission Control Device Requirement (alternative to coating limits)	Y	
<del>8-11-305</del>	<del>Alternate Emission Control Plan (optional)</del>	<del>Y</del>	
8-11-402	Operation and Maintenance Plan	Y	
8-11-504	Afterburner Temperature Monitoring (where applicable)	Y	
<del>SIP Regulation 8, Rule 11</del>	<del>Organic Compounds—Metal Container, Closure And Coil Coating (12/23/97)</del>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>	<del>Y<sup>1</sup></del>	
<del>8-11-301.9</del>	<del>VOC Limit—Inks</del>	<del>Y<sup>1</sup></del>	
NSPS Part 60	Standards of Performance for New Stationary Sources (12/23/71)		
Subpart A	General Provisions		
60.7	Notification and Record Keeping	Y	
60.8 (a)	Initial Performance Test	Y	

#### IV. Source-Specific Applicable Requirements

**Table IV-D  
 Source-Specific Applicable Requirements  
 S-4, S-10: Printer Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.9	Availability of Information	Y	
60.11 (a)	Compliance with standards and maintenance requirements	Y	
60.12	Circumvention	Y	
60.13 (a)(b)(e)(f)(i)	Monitoring Requirements	Y	
<b>NSPS Subpart WW</b>	<b>Standards of Performance for the Beverage Can Surface Coating Industry (8/25/83)</b>		
60.492(b)	VOC Limits	Y	
60.493 (b)	Monthly Performance Test	Y	
60.494	Monitoring of Operations	Y	
60.495	Reporting and Recordkeeping	Y	
60.496	Test Methods and Procedures	Y	
<b>BAAQMD Cond #391</b>			
<b>part 1</b>	<b>Facility VOC and HAP Limits [Cumulative Increase, 40 CFR 63.3480(b)]</b>	<b>Y</b>	
part 2	Afterburner Requirement [BACT, Regulation 8-11-302]	Y	
part 3	Automatic Oven Shutdown when Airflow is Lost [BACT]	Y	
part 5	Afterburner VOC Control Efficiency [BACT]	Y	
part 6	Incinerator Temperature [BACT]	Y	
part 7	Incinerator Temperature Monitoring/Recording [BACT, Regulation 8-11-504]	Y	
part 8	Allowable temperature excursions [Regulation 2-1-403]	Y	
part 9	Allowable temperature excursion recordkeeping [Regulation 2-1-403]	Y	
part 10	Definition of temperature excursion [Regulation 2-1-403]	Y	
part 11	Incinerator Temperature Recordkeeping [BACT]	Y	
part 12	Recordkeeping [Cumulative Increase, <b>Regulation 2-1-403</b> ]	Y	

**1 This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.**

## IV. Source-Specific Applicable Requirements

**Table IV-E**  
**Source-Specific Applicable Requirements**  
**S-5, S-11: Inside Spray Machines, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 1</b>	<b>General Provisions and Definitions (5/2/01)</b>		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Reporting requirement for periods of inoperation > 24 hours	Y	
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	N	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
1-523.5	Maintenance and calibration	N	
<b>SIP Regulation 1</b>	<b>General Provisions and Definitions (6/28/99)</b>		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y <sup>1</sup>	
1-523.3	Reports of Violations	Y <sup>1</sup>	
<b>BAAQMD Regulation 6</b>	<b>Particulate Matter and Visible Emissions (12/19/90)</b>		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
<b>BAAQMD Regulation 8, Rule 11</b>	<b>Organic Compounds – Metal Container, Closure And Coil Coating (11/19/97)</b>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>		
<del>8-11-301.4.1</del>	<del>—VOC Limit—Interior Body Spray</del>	<del>N</del>	
8-11-302	Emission Control Device Requirement (alternative to coating limits)	Y	
<del>8-11-305</del>	<del>Alternate Emission Control Plan (optional)</del>	<del>Y</del>	
8-11-306	Surface Preparation and Cleanup Solvent	Y	
8-11-402	Operation and Maintenance Plan	Y	
8-11-501	Coating Records	Y	
8-11-504	Afterburner Temperature Monitoring (where applicable)	Y	

## IV. Source-Specific Applicable Requirements

**Table IV-E**  
**Source-Specific Applicable Requirements**  
**S-5, S-11: Inside Spray Machines, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<del>SIP Regulation 8, Rule 11</del>	<del>Organic Compounds—Metal Container, Closure And Coil Coating (12/23/97)</del>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>	<del>Y<sup>+</sup></del>	
<del>8-11-301.4</del>	<del>VOC Limit—Interior Body Spray</del>	<del>Y<sup>+</sup></del>	
<b>NSPS Part 60</b>	<b>Standards of Performance for New Stationary Sources (12/23/71)</b>		
<b>Subpart A</b>	<b>General Provisions</b>		
60.7	Notification and Record Keeping	Y	
60.8 (a)	Initial Performance Test	Y	
60.9	Availability of Information	Y	
60.11 (a)	Compliance with standards and maintenance requirements	Y	
60.12	Circumvention	Y	
60.13 (a)(b)(e)(f)(i)	Monitoring Requirements	Y	
<b>NSPS Subpart WW</b>	<b>Standards of Performance for the Beverage Can Surface Coating Industry (8/25/83)</b>		
60.492 (c)	VOC Limit – Two-Piece Can Inside Spray	Y	
60.493 (b)	Monthly Performance Test	Y	
60.494	Monitoring of Operations	Y	
60.495	Reporting and Recordkeeping	Y	
60.496	Test Methods and Procedures	Y	
<b>BAAQMD Cond #391</b>			
part 1	Facility VOC and HAP Limits [Cumulative Increase, 40 CFR 63.3480(b)]	Y	
part 4	Exhaust Duct Vacuum Pressure [BACT]	Y	
part 5	Afterburner VOC Control Efficiency [BACT]	Y	
part 6	Incinerator Temperature [BACT]	Y	
part 7	Incinerator Temperature Monitoring/Recording [BACT, Regulation 8-11-504]	Y	
part 8	Allowable temperature excursions [Regulation 2-1-403]	Y	

#### IV. Source-Specific Applicable Requirements

**Table IV-E**  
**Source-Specific Applicable Requirements**  
**S-5, S-11: Inside Spray Machines, Line 1 & Line 2**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 9	Allowable temperature excursion recordkeeping [Regulation 2-1-403]	Y	
part 10	Definition of temperature excursion [Regulation 2-1-403]	Y	
part 11	Incinerator Temperature Recordkeeping [BACT]	Y	
part 12	Recordkeeping [Cumulative Increase, <b>Regulation 2-1-403</b> ]	Y	
<b>BAAQMD Cond #16547</b>			
part 1	Particulate Abatement Requirement [Regulation 2-1-403]	Y	
part 2	Quarterly Baghouse Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	

**1 This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.**

**Table IV-F**  
**Source-Specific Applicable Requirements**  
**S-6, S-12: Bake Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 1</b>	<b>General Provisions and Definitions (5/2/01)</b>		
<b>1-523</b>	<b>Parametric Monitoring and Recordkeeping Procedures</b>	<b>N</b>	
<b>1-523.1</b>	<b>Reporting requirement for periods of inoperation &gt; 24 hours</b>	<b>Y</b>	
<b>1-523.2</b>	<b>Limit on duration of inoperation</b>	<b>Y</b>	
<b>1-523.3</b>	<b>Reporting requirement for violations of any applicable limits</b>	<b>N</b>	
<b>1-523.4</b>	<b>Records of inoperation, tests, calibrations, adjustments, &amp; maintenance</b>	<b>Y</b>	
<b>1-523.5</b>	<b>Maintenance and calibration</b>	<b>N</b>	



## IV. Source-Specific Applicable Requirements

**Table IV-F**  
**Source-Specific Applicable Requirements**  
**S-6, S-12: Bake Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>SIP Regulation 1</b>	<b>General Provisions and Definitions (6/28/99)</b>		
<b>1-523</b>	<b>Parametric Monitoring and Recordkeeping Procedures</b>	<b>Y<sup>1</sup></b>	
<b>1-523.3</b>	<b>Reports of Violations</b>	<b>Y<sup>1</sup></b>	
<b>BAAQMD Regulation 8, Rule 11</b>	<b>Organic Compounds – Metal Container, Closure And Coil Coating (11/19/97)</b>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>		
<del>8-11-301.4.1</del>	<del>—VOC Limit— Interior Body Spray</del>	<b>N</b>	
8-11-302	Emission Control Device Requirement (alternative to coating limits)	Y	
<del>8-11-305</del>	<del>Alternate Emission Control Plan (optional)</del>	<b>N</b>	
8-11-402	Operation and Maintenance Plan	Y	
8-11-504	Afterburner Temperature Monitoring (where applicable)	Y	
<b>SIP Regulation 8, Rule 11</b>	<b>Organic Compounds—Metal Container, Closure And Coil Coating (12/23/97)</b>		
<del>8-11-301</del>	<del>Metal Container or Closure Coating Limitations</del>	<b>N<sup>+</sup></b>	
<del>8-11-301.4</del>	<del>VOC Limit— Interior Body Spray</del>	<b>N<sup>+</sup></b>	
<b>NSPS Part 60</b>	<b>Standards of Performance for New Stationary Sources (12/23/71)</b>		
<b>Subpart A</b>	<b>General Provisions</b>	Y	
60.7	Notification and Record Keeping	Y	
60.8 (a)	Initial Performance Test	Y	
60.9	Availability of Information	Y	
60.11 (a)	Compliance with standards and maintenance requirements	Y	
60.12	Circumvention	Y	
60.13 (a)(b)(e)(f)(i)	Monitoring Requirements	Y	
<b>NSPS Subpart WW</b>	<b>Standards of Performance for the Beverage Can Surface Coating Industry (8/25/83)</b>		
60.492(c)	VOC Limits	Y	
60.493 (b)	Monthly Performance Test	Y	
60.494	Monitoring of Operations	Y	

#### IV. Source-Specific Applicable Requirements

**Table IV-F  
 Source-Specific Applicable Requirements  
 S-6, S-12: Bake Ovens**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.495	Reporting and Recordkeeping	Y	
60.496	Test Methods and Procedures	Y	
<b>BAAQMD Cond #391</b>			
<b>part 1</b>	<b>Facility VOC and HAP Limits [Cumulative Increase, 40 CFR 63.3480(b)]</b>	<b>Y</b>	
part 2	Afterburner Requirement [BACT, Regulation 8-11-302]	Y	
part 3	Automatic Oven Shutdown when Airflow is Lost [BACT]	Y	
part 5	Afterburner VOC Control Efficiency [BACT]	Y	
part 6	Incinerator Temperature [BACT]	Y	
part 7	Incinerator Temperature Monitoring/Recording [BACT, Regulation 8-11-504]	Y	
part 8	Allowable temperature excursions [Regulation 2-1-403]	Y	
part 9	Allowable temperature excursion recordkeeping [Regulation 2-1-403]	Y	
part 10	Definition of temperature excursion [Regulation 2-1-403]	Y	
part 11	Incinerator Temperature Recordkeeping [BACT]	Y	
part 12	Recordkeeping [Cumulative Increase, <b>Regulation 2-1-403</b> ]	Y	

**1 This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.**

**Table IV-G  
 Source-Specific Applicable Requirements  
 S-13, S-14, S-15: Storage Tanks; Basecoat, Overvarnish, Inside Spray**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
------------------------	--	-----------------------------	-----------------------

#### IV. Source-Specific Applicable Requirements

**Table IV-G**  
**Source-Specific Applicable Requirements**  
**S-13, S-14, S-15: Storage Tanks; Basecoat, Overvarnish, Inside Spray**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids ( <del>1/20/93</del> 11/27/02)		
<del>8-5-301</del>	<del>Standards—Storage Tanks Smaller than 150m<sup>3</sup></del>	<del>Y</del>	
<del>8-5-328</del>	<del>Tank Cleaning Requirements</del>	<del>Y</del>	
8-5-301	Storage Tanks Control Requirements (Aboveground Tanks >9,906 gallons to <19,803 gallons)	Y	
8-5-302	Requirements for Submerged Fill Pipes	Y	
8-5-501.1	Records (Fixed Roof Tanks)	Y	

**Table IV-H**  
**Source-Specific Applicable Requirements**  
**S-16: Scrap Collection System**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	Process Weight Limitation	Y	
6-401	Appearance of Emissions	Y	

**Table IV-I**  
**Source-Specific Applicable Requirements**  
**S-17: Lime Silo**

#### IV. Source-Specific Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 6</b>	<b>Particulate Matter and Visible Emissions (12/19/90)</b>		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
<b>6-311</b>	<b>Process Weight Limitation</b>	<b>Y</b>	
6-401	Appearance of Emissions	Y	
<b>BAAQMD Cond #16548</b>			
part 1	Particulate Abatement Requirement [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 1-441]	Y	

## V. SCHEDULE OF COMPLIANCE

The permit holder shall continue to comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit **on a timely basis**.

## VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

### Condition #391

For Sources: 1 through 12 (Beverage Can Coating Sources)

#### EMISSIONS

1. Total VOC emissions due to coating usage and clean-up solvent usage at this facility shall not exceed 39.2 tons/year. **Total emissions of hazardous air pollutants (HAPs) at this facility shall be less than 10 tons per year for any single HAP and 25 tons per year for any combination of HAPs.** (basis: Cumulative Increase, **40 CFR 63.3481(b)**)

#### VOC ABATEMENT

2. VOC **and HAP** emissions from the following sources shall be collected and controlled by a direct flame incineration afterburner during all periods of operation: (basis: BACT, Regulation 8-11-302)

Basecoater Pin Ovens (Sources 2 and 8)

Printer Pin Ovens (Sources 4 and 10)

Inside Bake Ovens (Sources 6 and 12)

Enclosed Inside Spray Machine Banks (Sources 5 and 11); including the enclosed doubling boxes between spray machines and vacuum elevators

3. The Basecoater Pin Ovens S-2 and S-8, the Printer Pin Ovens S-4 and S-10, and the Inside Bake Ovens S-6 and S-12 shall not be operated unless ducted and vented as designed to the Direct Flame Afterburner A-1. The ducting from each oven shall be equipped with an airflow switch electrically connected to the oven control panel. In the event of a loss of airflow due to mechanical failure, the affected oven shall automatically shut down and all can production at the affected line shall cease. (basis: BACT)

## VI. Permit Conditions

### Condition #391

For Sources: 1 through 12 (Beverage Can Coating Sources)

4. In order to demonstrate adequate VOC **and HAP** collection at the Inside Spray Machine Banks S-5 and S-11 (as described above), monitoring devices shall be installed in the ducting from the inside spray machine banks, the enclosed doubling boxes between spray machines, and the vacuum elevators for each line. A magnahelic gauge or other approved device shall be installed and maintained downstream of each affected exhaust duct to indicate negative pressure at the duct. A minimum vacuum pressure of 0.2 inches of water column (as indicated by the monitoring devices) shall be maintained throughout the system. **The vacuum pressure from each exhaust duct monitoring device shall be recorded on a daily basis.** (basis: BACT)
5. The VOC emission control efficiency of the incinerator shall be maintained at a minimum of 95% whenever the inlet concentration of VOC to the incinerator is equal to or greater than 500 ppm, measured as methane. ~~National Can~~ **The permit holder** shall be charged for all uncontrolled emissions during periods of afterburner failure towards compliance with ~~Condition Part~~ #1 above. (basis: BACT)
6. A minimum incinerator temperature of 1450 °F shall be maintained at all times when the incinerator is required to be in operation as specified in ~~Condition Part~~ #5. (basis: BACT)
7. In order to insure that a minimum average incinerator temperature of 1450 °F is maintained, the incinerator shall be equipped with continuous temperature measuring and recording instrumentation, consisting of at least three thermocouple temperature probes in the incinerator and at least one recording device, which will continuously record the incinerator temperature as measured by each of the three thermocouples. (basis: BACT, Regulation 8-11-504)
8. The temperature limit in part 6 shall not apply during an “Allowable Temperature Excursion”, provided that the temperature controller setpoint complies with the temperature limit. An Allowable Temperature Excursion is one of the following:
  - a. A temperature excursion not exceeding 20 degrees F; or
  - b. A temperature excursion for a period or periods which when combined are less than or equal to 15 minutes in any hour; or

## VI. Permit Conditions

- c. A temperature excursion for a period or periods which when combined are more than 15 minutes in any hour, provided that all three of the following criteria are met.
  - i. the excursion does not exceed 50 degrees F;
  - ii. the duration of the excursion does not exceed 24 hours; and
  - iii. the total number of such excursions does not exceed 12 per calendar year (or any consecutive 12 month period).

Two or more excursions greater than 15 minutes in duration occurring during the same 24-hour period shall be counted as one excursion toward the 12 excursion limit. (basis: Regulation 2-1-403)

- 9. For each Allowable Temperature Excursion that exceeds 20 degrees F. and 15 minutes in duration, the Permit Holder shall keep sufficient records to demonstrate that they meet the qualifying criteria described above. Records shall be retained for a minimum of five years from the date of entry, and shall be made available to the District upon request. Records shall include at least the following information:
  - a. Temperature controller setpoint;
  - b. Starting date and time, and duration of each Allowable Temperature Excursion;
  - c. Measured temperature during each Allowable Temperature Excursion;
  - d. Number of Allowable Temperature Excursions per month, and total number for the current calendar year; and
  - e. All strip charts or other temperature records.(basis: Regulation 2-1-403)
- 10. For the purposes of parts 8 and 9, a temperature excursion refers only to temperatures below the limit.
- 11. The temperature data collected from this instrumentation shall be maintained in a file which shall be available for District inspection for a period of at least 60 months following the date on which such data or reports are recorded or made. (basis: BACT, Regulation 2-6-501)

### ~~RECORDKEEPING AND REPORTING~~

~~12a. The following data shall be maintained on a daily basis: (basis: Cumulative Increase, Regulation 2-6-501)~~

## VI. Permit Conditions

- ~~— Operating time of Coating Lines 1 and 2~~
- ~~— Can production for each line (cans/day)~~
- ~~— Amount and type of coating used for Basecoat,~~
- ~~— Inside Spray and overvarnish.~~
- ~~— A recorded value from each exhaust duct vacuum monitoring device.~~
  
- b. ~~The following data shall be maintained on a weekly basis: (basis: Cumulative Increase)~~
  - ~~— Amount of clean-up solvent used,~~
  - ~~— Amount of Bottom Rim Varnish.~~
  
- e. ~~These records shall be available for District inspection for a period of at least 60 months following the date which such data or reports are recorded.~~

**12. In order to demonstrate compliance with the above requirements, the permit holder shall keep the following records in a District approved log:**

- a. **A complete list of all coatings and organic solvents used at Coating Lines 1 and 2. This list shall include the overall VOC content and the volume fraction of each organic HAP constituent for each coating used.**
- b. **Daily records of the total amount of each coating and each organic solvent used. From this, the total mass of VOC used shall be derived.**
- c. **Daily records of the total mass of VOC assumed to be captured and sent to the A-1 Afterburner.**
- d. **Daily totals of VOC emissions (after abatement) from Coating Lines 1 and 2, summarized on a monthly basis.**
- e. **The total mass of each organic HAP present in the coatings and solvents used on a monthly basis.**
- f. **Monthly records of the total amount of each organic HAP assumed to be captured and sent to the A-1 Afterburner.**
- g. **Monthly totals of the calculated abated emissions for each organic HAP present.**

**These records shall be kept on site and made available for inspection by District personnel upon request for at least 60 months from the date on which a record was made. (basis: Cumulative Increase, Regulation 2-1-403)**

**Condition #16547**

For Sources 5 and 11, Inside Spray Machines, Line 1 & Line 2



## VI. Permit Conditions

1. All particulate matter emissions from these sources shall be routed to A2, Pulse Jet Baghouse. (basis: Regulation 2-1-403)
2. The baghouse shall be inspected quarterly to ensure proper operation. The following items shall be checked: (basis: Regulation 2-1-403)
  - a. The baghouse exhaust shall be checked for evidence of particulate breakthrough. If breakthrough is evident from dust buildup in the duct, the filter bags shall be checked for any tears, holes, abrasions, and scuffs, and replaced as needed.
  - b. All hoppers shall be discharged in a timely manner.
  - c. The pulsejet cleaning system shall be maintained and operated in accordance with the manufacturer's recommendations.
3. In order to demonstrate compliance with the above permit conditions, the following records shall be maintained in a District approved log. These records shall be kept on site and made available for District inspection for a period of at least five years from the date on which a record is made. (basis: Regulation 2-6-501)
  - a. Records of all inspections and all maintenance work including bag replacement for the baghouse. Records of each inspection shall consist of a log containing the date of inspection and the initials of the personnel that inspects the baghouse.

### **Condition #16548**

For Source 17, Lime Silo

1. Particulate matter emissions during loading operations from Source 17, Lime Silo, shall be controlled by A8, Lime Silo Baghouse. (basis: Regulation 2-1-403)
2. A8, Lime Silo Baghouse, shall be checked for visible emissions on an annual basis. The visible emissions check shall take place while the equipment is operating and during daylight hours. If any visible emissions are detected, the operator shall take corrective action, and check for visible emissions during the next loading event. If no visible emissions are detected, the operator shall continue to check for visible emissions every year. (basis: Regulation 2-6-501)
3. The operator shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed on A-8, Lime Silo

Plant Name: Rexam Beverage Can

Permit for Site #: A1665

~~Expiration Date: July 28, 2004~~

~~ID: RTH~~

## VI. Permit Conditions

Baghouse. The records shall be retained for five (5) years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

## VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, ~~either~~ **using the following codes:** annual (A), quarterly (Q), monthly (M), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

**This section is only a summary of the limits and monitoring requirements. In the case of a conflict with any requirement in Sections I-VI, the preceding sections take precedence over Section VII.**

**Table VII-A  
 Applicable Limits and Compliance Monitoring Requirements  
 S-1, S-7: Roller Coaters, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>VOC</del>	<del>BAAQMD 8-11-301.3</del>	<del>Y</del>		<del>Two Piece Can Basecoat: 250 g/l (2.1 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-504</del>	<del>P/D</del>	<del>Coating-records</del>
	BAAQMD 8-11-302 (alternative to 8-11-301.3)	Y		Abatement Device efficiency $\geq 90\%$	BAAQMD 8-11-504	C	Temperature of incineration unit

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-A  
Applicable Limits and Compliance Monitoring Requirements  
S-1, S-7: Roller Coaters, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	<del>BAAQMD-8-11-305.1 (optional)</del>	<del>Y</del>		<del>Daily-weighted-average-VOC-emissions-from-all-coatings-equivalent-to-VOC-limits-specified-by-8-11-301</del>	<del>BAAQMD-8-11-305.3-8-11-503.1</del>	<del>P/A-P/E</del>	<del>Alternative-Emission-Control-Plan-submittal-Excess-emissions-reporting</del>
VOC	NSPS Subpart WW, 60.492 (a)	Y		Exterior Base Coat: 0.29 kilogram of VOC per liter (2.42 lb/gal) of coating solids	NSPS Subpart WW, 60.493 (b)	P/M	Coating records, Initial performance test, Monthly operating parameters
	Condition #391, part 1	Y		39.2 tons/yr, facility limit	Condition #391, part <del>9(a)</del> 12	P/D	<del>Operating-time,- Can-production-rate,- Amount of coating-used</del> Daily calculation of VOC emissions from Coating Lines 1 and 2

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-A**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-1, S-7: Roller Coaters, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<b>HAP</b>	<b>Condition #391, part 1</b>	<b>Y</b>		<b>&lt;10 tons/yr, single HAP and &lt;25 tons/yr, any combination of HAPs</b>	<b>Condition #391, part 12</b>	<b>P/M</b>	<b>Monthly calculation of HAP emissions from Coating Lines 1 and 2</b>

**Table VII-B**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-2, S-8: Coater Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>VOC</del>	<del>BAAQMD-8-11-301.3</del>	<del>Y</del>		<del>Two-Piece Can-Basecoat: 250 g/l (2.1 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating-records</del>
<b>VOC</b>	BAAQMD 8-11-302 (alternative to 8-11-301.3)	Y		Abatement Device efficiency $\geq 90\%$	BAAQMD 8-11-504	C	Temperature of incineration unit

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-B**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-2, S-8: Coater Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	NSPS Subpart WW, 60.492 (a)	Y		Exterior Base Coat: 0.29 kilogram of VOC per liter (2.42 lb/gal) of coating solids	NSPS Subpart WW, 60.493 (b)	P/M	Coating records, Initial performance test, Monthly operating parameters
	Condition #391, part 1	Y		39.2 tons/yr, facility limit	Condition #391, part <del>9(a)</del> 12	P/D	<del>Operating time, Can production rate, Amount of coating used</del> Daily calculation of VOC emissions from Coating Lines 1 and 2
	Condition #391, part 5	Y		Abatement Device efficiency $\geq 95\%$	Condition #391, part 7	C	Temperature of incineration unit
	Condition #391, part 6	Y		Minimum Incinerator Temperature of 1450 degrees F	Condition #391, part 7	C	Temperature of incineration unit

**VII. Applicable Limits & Compliance Monitoring Requirements**

**Table VII-B  
Applicable Limits and Compliance Monitoring Requirements  
S-2, S-8: Coater Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<b>HAP</b>	<b>Condition #391, part 1</b>	<b>Y</b>		<b>&lt;10 tons/yr, single HAP and &lt;25 tons/yr, any combination of HAPs</b>	<b>Condition #391, part 12</b>	<b>P/M</b>	<b>Monthly calculation of HAP emissions from Coating Lines 1 and 2</b>
<b>Periods of Inoperation for Parametric Monitors</b>	<b>BAAQMD 1-523.2</b>	<b>Y</b>		<b>15 consecutive days/incident and 30 calendar days/12 month period</b>	<b>BAAQMD 1-523.4</b>	<b>P/D</b>	<b>Operating Records for All Parametric Monitors</b>

**Table VII-C  
Applicable Limits and Compliance Monitoring Requirements  
S-3, S-9: Printers, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>VOC</del>	<del>BAAQMD 8-11-301.3</del>	<del>Y</del>		<del>Overvarnish: 250 g/l (2.1 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
	<del>BAAQMD 8-11-301.10</del>	<del>N</del>		<del>Inks: 300 g/l (2.5 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-C**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-3, S-9: Printers, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 8-11-302 (alternative to 8-11-301.3, 301.10)	Y		Abatement Device efficiency $\geq 90\%$	BAAQMD 8-11-504	C	Temperature of incineration unit
	<del>BAAQMD 8-11-305.1 (optional)</del>	<del>Y</del>		<del>Daily weighted average VOC emissions from all coatings equivalent to VOC limits specified by 8-11-301</del>	<del>BAAQMD 8-11-305.3—8-11-503.1</del>	<del>P/A—P/E</del>	<del>Alternative Emission Control Plan submittal—Excess emissions reporting</del>
	<del>SIP 8-11-301.9</del>	<del>Y</del>		<del>Inks: 300 g/l (2.5 lb/gal) of coating applied, excluding water</del>	<del>SIP 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
VOC	NSPS Subpart WW, 60.492 (b)	Y		Overvarnish: 0.46 kilogram of VOC per liter (3.84 lb/gal) of coating solids	NSPS Subpart WW, 60.493 (b)	P/M	Coating records, Initial performance test, Monthly operating parameters



## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-C**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-3, S-9: Printers, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	Condition #391, part 1	Y		39.2 tons/yr, facility limit	Condition #391, part <del>9(a)</del> 12	P/D	<del>Operating time, Can production rate, Amount of coating used</del> Daily calculation of VOC emissions from Coating Lines 1 and 2
<b>HAP</b>	<b>Condition #391, part 1</b>	<b>Y</b>		<b>&lt;10 tons/yr, single HAP and &lt;25 tons/yr, any combination of HAPs</b>	<b>Condition #391, part 12</b>	<b>P/M</b>	<b>Monthly calculation of HAP emissions from Coating Lines 1 and 2</b>
<b>Periods of Inoperation for Parametric Monitors</b>	<b>BAAQMD 1-523.2</b>	<b>Y</b>		<b>15 consecutive days/incident and 30 calendar days/12 month period</b>	<b>BAAQMD 1-523.4</b>	<b>P/D</b>	<b>Operating Records for All Parametric Monitors</b>

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-D**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-4, S-10: Printer Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>VOC</del>	<del>BAAQMD 8-11-301.3</del>	<del>Y</del>		<del>Overvarnish: 250 g/l (2.1 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
	<del>BAAQMD 8-11- 301.10</del>	<del>N</del>		<del>Inks: 300 g/l (2.5 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
VOC	BAAQMD 8-11-302 (alternative to 8-11- 301.3, 301.10)	Y		Abatement Device efficiency $\geq 90\%$	BAAQMD 8-11-504	C	Temperature of incineration unit
	<del>SIP 8-11-301.9</del>	<del>Y</del>		<del>Inks: 300 g/l (2.5 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
	NSPS Subpart WW, 60.492 (b)	Y		Overvarnish / Clear Basecoat: 0.46 kilogram of VOC per liter (3.84 lb/gal) of coating solids	NSPS Subpart WW, 60.493 (b)	P/M	Coating records, Initial performance test, Monthly operating parameters

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-D**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-4, S-10: Printer Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	Condition #391, part 1	Y		39.2 tons/yr, facility limit	Condition #391, part <del>9(a)</del> <b>12</b>	P/D	<del>Operating time, Can production rate, Amount of coating used</del> <b>Daily calculation of VOC emissions from Coating Lines 1 and 2</b>
VOC	Condition #391, part 5	Y		Abatement Device efficiency $\geq 95\%$	Condition #391, part 7	C	Temperature of incineration unit
	Condition #391, part 6	Y		Minimum Incinerator Temperature of 1450 degrees F	Condition #391, part 7	C	Temperature of incineration unit
<b>HAP</b>	<b>Condition #391, part 1</b>	<b>Y</b>		<b>&lt;10 tons/yr, single HAP and &lt;25 tons/yr, any combination of HAPs</b>	<b>Condition #391, part 12</b>	<b>P/M</b>	<b>Monthly calculation of HAP emissions from Coating Lines 1 and 2</b>
<b>Periods of Inoperation for Parametric Monitors</b>	<b>BAAQMD 1-523.2</b>	<b>Y</b>		<b>15 consecutive days/incident and 30 calendar days/12 month period</b>	<b>BAAQMD 1-523.4</b>	<b>P/D</b>	<b>Operating Records for All Parametric Monitors</b>

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-E**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-5, S-11: Inside Spray Machines, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>VOC</del>	<del>BAAQMD 8-11-301.4.1</del>	<del>N</del>		<del>Interior Body Spray: 420 g/l (3.5 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
	BAAQMD 8-11-302 (alternative to 8-11-301.4)	Y		Abatement Device efficiency $\geq 90\%$	BAAQMD 8-11-504	C	Temperature of incineration unit
	<del>BAAQMD 8-11-305.1 (optional)</del>	<del>Y</del>		<del>Daily weighted-average VOC emissions from all coatings equivalent to VOC limits specified by 8-11-301</del>	<del>BAAQMD 8-11-305.3-8-11-503.1</del>	<del>P/A-P/E</del>	<del>Alternative Emission Control Plan submittal- Excess-emissions-reporting</del>
	<del>SIP 8-11-301.4</del>	<del>Y</del>		<del>Interior Body Spray: 510 g/l (4.2 lb/gal) of coating applied, excluding water</del>	<del>SIP 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
	NSPS Subpart WW, 60.492(c)	Y		Inside Spray: 0.89 kilogram of VOC per liter (7.43 lb/gal) of coating solids	NSPS Subpart WW, 60.493 (b)	P/M	Coating records, Initial performance test, Monthly operating parameters

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-E**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-5, S-11: Inside Spray Machines, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	Condition #391, part 1	Y		39.2 tons/yr, facility limit	Condition #391, part <del>9(a)</del> <b>12</b>	P/D	<del>Operating time, Can production rate, Amount of coating used</del> <b>Daily calculation of VOC emissions from Coating Lines 1 and 2</b>
	<b>Condition #391, part 4</b>	<b>Y</b>		<b>Minimum Vacuum Pressure, 0.2 inches of water column (gauge)</b>	<b>Condition #391, part 4</b>	<b>P/D</b>	<b>Ventilation System negative pressure monitoring</b>
	Condition #391, part 5	Y		Abatement Device efficiency $\geq 95\%$	Condition #391, part 4	P/D	Ventilation System negative pressure monitoring
	Condition #391, part 5	Y		Abatement Device efficiency $\geq 95\%$	Condition #391, part 7	C	Temperature of incineration unit
	Condition #391, part 6	Y		Minimum Incinerator Temperature of 1450 degrees F	Condition #391, part 7	C	Temperature of incineration unit
<b>HAP</b>	<b>Condition #391, part 1</b>	<b>Y</b>		<b>&lt;10 tons/yr, single HAP and &lt;25 tons/yr, any combination of HAPs</b>	<b>Condition #391, part 12</b>	<b>P/M</b>	<b>Monthly calculation of HAP emissions from Coating Lines 1 and 2</b>

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-E**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-5, S-11: Inside Spray Machines, Line 1 & Line 2**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>TSP</del> <b>Opacity</b>	Regulation 6-301	Y		Ringelmann 1.0		N	
	Regulation 6-310	Y		0.15 gr/dscf	Condition #16547, part 2	P/Q	Baghouse Inspection
<b>Periods of Inoperation for Parametric Monitors</b>	<b>BAAQMD 1-523.2</b>	<b>Y</b>		<b>15 consecutive days/incident and 30 calendar days/12 month period</b>	<b>BAAQMD 1-523.4</b>	<b>P/D</b>	<b>Operating Records for All Parametric Monitors</b>

**Table VII-F**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-6, S-12: Bake Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>VOC</del>	<del>BAAQMD 8-11-301.4.1</del>	<del>N</del>		<del>Interior Body Spray: 420 g/l (3.5 lb/gal) of coating applied, excluding water</del>	<del>BAAQMD 8-11-501</del>	<del>P/D</del>	<del>Coating records</del>
	BAAQMD 8-11-302 (alternative to 8-11-301.4)	Y		Abatement Device efficiency $\geq 90\%$	BAAQMD 8-11-504	C	Temperature of incineration unit

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-F**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-6, S-12: Bake Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	<del>SIP 8-11-301.4</del>	<del>Y</del>		<del>Interior Body Spray: 510 g/l (4.2 lb/gal) of coating applied, excluding water</del>			
	NSPS Subpart WW, 60.492 (c)	Y		Inside Spray Coat: 0.89 kilogram of VOC per liter (7.43 lb/gal) of coating solids	NSPS Subpart WW, 60.493 (b)	P/M	Coating records, Initial performance test, Monthly operating parameters
	Condition #391, part 1	Y		39.2 tons/yr, facility limit	Condition #391, part <del>9(a)</del> 12	P/D	<del>Operating time, Can production rate, Amount of coating used</del> Daily calculation of VOC emissions from Coating Lines 1 and 2
	Condition #391, part 5	Y		Abatement Device efficiency $\geq 95\%$	Condition #391, part 7	C	Temperature of incineration unit
VOC	Condition #391, part 6	Y		Minimum Incinerator Temperature of 1450 degrees F	Condition #391, part 7	C	Temperature of incineration unit

## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-F  
Applicable Limits and Compliance Monitoring Requirements  
S-6, S-12: Bake Ovens**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
HAP	Condition #391, part 1	Y		<10 tons/yr, single HAP and <25 tons/yr, any combination of HAPs	Condition #391, part 12	P/M	Monthly calculation of HAP emissions from Coating Lines 1 and 2
Periods of Inoperation for Parametric Monitors	BAAQMD 1-523.2	Y		15 consecutive days/incident and 30 calendar days/12 month period	BAAQMD 1-523.4	P/D	Operating Records for All Parametric Monitors

**Table VII-G  
Applicable Limits and Compliance Monitoring Requirements  
S-16, Scrap Collection System**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>TSP</del> Opacity	Regulation 6-301	Y		Ringelmann 1.0		N	
	Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		2.7 lb/hr (throughput = 1,000 lb/hr)		N	



## VII. Applicable Limits & Compliance Monitoring Requirements

**Table VII-GH**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-17, Lime Silo**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<del>TSPO</del> <b>acity</b>	Regulation 6-301	Y		Ringelmann 1.0	Condition #16548, part 2, 3	P/A	Visible Emissions Checks, Records for S-17
	Regulation 6-310	Y		0.15 gr/dscf		N	
<b>FP</b>	<b>BAAQMD Regulation 6-311</b>	<b>Y</b>		<b>16.6 lb/hr (throughput = 16,000 lb/hr)</b>		<b>N</b>	

## VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally found in Section 600 **et seq.** of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII - Applicable Emission Limits & Compliance Monitoring Requirements.

**Table VIII  
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulate; <b>or USEPA Method 5, Determination of Particulate Matter Emissions from Stationary Sources</b>
<b>BAAQMD 6-311</b>	<b>Process Weight Rate Based Emissions Limits</b>	<b>Manual of Procedures, Volume IV, ST-15, Particulates Sampling, or Calculate Emissions in Accordance with EPA AP-42 Procedures</b>
<del>BAAQMD 8-11-301.3</del>	<del>Basecoat / Overvarnish VOC Limit</del>	<del>Manual of Procedures, Volume III, Method 21, Determination of Compliance of Volatile Organic Compounds for Water Reducible Coatings or Method 22, Determination of Compliance of Volatile Organic Compounds for Solvent Based Coatings, Inks and Other Related Products</del>
<del>BAAQMD 8-11-301.4</del>	<del>Interior Body Spray VOC Limit</del>	<del>Manual of Procedures, Volume III, Method 21, Determination of Compliance of Volatile Organic Compounds for Water Reducible Coatings or Method 22, Determination of Compliance of Volatile Organic Compounds for Solvent Based Coatings, Inks and Other Related Products</del>
<del>BAAQMD 8-11-301.9</del>	<del>Ink VOC Limit</del>	<del>Manual of Procedures, Volume III, Method 21, Determination of Compliance of Volatile Organic Compounds for Water Reducible Coatings or Method 22, Determination of Compliance of Volatile Organic Compounds for Solvent Based Coatings, Inks and Other Related Products</del>
BAAQMD 8-11-302	Emission Control Device Limitation	Manual of Procedures, Volume IV, ST-7, "Organic Compounds" <b>or</b> EPA Method 25 "Determination of Total Gaseous Nonmethane Organic Emissions as Carbon" or 25A "Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer"

**VIII. Test Methods (continued)**

**Table VIII  
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
<del>SIP 8-11-301.4</del>	<del>Interior Body Spray VOC Limit</del>	<del>Manual of Procedures, Volume III, Method 21, Determination of Compliance of Volatile Organic Compounds for Water Reducible Coatings or Method 22, Determination of Compliance of Volatile Organic Compounds for Solvent Based Coatings, Inks and Other Related Products</del>
<del>SIP 8-11-301.9</del>	<del>Ink VOC Limit</del>	<del>Manual of Procedures, Volume III, Method 21, Determination of Compliance of Volatile Organic Compounds for Water Reducible Coatings or Method 22, Determination of Compliance of Volatile Organic Compounds for Solvent Based Coatings, Inks and Other Related Products</del>
BAAQMD Cond. #391, part 4	Incinerator Abatement Control Efficiency	Manual of Procedures, Volume IV, ST-7, "Organic Compounds" <u>or</u> EPA Method 25 "Determination of Total Gaseous Nonmethane Organic Emissions as Carbon" or 25A "Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer"
NSPS Subpart WW	Standards of Performance for the Beverage Can Surface Coating Industry (8/25/83)	
60.492	Standards for VOCs	EPA Method 24 "Determination of Volatile Matter Content, Water Content, Density, Volume Solids, and Weight Solids of Surface Coatings"; or Approved Equivalent or Alternative Method

## IX. REVISION HISTORY

<b>Initial Permit Issuance (Application #16422):</b>	<b>July 28, 1999</b>	
<b>Administrative Amendment (No Application):</b> Facility name changed from American National Can to Rexam Beverage Can Company:	<b>February 19, 2003</b>	
<b>Title V Renewal (Application #8913):</b>	<b>April 6, 2005</b>	

## **X. GLOSSARY**

**ACT**

**Federal Clean Air Act**

**APCO**

**Air Pollution Control Officer**

**API**

**American Petroleum Institute**

**ARB**

**Air Resources Board**

**BAAQMD**

**Bay Area Air Quality Management District**

**BACT**

**Best Available Control Technology**

**BARCT**

**Best Available Retrofit Control Technology**

**C5**

**An Organic chemical compound with five carbon atoms**

**C6**

**An Organic chemical compound with six carbon atoms**

**CAA**

**The federal Clean Air Act**

**CAAQS**

**California Ambient Air Quality Standards**

**CAPCOA**

**California Air Pollution Control Officers Association**

**CEC**

**California Energy Commission**

**CEQA**

**California Environmental Quality Act**

**CEM**

**A "continuous emission monitor" is a monitoring device that provides a continuous direct measurement of some pollutant (e.g. NO<sub>x</sub> concentration) in an exhaust stream.**

## **X. Glossary**

### **CFR**

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

### **CO**

Carbon Monoxide

### **CO<sub>2</sub>**

Carbon Dioxide

### **Cumulative Increase**

The sum of permitted emissions from each new or modified source since a specified date. Used to determine whether threshold-based requirements are triggered.

### **District**

The Bay Area Air Quality Management District

### **dscf**

Dry Standard Cubic Feet

### **dscm**

Dry Standard Cubic Meter

### **E 6, E 9, E 12**

Very large or very small number values are commonly expressed in a form called scientific notation, which consists of a decimal part multiplied by 10 raised to some power. For example, 4.53 E 6 equals  $(4.53) \times (10^6) = (4.53) \times (10 \times 10 \times 10 \times 10 \times 10 \times 10) = 4,530,000$ . Scientific notation is used to express large or small numbers without writing out long strings of zeros.

### **EGT**

Exhaust Gas Temperature

### **EPA**

The federal Environmental Protection Agency.

### **Excluded**

Not subject to any District Regulations.

## X. Glossary

### **Federally Enforceable, FE**

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPS), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

### **FP**

Filterable Particulate as measured by BAAQMD Method ST-15, Particulate.

### **FR**

Federal Register

### **GDF**

Gasoline Dispensing Facility

### **GLC**

Ground level concentration.

### **GLM**

Ground Level Monitor

### **grains**

1/7000 of a pound

### **HAP**

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by both 40 CFR Part 63, and District Regulation 2, Rule 5.

### **H<sub>2</sub>S**

Hydrogen Sulfide

### **HHV**

Higher Heating Value. The quantity of heat evolved as determined by a calorimeter where the combustion products are cooled to 60F and all water vapor is condensed to liquid.

### **LHV**

Lower Heating Value. Similar to the higher heating value (see HHV) except that the water produced by the combustion is not condensed but retained as vapor at 60F.

## **X. Glossary**

### **Major Facility**

A facility with potential emissions of regulated air pollutants greater than 100 tons per year, greater than or equal to 10 tons per year of any single hazardous air pollutant, and/or greater than or equal to 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity as determined by the EPA administrator.

### **MFR**

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Act and implemented by District Regulation 2, Rule 6.

### **MOP**

The District's Manual of Procedures.

### **MSDS**

Material Safety Data Sheet

### **MW**

Megawatts

### **NA**

Not Applicable

### **NAAQS**

National Ambient Air Quality Standards

### **NESHAPS**

National Emission Standards for Hazardous Air Pollutants. Contained in 40 CFR Part 61.

### **NMHC**

Non-methane Hydrocarbons

### **NMOC**

Non-methane Organic Compounds (Same as NMHC)

### **NO<sub>x</sub>**

Oxides of nitrogen.

### **NSPS**

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Act, and implemented by both 40 CFR Part 60 and District Regulation 10.



## X. Glossary

### **NSR**

**New Source Review.** A federal program for preconstruction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

### **O2**

The chemical name for naturally-occurring oxygen gas.

### **Offset Requirement**

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any onsite contemporaneous emission reduction credits. Applies to emissions of POC, NO<sub>x</sub>, PM10, and SO<sub>2</sub>.

### **Phase II Acid Rain Facility**

A facility that generates electricity for sale through fossil-fuel combustion and by virtue of certain other characteristics (defined in Regulation 2, Rule 6) is subject to Titles IV and V of the Clean Air Act.

### **POC**

Precursor Organic Compounds

### **PM**

Total Particulate Matter

### **PM10**

Particulate matter with aerodynamic equivalent diameter of less than 10 microns

### **PSD**

**Prevention of Significant Deterioration.** A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

### **SCR**

A "selective catalytic reduction" unit is an abatement device that reduces NO<sub>x</sub> concentrations in the exhaust stream of a combustion device. SCRs utilize a catalyst, which operates at a specific temperature range, and injected ammonia to promote the conversion of NO<sub>x</sub> compounds to nitrogen gas.

## **X. Glossary**

### **SIP**

**State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.**

### **SO<sub>2</sub>**

**Sulfur dioxide**

### **SO<sub>2</sub> Bubble**

**An SO<sub>2</sub> bubble is an overall cap on the SO<sub>2</sub> emissions from a defined group of sources, or from an entire facility. SO<sub>2</sub> bubbles are sometimes used at refineries because combustion sources are typically fired entirely or in part by "refinery fuel gas" (RFG), a waste gas product from refining operations. Thus, total SO<sub>2</sub> emissions may be conveniently quantified by monitoring the total amount of RFG that is consumed, and the concentration of H<sub>2</sub>S and other sulfur compounds in the RFG.**

### **SO<sub>3</sub>**

**Sulfur trioxide**

### **THC**

**Total Hydrocarbons (NMHC + Methane)**

### **therm**

**100,000 British Thermal Unit**

### **Title V**

**Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.**

### **TOC**

**Total Organic Compounds (NMOC + Methane, Same as THC)**

### **TRMP**

**Toxic Risk Management Plan**

### **TSP**

**Total Suspended Particulate**

### **TVP**

**True Vapor Pressure**

### **VOC**

**Volatile Organic Compounds**

## X. Glossary

### Units of Measure:

<b>bhp</b>	=	<b>brake-horsepower</b>
<b>Btu</b>	=	<b>British Thermal Unit</b>
<b>g</b>	=	<b>grams</b>
<b>gal</b>	=	<b>gallon</b>
<b>hp</b>	=	<b>horsepower</b>
<b>hr</b>	=	<b>hour</b>
<b>lb</b>	=	<b>pound</b>
<b>in</b>	=	<b>inches</b>
<b>max</b>	=	<b>maximum</b>
<b>m<sup>2</sup></b>	=	<b>square meter</b>
<b>min</b>	=	<b>minute</b>
<b>MM</b>	=	<b>million</b>
<b>ppmv</b>	=	<b>parts per million, by volume</b>
<b>ppmw</b>	=	<b>parts per million, by weight</b>
<b>psia</b>	=	<b>pounds per square inch, absolute</b>
<b>psig</b>	=	<b>pounds per square inch, gauge</b>
<b>scfm</b>	=	<b>standard cubic feet per minute</b>
<b>yr</b>	=	<b>year</b>

### Symbols:

<b>&lt;</b>	=	<b>less than</b>
<b>&gt;</b>	=	<b>greater than</b>
<b>≤</b>	=	<b>less than or equal to</b>
<b>≥</b>	=	<b>greater than or equal to</b>

Plant Name: Rexam Beverage Can

Permit for Site #: A1665

~~Expiration Date: July 28, 2004~~

~~ID: RTH~~

~~XI. APPLICABLE STATE IMPLEMENTATION PLAN~~