REGULATION 11 HAZARDOUS POLLUTANTS RULE 4 BERYLLIUM ROCKET MOTOR FIRING

INDEX

11-4-100	GENERAL
11-4-101	Description
11-4-200	DEFINITIONS
11-4-201 11-4-202	Beryllium Propellant Rocket Motor Test Site
11-4-300	STANDARDS
11-4-301 11-4-302	Emissions From Test Sites Emissions From Closed Tanks
11-4-400	ADMINISTRATIVE REQUIREMENTS
11-4-401 11-4-402	Notification to APCO of Sampling or Emission Tests Measuring and Sampling
11-4-500	MONITORING AND RECORDS (Not Included)
11-4-600	MANUAL OF PROCEDURES
11-4-600	MANUAL OF PROCEDURES
11-4-601	Test Methods

REGULATION 11 HAZARDOUS POLLUTANTS RULE 4 BERYLLIUM ROCKET MOTOR FIRING

11-4-100 GENERAL

11-4-101 Description: The purpose of this Rule is to control the emission to the atmosphere of beryllium from rocket motor firing.

11-4-200 DEFINITIONS

- **11-4-201 Beryllium Propellant:** Any propellant incorporating beryllium which undergoes combustion to provide rocket propulsion.
- **11-4-202 Rocket Motor Test Site:** Any plant or installation where static test firing of a beryllium rocket motor and/or the disposal of beryllium propellant is conducted.

11-4-300 STANDARDS

- 11-4-301 Emissions From Test Sites: A person shall not emit combustion products from rocket motor test sites which cause time weighted atmospheric concentrations of beryllium to exceed 75 microgram minutes per m³ of air within the limits of 10 to 60 minutes, accumulated during any 2 consecutive weeks, in any area in which an effect adverse to public health could occur.
- **11-4-302** Emissions From Closed Tanks: A person shall not emit beryllium propellant combustion products from a closed tank in excess of 2 g per hour and maximum of 10 g per day.

11-4-400 ADMINISTRATIVE REQUIREMENTS

- 11-4-401 Notification to APCO of Sampling or Emission Tests: The APCO shall be notified at least 30 days prior to an air sampling test or emission test required by Sections 11-4-301 and 11-4-302 in order to have the option to conduct or observe the test.
- **11-4-402 Measuring and Sampling:** A person responsible for the firing of a beryllium rocket motor subject to Section 11-4-301 shall measure ambient air concentrations during and after firing and shall continuously sample combustion product from a tank subject to Section 11-4-302 so that compliance with standards can be determined.

11-4-600 MANUAL OF PROCEDURES

11-4-601 Test Methods: Test methods and procedures for air sampling test and emission tests required in Section 11-4-402 are specified in the Manual of Procedures, Volume VI, Section 4. (Amended March 17, 1982)