

# ASSESSMENT OF BANDS FOR WIND PROFILER ACCOMMODATION

(216-225, 400.15-406, and  
420-450 MHz Bands)

GARY PATRICK  
MICHAEL RICHMOND



U.S. DEPARTMENT OF COMMERCE  
Robert A. Mosbacher, Secretary

Janice Obuchowski, Assistant Secretary  
for Communications and Information

SEPTEMBER 1991



## **ABSTRACT**

This report presents an assessment of three candidate bands (216-225, 400.15-406, and 420-450 MHz) for the potential accommodation of Wind Profilers nationally, with consideration worldwide. The approach used to evaluate each band was based on two major factors: conformance to current regulations and electromagnetic compatibility (EMC). This report addresses current regulations, spectrum usage, and analyzes the EMC between two types of Wind Profilers and specific environmental systems for potential accommodation in three candidate bands. The results of this study can serve to indicate a suitable band and identify potential frequencies within that band to accommodate Wind Profiler operations.

## **KEY WORDS**

216-225 MHz Band  
400.15-406 MHz Band  
420-450 MHz Band  
Wind Profiler Radars  
Electromagnetic Compatibility (EMC) Analysis



## TABLE OF CONTENTS

Subsection	Page
SECTION 1 INTRODUCTION	
BACKGROUND .....	1-1
OBJECTIVE .....	1-2
APPROACH .....	1-2
SECTION 2 CONCLUSIONS AND RECOMMENDATIONS	
DISCUSSION OF RESULTS .....	2-1
216-225 MHz Band .....	2-1
400.15-406 MHz Band .....	2-2
420-450 MHz Band .....	2-3
Summary .....	2-4
CONCLUSIONS .....	2-5
General .....	2-5
Specific Conclusions for each band .....	2-6
RECOMMENDATIONS .....	2-6
SECTION 3 WIND PROFILER SYSTEM	
INTRODUCTION .....	3-1
WIND PROFILER OPERATIONS .....	3-1
WIND PROFILER DEPLOYMENT .....	3-4
WIND PROFILER CHARACTERISTICS .....	3-6
WIND PROFILER DESIGN .....	3-14
SUMMARY .....	3-15

**TABLE OF CONTENTS**  
(continued)

Subsection	Page
SECTION 4	
CONFORMANCE TO RADIO REGULATIONS	

INTRODUCTION .....	4-1
UNITED STATES - CANADA COORDINATION AGREEMENT .....	4-1
FREQUENCY ALLOCATIONS .....	4-1
216-225 MHz Band .....	4-2
400.15-406 MHz Band .....	4-4
420-450 MHz Band .....	4-4
SUMMARY .....	4-7
TECHNICAL STANDARDS .....	4-8
GOVERNMENT TECHNICAL STANDARDS .....	4-8
Radar Spectrum Engineering Criteria .....	4-8
WIND PROFILER CONFORMANCE TO GOVERNMENT TECHNICAL STANDARDS .....	4-8
WIND PROFILER CONFORMANCE TO NON-GOVERNMENT TECHNICAL STANDARDS .....	4-9

SECTION 5  
SPECTRUM USAGE

INTRODUCTION .....	5-1
BAND I: 216-225 MHz .....	5-1
General .....	5-1
216-220 MHz Band .....	5-1
Government Usage .....	5-2
Non-Government Usage .....	5-5
220-225 MHz Band .....	5-5
Government Usage .....	5-5
Non-Government Usage .....	5-7
BAND II: 400.15-406 MHz .....	5-8
General .....	5-8
400.15-401 MHz Band .....	5-8
401-402 MHz Band .....	5-9
402-403 MHz Band .....	5-10
403-406 MHz Band .....	5-10

# TABLE OF CONTENTS

(continued)

Subsection		Page
	SECTION 5	
	(Continued)	
BAND III: 420-450 MHz	.....	5-12
General	.....	5-12
Government Usage	.....	5-17
Non-Government Usage	.....	5-18

## SECTION 6 ELECTROMAGNETIC COMPATIBILITY

INTRODUCTION	.....	6-1
BAND I: 216-225 MHz	.....	6-2
216-220 MHz Band	.....	6-2
GOVERNMENT SYSTEMS	.....	6-2
Government Telemetry	.....	6-2
Government Land Mobile	.....	6-4
Navy SPASUR	.....	6-4
NON-GOVERNMENT SYSTEMS	.....	6-4
Non-Government Telemetry	.....	6-4
Non-Government Land Mobile and Maritime Mobile	.....	6-4
220-225 MHz Band	.....	6-4
GOVERNMENT SYSTEMS	.....	6-6
Army Fixed AN/GRC-103 Communication System	.....	6-6
NON-GOVERNMENT SYSTEMS	.....	6-6
Amateur Repeater	.....	6-6
EMC SUMMARY OF THE BAND 216-225 MHz	.....	6-6
SUMMARY OF RESULTS FOR THE 216-225 MHz BAND	.....	6-7
BAND II: 400.15-406 MHz	.....	6-7
INTRODUCTION	.....	6-7
Single Case (mainbeam coupling)	.....	6-9
Multiple Case	.....	6-11
Combination of Mainbeam and Sidelobe Wind Profiler Emissions	.....	6-15
Combination of Various Types of Profilers	.....	6-15

## TABLE OF CONTENTS

(continued)

Subsection	Page
	SECTION 6
	(Continued)
EMC SUMMARY OF THE 400.15-406 MHz .....	6-15
BAND III: 420-450 MHz .....	6-16
GOVERNMENT SYSTEMS .....	6-16
Major Radiolocation (Radar) Systems .....	6-16
Land-based Radars .....	6-16
Shipborne Radars .....	6-19
Airborne Radars .....	6-19
Drone Control .....	6-19
NON-GOVERNMENT .....	6-19
Amateur .....	6-20
Land Mobile .....	6-20
EMC SUMMARY OF THE BAND 420-450 MHz .....	6-20
SUMMARY OF RESULTS FOR THE 420-450 MHz BAND .....	6-22

## LIST OF FIGURES

Figure		
3-1	Typical beam configuration for Wind Profilers consists of three beams; one vertical, and two tilted 15 degrees from zenith (to the east and north, for example). Under some circumstances, two additional beams are needed (such as to the south and west). .....	3-3
3-2	Locations of initial 30 Wind Profilers to be deployed for the NOAA demonstration network .....	3-5
3-3	Type A Wind Profiler emission spectra .....	3-10
3-4	Type A Wind Profiler selectivity .....	3-11
3-5	Type B Wind Profiler emission spectra .....	3-12
3-6	Type B Wind Profiler selectivity .....	3-13
5-1	Distribution of GMF assignment with geographical coordinates in the 216-220 MHz band .....	5-3



## TABLE OF CONTENTS

(continued)

### LIST OF FIGURES

(continued)

Figure		Page
5-2	Distribution of GMF assignments with geographical coordinates in the 220-225 MHz band . . . . .	5-4
5-3	Contour map of TV-13 transmitters throughout the U.S. . . . .	5-6
5-4	Distribution of GMF assignments with geographical coordinates in the 420-430 MHz band . . . . .	5-14
5-5	Distribution of GMF assignments with geographical coordinates in the 430-440 MHz band . . . . .	5-15
5-6	Distribution of GMF assignments with geographical coordinates in the 440-450 MHz band . . . . .	5-16
6-1	SARSAT 406 MHz receiver IF selectivity. . . . .	6-8

Table		Page
-------	--	------

### LIST OF TABLES

2-1	Assessment of frequency bands 216-225 MHz, 400.15-406 MHz, and 420-450 MHz in terms of suitable, conditional, and unsuitable for possible Wind Profiler Accommodation . . . . .	2-5
3-1	Some typical properties of profilers operating at common frequencies . . . . .	3-2
3-2	Assumed characteristics for A & B Type Profilers . . . . .	3-9
4-1	Excerpts from the International and National Tables of Frequency Allocations for the Band 216-225 MHz . . . . .	4-3
4-2	Excerpts from the International and National Tables of Frequency Allocations for the Band 400.15-406 MHz . . . . .	4-5
4-3	Excerpts from the International and National Tables of Frequency Allocations for the Band 420-450 MHz . . . . .	4-6
4-4	Suitability . . . . .	4-7
5-1	Agency/Service distribution of frequency assignments in the 216-220 MHz band . . . . .	5-1
5-2	Agency/Service distribution of assignments in the 220-222 MHz band . . . . .	5-2

**TABLE OF CONTENTS**  
(continued)

Table	LIST OF TABLES (Continued)	Page
5-3	Agency/Service distribution of assignments in the 222-225 MHz band . . . . .	5-2
5-4	Agency/Service distribution of assignments in the 400.15-401 MHz band . . . . .	5-9
5-5	Agency/Service distribution of assignments in the 401-402 MHz band . . . . .	5-9
5-6	Agency/Service distribution of assignments in the 402-403 MHz band . . . . .	5-10
5-7	Agency/Service distribution of assignments in the 403-406 MHz band . . . . .	5-10
5-8	Agency/Service distribution of assignments in the 420-430 MHz band . . . . .	5-12
5-9	Agency/Service distribution of assignments in the 430-440 MHz band . . . . .	5-13
5-10	Agency/Service distribution of assignments in the 440-450 MHz band . . . . .	5-13
6-1	Services considered for EMC with Wind Profilers . . . . .	6-2
6-2	Assumed characteristics for systems in the 216-220 MHz Band . . . . .	6-3
6-3	Services considered for EMC with Wind Profilers 220-225 MHz . . . . .	6-5
6-4	Assumed characteristics for systems in the 220-225 MHz Band . . . . .	6-5
6-5	Co-channel distance separations required to preclude interference between Wind Profilers and systems operating in the 216-225 MHz Band . . . . .	6-7
6-6	Assumed system characteristics of COSPAS/SARSAT . . . . .	6-8
6-7	INR values for Type A and B Wind Profilers (mainbeam coupling) . . . . .	6-10
6-8	Calculated OFR values and required frequency separations for Type A and B Profilers (mainbeam Coupling) . . . . .	6-11
6-9	Number of Type A Profilers to be deployed as a function of central angle (excluding mainbeam) . . . . .	6-12
6-10	Number of Type A Profilers to be deployed as a function of central angle (excluding mainbeam) . . . . .	6-12
6-11	INR values for Type A Profilers (sidelobe coupling) . . . . .	6-13

**TABLE OF CONTENTS**  
(continued)

Table	LIST OF TABLES (Continued)	Page
6-12	INR values for Type B Profilers (sidelobe coupling) . . . . .	6-13
6-13	Calculated OFR values and required frequency separations for Type A Profilers (sidelobe coupling) . . . . .	6-14
6-14	Calculated OFR values and required frequency separations for Type B Profilers (sidelobe coupling) . . . . .	6-14
6-15	Services considered for EMC with Wind Profilers . . . . .	6-16
6-16	Assumed characteristics for systems in the 420-450 MHz Band . . . . .	6-17
6-17	Co-channel distance separations required to preclude interference between Wind Profilers and systems operating in the 420-450 MHz Band . . . . .	6-22

LIST OF APPENDICES

Appendix		
A	. . . . .	A-1
B	. . . . .	B-1

	LIST OF REFERENCES . . . . .	R-1
--	------------------------------	-----

