X21A1 SAFETY CHECKLIST					BROOKHAVEN NATIONAL LABORATORY NATIONAL SYNCHROTRON LIGHT SOURCE
Rev: C	Effective: 5/24/2007		Page 1 of 1		Number: LS-SCL-0087
Reviewed by:	Thomas McDonald	Reviewed by	y:		Approved by: J. Aloi

Original signatures on file.

The only official copy of this file is the one on-line in the NSLS Quality Assurance website. Before using a printed copy, verify that it is the most current version by checking the document effective date on the NSLS QA website.

	1. Valid Padlock Index and log, no locks open
	2. Exclusion Zone (EZ # 1) between the front end and the graphite tank in place and secure
	3. Lead wrapped around graphite filter tank as per photo, and view port covered with leade
	glass.
	4. Water cooled Beryllium window #1 and cross piece wrapped in lead.
	5. Exclusion Zone (EZ # 2) in place and secure
	6. Lead shielding covering burst disk.
	7. Lead shielding on Monochromator #1 including leaded glass on view port.
	8. Exclusion Zone (EZ # 3) in place and secure
	9. Bremsstrahlung shield (BS #1) in place and banded, as per photo.
	10. Lead wrapped around front face of Monochromator tank # 2 as per photo, and lead glass
	covering view port secure.
	11. Exclusion Zone (EZ # 4) in place and secure.(note: BS #2 inside EZ #4)
	12. Monochromator #3 view port wrapped in lead and covered with leaded glass.
	13. Exclusion Zone (EZ # 5) in place and secure.
	14. Lead wrapped around 2 view ports secure (top of the mirror tank)
	15. Exclusion Zone (EZ # 6) in place and secure.
	16. View ports(8) on Mirror Tank #2 covered in lead
	17. Exclusion Zone (EZ # 7) in place and secure.
	18. View port covered with leaded glass, in place and secure.
	19. Vacuum Bellows #7 wrapped in lead.
	20. Bremsstrahlung shield (BS #3) in place and banded, as per photo.
	21. Photon Shutter wrapped in lead as per photo
	22. Vacuum Bellows #8 wrapped in lead.
	23. Beam pipe and interlock cables locked in place in the X21A3 hutch
	24. Vacuum Bellows #9 wrapped in lead
	25. Exclusion Zone (EZ #8) in place and secure
	26. Vacuum Bellows # 10 wrapped in lead.
	27. Exclusion Zone (EZ #9) in place and secure.
	28. Bremsstrahlung shield (BS #4) in place and banded, as per photo.
	29. View port covered with leaded glass, in place and secure.
	30. Beamstop in X21A1 hutch in place and secure, as per photo.
(PCO / Beamline Staff: Date:
J	ser System Checks
	A. User interlock indicates all valves open.
	B User interlock indicates all valves open.
	C. User interlock indicates cooling of monochromator running.
_	c. Oser interfock indicates cooming or monocinomator running.
	Reamline Ren: Date: