

Wideband HF Noise/Interference Modeling Part II: Higher-Order Statistics

**John J. Lemmon
Christopher J. Behm**



**U.S. DEPARTMENT OF COMMERCE
Barbara Hackman Franklin, Secretary**

Gregory F. Chapados, Assistant Secretary
for Communications and Information

January 1993

CONTENTS

	Page
LIST OF FIGURES	iv
LIST OF TABLES	viii
ABSTRACT	1
1. INTRODUCTION	1
1.1 Background	1
1.2 Noise/Interference Model	2
1.3 Scope	5
2. AUTOCORRELATION FUNCTIONS	7
2.1 Calculation of the Autocorrelation Function	7
2.2 Comparisons of Model with Measurements	10
3. DISTRIBUTIONS OF ENVELOPE LEVEL CROSSINGS	41
3.1 Pulse Width and Pulse Spacing Distributions	42
3.2 Comparisons of Model With Measurements	81
4. SUMMARY AND CONCLUSIONS	84
5. ACKNOWLEDGMENTS	86
6. REFERENCES	87
APPENDIX	91

LIST OF FIGURES

	Page
Figure 1. I-channel data at 5.936 MHz (case study 1)	13
Figure 2. Normalized autocorrelation function for (a) $0 \leq \tau \leq 4\text{ms}$, (b) $4 \text{ ms} \leq \tau \leq 8\text{ms}$, (c) $0.996 \text{ s} \leq \tau \leq 1.0 \text{ s}$, and (d) $1.0 \text{ s} \leq \tau \leq 1.004 \text{ s}$ (case study 1)	14
Figure 3. Average power of measured noise/interference (case study 1)	15
Figure 4. I-channel data at 19.29 MHz (case study 2)	16
Figure 5. Normalized autocorrelation function for (a) $0 \leq \tau \leq 4\text{ms}$, (b) $4\text{ms} \leq \tau \leq 8\text{ms}$, (c) $0.996 \text{ s} \leq \tau \leq 1.0\text{s}$, and (d) $1.0 \text{ s} \leq \tau \leq 1.004 \text{ s}$ (case study 2)	17
Figure 6. Average power of measured noise/interference (case study 2)	18
Figure 7. I-channel data at 13.666 MHz (case study 3)	19
Figure 8. Normalized autocorrelation function for (a) $0 \leq \tau \leq 4\text{ms}$, (b) $4\text{ms} \leq \tau \leq 8\text{ms}$, (c) $0.996\text{s} \leq \tau \leq 1.0 \text{ s}$, and (d) $1.0 \text{ s} \leq \tau \leq 1.004 \text{ s}$ (case study 3)	20
Figure 9. Average power of measured noise/interference (case study 3)	21
Figure 10. Power spectrum of measured noise/interference on a scale from 0 to 128 kHz (case study 3)	23
Figure 11. I-channel data at 13.666 MHz (case study 4)	25
Figure 12. Normalized autocorrelation function for (a) $0 \leq \tau \leq 4\text{ms}$, (b) $4\text{ms} \leq \tau \leq 8\text{ms}$, (c) $0.996 \text{ s} \leq \tau \leq 1.0\text{s}$, and (d) $1.0\text{s} \leq \tau \leq 1.004 \text{ s}$ (case study 4)	26
Figure 13. Average power of measured noise/interference (case study 4)	27
Figure 14. I-channel data at 23.862 MHz (case study 5)	28
Figure 15. Normalized autocorrelation function for (a) $0 \leq \tau \leq 4\text{ms}$, (b) $4\text{ms} \leq \tau \leq 8\text{ms}$, (c) $0.996 \text{ s} \leq \tau \leq 1.0 \text{ s}$, and (d) $1.0 \text{ s} \leq \tau \leq 1.004 \text{ s}$ (case study 5)	29

List of Figures (cont.)

	Page
Figure 16. Average power of measured noise/interference (case study 5)	30
Figure 17. Normalized autocorrelation function of simulated noise/interference (Gaussian noise and narrowband interferers)	31
Figure 18. Normalized autocorrelation function of simulated noise/interference (Gaussian noise, narrowband interferers, and impulsive noise)	35
Figure 19. Power spectrum of simulated noise/interference over a bandwidth of 1.024 MHz	37
Figure 20. Power spectrum of simulated noise/interference on a scale from 0 to -128 kHz	38
Figure 21. I-channel data of simulated noise/interference	39
Figure 22. Normalized autocorrelation function of simulated noise/interference	40
Figure 23. Voltage envelope of measured noise/interference (case study 1)	43
Figure 24. Pulse width distributions of measured noise/interference at thresholds of (a) 0, (b) 10, (c) 20, (d) 30, (e) 40, (f) 50, (g) 70, and (h) 90 (case study 1)	44
Figure 25. Pulse spacing distributions of measured noise/interference at thresholds of (a) 0, (b) 10, (c) 20, (d) 30, (e) 40, (f) 50, (g) 70, and (h) 90 (case study 1)	46
Figure 26. Voltage envelope of measured noise/interference (case study 2)	48
Figure 27. Pulse width distributions of measured noise/interference at thresholds of (a) 20, (b) 40, (c) 60, (d) 80, (e) 100, (f) 120, (g) 140, and (h) 160 (case study 2)	49
Figure 28. Pulse spacing distributions of measured noise/interference at thresholds of (a) 20, (b) 40, (c) 60, (d) 80, (e) 100, (f) 120, (g) 140, and (h) 160 (case study 2)	51

List of Figures (cont.)

Figure 29.	Voltage envelope of measured noise/interference (case study 3)	53
Figure 30.	Pulse width distributions of measured noise/interference at thresholds of (a) 0, (b) 10, (c) 20, (d) 30, (e) 40, (f) 45 (case study 3)	54
Figure 31.	Pulse spacing distributions of measured noise/interference at thresholds of (a) 0, (b) 10, (c) 20, (d) 30, (e) 40, and (f) 45 (case study 3)	56
Figure 32.	Voltage envelope of measured noise/interference (case study 4)	58
Figure 33.	Pulse width distributions of measured noise/interference at thresholds of (a) 0, (b) 5, (c) 10, (d) 20, (e) 30, and (f) 40 (case study 4)	59
Figure 34.	Pulse spacing distributions of measured noise/interference at thresholds of (a) 0, (b) 5, (c) 10, (d) 20, and (e) 30 (case study 4)	61
Figure 35.	Voltage envelope of measured noise/interference (case study 5)	62
Figure 36.	Pulse width distributions of measured noise/interference at thresholds of (a) 0, (b) 5, (c) 10, (d) 25, and (e) 30 (case study 5)	63
Figure 37.	Pulse spacing distributions of measured noise/interference at thresholds of (a) 0, (b) 5, (c) 10, (d) 20, and (e) 30 (case study 5)	64
Figure 38.	Voltage envelope of measured noise/interference on a scale from 0 to 64 ms (case study 5)	65
Figure 39.	Voltage envelope of simulated noise/interference	66
Figure 40.	Pulse width distributions of simulated noise/interference at thresholds of (a) 0.5 (b) 10, (c) 20, (d) 30, (e) 40, (f) 50, (g) 70, and (h) 80	67
Figure 41.	Pulse spacing distributions of simulated noise/interference at thresholds of (a) 0, (b) 10, (c) 20, (d) 30, (e) 40, (f) 50, (g) 70, and (h) 80	69
Figure 42.	Voltage envelope of simulated noise/interference	71

List of Figures (cont.)

	Page
Figure 43. Pulse width distributions of simulated noise/interference at thresholds of (a) 0.5, (b) 5, (c) 10, (d) 15, (e) 20, (f) 25, (g) 30, and (h) 40	72
Figure 44. Pulse spacing distributions of simulated noise/interference at thresholds of (a) 0, (b) 5, (c) 10, (d) 15, (e) 20, (f) 25, (g) 30, and (h) 40	74
Figure 45. Pulse width distributions of simulated noise/interference at thresholds of (a) 0.5, (b) 5, (c) 10, (d) 15, (e) 20, (f) 25, (g) 30, and (h) 40	76
Figure 46. Pulse spacing distributions of simulated noise/interference at thresholds of (a) 0, (b) 5, (c) 10, (d) 15, (e) 20, (f) 25, (g) 30, and (h) 40	78

LIST OF TABLES

	Page
Table 1. Measurement Characteristics of Wideband HF Noise/Interference Records Used in Case Studies	11
Table 2. Parameters Used in the Simulation Model for Figures 17 and 39-41	33
Table 3. Parameters Used in the Simulation Model for Figures 18 and 42-46	34
Table A-1. Measurement Characteristics of Wideband HF Noise/Interference Records	91