

OCRWM	Design Calculation or Analysis Cover Sheet	1.QA: QA 2.Page: 1
--------------	---	-----------------------

3. System Storm Drainage	4. Document Identifier 000-00C-CD04-00100-000-00A
-----------------------------	--


5. Title
Hydrologic Engineering Studies for the North Portal Pad and Vicinity

6. Group
CIVIL/STRUCTURAL/ARCHITECTURAL

7. Document Status Designation
 Preliminary Final Cancelled

8. Notes/Comments
 This calculation provides additional analyses to supplement the results presented in ANL-EBS-MD-000060 Rev 00.
 A review of this document is not required because it is the initial issue and no other organizations or disciplines are affected.
 Issuance of this document will resolve TBV-5492.
 Alternate calculations used to check the PMF calculations are included in Attachment 26.
 See Page 2 for additional notes.

Attachments	Total Number of Pages
List of attachments provided in Section 10 of this calculation	

9. No.	10. Reason for Revision	11. Total # of Pgs.	12. Last Pg. #	13. Originator (Print/Sign/Date)	14. Checker (Print/Sign/Date)	15. QER (Print/Sign/Date)	16. Approved/Accepted (Print/Sign)	17. Date
00A	Initial issue	356 + 1 CD	26-4	Jeanne Hudson <i>Jeanne Hudson</i> 4/20/04 Matthew Knopp <i>Matthew Knopp</i> 4/22/04 Vivian Lee <i>Vivian Lee</i> 4/20/04 Phillip Mineart <i>Phillip Mineart</i> 4/20/04 See note on page 2, Block 8	Jeanne Hudson <i>Jeanne Hudson</i> 4/20/04 Vivian Lee <i>Vivian Lee</i> 4/20/04 Phillip Mineart <i>Phillip Mineart</i> 4/20/04 Douglas Wright <i>Douglas Wright</i> 04-21-2004 See note on page 2, Block 8	Dan Tunney <i>Daniel Tunney</i> 4/22/2004	<i>Richard Bernisi</i>  4/22/04	

OCRWM	Design Calculation or Analysis Cover Sheet	1.QA: QA 2.Page: 2
--------------	---	-----------------------

3. System Storm Drainage	4. Document Identifier 000-00C-CD04-00100-000-00A
-----------------------------	---

5. Title
Hydrologic Engineering Studies for the North Portal Pad and Vicinity

6. Group
CIVIL/STRUCTURAL/ARCHITECTURAL

7. Document Status Designation
 Preliminary Final Cancelled

8. Notes/Comments
Several authors prepared this calculation. The originators and checkers of the various sections are shown below. For attachments containing computer program output, the originator and checker (other than the originator) of the attachment also performed and checked the computer runs and files. The originator and checker of files in Attachment 1 are listed in Table 10-1. Attachments 3 and 1.22 contain preliminary sketches that support this preliminary calculation.

Section(s)	Originator	Checker
Table of Contents; Acronyms; Abbreviations; Sections 1 through 5	Vivian Lee	Jeanne Hudson
Sections 6.1 and 6.2	Jeanne Hudson	Vivian Lee
Sections 6.3 through 6.5	Vivian Lee	Jeanne Hudson
Section 6.6	Phillip Mineart	Jeanne Hudson
Sections 6.7 and 6.8	Vivian Lee	Jeanne Hudson
Section 6.9	Jeanne Hudson	Vivian Lee
Section 6.10	Vivian Lee	Jeanne Hudson
Sections 6.11 and 6.12	Vivian Lee	Phillip Mineart
Section 7.1 and 7.2	Jeanne Hudson	Vivian Lee
Sections 7.3 through 7.7	Vivian Lee	Jeanne Hudson
Section 7.8	Phillip Mineart	Jeanne Hudson
Sections 7.9 and 7.10	Vivian Lee	Jeanne Hudson
Section 7.11	Jeanne Hudson	Vivian Lee
Sections 7.12 through 7.14	Vivian Lee	Phillip Mineart
Sections 8 through 10	Vivian Lee	Jeanne Hudson
Attachment 1 (see note in Block 8)	Hudson, Knopp, Lee, and Mineart	Hudson, Lee, Mineart, and Wright
Attachment 2	Vivian Lee	N/A
Attachment 3	Jeanne Hudson	N/A
Attachment 4	Phillip Mineart	Jeanne Hudson
Attachment 5	Vivian Lee	Jeanne Hudson
Attachment 6	Jeanne Hudson	Vivian Lee
Attachments 7 through 9	Vivian Lee	Jeanne Hudson
Attachment 10	Phillip Mineart	Jeanne Hudson
Attachments 11 and 12	Vivian Lee	Jeanne Hudson
Attachment 13	Jeanne Hudson	Vivian Lee
Attachment 14	Vivian Lee	Jeanne Hudson
Attachment 15	Vivian Lee	Phillip Mineart
Attachments 16 through 20	Vivian Lee	Jeanne Hudson
Attachment 21	Phillip Mineart	Jeanne Hudson
Attachments 22 and 23	Vivian Lee	Jeanne Hudson
Attachment 24	Jeanne Hudson	Vivian Lee
Attachment 25	Vivian Lee	Phillip Mineart
Attachment 26 (Checker's Alternate Calculations for PMF Analyses discussed in Sections 4 and 5)	Jeanne Hudson	N/A

TABLE OF CONTENTS

ACRONYMS	8
ABBREVIATIONS	9
1 PURPOSE	10
2 QUALITY ASSURANCE	10
3 USE OF COMPUTER SOFTWARE	10
3.1 Probable Maximum Flood Calculation	11
3.2 Flood Inundation Calculation	11
3.3 Topographic Surface Generation	11
3.4 Other Software	12
4 PROBABLE MAXIMUM FLOOD ANALYSIS FOR ALTERNATIVE 1	13
4.1 Method for Alternative 1	13
4.2 Inputs for Alternative 1	13
4.2.1 Layout Design	13
4.2.2 Precipitation.....	13
4.2.3 Topographic Data	13
4.2.4 Sub-Basin Properties.....	14
4.2.5 Channel Properties.....	15
4.2.6 Initial Abstraction and Infiltration Rate.....	15
4.3 Assumptions for Alternative 1	15
4.3.1 Homogeneity of Watershed Properties	15
4.3.2 Overland Flow Elements.....	15
4.3.3 Manmade Channels.....	16
4.4 Results for Alternative 1	17
5 PROBABLE MAXIMUM FLOOD ANALYSIS FOR ALTERNATIVE 2	19
5.1 Method for Alternative 2	19
5.2 Inputs for Alternative 2	19
5.2.1 Layout Design	19
5.2.2 Precipitation.....	19
5.2.3 Topographic Data	19
5.2.4 Sub-Basin Properties.....	19
5.2.5 Channel Properties.....	20
5.2.6 Initial Abstraction and Infiltration Rate.....	20
5.3 Assumptions for Alternative 2	20
5.3.1 Homogeneity of Watershed Properties	21
5.3.2 Overland Flow Elements.....	21
5.3.3 Manmade Channels.....	21
5.4 Results for Alternative 2	22
6 FLOOD INUNDATION ANALYSIS FOR ALTERNATIVE 1	23
6.1 Method, Alternative 1.....	23

6.2	No Mitigation Scenario for the North Portal Pad, Alternative 1	23
6.3	Diversion Around Muck Storage A, Alternative 1	27
6.4	Downstream of Muck Storage A, Alternative 1	30
6.5	Diversion East of Optional Aging Facility and Around North Construction Portal, Alternative 1	32
6.6	Aging Facility and North Portal Pad, Alternative 1	35
6.7	East of North Portal Pad, Alternative 1	39
6.8	Downstream of North Portal Pad, Alternative 1	41
6.9	Railroad Bridge Crossing, Alternative 1	43
6.10	South Portal, Alternative 1	46
6.11	Intake and Exhaust Shafts, Alternative 1	50
6.12	Scour Analysis, Alternative 1	51
7	FLOOD INUNDATION ANALYSIS FOR ALTERNATIVE 2	52
7.1	Method, Alternative 2	52
7.2	No Mitigation Scenario for the North Portal Pad, Alternative 2	52
7.3	Diversion Around Muck Storage A, Alternative 2	53
7.4	Diversion Around Aging Pad 3, Alternative 2	56
7.5	Diversion Around Aging Pad 2, Alternative 2	59
7.6	North Construction Portal, Alternative 2	62
7.7	Diversion North of Aging Facility, Alternative 2	64
7.8	Aging Facility and North Portal Pad, Alternative 2	67
7.9	East of North Portal Pad, Alternative 2	70
7.10	Downstream of North Portal Pad, Alternative 2	72
7.11	Railroad Bridge Crossing, Alternative 2	75
7.12	South Portal Pad, Alternative 2	78
7.13	Intake and Exhaust Shafts, Alternative 2	78
7.14	Scour Analysis, Alternative 2	78
8	CONCLUSIONS AND LIMITATIONS	79
8.1	Conclusions for Flood Inundation Analysis	79
8.2	Limitations	80
9	REFERENCES	82
10	ATTACHMENTS	84

List of Tables

Table 3-1	Software Usage	11
Table 4-1	Properties of Sub-Basins Used in HEC-1 Model, Alternative 1	14
Table 4-2	Properties of Natural Channels Used in HEC-1 Model, Alternative 1	15
Table 4-3	Properties of Overland Flow Elements, Alternative 1	16
Table 4-4	Properties of Manmade Channels Used in HEC-1 Model, Alternative 1	17

Table 4-5	Results of PMF Analysis, Alternative 1.....	18
Table 5-1	Properties of Sub-Basins Used in HEC-1 Model, Alternative 2.....	19
Table 5-2	Properties of Natural Channels Used in HEC-1 Model, Alternative 2.....	20
Table 5-3	Properties of Overland Flow Elements, Alternative 2.....	21
Table 5-4	Properties of Manmade Channels Used in HEC-1 Model, Alternative 2..	22
Table 5-5	Results of PMF Analysis, Alternative 2.....	22
Table 6-1	Flood Inundation Results for No Mitigation Scenario, Alternative 1.....	25
Table 6-2	Flood Inundation Results Around Muck Storage A, Alternative 1.....	29
Table 6-3	Flood Inundation Results Downstream of Muck Storage A, Alternative 1...	31
Table 6-4	Flood Inundation Results East of Optional Aging Facility and Around North Construction Portal, Alternative 1.....	34
Table 6-5	Flood Inundation Results Around Aging Facility and North Portal Pad, Alternative 1.....	37
Table 6-6	Flood Inundation Results Around North Portal Pad with Floodwall/Levee, Alternative 1.....	38
Table 6-7	Flood Inundation Results for Primary Channel East of North Portal Pad, Alternative 1.....	40
Table 6-8	Flood Inundation Results Downstream of North Portal Pad, Alternative 1..	42
Table 6-9	Flood Inundation Results Near Railroad Bridge Crossing, Alternative 1	45
Table 6-10	Boundary Conditions for South Portal Routings, Alternative 1.....	48
Table 6-11	Flood Inundation Results Around South Portal, Alternative 1.....	48
Table 6-12	Yield of Sub-Basins, Alternative 1.....	50
Table 7-1	Flood Inundation Results Around Muck Storage A, Alternative 2.....	55
Table 7-2	Flood Inundation Results Around Aging Pad 3, Alternative 2.....	58
Table 7-3	Flood Inundation Results Around Aging Pad 2, Alternative 2.....	61
Table 7-4	Flood Inundation Results Near North Construction Portal, Alternative 2....	63
Table 7-5	Flood Inundation Results North of Aging Facility, Alternative 2.....	66

Table 7-6	Flood Inundation Results Around Aging Facility and North Portal Pad, Alternative 2.....	69
Table 7-7	Flood Inundation Results for Primary Channel East of North Portal Pad, Alternative 2.....	71
Table 7-8	Flood Inundation Results Downstream of North Portal Pad, Alternative 2	74
Table 7-9	Flood Inundation Results Near Railroad Bridge Crossing, Alternative 2....	77
Table 8-1	Summary of Manmade Channels for Diversion of Flows Away from Critical Facilities, Alternative 1.....	80
Table 8-2	Summary of Manmade Channels for Diversion of Flows Away from Critical Facilities, Alternative 2.....	80
Table 10-1	List of Electronic Files Included in Attachment 1.....	85

List of Figures

Figure 4-1	Delineation of Sub-basins for HEC-1 Model, Alternative 1.....	86
Figure 4-2	Schematic Diagram of Watershed Network, Alternative 1.....	87
Figure 4-3	PMP Hyetograph for the South Portal (3-minute interval).....	88
Figure 5-1	Delineation of Sub-basins for HEC-1 Model, Alternative 2.....	89
Figure 5-2	Schematic Diagram of Watershed Network, Alternative 2.....	90
Figure 6-1	Inundation Surface for No Mitigation Scenario, Alternative 1.....	91
Figure 6-2	Inundation Surface Around Muck Storage A, Alternative 1.....	92
Figure 6-3	Inundation Surface Downstream of Muck Storage A, Alternative 1.....	93
Figure 6-4	Inundation Surface East of Optional Aging Facility and Around North Construction Portal, Alternative 1.....	94
Figure 6-5	Inundation Surface Near Aging Facility and North Portal Pad (Channel Alternative), Alternative 1.....	95
Figure 6-6	Inundation Surface Near Aging Facility and North Portal Pad (Wall Alternative), Alternative 1.....	96
Figure 6-7	Inundation Surface East of North Portal Pad, Alternative 1.....	97
Figure 6-8	Inundation Surface Downstream of North Portal Pad, Alternative 1.....	98
Figure 6-9	Inundation Surface Near Railroad Bridge Crossing, Alternative 1.....	99
Figure 6-10	Inundation Surface Around South Portal, Alternative 1.....	100
Figure 6-11	Intake and Exhaust Portals, Alternative 1.....	101
Figure 7-1	Inundation Surface Around Muck Storage A, Alternative 2.....	102

Figure 7-2	Inundation Surface Around Aging Pad 3, Alternative 2.....	103
Figure 7-3	Inundation Surface Around Aging Pad 2, Alternative 2.....	104
Figure 7-4	Inundation Surface Near North Construction Portal, Alternative 2.....	105
Figure 7-5	Inundation Surface North of Aging Facility, Alternative 2.....	106
Figure 7-6	Inundation Surface Around Aging Facility and North Portal Pad, Alternative 2.....	107
Figure 7-7	Inundation Surface East of North Portal Pad, Alternative 2.....	108
Figure 7-8	Inundation Surface Downstream of North Portal Pad, Alternative 2.....	109
Figure 7-9	Inundation Surface Near Railroad Bridge Crossing, Alternative 2.....	110
Figure 8-1	Combined Inundation Surfaces Near North Portal Pad and Vicinity, Alternative 1.....	111
Figure 8-2	Combined Inundation Surfaces Near North Portal Pad and Vicinity, Alternative 2.....	112

ACRONYMS

COE	U.S. Army Corps of Engineers
CRWMS	Civilian Radioactive Waste Management System
CSCI	Computer Software Configuration Item
DOE	U.S. Department of Energy
DTN	Data Tracking Number
ESF	Exploratory Studies Facility
EIS	Environmental Impact Statement
FEMA	Federal Emergency Management Agency
FHWA	Federal Highway Administration
HEC	Hydrologic Engineering Center
HEC-RAS	Hydrologic Engineering Center, River Analysis System
HMR	Hydrometeorological Report
M&O	Management and Operating Contractor
NOAA	National Oceanic and Atmospheric Administration
NPP	North Portal Pad
NRCS	Natural Resources Conservation Service
PMF	Probable Maximum Flood
PMP	Probable Maximum Precipitation
QARD	Quality Assurance Requirements and Description
SCS	Soil Conservation Service
STN	Software Tracking Number
TDMS	Technical Data Management System
URS	URS Corporation
USBR	U.S. Bureau of Reclamation
USDA	U.S. Department of Agriculture
YMP	Yucca Mountain Site Characterization Project

ABBREVIATIONS

cfs	cubic feet per second
ft	feet
ft ²	square feet
ft/s	feet per second
FY	Fiscal Year
mi	miles

1 PURPOSE

PMF Inundation Studies at North Portal Pad and Vicinity were performed to provide preliminary design information for the proposed surface facilities for the Yucca Mountain Nuclear Repository. Knowledge of the potential for inundation due to large flood events is necessary in designing the surface facilities because of the risk of flood damage to the facilities, as well as the flood transport of radioactive materials away from the facilities. A previous study of PMF inundation (Ref. 6) was conducted for the project. However significant design changes have occurred since that study was completed necessitating the need to update the PMF study. For the current study, the study area was enlarged to encompass the South Portal Pad. Two alternative facility layouts were considered.

The purpose of this calculation is to:

1. Determine the magnitude and duration of runoff that would occur in Midway Valley Wash during a PMF event; and
2. Determine flow characteristics during the PMF, including the maximum lateral extent of inundation, flow depths, and velocities that may impact the surface facilities.
3. Provide mitigation measures to prevent flood waters from inundating critical facilities.

2 QUALITY ASSURANCE

This document was developed in accordance with procedure AP-3.12Q, *Design Calculations and Analysis* (Ref. 1). The North Portal Pad and Vicinity include structures (e.g., the Dry Transfer Facility) identified as safety category on the Q List (Ref. 7, p. A-2). Therefore, this document is subject to the Quality Assurance Requirements and Description (QARD) (Ref. 11). As stated in Section 1, this calculation was prepared to support preliminary design activities. As such, preliminary sketches of the surface facilities around the North Portal Pad (included in Attachment 3) as well as the preliminary design data for intake and exhaust shafts were used for the analyses presented herein since the final design of such facilities has not been developed. Where appropriate, comments were included in the calculation to denote the range of validity of these preliminary calculations should the final design differ from that used for the analysis.

3 USE OF COMPUTER SOFTWARE

Software listed in Table 3-1 is qualified and was obtained from Software Configuration Management. The software was appropriate for the applications described in this report, and the software was used within its range of validation. The computers used to run HEC-1 and HEC-RAS software are located in the URS office in Oakland, California. The serial number of the computer used to run HEC-1 is US832900YK. This computer was one of two computers used to run HEC-RAS. The serial number of the second computer is US00303734. The computer used to run ArcINFO V.7.2.1 is located in the Yucca Mountain Las Vegas Office, Nevada. The BSC property tag number of this computer is 700810.

Table 3-1. Software Usage

Reference	Name	STN/CSCI Identifier	CPU Operating Platform	CPU Operating System
Ref. 4, Ref. 21	HEC-1 Version 4.0	30078-V4.0	PC	DOS Emulation
Ref. 5, Ref. 22	HEC-RAS Version 2.1	30079-V2.1	PC	DOS Emulation
Ref. 10, Ref. 23	ArcINFO V.7.2.1	STN 10033-7.2.1-00	SGI	IRIX 6.5

3.1 PROBABLE MAXIMUM FLOOD CALCULATION

The U.S. Army Corps of Engineers' Hydrologic Engineering Center (HEC) HEC-1 computer software, Version 4.0 (Ref. 18) was used to perform the rainfall-runoff simulations using the Probable Maximum Precipitation (PMP) amounts. This is the same software used in the previous study (Ref. 6). HEC-1 was designed to simulate the surface runoff response of a watershed to precipitation. The program represents the watershed as an interconnected network of hydraulic and hydrologic components. A component may be a sub-area of the watershed, river channel, reservoir, or diversion. Each component is described by its physical characteristics and mathematical relations that describe the pertinent hydrologic and hydraulic processes. In the HEC-1 software, the study area was divided into drainage sub-areas so that PMF hydrographs were calculated at key locations in the study area. The HEC-1 input and output files are included in Attachments 1.02 and 1.03.

3.2 FLOOD INUNDATION CALCULATION

The U.S. Army Corps of Engineers, Hydrologic Engineering Center, River Analysis System software (HEC-RAS), Version 2.1 (Ref. 3), was used for the flood inundation analysis. This program is designed for flood inundation studies and flood risk analysis. This software performs standard backwater computations to predict water surface elevations under steady gradually varied flow conditions. HEC-RAS is one of the FEMA nationally accepted computer software that can be used to estimate flood elevations (Ref. 13). This is the same software used in the previous study (Ref. 6). The HEC-RAS input and output files are included in Attachments 1.04 through 1.21, Attachments 6 through 14, and Attachments 16 through 24.

The computational procedure used in HEC-RAS is based on solution of the one-dimensional energy equation. Energy losses consist of surface roughness and expansion/contraction losses. Energy loss by surface roughness is evaluated using Manning's equation and requires the user to define a roughness coefficient. The momentum equation is used in situations where flow is rapidly varied, such as hydraulic jumps and flow through bridges. A rigid channel boundary is used in the computations (i.e., channel cross section shapes do not change as a result of sediment deposition or scour).

3.3 TOPOGRAPHIC SURFACE GENERATION

The ArcINFO Version 7.2.1 software (Ref. 10) developed by Environmental Systems Research Institute (ESRI) was used for the creation of a topographic surface in the form of a Triangulated Irregular Network (TIN) which was needed for the hydrologic analyses. The output TIN is included in Attachment 1.01. The input files are discussed in Section 4.2.3.

3.4 OTHER SOFTWARE

Microsoft Excel 2000 was used to perform routine calculations presented in all the tables in Sections 4 to 7, as well as in attachments including excavation volume calculations, weir flow calculations, and alternate PMF calculations using the Rational Method. Arcview V.3.2 was used to extract elevation data from a TIN by querying information along user-defined lines. ArcGIS V.8.3 was used to calculate areas of watersheds defined as polygons, lengths of streams defined as lines, and present output from HEC-RAS graphically to show inundation boundaries. The solutions are documented in sufficient detail to allow an independent check to reproduce or verify the results without recourse to the originator. The use of these software as described is exempt according to Sections 2.1.2 and 2.1.6 of LP-SI.11Q-BSC (Ref. 2) (see Attachment 2).

4 PROBABLE MAXIMUM FLOOD ANALYSIS FOR ALTERNATIVE 1

4.1 METHOD FOR ALTERNATIVE 1

A rainfall-runoff simulation was performed using the HEC-1 computer software to determine the surface runoff at pertinent locations in the vicinity of the North Portal and South Portal during a Probable Maximum Flood (PMF) event for Alternative 1. The layout sketches for Alternative 1 are provided in Attachment 3. The study area encompasses Midway Valley Wash, Drillhole Wash, and Split Wash, and is bounded by Yucca Mountain to the west, and Fran Ridge and Alice Hill to the east. The area was divided into 14 sub-basins as presented in Figure 4-1 to provide information on flows near the surface facilities. The sub-basins boundaries were modified from the previous report (Ref. 6) around the North Portal Pad to reflect the changes in layout, while additional sub-basins were delineated to include the South Portal in the hydrologic analysis. Figure 4-2 is a schematic diagram of the watershed network illustrating the routing of flow through the sub-basins. The Probable Maximum Precipitation (PMP) was determined using procedures presented in the National Oceanic and Atmospheric Administration's Hydrometeorological Report No. 49 (HMR 49) (Ref. 14).

4.2 INPUTS FOR ALTERNATIVE 1

4.2.1 Layout Design

The preliminary layout sketches of the surface facilities for Alternative 1 (Attachment 3) including the proposed North Portal Pad, Muck Storage Areas, Aging Facilities, and Railroad Alignment were used to define the extent of the drainage area.

4.2.2 Precipitation

The local storm PMP value at the North Portal Pad was calculated in the previous report (Ref. 6, p. 33) to be 13.2 inches with a duration of 6 hours (herein referred to as PMP-North Portal). This hyetograph was adopted in the present calculation. Since a local thunderstorm system affecting the South Portal can be independent of one that occurs at the North Portal Pad, a separate PMP value was developed for the tributary area of Drillhole Wash and Split Wash following HMR 49 procedures (herein referred to as PMP-South Portal). This will lead to a more conservative estimate of the maximum flows at the North Portal and South Portal because the rainfall intensity is inversely related to the drainage area. With an area of 6.5 square miles, the local 6-hour PMP-South Portal was computed to be 12.9 inches. Figure 4-3 shows the 3-minute interval hyetograph generated for the South Portal sub-basins. The calculations supporting the PMP-South Portal are provided in Attachment 4.

4.2.3 Topographic Data

A composite TIN (Triangulated Irregular Network) comprising two datasets (DTN #s MO0002SPATOP00.001 (Ref. 15) and MO9906COV98462.000 (Ref. 16)) was generated using ArcINFO V.7.2.1 to produce a topographic representation of the project area. The output TIN is included in Attachment 1.01. The dataset MO9906COV98462.000 (Ref. 16) contains 2-foot contour data encompassing the North Portal Pad and vicinity, whereas

the dataset MO0002SPATOP00.001 (Ref. 15) consists of an output gridded (100-foot spacing) surface that covers the entire watershed. The 2 datasets have overlapping information and the goal was to use the best available data for the region analyzed. The 2-foot contours from DTN MO9906COV98462.000 (Ref. 16) were the preferred data as they have the best vertical resolution available. The 2-foot contours were clipped to the extent of the study area. The gridded elevation points from DTN MO0002SPATOP00.001 (Ref. 15) were then clipped to the same extent, and points overlapping the area where 2-foot contours existed were eliminated.

4.2.4 Sub-Basin Properties

The unit hydrograph method was used to develop the runoff hydrograph for each sub-basin. Two parameters are needed to prescribe the unit hydrograph for each natural sub-basin using the Natural Resources Conservation Service (NRCS) Dimensionless Unit Hydrograph (Ref. 18, pp. 23-24): area and lag time. The areas of the sub-basins were obtained from the topographic data (refer to Section 4.2.3) using ArcGIS V.8.3 and are summarized in Table 4-1. The lag time was calculated using the U.S. Bureau of Reclamation (USBR) empirical formula (Ref. 12, pp. 29-38) according to the previous report (Ref. 6, pp. 18-19, 35-37), with the results tabulated in Table 4-1:

$$lag = C \left(\frac{L \cdot L_{ca}}{\sqrt{S}} \right)^{0.33} \quad (\text{hours})$$

where C = 1.1 (Ref. 6, p. 19, 35-37)

L = total channel length (mi)

L_{ca} = length along the flow path from the basin outlet to the point opposite the centroid of the basin area (mi)

S = slope of the channel (ft/mi)

Sub-basins that include constructed surfaces such as FAC1, FAC2, FAC3 and FAC4 (see Figure 4-1 for sub-basins layout) were simulated as overland flow elements and did not require lag time calculation.

Table 4-1. Properties of Sub-Basins Used in HEC-1 Model, Alternative 1

Basin Name	Area (mi ²)	Total channel length (mi)	Length from centroid to outlet (mi)	Slope (ft/mi)	Lag time (hr)
ND1	1.156	3.391	1.306	437.66	0.659
ND2	0.394	1.828	0.861	528.52	0.454
D3	1.149	3.429	1.674	526.68	0.696
ND4	0.816	2.931	1.478	349.65	0.679
D5	0.201	0.582	0.242	173.64	0.246
D6	1.380	3.240	1.205	151.53	0.753
S1	0.361	1.311	0.504	639.09	0.330
E1	4.495	6.029	2.613	369.36	1.030
E2	1.808	3.222	1.742	379.60	0.730
E3	0.840	1.832	0.981	150.68	0.583
FAC1	0.368	N/A	N/A	N/A	N/A

Basin Name	Area (mi ²)	Total channel length (mi)	Length from centroid to outlet (mi)	Slope (ft/mi)	Lag time (hr)
FAC2	0.164	N/A	N/A	N/A	N/A
FAC3	0.433	N/A	N/A	N/A	N/A
FAC4	0.244	N/A	N/A	N/A	N/A

4.2.5 Channel Properties

The Muskingum-Cunge method (Ref. 18, pp. 40-41) was used to perform hydrograph routing along the natural channels through the watershed network. Inputs for the HEC-1 model are presented in Table 4-2 and include the length, slope, and dimensions of the channels which were obtained from the topographic data (refer to Section 4.2.3). The roughness coefficient, Manning's n was selected to be 0.09 for the natural channels for the high sediment flow case based on the previous study (Ref. 6, pp. 28-29).

Table 4-2. Properties of Natural Channels Used in HEC-1 Model, Alternative 1

Channel Name	Length (ft)	Slope (ft/ft)	Bottom Width (ft)	Side Slope (h:1)
cp5cp6	5120	0.023438	30	10
cp2cp6	13700	0.027007	30	10
fac1cp6	8750	0.027429	25	10
fac3cp6	4250	0.018824	40	32
cp7cp8	5400	0.018519	100	25

4.2.6 Initial Abstraction and Infiltration Rate

An initial abstraction of 1 inch and infiltration rate of 1.5 inches per hour used in the previous report (Ref. 6, pp. 27-28, 35-37) were adopted in this calculation.

4.3 ASSUMPTIONS FOR ALTERNATIVE 1

The following assumptions were used in the HEC-1 model for Alternative 1.

4.3.1 Homogeneity of Watershed Properties

The PMP-North Portal and PMP-South Portal are assumed to be spatially uniform within the respective tributary areas during the entire duration of the storm. The soils are assumed to be fairly homogeneous throughout the site. Because the size of the watershed is relatively small, the assumption of spatial homogeneity is deemed appropriate and is used throughout the analysis.

4.3.2 Overland Flow Elements

Assumptions were made on the site drainage at the Muck Storage Areas (designated as FAC1 and FAC4), Aging Facilities (FAC2) and North Portal Pad (FAC3) to calculate the surface runoff. These facilities were modeled as overland flow elements because they will result in distributed outflows in the absence of surface drainages. Overland flow

elements are described by an overland flow length, slope, roughness factor, and percent of sub-basin area represented by the element. The parameters for the North Portal Pad and Aging Facility were computed from the preliminary layout sketches (Attachment 3). A 2 percent slope was assumed for the Aging Facility since the gradient as determined from the preliminary layout sketches was considered too small to allow for proper drainage. The Optional Aging Facility and Muck Storage Areas were assumed to be built up to the same gradient as the existing topographic data (refer to Section 4.2.3) since a detailed grading plan for these facilities has not been developed. The Optional Aging Facility was also assumed to be constructed above the PMF water surface elevations to ensure that waste could not be transported by flood flows. Muck Storage A was assumed to be above the PMF to ensure that the flood flows coming from sub-basins S1 and ND4 would be contained within the manmade channel described in Section 4.3.3 so that these flows would not reach the North Portal Pad. Muck Storage B was assumed to be above the PMF so that flows from sub-basins E1 and FAC4 would be confined to the northern side of the muck pile, resulting in higher water surface elevations near the railroad bridge, and a more conservative design of the bridge opening. The parameters for the areas modeled as overland flow elements are summarized in Table 4-3. A resistance factor of 0.10 was selected for asphalt/concrete surfaces and soil/muck piles (Ref. 18, p. 35).

Table 4-3. Properties of Overland Flow Elements, Alternative 1

Sub-Basin Name	Overland Flow Length (ft)	Slope (ft/ft)	Percent of Sub-Basin Area
FAC1	3500	0.01	100
FAC2 (northern)	2700	0.0426	83.5
FAC2 (southern)	840	0.02	16.5
FAC3 (eastern)	2600	0.035	75
FAC3 (western)	3300	0.0485	25
FAC4 (eastern)	2700	0.0296	50
FAC4 (western)	2400	0.104	50

4.3.3 Manmade Channels

Since one of the objectives of the hydrologic analysis is to reduce the flood elevations at the North Portal Pad, manmade channels were assumed for Alternative 1 to divert the flow away from the pad. Specifically, the following manmade channels were introduced in the analysis:

- Channel s1cp2 to divert the flow from sub-basins S1 and ND4;
- Channel d3cp5 to divert the flow from sub-basin D3 away from North Portal Pad;
- Channel nd2cp3 to divert the flow from sub-basin ND2 around the Aging Facilities;
- Channels cp4cp1 and cp1cp5 to divert the flow from ND1, ND2, FAC2 and D5 away from North Portal Pad;
- Channel e2cp7 to divert the flow from sub-basin E2.

The kinematic wave method was used for routing hydrographs along manmade channels and it requires the inputs of channel length, slope, dimensions and roughness coefficient. Nominal dimensions were assumed for the manmade channels with the slope estimated

from the topographic data (refer to Section 4.2.3) as presented in Table 4-4. A Manning's n value of 0.09 was used for the manmade channels.

Table 4-4. Properties of Manmade Channels Used in HEC-1 Model, Alternative 1

Channel Name	Length (ft)	Slope (ft/ft)	Bottom Width (ft)	Side Slope (h:1)
s1cp2	3500	0.005714	10	11
d3cp5	7970	0.030113	25	2
nd2cp3	2450	0.02449	25	2
cp4cp1	2580	0.025194	25	2
cp1cp5	1280	0.025	25	2
e2cp7	2700	0.018519	25	2

4.4 RESULTS FOR ALTERNATIVE 1

Table 4-5 summarizes the peak discharges predicted by the HEC-1 computer software for Alternative 1 using the inputs and assumptions discussed in the preceding sub-sections. The complete HEC-1 inputs and results and supplementary calculations are included in Attachments 1.02 and 5. In addition to the discharge for individual sub-basins, HEC-1 also estimated the PMF discharges at flow concentration points where hydrographs from two or more sub-basins are combined before being routed downstream.

The inclusion of manmade channels to divert the floodwaters away from the North Portal Pad reduced the peak discharge along the northern edge of the North Portal Pad to about 9,000 cfs (at Flow Concentration Point CP1), which is substantially less than the peak flow of 20,940 cfs determined from the previous study (Ref. 6, pp. 34, 37). With the proposed railroad alignment, the peak flow through the bridge section is about 21,300 cfs (at Flow Concentration Point CP7).

Table 4-5. Results of PMF Analysis, Alternative 1

Sub-Basin	Peak Flow (cfs)		Flow Concentration Point	Peak Flow (cfs)
ND4	3,853		CP2	6,521
S1	2,801		CP3	7,851
D3	5,322		CP4	8,358
ND2	2,487		CP1	9,009
ND1	5,576		CP5	13,777
FAC2	1,954		CP6	27,989
D5	1,854		CP7	21,287
FAC1	1,953		CP8	23,571
FAC3	4,164		CP9	50,894
D6	6,013			
E1	14,220			
E2	7,498			
E3	4,118			
FAC4	2,260			

5 PROBABLE MAXIMUM FLOOD ANALYSIS FOR ALTERNATIVE 2

5.1 METHOD FOR ALTERNATIVE 2

The same method as described under Section 4.1 was used to determine the surface runoff at pertinent locations in the vicinity of the North Portal and South Portal during a Probable Maximum Flood (PMF) event for Alternative 2. The sub-basins boundaries were modified from those of Alternative 1 to reflect the differences in layout arrangement predominantly near the Aging Facilities and North Portal Pad, giving a total of 15 sub-basins as presented in Figure 5-1. Since the Muck Storage Areas may not be fully constructed at the commencement of repository operation, the PMF analysis was conducted for the worst-case scenario to give the maximum inundation so that the mitigation measures can be adequately designed. As such, Muck Storage A was considered to be not yet constructed which means a larger man-made channel will be needed up-gradient of the muck pile to prevent the flow from upstream sub-basins from impinging on the North Portal Pad. On the other hand, the presence of Muck Storage B will block the free passage of water through the railroad bridge leading to higher water surface elevations around the bridge. Therefore, Muck Storage B was included in the analysis. Figure 5-2 is a schematic diagram of the watershed network illustrating the routing of flow through the sub-basins.

5.2 INPUTS FOR ALTERNATIVE 2

5.2.1 Layout Design

The preliminary layout sketch of the surface facilities for Alternative 2 (Attachment 3) including the proposed North Portal Pad, Muck Storage Areas, Aging Facilities, and Railroad Alignment was used to define the extent of the drainage area.

5.2.2 Precipitation

The PMP values for Alternative 2 were the same as Alternative 1.

5.2.3 Topographic Data

The topographic data used for the analysis were described in Section 4.2.3.

5.2.4 Sub-Basin Properties

The areas and lag times of the Alternative 2 sub-basins are summarized in Table 5-1. Sub-basins that have primarily constructed surfaces such as FAC2, FAC3 and FAC4 (see Figure 5-1 for sub-basins layout) were simulated as overland flow elements and did not require lag time calculation. Aging Pads 2 and 3 were included in their respective sub-basin as impervious area.

Table 5-1. Properties of Sub-Basins Used in HEC-1 Model, Alternative 2

Basin Name	Area (mi ²)	Total channel length (mi)	Length from centroid to outlet (mi)	Slope (ft/mi)	Lag time (hr)
D3	1.135	3.414	1.658	523.78	0.694

Basin Name	Area (mi ²)	Total channel length (mi)	Length from centroid to outlet (mi)	Slope (ft/mi)	Lag time (hr)
D5	0.277	0.971	0.518	171.42	0.375
D6	1.511	3.214	1.254	151.02	0.761
D7	0.091	0.771	0.476	216.03	0.326
D8	0.124	0.775	0.374	199.87	0.305
E1	4.325	6.053	2.745	366.55	1.050
E2	1.808	3.279	1.772	385.56	0.736
E3	0.847	1.925	1.042	127.78	0.622
FAC2	0.085	N/A	N/A	N/A	N/A
FAC3	0.498	N/A	N/A	N/A	N/A
FAC4	0.244	N/A	N/A	N/A	N/A
ND1	1.142	3.676	1.479	421.88	0.709
ND2	0.614	1.935	0.684	507.78	0.432
ND4	0.800	2.833	1.413	341.25	0.664
S1	0.307	1.223	0.475	670.73	0.314

5.2.5 Channel Properties

Table 5-2 presents the length, slope, and dimensions of the Alternative 2 natural channels obtained from the topographic data (refer to Section 4.2.3). These parameters were used in the Muskingum-Cunge routing method (Ref. 18, pp. 40-41). The roughness coefficient, Manning's n was selected to be 0.09 for the natural channels for the high sediment flow case based on the previous study (Ref. 6, pp. 28-29).

Table 5-2. Properties of Natural Channels Used in HEC-1 Model, Alternative 2

Channel Name	Length (ft)	Slope (ft/ft)	Bottom Width (ft)	Side Slope (h:1)
cp2cp6	13,700	0.0270	30	10
d3cp1	2,900	0.0414	400	43
cp1cp3	1,660	0.0175	230	10
d8cp5	1,800	0.0306	35	5
cp5cp6	7,000	0.0247	30	10
d7cp6	7,900	0.0265	25	10
fac3cp6	3,960	0.0205	40	32
cp7cp8	5,400	0.0185	100	25

5.2.6 Initial Abstraction and Infiltration Rate

The values of initial abstraction and infiltration rate were the same as Alternative 1 (see Section 4.2.6).

5.3 ASSUMPTIONS FOR ALTERNATIVE 2

The following assumptions were used in the HEC-1 model to determine surface runoff under Alternative 2.

5.3.1 Homogeneity of Watershed Properties

The homogeneity assumption discussed in Section 4.3.1 also applied to Alternative 2.

5.3.2 Overland Flow Elements

Assumptions were made on the site drainage at Muck Storage B (designated as FAC4), Aging Facility (FAC2) and North Portal Pad (FAC3) to calculate the surface runoff. These facilities were modeled as overland flow elements because they will result in distributed outflows in the absence of surface drainages. Overland flow elements are described by an overland flow length, slope, roughness factor, and percent of sub-basin area represented by the element. The parameters for the North Portal Pad and Aging Facility were computed from the preliminary layout sketches (Attachment 3). The North Portal Pad was assumed to be enlarged to encompass the future dry transfer facility. A 2 percent slope was assumed for the Aging Facility to ensure that the water impounding on the pad will drain offsite such that no ponding will occur. The same assumptions stated in Section 4.3.2 were applied to Muck Storage B since it is unchanged from Alternative 1. These parameters are summarized in Table 5-3. A resistance factor of 0.10 was selected for asphalt/concrete surfaces and soil/muck piles (Ref. 18, p. 35).

Table 5-3. Properties of Overland Flow Elements, Alternative 2

Sub-Basin Name	Overland Flow Length (ft)	Slope (ft/ft)	Percent of Sub-Basin Area
FAC2	1600	0.02	100
FAC3 (eastern)	2700	0.023	62
FAC3 (western)	3200	0.0725	38
FAC4 (eastern)	2700	0.0296	50
FAC4 (western)	2400	0.104	50

5.3.3 Manmade Channels

As in Alternative 1, manmade channels were assumed to divert the flow away from the North Portal Pad to reduce the flood elevations. Specifically, the following manmade channels were included in the HEC-1 analysis as they would influence the hydrograph routing:

- Channel s1cp2 to divert the flow from sub-basins S1 and ND4;
- Channel cp3cp4 to divert the flow from ND1, ND2, D3, FAC2 and D5 away from the North Portal Pad;
- Channel e2cp7 to divert the flow from sub-basin E2.

The kinematic wave method was used for routing hydrographs along manmade channels and it requires the inputs of channel length, slope, dimensions and roughness coefficient. Nominal dimensions were assumed for the manmade channels with the slope estimated from the topographic data (refer to Section 4.2.3) as presented in Table 5-4. A Manning's n value of 0.09 was used for the manmade channels as in Alternative 1.

Table 5-4. Properties of Manmade Channels Used in HEC-1 Model, Alternative 2

Channel Name	Length (ft)	Slope (ft/ft)	Bottom Width (ft)	Side Slope (h:1)
s1cp2	3,740	0.0075	25	2
cp3cp4	2,300	0.0226	25	2
e2cp7	2,700	0.0185	25	2

5.4 RESULTS FOR ALTERNATIVE 2

Table 5-5 summarizes the peak discharges predicted by the HEC-1 computer software for Alternative 2 using the inputs and assumptions discussed in the preceding sub-sections. The complete HEC-1 inputs and results as well as supplementary calculations are included in Attachments 1.03 and 5. In addition to the discharge for individual sub-basins, HEC-1 also estimated the PMF discharges at flow concentration points where hydrographs from two or more sub-basins are combined before being routed downstream.

The peak discharge along the northern edge of the North Portal Pad is about 14,400 cfs (at Flow Concentration Point CP4), which is significantly higher than that of Alternative 1 because there is no manmade channel to reroute the runoff from sub-basin D3 and part of sub-basin ND2 before it gets to the North Portal Pad. Although the area of impervious surface is smaller than that of Alternative 1, the peak discharge at Flow Concentration Point CP6 is higher due to the different routing arrangement that alters the superposition of hydrographs. On the other hand, the peak flow through the bridge section is slightly reduced to about 20,400 cfs (at Flow Concentration Point CP7) as a result of the southward extension of the North Portal Pad which cuts off a portion of the area draining to the railroad bridge.

Table 5-5. Results of PMF Analysis, Alternative 2

Sub-Basin	Peak Flow (cfs)		Flow Concentration Point	Peak Flow (cfs)
ND4	3,839		CP2	5,731
S1	2,453		CP1	7,859
D3	5,269		CP3	13,284
ND2	3,996		CP4	14,369
ND1	5,213		CP5	14,863
FAC2	1,079		CP6	29,438
D5	2,026		CP7	20,425
D8	1,004		CP8	22,864
D7	712		CP9	50,819
FAC3	4,704			
D6	6,577			
E1	13,474			
E2	7,448			
FAC4	2,260			
E3	3,961			

6 FLOOD INUNDATION ANALYSIS FOR ALTERNATIVE 1

6.1 METHOD, ALTERNATIVE 1

Flood inundation calculations were performed for each facility identified on the three preliminary layout sketches contained in Attachment 3. Alternative 1 includes analyses using the layout shown in the sketch titled "Geological Repository Operations Area North Portal – Plot Plan" and in the sketch labeled "Preliminary for Predecisional Study 8/7/03." For the North Portal Pad, separate inundation calculations were conducted for conditions with no major drainage facilities constructed and with proposed drainage facilities. The proposed drainage facilities are not intended to be detailed designs but were selected to demonstrate the feasibility of protecting critical facilities from the PMF. The inundation calculations are provided in the order from a general north to south direction following the "no mitigation" scenario calculation for the North Portal Pad. The calculations for Alternative 1 are included in Sections 6.2 through 6.12.

6.2 NO MITIGATION SCENARIO FOR THE NORTH PORTAL PAD, ALTERNATIVE 1

6.2.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

One river reach was used for routing flow across the North Portal Pad, assuming that no flood control measures, such as diversion channels or flood walls, were implemented. Flow was routed from FAC2 downstream to the gap between Alice Hill and Fran Ridge as shown in Figure 6-1. Cross sections were developed from the topographic data (refer to Section 4.2.3) using Arcview V.3.2 and modified for the surface facilities based on the preliminary layout sketches (Attachment 3). Cross-sections are included in Attachment 6 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Even though the conditions modeled in the PMF analysis are slightly different than this "no mitigation" scenario, they can be used to estimate the runoff. Peak discharges presented in Table 4-5 were used with a bulking factor as inputs to the HEC-RAS software. As stated in Section 6.2.2, for the no mitigation scenario, it was assumed that the Optional Aging Facility and Muck Storage A would not yet be constructed. Without any flood control measures, runoff from ND4 would reach the upstream edge of the North Portal Pad. Therefore, flow at Station 10815 (see Figure 6-1) would consist of runoff from sub-basins ND2, D3, FAC2, S1, and ND4. Using the bulking factor of 10% based on the previous report, (Ref. 6, pp. 29-30) this results in a flow of 18,058 cfs at the upstream boundary. At Section 9898, flow was increased to 24,192 to account for flow contributed by ND1. At Station 7785, flow was increased to 28,379 cfs to account for the addition of flow from FAC1 and D5. By adding the peak flows from the individual sub-

basins, this results in a conservative estimate of the peak flow that could potentially reach the upstream end of the North Portal Pad. Runoff from the existing area proposed for the Optional Aging Facility would also be slightly less than calculated in the PMF analysis.

Some flow would run off the eastern edge of the pad due to the fact that the final grade of the eastern edge will be higher than the natural ground surface as shown on the preliminary layout sketch (Attachment 3).

A conservative approach was used to estimate the quantity of water flowing down the pad. The assumptions of weir flow described in Section 6.2.2 were used to calculate the flow between Stations 7500 and 6940. These calculations are included Attachment 6. At Station 7242, the flow was decreased to 21,544 cfs to account for spill flow over the edge of the pad. From Station 6940 to 5059, flow was estimated to be 10,576 cfs. At Station 4606, flow was increased back to 28,379 to account for the rejoining of spill flows.

6.2.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows under no mitigation scenario for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of Optional Aging Facility and Muck Storage A

It was assumed that the Optional Aging Facility and Muck Storage A would not yet be constructed in order to approximate "existing" conditions. This means runoff from ND4 would reach the Aging Facility and the North Portal Pad.

Spill Flow from North Portal Pad

It was assumed that flow over the edge of the pad could be estimated by using an iterative approach to calculate the weir flow between Stations 7500 and 6940. These calculations are included Attachment 6. The assumption was needed because HEC-RAS is limited to modeling one-dimensional, steady state flow. It was determined that at least 6,835 cfs would run off the pad between Stations 7500 and 7242, and 10,968 cfs would run off between Stations 7242 and 6940. Even though more flow would continue to spill over the edge downstream, it was assumed that the flow from Station 6940 to 5059 would remain at 10,576 cfs to be conservative. At Station 4606, it was assumed that the flow over the pad would rejoin with the spilled flow, so the flow was increased back to 28,379 cfs.

Manning’s Roughness Coefficient

Manning’s roughness coefficient of 0.089 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.04 and 0.03, respectively.

6.2.3 Results

Table 6-1 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, without the construction of major drainage facilities. The extent of the inundation is shown in Figure 6-1. Results indicate that water depths on the Aging Facility would range between 2 and 5 feet. Water depths across the North Portal Pad would range between approximately 2 and 11 feet. The entrance to the North Portal would remain approximately 9 feet above the inundation surface. The complete HEC-RAS output results are included in Attachments 1.04 and 6.

Table 6-1. Flood Inundation Results for No Mitigation Scenario, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
10815	18,058	3778	8.8	0.83
10438	18,058	3765	5.5	0.52
9898	24,192	3757	3.7	0.35
9621	24,192	3750	12.1	1
9236	24,192	3733	7.0	0.57
8940	24,192	3726	7.6	0.61
8553	24,192	3716	6.7	0.6
8327	24,192	3709	7.4	0.69
8038	24,192	3691	18.4	0.99
7785	28,379	3684	5.4	0.43
7500	28,379	3682	3.0	0.28
7242	21,544	3680	3.9	0.4
6940	10,576	3677	2.3	0.23
6704	10,576	3675	4.3	0.5
6416	10,576	3672	0.8	0.05
6130	10,576	3672	0.9	0.06
5837	10,576	3672	0.9	0.06
5511	10,576	3672	0.9	0.06
5059	10,576	3671	6.4	1.01

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
4606	28,379	3615	6.7	0.66
3953	28,379	3594	7.7	0.63
3289	28,379	3577	7.6	0.6
2827	28,379	3565	7.5	0.59
2301	28,379	3554	6.6	0.55
1826	28,379	3542	7.8	0.64
1188	28,379	3529	5.8	0.46
568	28,379	3515	9.2	0.68

6.3 DIVERSION AROUND MUCK STORAGE A, ALTERNATIVE 1

6.3.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing consists of a main river branch extending from the northern boundary of Muck Storage A to the gap between Alice Hill and Fran Ridge as shown in Figure 6-2. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 7 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used with a bulking factor as inputs to the HEC-RAS software. Along the northern boundary of Muck Storage A, i.e., from Station 17644 to Station 12712 (as shown on Figure 6-2), the peak flow at CP2 was used as it represents the combined flows from sub-basins S1 and ND4. With a bulking factor of 10% based on the previous report (Ref. 6, pp. 29-30), the flow for this reach is 7,173 cfs. Downstream of CP2, the flow will increase due to additional runoff from part of sub-basin D6. The area that will drain to the main channel was calculated to be 0.665 mi² using ArcGIS V.8.3, and the additional runoff was calculated by proportioning the area to the total drainage area of sub-basin D6, resulting in a total bulked flow of 10,363 cfs. This is a conservative approach because the peak flow from CP2 may not be concurrent with that from sub-basin D6.

6.3.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows around Muck Storage A for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted. For the proposed mitigation designs the flows are directed into existing channels to increase the probability that new channels will not form near the North Portal Pad.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed along the northern boundary of Muck Storage A between Station 16740 and 13226 to divert the flow from sub-basins S1 and ND4 eastward to flow concentration point CP2 to reduce the flow impacting the North Portal Pad. The channel is assumed to have a bottom width of 10 feet, a 2:1 side

slope on the downhill side and the natural slope on the uphill side, and a gradient of 0.0026, resulting in an excavation volume of about 68,000 cubic yards (volume calculation included in Attachment 7). The average channel depth is about 14 feet. However, since the channel has to pass through a few ridges along its alignment, the maximum depth of excavation will be approximately 20 feet at the deepest section.

Configuration of Muck Storage A

Muck Storage A is assumed to be approximately 20 feet high along the northern boundary such that it is above the PMF water surface elevations. Since the muck storage has not been designed, this assumption will ensure that the flood flows coming from sub-basins S1 and ND4 will be contained within the manmade channel. Otherwise, if the final configuration of the muck storage is different such that it will be overtopped during the PMF event, more water will reach the North Portal Pad resulting in higher water surface elevations.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.0619 and 0.0244, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

6.3.3 Results

Table 6-2 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 6-2. Results indicate that the PMF flow is contained within the manmade channel along the northern boundary of Muck Storage A given the assumptions stated above. The PMF flow is also contained within the natural channel downstream of CP2, thus assuring that the flow will not affect the North Portal Pad under the high sediment transport conditions. The complete HEC-RAS output results are included in Attachments 1.05 and 7.

Table 6-2. Flood Inundation Results Around Muck Storage A, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
17644	7173	3933	9.67	0.89
17245	7173	3913	10.46	0.8
16740	7173	3899	2.03	0.09
16126	7173	3899	1.14	0.05
15507	7173	3899	2.36	0.09
14755	7173	3898	5.35	0.26
13676	7173	3890	9.12	0.51
13227	7173	3882	7.02	0.53
12712	7173	3860	7.63	0.54
11769	10363	3827	12.85	0.93
10590	10363	3785	11.2	0.67
8898	10363	3733	16.01	0.84
8023	10363	3706	12.34	0.7
6683	10363	3674	12.26	0.64
4642	10363	3624	11.32	0.7
2917	10363	3584	5.94	0.53
1730	10363	3560	6.33	0.54
286	10363	3527	7.13	0.59

6.4 DOWNSTREAM OF MUCK STORAGE A, ALTERNATIVE 1

6.4.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing consists of a single branch extending from the southern boundary of Muck Storage A to the gap between Alice Hill and Fran Ridge as shown in Figure 6-3. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 8 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). The flow from FAC1 will enter the channel at the upstream boundary with the amount calculated to be 2,150 cfs including bulking. Along the watercourse, the flow will continuously increase due to additional runoff from part of sub-basin D6. The area that will drain to this channel was calculated to be 0.234 mi² using ArcGIS V.8.3 (as delineated on Figure 6-3) by proportioning the area to the total drainage area of sub-basin D6, resulting in a total bulked flow of 3,268 cfs that was applied to the entire reach. This is a conservative approach because the peak flow from FAC1 may not be concurrent with that from sub-basin D6, and in reality the incremental runoff will only reach its peak at the downstream end of the channel.

6.4.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows downstream of Muck Storage A for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of Muck Storage A

There is no grading plan developed for Muck Storage A. It is assumed to be configured in such a way to direct the surface runoff to the natural channel identified in this routing so that the North Portal Pad will be protected from flooding resulting from uncontrolled sheetflow.

Manning’s Roughness Coefficient

Manning’s roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.0266 and 0.0217, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

6.4.3 Results

Table 6-3 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 6-3. Results indicate that the capacity of the natural channel is sufficient to carry the PMF flow such that no overtopping is expected to occur. Therefore, the North Portal Pad will not be inundated by the flow propagating down this primary channel. The complete HEC-RAS output results are included in Attachments 1.06 and 8.

Table 6-3. Flood Inundation Results Downstream of Muck Storage A, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
8522	3,268	3758	11.21	0.99
8091	3,268	3744	8.7	0.59
7652	3,268	3731	9.14	0.72
6694	3,268	3701	8.85	0.66
5946	3,268	3679	8.55	0.67
5119	3,268	3653	9.32	0.7
4220	3,268	3627	7.53	0.61
3417	3,268	3606	6.89	0.62
2408	3,268	3577	3.92	0.55
1620	3,268	3560	4.48	0.45
740	3,268	3542	6.28	0.61
59	3,268	3525	4.43	0.5

6.5 DIVERSION EAST OF OPTIONAL AGING FACILITY AND AROUND NORTH CONSTRUCTION PORTAL, ALTERNATIVE 1

6.5.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing as shown on Figure 6-4 consists of a single branch that begins at the base of sub-basin D3, continues along the northern and then the eastern boundary of the Optional Aging Facility, and subsequently goes through a manmade reach before discharging into the natural channel east of sub-basin D5. The routing was set up with the objective to reduce the PMF water surface elevation at the North Portal Pad by diverting the flow from sub-basin D3, which would otherwise impinge on the northern boundary of the pad. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 9 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). Therefore, the bulked peak flow from sub-basin D3 of 5,854 cfs was applied to the entire reach.

6.5.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows east of the optional aging facility for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted. For the proposed mitigation designs the flows are directed into existing channels to increase the probability that new channels will not form near the North Portal Pad.

Configuration of Optional Aging Facility, North Construction Portal and Muck Storage A

The Optional Aging Facility and North Construction Portal are assumed to be above the PMF water surface elevation to ensure that waste could not be transported by flood flows. Muck Storage A is also assumed to be above the PMF water surface elevation (see rationale in Section 6.3.2) and 50 feet apart from the Optional Aging Facility, thereby leaving a flow passage of approximately 50 feet wide for the floodwater to get through.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed along the northern boundary of the Optional Aging Facility (between Station 5460 and 5105 on Figure 6-4) to divert the flow from sub-basin D3 to the natural drainage east of the facility. This will provide proper drainage to contain and route stormwater for protection of the surface facilities. The pad of the North Construction Portal is assumed to be shifted to the north to be above the channel. The channel is assumed to have a bottom width of 25 feet, with 2:1 side slopes and a gradient of 0.0197, requiring about 9,000 cubic yards of excavation. The average channel is about 13 feet. Where the channel passes through the ridge, the channel depth will be about 13 to 15 feet. Secondly, in order to safely convey the flow away from the North Portal Pad, a 2,000-foot long manmade channel is assumed to be constructed between Station 2480 and Station 224 to divert the floodwater to the natural channel. This channel will have a bottom width of 25 feet, with 2:1 side slopes and a gradient of 0.022 to contain the flow within the channel without overtopping. This requires an excavation of approximately 80,000 cubic yards with an average channel depth of 18 feet. The volume calculations are included in Attachment 9.

Blockage of Natural Drainages

In order to direct the floodwater down the manmade channel, the natural drainages between Stations 1371 and 529 are assumed to be blocked with fill material immediately downstream of their intersection with the manmade channel to prevent the water from flowing down to the North Portal Pad. The fill material should be placed at least up to the predicted maximum water surface elevations, or 1 to 2 feet higher for provision of freeboard.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.043 and 0.0385, respectively.

6.5.3 Results

Table 6-4 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 6-4. The flow coming down from sub-basin D3 will be intercepted by the manmade channel along the northern boundary of Optional Aging Facility and diverted eastward to the natural

drainage. Thereafter the flow will be confined in the passage between the Optional Aging Facility and Muck Storage A which serve as barriers to prevent the flow from spreading laterally. Further downstream the water will be conveyed by the manmade channel that is sized to contain the flow until the water is ultimately discharged into the natural channel. The North Portal Pad will not be affected by this flow because of the modifications made to the drainage pattern as discussed above. The complete HEC-RAS output results are included in Attachments 1.07 and 9.

Table 6-4. Flood Inundation Results East of Optional Aging Facility and Around North Construction Portal, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
6504	5,854	3915	6.22	0.6
6220	5,854	3904	9.21	0.87
5862	5,854	3885	3.4	0.34
5668	5,854	3880	11.32	0.82
5460	5,854	3875	8.9	0.54
5252	5,854	3869	11.93	0.78
5105	5,854	3864	9.92	0.7
4958	5,854	3859	9.43	0.7
4705	5,854	3848	9.95	0.86
4239	5,854	3833	8.44	0.58
3831	5,854	3822	11.53	0.62
3425	5,854	3811	11.88	0.63
3077	5,854	3803	12.53	0.7
2808	5,854	3790	16.29	1.1
2480	5,854	3778	9.32	0.57
2191	5,854	3772	9.33	0.57
1831	5,854	3764	9.34	0.57
1371	5,854	3755	9.32	0.57
949	5,854	3746	9.37	0.57
529	5,854	3738	9.22	0.56
224	5,854	3728	13.05	0.85
57	5,854	3722	11.94	0.79

6.6 AGING FACILITY AND NORTH PORTAL PAD, ALTERNATIVE 1

6.6.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing consists of a main river branch extending from the north-west corner of the Optional Aging Facility (area FAC2 in the hydrology model) around the lower Aging Facility and towards the south-east just north of the North Portal Pad (NPP) as shown in Figure 6-5. Cross sections were developed from topographic data described in Section 4.2.3 using Arcview V.3.2 and modified for the surface facilities based on the preliminary layout sketch (Attachment 3). Cross-Sections are included in Attachment 10 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used with a bulking factor as inputs to the HEC-RAS software. Along the aging facilities, i.e., from Station 8215 to Station 3864 (as shown on Figure 6-5), the peak flow at CP3 was used as it represents the combined flows from sub-basins ND1 and ND2. With a bulking factor of 10% based on the previous report (Ref. 6, pp. 29-30), the flow for this reach is 8,636 cfs. Downstream of CP3, the flow will increase due to additional runoff from FAC2 and D5 resulting in a total bulked flow of 9,910 cfs.

6.6.2 Assumptions

The followings assumptions were used in the HEC-RAS software for routing flows around the Aging Facility and North Portal Pad for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted. For the proposed mitigation designs the flows are directed into existing channels to increase the probability that new channels will not form near the North Portal Pad.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed along the western boundary of the Aging Facility to retain runoff from sub-basins ND2 and ND1 and divert it southeastward to flow concentration point CP3 to prevent runoff to the Aging Facility. The channel is assumed to have a bottom width of 35 feet, a 2:1 side slope, and a gradient

of 0.034, resulting in an excavation volume of about 85,000 cubic yards. The depth of the excavation varies from about 10 feet to 25 feet along its alignment.

From the Aging Facility east past the North Portal Pad it was assumed that the flow would be transported in either a manmade channel or constrained by floodwalls or levees from flowing onto the North Portal Pad. For the channel construction scenario, the channel was assumed to have 2:1 side slopes and a bottom width of 35 feet between Stations 3684 and 1536 decreasing to about 30 feet wide downstream of this station. The average channel depth is about 20 feet, and varies from about 10 feet to 30 feet deep at the deepest location. The average gradient is about 0.027. This requires an excavation of 200,000 cubic yards. The volume calculations are included in Attachment 10. Even with a large channel bottom width the channel is not quite large enough to contain the flow. Small berms on the order of 5 to 6 feet tall would be needed between stations 3440 and 2806 where the gradient is the shallowest. A 2-foot berm would be needed near Station 1283 to prevent flow onto the North Portal Pad. Also, the constructed channel will cross several natural drainages. To prevent stormwater runoff from flowing down those drainages, the drainages should be blocked on the downstream side of the manmade channel at each crossing.

If no drainage channels are constructed north of the North Portal Pad floodwalls or levees will be needed. Assuming the wall is constructed along the same alignment as the channel as shown in Figure 6-6, the wall or levee would need to start at Station 3684 and be tied into Exile Hill. The wall would need to be approximately 10 to 12 feet tall from Station 3225 to Station 2275, and between 4 and 12 feet tall from Station 2275 to Station 469 downstream of the pad. The total length of the wall is about 3,200 feet.

Configuration of Aging Facility FAC2

The Optional Aging Facility was assumed to be above the PMF water surface elevations, which means that the Facility should be approximately 10 feet above the natural ground elevation along the northwestern boundary. The actual height could be more or less depending upon the exact location of the facility.

The Aging Facility, as shown on Figure 6-5 is assumed to be protected by a channel running along its western and southern edge. A small berm or levee may be needed at the northwestern corner of the facility to reduce the size of the channel required at this location. With these drainage structures the facility can be located at any elevation.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.089 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were specified at both boundaries in the HEC-RAS software (i.e., the water surface slope is assumed to follow the channel ground surface slope). The channel ground surface slopes at the downstream and upstream boundaries were estimated from the topographic data described in Section 4.2.3 to be 0.006 and 0.031, respectively.

6.6.3 Results

Table 6-5 presents the best estimate of PMF water surface elevations and flow velocities at each cross section for the scenario with channel construction, with the extent of the inundation shown in Figure 6-5. Results indicate that the PMF flow is contained within the manmade channel along the northern boundary of the North Portal Pad and to the south and west of the Aging Facility. Table 6-6 presents the best estimate of PMF water surface elevations and flow velocities at each cross section for the scenario with floodwalls/levees, with the extent of the inundation shown in Figure 6-6. The complete HEC-RAS output results are included in Attachments 1.08 and 10.

Table 6-5. Flood Inundation Results Around Aging Facility and North Portal Pad, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
8215	8,636	3892	3.22	0.23
8049	8,636	3889	3.07	0.61
7771	8,636	3873	11.76	0.88
7444	8,636	3856	13.94	0.74
7029	8,636	3832	9.67	0.79
6211	8,636	3797	9.47	0.69
5838	8,636	3787	5.15	0.28
5637	8,636	3784	10.07	0.61
5124	8,636	3771	10.71	0.62
4823	8,636	3766	8.5	0.46
4685	8,636	3763	10.98	0.59
4456	8,636	3756	13.9	0.87
4109	8,636	3739	13.89	0.87
3865	8,636	3728	13.24	0.82
3685	9,910	3725	8.51	0.45
3440	9,910	3721	9.18	0.49
3225	9,910	3720	6.35	0.3
3020	9,910	3717	9.61	0.5
2807	9,910	3712	12.88	0.76
2576	9,910	3704	12.88	0.76
2275	9,910	3693	12.83	0.75
1901	9,910	3684	8.35	0.43
1536	9,910	3683	3.67	0.15
1283	9,910	3680	11.81	0.63
942	9,910	3671	11.81	0.67

**Table 6-6. Flood Inundation Results Around North Portal Pad with
 Floodwall/Levee, Alternative 1**

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
8215	8,636	3892	3.29	0.23
8049	8,636	3888	0.8	0.52
7771	8,636	3873	10.6	0.76
7444	8,636	3856	13.88	0.74
7029	8,636	3833	9.31	0.74
6211	8,636	3797	11.58	0.89
5838	8,636	3788	4.51	0.24
5637	8,636	3783	15.87	1
5124	8,636	3778	9.89	0.56
4823	8,636	3774	8.64	0.47
4685	8,636	3767	15.77	1
4456	8,636	3764	3.69	0.26
4109	8,636	3756	16.15	1
3865	8,636	3743	8.81	0.72
3685	9,910	3734	8.81	0.94
3440	9,910	3727	5.65	0.43
3225	9,910	3727	2.87	0.14
3020	9,910	3726	6.45	0.33
2807	9,910	3723	9.32	0.56
2576	9,910	3719	7.01	0.39
2275	9,910	3714	8.2	0.48
1901	9,910	3702	13.17	0.96
1536	9,910	3691	8.24	0.57
1283	9,910	3688	8.06	0.42
942	9,910	3684	6.78	0.45
469	9,910	3669	11.15	0.98
66	9,910	3644	11.59	0.73

6.7 EAST OF NORTH PORTAL PAD, ALTERNATIVE 1

6.7.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

A single branch representing the primary channel east of the North Portal Pad was set up that extends from the downstream end of the manmade channel draining the Optional Aging Facility to the gap between Alice Hill and Fran Ridge as shown in Figure 6-7. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 11 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). The channel collects floodwater from the two manmade channels that divert water from sub-basin D3 and from flow concentration point CP1, as well as distributed runoff from part of sub-basin D6 along its watercourse. The area that will drain to this channel was calculated to be 0.157 mi² using ArcGIS V.8.3 (as delineated on Figure 6-7), and the additional bulked flow was calculated to be 753 cfs by proportioning the area to the total drainage area of sub-basin D6. This amount was added to the bulked flows at d3cp5 and CP5 to give total flows of 6,600 cfs and 15,908 cfs that were used for the reach upstream and downstream of Station 5224, respectively.

6.7.2 Assumptions

The followings assumptions were used in the HEC-RAS software for routing flows east of the North Portal Pad for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.044 and 0.028, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

6.7.3 Results

Table 6-7 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 6-7. Results indicate that the capacity of the natural channel is sufficient to carry the PMF flow such that no overtopping is expected to occur. Therefore, the North Portal Pad will not be inundated by the flow propagating down this primary channel. The complete HEC-RAS output results are included in Attachments 1.09 and 11.

Table 6-7. Flood Inundation Results for Primary Channel East of North Portal Pad, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
7437	6,600	3719	12.91	0.76
7022	6,600	3701	13.71	0.92
6501	6,600	3683	11.98	0.71
6115	6,600	3668	14.71	0.9
5705	6,600	3658	8.72	0.47
5224	15,908	3645	15.39	0.82
4776	15,908	3633	13.03	0.68
4247	15,908	3618	14.32	0.77
3745	15,908	3604	12.75	0.71
3207	15,908	3591	11.23	0.68
2536	15,908	3572	9.15	0.68
1447	15,908	3549	4.68	0.45
181	15,908	3523	7.56	0.63

6.8 DOWNSTREAM OF NORTH PORTAL PAD, ALTERNATIVE 1

6.8.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing consists of a single branch extending from the eastern boundary of North Portal Pad to the gap between Alice Hill and Fran Ridge as shown in Figure 6-8. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 12 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). The overland flow from sub-basin FAC3 will enter the channel at the upstream boundary with the amount calculated to be 4,580 cfs including bulking. Along the watercourse, the flow will continuously increase due to additional runoff from part of sub-basin D6. The area that will drain to this channel was calculated to be 0.324 mi² using ArcGIS V.8.3 (as delineated on Figure 6-8) by proportioning the area to the total drainage area of sub-basin D6, resulting in a total bulked flow of 6,135 cfs that was applied to the entire reach. This is a conservative approach because the peak flow from FAC3 may not be concurrent with that from sub-basin D6, and in reality the incremental runoff will only reach its peak at the downstream end of the channel.

6.8.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows downstream of the North Portal Pad for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of North Portal Pad

The North Portal Pad will be constructed above the PMF water surface elevation according to the preliminary layout sketches (Attachment 3). No site drainage was included in the layout. It is assumed that the runoff from Exile Hill will be routed around the North Portal Pad and discharged into the natural channel downstream of the pad along with the runoff from the pad itself.

Manning’s Roughness Coefficient

Manning’s roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.028 and 0.024, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

6.8.3 Results

Table 6-8 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 6-8. Results indicate that the capacity of the natural channel is sufficient to carry the PMF flow such that no overtopping is expected to occur. Therefore, the North Portal Pad will be outside the inundation limits. The complete HEC-RAS output results are included in Attachments 1.10 and 12.

Table 6-8. Flood Inundation Results Downstream of North Portal Pad, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
3786	6,135	3603	12.69	0.98
3421	6,135	3593	6.92	0.5
3072	6,135	3584	9.95	0.73
2608	6,135	3573	5.91	0.5
2106	6,135	3567	6.23	0.57
1552	6,135	3549	5.34	0.55
1026	6,135	3537	4.82	0.52
557	6,135	3528	5.13	0.48
56	6,135	3517	5.48	0.55

6.9 RAILROAD BRIDGE CROSSING, ALTERNATIVE 1

6.9.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing of flow concentrating at CP7 under the proposed railroad was performed using one river reach. Flow was routed along the northern edge of Muck Storage B down to the gap between Alice Hill and Fran Ridge as shown in Figure 6-9. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and the preliminary layout sketch (Attachment 3). Cross-sections are included in Attachment 13 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used with a bulking factor as inputs to the HEC-RAS software. A conservative approach was taken to size the two bridges north of Muck Storage B. With the proposed railroad graded to elevation 3667.1 feet, the alignment along the southern end of the eastern edge of Muck Storage B would be in cut. Some flow from sub-basin E2 would escape into sub-basin E3 as flow continued north along the railroad until the grade is above the natural ground surface along the eastern edge of the muck storage pile. The assumption described in Section 4.3.3 that all the runoff from E2 would be diverted to CP7 was used to obtain the maximum flow upstream of the railroad and to be consistent with the PMF analysis.

From Station 7120 to Station 6445 (as shown on Figure 6-9), flow was estimated to be 2,486 cfs for the peak flow from FAC4 with a bulking factor of 10% based on the previous report (Ref. 6, pp. 29-30). At Station 6003, flow was increased to 23,416 cfs, which accounts for the bulked flow at CP7. The flow was increased to 25,928 cfs (the bulked peak flow at CP8) at Station 3939 to account for additional flow from sub-basin E3.

6.9.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows under the railroad for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of Muck Storage B

Muck Storage B is assumed to be approximately 20 feet high along the northern boundary and configured so that it does not block the bottom of the channel along its northern edge. This assumption was made because the design of Muck Storage B is not finalized, and this configuration confines the runoff from sub-basins E1 and FAC4 to the northern side of Muck Storage B but still allows flow through the natural channel. The presence of Muck Storage B results in a conservatively high estimate of water surface elevations near the railroad so that the bridge opening can be properly sized to prevent flow from impinging on the North Portal Pad.

Configuration of Structure Shown in Floodplain

It was assumed that the Visitors Center shown on the preliminary layout sketch (Attachment 3) to be located at the base of Fran Ridge would not be protected from the PMF because it is not important to safety, as defined on the Q List (Ref. 7, p. A-2). Therefore, it could be within the flood inundation surface shown in Figure 6-9.

Bridge Openings

Nominal bridge dimensions were assumed because the bridge design had not been developed at the time this analysis was conducted.

The bridge over the realignment of "H" Road was assumed to be 60 feet long and 190 feet wide in the direction of flow. These dimensions were assumed to allow traffic to pass under the bridge, and to allow for grading of the railroad alignment. It was assumed to be a clear span without any piers. The bridge deck was assumed to be 6 feet thick, as assumed in the previous study (Ref. 6, p. 26).

The bridge across the natural channel at CP7, just north of Muck Storage B, was assumed to be 110 feet long, in order to adequately convey the PMF, and 190 feet wide, to allow for grading of the railroad alignment. It was assumed that there would be one row of 4-foot diameter piers down the center of the channel. The bridge deck was assumed to be 6 feet thick. These dimensions are consistent with a typical concrete freeway bridge, as assumed in the previous study (Ref. 6, p. 26).

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface

slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.05 and 0.028, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

6.9.3 Results

Table 6-9 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 6-9. Results indicate that the PMF flow will not overtop the portion of “H” Road leading to the southeastern edge of the North Portal Pad, assuming that the two bridge openings are at least as large as stated above. Therefore, the North Portal Pad will remain outside of the floodplain boundary. If both bridges are constructed as clear spans, the water surface elevation as far upstream as Station 6445 would be approximately 2 feet lower. The complete HEC-RAS output results are included in Attachment 1.11 and Attachment 13.

Table 6-9. Flood Inundation Results Near Railroad Bridge Crossing, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
7120	2,486	3,659	5.6	0.74
6890	2,486	3,651	3.8	0.45
6445	2,486	3,647	0.4	0.02
6003	23,416	3,647	2.1	0.08
5855	23,416	3,647	1.2	0.04
5736	23,416	3,647	0.7	0.02
5600	Bridge			
5478	23416	3,618	21.3	2.1
5180	23,416	3,615	9.5	0.69
4822	23,416	3,607	7.1	0.54
3939	25,928	3,590	7.3	0.53
3331	25,928	3,583	5.7	0.33
2847	25,928	3,575	10.0	0.62
2360	25,928	3,566	8.5	0.52
1909	25,928	3,558	9.9	0.57
1376	25,928	3,549	10.4	0.57
823	25,928	3,538	10.1	0.59
170	25,928	3,522	10.5	0.69

6.10 SOUTH PORTAL, ALTERNATIVE 1

6.10.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The South Portal is located within sub-basin E2. Three routings were performed to determine the limits of inundation in the vicinity of the South Portal during a PMF event. The first routing designated as sportal1 on Figure 6-10 consists of a single river branch along the main stream of sub-basin E2 extending from midway up the sub-basin to south of the Muck Pile Hill. The remaining two routings include the tributaries draining the northern and southern portions of Boundary Ridge, which are sub-catchments within sub-basin E2. These are designated as sportal2 and sportal3 on Figure 6-10. Also shown on Figure 6-10 is the delineation of the two sub-catchments. Cross sections for all the branches were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 14 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 1. Peak discharges presented in Table 4-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). Since the main stream will intercept the runoff from the northern and southern Boundary Ridge sub-catchments downstream of Station 2618 of sportal1, the bulked peak flow of 8,248 cfs at the outlet of sub-basin E2 was only applied to sportal1 downstream of this station. A smaller flow of 6,765 cfs was used for the upstream reach by proportioning the tributary drainage area to the total drainage area of E2, with the tributary drainage area obtained by deducting the areas of the northern and southern Boundary Ridge sub-catchments, which were calculated with ArcGIS V.8.3 to be 0.106 and 0.219 mi², respectively. Using these sub-catchment areas, the bulked peak flows for sportal3 and sportal2 were calculated to be 484 and 1,000 cfs, respectively.

6.10.2 Assumptions

The following assumptions were used in the HEC-RAS software for routings around the South Portal for Alternative 1.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of Muck Storage B

Muck Storage B is assumed to be above the PMF water surface elevations because it will be constructed above the existing ground elevation with muck pile. It is also assumed to be shifted westward to accommodate the railroad alignment such that it is tied to the ridge along the southern boundary of sub-basin FAC4, thus blocking the floodwater from flowing over the muck pile. Since Muck Storage B has not been designed, assumptions are needed to route the flood flows around the facility. This assumption has no effect on the inundation around the South Portal Pad because Muck Storage B is located downstream far away from the critical facilities.

Configuration of South Portal Pad

The South Portal Pad is assumed to be above the PMF water surface elevations to ensure that waste could not be transported by flood flows. This is a reasonable assumption given the critical nature of the South Portal.

Spill Over Flow

Although the output from HEC-RAS indicates that the flow at Station 5195 of sportal1 will not be contained in the main channel and will probably undergo sheetflow down the ridge east of the channel (to the adjacent sub-basin), it is assumed that the same amount of water will continue downstream to provide a conservative estimate of the PMF water surface elevations at the downstream locations along sportal1.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries for each branch to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries for sportal1 (i.e., the water surface slope follows the channel ground surface slope). Similarly, normal flow conditions were assumed at the upstream boundaries for sportal2 and sportal3. Since the downstream boundaries of sportal2 and sportal3 are connected to sportal1, the predicted water surface elevations from HEC-RAS at Stations 2618 and 2189 of sportal1 were used. Table 6-10 summarizes the boundary conditions for the 3 south portal branches.

Table 6-10. Boundary Conditions for South Portal Routings, Alternative 1

Routing	Upstream boundary	Downstream boundary
Sportal1	S=0.0458	S=0.0313
Sportal2	S=0.0393	WSEL @ Station 2189 of sportal1
Sportal3	S=0.075	WSEL @ Station 2618 of sportal1

6.10.3 Results

Table 6-11 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 6-10. For sportal1 routing, results indicate that the PMF flow will not be contained within the natural channel at Station 5195 resulting in sheetflow down the ridge east of the main channel. If that happens, the flow will be intercepted by the topsoil storage area and diverted down the valley. Considering the unconsolidated nature of sediments in the watershed, new flow paths may open up during a PMF event and therefore the potential reduction in flow downstream of Station 5195 was ignored in order to obtain the maximum water surface elevation along sportal1. Downstream of Station 1573, the water surface elevation will build up against Muck Storage B, which serves as a barrier to the flow.

For sportal2 routing, the PMF flow is contained within the natural channel and the South Portal is outside the inundation limits. On the other hand, due to the small size of the natural channel the flow will not be contained within sportal3 and the depth of water along the northern edge of the elevated South Portal Pad is estimated to be less than 1 foot.

The complete HEC-RAS output results are included in Attachments 1.12 and 14.

Table 6-11. Flood Inundation Results Around South Portal, Alternative 1

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
Sportal1-main				
5948	6,765	3904	11.04	0.87
5640	6,765	3889	10.16	0.82
5195	6,765	3867	8.14	0.84
4739	6,765	3848	9.38	0.69
4210	6,765	3822	9.73	1.03
3574	6,765	3791	5.6	0.57
3053	6,765	3766	8.73	1.07
2618	8,248	3750	4.3	0.44
2189	8,248	3738	12.82	0.86
1573	8,248	3721	3.7	0.3
1187	8,248	3714	13.24	0.85
770	8,248	3698	9.66	0.74
376	8,248	3683	7.02	0.72

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
22	8,248	3670	4.42	0.58
Sportal2				
2359	1,000	3809	6.36	0.62
2045	1,000	3798	7.18	0.74
1811	1,000	3790	4.71	0.52
1648	1,000	3784	7.65	0.93
1462	1,000	3778	4.21	0.46
1261	1,000	3770	7.13	0.99
1085	1,000	3765	3.21	0.4
895	1,000	3759	7.76	0.88
628	1,000	3751	3.62	0.42
337	1,000	3742	7.62	0.88
12	1,000	3738	1.66	0.11
Sportal3				
1598	484	3842	6.12	0.86
1455	484	3831	6.69	0.93
1335	484	3823	4.89	0.63
1170	484	3814	4.02	0.89
956	484	3801	2.62	0.52
690	484	3785	2.69	0.87
495	484	3772	2.56	0.5
242	484	3758	4.19	0.99
64	484	3749	1.36	0.15

6.11 INTAKE AND EXHAUST SHAFTS, ALTERNATIVE 1

There are 9 intake and exhaust shafts in the study area. Figure 6-11 presents their locations in the watershed. Since they are all located on ridges above the natural channels, no accumulation of runoff is expected to occur around the shafts during a PMF event. Sheetflow over the pads of the shafts is likely to take place during the intense precipitation. Since the depth of flow will be very thin in comparison with the width of flow, the Manning's formula for a wide open channel can be used (Ref. 8, pp. 148-150):

$$q = \frac{1.49}{n} \sqrt{S} y_m^{5/3} \quad (6-1)$$

where: q = discharge per unit width (cfs/ft)
 n = Manning's n
 S = slope of surface (ft/ft)
 y_m = average depth of flow (ft)

The yield (i.e. flow per unit area) was calculated for each natural sub-basin (i.e. sub-basins modified by surface facilities were excluded) using the flows and areas from the PMF analysis presented in Section 4, and the discharge over the shaft was estimated by multiplying the maximum yield from all the sub-basins by the drainage area of the shaft. Table 6-12 summarizes the yield of the sub-basins with the maximum yield being 9,270 cfs/mi².

Table 6-12. Yield of Sub-Basins, Alternative 1

Sub-Basin	Peak Flow (cfs)	Sub-Basin Area (mi ²)	Yield (cfs/mi ²)
ND4	3853	0.82	4,699
S1	2801	0.36	7,781
D3	5322	1.15	4,628
ND2	2487	0.39	6,377
ND1	5576	1.16	4,807
D5	1854	0.2	9,270
D6	6013	1.38	4,357
E1	14220	4.49	3,167
E2	7498	1.81	4,143
E3	4118	0.84	4,902

6.11.1 Assumptions

Flow Width

The width of flow impacting the shaft was assumed to be equal to the diameter of the shaft, which is assumed to be 26 feet (refer to Attachment 1.22).

Drainage Area

Sheetflow usually occurs over a maximum distance of 300 feet before the flow becomes shallow concentrated flow (Ref. 19, p.3-3). Based on this threshold value, the area

draining to a shaft pad was taken to be 300 feet multiplied by the width of the flow. This gives a drainage area of 7,800 ft².

Slope of Pad

The shaft pad is assumed to have a nominal slope of 2 percent to allow for proper drainage.

Manning's Roughness Coefficient

The Manning's roughness coefficient of 0.09 used in the previous report (Ref. 6, pp. 28-29) was adopted in this calculation.

6.11.2 Results

For a yield of 9,270 cfs/mi² and an area of 7,800 ft², the maximum discharge is 2.6 cfs. Using a flow width of 26 feet, the discharge per unit width is 0.1 cfs/ft.

Substituting the parameters into the Manning's formula, Equation 6-1, the average depth over the shaft pad is about 0.2 feet.

6.12 SCOUR ANALYSIS, ALTERNATIVE 1

The scour analysis conducted in the previous report (Ref. 6, pp. 42-44) was revised to reflect the changes in railroad alignment. The proposed new bridge is located east of Muck Pile Hill at the outlet of sub-basin FAC4 (see Figure 4-1). The depth of scour at the railroad bridge was estimated using procedures described in the Federal Highway Administration's Hydraulic Engineering Circular No. 18 (HEC-18) (Ref. 17, pp. 6.1 to 6.6).

In the previous report (Ref. 6, pp. 30, 42-44), the total scour at a bridge was calculated as the sum of contraction scour and local scour. The critical velocity for initiation of contraction scour was determined to be 2.9 to 4.3 ft/s (Ref. 6, p. 43). Since the mean velocity immediately upstream of the bridge at Station 5736 (see Table 6-9) is 0.7 ft/s, no contraction scour is predicted to occur.

The local scour at the piers was calculated using the CSU equation (Ref. 17, Eq. 6.3, p. 6.4) as in the previous report (Ref. 6, p. 43). The scour calculations for Alternative 1 are included in Attachment 15. Based on a maximum water depth of 29 feet with Froude number of 0.02 at Station 5736 (see Attachment 13), the local scour depth at the bridge located immediately north of Muck Storage B is estimated to be 3.6 feet. Similarly, with a water depth of 8 feet the local scour depth at the H-road bridge is about 2.3 feet.

7 FLOOD INUNDATION ANALYSIS FOR ALTERNATIVE 2

7.1 METHOD, ALTERNATIVE 2

The HEC-RAS software was used to perform river routing simulations for determination of flood inundation extents. As mentioned in Section 6.1, Alternative 2 includes analyses using the layout shown in the sketch titled “Midway Valley Wash” (Sketch No. 100-COK-CD04-00101-000-00A) included in Attachment 3. For the North Portal Pad, the potential for inundation without major drainage facilities constructed is described in Section 7.2. Inundation calculations conducted for the proposed drainage facilities are described in Sections 7.3 to 7.14. The proposed drainage facilities are not intended to be detailed designs but were selected to demonstrate the feasibility of protecting critical facilities from the PMF. The inundation calculations are provided in the order from a general north to south direction following the no mitigation scenario for the North Portal Pad.

7.2 NO MITIGATION SCENARIO FOR THE NORTH PORTAL PAD, ALTERNATIVE 2

As discussed in Section 6.2, without any flood control measures, the Aging Facility and North Portal Pad would be inundated under the PMF. Calculations to determine the extent of inundation were not performed for Alternative 2 because flooding would be similar to that occurring for Alternative 1. Flow from upstream watersheds, including sub-basins ND1, ND2, FAC2, D3, D5, D7, D8, S1, and ND4 (shown in Figure 5-1) would be directed toward the Aging Facility, Aging Pads 2 and 3, and the North Portal Pad. Therefore, some form of flood protection will be required in order to protect the critical facilities within the study area.

7.3 DIVERSION AROUND MUCK STORAGE A, ALTERNATIVE 2

7.3.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

As explained in Section 5.1, Muck Storage A is considered to be not yet constructed to determine the maximum inundation for sizing the manmade channel around its northern boundary to divert the flows from sub-basins S1 and ND4. The routing consists of a main river branch extending from the base of sub-basin S1 to the gap between Alice Hill and Fran Ridge as shown in Figure 7-1. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 16 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2 presented in Section 5. Peak discharges presented in Table 5-5 were used with a bulking factor as inputs to the HEC-RAS software. From the base of sub-basin S1 to the eastern end of sub-basin ND4, i.e., Station 17331 to Station 12712 (as shown on Figure 7-1), the peak flow at CP2 was used as it represents the combined flows from sub-basins S1 and ND4. With a bulking factor of 10% based on the previous report (Ref. 6, pp. 29-30), the flow for this reach is 6,300 cfs. Downstream of CP2, the flow will increase due to additional runoff from part of sub-basin D6. The area that will drain to the main channel was calculated to be 0.735 mi² using ArcGIS V.8.3, and the additional runoff was calculated by proportioning the area to the total drainage area of sub-basin D6, resulting in a total bulked flow of 9,820 cfs. This is a conservative approach because the peak flow from CP2 may not be concurrent with that from sub-basin D6.

7.3.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows around Muck Storage A for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new flow paths cannot be predicted. For the proposed mitigation designs the flows are directed into existing channels to increase the probability that new channels will not form near the North Portal Pad.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed to the north of Muck Storage A between Station 16814 and 13175 to divert the flow from sub-basins S1 and ND4 eastward to flow concentration point CP2 to reduce the flow impacting the North Portal Pad. The channel is assumed to have a bottom width of 25 feet with 2:1 side slopes, and a gradient of 0.0065, resulting in an excavation volume of about 195,000 cubic yards (volume calculation included in Attachment 16). The average channel depth is about 20 feet. However, since the channel has to pass through a few ridges along its alignment, the maximum depth of excavation will be approximately 28 feet at the deepest section. In addition, to avoid excessive channel excavation, a 2 to 10-foot high berm will be needed downhill of the manmade channel between Stations 16814 and 16390.

Blockage of Natural Drainages

In order to direct the floodwater down the manmade channel, the natural drainages along the northern boundary of Muck Storage A (as shown on Figure 7-1) are assumed to be blocked with fill material immediately downhill of their intersection with the manmade channel to prevent the water from flowing down to the North Portal Pad. The fill material should be placed at least up to the predicted maximum water surface elevations, or 1 to 2 feet higher for provision of freeboard.

Configuration of Muck Storage A

Since the location of Muck Storage A has not been fixed, it is assumed to be constructed within the limits indicated on Figure 7-1 such that it will be between the manmade channel and the future Aging Pads 2 and 3 in the north-south direction, and will not block the natural channels in sub-basins D6 and ND2. The analysis conducted for Alternative 2 will be valid as long as Muck Storage A lies within those limits.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.0619 and 0.0244, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on

the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

7.3.3 Results

Table 7-1 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-1. Results indicate that the PMF flow is contained within the proposed manmade channel. The PMF flow is also contained within the natural channel downstream of CP2, thus assuring that the flow will not affect the North Portal Pad under the high sediment transport conditions. The complete HEC-RAS output results are included in Attachments 1.13 and 16.

Table 7-1. Flood Inundation Results Around Muck Storage A, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
17,331	6,300	3,933	8.5	0.78
17,044	6,300	3,919	10.4	0.86
16,814	6,300	3,905	7.0	0.37
16,390	6,300	3,902	6.2	0.29
15,650	6,300	3,898	6.2	0.33
15,011	6,300	3,894	6.3	0.34
14,371	6,300	3,889	6.3	0.34
13,789	6,300	3,885	6.6	0.36
13,273	6,300	3,881	7.3	0.4
13,175	6,300	3,875	13.4	0.89
12,712	6,300	3,859	8.1	0.61
11,769	9,820	3,827	11.4	0.81
10,590	9,820	3,784	11.9	0.74
8,898	9,820	3,733	14.4	0.74
8,023	9,820	3,706	13.3	0.79
6,683	9,820	3,676	9.1	0.45
4,642	9,820	3,623	12.5	0.82
2,917	9,820	3,587	3.0	0.2
1,730	9,820	3,559	6.2	0.54
286	9,820	3,527	7.0	0.59

7.4 DIVERSION AROUND AGING PAD 3, ALTERNATIVE 2

7.4.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing as shown on Figure 7-2 consists of a single branch that begins with a manmade reach along the northern and eastern boundaries of Aging Pad 3, subsequently discharges into the natural channel downstream of sub-basin D7, and ends at the gap between Alice Hill and Fran Ridge. The objectives of the routing are to determine the diversion required to prevent flooding at Aging Pad 3, and to confirm that the runoff from sub-basin D7 will be contained in the natural channel downstream of the pad. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 17 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). Therefore, the bulked peak flow from sub-basin D7 of 780 cfs was applied to the upper reach between Stations 9975 and 7842. Downstream of the pad, the flow will increase due to additional runoff from part of sub-basin D6. The area that will drain to the main channel was calculated to be 0.194 mi² using ArcGIS V.8.3, and the additional runoff was calculated by proportioning the area to the total drainage area of sub-basin D6, resulting in a total bulked flow of 1,710 cfs. This is a conservative approach because the peak flow from sub-basin D7 may not be concurrent with that from sub-basin D6.

7.4.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows around Aging Pad 3 for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new flow paths cannot be predicted.

Configuration of Aging Pad 3 and Muck Storage A

Since the grading plan is not available for Aging Pad 3 on the preliminary sketch included as Attachment 3, from a construction standpoint it is logical to assume that the pad will be partly in cut (likely the northern portion) and partly on fill (likely the southern

portion) to optimize the quantities of excavation and borrow materials. This means that the runoff from sub-basin D7 will impinge directly on Aging Pad 3 if there is no diversion to route the flow around the facility. Secondly, Muck Storage A is assumed to be not yet constructed or once constructed to have a similar slope as the existing topography. This will ensure that the runoff from D7 will not be greater than that adopted in the analysis.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed along the northern and eastern boundaries of Aging Pad 3 (between Station 9975 and 7652 on Figure 7-2) to intercept and divert the flow from sub-basin D7 around the pad to the natural channel southeast of the facility. The channel is assumed to have a bottom width of 10 feet, with 2:1 side slopes and variable gradient to fit the local terrain. The average gradient is about 0.039, yielding a total volume of excavation of 25,000 cubic yards. The average depth of channel is about 10 feet because part of the channel has to pass through ridges. The volume calculations are included in Attachment 17.

Blockage of Natural Drainages

In order to direct the floodwater to the manmade channel, the natural drainage between Stations 9975 and 9801 is assumed to be blocked with fill material immediately downhill of its intersection with the manmade channel to prevent the water from flowing down to Aging Pad 3. The fill material should be placed at least up to the predicted maximum water surface elevations, or 1 to 2 feet higher for provision of freeboard.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.037 and 0.0217, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

7.4.3 Results

Table 7-2 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-2. The flow coming down from sub-basin D7 will be intercepted by the manmade channel that is sized to contain the water within its banks along the entire reach. Once the water is discharged into the natural channel, results indicate that the capacity of the natural channel is sufficient to carry the PMF flow such that no overtopping is expected to occur. Therefore, the North Portal Pad will not be inundated by the flow propagating down this primary channel. The complete HEC-RAS output results are included in Attachments 1.14 and 17.

Table 7-2. Flood Inundation Results Around Aging Pad 3, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
9975	780	3,815	7.6	0.93
9801	780	3,807	5.6	0.5
9677	780	3,805	5.6	0.49
9556	780	3,802	5.2	0.45
9414	780	3,801	3.9	0.31
9295	780	3,795	8.8	0.88
9139	780	3,787	7.7	0.74
8969	780	3,780	6.3	0.58
8735	780	3,770	8.2	0.81
8465	780	3,759	5.7	0.57
8166	780	3,748	7.7	0.74
7842	780	3,735	6.6	0.61
7652	1,710	3,729	8.6	0.68
6694	1,710	3,699	7.0	0.62
5946	1,710	3,677	6.7	0.63
5119	1,710	3,651	7.4	0.66
4220	1,710	3,626	6.7	0.58
3417	1,710	3,605	5.5	0.59
2408	1,710	3,576	2.7	0.48
1620	1,710	3,559	3.6	0.42
740	1,710	3,541	4.6	0.55
59	1,710	3,524	3.6	0.48

7.5 DIVERSION AROUND AGING PAD 2, ALTERNATIVE 2

7.5.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing as shown on Figure 7-3 consists of a single branch that begins with a manmade channel along the northern boundary of Aging Pad 2, continues in the natural channel to the east of the pad, and ends where it meets another manmade channel built to route floodwater around the North Portal Pad (refer to Section 7.8). Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 18 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). Therefore, the bulked peak flow of 1,100 cfs for sub-basin D8 was used. The incremental flow from the portion of sub-basin D5 that drains to this routing reach was neglected because it is insignificant compared to the runoff from D8.

7.5.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows around Aging Pad 2 for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new flow paths cannot be predicted. For the proposed mitigation designs the flows are directed into existing channels to increase the probability that new channels will not form near Aging Pad 2.

Configuration of Aging Pad 2 and Muck Storage A

Since the grading plan is not available for Aging Pad 2 on the preliminary sketches included as Attachment 3, from a construction standpoint it is logical to assume that the pad will be partly in cut (likely the northern portion) and partly on fill (likely the southern portion) to optimize the quantities of excavation and borrow materials. This means that the runoff from sub-basin D8 will impinge directly on Aging Pad 2 in the absence of any diversions. Secondly, Muck Storage A is assumed to be not yet constructed or once

constructed to have a similar slope as the existing topography. This will ensure that the runoff from D8 will not be greater than that adopted in the analysis.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed along the northern boundary of Aging Pad 2 (between Stations 4432 and 3408 on Figure 7-3) to intercept and divert the flow from sub-basin D8 to the second natural channel east of the pad. The second natural channel was chosen because it has a larger capacity and it is farther away from Aging Pad 2. A longer manmade channel will be required if the flow is discharged into the natural channel along the eastern boundary of Aging Pad 2 because the northern portion of the pad is likely to be in cut. The channel is assumed to have a bottom width of 10 feet, 2:1 side slopes, and an average gradient of 0.007. The average depth is 12 feet while the total volume of excavation is about 15,000 cubic yards. The volume calculations are included in Attachment 18.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow was assumed at the upstream boundary in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope) using the manmade channel ground slope of 0.005 along the northern boundary. In reality, the runoff from sub-basin D8 will enter the channel laterally and hence the value used for the upstream boundary is irrelevant. Because this routing ends at the other manmade channel CP3CP4, the water surface elevation predicted at Station 1828 of CP3CP4 was used for the downstream boundary.

7.5.3 Results

Table 7-3 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-3. The flow coming down from sub-basin D8 will be intercepted by the manmade channel that is sized to contain the water within its banks. Once the water is discharged into the natural channel, results indicate that the capacity of the natural channel is sufficient to carry the PMF flow such that no overtopping is expected to occur. Therefore, the North Portal Pad will not be inundated by uncontrolled flow propagating down this primary channel. The complete HEC-RAS output results are included in Attachments 1.15 and 18.

Table 7-3. Flood Inundation Results Around Aging Pad 2, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
4432	1,100	3,823	3.8	0.27
4158	1,100	3,821	3.8	0.28
3935	1,100	3,820	4.0	0.29
3745	1,100	3,819	4.3	0.32
3574	1,100	3,814	8.2	0.72
3408	1,100	3,808	5.1	0.62
3259	1,100	3,802	5.3	0.65
3057	1,100	3,794	6.4	0.72
2801	1,100	3,782	6.3	0.71
2441	1,100	3,770	5.6	0.56
2046	1,100	3,757	7.0	0.7
1394	1,100	3,735	5.8	0.58
924	1,100	3,719	7.0	0.72
543	1,100	3,709	4.1	0.39
76	1,100	3,692	7.8	0.84

7.6 NORTH CONSTRUCTION PORTAL, ALTERNATIVE 2

7.6.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing as shown on Figure 7-4 consists of a single branch that begins at the base of sub-basin D3, continues along the natural channel west of the North Construction Portal, and ends at flow concentration point 1. There are a few indistinct natural drainages at the base of sub-basin D3. Since the objective of this routing is to determine the inundation extent in the vicinity of the North Construction Portal, the preferred flow path was set up along the natural channel closest to the North Construction Portal. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 19 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). Therefore, the bulked peak flow from sub-basin D3 of 5,800 cfs was applied from the upstream end of the channel to Station 2746, beyond that the bulked flow of 8650 cfs at CP1 was used.

7.6.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows around the North Construction Portal for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of North Construction Portal and Aging Facility

Since the design elevation has not been determined, the North Construction Portal is assumed to be above the PMF water surface elevation to ensure that floodwater will not get into the underground facilities through the portal. Given the critical nature of the facilities, it is reasonable to assume that an adequate level of protection will be incorporated into the final design to prevent the intrusion of floodwater either by elevating the portal or by some kind of flood barriers (e.g. walls or berms). Similarly, it is assumed that preventive measures will be implemented around the Aging Facility to

protect it against floodwater. Refer to Section 7.7 for detailed flood inundation analysis at the Aging Facility.

Manning’s Roughness Coefficient

Manning’s roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.044 and 0.031, respectively.

7.6.3 Results

Table 7-4 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-4. The flow coming down from sub-basin D3 will be combined with runoff from sub-basin ND2 and spread over the small natural drainages. Since the North Construction Portal and Aging Facility are assumed to be protected against the PMF, they are outside the inundation limits. The complete HEC-RAS output results are included in Attachments 1.16 and 19.

Table 7-4. Flood Inundation Results Near North Construction Portal, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
3737	5,800	3,932	3.6	0.42
3205	5,800	3,908	8.6	0.94
2746	5,800	3,885	4.9	0.56
2380	8,650	3,869	4.5	0.64
1975	8,650	3,848	6.1	0.8
1551	8,650	3,830	4.5	0.54
1094	8,650	3,814	9.0	0.76
644	8,650	3,796	8.7	0.74
84	8,650	3,777	6.4	0.63

7.7 DIVERSION NORTH OF AGING FACILITY, ALTERNATIVE 2

7.7.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing as shown on Figure 7-5 consists of a single branch that begins at the foothill of the ridge northwest of the Aging Facility, continues in a manmade reach that runs along the northern boundary of Aging Facility, then discharges into the natural channel and ends where it meets another manmade channel built to route floodwater around the North Portal Pad (refer to Section 7.8). Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 20 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). Therefore, the bulked peak flow of 8,650 cfs at flow concentration point CP1 was applied to the entire reach. The incremental flow from the portion of sub-basin D5 that drains to this routing reach was neglected because it is insignificant compared to the flow at CP1.

7.7.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows north of the aging facility for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new flow paths cannot be predicted. For the proposed mitigation designs the flows are directed into existing channels to increase the probability that new channels will not form near the North Portal Pad.

Configuration of Aging Facility

The grading of the Aging Facility is not available on the preliminary sketch for Alternative 2 and it is assumed that it will be partly in cut and partly on fill as in Alternative 1 in order to balance the quantities of excavation and import volumes. Based on the existing topography, it is likely that the northern and western portion of the pad will be in cut. This means that the runoff from sub-basins D3 and ND2 will inundate the Aging Facility in the absence of any diversions.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed along the northern boundary of the Aging Facility (between Station 4055 and 1743 on Figure 7-5) to capture and divert the flow from sub-basins D3 and ND2 to the natural channel east of the pad. This assumption is necessary to ensure that the waste handling facility will not be flooded during the PMF event. The channel is assumed to have a bottom width of 25 feet with 2:1 side slopes. The gradient is steepest at the foothill at 0.091 and flattens to 0.027 along the northern boundary of the Aging Facility, resulting in an average slope of 0.038. The total volume of excavation is about 80,000 cubic yards and the average channel depth is about 16 feet. The volume calculations are included in Attachment 20.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow was assumed at the upstream boundary in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope) with the channel ground surface slope estimated to be 0.099 from the topographic data (refer to Section 4.2.3). Because this routing ends at the other manmade channel CP3CP4, the average of the water surface elevations predicted at Stations 3612 and 3053 of CP3CP4 was used for the downstream boundary.

7.7.3 Results

Table 7-5 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-5. The flow coming down from sub-basins D3 and ND2 will be intercepted by the manmade channel along the northern boundary of the Aging Facility and diverted eastward to the natural drainage. The manmade channel is sized to completely contain the flow such that the Aging Facility will not be inundated regardless of its final design elevation. The flow will be ultimately discharged into the natural channel, which is large enough to convey the water without overtopping according to the model outputs. This means the Aging Facility will stay out of the inundation extent. The complete HEC-RAS output results are included in Attachments 1.17 and 20.

Table 7-5. Flood Inundation Results North of Aging Facility, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
4055	8,650	3,857	18.5	1.23
3929	8,650	3,846	17.4	1.13
3732	8,650	3,827	18.4	1.21
3521	8,650	3,817	15.6	0.98
3407	8,650	3,813	11.5	0.67
3177	8,650	3,806	11.5	0.67
2836	8,650	3,797	11.5	0.67
2576	8,650	3,790	11.5	0.67
2322	8,650	3,783	11.4	0.66
2220	8,650	3,781	11.2	0.64
2044	8,650	3,775	12.7	0.75
1743	8,650	3,768	8.0	0.59
1280	8,650	3,756	9.4	0.67
955	8,650	3,746	10.3	0.73
643	8,650	3,737	9.0	0.62
351	8,650	3,728	10.1	0.76
49	8,650	3,721	6.0	0.39

7.8 AGING FACILITY AND NORTH PORTAL PAD, ALTERNATIVE 2

7.8.2 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing consists of a main river branch extending from the north-west corner of the western aging facility (area FAC2 in the hydrology model) following the western then southern edge of the aging facility then south-east just north of the North Portal Pad (NPP) as shown in Figure 7-6. Cross sections were developed from topographic data described in Section 4.2.3 using Arcview V.3.2 and modified for the surface facilities based on the preliminary layout sketch (Attachment 3). Cross-sections are included in Attachment 21 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used with a bulking factor of 10% as inputs to the HEC-RAS software. Along the aging facilities, i.e., from Station 7795 to Station 4476 (as shown on Figure 7-6), the peak flow at ND1 was used. With a bulking factor of 10% based on the previous report (Ref. 6, pp. 29-30), the flow for this reach is 5,734 cfs. Downstream of the aging facility the flow at CP4 was used which includes additional runoff from FAC2, D5, D3 and ND2 and resulting in a total bulked flow of 15806 cfs (see Figure 5-1 for location of sub-basins).

7.8.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows around the Aging Facility and North Portal Pad for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted. For the proposed mitigation designs the flows are directed into existing channels to increase the probability that new channels will not form near the North Portal Pad.

Properties of Manmade Channel

It is assumed that a manmade channel will be constructed along the western and southern boundaries of the Aging Facility to capture runoff from sub-basins ND2 and ND1 and divert it eastward to flow concentration point CP3 to prevent runoff to the Aging Facility. The channel has an average depth of approximately 25 feet and a bottom width of from 5

feet to 28 feet around the aging facility with 2:1 side slopes. The excavation volume is about 121,500 cubic yards. The volume calculations are included in Attachment 21.

From the Aging Facility east past the North Portal Pad it was assumed that the flow would be transported in a manmade channel to prevent it from flowing onto the North Portal Pad. The channel was assumed to have 2:1 side slopes and a bottom width of 15 feet between Stations 4249 and 40. The average channel depth is about 20 feet, and varies from about 10 feet to 30 feet deep at the deepest location. This channel requires an excavation of approximately 175,000 cubic yards. The volume calculations are included in Attachment 21. The channel is not quite large enough to contain the flow immediately downstream of Exile Hill. Small berms or levees on the order of 3 to 4 feet tall would be needed starting upstream of station 3612 continuing to downstream of Station 3053. Also, the constructed channel will cross several natural drainages. To prevent stormwater runoff from flowing down those drainages, the drainages should be blocked on the downstream side of the manmade channel at each crossing.

Configuration of Aging Facility FAC2

The Aging Facility, as shown on Figure 7-6 is assumed to be protected by a channel running along its western and southern edge. The Aging Facility was assumed to be built at an elevation of 3790. This results in the Aging Facility being in cut west of between Stations 5009 and 5468 and on fill east of this point. The constructed channel was assumed to fade out between Stations 5009 and 4477 where the fill would prevent runoff of storm water runoff. If the Aging Facility is built at an elevation different than 3790 the flood elevations presented in this report will not be affected as long as the fill east of Station 5009 is greater than about 3 feet.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were specified at both boundaries in the HEC-RAS software (i.e., the water surface slope is assumed to follow the channel ground surface slope). The channel ground surface slopes at the downstream and upstream boundaries were estimated from the topographic data described in Section 4.2.3 to be 0.025 and 0.001, respectively.

7.8.2 Results

Table 7-6 presents the best estimate of PMF water surface elevations and flow velocities at each cross with the extent of the inundation shown in Figure 7-6. The man-made

channel is sized to transport the PMF around the North Portal Pad. The exact layout and elevation of the pad will not affect the results as long as the layout remains south and west of the man-made channel and the natural drainage the flood waters discharge into. The complete HEC-RAS output results are included in Attachments 1.18 and 21.

Table 7-6. Flood Inundation Results Around Aging Facility and North Portal Pad, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
7796	5,734	3846	11.0	0.69
7318	5,734	3836	8.8	0.52
6710	5,734	3825	9.3	0.56
6265	5,734	3816	9.4	0.56
5925	5,734	3808	11.0	0.68
5468	5,734	3796	9.2	0.57
5009	5,734	3784	8.7	0.59
4477	5,734	3760	1.3	0.18
4249	15,806	3752	11.2	0.76
3612	15,806	3729	7.9	0.48
3053	15,806	3713	12.4	0.59
2431	15,806	3701	12.0	0.59
2029	15,806	3693	11.8	0.58
1828	16,349	3689	12.1	0.6
1383	16,349	3680	12.2	0.6
968	16,349	3671	13.1	0.66
519	16,349	3659	11.3	0.64
40	16,349	3645	10.5	0.65

7.9 EAST OF NORTH PORTAL PAD, ALTERNATIVE 2

7.9.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

A single branch representing the primary channel east of the North Portal Pad was set up that extends from the downstream end of the manmade channel diverting flow around the North Portal Pad to the gap between Alice Hill and Fran Ridge as shown in Figure 7-7. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 22 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). The channel collects stormwater from the manmade channel that diverts water around the North Portal Pad, as well as distributed runoff from part of sub-basin D6 along its watercourse. Note that the delineation of sub-catchments in sub-basin D6 is not exact because there is no distinct drainage divide in the wash towards the bottom of D6. The area that will drain to this channel was calculated to be 0.204 mi² using ArcGIS V.8.3 (as delineated on Figure 7-7), and the additional bulked flow was calculated by proportioning the area to the total drainage area of sub-basin D6. This amount was added to the bulked flows at flow concentration point CP5 to give a total flow of 17,330 cfs that was used for the entire reach. This is a conservative approach because the peak discharge from sub-basin D6 is unlikely to be concurrent with the peak flow at CP5.

7.9.2 Assumptions

The followings assumptions were used in the HEC-RAS software for routing flows east of the North Portal Pad for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best

estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.025 and 0.028, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

7.9.3 Results

Table 7-7 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-7. Results indicate that the capacity of the natural channel is sufficient to carry the PMF flow upstream of Station 3745, beyond which the flow will spread over the wash and ultimately converge at the gap between Alice Hill and Fran Ridge. Nonetheless, the North Portal Pad will not be inundated by the flow propagating down this primary channel because the overtopping occurs downstream of the pad. The complete HEC-RAS output results are included in Attachments 1.19 and 22.

Table 7-7. Flood Inundation Results for Primary Channel East of North Portal Pad, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
5224	17,330	3,645	15.8	0.82
4776	17,330	3,634	12.8	0.64
4247	17,330	3,618	15.2	0.81
3745	17,330	3,605	12.2	0.65
3207	17,330	3,590	12.7	0.77
2536	17,330	3,572	2.7	0.2
1447	17,330	3,550	4.5	0.42
181	17,330	3,523	7.8	0.64

7.10 DOWNSTREAM OF NORTH PORTAL PAD, ALTERNATIVE 2

7.10.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing consists of a single branch representing the main channel extending from the eastern boundary of North Portal Pad to the gap between Alice Hill and Fran Ridge as shown in Figure 7-8. The objective is to determine the degree of flooding immediately downstream of the North Portal Pad. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and are included in Attachment 23 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used as inputs to the HEC-RAS software, and were increased by a bulking factor that was determined to be 10% in a previous report (Ref. 6, pp. 29-30). The overland flow from sub-basin FAC3 will enter the channel at the upstream boundary with the amount calculated to be 5,170 cfs including bulking. Along the watercourse, the flow will continuously increase due to additional runoff from part of sub-basin D6. The area that will drain to this channel was calculated to be 0.377 mi² using ArcGIS V.8.3 (as delineated on Figure 7-8) by proportioning the area to the total drainage area of sub-basin D6, resulting in a total bulked flow of 6,980 cfs that was applied to the entire reach. This is a conservative approach because the peak flow from FAC3 may not be concurrent with that from sub-basin D6, and in reality the incremental runoff will only reach its peak at the downstream end of the channel.

7.10.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows downstream of the North Portal Pad for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of North Portal Pad

The nominal elevations of the main platform of the North Portal Pad and the balance of plant are 3,666 and 3,635 feet, respectively according to the preliminary sketch for Alternative 2 (Refer to Attachment 3). Both pads are assumed to have a 2 percent slope eastward so that the runoff from Exile Hill along with the runoff from the pads

themselves will be discharged into the natural channel located east of the balance of the plant. This means that the elevation of the balance of plant will vary from 3,647 to 3,623 feet along its edge adjacent to the natural channel. Since no facilities important to safety are located on the balance of plant as identified on the Q list (Ref. 7, p. A-2), it is assumed that no flood protection measures will be provided for this lower pad.

Configuration of Evaporation Pond

The evaporation pond located to the east of the North Portal Pad is assumed to be constructed at grade because no design elevation is given in the layout sketch for Alternative 2. Since it is not a critical facility, it is assumed that no flood protection measures will be provided.

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.030 and 0.024, respectively. The upstream ground slope will actually be modified by the construction of the main platform and will become fairly steep. To be conservative, the natural ground slope was used instead of the slope of the graded fill since the fill gradient is not shown on the preliminary sketch. On the other hand, the actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

7.10.3 Results

Table 7-8 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-8. Results indicate that the floodwater will be piled up against the North Portal Pad along the northeastern edge of the balance of plant based on the assumed pad slope and elevation. However, the balance of plant will be inundated if its northern corner is below 3,539 feet elevation and the inundation limits will be different than that shown in Figure 7-8. Secondly, the evaporation pond is predicted to be inundated with floodwater under the

assumption given above. The complete HEC-RAS output results are included in Attachments 1.20 and 23.

**Table 7-8. Flood Inundation Results Downstream of North Portal Pad,
 Alternative 2**

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
5102	6,980	3,639	7.1	0.65
5018	6,980	3,637	5.3	0.56
4874	6,980	3,632	6.5	0.64
4582	6,980	3,624	5.6	0.54
4340	6,980	3,620	6.2	0.4
4085	6,980	3,612	8.4	0.77
3906	6,980	3,605	9.6	0.71
3687	6,980	3,599	7.6	0.62
3422	6,980	3,593	6.9	0.48
3072	6,980	3,585	9.7	0.71
2608	6,980	3,574	5.7	0.49
2106	6,980	3,563	5.4	0.56
1552	6,980	3,549	5.5	0.55
1026	6,980	3,537	5.1	0.53
557	6,980	3,528	4.5	0.46
56	6,980	3,517	5.5	0.55

7.11 RAILROAD BRIDGE CROSSING, ALTERNATIVE 2

7.11.1 Inputs

Inputs for the HEC-RAS computer software consist of river geometry and inflows.

River Network and Cross Sections

The routing of flow concentrating at CP7 under the proposed railroad was performed using one river reach. Flow was routed along the northern edge of Muck Storage B down to the gap between Alice Hill and Fran Ridge as shown in Figure 7-9. Cross sections were developed from topographic data (refer to Section 4.2.3) using Arcview V.3.2 and the preliminary layout sketch for Alternative 2 (Attachment 3). Cross-sections are included in Attachment 24 to this calculation.

Flows

Inflows needed for the flood inundation analysis were obtained from the PMF analysis for Alternative 2. Peak discharges presented in Table 5-5 were used with a bulking factor as inputs to the HEC-RAS software. With the proposed railroad graded to elevation 3666 feet, the alignment along the southern end of the eastern edge of Muck Storage B would be in cut. Some flow from sub-basin E2 would escape into sub-basin E3 as flow continued north along the railroad until the grade is above the natural ground surface along the eastern edge of the muck storage pile. To be consistent with the PMF analysis described in Section 5, and to be conservative in sizing the two bridges along the railroad alignment north of Muck Storage B, all the runoff from E2 was diverted to CP7 to obtain the maximum flow upstream of the railroad.

From Station 7119 to Station 6220 (as shown on Figure 7-9), flow was estimated to be 2,490 cfs for the peak flow from FAC4 with a bulking factor of 10% based on the previous report (Ref. 6, pp. 29-30). At Station 6028, flow was increased to 22,470 cfs, which accounts for the bulked flow at CP7. The flow was increased to 25,150 cfs (the bulked peak flow at CP8) at Station 3938 to account for additional flow from sub-basin E3.

7.11.2 Assumptions

The following assumptions were used in the HEC-RAS software for routing flows under the railroad for Alternative 2.

Fixed flow path

New flow paths often form during large floods in a wash such as Midway Valley Wash as evident by the numerous channels in Midway Valley Wash that appear to have been formed by historic floods. For the purpose of calculating the PMF water surface elevations, it is assumed that the floodwater will follow the channels used in the HEC-RAS simulations because the formation of new paths cannot be predicted.

Configuration of Muck Storage B

Muck Storage B is assumed to be approximately 20 feet high along the northern boundary and configured so that it does not block the bottom of the channel along its northern edge. This assumption was made because the design of Muck Storage B is not finalized, and this configuration confines the runoff from sub-basins E1 and FAC4 to the northern side of Muck Storage B but still allows flow through the natural channel. The presence of Muck Storage B results in a conservatively high estimate of water surface elevations near the railroad so that the bridge opening can be properly sized to prevent flow from impinging on the North Portal Pad.

Configuration of Structure Shown in Floodplain

It was assumed that the Visitors Center shown on the preliminary layout sketch (Attachment 3) to be located at the base of Fran Ridge would not be protected from the PMF because it is not important to safety, as defined on the Q List (Ref. 7, p. A-2). Therefore, it could be within the flood inundation surface shown in Figure 7-9.

Bridge Openings

Nominal bridge dimensions were assumed because the bridge design had not been developed at the time this analysis was conducted.

The bridge over the realignment of "H" Road was assumed to be 60 feet long and 190 feet wide in the direction of flow. These dimensions were assumed to allow traffic to pass under the bridge, and to allow for grading of the railroad alignment. It was assumed to be a clear span without any piers. The bridge deck was assumed to be 6 feet thick, as assumed in the previous study (Ref. 6, p. 26).

The bridge across the natural channel at CP7, just north of Muck Storage B, was assumed to be 90 feet long, in order to adequately convey the PMF, and 190 feet wide, to allow for grading of the railroad alignment. It was assumed that there would be one row of 4-foot diameter piers down the center of the channel. The bridge deck was assumed to be 6 feet thick. These dimensions are consistent with a typical concrete freeway bridge, as assumed in the previous study (Ref. 6, p. 26).

Manning's Roughness Coefficient

Manning's roughness coefficient of 0.09 was used in the previous report (Ref. 6, pp. 28-29) for both the main channel and the floodplains in the HEC-RAS software to evaluate energy loss due to friction under the high sediment transport conditions. This best estimate value was adopted in this calculation because it provides a conservatively high, yet realistic, estimate of water surface elevations that may occur during a PMF event.

Boundary Conditions

Boundary conditions are required at the upstream and downstream boundaries to allow for both supercritical and subcritical flow conditions within the river reach. Normal flow conditions were assumed at both boundaries in the HEC-RAS software (i.e., the water surface slope follows the channel ground surface slope). The channel ground surface

slopes at the upstream and downstream boundaries were estimated from the topographic data (refer to Section 4.2.3) to be 0.05 and 0.028, respectively. The actual downstream boundary is probably different than the normal flow conditions because the water surface elevation is also governed by the other streams merging at the gap. However, the impact of the downstream condition will not extend very far upstream (on the order of a few hundred feet) in consideration of the gradient of the channel, which means the inundation results will be essentially unaffected by this assumption.

7.11.3 Results

Table 7-9 presents the best estimate of PMF water surface elevations and flow velocities at each cross section, with the extent of the inundation shown in Figure 7-9. Results indicate that the PMF flow will not impinge on the North Portal Pad, assuming that the two bridge openings are approximately as large as stated above. Therefore, the North Portal Pad will remain outside of the floodplain boundary. If both bridges are constructed as clear spans, the water surface elevations from the bridges to as far upstream as Station 6570 would be nearly 3 feet lower. The complete HEC-RAS output results and the output table for this clear span scenario are included in Attachment 1.21 and Attachment 24 to this calculation.

Table 7-9. Flood Inundation Results Near Railroad Bridge Crossing, Alternative 2

Station	Peak PMF Flow (cfs)	Water Surface Elevation (ft)	Velocity (ft/s)	Froude No.
7119	2,486	3,659	5.6	0.75
6858	2,486	3,650	3.8	0.45
6570	2,486	3,647	0.6	0.03
6220	2,486	3,647	0.3	0.01
6028	22,470	3,647	2.2	0.08
5846	22,470	3,647	1.4	0.05
5681	22,470	3,647	1.0	0.03
5580	Bridge			
5477	22,470	3,617	25.4	2.6
5139	22,470	3,614	8.4	0.58
4765	22,470	3,606	8.2	0.62
4344	22,470	3,597	6.6	0.49
3938	25,150	3,590	7.2	0.53
3332	25,150	3,583	5.6	0.33
2846	25,150	3,575	10.0	0.62
2361	25,150	3,566	8.2	0.51
1910	25,150	3,558	10.2	0.61
1377	25,150	3,551	7.3	0.36
826	25,150	3,537	12.4	0.8
479	25,150	3,529	7.1	0.41
171	25,150	3,522	10.4	0.68

7.12 SOUTH PORTAL, ALTERNATIVE 2

The layout at the South Portal is the same between Alternatives 1 and 2 as shown on the sketches included as Attachment 3 to this calculation. Therefore, the PMF water surface elevations and the resulting inundation surface presented in Section 6.10 are also valid for Alternative 2. In essence, the South Portal is outside the inundation limits based on the results of the HEC-RAS software.

7.13 INTAKE AND EXHAUST SHAFTS, ALTERNATIVE 2

The major changes between Alternatives 1 and 2 are the configuration of the North Portal Pad and Aging Facilities. As such, the analysis conducted for the intake and exhaust shafts as presented in Section 6.11 for Alternative 1 is also valid for Alternative 2. That is, the average depth over the shaft pad is about 0.2 feet.

7.14 SCOUR ANALYSIS, ALTERNATIVE 2

Although the railroad alignment has not changed from Alternative 1, scour analysis was conducted for Alternative 2 because the flow dynamics are slightly altered with different discharges and bridge opening configuration. The scour calculations for Alternative 2 are included in Attachment 25. Similar to Alternative 1, no contraction scour is predicted to occur as the mean velocity immediately upstream of the bridge of 1.0 ft/s is substantially lower than the critical velocity for initiation scour of 2.9 to 4.3 ft/s (Ref. 6, p.43). On the other hand, the local scour depths at piers, estimated using the CSU equation (Ref. 17, Eq. 6.3, p. 6.4), are slightly larger at 4.4 and 2.9 feet for the bridges located immediately north of Muck Storage B and at H-road, respectively.

8 CONCLUSIONS AND LIMITATIONS

8.1 CONCLUSIONS FOR FLOOD INUNDATION ANALYSES

Hydrologic and hydraulic analyses were conducted for storm water runoff from a Probable Maximum Precipitation (PMP) event at the Yucca Mountain site for two alternative configurations of the surface facilities. Sections 4 and 5 of the report describe the rainfall and runoff generated for Alternatives 1 and 2, respectively. The flows generated from the PMP (i.e., the Probable Maximum Flood (PMF)) were routed around critical facilities to determine water surface elevations at critical locations. Outputs from the computer software are considered reasonable based on the input data.

Figure 6-1 shows the inundation at the North Portal Pad for Alternative 1 during a PMF event without implementing any mitigation measures. Because of the critical nature of the facilities near the North Portal Pad and vicinity, mitigation measures were designed that eliminated flooding at the facility. Sections 6-3 through 6-10 describe the hydraulic analyses and mitigations when required for Alternative 1. The mitigation measures consist mainly of large drainage channels that direct flows away from critical facilities, and their properties are summarized in Table 8-1. It should be emphasized that the channel dimensions are intended for use in the hydraulic analysis presented in this report, and not meant to replace detailed design that will be required at the project's final design stage. In the case of drainage just north of the North Portal Pad, in addition to the option of a drainage channel, the option of a floodwall or levee was also studied. The total volume of excavation required for all the manmade channels to prevent flooding at the North Portal Pad is about 442,000 cubic yards. For the diversion just north of the North Portal Pad about 200,000 yards of excavation could be eliminated by constructing a 3,200-foot long levee ranging from 2 to 12 feet high, excluding freeboard. The combined inundation surfaces for the critical facilities near the North Portal Pad and vicinity under Alternative 1 are shown on Figure 8-1.

Similar inundation results at the North Portal Pad are anticipated for Alternative 2 in the absence of any mitigation measures because the pad is in the same general location and the elevation of the final grade is lower. Therefore, mitigation measures were included in the hydraulic analyses when required, as presented in Sections 7-3 through 7-12 for Alternative 2. Table 8-2 summarizes the properties of the manmade channels designed to divert flows away from the critical facilities. Additional manmade channels are needed to route flows around Aging Pads 2 and 3. Note that the larger channel for diverting flows around Muck Storage A is not due to the differences between Alternatives 1 and 2, but the premise that the muck pile is not yet constructed and thus there is no barrier on the downhill side. It should also be emphasized that the channel dimensions are intended for use in the hydraulic analysis presented in this report, and not meant to replace detailed design that will be required at the project's final design stage. The total volume of excavation required for all the manmade channels to prevent flooding at the North Portal Pad is about 442,000 cubic yards. The combined inundation surfaces for the critical

facilities near the North Portal Pad and vicinity under Alternative 2 are shown on Figure 8-2.

Results of these analyses are appropriate for the intended use of the study as stated under Section 1 of this report.

Table 8-1. Summary of Manmade Channels for Diversion of Flows Away From Critical Facilities, Alternative 1

Manmade Channel	Starting Station	Ending Station	Length (ft)	Slope (ft/ft)	Bottom Width (ft)	Side Slope (h:1)	Volume of Excavation (CY)
Diversion around Muck Storage A	16740	13227	3514	0.0026	10	2	68,000
East of Optional Aging Facility – Reach 1	5460	5105	355	0.0197	25	2	9,000
East of Optional Aging Facility – Reach 2	2480	224	2256	0.022	25	2	80,000
Aging Facility	5838	3864	1974	0.034	35	2	85,000
North Portal Pad	3684	66	3618	0.027 (average)	30-35	2	200,000
Total Volume							442,000

Table 8-2. Summary of Manmade Channels for Diversion of Flows Away From Critical Facilities, Alternative 2

Manmade Channel	Starting Station	Ending Station	Length (ft)	Slope (ft/ft)	Bottom Width (ft)	Side Slope (h:1)	Volume of Excavation (CY)
Diversion around Muck Storage A	16814	13175	3639	0.0065	25	2	195,000
Diversion around Aging Pad 3	9975	7652	2323	0.039	10	2	25,000
Diversion around Aging Pad 2	4432	3408	1024	0.007	10	2	15,000
Northern boundary of Aging Facility	4055	1743	2312	0.038	25	2	80,000
Western and southern boundaries of Aging Facility	7796	4477	3319	0.024	15	2	121,500
North Portal Pad	4249	40	4209	0.027	15	2	175,000
Total Volume							611,500

8.2 LIMITATIONS

As pointed out in the assumption for the flood routing analyses, new flow paths may be opened up during a PMF event because of the unconsolidated nature of sediments in

Midway Valley Wash. However, since a rigid channel bed is implicitly assumed in the HEC-RAS software and the formation of new paths cannot be predicted with the current state-of-the-technology, there is uncertainty in the estimate of flow propagation and hence the flood inundation extents.

The scour analysis presented in Sections 6-12 and 7-14 assumed uniform soil property with depth but in reality, the erosion may stop if a harder stratum is encountered depending on the erodibility of the bed material. This means that the scour depth could have been overestimated.

The effect of wind waves has not been included in this analysis. The transitory nature of the flooding, short fetch distance, and relatively shallow water depth make additional height of water from wind action very minimal.

9 REFERENCES

1. AP-3.12Q, Rev. 2, ICN 2. *Design Calculations and Analyses*. Washington, D.C.: U.S. Department of Energy, Office of Civilian Radioactive Waste Management. ACC: DOC.20040318.0002.
2. LP-SI.11Q-BSC, Rev. 0, ICN 0. *Software Management*. Washington, D.C.: U.S. Department of Energy, Office of Civilian Radioactive Waste Management. ACC: DOC.20040225.0007.
3. Brunner, G.W. 1997. *HEC-RAS River Analysis System Hydraulic Reference Manual*. Version 2.0. Davis, California: U.S. Army Corps of Engineers, Hydrologic Engineering Center. TIC: 243256
4. BSC (Bechtel SAIC Company) 1999. *Software Code: HEC-1*. V4.0. 30078-V4.0.
5. BSC (Bechtel SAIC Company) 1999. *Software Code: HEC-RAS*. V2.1. 30079-V2.1.
6. BSC (Bechtel SAIC Company) 2002. *Preliminary Hydrologic Engineering Studies for the North Portal Pad and Vicinity*. ANL-EBS-MD-000060 REV 00. Las Vegas, Nevada: Bechtel SAIC Company. ACC: MOL.20021028.0123.
7. BSC (Bechtel SAIC Company) 2003. *Q-List*. TDR-MGR-RL-000005 REV 00. Las Vegas, Nevada: Bechtel SAIC Company. ACC: DOC.20030930.0002.
8. Chow, V.T. 1959. *Open-Channel Hydraulics*. New York, New York: McGraw-Hill. TIC: 233922.
9. CRWMS M&O 2000. *User's Manual for ARC/INFO 7.2.1*. SDN: 10033-UM-7.2.1-00. Las Vegas, Nevada: CRWMS M&O. ACC MOL.20020129.0112.
10. CRWMS M&O 2000. *Software Code: ARC/INFO*. V7.2.1. SGI Irix. 10033-7.2.1-00.
11. DOE (U.S. Department of Energy) 2004. *Quality Assurance Requirements and Description*. DOE/RW-0333P, Rev. 14. Washington, D.C.: U.S. Department of Energy, Office of Civilian Radioactive Waste Management. ACC: DOC.20040331.0004.
12. Duncan, W.; Huntley, C.; Hokenstrom, J.; Cudworth, A.; McDaniel, T.; Blair, H.; Bartlett, S.; Hatcher, R.; Boggs, H.; Hennig, C.; Rhone, T.; Gersch, W.; Yocom, L.; Warren, H.; Achterberg, D.; Trieste, D.; Strand, R.; Pemberton, E.; Simmonds, R.; Hart, J.; Wright, R.; and Restad, R. 1987. *Design of Small Dams*. 3rd Edition. Denver, Colorado: U.S. Department of the Interior, Bureau of Reclamation. TIC: 242958.

13. FEMA (Federal Emergency Management Agency) 2001. "Hydraulic Models Accepted by FEMA for NFIP Usage." [Washington, D.C.]: Federal Emergency Management Agency. Accessed November 27, 2001. TIC: 251302.
http://www.fema.gov/mit/tsd/en_hydra.htm
14. Hansen, E.M.; Schwarz, F.K.; and Riedel, J.T. 1977. *Probable Maximum Precipitation Estimates, Colorado River and Great Basin Drainages*. Hydrometeorological Report No. 49. Silver Spring, Maryland: U.S. Department of Commerce, National Oceanic and Atmospheric Administration. TIC: 220224.
15. MO0002SPATOP00.001. Topographic Grid Data. Submittal data: 02/24/2000.
16. MO9906COV98462.000. Coverage: TOPO2FTS. Submittal date: 06/07/1999.
17. Richardson, E.V. and Davis, S.R. 2001. *Evaluating Scour at Bridges*. 4th Edition. FHWA NHI 01-001. Hydraulic Engineering Circular No. 18. Washington, D.C.: Federal Highway Administration, National Highway Institute. ACC MOL.20040318.0075.
18. U.S. Army Corps of Engineers. 1990. *HEC-1, Computer Program, User's Manual*. CPD-1A, Version: 4.0. Davis, California: U.S. Army Corps of Engineers. TIC: 243325.
19. USDA (U.S. Department of Agriculture) 1986. "Estimating Runoff." *Urban Hydrology for Small Watersheds*. TR-55. [Washington, D.C.]: U.S. Department of Agriculture. ACC: MOL.20040217.0018
20. Viessman, W. Jr; Knapp, J.W.; Lewis, G.L. and Harbaugh, T.E. 1977. *Introduction to Hydrology*. 2nd Edition. Series in Civil Engineering. New York, New York: Harper & Row. TIC: 242946.
21. CRWMS M&O 1999. *Software Qualification Report for HEC-1 V4.0*. CSCI: 30078 V4.0 DI: 30078-2003, Rev. 01. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19990521.0220.
22. CRWMS M&O 1999. *Software Qualification Report HEC-RAS V2.1*. CSCI: 30079 V2.1 DI: 30079-2003, Rev. 01. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.19990521.0221.
23. CRWMS M&O 2000. *Validation Test Report for ARC/INFO*. SDN: 10033-VTR-7.2.1-00. Las Vegas, Nevada: CRWMS M&O. ACC: MOL.20020129.0113

10 ATTACHMENTS

There are a total of 27 attachments to this calculation listed as follows. Refer to Table 10-1 for the detailed listing of contents in Attachment 1. Note that the cover sheet is included in each attachment.


No.	No. of Pages	Content
1	1	CD containing electronic files
2	5	Correspondence with SCM
3	4	Layout Sketches of Alternatives 1 and 2
4	4	PMP Calculations for South Portal
5	3	Hydrology Calculations for Alternatives 1 and 2
6	18	Hydraulic Calculations for No Mitigation Scenario, Alternative 1
7	14	Hydraulic Calculations for Routing Around Muck Storage A, Alternative 1
8	6	Hydraulic Calculations for Routing Downstream of Muck Storage A, Alternative 1
9	16	Hydraulic Calculations for Routing Around Optional Aging Facility and North Construction Portal, Alternative 1
10	20	Hydraulic Calculations for Routing Around Aging Facility and North Portal Pad, Alternative 1
11	7	Hydraulic Calculations for Routing East of North Portal Pad, Alternative 1
12	6	Hydraulic Calculations for Routing Downstream of North Portal Pad, Alternative 1
13	10	Hydraulic Calculations for Routing Near Railroad Bridge Crossing, Alternative 1
14	17	Hydraulic Calculations for South Portal Routings, Alternative 1
15	2	Scour Analysis, Alternative 1
16	14	Hydraulic Calculations for Routing Around Muck Storage A, Alternative 2
17	16	Hydraulic Calculations for Routing Around Aging Pad 3, Alternative 2
18	12	Hydraulic Calculations for Routing Around Aging Pad 2, Alternative 2
19	7	Hydraulic Calculations for Routing Around North Construction Portal, Alternative 2
20	14	Hydraulic Calculations for Routing North of Aging Facility, Alternative 2
21	14	Hydraulic Calculations for Routing Around Aging Facility and North Portal Pad, Alternative 2
22	6	Hydraulic Calculations for Routing East of North Portal Pad, Alternative 2

No.	No. of Pages	Content
23	8	Hydraulic Calculations for Routing Downstream of North Portal Pad, Alternative 2
24	13	Hydraulic Calculations for Routing Near Railroad Bridge Crossing, Alternative 2
25	2	Scour Analysis, Alternative 2
26	5	Checker's Alternate Calculations for PMF

Table 10-1. List of Electronic Files Included in Attachment 1




Directory	File name	Size (kilobyte)	Time	Date	Originator	Checker
1.01	urssurf.e00	108,524	9:51 am	11/10/2003	Matthew Knopp	Douglas Wright
1.02	FINAL.out	117	4:37 pm	3/1/2004	Vivian Lee	Jeanne Hudson
1.03	ALT2.out	121	4:00 pm	2/18/2004	Vivian Lee	Jeanne Hudson
1.04	Exist2.rep	87	4:31 pm	3/1/2004	Jeanne Hudson	Vivian Lee
1.05	cp2cp6.rep	29	9:21 am	12/8/2003	Vivian Lee	Jeanne Hudson
1.06	fac1.rep	29	1:59 pm	11/24/2003	Vivian Lee	Jeanne Hudson
1.07	fac2.rep	31	2:08 pm	11/24/2003	Vivian Lee	Jeanne Hudson
1.08	nppq.rep	82	10:25 am	12/12/2003	Phillip Mineart	Jeanne Hudson
1.08	nppq-levee.rep	41	9:41 am	12/12/2003	Phillip Mineart	Jeanne Hudson
1.09	cp5.rep	28	3:00 pm	11/24/2003	Vivian Lee	Jeanne Hudson
1.10	fac3.rep	20	3:55 pm	11/24/2003	Vivian Lee	Jeanne Hudson
1.11	underrr.rep	63	4:26 pm	3/1/2004	Jeanne Hudson	Vivian Lee
1.12	sportal1.rep	29	6:08 pm	11/26/2003	Vivian Lee	Jeanne Hudson
1.12	sportal2.rep	19	6:04 pm	11/26/2003	Vivian Lee	Jeanne Hudson
1.12	sportal3.rep	18	9:23 am	12/8/2003	Vivian Lee	Jeanne Hudson
1.13	a2_cp2cp6.rep	35	5:48 pm	2/19/2004	Vivian Lee	Jeanne Hudson
1.14	a2_d7cp6.rep	40	11:35 am	2/24/2004	Vivian Lee	Jeanne Hudson
1.15	a2_d8cp5.rep	31	5:49 pm	2/26/2004	Vivian Lee	Jeanne Hudson
1.16	a2_d3.rep	21	2:13 pm	2/13/2004	Vivian Lee	Jeanne Hudson
1.17	a2_nd2cp3.rep	32	3:34 pm	2/25/2004	Vivian Lee	Jeanne Hudson
1.18	a2_npp.rep	1,009	3:07 pm	2/27/2004	Phillip Mineart	Jeanne Hudson
1.19	a2_cp5.rep	20	10:10 am	2/26/2004	Vivian Lee	Jeanne Hudson
1.20	a2_fac3.rep	34	2:17 pm	2/26/2004	Vivian Lee	Jeanne Hudson
1.21	rr_alt2.rep	65	12:25 pm	3/1/2004	Jeanne Hudson	Vivian Lee
1.22	800-P00-TUN0-00701-000-00A.jpg	4,280	2:02 pm	9/16/2003	Vivian Lee	N/A
						See note in Block 8 on page 2 of the cover sheet.


Note: The file sizes and times may vary with operating system.
 The name of the directory is the same as the attachment number.



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Railroad Alignment
-  Flow Concentration Points
-  Watershed Boundaries




Yucca Mountain
Project # 18839594

Delineation of Sub-basins
for HEC-1 Model,
Alternative 1

Figure
4-1


Figure 4-2. Schematic Diagram of Watershed Network, Alternative 1




Legend

- Sub-basin
- Flow Concentration Point
- Natural/Manmade Channel

Figure 4-3. PMP Hyetograph for the South Portal
(3-minute interval)






Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend




Streams used in HEC-1 Model




	Yucca Mountain	Delineation of Sub-basins for HEC-1 Model, Alternative 2	Figure 5-1
	Project # 18839594		

Figure 5-2. Schematic Diagram of Watershed Network, Alternative 2



Legend


- Sub-basin
- Flow Concentration Point
- Natural/Manmade Channel



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

- Watershed Boundaries
- Inundation Surface
- Elevation Contours (for Presentation Purposes Only)
- 25 ft. Interval
- 5 ft. Interval




Yucca Mountain
Project # 18839594

Inundation Surface
for No Mitigation Scenario,
Alternative 1






Figure
6-1


URS Corporation L:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev000_2004\A1_T1\Inundation_Surface_for_No_Mitigation_Scenario.mxd Date: 3/2/2004 1:04:33 PM Name: dhwgtho





Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Sub-catchment Area
-  Inundation Surface
- Elevation Contours**
(for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval










	Yucca Mountain	Inundation Surface Around Muck Storage A, Alternative 1	Figure 6-2
	Project # 18839594		



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Sub-catchment Area
-  Inundation Surface
-  Elevation Contours (for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval




Yucca Mountain
Project # 18839594

Inundation Surface Downstream
of Muck Storage A,
Alternative 1






Figure
6-3

URS Corporation L:\Projects\Yucca_Mtn_Hydr_18839594\MXD\Rev00C_2004\A1_11\Inundation Surface Downstream of Muck Storage A.mxd Date: 3/2/2004 1:33:10 PM Name: dhwg90




Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches


Legend

-  Watershed Boundaries
-  Inundation Surface
-  Elevation Contours (for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval



	Yucca Mountain	Inundation Surface East of Optional Aging Facility and Around North Construction Portal, Alternative 1	Figure 6-4
	Project # 18839594		


URS Corporation L:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev00C_2004\Alt_1\Inundation Surface East of Optional Aging Facility.mxd Date: 3/2/2004 1:41:24 PM Name: dhwng90



Yucca Mountain
Project # 18839594

Inundation Surface Near Aging Facility and North Portal Pad (Channel Alternative), Alternative 1


Figure 6-5



Yucca Mountain
 Project # 18839594

Inundation Surface Near Aging Facility
 and North Portal Pad (Wall Alternative),
 Alternative 1

Figure
 6-6




Legend

- Watershed Boundaries
- Sub-catchment Area
- Inundation Surface

Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches


- Elevation Contours**
(for Presentation Purposes Only)
- 25 ft. Interval
- 5 ft. Interval



Yucca Mountain
Project # 18839594

Inundation Surface
East of North Portal Pad,
Alternative 1


Figure
6-7



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

- Watershed Boundaries
- Sub-catchment Area
- Inundation Surface
- Elevation Contours**
(for Presentation Purposes Only)
- 25 ft. Interval
- 5 ft. Interval




Yucca Mountain
Project # 18839594

Inundation Surface
Downstream of North Portal Pad,
Alternative 1






Figure
6-8


URS Corporation L:\Projects\Yucca_Min_Hydro_18839594\MXD\Rev00C_2004\A1_11\Inundation Surface Downstream of North Portal Pad.mxd Date: 3/2/2004 1:58:38 PM Name: dhwnght



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Inundation Surface
-  Elevation Contours
(for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval




Yucca Mountain
Project # 18839594

Inundation Surface Near
Railroad Bridge Crossing,
Alternative 1




Figure
6-9



URS Corporation L:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev00C_2004\A1_1.mxd Inundation Surface Near Railroad Bridge Crossing.mxd Date: 3/2/2004 3:18:48 PM Name: dhwg90



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Sub-catchment Area
-  Inundation Surface


- Elevation Contours
(for Presentation Purposes Only)
-  25 ft. Interval
 -  5 ft. Interval



Yucca Mountain
Project # 18839594




Inundation Surface Around
South Portal, Alternative 1


Figure
6-10



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches
 Topographic information shown for presentation purposes only.


Legend

-  Railroad Alignment
-  Watershed Boundaries
-  Intake/Exhaust Shaft Location (see Attachment 1.22)






	Yucca Mountain	Intake and Exhaust Portals, Alternative 1	Figure 6-11
	Project # 18839594		

URS Corporation L:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev00C_2004\AI_1\Intake and exhaust portals.mxd Date: 3/2/2004 3:35:14 PM Name: dhwg90





Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend


-  Watershed Boundaries
-  Sub-catchment Area
-  Inundation Surface


Elevation Contours
(for Presentation Purposes Only)

-  25 ft. Interval
-  5 ft. Interval

0 500 1,000 2,000 3,000 4,000 Feet








	Yucca Mountain	Inundation Surface Around Muck Storage A , Alternative 2	Figure 7-1
	Project # 18839594		



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Sub-catchment Area
-  Inundation Surface
- Elevation Contours (for Presentation Purposes Only)**
 -  25 ft. Interval
 -  5 ft. Interval

0 500 1,000 2,000 3,000 4,000 Feet




URS

Yucca Mountain
Project # 18839594





Inundation Surface Around
Aging Pad 3, Alternative 2

Figure
7-2




Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend


-  Watershed Boundaries
-  Inundation Surface
- Elevation Contours**
(for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval

0 250 500 1,000 1,500 2,000 Feet








	Yucca Mountain	Inundation Surface Around Aging Pad 2, Alternative 2	Figure 7-3
	Project # 18839594		

URS Corporation L:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev00C_2004\Alt_2\around Aging Pad 2 for Alternative 2.mxd Date: 3/2/2004 4:03:19 PM Name: dhwg90



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches


Legend

-  Watershed Boundaries
-  Inundation Surface
-  Elevation Contours
(for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval

0 500 1,000 2,000 3,000 4,000 Feet




	Yucca Mountain	Inundation Surface near North Construction Portal, Alternative 2	Figure 7-4
	Project # 18839594		



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches


Legend

-  Watershed Boundaries
-  Inundation Surface
-  Elevation Contours (for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval








URS	Yucca Mountain	Inundation Surface North of Aging Facility, Alternative 2	Figure 7-5
	Project # 18839594		

URS Corporation L:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev00C_2004\A1_2\Inundation Surface North of Aging Facility Alternative 2.mxd Date: 3/2/2004 4:23:05 PM Name: drawing0



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches


Legend

-  Watershed Boundaries
-  Inundation Surface
-  Elevation Contours
(for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval

0 500 1,000 2,000 3,000 4,000 Feet






	Yucca Mountain	Inundation Surface Around Aging Facility and North Portal Pad, Alternative 2	Figure 7-6
	Project # 18839594		



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Sub-catchment Area
-  Inundation Surface

Elevation Contours
(for Presentation Purposes Only)


-  25 ft. Interval
-  5 ft. Interval

0 500 1,000 2,000 3,000 4,000 Feet






	Yucca Mountain	Inundation Surface East of North Portal Pad, Alternative 2	Figure 7-7
	Project # 18839594		

I:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev00C_2004\Alt_2\East of North Portal Pad for Alternative 2.mxd Date: 3/2/2004 4:28:34 PM Name: dharab00






Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Sub-catchment Area
-  Inundation Surface

Elevation Contours
(for Presentation Purposes Only)


-  25 ft. Interval
-  5 ft. Interval



Yucca Mountain
Project # 18839594


Inundation Surface Downstream
of North Portal Pad, Alternative 2

Figure
7-8




Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend







	Yucca Mountain	Inundation Surface for Railroad Bridge Crossing, Alternative 2	Figure 7-9
	Project # 18839594		



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches

Legend

-  Watershed Boundaries
-  Inundation Surface

- Elevation Contours
(for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval




Yucca Mountain
Project # 18839594

Combined Inundation Surfaces
Near North Portal Pad and Vicinity,
Alternative 1

Figure
8-1

URS Corporation L:\Projects\Yucca_Mtn_Hydro_18839594\MXD\Rev00C_2004\A1_1\Ssummary Inundation Surfaces.mxd Date: 3/2/2004 11:41:07 AM Name: dhwright0



Note: Please Refer to Attachment 3 for Full-size Version of Layout Sketches
 The inundation surface near the South Portal Pad is unchanged from Alternative 1 and is shown on Figure 8-1.

Legend

-  Watershed Boundaries
-  Inundation Surface
- Elevation Contours**
(for Presentation Purposes Only)
-  25 ft. Interval
-  5 ft. Interval

0 500 1,000 2,000 3,000 4,000 Feet



Yucca Mountain

Project # 18839594

Combined Inundation Surfaces
 Near North Portal Pad and Vicinity,
 Alternative 2

Figure
 8-2

**Attachment 1: CD ontaining electronic files
(Document ID: 000-00C-CD04-00100-000-00A)**

Attachment 2: Correspondence with SCM
(Document ID: 000-00C-CD04-00100-000-00A)



"Jeffery
Mason/YM/RWDOE"
<Jeffery_Mason@Notes.YMP.GOV>

To: Susan_Olig@urscorp.com
cc: Vivian_Lee@urscorp.com, "Lyle Southworth/YM/RWDOE"
<Lyle_Southworth@ymp.gov>
Subject: Re: Use of ARCVIEW v. 3.2 and ArcInfo v. 8 for hydrologic analysis

10/09/2003 07:59 AM

Susan,

After discussing this with SCM management it was determined that using these codes under the 2.1.6 exemption is acceptable, as long as the last sentence, "The solution must be documented in sufficient detail in a technical product to allow an independent reviewer to reproduce or verify the results by visual inspection or hand calculation without recourse to the originator." SCM would only recommend that you seek a third party, not associated with this technical product, to review and see if the work done with these programs meets the definition of the exemption.

Please let me know if you need anything else.

Jeff

Susan_Olig@URSCorp.com on 10/08/2003 04:18:15 PM

To: Jeffery_Mason@notes.ymp.gov
cc: Vivian_Lee@URSCorp.com
Subject: Use of ARCVIEW v. 3.2 and ArcInfo v. 8 for hydrologic analysis
User Filed as: Not Categorized in ERMS

-----|
|
|
| If this external e-mail is a record and you are the first OCRWM
recipient, click |
| the 'File to ERMS' button in the toolbar to categorize this
e-mail

Jeff,
I tried calling you about this but must have an old number! (702-295-5547). Hopefully Vivian has provided you with enough info below. She should be in on the call and her number is 510-874-1733. I will be out of the office on Th and F but can still participate in a call from home on Th between 8 and 10 or between 11:45 and 2:30 (home phone is 925-229-2909). Alternatively, you can just do the call with Vivian or I'll

be back in on Monday.

By the way, Vivian can do a conference call from our office and patch both you and I in, as well as a few others if you don't want to go to the hassle of setting up a bridge number. However, we need the phone numbers.

thanks,
susan

Susan S. Olig, R.G.
Sr. Project Geologist
Seismic Hazards Group
URS Corporation
500 12th Street, Suite 200
Oakland, CA 94607-4014

ph: 510-874-1729
fax: 510-874-3268
email: susan_olig@urscorp.com

----- Forwarded by Susan Olig/Oakland/URSCorp on 10/08/2003 03:58 PM -----

Vivian Lee

10/07/2003 04:19 PM
Mason/YM/RWDOE" <Jeffery_Mason@Notes.YMP.GOV>
Subject: Use of ARCVIEW v. 3.2 and ArcInfo v. 8 for hydrologic analysis
(Document link: Susan Olig)

To:
Susan_Olig@urscorp.com
cc: "Jeffery
Subject: Use of ARCVIEW v.
3.2 and ArcInfo v. 8 for hydrologic analysis
(Document link: Susan Olig)

Hi Susan,

We use ARCVIEW v. 3.2 and ArcInfo v. 8 for pre- and post-processing of data that are used in or generated by a qualified software (HEC-RAS) to calculate water surface elevations.

Specifically, ARCVIEW v.3.2 has been used to extract elevation data from a digital elevation model (DEM) by querying information along user-defined lines.

Several functions have been utilized in ArcInfo v.8:

- (1) Calculate area of watersheds which are defined as polygons;
- (2) Calculate length of streams which are defined as lines;
- (3) Present output from HEC-RAS graphically to show inundation boundaries.

I hope this helps in clarifying how the software are used in our analysis.

Vivian

"Jeffery
Mason/YM/RWDOE" To:
Susan_Olig@urscorp.com
<Jeffery_Mason@Not cc:

Vivian_Lee@urscorp.com
es.YMP.GOV>
3.2 COTS?

Subject: Re: Is ARCVIEW v.

10/07/2003 02:32
PM

Susan,

Good to hear from you again! The questions you have posed have been argued back and forth quite extensively and the final decision came down to how the software was being used. If you could provide me a more detailed explanation as to what the software is being used to support. I will have SCM management review it and I'll put together a conference call to provide you an informed direction.

Jeff

Susan_Olig@URSCorp.com on 10/07/2003 09:44:50 AM

To: Jeffery_Mason@notes.ymp.gov
cc: Vivian_Lee@URSCorp.com
Subject: Is ARCVIEW v. 3.2 COTS?

User Filed as: Not Categorized in ERMS

-----|

|
|
| If this external e-mail is a record and you are the first OCRWM recipient, click |
| the 'File to ERMS' button in the toolbar to categorize this e-mail |

-----|

Hi Jeff,
Would ARCVIEW v. 3.2 be considered COTS (Commercial off the shelf software)? How about ARCINFO v. 8? I was guessing it would be, but on



checking the SBR for week ending 7-25-03, I noticed that ARCINFO v. 7.2.1 is baselined, which made me wonder, because if its COTS, why was that version qualified?

We have some hydrologists using it for some Q calculations (generating cross sections and calculating areas for input into an analysis) and they were thinking its COTS that does not need to be qualified as per section 2.1.6 of the Software Management procedure. Is that correct?
thanks,
susan

Susan S. Olig, R.G.
Sr. Project Geologist
Seismic Hazards Group
URS Corporation
500 12th Street, Suite 200
Oakland, CA 94607-4014

ph: 510-874-1729
fax: 510-874-3268
email: susan_olig@urscorp.com

**Attachment 3: Layout Sketches of Alternatives 1 and 2
(Document ID: 000-00C-CD04-00100-000-00A)**




LEGEND

AREA No.	DESCRIPTION
17A	AGING (1000 MTHM)
17B	AGING (5,000 MTHM) FUTURE
17C	SHIELDED CANISTER FACILITY (SCF) FUTURE
110	DRY TRANSFER FACILITY #1 (DTF-1)
120	DRY TRANSFER FACILITY #2 (DTF-2)
130	REMEDIATION BLDG (RB)
14A	TRANSPORTATION CASK RECEIPT BUILDING (TCRB)
14B	TRANSPORTATION CASK BUFFER STORAGE AREA (30 DAYS)
150	WASTE PACKAGE RECEIPT BUILDING (WPRB)
160	LOW LEVEL WASTE HANDLING (LLWH)
180	DRY TRANSFER FACILITY #3 (DTF-3) FUTURE
190	CANISTER HANDLING FACILITY (CHF)
220	HEAVY EQUIPMENT MAINTENANCE BUILDING (HEMB)
230	EQUIPMENT MAINTENANCE/WAREHOUSE BUILDING (EMWB)
25A	UTILITY BUILDING
25B	COOLING TOWER
25C	EVAPORATION POND
260	ELECTRICAL GENERATORS AND SWITCH HOUSE
270	MAIN SWITCHYARD
28A	FIRE WATER FACILITY
28B	FIRE WATER FACILITY
290	SEPTIC TANK & LEACH FIELD (EXISTING)
30A	CENTRAL SECURITY STATION
30B	CASK RECEIPT SECURITY STATION
30C	SOUTH PERIMETER SECURITY STATION
33A	RAILROAD CAR STAGING AREA
33B	TRUCK STAGING
600	NORTH CENTRAL PARKING
610	VISITOR CENTER
620	ADMINISTRATION BUILDING
63A	FIRE, RESCUE AND MEDICAL BUILDING
63B	FIRE, RESCUE AND MEDICAL BUILDING (CONSTRUCTION/REMOVE)
65A	ADMINISTRATION SECURITY STATION
66A	HELICOPTER PAD
66B	HELICOPTER PAD (CONSTRUCTION/REMOVE)
68A	WAREHOUSE/CENTRAL RECEIVING
68B	MATERIALS/YARD STORAGE
690	SMALL VEHICLE REPAIR SHOP
700	FUEL DEPOT
71A	CRAFT SHOPS
71B	EQUIPMENT YARD STORAGE
900	STORM WATER / RETENTION POND

- x - FENCE
- FUTURE
- 3625 25' CONTOURS
- 5' CONTOURS
- CHARACTERIZED AREA (NEW)
- CHARACTERIZED AREA (EXISTING)
- WATER
- POWER
- RAILROAD
- ROAD
- SECURITY FENCE (GROA)

- NOTES:**
- 1 RAIL ALIGNMENT SHOWN IS CONCEPTUAL. FINAL ALIGNMENT TO BE DETERMINED BY TRANSPORTATION STUDY.
 - 2 ROAD ALIGNMENT SHOWN IS CONCEPTUAL. FINAL ALIGNMENT TO BE DETERMINED IN DETAIL DESIGN PHASE
 - 3 ALL PAD ELEVATIONS SHOWN ARE PRELIMINARY AND THEREFORE ARE SUBJECT TO CHANGE AS THE FACILITY DESIGN DEVELOPES




THIS DRAWING IS PRELIMINARY AND NOT FOR FABRICATION.

APPROVALS	INITIAL/DATE
DRAWN BY RF PAVELKA	
ORIGINATOR A. EDMONSTONE	
CHECKED	
VERIFICATION	
DESIGN LEAD ENGINEER F. BASAMANDWICZ	
QUALITY ENGINEERING REP	
SIZE D	SCALE 1"=400'-0"
DOCUMENT IDENTIFIER 100-P0K-MGR0-10701-000-00A	REV 10f1
QA CLASSIFICATION NA	CAD FILENAME 100P0KMGRO10701.SKT
CAD CODE	



REV	DESCRIPTION	DATE	DRN	DRG	CHK	VER	DLE	DER	PM	PROJECT MANAGER
A	ISSUED FOR DESIGN DEVELOPMENT									

ARCH D - 24"x36" RECORD DESIGNATOR OA: NA



DRAFT
 RM
 4/15/04

MIDWAY VALLEY WASH
SKETCH NO. 100-COK-CD04-00101-000-00A



Text is not relevant at 2/12/04

2/12/04
2/12/04

2/12/04
2/12/04

Railroad Alignment

PRELIMINARY
FOR
PREDECISIONAL STUDY
8/1/03

N 770.000

N 765.000

N 760.000

E 565.000

E 570.000

E 575.000

PROJECT: [illegible]
DATE: 8/1/03
PAGE 3-3

**Attachment 4: PMP Calculations for South Portal
(Document ID: 000-00C-CD04-00100-000-00A)**

Attachment 4: PMP Calculations for South Portal Pad

The procedures presented in HMR 49 (Ref. 14) were used to calculate the PMP – South Portal. The calculations on the following pages show that the 6-hour duration local storm PMP of 12.9 inches is more severe than the largest 6-hour general storm of 5.8 inches, which was calculated to occur during the month of September.

Table 6.1.--General-storm PMP computations for the Colorado River and Great basin

Drainage Midway Valley - South Portal Area Area 6.5
 Latitude 36° 51', Longitude 116° 27' of basin center
 Month September

Step Pm 3/3/04
mi² (km²)
note: 3/3/04
above correction should read
mi² (km²)
RM
4/15/04

Step Duration (hrs)
 6 12 18 24 48 72

A. Convergence PMP

1. Drainage average value from one of figures 2.5 to 2.16 10.8 in. (mm) *Pm 3/3/04*
2. Reduction for barrier-elevation [fig. 2.18] 65 %
3. Barrier-elevation reduced PMP [step 1 X step 2] 7.0 in. (mm) *Pm 3/3/04*
4. Durational variation [figs. 2.25 to 2.27 and table 2.7].

68	NA	NA	NA	NA	NA	%
----	----	----	----	----	----	---
5. Convergence PMP for indicated durations [steps 3 X 4]

4.8	NA	NA	NA	NA	NA	in. (mm)
-----	----	----	----	----	----	----------
6. Incremental 10 mi² (26 km²) PMP [successive subtraction in step 5]

4.8	NA	NA	NA	NA	NA	in. (mm)
-----	----	----	----	----	----	----------
7. Areal reduction [select from figs. 2.28 and 2.29]

100	NA	NA	NA	NA	NA	%
-----	----	----	----	----	----	---
8. Areally reduced PMP [step 6 X step 7]

4.8	NA	NA	NA	NA	NA	in. (mm)
-----	----	----	----	----	----	----------
9. Drainage average PMP [accumulated values of step 8]

4.8	NA	NA	NA	NA	NA	in. (mm)
-----	----	----	----	----	----	----------

B. Orographic PMP

1. Drainage average orographic index from figure 3.11a to d. 3.0 in. (mm) *Pm 3/3/04*
2. Areal reduction [figure 3.20] 100 %
3. Adjustment for month [one of figs. 3.12 to 3.17] 100 %
4. Areally and seasonally adjusted PMP [steps 1 X 2 X 3] 3.0 in. (mm) *Pm 3/3/04*
5. Durational variation [table 3.6]

32	NA	NA	NA	NA	NA	%
----	----	----	----	----	----	---
6. Orographic PMP for given durations [steps 4 X 5]

1.0	NA	NA	NA	NA	NA	in. (mm)
-----	----	----	----	----	----	----------

C. Total PMP

1. Add steps A9 and B6 5.8 *NA NA NA NA NA in. (mm) Pm 3/3/04*
2. PMP for other durations from smooth curve fitted to plot of computed data.
3. Comparison with local-storm PMP (see sec. 6.3).

Table 6.3A.--Local-storm PMP computation, Colorado River, Great Basin and California drainages. For drainage average depth PMP. Go to table 6.3B if areal variation is required.

Drainage Midway Valley - South Portal Area Area 6.5 mi² (~~km²~~) *6.5 km² 3/3/04*
 Latitude 36° 51' Longitude 116° 27' Minimum Elevation 3520 ft (~~m~~)

Steps correspond to those in sec. 6.3A.

1. Average 1-hr 1-mi² (2.6-km²) PMP for drainage [fig. 4.5]. 10.3 in. (~~mm~~) *3/3/04*
2. a. Reduction for elevation. [No adjustment for elevations up to 5,000 feet (1,524 m): 5% decrease per 1,000 feet (305 m) above 5,000 feet (1,524 m)]. 100 %
- b. Multiply step 1 by step 2a. 10.3 in. (~~mm~~) *3/3/04*
3. Average 6/1-hr ratio for drainage [fig. 4.7]. 1.36 *3/3/04*
4. Durational variation for 6/1-hr ratio of step 3 [table 4.4].

	Duration (hr)										%
	1/4	1/2	3/4	1	2	3	4	5	6		
6/1-hr ratio	67	85	94	100	116	124	129	133	136		
5. 1-mi² (2.6-km²) PMP for indicated durations [step 2b X step 4].

6/1-hr PMP	6.9	8.8	9.7	10.3	11.9	12.8	13.3	13.7	14.0	in. (mm)
------------	-----	-----	-----	------	------	------	------	------	------	-----------------------
6. Areal reduction [fig. 4.9].

Areal reduction	80	83	85	87	88	89	90	91	92	%
-----------------	----	----	----	----	----	----	----	----	----	---
7. Areal reduced PMP [steps 5 X 6].

Areal reduced PMP	5.5	7.3	8.2	9.0	10.5	11.4	12.0	12.5	12.9	in. (mm)
-------------------	-----	-----	-----	-----	------	------	------	------	------	-----------------------
8. Incremental PMP [successive subtraction in step 7].

Incremental PMP				9.0	1.5	0.9	0.6	0.5	0.4	in. (mm)
15-min. increments	5.5	1.8	0.9	0.8						
9. Time sequence of incremental PMP according to:

Used EM 1110-2-1411 COE Method as in previous report (Ref. 6, p. 16)



Hourly increments [table 4.7].

Hourly increments	0.4	0.6	1.5	9.0	0.9	0.5	in. (mm)
-------------------	-----	-----	-----	-----	-----	-----	-----------------------





Four largest 15-min. increments [table 4.8].

Four largest 15-min. increments	5.5	1.8	0.9	0.8	in. (mm)
---------------------------------	-----	-----	-----	-----	-----------------------

**Attachment 5: Hydrology Calculations for Alternatives 1 and 2
(Document ID: 000-00C-CD04-00100-000-00A)**




Legend

-  Railroad Alignment
-  Watershed Centroids
-  Longest Watercourses
-  Watershed Boundaries




	Yucca Mountain	Calculation of Sub-basin Properties for Inputs to HEC-1 Model, <i>Alternative 1</i>	Figure
	Project # 18839594		



Checker comment: Since the collection point for sub-basin D5 is located above the downstream end of the longest stream, the watershed could have been cut off as shown. However, since the area is small, it will not have a significant effect on the flow calculated at CP4. Also, the way the watershed is currently shown, flow at CP4 would be just slightly larger than it should be, which results in a more conservative design of the man-made channel north of the North Portal Pad (FAC3).

Legend

- Flow Concentration Points
- centroids_alt2
- Watershed Boundaries
- Value
High : 6660.330078
Low : 2438.387939



	Yucca Mountain	Delineation of Sub-basins for HEC-1 Model for Alternative 2	Figure X
	Project # 18839594		

**Attachment 6: Hydraulic Calculations for No Mitigation Scenario, Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**

These numbers refer to the page number of the attached HEC-RAS results

River Station	Length Between Sections (ft)	Elev. At Left Edge of Pad (ft)	WSE w/o any spills (ft)	WSE after 1st Iteration (ft)	WSE after 2nd Iteration (ft)	WSE after 3rd Iteration (ft)	WSE after 4th Iteration (ft)	WSE after 5th Iteration (ft)	Depth w/o any spills (ft)	Depth after 1st Iteration (ft)	Depth after 2nd Iteration (ft)	Depth after 3rd Iteration (ft)	Depth after 4th Iteration (ft)
7500		3678.2	3682.1	3681.7	3682	3681.8	3681.9	3681.8	3.9	3.5	3.8	3.6	3.7
	258								5.8	4.15	5.2	4.55	4.9
7242		3673.7	3681.4	3678.5	3680.3	3679.2	3679.8	3679.5	7.7	4.8	6.6	5.5	6.1
	302								8.2	3.55	7.0	5.3	6.3
6940		3671	3679.7	3673.3	3678.3	3676.1	3677.5	3676.8	8.7	2.3	7.3	5.1	6.5

Values taken directly from HEC-RAS

Example Depth Calculations:
(after 3rd Iteration)

$$5.5 = 3679.2 - 3673.7$$

\uparrow WSE after 3rd Iteration \uparrow Elev at Left Edge of Pad

5.3 = Average depth between Stations 7242 and 6940

$$5.3 = \frac{5.5 + 5.1}{2}$$

HEC-RAS results show that water starts to spill over the left edge (facing downstream) of the pad at River Station 7500.

To be conservative, flow spilling over the edge will only be calculated between stations 7500 and 7242 and Stations 7242 and 6940. Flows in HEC-RAS will be decreased at the downstream sections (Stations 7242 and 6940).

Results after Initial Run Without Spills over Edge of North Portal Pad

HEC-RAS Plan: plan2 River: cross_pad_2 Reach: reach1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	Max Chl Dpth (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Invert Slope	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
reach1	10815.16	18058	3770	8.07	3778.07	3777.32	3779.41	0.052897	0.6184	8.76	1976.55	545.6	0.83
reach1	10438.38	18058	3757.94	6.81	3764.75	3762.56	3765.21	0.020345	0.5864	5.45	3314.41	955.88	0.52
reach1	9898.005	24192	3742	14.95	3756.95	3753.01	3757.16	0.009195	0.5569	3.66	6604.95	2011.41	0.35
reach1	9621.383	24192	3743.75	6.45	3750.2	3750.2	3752.45	0.070457	0.5632	12.04	2010.27	455.58	1
reach1	9236.129	24192	3722.94	10.47	3733.41		3734.17	0.022125	0.5092	6.99	3462.18	732.74	0.57
reach1	8939.948	24192	3716.78	9.44	3726.22		3727.11	0.025645	0.4884	7.57	3195.02	669.64	0.61
reach1	8552.508	24192	3706	10.19	3716.19		3716.89	0.026828	0.4606	6.72	3601.48	934.31	0.6
reach1	8326.505	24192	3700	9.05	3709.05		3709.89	0.036493	0.434	7.34	3296.63	943.47	0.69
reach1	8037.583	24192	3680	10.73	3690.73	3690.73	3696.07	0.063988	0.3648	18.55	1304.35	123.1	1
reach1	7785.279	28379	3678.2	5.97	3684.17	3682.26	3684.66	0.01489	0.3577	5.65	5023.77	1172.19	0.46
reach1	7499.846	28379	3670.25	25.35	3682.07	3679.74	3682.13	0.001492	0.3298	1.58	15176.4	3245.35	0.14
reach1	7241.71	28379	3673.7	7.66	3681.36		3681.51	0.005864	0.3432	3.15	9005.38	2319.7	0.28
reach1	6939.672	28379	3671	8.67	3679.67		3679.83	0.005242	0.3342	3.21	8852.61	2041.11	0.27
reach1	6704.251	28379	3670.7	6.71	3677.41		3677.85	0.020248	0.333	5.31	5345.61	1593.57	0.51
reach1	6416.374	28379	3662.13	12.58	3674.7		3674.74	0.000506	0.3032	1.57	18073.73	2108.91	0.09
reach1	6129.828	28379	3662.13	12.41	3674.53		3674.58	0.000629	0.3032	1.7	16712.41	2041.4	0.1
reach1	5837.239	28379	3662.13	12.21	3674.33		3674.38	0.00073	0.3032	1.75	16236.68	2123.45	0.11
reach1	5510.757	28379	3662.13	11.96	3674.09		3674.13	0.000779	0.3032	1.71	16580.19	2349.28	0.11
reach1	5058.868	28379	3668.7	3.72	3672.42	3672.42	3673.35	0.094322	0.3177	7.74	3665.62	1972.08	1
reach1	4605.871	28379	3600.08	12.29	3612.37	3613.67	3615.66	0.158819	0.1662	14.56	1948.62	695.45	1.42
reach1	3953.237	28379	3581.01	12.94	3593.95	3592.19	3594.88	0.02765	0.137	7.71	3683.01	795.15	0.63
reach1	3289.191	28379	3568	8.56	3576.56		3577.45	0.024896	0.1174	7.59	3766.7	813.19	0.6
reach1	2826.662	28379	3558.01	7.27	3565.28		3566.14	0.024051	0.0958	7.48	3881.66	856.5	0.59
reach1	2301.463	28379	3546	7.54	3553.54		3554.22	0.021106	0.073	6.6	4300.65	959.69	0.55
reach1	1825.637	28379	3534	7.82	3541.82		3542.73	0.028048	0.0478	7.78	3810.09	956.28	0.64
reach1	1187.667	28379	3520	8.57	3528.57		3529.07	0.014489	0.0258	5.84	5076.89	1119.2	0.46
reach1	567.693	28379	3504	11.31	3515.31	3513.83	3516.69	0.030058		9.18	3024.2	517.92	0.68

Results after 1st Iteration

HEC-RAS Plan: plan2 River: cross_pad_2 Reach: reach1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	Max Chl Dpth (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Invert Slope	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
reach1	10815.16	18058	3770	8.07	3778.07	3777.32	3779.41	0.052914	0.6184	8.76	1976.28	545.55	0.83
reach1	10438.38	18058	3757.94	6.81	3764.75	3762.56	3765.21	0.020341	0.5864	5.45	3314.64	955.91	0.52
reach1	9898.005	24192	3742	14.95	3756.95	3753.01	3757.16	0.009197	0.5569	3.66	6604.49	2011.38	0.35
reach1	9621.383	24192	3743.75	6.45	3750.2	3750.2	3752.45	0.070533	0.5632	12.05	2009.61	455.55	1
reach1	9236.129	24192	3722.94	10.47	3733.41		3734.17	0.022113	0.5092	6.99	3462.89	732.82	0.57
reach1	8939.948	24192	3716.78	9.44	3726.22		3727.11	0.025681	0.4884	7.58	3193.06	669.33	0.61
reach1	8552.508	24192	3706	10.2	3716.2		3716.9	0.02676	0.4606	6.71	3605.14	934.91	0.6
reach1	8326.505	24192	3700	9.05	3709.05		3709.89	0.036695	0.434	7.35	3290.64	943.1	0.69
reach1	8037.583	24192	3680	10.8	3690.8	3690.8	3696.07	0.062753	0.3648	18.43	1312.5	123.11	0.99
reach1	7785.279	28379	3678.2	6.15	3684.35	3682.26	3684.81	0.013097	0.3577	5.43	5223.74	1177.88	0.44
reach1	7499.846	28379	3670.25	25	3681.72	3679.74	3681.88	0.006732	0.3298	3.15	8921.15	3091.64	0.3
reach1	7241.71	19009	3673.7	4.76	3678.46	3677.64	3678.92	0.03375	0.3432	5.46	3483.28	1462.96	0.62
reach1	6939.672	572	3671	2.32	3673.32		3673.33	0.002404	0.3342	0.9	634.36	546.38	0.15
reach1	6704.251	572	3670.7	1.58	3672.28		3672.34	0.018443	0.333	1.93	296.14	375.08	0.38
reach1	6416.374	572	3662.13	7.57	3669.7		3669.7	0.000002	0.3032	0.07	8672.02	1629.95	0.01
reach1	6129.828	572	3662.13	7.57	3669.7		3669.7	0.000002	0.3032	0.07	7973.27	1565.58	0.01
reach1	5837.239	572	3662.13	7.57	3669.7		3669.7	0.000002	0.3032	0.07	7627.82	1590.67	0.01
reach1	5510.757	572	3662.13	7.57	3669.7		3669.7	0.000003	0.3032	0.07	7672.94	1706.99	0.01
reach1	5058.868	572	3668.7	0.78	3669.48	3669.48	3669.68	0.158819	0.3177	3.55	161.28	413.66	1
reach1	4605.871	28379	3600.08	14.52	3614.6	3613.67	3615.29	0.034897	0.1662	6.69	4242.21	1504.98	0.66
reach1	3953.237	28379	3581.01	12.94	3593.95	3592.19	3594.88	0.02765	0.137	7.71	3683.01	795.15	0.63
reach1	3289.191	28379	3568	8.56	3576.56		3577.45	0.024896	0.1174	7.59	3766.7	813.19	0.6
reach1	2826.662	28379	3558.01	7.27	3565.28		3566.14	0.024051	0.0958	7.48	3881.66	856.5	0.59
reach1	2301.463	28379	3546	7.54	3553.54		3554.22	0.021106	0.073	6.6	4300.65	959.69	0.55
reach1	1825.637	28379	3534	7.82	3541.82		3542.73	0.028048	0.0478	7.78	3810.09	956.28	0.64
reach1	1187.667	28379	3520	8.57	3528.57		3529.07	0.014489	0.0258	5.84	5076.89	1119.2	0.46
reach1	567.693	28379	3504	11.31	3515.31	3513.83	3516.69	0.030058		9.18	3024.2	517.92	0.68

Results after 2nd Iteration

HEC-RAS Plan: plan2 River: cross_pad_2 Reach: reach1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	Max Chl Dpth (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Invert Slope	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
reach1	10815.16	18058	3770	8.07	3778.07	3777.32	3779.41	0.052914	0.6184	8.76	1976.28	545.55	0.83
reach1	10438.38	18058	3757.94	6.81	3764.75	3762.56	3765.21	0.020341	0.5864	5.45	3314.64	955.91	0.52
reach1	9898.005	24192	3742	14.95	3756.95	3753.01	3757.16	0.009197	0.5569	3.66	6604.49	2011.38	0.35
reach1	9621.383	24192	3743.75	6.45	3750.2	3750.2	3752.45	0.070533	0.5632	12.05	2009.61	455.55	1
reach1	9236.129	24192	3722.94	10.47	3733.41		3734.17	0.022113	0.5092	6.99	3462.89	732.82	0.57
reach1	8939.948	24192	3716.78	9.44	3726.22		3727.11	0.025681	0.4884	7.58	3193.06	669.33	0.61
reach1	8552.508	24192	3706	10.2	3716.2		3716.9	0.02676	0.4606	6.71	3605.14	934.91	0.6
reach1	8326.505	24192	3700	9.05	3709.05		3709.89	0.036695	0.434	7.35	3290.64	943.1	0.69
reach1	8037.583	24192	3680	10.8	3690.8	3690.8	3696.07	0.062753	0.3648	18.43	1312.5	123.11	0.99
reach1	7785.279	28379	3678.2	6.18	3684.38	3682.26	3684.84	0.01283	0.3577	5.4	5256.56	1178.75	0.43
reach1	7499.846	28379	3670.25	25.31	3682.03	3679.74	3682.16	0.005144	0.3298	2.91	9705.87	3196.26	0.26
reach1	7241.71	22708	3673.7	6.6	3680.3		3680.48	0.008436	0.3432	3.39	6694.37	2028.12	0.33
reach1	6939.672	17456	3671	7.34	3678.34		3678.46	0.004822	0.3342	2.75	6344.23	1727.9	0.25
reach1	6704.251	17456	3670.7	5.54	3676.24		3676.59	0.021333	0.333	4.79	3640.92	1315.16	0.51
reach1	6416.374	17456	3662.13	11.23	3673.36		3673.38	0.000306	0.3032	1.14	15322.33	1986.21	0.07
reach1	6129.828	17456	3662.13	11.13	3673.26		3673.28	0.000378	0.3032	1.23	14185.68	1917.86	0.08
reach1	5837.239	17456	3662.13	11.01	3673.14		3673.16	0.000436	0.3032	1.27	13779.63	1986.02	0.08
reach1	5510.757	17456	3662.13	10.87	3672.99		3673.02	0.000461	0.3032	1.24	14091.19	2188.86	0.09
reach1	5058.868	17456	3668.7	3.06	3671.76	3671.76	3672.53	0.100593	0.3177	7.02	2485.28	1623.82	1
reach1	4605.871	28379	3600.08	14.52	3614.6	3613.67	3615.29	0.034897	0.1662	6.69	4242.21	1504.98	0.66
reach1	3953.237	28379	3581.01	12.94	3593.95	3592.19	3594.88	0.02765	0.137	7.71	3683.01	795.15	0.63
reach1	3289.191	28379	3568	8.56	3576.56		3577.45	0.024896	0.1174	7.59	3766.7	813.19	0.6
reach1	2826.662	28379	3558.01	7.27	3565.28		3566.14	0.024051	0.0958	7.48	3881.66	856.5	0.59
reach1	2301.463	28379	3546	7.54	3553.54		3554.22	0.021106	0.073	6.6	4300.65	959.69	0.55
reach1	1825.637	28379	3534	7.82	3541.82		3542.73	0.028048	0.0478	7.78	3810.09	956.28	0.64
reach1	1187.667	28379	3520	8.57	3528.57		3529.07	0.014489	0.0258	5.84	5076.89	1119.2	0.46
reach1	567.693	28379	3504	11.31	3515.31	3513.83	3516.69	0.030058		9.18	3024.2	517.92	0.68

Results after 3rd Iteration

HEC-RAS Plan: plan2 River: cross_pad_2 Reach: reach1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	Max Chl Dpth (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Invert Slope	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
reach1	10815.16	18058	3770	8.07	3778.07	3777.32	3779.41	0.052914	0.6184	8.76	1976.28	545.55	0.83
reach1	10438.38	18058	3757.94	6.81	3764.75	3762.56	3765.21	0.020341	0.5864	5.45	3314.64	955.91	0.52
reach1	9898.005	24192	3742	14.95	3756.95	3753.01	3757.16	0.009197	0.5569	3.66	6604.49	2011.38	0.35
reach1	9621.383	24192	3743.75	6.45	3750.2	3750.2	3752.45	0.070533	0.5632	12.05	2009.61	455.55	1
reach1	9236.129	24192	3722.94	10.47	3733.41		3734.17	0.022113	0.5092	6.99	3462.89	732.82	0.57
reach1	8939.948	24192	3716.78	9.44	3726.22		3727.11	0.025681	0.4884	7.58	3193.06	669.33	0.61
reach1	8552.508	24192	3706	10.2	3716.2		3716.9	0.02676	0.4606	6.71	3605.14	934.91	0.6
reach1	8326.505	24192	3700	9.05	3709.05		3709.89	0.036695	0.434	7.35	3290.64	943.1	0.69
reach1	8037.583	24192	3680	10.8	3690.8	3690.8	3696.07	0.062753	0.3648	18.43	1312.5	123.11	0.99
reach1	7785.279	28379	3678.2	6.16	3684.36	3682.26	3684.81	0.013062	0.3577	5.43	5227.98	1177.99	0.44
reach1	7499.846	28379	3670.25	25.08	3681.8	3679.74	3681.95	0.00626	0.3298	3.08	9126.78	3134.58	0.29
reach1	7241.71	20425	3673.7	5.52	3679.22		3679.52	0.017727	0.3432	4.36	4680.14	1695.77	0.46
reach1	6939.672	6038	3671	5.13	3676.13		3676.19	0.0039	0.3342	1.95	3098.46	1207.55	0.21
reach1	6704.251	6038	3670.7	3.71	3674.41		3674.62	0.021483	0.333	3.69	1637.87	882.09	0.48
reach1	6416.374	6038	3662.13	9.32	3671.45		3671.45	0.00008	0.3032	0.52	11697.16	1811.89	0.04
reach1	6129.828	6038	3662.13	9.3	3671.42		3671.43	0.000098	0.3032	0.56	10830.7	1740.33	0.04
reach1	5837.239	6038	3662.13	9.27	3671.39		3671.4	0.000112	0.3032	0.58	10488.79	1785.46	0.04
reach1	5510.757	6038	3662.13	9.23	3671.36		3671.36	0.000118	0.3032	0.56	10704.54	1949.49	0.04
reach1	5058.868	6038	3668.7	1.99	3670.69	3670.69	3671.2	0.119722	0.3177	5.75	1050.11	1055.52	1.02
reach1	4605.871	28379	3600.08	14.52	3614.6	3613.67	3615.29	0.034897	0.1662	6.69	4242.21	1504.98	0.66
reach1	3953.237	28379	3581.01	12.94	3593.95	3592.19	3594.88	0.02765	0.137	7.71	3683.01	795.15	0.63
reach1	3289.191	28379	3568	8.56	3576.56		3577.45	0.024896	0.1174	7.59	3766.7	813.19	0.6
reach1	2826.662	28379	3558.01	7.27	3565.28		3566.14	0.024051	0.0958	7.48	3881.66	856.5	0.59
reach1	2301.463	28379	3546	7.54	3553.54		3554.22	0.021106	0.073	6.6	4300.65	959.69	0.55
reach1	1825.637	28379	3534	7.82	3541.82		3542.73	0.028048	0.0478	7.78	3810.09	956.28	0.64
reach1	1187.667	28379	3520	8.57	3528.57		3529.07	0.014489	0.0258	5.84	5076.89	1119.2	0.46
reach1	567.693	28379	3504	11.31	3515.31	3513.83	3516.69	0.030058		9.18	3024.2	517.92	0.68

Results after 4th Iteration

HEC-RAS Plan: plan2 River: cross_pad_2 Reach: reach1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	Max Chl Dpth (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Invert Slope	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
reach1	10815.16	18058	3770	8.07	3778.07	3777.32	3779.41	0.052914	0.6184	8.76	1976.28	545.55	0.83
reach1	10438.38	18058	3757.94	6.81	3764.75	3762.56	3765.21	0.020341	0.5864	5.45	3314.64	955.91	0.52
reach1	9898.005	24192	3742	14.95	3756.95	3753.01	3757.16	0.009197	0.5569	3.66	6604.49	2011.38	0.35
reach1	9621.383	24192	3743.75	6.45	3750.2	3750.2	3752.45	0.070533	0.5632	12.05	2009.61	455.55	1
reach1	9236.129	24192	3722.94	10.47	3733.41		3734.17	0.022113	0.5092	6.99	3462.89	732.82	0.57
reach1	8939.948	24192	3716.78	9.44	3726.22		3727.11	0.025681	0.4884	7.58	3193.06	669.33	0.61
reach1	8552.508	24192	3706	10.2	3716.2		3716.9	0.02676	0.4606	6.71	3605.14	934.91	0.6
reach1	8326.505	24192	3700	9.05	3709.05		3709.89	0.036695	0.434	7.35	3290.64	943.1	0.69
reach1	8037.583	24192	3680	10.8	3690.8	3690.8	3696.07	0.062753	0.3648	18.43	1312.5	123.11	0.99
reach1	7785.279	28379	3678.2	6.17	3684.37	3682.26	3684.82	0.012969	0.3577	5.42	5239.36	1178.3	0.43
reach1	7499.846	28379	3670.25	25.19	3681.91	3679.74	3682.05	0.005667	0.3298	2.99	9415.61	3176.58	0.27
reach1	7241.71	21869	3673.7	6.14	3679.84		3680.06	0.01149	0.3432	3.77	5795.86	1887.11	0.38
reach1	6939.672	12288	3671	6.52	3677.52		3677.61	0.004501	0.3342	2.46	5003.35	1534.48	0.24
reach1	6704.251	12288	3670.7	4.83	3675.53		3675.84	0.021817	0.333	4.43	2774.64	1148.09	0.5
reach1	6416.374	12288	3662.13	10.47	3672.59		3672.6	0.000204	0.3032	0.89	13827.93	1916.27	0.06
reach1	6129.828	12288	3662.13	10.4	3672.53		3672.54	0.00025	0.3032	0.96	12808.31	1847.04	0.06
reach1	5837.239	12288	3662.13	10.32	3672.45		3672.46	0.000288	0.3032	0.99	12434.88	1906.61	0.07
reach1	5510.757	12288	3662.13	10.23	3672.35		3672.37	0.000303	0.3032	0.97	12717.94	2095.1	0.07
reach1	5058.868	12288	3668.7	2.65	3671.35	3671.35	3672.03	0.108585	0.3177	6.62	1856	1403.26	1.01
reach1	4605.871	28379	3600.08	14.52	3614.6	3613.67	3615.29	0.034897	0.1662	6.69	4242.21	1504.98	0.66
reach1	3953.237	28379	3581.01	12.94	3593.95	3592.19	3594.88	0.02765	0.137	7.71	3683.01	795.15	0.63
reach1	3289.191	28379	3568	8.56	3576.56		3577.45	0.024896	0.1174	7.59	3766.7	813.19	0.6
reach1	2826.662	28379	3558.01	7.27	3565.28		3566.14	0.024051	0.0958	7.48	3881.66	856.5	0.59
reach1	2301.463	28379	3546	7.54	3553.54		3554.22	0.021106	0.073	6.6	4300.65	959.69	0.55
reach1	1825.637	28379	3534	7.82	3541.82		3542.73	0.028048	0.0478	7.78	3810.09	956.28	0.64
reach1	1187.667	28379	3520	8.57	3528.57		3529.07	0.014489	0.0258	5.84	5076.89	1119.2	0.46
reach1	567.693	28379	3504	11.31	3515.31	3513.83	3516.69	0.030058		9.18	3024.2	517.92	0.68

Results after 5th Iteration


HEC-RAS Plan: plan2 River: cross_pad_2 Reach: reach1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	Max Chl Dpth (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Invert Slope	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
reach1	10815.16	18058	3770	8.07	3778.07	3777.32	3779.41	0.052914	0.6184	8.76	1976.28	545.55	0.83
reach1	10438.38	18058	3757.94	6.81	3764.75	3762.56	3765.21	0.020341	0.5864	5.45	3314.64	955.91	0.52
reach1	9898.005	24192	3742	14.95	3756.95	3753.01	3757.16	0.009197	0.5569	3.66	6604.49	2011.38	0.35
reach1	9621.383	24192	3743.75	6.45	3750.2	3750.2	3752.45	0.070533	0.5632	12.05	2009.61	455.55	1
reach1	9236.129	24192	3722.94	10.47	3733.41		3734.17	0.022113	0.5092	6.99	3462.89	732.82	0.57
reach1	8939.948	24192	3716.78	9.44	3726.22		3727.11	0.025681	0.4884	7.58	3193.06	669.33	0.61
reach1	8552.508	24192	3706	10.2	3716.2		3716.9	0.02676	0.4606	6.71	3605.14	934.91	0.6
reach1	8326.505	24192	3700	9.05	3709.05		3709.89	0.036695	0.434	7.35	3290.64	943.1	0.69
reach1	8037.583	24192	3680	10.8	3690.8	3690.8	3696.07	0.062753	0.3648	18.43	1312.5	123.11	0.99
reach1	7785.279	28379	3678.2	6.16	3684.36	3682.26	3684.82	0.013034	0.3577	5.42	5231.42	1178.09	0.44
reach1	7499.846	28379	3670.25	25.12	3681.84	3679.74	3681.99	0.006029	0.3298	3.05	9234.69	3157.05	0.28
reach1	7241.71	21103	3673.7	5.8	3679.5		3679.76	0.014527	0.3432	4.08	5167.93	1781.95	0.42
reach1	6939.672	8687	3671	5.8	3676.8		3676.87	0.004203	0.3342	2.19	3957.89	1364.78	0.23
reach1	6704.251	8687	3670.7	4.25	3674.95		3675.2	0.021775	0.333	4.06	2140.73	1008.45	0.49
reach1	6416.374	8687	3662.13	9.85	3671.97		3671.98	0.000131	0.3032	0.69	12660.81	1859.82	0.05
reach1	6129.828	8687	3662.13	9.81	3671.93		3671.94	0.000161	0.3032	0.74	11727.38	1789.5	0.05
reach1	5837.239	8687	3662.13	9.76	3671.88		3671.89	0.000185	0.3032	0.76	11374.29	1841.57	0.05
reach1	5510.757	8687	3662.13	9.69	3671.82		3671.83	0.000194	0.3032	0.75	11625.07	2017.37	0.05
reach1	5058.868	8687	3668.7	2.3	3671	3671	3671.59	0.11344	0.3177	6.17	1407.65	1222.07	1.01
reach1	4605.871	28379	3600.08	14.52	3614.6	3613.67	3615.29	0.034897	0.1662	6.69	4242.21	1504.98	0.66
reach1	3953.237	28379	3581.01	12.94	3593.95	3592.19	3594.88	0.02765	0.137	7.71	3683.01	795.15	0.63
reach1	3289.191	28379	3568	8.56	3576.56		3577.45	0.024896	0.1174	7.59	3766.7	813.19	0.6
reach1	2826.662	28379	3558.01	7.27	3565.28		3566.14	0.024051	0.0958	7.48	3881.66	856.5	0.59
reach1	2301.463	28379	3546	7.54	3553.54		3554.22	0.021106	0.073	6.6	4300.65	959.69	0.55
reach1	1825.637	28379	3534	7.82	3541.82		3542.73	0.028048	0.0478	7.78	3810.09	956.28	0.64
reach1	1187.667	28379	3520	8.57	3528.57		3529.07	0.014489	0.0258	5.84	5076.89	1119.2	0.46
reach1	567.693	28379	3504	11.31	3515.31	3513.83	3516.69	0.030058		9.18	3024.2	517.92	0.68


Final Results


HEC-RAS Plan: plan2 River: cross_pad_2 Reach: reach1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	Max Chl Dpth (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Invert Slope	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
reach1	10815.16	18058	3770	8.07	3778.07	3777.32	3779.41	0.052914	0.6184	8.76	1976.28	545.55	0.83
reach1	10438.38	18058	3757.94	6.81	3764.75	3762.56	3765.21	0.020341	0.5864	5.45	3314.64	955.91	0.52
reach1	9898.005	24192	3742	14.95	3756.95	3753.01	3757.16	0.009197	0.5569	3.66	6604.49	2011.38	0.35
reach1	9621.383	24192	3743.75	6.45	3750.2	3750.2	3752.45	0.070533	0.5632	12.05	2009.61	455.55	1
reach1	9236.129	24192	3722.94	10.47	3733.41		3734.17	0.022113	0.5092	6.99	3462.89	732.82	0.57
reach1	8939.948	24192	3716.78	9.44	3726.22		3727.11	0.025681	0.4884	7.58	3193.06	669.33	0.61
reach1	8552.508	24192	3706	10.2	3716.2		3716.9	0.02676	0.4606	6.71	3605.14	934.91	0.6
reach1	8326.505	24192	3700	9.05	3709.05		3709.89	0.036695	0.434	7.35	3290.64	943.1	0.69
reach1	8037.583	24192	3680	10.8	3690.8	3690.8	3696.07	0.062753	0.3648	18.43	1312.5	123.11	0.99
reach1	7785.279	28379	3678.2	6.16	3684.36	3682.26	3684.82	0.013001	0.3577	5.42	5235.39	1178.19	0.43
reach1	7499.846	28379	3670.25	25.16	3681.88	3679.74	3682.02	0.005833	0.3298	3.02	9330.98	3170.72	0.28
reach1	7241.71	21544	3673.7	5.98	3679.68		3679.92	0.012814	0.3432	3.92	5501.61	1838.58	0.4
reach1	6939.672	10576	3671	6.2	3677.2		3677.28	0.004367	0.3342	2.34	4521.77	1458.76	0.23
reach1	6704.251	10576	3670.7	4.57	3675.27		3675.55	0.021754	0.333	4.26	2482.03	1085.86	0.5
reach1	6416.374	10576	3662.13	10.18	3672.31		3672.32	0.000169	0.3032	0.8	13287.98	1890.36	0.05
reach1	6129.828	10576	3662.13	10.13	3672.25		3672.27	0.000208	0.3032	0.86	12308.65	1820.67	0.06
reach1	5837.239	10576	3662.13	10.06	3672.19		3672.2	0.000239	0.3032	0.89	11945.32	1876.87	0.06
reach1	5510.757	10576	3662.13	9.98	3672.11		3672.12	0.000251	0.3032	0.87	12214.32	2059.64	0.06
reach1	5058.868	10576	3668.7	2.5	3671.2	3671.2	3671.83	0.109279	0.3177	6.39	1654.51	1324.91	1.01
reach1	4605.871	28379	3600.08	14.52	3614.6	3613.67	3615.29	0.034897	0.1662	6.69	4242.21	1504.98	0.66
reach1	3953.237	28379	3581.01	12.94	3593.95	3592.19	3594.88	0.02765	0.137	7.71	3683.01	795.15	0.63
reach1	3289.191	28379	3568	8.56	3576.56		3577.45	0.024896	0.1174	7.59	3766.7	813.19	0.6
reach1	2826.662	28379	3558.01	7.27	3565.28		3566.14	0.024051	0.0958	7.48	3881.66	856.5	0.59
reach1	2301.463	28379	3546	7.54	3553.54		3554.22	0.021106	0.073	6.6	4300.65	959.69	0.55
reach1	1825.637	28379	3534	7.82	3541.82		3542.73	0.028048	0.0478	7.78	3810.09	956.28	0.64
reach1	1187.667	28379	3520	8.57	3528.57		3529.07	0.014489	0.0258	5.84	5076.89	1119.2	0.46
reach1	567.693	28379	3504	11.31	3515.31	3513.83	3516.69	0.030058		9.18	3024.2	517.92	0.68






















57


**Attachment 7: Hydraulic Calculations for Routing Around Muck Storage A, Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**




Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 17644.03




Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 17245.36




Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 16739.54




Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 16126.43




Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 15507.11




Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 14754.99





Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 13675.58




Routing along cp2cp6 1) Q-cp2cp6 11/24/2003
RS = 13227.14















Profile Output Table - Standard Table 1
 HEC-RAS Plan: Q-cp2cp6 River: cp2cp6 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 18
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	17644.03	7173.00	3929.04	3933.07	3932.80	3934.00	0.059018	9.67	952.37	388.31	0.89	
main	17245.36	7173.00	3905.72	3913.22	3913.22	3914.19	0.042263	10.46	1069.69	461.61	0.80	
main	16739.54	7173.00	3880.00	3898.96	3886.70	3898.99	0.000344	2.03	4924.89	506.36	0.09	
main	16126.43	7173.00	3878.41	3898.88	3884.44	3898.89	0.000092	1.14	8033.91	597.24	0.05	
main	15507.11	7173.00	3876.80	3898.74	3886.51	3898.78	0.000397	2.36	4415.71	406.99	0.09	
main	14754.99	7173.00	3874.84	3897.64	3887.71	3898.07	0.003604	5.35	1430.15	155.15	0.26	
main	13675.58	7173.00	3872.03	3889.51	3884.91	3890.81	0.016160	9.12	786.11	79.93	0.51	
main	13227.14	7173.00	3870.87	3882.18	3882.18	3882.67	0.019262	7.02	1463.04	562.68	0.53	
main	12711.60	7173.00	3853.52	3859.80	3858.65	3860.29	0.018706	7.63	1348.92	396.68	0.54	
main	11769.43	10363.00	3820.16	3826.95	3826.86	3828.89	0.055918	12.85	972.42	238.21	0.93	
main	10589.56	10363.00	3775.33	3785.00	3783.59	3786.33	0.025036	11.20	1205.04	224.59	0.67	
main	8898.103	10363.00	3720.00	3732.74		3735.60	0.036330	16.01	860.06	134.87	0.84	
main	8023.107	10363.00	3696.00	3706.40		3708.12	0.026802	12.34	1057.27	169.51	0.70	
main	6682.772	10363.00	3662.00	3674.27	3672.07	3675.91	0.021662	12.26	1110.63	166.54	0.64	
main	4641.928	10363.00	3615.16	3624.08	3622.30	3625.61	0.028251	11.32	1117.47	203.60	0.70	
main	2916.802	10363.00	3580.00	3583.98	3582.69	3584.41	0.020158	5.94	1984.76	616.40	0.53	
main	1729.693	10363.00	3555.15	3559.45		3559.86	0.021243	6.33	2096.67	748.55	0.54	
main	286.470	10363.00	3522.00	3526.69	3525.78	3527.18	0.024412	7.13	1913.94	672.31	0.59	












Channel Modification - Cut and Fill Data

River:	cp2cp6	Reach:	main							
RS		Area L	Area Ch	Area R	Area T	Volume L	Volume Ch	Volume R	Volume T	
		(sq ft)	(sq ft)	(sq ft)	(sq ft)	(cu yd)	(cu yd)	(cu yd)	(cu yd)	
16739.54	Cut	0	36	0	36	0	647	0	647	
	Fill	0	0	0	0	0	0	0	0	
	Net	0	36	0	36	0	647	0	647	
16126.43	Cut	0	21	0	21	29	1243	7	1280	
	Fill	0	0	0	0	0	0	0	0	
	Net	0	21	0	21	29	1243	7	1280	
15507.11	Cut	3	88	1	91	46	14450	9	14505	
	Fill	0	0	0	0	0	0	0	0	
	Net	3	88	1	91	46	14450	9	14505	
14754.99	Cut	1	950	0	951	8631	24005	6629	39265	
	Fill	0	0	0	0	0	0	0	0	
	Net	1	950	0	951	8631	24005	6629	39265	
13675.58	Cut	431	251	332	1014	3586	3792	2759	10137	
	Fill	0	0	0	0	0	0	0	0	
	Net	431	251	332	1014	3586	3792	2759	10137	
13226.35	Cut	0	205	0	205	0	1953	0	1953	
	Fill	0	0	0	0	0	0	0	0	
	Net	0	205	0	205	0	1953	0	1953	
Total	Cut					12292	46091	9403	67786	
	Fill					0	0	0	0	
	Net					12292	46091	9403	67786	


**Attachment 8: Hydraulic Calculations for Routing Downstream of Muck Storage A,
Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**








Profile Output Table - Standard Table 1
 HEC-RAS Plan: Q-fac1 River: fac1cp6 Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 12
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	8522.402	3268.00	3753.36	3758.05	3758.05	3759.85	0.071011	11.21	309.78	89.71	0.99	
main	8090.588	3268.00	3735.90	3743.63	3742.10	3744.65	0.021732	8.70	431.96	89.31	0.59	
main	7651.747	3268.00	3724.81	3731.26		3732.54	0.036110	9.14	368.78	87.99	0.72	
main	6693.994	3268.00	3694.90	3700.97		3702.05	0.028167	8.85	417.08	101.43	0.66	
main	5946.033	3268.00	3672.24	3678.88		3679.98	0.030962	8.55	399.42	93.96	0.67	
main	5119.450	3268.00	3646.00	3652.70		3653.90	0.032203	9.32	400.87	104.68	0.70	
main	4220.337	3268.00	3621.48	3627.27		3628.07	0.025554	7.53	485.59	138.95	0.61	
main	3416.825	3268.00	3601.45	3605.75	3604.85	3606.36	0.028456	6.89	554.40	202.36	0.62	
main	2408.215	3268.00	3574.58	3576.70	3576.18	3577.04	0.029494	3.92	723.83	386.09	0.55	
main	1620.471	3268.00	3556.00	3560.20	3559.10	3560.45	0.015675	4.48	899.22	467.37	0.45	
main	740.439	3268.00	3537.20	3541.57	3540.68	3542.09	0.029095	6.28	616.59	310.04	0.61	
main	58.720	3268.00	3522.00	3524.75	3524.13	3524.97	0.021705	4.43	896.18	528.25	0.50	













**Attachment 9: Hydraulic Calculations for Routing Around Optional Aging Facility and
North Construction Portal, Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**









Routing around Aging Facilities 1) Q-fac2ext 11/24/2003
RS = 4704.974




Routing around Aging Facilities 1) Q-fac2ext 11/24/2003
RS = 4238.595





Routing around Aging Facilities 1) Q-fac2ext 11/24/2003
RS = 3831.045




Routing around Aging Facilities 1) Q-fac2ext 11/24/2003
RS = 3424.526








Routing around Aging Facilities 1) Q-fac2ext 11/24/2003
RS = 223.728




Routing around Aging Facilities 1) Q-fac2ext 11/24/2003
RS = 56.792




Profile Output Table - Standard Table 1
 HEC-RAS Plan: Q-fac2ext River: fac2-ext Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 22
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	6504.219	5854.00	3911.56	3915.06	3914.29	3915.52	0.027901	6.22	1104.38	436.18	0.60	
main	6219.605	5854.00	3899.78	3903.52	3903.52	3904.33	0.058436	9.21	898.10	488.45	0.87	
main	5861.798	5854.00	3881.99	3885.09	3883.27	3885.32	0.009378	3.40	1545.79	443.35	0.34	
main	5668.085	5854.00	3873.96	3880.07	3879.44	3881.81	0.042476	11.32	584.35	121.45	0.82	
main	5459.615	5854.00	3862.00	3874.93	3871.27	3876.16	0.017921	8.90	657.97	76.74	0.54	
main	5252.428	5854.00	3857.92	3868.53	3867.20	3870.74	0.039863	11.93	490.70	67.46	0.78	
main	5105.160	5854.00	3855.02	3863.94	3863.94	3865.08	0.033164	9.92	834.06	322.35	0.70	
main	4957.751	5854.00	3852.78	3858.78	3858.13	3859.68	0.031697	9.43	861.12	282.60	0.70	
main	4704.974	5854.00	3842.98	3847.89	3847.51	3849.39	0.053566	9.95	605.81	164.00	0.86	
main	4238.595	5854.00	3826.35	3833.48	3831.61	3834.41	0.020965	8.44	768.52	129.00	0.58	
main	3831.045	5854.00	3810.54	3821.66	3818.86	3823.70	0.033011	11.53	510.54	48.80	0.62	
main	3424.526	5854.00	3799.57	3811.24	3807.61	3813.12	0.020874	11.88	565.20	50.70	0.63	
main	3077.262	5854.00	3792.00	3802.90	3800.21	3805.01	0.026180	12.53	535.73	54.00	0.70	
main	2807.831	5854.00	3780.89	3790.21	3790.21	3793.78	0.073665	16.29	399.07	58.00	1.10	
main	2480.189	5854.00	3765.00	3777.54	3774.29	3778.89	0.020358	9.32	628.67	82.57	0.57	
main	2190.768	5854.00	3759.10	3771.63	3768.35	3772.98	0.020409	9.33	627.21	75.11	0.57	
main	1830.626	5854.00	3751.75	3764.28	3761.02	3765.63	0.020439	9.34	626.88	75.10	0.57	
main	1370.988	5854.00	3742.37	3754.92	3751.65	3756.26	0.020309	9.32	628.37	75.18	0.57	
main	949.068	5854.00	3733.77	3746.27	3743.05	3747.63	0.020607	9.37	625.00	75.00	0.57	
main	528.748	5854.00	3725.19	3737.82	3734.46	3739.14	0.019755	9.22	634.83	75.53	0.56	
main	223.728	5854.00	3720.00	3728.40	3728.09	3730.47	0.043376	13.05	548.18	114.05	0.85	
main	56.792	5854.00	3712.38	3721.63	3721.03	3723.64	0.038526	11.94	568.95	134.82	0.79	




Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003




Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003




Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003




Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003




Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003




Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003





Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003





Routing around Aging Facilities Qtopo Debris flow for fac2 ext channel 11/24/2003










Channel Modification - Cut and Fill Data

River: fac2-ext Reach: main

RS		Area L (sq ft)	Area Ch (sq ft)	Area R (sq ft)	Area T (sq ft)	Volume L (cu yd)	Volume Ch (cu yd)	Volume R (cu yd)	Volume T (cu yd)
5459.615	Cut	69	724	27	820	310	5265	105	5680
	Fill	0	0	0	0	0	0	0	0
	Net	69	724	27	820	310	5265	105	5680
5252.428	Cut	12	648	0	660	33	2461	1	2495
	Fill	0	0	0	0	0	0	0	0
	Net	12	648	0	660	33	2461	1	2495
5105.16	Cut	0	254	0	254	0	695	0	695
	Fill	0	0	0	0	0	0	0	0
	Net	0	254	0	254	0	695	0	695
Total	Cut					343	8420	106	8869
	Fill					0	0	0	0
	Net					343	8420	106	8869
2480.189	Cut	41	704	16	761	222	7458	84	7763
	Fill	0	0	0	0	0	0	0	0
	Net	41	704	16	761	222	7458	84	7763
2190.768	Cut	0	687	0	687	0	11374	0	11374
	Fill	0	0	0	0	0	0	0	0
	Net	0	687	0	687	0	11374	0	11374
1830.626	Cut	0	1018	0	1018	0	18626	0	18626
	Fill	0	0	0	0	0	0	0	0
	Net	0	1018	0	1018	0	18626	0	18626
1370.988	Cut	0	1170	0	1170	269	17916	188	18373
	Fill	0	0	0	0	0	0	0	0
	Net	0	1170	0	1170	269	17916	188	18373
949.068	Cut	34	1123	24	1182	268	17035	188	17490
	Fill	0	0	0	0	0	0	0	0
	Net	34	1123	24	1182	268	17035	188	17490
528.748	Cut	0	1065	0	1065	0	6018	0	6018
	Fill	0	0	0	0	0	0	0	0
	Net	0	1065	0	1065	0	6018	0	6018
Total	Cut					758	78428	460	79645
	Fill					0	0	0	0
	Net					758	78428	460	79645


**Attachment 10: Hydraulic Calculations for Routing Around Aging Facility and North
Portal Pad, Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**



Profile Output Table - Standard Table 1
 HEC-RAS Plan: Plan 12 River: fac2w-fac3 Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 27
 # Plans = 1
 # Profiles = 1





Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	8215.041	8636.00	3885.44	3891.96	3886.43	3892.21	0.003189	3.22	2286.52	299.66	0.23	
main	8048.594	8636.00	3887.62	3888.54	3887.74	3890.36	0.045852	3.07	802.71	150.43	0.61	
main	7770.874	8636.00	3865.13	3872.71	3872.57	3874.74	0.055504	11.76	795.11	192.47	0.88	
main	7443.768	8636.00	3844.00	3856.12	3856.12	3858.18	0.066204	13.94	768.39	172.71	0.74	
main	7028.908	8636.00	3825.63	3832.44	3832.14	3833.73	0.042874	9.67	1019.55	336.38	0.79	
main	6211.489	8636.00	3790.00	3797.18	3796.60	3798.00	0.030728	9.47	1274.72	383.59	0.69	
main	5838.303	8636.00	3775.40	3787.44	3782.85	3787.77	0.004766	5.15	2002.21	294.67	0.28	
main	5637.145	8636.00	3770.39	3783.64	3780.65	3785.21	0.023227	10.07	857.91	100.63	0.61	
main	5123.930	8636.00	3757.61	3770.76	3767.70	3772.54	0.023385	10.71	806.22	87.61	0.62	
main	4823	8636.00	3750.12	3765.55	3760.21	3766.67	0.012417	8.50	1015.79	96.70	0.46	
main	4685	8636.00	3748.00	3762.63	3758.73	3764.50	0.021426	10.98	786.57	72.55	0.59	
main	4455.997	8636.00	3744.81	3755.74	3754.93	3758.74	0.048006	13.90	621.26	78.71	0.87	
main	4108.803	8636.00	3728.14	3739.07	3742.07	3742.07	0.047928	13.89	621.63	78.73	0.87	
main	3864.722	8636.00	3716.43	3727.74	3730.47	3730.47	0.041982	13.24	652.08	80.26	0.82	
main	3684.510	9910.00	3707.78	3724.70	3718.68	3725.82	0.011268	8.51	1164.44	102.67	0.45	
main	3440.055	9910.00	3705.25	3721.32	3716.15	3722.63	0.013846	9.18	1079.36	104.69	0.49	
main	3225.065	9910.00	3703.10	3719.58	3715.09	3720.06	0.004883	6.35	2090.92	329.32	0.30	
main	3020.229	9910.00	3701.05	3716.80	3711.97	3718.23	0.014714	9.61	1032.34	94.43	0.50	
main	2806.897	9910.00	3698.92	3711.65	3709.84	3714.22	0.034991	12.88	769.61	85.92	0.76	
main	2575.744	9910.00	3690.83	3703.56	3701.73	3706.13	0.035013	12.88	769.42	85.90	0.76	
main	2275.362	9910.00	3680.31	3693.07	3691.21	3695.63	0.034632	12.83	772.52	86.06	0.75	
main	1900.733	9910.00	3667.20	3684.33	3678.10	3685.41	0.010711	8.35	1186.33	103.52	0.43	
main	1536.204	9910.00	3654.44	3683.44	3665.34	3683.65	0.001164	3.67	2697.79	151.03	0.15	
main	1283.309	9910.00	3666.24	3680.14	3678.14	3682.17	0.022687	11.81	944.81	145.35	0.63	
main	941.845	9910.00	3657.02	3671.33	3668.55	3673.50	0.027021	11.81	839.16	87.25	0.67	
main	469.409	9910.00	3644.26	3658.05	3655.80	3660.47	0.031439	12.48	793.81	85.15	0.72	
main	66.053	9910.00	3633.37	3643.49	3642.75	3645.39	0.031036	11.66	970.17	181.32	0.72	





Profile Output Table - Standard Table 1
 HEC-RAS Plan: Plan 12 River: fac2w-fac3 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 27
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	8215.041	8636.00	3885.44	3891.96	3886.43	3892.21	0.003189	3.22	2286.52	299.66		0.23
main	8048.594	8636.00	3887.62	3888.54	3887.74	3890.36	0.045852	3.07	802.71	150.43		0.61
main	7770.874	8636.00	3865.13	3872.71	3872.57	3874.74	0.055504	11.76	795.11	192.47		0.88
main	7443.768	8636.00	3844.00	3856.12	3856.12	3858.18	0.066204	13.94	768.39	172.71		0.74
main	7028.908	8636.00	3825.63	3832.44	3832.14	3833.73	0.042874	9.67	1019.55	336.38		0.79
main	6211.489	8636.00	3790.00	3797.18	3796.60	3798.00	0.030728	9.47	1274.72	383.59		0.69
main	5838.303	8636.00	3775.40	3787.44	3782.85	3787.77	0.004766	5.15	2002.21	294.67		0.28
main	5637.145	8636.00	3770.39	3783.64	3780.65	3785.21	0.023227	10.07	857.91	100.63		0.61
main	5123.930	8636.00	3757.61	3770.76	3767.70	3772.54	0.023385	10.71	806.22	87.61		0.62
main	4823	8636.00	3750.12	3765.55	3760.21	3766.67	0.012417	8.50	1015.79	96.70		0.46
main	4685	8636.00	3748.00	3762.63	3758.73	3764.50	0.021426	10.98	786.57	72.55		0.59
main	4455.997	8636.00	3744.81	3755.74	3754.93	3758.74	0.048006	13.90	621.26	78.71		0.87
main	4108.803	8636.00	3728.14	3739.07		3742.07	0.047928	13.89	621.63	78.73		0.87
main	3864.722	8636.00	3716.43	3727.74		3730.47	0.041982	13.24	652.08	80.26		0.82
main	3684.510	9910.00	3707.78	3724.70	3718.68	3725.82	0.011268	8.51	1164.44	102.67		0.45
main	3440.055	9910.00	3705.25	3721.32	3716.15	3722.63	0.013846	9.18	1079.36	104.69		0.49
main	3225.065	9910.00	3703.10	3719.58	3715.09	3720.06	0.004883	6.35	2090.92	329.32		0.30
main	3020.229	9910.00	3701.05	3716.80	3711.97	3718.23	0.014714	9.61	1032.34	94.43		0.50
main	2806.897	9910.00	3698.92	3711.65	3709.84	3714.22	0.034991	12.88	769.61	85.92		0.76
main	2575.744	9910.00	3690.83	3703.56	3701.73	3706.13	0.035013	12.88	769.42	85.90		0.76
main	2275.362	9910.00	3680.31	3693.07	3691.21	3695.63	0.034632	12.83	772.52	86.06		0.75
main	1900.733	9910.00	3667.20	3684.33	3678.10	3685.41	0.010711	8.35	1186.33	103.52		0.43
main	1536.204	9910.00	3654.44	3683.44	3665.34	3683.65	0.001164	3.67	2697.79	151.03		0.15
main	1283.309	9910.00	3666.24	3680.14	3678.14	3682.17	0.022687	11.81	944.81	145.35		0.63
main	941.845	9910.00	3657.02	3671.33	3668.55	3673.50	0.027021	11.81	839.16	87.25		0.67
main	469.409	9910.00	3644.26	3658.05	3655.80	3660.47	0.031439	12.48	793.81	85.15		0.72
main	66.053	9910.00	3633.37	3643.49	3642.75	3645.39	0.031036	11.66	970.17	181.32		0.72















North Portal Pad - Aging with Q topo Plan 12 12/11/2003

River = fac2w-fac3 Reach = main RS = 66.053



Calculations of Volume to be Excavated for North Portal Pad Channel

Delta Column	0		3		6		9		12		15		18		
Delta Row	0	18	15	15	12	6	6	7	4	5	4	5	5	5	
River Station	3684.51	3440.0552	3225.0647	3020.2293	2806.897	2575.7443	2275.362	1900.7328							
Bottom width	35	35 SE\$40	\$E\$39	35 SH\$37	\$H\$36	35 SK\$34	\$K\$33	35 SN\$28	\$N\$27	35 \$Q\$29	\$Q\$28	35 \$T\$26	\$T\$25	35 SWS\$27	\$WS\$26
Top Width	129.24	99.57 SE\$41	\$E\$38	77.88 SH\$38	\$H\$35	89.51 SK\$35	\$K\$32	97.72 SN\$29	\$N\$26	106.91 \$Q\$30	\$Q\$27	135.61 \$T\$27	\$T\$24	158.69 SWS\$28	\$WS\$25
Depth (L)	23.56	16.01 SF\$39	\$F\$38	10.9 SH\$36	\$S\$35	15.41 SK\$33	\$L\$32	17.89 SO\$27	\$O\$26	19.73 \$R\$28	\$R\$27	27.27 \$U\$25	\$U\$24	32.3 SX\$26	\$X\$25
Depth (R)	23.56	16.27 SF\$41	\$F\$40	10.54 SH\$38	\$S\$37	11.85 SK\$35	\$L\$34	13.47 SO\$29	\$O\$28	16.23 \$R\$30	\$R\$29	23.03 \$U\$27	\$U\$26	29.54 SX\$28	\$X\$27
Area	1934.747	1085.9799	605.0368	648.53565	1040.5248	1275.7709	2145.42075	2994.4474							
Volume (yds)		13,675	6,732	5,514	7,463	9,915	19,031	35,658							
Cross - Section Data	0 3732.68	0 3726.27	0 3730.56	0 3730.93	0 3724.59	0 3720	0 3718.01	0 3709.64							
6.88 3732.68	6.96 3726	0.16 3730.55	17.21 3730.62	0.25 3724.59	4.63 3720	0.37 3718	1.54 3709.61								
44.05 3732	9.82 3726	11.25 3730	37.28 3730	12.08 3724	28.06 3718.4	34.41 3716.59	17.25 3709.42								
48.78 3732	14.21 3725.8	48.83 3728.37	70.35 3728.62	18.79 3724	35.02 3718	49.86 3716	70.18 3708.19								
73.52 3732	51.53 3724.93	64.65 3728	81.67 3728	27.72 3723.47	36.69 3717.76	67.52 3714.78	76.29 3708.05								
86.36 3731.65	63.84 3724	83.89 3726.86	110.67 3726.55	53.73 3722	68 3717.49	84.47 3714	77.49 3707.57								
98.25 3731.51	69.46 3724	104.93 3726.41	114.02 3726.48	78.65 3721.12	78.89 3717.5	108.24 3714	91.27 3707.57								
132.91 3731.62	92.64 3724	110.49 3726	127.51 3726	97.41 3720.94	110.43 3716	123.78 3713.21	139.64 3706								
147.47 3730.94	93.76 3723.85	113.02 3725.57	172.43 3722.02	114.35 3720	130.73 3714.31	152.38 3712.61	144 3705.83								
160.47 3730.38	116.33 3723.28	139.59 3723.77	172.61 3722.01	118.36 3719.84	135.78 3714	171.84 3712	149.59 3705.64								
166.97 3731.6	130.93 3723.31	160.04 3722.33	172.73 3722	124.98 3719.57	139.18 3714	216.7 3710.28	178.94 3704								
193.86 3731.86	156.49 3723.83	162 3722	175.08 3722	152.19 3719.07	147.45 3713.34	225.56 3710	186.46 3702.76								
222.62 3731.6	159.99 3723.8	165.83 3722	201.8 3722.32	178.16 3718.69	171.66 3712.55	269.76 3708.43	197.3 3702								
226.37 3731.34	170.69 3724	175.21 3721.44	207.79 3722.27	189.96 3718.25	198.79 3712.45	282.96 3708	209.58 3700.87								
283.68 3731.34	191.26 3724	197.31 3720	216.1 3721.79	199.03 3718	206.28 3712.2	297.4 3707.58	217.07 3699.34								
283.84 3731.34	195.82 3723.39	213.93 3719.47	231.27 3720.88	223.58 3717.32	213.17 3712	351.95 3680.31	222.4 3699.5								
330.96 3707.78	228.35 3722	237.49 3718	253.12 3720.66	239.93 3716.81	238.65 3710.86	386.95 3680.31	287.01 3667.2								
365.96 3707.78	238.58 3722.23	251.84 3717.62	291.96 3716.2	274.71 3698.92	243.79 3710.56	433.01 3703.34	322.01 3667.2								
413.08 3731.34	243.91 3722.26	295.44 3716.31	295.28 3720	309.71 3698.92	283.24 3690.83	462.66 3702.22	381.09 3696.74								
413.24 3731.34	258.52 3723.02	303.7 3716	299.2 3719.77	336.65 3712.39	318.24 3690.83	468.58 3702	395.78 3696.92								
503.06 3731.34	273.58 3723.74	305.66 3716	322.22 3717.5	340.91 3712.39	350.7 3707.06	471.37 3701.9	429.33 3696								
576.79 3730	278.73 3723.62	311.04 3715.8	334.65 3717.16	351.88 3712	358.73 3706.36	522.4 3680	452.8 3695.42								
580.22 3729.96	303.28 3722	357.49 3714.42	344.92 3716.46	375.32 3710.6	363.6 3705.73	547.37 3680	498.64 3680								
581.07 3729.95	311.49 3721.67	365.21 3714.51	375.74 3701.05	388.61 3710.34	371.41 3704	559.92 3680	519.15 3680								
583.08 3729.89	338.93 3721.35	377.71 3714	410.74 3701.05	393.15 3710	385.58 3702.99	587.11 3680	541.61 3680								
618.22 3729	358.19 3722	378.52 3714	434.43 3712.9	409.79 3708.31	416.02 3702	596.04 3680	564.11 3680								
651.23 3728	370.64 3722	400.32 3703.1	437.05 3712.69	425.48 3705.99	428.19 3702	618.41 3680	599.66 3680								
653.77 3727.94	390.18 3721.21	435.32 3703.1	455.48 3708.49	443.27 3704.88	433.43 3701.48	635.53 3680	628.77 3680								
658.29 3727.74	392.99 3721.26	456.4 3713.64	458.44 3708.2	445.7 3703.59	462.44 3702	638.83 3680	639.69 3680								
689.87 3726	425.02 3705.25	474.78 3713.45	498.7 3708.04	465.98 3703.21	467.15 3702.09	666.5 3680									
705.18 3726	460.02 3705.25	490.29 3713.09	499.15 3708	484.09 3704	468.37 3702.07	683.22 3680									
726.23 3724.75	492.56 3721.52	508.94 3713.39	499.36 3707.99	508.19 3704	505.85 3702.52	686.15 3680									
752.04 3724.22	505.85 3721.41	531.63 3714	527.63 3707.66	534.06 3704	525.92 3702	688.74 3680									
758.56 3724	518.6 3721.25	539.8 3714.4	535.36 3707.75	541.18 3704	539.94 3701.31	697.09 3680									
782.5 3723.22	553.43 3720	545.54 3714.15	547.05 3707.49	562.39 3703.02	554.15 3701.27										
	555.07 3719.95	557.76 3714	578.44 3706	582.21 3705.24	580 3698.44										
	558.41 3719.88	587.34 3714	621.54 3709.02	586.07 3706.67	586.46 3697.42										
	602.32 3718.95	624.77 3712.8	632.27 3708.83	587.35 3706.66	593.24 3696										
	618.9 3718	654.53 3712	639.19 3709.45		618.51 3696										
	644.44 3718	673.52 3711.56	644.55 3710		628.7 3696.09										
	649.32 3717.85	700.15 3711.72	656.46 3710.57		629.9 3696.06										
	652.53 3717.81	706.53 3711.66	679.81 3710		631.43 3696										
	679.6 3716.45	748.84 3710	717.24 3709.21		645.15 3696										
	687.04 3716.09	751.08 3710	753.36 3708.31												
	688.07 3716.11	759.4 3710	761.18 3708												
	689.62 3716.16	784.06 3709.1	766.06 3707.81												
	718.22 3716.8		777.13 3707.49												
	724.46 3716.97														
	737.53 3717.29														
	742.13 3717.47														
	748.87 3717.28														
	756.54 3717.12														
	776.69 3716.57														
	797.1 3715.47														


Calculations of Volume to be Excavated for North Portal Pad Channel



Delta Column	21		24		27		30		33								
Delta Flow	4		11		18		12		11								
River Station	1536.2041		1283.3092		941.845		469.4095		66.05								
Bottom width	35 \$Z\$26	\$Z\$25	30 \$AC\$33	\$AC\$32	30 \$AF\$40	\$AF\$39	30 \$AI\$34	\$AI\$33	30 \$AL\$33	\$AL\$32							
Top Width	159.71	\$Z\$27	\$Z\$24	71.59	\$AC\$34	\$AC\$31	110.9	\$AF\$41	\$AF\$38	114.09	\$AI\$35	\$AI\$32	36.85	\$AL\$34	\$AL\$31	Total Volume	Max
Depth (L)	32.27	\$AA\$25	\$AA\$24	10.5	\$AD\$32	\$AD\$31	21.99	\$AG\$39	\$AG\$38	21.9	\$AJ\$33	\$AJ\$32	1.5	\$AM\$32	\$AM\$31	Value	MinValue
Depth (R)	30.08	\$AA\$27	\$AA\$26	10.29	\$AD\$34	\$AD\$33	18.46	\$AG\$41	\$AG\$40	20.14	\$AJ\$35	\$AJ\$34	1.92	\$AM\$34	\$AM\$33	Average	
Area	3035.042125		528.014025		1424.85125		1514.386		57.15675								
Volume (yds)	40,702		16,687		12,349		25,719		11,739						205,179		
	0	3703.6	0	3692.92	0	3684.56	0	3660.84	0	3655.27							
Cross - Section Data	30.8	3702.66	1.93	3692.95	14.41	3684	0.12	3660.85	1.31	3655.26							
	49.84	3702	20.68	3693.31	41.24	3683.01	5.74	3660.84	15.27	3655.19							
	62.01	3701.38	36.98	3693.06	53.83	3682	9.39	3660.79	40.4	3656							
	89.03	3700	58.79	3692.77	68.41	3680.99	17.17	3662	41.09	3656							
	95.71	3698.74	87.32	3692.49	73.27	3680	35.15	3663.03	67.56	3655.24							
	105.05	3696.24	97.88	3692.4	78.88	3679.02	44.77	3664.59	83.16	3655.07							
	116.55	3694.63	108.05	3692	110.23	3678	52.36	3665.4	106.62	3654							
	124.75	3692.24	132.5	3691.14	110.37	3678.01	66.55	3666.7	126.75	3653.18							
	126.16	3691.88	170.26	3690	110.93	3678	72.52	3667.16	139.98	3652							
	150.9	3688.86	183.06	3689.59	142.08	3678	82.31	3667.69	157.87	3650.18							
	156.39	3688	211.83	3688.6	160.74	3679.93	105.87	3668.32	159.87	3650							
	171.72	3688	223.82	3688.25	162.24	3680	111.24	3668.2	163.7	3649.54							
	200.35	3687.05	228.08	3688	164.78	3680.16	163.9	3668.05	179.3	3647.6							
	218.64	3686.71	230.16	3687.63	181.2	3682	165.5	3668.06	198.72	3645.06							
	283.19	3654.44	247.81	3687.18	202.02	3682.76	172.65	3668	204.8	3644.2							
	318.19	3654.44	282.16	3686	230.4	3682.68	206.33	3667.67	208.58	3643.66							
	378.35	3684.52	285.63	3685.23	241.36	3682.43	213.53	3667.64	228.01	3640.93							
	391.15	3684.85	299.51	3680.97	274.95	3682.03	246.14	3668	239.79	3638.93							
	400.01	3686.47	302.69	3679.88	275.8	3682.03	254.18	3668.09	246.72	3637.03							
	410.06	3688.61	315.46	3676.93	276.64	3682	256.93	3668	253.8	3635.61							
	456.62	3689.93	320.19	3676.74	311.48	3681.22	282.46	3666.57	268.01	3634.87							
	457.71	3690	341.2	3666.24	332.38	3681.09	296.57	3666.16	271.02	3633.37							
	458.08	3689.99	371.2	3666.24	348.4	3681.08	340.37	3644.26	301.02	3633.37							
	458.99	3689.96	391.78	3676.53	381.8	3680.31	370.37	3644.26	304.86	3635.29							
	507.79	3680	406.01	3676	388.24	3680.2	410.66	3664.4	311.37	3635.71							
	524.53	3680	406.96	3675.99	395.53	3680	424.75	3664	316.84	3637.03							
	565.62	3680	407.4	3676	436.96	3679.16	431.33	3663.61	328.13	3639.05							
	597.54	3680	409.8	3676.34	442.07	3679.01	439.55	3663.54	332.24	3639.85							
	618.15	3680	422.83	3678.31	486.05	3657.02	466.23	3663.35	332.7	3639.95							
	640.99	3680	425.35	3678.69	516.05	3657.02	478.41	3663.3	335.09	3640							
	664.7	3680	447.3	3680	552.97	3675.48	514.36	3662.44	374.91	3640.59							
	666.65	3680	448.68	3680	589.6	3674.13	524.8	3662.15	388.16	3642.73							
			454.29	3680	592.49	3674	530.1	3662	390.98	3643.47							
			489.29	3680	618.62	3672.34	565.86	3660.79	403.15	3645.13							
			497.2	3680	623.52	3672	589.84	3660	411.77	3646							
			529.41	3680	644.49	3670.04	610.11	3659.57	417.28	3646.47							
			531.92	3680	644.99	3670.02	623.42	3659.25	429.9	3646.64							
			534.47	3680	645.33	3670	648.88	3658.96	442.39	3648							
			573.97	3680	698.24	3670	675.78	3656.34	469.08	3649.56							
			591.99	3680	699.97	3669.55	690.86	3658	476.12	3650							
					726.65	3668	693.25	3657.95	482.07	3650.44							
					728.19	3667.54	696.26	3657.87	503.77	3652							
					739.3	3667.15	733.44	3656.74	542.87	3653.74							
					753.11	3664	764.85	3656	547.02	3653.9							
					790.53	3664	782.58	3655.57	552.17	3654							
					792.45	3664.53	835.02	3654.29	602.15	3655.1							
					807.31	3669.68	844.62	3654.03	628.99	3655.23							
					808.22	3670			643.87	3655.34							
					824.9	3670			680.79	3655.68							
					837.04	3669.18			690.48	3655.72							
					858.35	3669.6			697.49	3655.6							
					870	3669.36			725.98	3655.13							
					897.2	3674											
					923.66	3674											
					927.98	3674											
					935.5	3674											
					958.97	3674											
					982.7	3674											

Profile Output Table - Standard Table 1
 HEC-RAS Plan: lev River: fac2w-fac3 Reach: main



Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 27
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	8215.041	8636.00	3885.44	3891.74	3886.43	3892.00	0.003481	3.29	2219.06	297.80		0.23
main	8048.594	8636.00	3887.62	3887.77	3887.77	3890.21	0.074641	0.80	688.78	143.01		0.52
main	7770.874	8636.00	3865.13	3873.20	3872.62	3874.83	0.040449	10.60	891.78	202.47		0.76
main	7443.768	8636.00	3844.00	3856.14	3856.14	3858.18	0.065561	13.88	771.04	172.88		0.74
main	7028.908	8636.00	3825.63	3832.65	3832.14	3833.84	0.037487	9.31	1094.00	359.98		0.74
main	6211.489	8636.00	3790.00	3796.64	3796.64	3797.86	0.052309	11.58	1068.69	377.00		0.89
main	5838.303	8636.00	3775.40	3788.43	3782.77	3788.68	0.003269	4.51	2302.78	312.78		0.24
main	5637.145	8636.00	3771.98	3782.64	3782.64	3786.56	0.064877	15.87	544.07	69.03		1.00
main	5123.930	8636.00	3763.26	3777.96	3774.02	3779.48	0.018437	9.89	872.81	88.78		0.56
main	4823	8636.00	3758.14	3773.61	3768.41	3774.77	0.012899	8.64	1000.03	95.59		0.47
main	4685	8636.00	3755.80	3767.24	3767.24	3771.10	0.064256	15.77	547.71	70.76		1.00
main	4455.997	8636.00	3751.90	3764.44	3761.18	3764.63	0.004262	3.69	2481.61	425.34		0.26
main	4108.803	8636.00	3746.00	3756.42	3756.42	3760.47	0.066421	16.15	534.63	65.50		1.00
main	3864.722	8636.00	3737.87	3742.83	3742.24	3743.84	0.035385	8.81	1141.07	334.48		0.72
main	3684.510	9910.00	3730.02	3733.57	3733.53	3734.66	0.074547	8.81	1202.36	503.06		0.94
main	3440.055	9910.00	3721.78	3727.18	3725.39	3727.60	0.014582	5.65	1918.27	461.91		0.43
main	3225.065	9910.00	3713.81	3726.88	3718.20	3726.97	0.000972	2.87	4235.01	448.13		0.14
main	3020.229	9910.00	3714.00	3726.06	3722.19	3726.51	0.007600	6.45	1935.10	294.72		0.33
main	2806.897	9910.00	3712.88	3722.95	3721.60	3723.88	0.022123	9.32	1372.74	289.87		0.56
main	2575.744	9910.00	3708.76	3718.95	3715.98	3719.57	0.015308	7.01	1581.93	290.21		0.39
main	2275.362	9910.00	3704.24	3714.20	3711.86	3714.94	0.015431	8.20	1581.54	328.55		0.48
main	1900.733	9910.00	3695.65	3701.94	3701.94	3704.44	0.062605	13.17	804.57	163.04		0.96
main	1536.204	9910.00	3684.24	3691.14	3689.54	3691.84	0.019907	8.24	1503.77	324.40		0.57
main	1283.309	9910.00	3676.00	3687.82	3682.62	3688.60	0.008857	8.06	1513.21	196.26		0.42
main	941.845	9910.00	3676.42	3684.19	3682.55	3684.62	0.015100	6.78	1959.36	515.62		0.45
main	469.409	9910.00	3665.22	3669.35	3669.35	3670.72	0.078687	11.15	1069.45	375.79		0.98
main	66.053	9910.00	3634.00	3643.76	3643.05	3645.62	0.031040	11.59	982.56	185.25		0.73








these sections
 (4823 + 4885) aren't
 shown on Fig 5-6,
 but they look OK.












**Attachment 11: Hydraulic Calculations for Routing East of North Portal Pad,
Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**




Profile Output Table - Standard Table 1
 HEC-RAS Plan: Q-cp5cp6 River: cp5cp6 Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 13
 # Plans = 1
 # Profiles = 1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	7436.775	6600.00	3709.79	3719.37	3718.74	3721.30	0.032914	12.91	664.09	130.04		0.76
main	7021.613	6600.00	3692.64	3701.44	3701.42	3704.22	0.052392	13.71	519.91	100.92		0.92
main	6500.608	6600.00	3673.63	3682.86		3684.47	0.027864	11.98	680.37	108.51		0.71
main	6115.281	6600.00	3658.08	3667.61	3667.61	3670.56	0.047553	14.71	518.79	93.26		0.90
main	5705.012	6600.00	3646.93	3658.26	3654.87	3659.12	0.011765	8.72	939.60	129.96		0.47
main	5224.491	15908.00	3634.00	3644.94		3647.51	0.035105	15.39	1371.07	215.95		0.82
main	4775.979	15908.00	3620.03	3632.71		3634.55	0.023438	13.03	1576.09	217.78		0.68
main	4247.177	15908.00	3607.26	3618.28		3620.38	0.030858	14.32	1483.03	231.20		0.77
main	3745.220	15908.00	3593.93	3604.11		3605.90	0.026697	12.75	1580.81	242.08		0.71
main	3206.879	15908.00	3582.00	3590.58	3589.20	3591.54	0.025769	11.23	2477.53	800.61		0.68
main	2535.671	15908.00	3566.00	3572.29	3571.66	3572.90	0.029679	9.15	2772.39	1050.63		0.68
main	1446.724	15908.00	3546.00	3549.28		3549.53	0.016088	4.68	3978.98	1556.38		0.45
main	180.971	15908.00	3518.07	3522.69	3521.63	3523.32	0.028034	7.56	2539.46	776.58		0.63


Routing along cp5cp6 Qtopo-debris flow along cp5cp6 11/24/2003

RS = 7436.775




Routing along cp5cp6 Qtopo-debris flow along cp5cp6 11/24/2003

RS = 7021.613




Routing along cp5cp6 Qtopo-debris flow along cp5cp6 11/24/2003


RS = 6500.608




Routing along cp5cp6 Qtopo-debris flow along cp5cp6 11/24/2003


RS = 6115.281








Routing along cp5cp6 Qtopo-debris flow along cp5cp6 11/24/2003




**Attachment 12: Hydraulic Calculations for Routing Downstream of North Portal Pad,
Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**




Profile Output Table - Standard Table 1
 HEC-RAS Plan: Q-fac3cp6 River: fac3cp6 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 9
 # Plans = 1
 # Profiles = 1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	3786.480	6135.00	3596.41	3603.02	3603.02	3605.15	0.065069	12.69	558.57	151.10	0.98	
main	3421.348	6135.00	3586.00	3592.69	3590.90	3593.22	0.016318	6.92	1107.96	278.51	0.50	
main	3071.519	6135.00	3578.00	3584.19	3583.93	3585.14	0.034721	9.95	900.89	324.18	0.73	
main	2607.715	6135.00	3568.00	3573.32		3573.63	0.018078	5.91	1479.82	628.25	0.50	
main	2105.532	6135.00	3558.00	3562.67	3562.01	3563.04	0.024826	6.23	1336.95	627.99	0.57	
main	1551.928	6135.00	3546.00	3549.20	3548.22	3549.50	0.024055	5.34	1410.40	655.44	0.55	
main	1025.787	6135.00	3533.78	3536.87		3537.16	0.022853	4.82	1411.47	665.47	0.52	
main	557.280	6135.00	3524.00	3527.52	3526.39	3527.80	0.017614	5.13	1500.34	631.04	0.48	
main	55.956	6135.00	3514.00	3517.09	3516.17	3517.54	0.024009	5.48	1167.38	434.55	0.55	






Routing along fac3cp6 Qtopo-debris flow for Fac3cp6 routing 11/24/2003




**Attachment 13: Hydraulic Calculations for Routing Near Railroad Bridge Crossing,
Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**





HEC-RAS Output for Routing Under Railroad Bridge, Alternative 1


HEC-RAS Plan: plan1 River: RR_cp8 Reach: reach1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl	Max Chl Dpth (ft)	Invert Slope
reach1	7119.762	2486	3656.23	3658.83	3658.5	3659.31	0.053031	5.57	455.31	320.23	0.74	2.6	0.3575
reach1	6889.707	2486	3646.61	3650.86		3651.07	0.017481	3.8	696.35	415.52	0.45	4.25	0.3157
reach1	6445.414	2486	3633.43	3647.15	3635.82	3647.15	0.000023	0.43	7351.54	1026.74	0.02	13.72	0.2861
reach1	6003.442	23416	3624	3647.04	3632.38	3647.08	0.00028	2.1	17241.76	2423.55	0.08	23.04	0.2647
reach1	5854.853	23416	3620	3647.03	3628.87	3647.04	0.000073	1.18	32209.01	3240.41	0.04	27.03	0.2378
reach1	5735.813	23416	3618	3647.03	3627.01	3647.03	0.000023	0.69	49084.55	3496.47	0.02	29.03	0.221
reach1	5600	Bridge											
reach1	5478.482	23416	3612.2	3618.16	3620.24	3625.04	0.348387	21.26	1129.56	388.1	2.1	5.96	0.1905
reach1	5179.747	23416	3605.27	3614.95	3613.97	3616.22	0.03011	9.54	2832.41	732.19	0.69	9.68	0.1673
reach1	4821.742	23416	3598	3606.58		3607.16	0.018957	7.07	4198.95	1248.33	0.54	8.58	0.147
reach1	3938.849	25928	3581.82	3589.82		3590.63	0.017788	7.28	3626.1	721.75	0.53	8	0.1287
reach1	3331.107	25928	3570	3582.81		3583.29	0.006124	5.73	4845.21	660.74	0.33	12.81	0.1092
reach1	2846.861	25928	3562	3574.95		3576.42	0.021805	10	2791.26	457.3	0.62	12.95	0.0927
reach1	2360.348	25928	3552	3566.11		3567.09	0.015862	8.48	3594.06	719.01	0.52	14.11	0.0721
reach1	1908.948	25928	3544	3558.08		3559.41	0.01797	9.88	3088.44	548.84	0.57	14.08	0.0544
reach1	1375.587	25928	3534.76	3548.63		3550.07	0.017219	10.41	3027.2	524.03	0.57	13.87	0.0371
reach1	823.456	25928	3526.79	3538.47		3539.84	0.019766	10.08	2968.3	477.5	0.59	12.47	0.0226
reach1	170.341	25928	3512	3522.38	3521.19	3523.96	0.028024	10.5	2769.85	559.06	0.69	10.38	












HEC-RAS Output for Clear Span Scenario for Alternative 1

HEC-RAS Plan: nopiers River: RR_cp8 Reach: reach1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl	Max Chl Dpth (ft)	Invert Slope
reach1	7119.762	2486	3656.23	3658.5	3658.5	3659.23	0.103598	6.88	361.52	255.36	1.01	2.27	0.3575
reach1	6889.707	2486	3646.61	3650.58	3649.87	3650.87	0.026398	4.36	590.86	355.04	0.54	3.97	0.3157
reach1	6445.414	2486	3633.43	3644.91	3635.82	3644.92	0.000054	0.57	5308.68	853.11	0.03	11.48	0.2861
reach1	6003.442	23416	3624	3644.72	3632.38	3644.79	0.000505	2.61	12728.37	1645.46	0.11	20.72	0.2647
reach1	5854.853	23416	3620	3644.7	3628.87	3644.72	0.000155	1.6	24689.21	3216.85	0.06	24.7	0.2378
reach1	5735.813	23416	3618	3644.7	3627.01	3644.71	0.00004	0.86	40957.2	3484.69	0.03	26.7	0.221
reach1	5600	Bridge											
reach1	5478.482	23416	3612.2	3618.17	3620.24	3624.99	0.34365	21.17	1134.97	388.75	2.09	5.97	0.1905
reach1	5179.747	23416	3605.27	3614.95	3613.97	3616.22	0.03011	9.54	2832.41	732.19	0.69	9.68	0.1673
reach1	4821.742	23416	3598	3606.58		3607.16	0.018957	7.07	4198.95	1248.33	0.54	8.58	0.147
reach1	3938.849	25928	3581.82	3589.82		3590.63	0.017788	7.28	3626.1	721.75	0.53	8	0.1287
reach1	3331.107	25928	3570	3582.81		3583.29	0.006124	5.73	4845.21	660.74	0.33	12.81	0.1092
reach1	2846.861	25928	3562	3574.95		3576.42	0.021805	10	2791.26	457.3	0.62	12.95	0.0927
reach1	2360.348	25928	3552	3566.11		3567.09	0.015862	8.48	3594.06	719.01	0.52	14.11	0.0721
reach1	1908.948	25928	3544	3558.08		3559.41	0.01797	9.88	3088.44	548.84	0.57	14.08	0.0544
reach1	1375.587	25928	3534.76	3548.63		3550.07	0.017219	10.41	3027.2	524.03	0.57	13.87	0.0371
reach1	823.456	25928	3526.79	3538.47		3539.84	0.019766	10.08	2968.3	477.5	0.59	12.47	0.0226
reach1	170.341	25928	3512	3522.38	3521.19	3523.96	0.028024	10.5	2769.85	559.06	0.69	10.38	

These results show how water surface elevations upstream of the railroad bridge would be approximately 2 ft. lower if both bridges were constructed as clear spans.

Clear Span Scenario




**Attachment 14: Hydraulic Calculations for South Portal Routings, Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)**




Profile Output Table - Standard Table 1
 HEC-RAS Plan: Qspl-mod River: sportall1 Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 14
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	5948.179	6765.00	3898.00	3903.50	3903.46	3904.88	0.050825	11.04	790.50	270.29	0.87	
main	5639.986	6765.00	3884.00	3888.86		3890.05	0.045509	10.16	815.74	247.94	0.82	
main	5194.676	6765.00	3862.50	3866.70	3866.48	3867.38	0.056452	8.14	1046.61	518.39	0.84	
main	4738.707	6765.00	3842.00	3847.83	3847.83	3848.56	0.031369	9.38	1309.00	726.66	0.69	
main	4209.766	6765.00	3818.29	3821.60	3821.72	3822.54	0.087759	9.73	914.13	581.06	1.03	
main	3573.802	6765.00	3787.35	3791.09	3790.36	3791.34	0.026304	5.60	1736.35	1029.80	0.57	
main	3052.944	6765.00	3764.00	3766.08	3766.08	3766.88	0.103582	8.73	955.90	657.58	1.07	
main	2618.102	8248.00	3746.97	3750.18	3748.97	3750.50	0.015978	4.30	1964.28	801.29	0.44	
main	2189.383	8248.00	3730.59	3737.99	3737.99	3739.61	0.045036	12.82	912.70	255.30	0.86	
main	1573.409	8248.00	3715.33	3720.63	3717.91	3720.84	0.006012	3.70	2252.07	477.20	0.30	
main	1187.055	8248.00	3705.73	3713.67	3713.07	3715.76	0.042005	13.24	744.83	127.27	0.85	
main	770.309	8248.00	3692.50	3698.07	3697.23	3699.14	0.036600	9.66	1013.01	254.20	0.74	
main	375.616	8248.00	3679.79	3682.98	3682.34	3683.60	0.041746	7.02	1310.81	523.23	0.72	
main	21.937	8248.00	3668.22	3670.36	3669.63	3670.83	0.031300	4.42	1502.13	595.81	0.58	




South Portal Routing Q-Debris flow at S Portal 1 - prop Q mod 11/24/2003




South Portal Routing Q-Debris flow at S Portal 1 - prop Q mod 11/24/2003




South Portal Routing Q-Debris flow at S Portal 1 - prop Q mod 11/24/2003




South Portal Routing Q-Debris flow at S Portal 1 - prop Q mod 11/24/2003






South Portal Routing Q-Debris flow at S Portal 1 - prop Q mod 11/24/2003




South Portal Routing Q-Debris flow at S Portal 1 - prop Q mod 11/24/2003





Profile Output Table - Standard Table 1
 HEC-RAS Plan: Q-sportal2 River: sportal2 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 11
 # Plans = 1
 # Profiles = 1

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	2359.352	1000.00	3805.70	3809.18	3808.43	3809.72	0.029921	6.36	182.24	77.50	0.62	
main	2045.065	1000.00	3794.00	3797.60		3798.27	0.045202	7.18	167.22	91.72	0.74	
main	1811.135	1000.00	3787.56	3790.47		3790.78	0.023241	4.71	231.46	111.42	0.52	
main	1648.293	1000.00	3781.36	3783.72	3783.72	3784.42	0.078375	7.65	159.88	113.66	0.93	
main	1461.889	1000.00	3774.92	3777.68	3776.85	3777.89	0.017931	4.21	287.96	165.93	0.46	
main	1260.977	1000.00	3768.44	3770.17	3770.17	3770.83	0.095761	7.13	157.98	121.74	0.99	
main	1085.369	1000.00	3762.00	3764.62	3763.69	3764.77	0.014725	3.21	324.35	182.10	0.40	
main	894.514	1000.00	3756.00	3758.71	3758.71	3759.51	0.066417	7.76	152.43	98.54	0.88	
main	628.252	1000.00	3748.41	3750.81	3749.95	3750.97	0.015826	3.62	322.01	187.08	0.42	
main	336.737	1000.00	3738.00	3741.76	3741.76	3742.46	0.069236	7.62	164.31	117.30	0.88	
main	11.824	1000.00	3730.41	3737.99	3733.55	3738.02	0.000762	1.66	815.11	233.27	0.11	











Profile Output Table - Standard Table 1


HEC-RAS Plan: Q-sportal3 River: sportal3 Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 9
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	1598.140	484.00	3840.29	3842.20	3842.16	3842.65	0.073753	6.12	97.58	96.20		0.86
main	1454.774	484.00	3829.00	3830.83	3830.83	3831.33	0.084764	6.69	92.24	91.06		0.93
main	1334.949	484.00	3821.59	3823.71	3823.47	3823.97	0.037830	4.89	131.11	121.09		0.63
main	1170.287	484.00	3812.45	3813.72	3813.72	3814.08	0.106348	4.02	103.95	139.46		0.89
main	955.880	484.00	3800.00	3800.84	3800.66	3800.94	0.033011	2.62	208.66	368.87		0.52
main	689.799	484.00	3784.23	3784.81	3784.81	3784.99	0.131993	2.69	144.42	433.96		0.87
main	494.827	484.00	3771.33	3772.46	3772.22	3772.53	0.031766	2.56	237.97	450.38		0.50
main	241.653	484.00	3756.97	3757.74	3757.74	3757.96	0.136168	4.19	127.84	303.44		0.99
main	64.428	484.00	3747.10	3750.18	3748.87	3750.20	0.001836	1.36	512.92	370.45		0.15







South Portal Routing Q-Debris flow at S Portal 3 mod 12/7/2003



Attachment 15: Scour Analysis, Alternative 1
(Document ID: 000-00C-CD04-00100-000-00A)

CSU Equation for local scour

$$\frac{y_s}{a} = 2.0 K_1 K_2 K_3 \left(\frac{y_1}{a}\right)^{0.35} F_r^{0.43} \quad (\text{Eq. } \overset{6.3}{22}) \quad (\text{Ref. 17})$$

max. water depth $y_1 = 29$ feet @ bridge north of
~~26~~ \rightarrow $\overset{31.104}{\text{at pm}}$ Muck Storage A

from previous study (BSC, 2002)
 $\left\{ \begin{array}{l} K_1 = 1.0 \text{ round rose pier} \\ K_2 = 1.0 \text{ piers aligned w/ flow} \\ K_3 = 1.2 \text{ medium dunes} \end{array} \right.$

(Ref. 6, p. 43) $\frac{y_s}{a} = 2.0 \times 1 \times 1 \times 1.2 \times \left(\frac{29}{4}\right)^{0.35} (0.02)^{0.43}$

$\therefore \frac{y_s}{a} = 0.89 \checkmark$

$y_s = 0.89 \times 4 = \boxed{3.6 \text{ ft}} \checkmark$


note: That the value of K_4 using the new method is 1.0 so answer at the bridge @ H-road is unchanged.

$y_1 = 8$ feet


$\frac{y_s}{a} = 2 \times 1 \times 1 \times 1.2 \times \left(\frac{8}{4}\right)^{0.35} (0.02)^{0.43}$

$= 0.57$
 $y_s = 0.57 \times 4 = \boxed{2.3 \text{ ft}}$


**Attachment 16: Hydraulic Calculations for Routing Around Muck Storage A,
Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 17331.33




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 17044.08




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 16814.03




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 16390.46




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 15649.82




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 15010.95



Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 14370.94




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 13789.19




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004

Geom: Exist. ground for cp2cp6 routing - Alt2
RS = 13272.53




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004

Geom: Exist. ground for cp2cp6 routing - Alt2
RS = 13174.58




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004


Geom: Exist. ground for cp2cp6 routing - Alt2
RS = 12711.60




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004

Geom: Exist. ground for cp2cp6 routing - Alt2
RS = 11769.43







Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 4641.928




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 2916.802



Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 1729.693




Alt2 routing along cp2cp6 1) a2-cp2cp6-b 2/19/2004
 Geom: Exist. ground for cp2cp6 routing - Alt2
 RS = 286.470





Profile Output Table - Standard Table 1
 HEC-RAS Plan: a2-cp2cp6-b River: cp2cp6 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 20
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	17331.33	6300.00	3929.04	3933.06	3932.60	3933.78	0.045862	8.51	949.91	387.94	0.78	
main	17044.08	6300.00	3914.24	3918.78	3918.78	3919.65	0.052248	10.36	948.96	465.05	0.86	
main	16814.03	6300.00	3889.00	3904.99	3898.69	3905.74	0.008430	6.97	903.55	83.52	0.37	
main	16390.46	6300.00	3885.48	3902.22	3894.98	3902.75	0.005388	6.23	1188.76	148.29	0.29	
main	15649.82	6300.00	3880.66	3897.73	3890.29	3898.34	0.006510	6.24	1009.98	93.30	0.33	
main	15010.95	6300.00	3876.51	3893.56	3886.14	3894.16	0.006558	6.25	1007.21	93.17	0.34	
main	14370.94	6300.00	3872.35	3889.29	3881.98	3889.91	0.006735	6.32	997.38	92.76	0.34	
main	13789.19	6300.00	3868.57	3885.11	3878.20	3885.77	0.007458	6.56	960.35	91.15	0.36	
main	13272.53	6300.00	3864.98	3880.50	3874.61	3881.31	0.009759	7.25	869.32	87.06	0.40	
main	13174.58	6300.00	3865.00	3875.31	3874.64	3878.10	0.051846	13.40	470.30	66.23	0.89	
main	12711.60	6300.00	3853.52	3859.22	3859.22	3859.78	0.024392	8.14	1123.65	378.12	0.61	
main	11769.43	9820.00	3820.16	3827.25	3826.68	3828.76	0.041261	11.41	1045.59	245.96	0.81	
main	10589.56	9820.00	3775.33	3784.35	3783.37	3785.88	0.031563	11.94	1061.83	211.52	0.74	
main	8898.103	9820.00	3720.00	3733.13	3733.13	3735.41	0.028049	14.38	913.27	139.67	0.74	
main	8023.108	9820.00	3696.00	3705.56	3704.83	3707.61	0.035381	13.34	919.31	159.79	0.79	
main	6682.772	9820.00	3662.00	3676.11	3671.91	3676.99	0.009811	9.13	1437.62	188.24	0.45	
main	4641.928	9820.00	3615.16	3623.12	3623.12	3625.05	0.040989	12.54	932.16	183.17	0.82	
main	2916.802	9820.00	3580.00	3586.90	3586.90	3586.98	0.002506	3.03	4373.92	1010.61	0.20	
main	1729.693	9820.00	3555.15	3559.36	3558.03	3559.75	0.021017	6.21	2029.47	743.48	0.54	
main	286.470	9820.00	3522.00	3526.59	3525.70	3527.06	0.024421	7.03	1849.18	670.71	0.59	



















Attachment 17: Hydraulic Calculations for Routing Around Aging Pad 3, Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)














Alt 2 routing for D7cp6 1) A2_d7cp6 2/24/2004
 Geom: Exist ground for d7cp6: alt2
 RS = 4220.337




Alt 2 routing for D7cp6 1) A2_d7cp6 2/24/2004
 Geom: Exist ground for d7cp6: alt2
 RS = 3416.825




Alt 2 routing for D7cp6 1) A2_d7cp6 2/24/2004
 Geom: Exist ground for d7cp6: alt2
 RS = 2408.215



Alt 2 routing for D7cp6 1) A2_d7cp6 2/24/2004
 Geom: Exist ground for d7cp6: alt2
 RS = 1620.471








Profile Output Table - Standard Table 1
 HEC-RAS Plan: A2_d7cp6 River: d7cp6 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 22
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	9975.106	780.00	3812.80	3815.46	3815.45	3816.27	0.079881	7.60	114.29	75.37	0.93	
main	9801.160	780.00	3800.80	3806.99	3805.09	3807.48	0.019990	5.62	138.69	34.79	0.50	
main	9676.552	780.00	3798.31	3804.53	3802.60	3805.01	0.019684	5.59	139.46	34.87	0.49	
main	9556.460	780.00	3795.91	3802.42	3800.20	3802.84	0.016216	5.21	149.84	36.04	0.45	
main	9414.334	780.00	3793.06	3800.87	3797.35	3801.10	0.007460	3.90	199.88	41.22	0.31	
main	9294.755	780.00	3790.67	3795.27	3794.96	3796.48	0.068210	8.84	88.22	28.38	0.88	
main	9139.052	780.00	3781.48	3786.52		3787.44	0.046738	7.69	101.37	30.19	0.74	
main	8969.225	780.00	3774.69	3780.43		3781.05	0.027528	6.33	123.20	32.94	0.58	
main	8735.299	780.00	3765.33	3770.15		3771.21	0.056321	8.23	94.77	29.38	0.81	
main	8464.553	780.00	3754.22	3759.17	3758.07	3759.67	0.027637	5.69	138.44	47.84	0.57	
main	8165.679	780.00	3742.54	3747.58	3746.83	3748.50	0.046967	7.71	101.18	30.16	0.74	
main	7842.364	780.00	3729.61	3735.20	3733.90	3735.87	0.030749	6.59	118.27	32.34	0.61	
main	7651.747	1710.00	3721.99	3728.65	3727.90	3729.68	0.033758	8.60	224.95	65.99	0.68	
main	6693.994	1710.00	3694.90	3699.29		3700.00	0.028090	6.98	265.11	82.62	0.62	
main	5946.033	1710.00	3672.24	3677.33		3678.01	0.030711	6.65	262.15	83.03	0.63	
main	5119.450	1710.00	3646.00	3651.15		3651.96	0.032238	7.37	249.90	88.11	0.66	
main	4220.337	1710.00	3621.48	3625.98		3626.49	0.024142	6.66	318.71	118.41	0.58	
main	3416.825	1710.00	3601.45	3604.59	3603.92	3604.99	0.029213	5.48	347.31	161.72	0.59	
main	2408.215	1710.00	3574.58	3576.05	3575.66	3576.28	0.027433	2.68	480.67	363.32	0.48	
main	1620.471	1710.00	3556.00	3559.39	3558.53	3559.57	0.015234	3.62	557.12	387.03	0.42	
main	740.439	1710.00	3537.20	3540.59	3539.86	3540.91	0.027174	4.64	387.06	199.58	0.55	
main	58.720	1710.00	3522.00	3524.13	3523.58	3524.29	0.021711	3.64	581.65	494.32	0.48	



















Attachment 18: Hydraulic Calculations for Routing Around Aging Pad 2, Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004

Geom: Exist ground for d8cp5: alt2
RS = 4431.679




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004

Geom: Exist ground for d8cp5: alt2
RS = 4157.539




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004

Geom: Exist ground for d8cp5: alt2
RS = 3934.955




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004

Geom: Exist ground for d8cp5: alt2
RS = 3744.804




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004

Geom: Exist ground for d8cp5: alt2
RS = 3574.439




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004

Geom: Exist ground for d8cp5: alt2
RS = 3408.435




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004


Geom: Exist ground for d8cp5: alt2
RS = 3259.103




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004

Geom: Exist ground for d8cp5: alt2
RS = 3057.014







Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004
 Geom: Exist ground for d8cp5: alt2
 RS = 924.243



Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004
 Geom: Exist ground for d8cp5: alt2
 RS = 542.899




Alt2 routing for d8cp5 1) a2_d8cp5 2/26/2004
 Geom: Exist ground for d8cp5: alt2
 RS = 76.208





Profile Output Table - Standard Table 1
 HEC-RAS Plan: a2_d8cp5 River: d8cp5 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 15
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	4431.679	1100.00	3813.00	3822.87	3818.14	3823.09	0.005292	3.75	293.48	49.48	0.27	
main	4157.539	1100.00	3811.63	3821.36	3816.77	3821.59	0.005643	3.84	286.53	48.91	0.28	
main	3934.955	1100.00	3810.52	3820.01	3815.66	3820.25	0.006311	4.00	274.83	47.94	0.29	
main	3744.804	1100.00	3809.57	3818.62	3814.71	3818.91	0.007766	4.32	254.36	46.21	0.32	
main	3574.439	1100.00	3807.44	3813.52	3812.58	3814.55	0.042556	8.16	136.40	47.10	0.72	
main	3408.435	1100.00	3805.23	3807.52	3807.02	3807.89	0.035208	5.12	235.82	157.91	0.62	
main	3259.103	1100.00	3798.72	3801.97	3801.43	3802.41	0.038158	5.29	209.69	110.17	0.65	
main	3057.014	1100.00	3790.41	3793.54	3793.24	3794.05	0.044581	6.41	209.48	133.90	0.72	
main	2801.107	1100.00	3778.49	3782.16	3781.67	3782.77	0.043389	6.30	177.68	78.45	0.71	
main	2440.716	1100.00	3765.91	3769.82	3768.79	3770.31	0.025259	5.62	198.18	69.49	0.56	
main	2045.932	1100.00	3752.00	3756.72	3756.07	3757.49	0.039563	7.04	158.00	56.25	0.70	
main	1394.165	1100.00	3731.26	3735.22	3734.32	3735.73	0.027044	5.78	195.54	71.52	0.58	
main	924.243	1100.00	3714.52	3718.85	3718.30	3719.60	0.041610	7.03	160.81	60.58	0.72	
main	542.899	1100.00	3704.00	3708.97	3707.01	3709.23	0.012056	4.09	269.24	80.68	0.39	
main	76.208	1100.00	3688.25	3691.75	3691.75	3692.56	0.059159	7.78	168.82	102.25	0.84	













**Attachment 19: Hydraulic Calculations for Routing Around North Construction Portal,
Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**





Profile Output Table - Standard Table 1
 HEC-RAS Plan: A2-D3 River: d3cpl Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 9
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	3736.659	5800.00	3929.48	3932.32	3931.13	3932.62	0.015351	3.62	1344.61	457.65		
main	3205.014	5800.00	3905.25	3908.10	3908.02	3908.99	0.073431	8.59	791.40	400.40		0.42
main	2745.979	5800.00	3882.28	3885.41	3885.41	3885.71	0.027046	4.88	1328.21	682.88		0.94
main	2379.708	8650.00	3867.08	3869.28	3868.85	3869.65	0.040791	4.45	1771.86	1023.70		0.56
main	1975.256	8650.00	3844.68	3848.18	3847.91	3848.95	0.061402	6.07	1262.63	635.92		0.64
main	1550.640	8650.00	3826.82	3829.94		3830.25	0.025824	4.47	1942.50	922.80		0.80
main	1093.631	8650.00	3808.81	3814.15		3815.08	0.040280	9.00	1254.51	582.66		0.54
main	644.474	8650.00	3789.90	3796.18	3795.50	3797.37	0.038413	8.70	1011.72	305.15		0.76
main	84.385	8650.00	3773.28	3777.18	3776.41	3777.74	0.030999	6.38	1446.63	585.80		0.74
												0.63










Alt2 routing for D3 Bulked flow for exist ground: alt2 2/20/2004





**Attachment 20: Hydraulic Calculations for Routing North of Aging Facility,
Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**












Alt2 routing for ND2cp3 1) a2-ND2cp3 2/25/2004

Geom: Exist ground for ND2CP3: alt2


RS = 48.717





Profile Output Table - Standard Table 1
 HEC-RAS Plan: a2-ND2cp3 River: nd2cp3 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 17
 # Plans = 1
 # Profiles = 1





Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	4055.409	8650.00	3846.50	3856.77	3857.18	3862.08	0.099283	18.50	467.65	66.08		
main	3928.721	8650.00	3834.93	3845.63	3846.02	3850.34	0.083505	17.43	499.27	89.02		1.23
main	3732.319	8650.00	3817.00	3827.33	3828.47	3832.55	0.097137	18.35	471.39	66.31		1.13
main	3521.369	8650.00	3805.02	3816.56	3816.50	3820.33	0.062313	15.60	554.54	71.14		1.21
main	3406.587	8650.00	3798.50	3812.63	3809.91	3814.68	0.027209	11.50	752.25	81.50		0.98
main	3177.197	8650.00	3792.26	3806.39	3803.67	3808.44	0.027153	11.49	752.83	81.53		0.67
main	2836.212	8650.00	3782.99	3797.12	3794.40	3799.17	0.027206	11.50	752.31	81.51		0.67
main	2575.824	8650.00	3775.90	3790.01	3787.30	3792.07	0.027302	11.51	751.32	81.46		0.67
main	2321.635	8650.00	3768.99	3783.20	3780.41	3785.21	0.026565	11.40	758.96	81.84		0.67
main	2220.481	8650.00	3766.24	3780.64	3777.66	3782.58	0.025126	11.17	774.70	82.59		0.66
main	2044.011	8650.00	3761.44	3774.71	3772.87	3777.19	0.035252	12.65	683.76	78.08		0.64
main	1743.471	8650.00	3758.00	3767.73	3766.90	3768.41	0.019566	7.96	1434.26	406.11		0.75
main	1280.360	8650.00	3749.40	3756.27	3755.50	3757.37	0.027968	9.44	1141.80	305.37		0.59
main	954.680	8650.00	3739.21	3746.18	3746.18	3747.35	0.033468	10.31	1220.39	486.96		0.67
main	643.478	8650.00	3730.00	3736.78	3735.97	3737.59	0.023636	9.00	1314.49	355.71		0.73
main	351.099	8650.00	3722.00	3727.51	3726.33	3728.59	0.037894	10.14	1125.98	339.22		0.62
main	48.717	8650.00	3713.07	3720.90	3718.42	3721.27	0.009155	5.98	1954.03	472.95		0.76
												0.39












Alt2 routing for ND2cp3 Manmade channel for ND2: alt2 2/25/2004


Geom: manmade channel for ND2cp3: alt2


RS = 48.717





Legend	
EG PF#1	□
WS PF#1	□
Crit PF#1	□
Ground	■
Levee	●
Bank Sta	●


**Attachment 21: Hydraulic Calculations for Routing Around Aging Facility and North
Portal Pad, Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**
















Profile Output Table - Standard Table 1
 HEC-RAS Plan: final1 River: fac2 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 18
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	7795.576	5734.00	3833.00	3846.42	3844.22	3848.30	0.031012					
main	7318.223	5734.00	3821.07	3836.14	3832.13	3837.35	0.017308	11.00	521.23	65.68		0.69
main	6709.892	5734.00	3808.90	3825.21	3821.55	3826.57	0.019974	8.84	648.49	73.18		0.52
main	6265.466	5734.00	3800.02	3816.29	3812.67	3817.66	0.020252	9.34	613.95	70.26		0.56
main	5925.194	5734.00	3793.21	3808.18	3805.86	3810.05	0.030611	9.39	610.76	70.08		0.56
main	5467.605	5734.00	3784.06	3796.10	3792.89	3797.43	0.020312	10.96	523.06	64.88		0.68
main	5008.609	5734.00	3774.88	3784.50	3784.09	3785.39	0.023337	9.23	621.41	75.69		0.57
main	4476.860	5734.00	3757.54	3760.39	3757.02	3760.51	0.003266	8.69	887.57	1050.19		0.59
main	4249.302	15806.00	3733.00	3752.03	3751.10	3753.85	0.037296	1.27	2150.44	776.71		0.18
main	3612.329	15806.00	3710.71	3728.65	3727.10	3729.39	0.014480	11.18	1574.57	361.63		0.76
main	3053.446	15806.00	3691.15	3713.18	3708.51	3715.56	0.020284	7.94	2492.73	512.88		0.48
main	2430.849	15806.00	3678.70	3700.87	3696.07	3703.11	0.019877	12.38	1276.46	93.24		0.59
main	2029.049	15806.00	3670.66	3693.02	3688.03	3695.20	0.019113	12.01	1315.94	103.69		0.59
main	1828.247	16349.00	3666.65	3689.11	3684.30	3691.40	0.020017	11.84	1335.39	104.44		0.58
main	1383.099	16349.00	3657.74	3680.19	3675.39	3682.49	0.020062	12.15	1346.14	104.86		0.60
main	968.465	16349.00	3649.45	3670.94	3667.13	3673.62	0.024585	12.16	1344.99	104.81		0.60
main	519.215	16349.00	3640.47	3659.44	3656.30	3661.44	0.024022	13.12	1246.38	100.98		0.66
main	40.365	16349.00	3630.89	3645.39	3643.28	3647.09	0.025003	11.35	1440.58	149.40		0.64
								10.51	1576.28	215.66		0.65


Yuca Mtn Feb 2004 Simulations final run plan with interp section 2/25/2004
Geom: 20 foot wide 5467 to 5008














Yuca Mtn Feb 2004 Simulations final run plan with interp section 2/25/2004



Yuca Mtn Feb 2004 Simulations final run plan with interp section 2/25/2004




**Attachment 22: Hydraulic Calculations for Routing East of North Portal Pad,
Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**





Profile Output Table - Standard Table 1
 HEC-RAS Plan: A2_cp5cp6 River: cp5cp6 Reach: main

Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 8
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	5223.742	17330.00	3634.00	3645.37	3644.60	3648.03	0.034979	15.76	1465.02	222.87		0.82
main	4775.979	17330.00	3620.03	3633.54		3635.29	0.020735	12.83	1760.65	230.73		0.64
main	4247.177	17330.00	3607.26	3618.48		3620.82	0.033822	15.17	1528.05	234.43		0.81
main	3745.220	17330.00	3593.93	3605.07		3606.69	0.021729	12.22	1824.37	261.40		0.65
main	3206.879	17330.00	3582.00	3590.48	3590.48	3591.72	0.033435	12.70	2399.21	799.46		0.77
main	2535.671	17330.00	3566.00	3572.43	3572.43	3572.49	0.002486	2.69	8749.40	2445.81		0.20
main	1446.724	17330.00	3546.00	3549.56	3547.97	3549.80	0.013636	4.54	4409.66	1559.53		0.42
main	180.971	17330.00	3518.07	3522.90	3521.78	3523.56	0.028031	7.79	2700.65	801.06		0.64








**Attachment 23: Hydraulic Calculations for Routing Downstream of North Portal Pad,
Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**





Profile Output Table - Standard Table 1
 HEC-RAS Plan: a2_fac3cp6 River: fac3cp6 Reach: main


Rivers = 1
 # Hydraulic Reaches = 1
 # River Stations = 16
 # Plans = 1
 # Profiles = 1


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude #	Chl
main	5102.493	6980.00	3635.06	3639.03	3638.51	3639.40	0.031133	7.08	1504.37	790.51		0.65
main	5017.680	6980.00	3634.00	3636.98	3636.38	3637.23	0.025676	5.25	1752.93	976.44		0.56
main	4873.665	6980.00	3628.00	3631.59	3631.24	3631.92	0.032024	6.53	1586.77	1033.94		0.64
main	4582.405	6980.00	3620.00	3623.62	3622.94	3623.86	0.023055	5.60	1915.23	1175.73		0.54
main	4340.225	6980.00	3610.72	3619.61	3618.20	3619.92	0.009497	6.19	1796.24	678.53		0.40
main	4085.360	6980.00	3606.53	3612.19	3611.76	3612.95	0.044787	8.37	1028.55	391.30		0.77
main	3906.139	6980.00	3598.79	3605.08	3603.88	3605.93	0.033165	9.59	1077.62	390.66		0.71
main	3687.420	6980.00	3594.00	3598.64		3599.34	0.026950	7.62	1078.67	311.41		0.62
main	3421.773	6980.00	3586.00	3593.26		3593.78	0.014487	6.89	1270.78	302.03		0.48
main	3071.519	6980.00	3578.00	3584.60	3584.06	3585.54	0.032344	9.69	1043.38	384.14		0.71
main	2607.715	6980.00	3568.38	3573.62		3573.91	0.016995	5.67	1667.75	652.27		0.49
main	2105.532	6980.00	3559.21	3562.85	3562.14	3563.25	0.025431	5.44	1449.15	643.42		0.56
main	1551.928	6980.00	3546.00	3549.40		3549.72	0.023655	5.53	1544.21	668.49		0.55
main	1025.787	6980.00	3533.78	3537.10		3537.42	0.023128	5.12	1545.56	677.65		0.53
main	557.280	6980.00	3524.00	3527.76	3526.54	3528.05	0.016738	4.50	1654.32	650.96		0.46
main	55.956	6980.00	3514.00	3517.32	3516.33	3517.81	0.024003	5.50	1268.53	442.31		0.55













**Attachment 24: Hydraulic Calculations for Routing Near Railroad Bridge Crossing,
Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**





HEC-RAS Output for Routing Under Railroad Bridge, Alternative 2


HEC-RAS Plan: plan3 River: under_rr Reach: alt2


Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl	Max Chl Dpth (ft)	Invert Slope
alt2	7118.878	2486	3656.22	3658.79	3658.47	3659.27	0.053886	5.6	454.08	319.65	0.75	2.57	0.4129
alt2	6858.027	2486	3646	3649.66		3649.88	0.017609	3.76	669.79	343.68	0.45	3.66	0.3737
alt2	6570.028	2486	3636.17	3647.26	3639.1	3647.27	0.000065	0.59	5040.69	835.53	0.03	11.09	0.3396
alt2	6219.761	2486	3627.41	3647.25	3630.43	3647.26	0.000009	0.34	10270.6	1197.51	0.01	19.84	0.3146
alt2	6028.322	22470	3624	3647.17	3632.86	3647.22	0.000298	2.15	14663.79	1388.87	0.08	23.17	0.2968
alt2	5846.451	22470	3620	3647.16	3628.66	3647.18	0.000094	1.35	24813.68	2217.36	0.05	27.16	0.2748
alt2	5680.882	22470	3616	3647.15	3625.29	3647.16	0.00004	0.95	33714.25	2358.41	0.03	31.15	0.2506
alt2	5580	Bridge											
alt2	5477.069	22470	3612.15	3617.47	3620.07	3627.36	0.544806	25.39	901.87	330.1	2.6	5.32	0.2304
alt2	5138.52	22470	3604	3614.18	3612.64	3615.18	0.020596	8.43	3052.76	717.27	0.58	10.18	0.2063
alt2	4765.212	22470	3598	3605.56		3606.46	0.0257	8.22	3107.76	768.23	0.62	7.56	0.1902
alt2	4344.215	22470	3589.07	3596.87		3597.45	0.015766	6.6	3798.33	864.28	0.49	7.8	0.169
alt2	3938.028	25150	3581.77	3589.68		3590.48	0.017869	7.21	3545.6	714.12	0.53	7.91	0.151
alt2	3331.791	25150	3570	3582.71		3583.18	0.005978	5.63	4780.4	655.99	0.33	12.71	0.1316
alt2	2846.012	25150	3562	3574.77		3576.23	0.022201	9.95	2711.36	449.85	0.62	12.77	0.1152
alt2	2360.864	25150	3552	3566.13		3567.06	0.014803	8.21	3602.81	719.43	0.51	14.13	0.0945
alt2	1909.809	25150	3544	3557.57		3559	0.020592	10.18	2832.3	477.97	0.61	13.57	0.0768
alt2	1377.371	25150	3534.83	3551		3551.65	0.006358	7.25	4367.44	617.07	0.36	16.17	0.0596
alt2	825.697	25150	3526.81	3536.95		3539.11	0.03854	12.37	2268.69	419.41	0.8	10.89	0.045
alt2	479.057	25150	3518.52	3529.32		3529.92	0.009507	7.09	4305.31	679.53	0.41	10.8	0.0211
alt2	170.534	25150	3512	3522.27	3521.11	3523.82	0.028031	10.4	2707.62	556.26	0.68	10.27	



















HEC-RAS Output for Clear Span Scenario for Alternative 2

HEC-RAS Plan: w/o piers River: under_rr Reach: alt2

Reach	River Sta	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl	Max Chl Dpth (ft)	Invert Slope
alt2	7118.878	2486	3656.22	3658.95	3658.47	3659.34	0.040398	5.09	505.31	328.9	0.66	2.73	0.4129
alt2	6858.027	2486	3646	3649.27		3649.59	0.034327	4.6	540.53	307.15	0.6	3.27	0.3737
alt2	6570.028	2486	3636.17	3644.51	3639.1	3644.53	0.000272	0.94	3022.76	658.11	0.07	8.34	0.3396
alt2	6219.761	2486	3627.41	3644.47	3630.43	3644.47	0.000019	0.45	7312.3	923.94	0.02	17.06	0.3146
alt2	6028.322	22470	3624	3644.32	3632.86	3644.41	0.000604	2.77	11029.08	1176.09	0.12	20.32	0.2968
alt2	5846.451	22470	3620	3644.28	3628.66	3644.31	0.000205	1.83	18554.51	2112.68	0.07	24.28	0.2748
alt2	5680.882	22470	3616	3644.27	3625.29	3644.29	0.000073	1.19	27185.71	2197.73	0.04	28.27	0.2506
alt2	5580	Bridge											
alt2	5477.069	22470	3612.15	3617.5	3620.07	3627.17	0.528484	25.1	912.46	332.19	2.56	5.35	0.2304
alt2	5138.52	22470	3604	3614.18	3612.64	3615.18	0.020596	8.43	3052.76	717.27	0.58	10.18	0.2063
alt2	4765.212	22470	3598	3605.56		3606.46	0.0257	8.22	3107.76	768.23	0.62	7.56	0.1902
alt2	4344.215	22470	3589.07	3596.87		3597.45	0.015766	6.6	3798.33	864.28	0.49	7.8	0.169
alt2	3938.028	25150	3581.77	3589.68		3590.48	0.017869	7.21	3545.6	714.12	0.53	7.91	0.151
alt2	3331.791	25150	3570	3582.71		3583.18	0.005978	5.63	4780.4	655.99	0.33	12.71	0.1316
alt2	2846.012	25150	3562	3574.77		3576.23	0.022201	9.95	2711.36	449.85	0.62	12.77	0.1152
alt2	2360.864	25150	3552	3566.13		3567.06	0.014803	8.21	3602.81	719.43	0.51	14.13	0.0945
alt2	1909.809	25150	3544	3557.57		3559	0.020592	10.18	2832.3	477.97	0.61	13.57	0.0768
alt2	1377.371	25150	3534.83	3551		3551.65	0.006358	7.25	4367.44	617.07	0.36	16.17	0.0596
alt2	825.697	25150	3526.81	3536.95		3539.11	0.03854	12.37	2268.69	419.41	0.8	10.89	0.045
alt2	479.057	25150	3518.52	3529.32		3529.92	0.009507	7.09	4305.31	679.53	0.41	10.8	0.0211
alt2	170.534	25150	3512	3522.27	3521.11	3523.82	0.028031	10.4	2707.62	556.26	0.68	10.27	

These results show how water surface elevations upstream of the railroad bridge would be nearly 3 ft. lower if both bridges were constructed as clear spans.





**Attachment 25: Scour Analysis, Alternative 2
(Document ID: 000-00C-CD04-00100-000-00A)**

CSU Equation: for local scour

$$\frac{y_s}{a} = 2.0 K_1 K_2 K_3 \left(\frac{y_1}{a}\right)^{0.35} Fr_1^{0.43} \quad \text{(Eq. 6.3) (Ref. 17)}$$

x 3/3/04

✓ max. water depth, $y_1 = 31$ feet @ bridge north of Muck Storage A

Aligned with flow
 $K_1 = 1.0$ } (Round nose)
 $K_2 = 1.0$ } from previous study (BSC, 2002)
 $K_3 = 1.2$ } medium dunes(?) (Ref. 6, pp. 42-44)
 $a = 4$ ft

$$\frac{y_s}{a} = 2.0 \times 1 \times 1 \times 1.2 \times \left(\frac{31}{4}\right)^{0.35} (0.03)^{0.43}$$

$$\frac{y_s}{a} = 1.1$$

$$y_s = 1.1 \times 4 = \boxed{4.4 \text{ ft}}$$

At the bridge at realigned H-Road

$y_1 = 10$ feet ✓

$$\therefore \frac{y_s}{a} = 2.0 \times 1 \times 1 \times 1.2 \times \left(\frac{10}{4}\right)^{0.35} (0.03)^{0.43}$$

$$= 0.73 \quad \text{PM 2/28/04}$$

note: correction should be ~~x 0.36~~

$$\therefore y_s = 0.73 \times 4 = \boxed{2.9 \text{ ft}}$$

PM
4/15/04

**Attachment 26: Checker's Alternate Calculations for PMF
(Document ID: 000-00C-CD04-00100-000-00A)**

Job Yucca Mtn

 Project No. 18839594

 Sheet NA of NA

 Description Alternate Method Check of HEC-1 Peak Flow

 Computed by J. Hudson

 Date 2/11/04

 Checked by NA

 Date NA

 Originator Initials and Date: JH 3/26/04

Reference

Check of Runoff Calculations for Subbasin NDI using SCS Curve Number Method (Ref. ~~19~~¹⁹, pp. ~~11-21~~^{2-1 to 2-11})
 JH 3/2/04 JH 2/12/04

- ① Estimate CN for basin. Soils in vicinity generally belong to Group B and D as stated in previous report (Ref. 6, p. 28).

Assumption: Used CN = average of B and D for Desert Shrub in poor hydrologic condition (Ref. ~~19~~¹⁹, p. ~~18~~²⁻³) JH 2/12/04
 JH 3/2/04

Rationale: Exact Hydrologic Soil Group is not known, and this assumption is only being used to approximate runoff as a check.

$$CN = \frac{77 + 88}{2}$$

$$CN = 83$$

- ② Calculate Runoff from Rainfall.

$$Q = \frac{(P - I_a)^2}{(P - I_a) + S} \quad \text{(Ref. ~~19~~¹⁹, p. ~~11~~²⁻¹) JH 2/12/04}$$

JH 3/2/04

Q = runoff (in)

P = rainfall (in)

S = potential max. retention after runoff begins (in)

I_a = initial abstraction (in)

$$I_a = 0.2 \cdot S \quad \text{(Ref. ~~19~~¹⁹, p. ~~11~~²⁻¹) JH 2/12/04}$$

JH 3/2/04

$$S = \frac{1000}{CN} - 10 \quad \text{(Ref. ~~19~~¹⁹, p. ~~11~~²⁻¹) JH 2/12/04}$$

JH 3/2/04

Job Yucca Mtn

 Project No. 18839594

 Sheet NA of NA

 Description Alternate Method Check

 Computed by J. Hudson

 Date 2/11/04
of HEC-1 Peak Flow

 Checked by NA

 Date NA

 Originator Initials and Date: JH 3/26/04

Reference

$$Q = \frac{\left[P - 0.2 \left(\frac{1000}{CN} - 10 \right) \right]^2}{P - 0.2 \left(\frac{1000}{CN} - 10 \right) + \frac{1000}{CN} - 10}$$

$$Q = \frac{\left[P - 0.2 \left(\frac{1000}{CN} - 10 \right) \right]^2}{P + 0.8 \left[\left(\frac{1000}{CN} \right) - 10 \right]}$$

for NDI, P = 13.2 in from HEC-1 output

$$Q = \frac{\left[13.2 - 0.2 \left(\frac{1000}{83} - 10 \right) \right]^2}{13.2 + 0.8 \left[\left(\frac{1000}{83} \right) - 10 \right]}$$

$$Q = \frac{163.6}{14.8} \quad \boxed{Q = 11 \text{ in}} = \text{rainfall excess over 6 hrs}$$

 ③ Determine Time of Concentration (T_c) from

~~$$T_c = 0.0000$$~~

$$T_c = 0.0078 \left[\frac{L}{S^{0.5}} \right]^{0.77} \quad \text{(Ref. } \overset{20}{*}, \text{ p. 434)}$$

 T_c (min)

L (ft) = Length from Table 4-1 = 3.391 mi for NDI = 17,904 ft

 $S \left(\frac{\text{ft}}{\text{ft}} \right) = \text{slope from Table 4-1} = 437.66 \frac{\text{ft}}{\text{mi}} = 0.083 \text{ ft/ft}$

$$T_c = 0.0078 \left[\frac{17,904}{(0.083)^{0.5}} \right]^{0.77}$$

$$T_c = 38.3 \text{ min} \quad \boxed{T_c = 0.6 \text{ hr}}$$

Job Yucca Mtn

 Project No. 18839594

 Sheet NA of NA

 Description Alternate Method Check

 Computed by J. Hudson

 Date 2/11/04
of HEC-1 Peak Flow

 Checked by NA

 Date NA

 Originator Initials and Date: JH 3/26/04

Reference

- ④ Calculate Peak Discharge using Graphical Peak Discharge Method (Ref. ~~JH~~¹⁹, pp. ~~32-38~~^{4-1 to 4-7})
 JH 3/2/04 JH 2/12/04

$$q_p = q_u A_m Q F_p$$

q_p = peak discharge (cfs)

q_u = unit peak discharge (csm/in)

A_m = drainage area (mi²) = 1.156 for NDI (from Table 4-1)

Q = runoff (in) = 11 in (previously calc'd)

F_p = pond and swamp adjustment factor = 1 (Ref. ~~JH~~¹⁹, p. ~~33~~⁴⁻²) JH 3/2/04 JH 2/12/04

for CN = 83, I_a = initial abstraction = 0.410 in (Ref. ~~JH~~¹⁹, p. ~~32~~⁴⁻¹) JH 3/2/04 JH 2/12/04

$$\frac{I_a}{P} = \frac{0.410}{13.2} = 0.03$$

Rainfall Distribution = Type II (Ref. ~~JH~~¹⁹, p. ~~42~~^{B-2}) JH 3/2/04 JH 2/12/04
 $q_u = 490$ csm/in (Ref. ~~JH~~¹⁹, p. ~~37~~⁴⁻⁶) JH 3/2/04 JH 2/12/04
 $q_p = 490 (1.156) (11) (1)$

$q_p = 6231 \text{ cfs}$

This shows good agreement w/
 the HEC-1 output for NDI
 of 5576 cfs.

Originator Initials and Date: *H* 3/26/04

Check of total Peak flow from all basins using Rational Method

Copied values are from Table 4-1 and HEC-1 output

Basin Name	(copied)	(calc'd)	(copied)	(calc'd)	(copied)	(calc'd)	(calc'd) Tc = 0.0078([L/(S^0.5)]^0.77) (Ref. 20, p. 434)	(calc'd) Q = CIA (Ref. 20, p. 507)	(calc'd) Q = CIA (Ref. 20, p. 507)	(copied) from HEC-1
	Area (mi ²)	Area (acres)	Total channel length (mi)	Total channel length (ft)	Slope (ft/mi)	Slope (ft/ft)	Kirpich Time of Concentration (min)	Low Peak Q, C = 0.2 (cfs)	High Peak Q, C = 1 (cfs)	Peak Q (cfs)
ND1	1.156	740	3.391	17904	437.66	0.083	38.3	1611	8055	5576
ND2	0.394	252	1.828	9652	528.52	0.100	22.1	549	2746	2487
D3	1.149	735	3.429	18105	526.68	0.100	36.0	1601	8007	5322
ND4	0.816	522	2.931	15476	349.65	0.066	37.3	1137	5686	3853
D5	0.201	129	0.582	3073	173.64	0.033	14.1	280	1401	1854
D6	1.38	883	3.24	17107	151.53	0.029	55.6	1923	9616	6013
S1	0.361	231	1.311	6922	639.09	0.121	15.9	503	2516	2801
E1	4.495	2877	6.029	31833	369.36	0.070	63.7	6265	31323	14220
E2	1.808	1157	3.222	17012	379.6	0.072	38.9	2520	12599	7498
E3	0.84	538	1.832	9673	150.68	0.029	35.9	1171	5853	4118
FAC1	0.368	236	N/A	N/A	N/A	N/A	N/A	513	2564	2099
FAC2	0.164	105	N/A	N/A	N/A	N/A	N/A	229	1143	1978
FAC3	0.433	277	N/A	N/A	N/A	N/A	N/A	603	3017	4695
FAC4	0.244	156	N/A	N/A	N/A	N/A	N/A	340	1700	2475
							36 (avg)	19,245 (sum)	96,225 (sum)	64,989 (sum)

The total flow from HEC-1 falls right within the range calculated using the Rational Method, which shows good agreement.

3-min Precip for North Portal Copied from HEC-1 (in)

0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015
0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015
0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025
0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025
0.085	0.085	0.085	0.085	0.085	0.085	0.085	0.085	0.085	0.085
0.085	0.085	0.085	0.085	0.085	0.085	0.085	0.085	0.085	0.085
1.18	1.18	1.18	1.18	1.18	0.38	0.38	0.38	0.38	0.38
0.18	0.18	0.18	0.18	0.18	0.14	0.14	0.14	0.14	0.14
0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025
0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025	0.025

peak of precip over average Tc of 36 minutes, shown in bold and totals:
 rainfall intensity, I, to use with Rational method:

6.5 in
 10.9 in/hr

C will fall in range between 0.2 for unimproved areas (Ref. 20, p. 508) to 1 for 100% of rainfall converting to runoff.

BSC

Engineering Change Notice

1. QA: QA
2. Page 1 of 1

Complete only applicable items.

000-00C-CD04-00100-000-00A-ECN1

3. Document Identifier: 000-00C-CD04-00100-000-00A	4. Rev.: 00A	5. Title: Hydrologic Engineering Studies for the North Portal Pad and Vicinity	6. ECN: 1
7. Reason for Change: These calculations will be used in the License Application documents, therefore the status must be identified as committed. The status designation of Hydrologic Engineering Studies for the North Portal Pad and Vicinity (000-00C-CD04-00100-000-00A) can be changed to "Committed" as the results are not expected to change in such a manner that will affect support of regulatory submittals.			
8. Supersedes Change Document: <input type="checkbox"/> Yes If, Yes, Change Doc.: _____ <input checked="" type="checkbox"/> No			
9. Change Impact:			
Inputs Changed: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		Results Impacted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
Assumptions Changed: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		Design Impacted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
10. Description of Change: (Address any "Yes" answers) Replace existing cover sheet with revised calculation cover sheet from LP 3.12 Q marked "committed".			
11. Originator: (Print/Sign/Date) VALERIE D. SAUNDERS / Valerie D Saunders / 8/23/05			
Checker: (Print/Sign/Date) Michael S Rubin / Michael S. Rubin / 8/23/05			
Approved: (Print/Sign/Date) Richard Perraisi / Richard Perraisi / 8/23/05			

L.D. Abernethy
QERC
8/23/05

No comments