

November 25, 2005



U.S. Department  
of Transportation

400 Seventh Street, S.W.  
Washington, D.C. 20590

**Pipeline and  
Hazardous Materials  
Safety Administration**

DOT-SP 8249  
(FIFTEENTH REVISION)

EXPIRATION DATE: October 31, 2009

(FOR RENEWAL, SEE § 107.109.)

1. GRANTEE: LPS Industries, LLC  
Moonachie, New Jersey
2. PURPOSE AND LIMITATIONS:
  - a. This special permit authorizes the manufacture, marking, sale and use of the specially designed combination packagings described herein for transportation in commerce of the materials listed in paragraph 6 without hazard labels or placards, with quantity limits not exceeding one liter for liquids or 2.85 kilograms for solids. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.13(a) in that Division 5.2 and toxic by inhalation (TIH) materials are included; § 173.13(b) in that passenger-carrying aircraft is authorized for certain materials; § 173.13(c)(1)(ii) in that absorbent material may be placed inside the inner barrier bag; and §§ 173.13(c)(1)(iv) and § 173.13(c)(2)(iii) in that a protective frame is authorized in place of an inner fiberboard box.

5. BASIS: This special permit is based on LPS Industries, LLC's application dated October 11, 2005 submitted in accordance with § 107.109.
6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Material Description <sup>1</sup>	Hazard Class/ Division	Identification Number	Packing Group
Flammable, liquids	3	As Appropriate	I, II or III
Flammable solids <sup>2,3</sup>	4.1	As Appropriate	II or III
Pyrophoric materials <sup>4</sup>	4.2	As Appropriate	I
Self heating materials <sup>3</sup>	4.2	As Appropriate	II or III
Dangerous When Wet materials	4.3	As Appropriate	I, II or III
Oxidizers <sup>4</sup>	5.1	As Appropriate	I, II or III
Organic peroxides <sup>2,3</sup>	5.2	As Appropriate	II
Toxic materials <sup>4</sup>	6.1	As Appropriate	I, II or III
Corrosive materials	8	As Appropriate	I, II or III
Miscellaneous hazardous materials	9	As Appropriate	II or III

1 - Only hazardous materials permitted to be transported aboard a passenger-carrying aircraft by column (9A) of the Hazardous Materials Table in § 172.101 are authorized for transport aboard passenger-carrying aircraft; only hazardous materials permitted to be transported aboard a cargo aircraft by column (9B) of the Hazardous Materials Table in § 172.101 are authorized for transport aboard cargo-only aircraft.

2 - Excludes Type A, B and C materials.

3 - Excludes materials which require temperature control.

4 - As restricted by paragraphs 7.c and 7.d.

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Packagings manufactured under the Ninth Revision of this special permit prior to September 30, 2000, are authorized for continued use. However, no new manufacture is authorized after September 30, 2000. Packagings manufactured after October 1, 2000 must meet the following requirements:

(1) Liquid hazardous material must be placed in a tightly closed glass, metal or plastic inner packaging(s) with a total capacity not exceeding 1.2 liters in volume per completed package. The inner packaging(s) must be sealed and must be compatible with the product. Inner packaging(s) must have sufficient outage so that they will not become liquid full at 55°C. The net quantity (measured at 20°C) in the inner packaging(s) may not exceed one liter;

(2) Solid hazardous material must be placed in a tightly closed glass, metal or plastic inner packaging(s). The net quantity of material in the inner packaging(s) may not exceed 2.85 kilograms. The inner packaging(s) must be sealed and must be compatible with the product;

(3) Inner packaging(s) containing liquid, pyrophoric solid, or dangerous when wet material must be:

(i) Surrounded by non-reactive absorbent material, in sufficient quantity to completely absorb the entire contents of the inner packaging(s) and placed into a hermetically sealed (e.g., goose-necked and tied, heat sealed, etc.) barrier bag (4 mils minimum) which is impervious to the lading; or

(ii) Placed into a hermetically sealed barrier bag (4 mils minimum) which is impervious to the lading and surrounded by non-reactive absorbent material in sufficient quantity to completely absorb the entire contents of the inner packaging(s); and

**November 25, 2005**

(iii) Then be placed in a metal can with a sufficient quantity of non-reactive filler material to immobilize the inner packaging(s) and fill all void spaces;

(iv) The metal can must be hermetically sealed for Division 4.2, 4.3 and TIH materials;

(4) The inner packaging from 7.a.(2) or 7.a.(3) must then be placed in a fiberboard box that is placed in a hermetically sealed barrier bag which is impervious to the lading.

(5) The intermediate packaging must then be placed inside an outer packaging conforming to § 173.201 for liquids or § 173.211 for solids. Up to four intermediate packagings may be placed into an outer package.

(6) All closures must be held securely in place by positive means.

b. TESTING -

(1) The completed package, assembled as for transportation and with the inner packaging(s) filled 98% full with liquid, must be successfully tested in accordance with 49 CFR Part 178 at the Packing Group I level.

(2) The metal can with inner packaging(s) filled 98% full, must be successfully tested in accordance with 49 CFR Part 178 at the Packing Group I level. In addition for TIH, and pyrophoric materials, the metal can must be capable of withstanding a pressure differential of 100 kPa.

c. ADDITIONAL SAFETY CONTROL MEASURES FOR A MATERIAL TOXIC BY INHALATION - The following provisions are applicable to materials meeting the definition of "material toxic by inhalation" in § 171.8 that are packaged in accordance with the requirements of this special permit:

(1) Each outside package must be marked "INHALATION HAZARD" in letters at least 12.0 mm (one-half inch) high on a contrasting background in close proximity to the marking specified in paragraph 8.g.

(2) Shipping papers must contain a notation "TOXIC

**November 25, 2005**

INHALATION HAZARD" in addition to the shipping paper requirements of Subpart C of Part 172.

d. MATERIALS WHICH MAY NOT BE TRANSPORTED BY PASSENGER-CARRYING AIRCRAFT -

(1) Materials which meet the definition of "material toxic by inhalation" in § 171.8 (any zone).

(2) Materials which meet the definition of oxidizer, at the Packing Group I level in accordance with § 173.127(b) (1) (i).

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging(s) authorized by this special permit for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this special permit.

b. A person who is not a holder of this special permit, but receives a package covered by this special permit, may reoffer it for transportation provided no modifications or changes are made to the package and it is offered for transportation in conformance with this special permit and the HMR.

c. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this special permit must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated by the Office of Hazardous Materials Special Permits and Approvals for a specific manufacturing facility.

e. A current copy of this special permit must be maintained at each facility where the package is manufactured under this special permit. It must be made available to a DOT representative upon request.

f. For transportation by aircraft, the completed package must be offered in conformance with § 173.27(c).

g. MARKING and LABELING

(1) Each package shipped under this special permit must be marked "DOT-SP 8249 - NO HAZARD LABELS REQUIRED" in letters at least 12.0 mm (one-half inch) high on a contrasting background in proximity to required DOT markings.

(2) Each package that is offered for transportation by aircraft which contains a material which is not authorized to be transported aboard a passenger-carrying aircraft by column (9A) of the Hazardous Materials Table in § 172.101 must bear a CARGO ONLY AIRCRAFT label.

(3) If the inner metal can is not capable of withstanding a pressure differential of 100 kPa, then the can must be marked in letters at least 6.0 mm (one-quarter inch) high on a contrasting background that the can is not suitable for TIH or Pyrophoric Materials.

(5) Packagings permanently marked 'DOT-E 8249', prior to October 1, 2006 may continue to be used under this special permit for the remaining service life of the packaging or until the special permit is no longer valid. Packagings marked on or after October 1, 2006 must be marked 'DOT-SP 8249'.

(6) Shipping papers displaying 'DOT-E 8249' may continue to be used until October 1, 2006, provided the special permit remains valid.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo aircraft only with restrictions (see paragraph 6, note 1), and passenger-carrying aircraft with restrictions (see paragraph 6, note 1 and paragraph 7.d).
10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each aircraft used to transport packages covered by this special permit. The shipper must furnish a copy of this special permit to the air carrier before or at the time the shipment is tendered.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:

**November 25, 2005**

- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
- o Persons operating under the terms of this exemption must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
- o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term 'exemption' to 'special permit' and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this special permit.) In addition, the holder(s) of this special permit must also inform the AAHMS, in writing, as soon as practicable of any incidents involving the package and shipments made under this special permit.

Issued in Washington, D.C.

A handwritten signature in blue ink, appearing to read "R. Ryan Parker". The signature is fluid and cursive, with a large loop at the end.

for Robert A. McGuire  
Associate Administrator for  
Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous  
Materials Safety, Pipeline and Hazardous Materials Safety  
Administration, Department of Transportation, Washington, D.C.  
20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the  
Hazardous Materials Safety Homepage at  
[http://hazmat.dot.gov/sp\\_app/special\\_permits/spec\\_perm\\_index.htm](http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm)  
Photo reproductions and legible reductions of this special permit  
are permitted. Any alteration of this special permit is  
prohibited.

PO: RDT/am