

120 PSI MINOVA MAIN LINE TEKSEAL[®]
MSHA SEAL APPROVAL NUMBER 120-75.336.1.07.15.0

120-psi Minova Main Line Tekseal[®]

This seal consists of Tekseal[®] material manufactured by Minova USA, Inc. (*Minova*) and is designed to withstand an overpressure of 120-psi from a mine explosion. Tekseal is a pumpable, cementitious grout. This plug-type seal design is intended for use in stable entries where significant convergence is not expected, but is also applicable in entries where some convergence will occur. The seal design does not require convergence pressure on the seal.

The required thickness of the seal and the construction requirements are detailed in the report titled, "*120 psi MINOVA MAIN LINE TEKSEAL[®] IN A STABLE ENTRY,*" dated September 19, 2007. The required minimum thickness of the seal depends on the height and width of the mine entry at the seal location (after loose and unsuitable material is removed) and is provided by Minova in a table. Minimum seal thicknesses are provided for entry sizes up to 30 feet in height and 28 feet in width. The design is based on the seal being subjected to a dynamic overpressure of 120 psi which is applied instantaneously and held for a duration of 1.5 seconds. The seal design is certified by a Registered (Licensed) Professional Engineer as being in accordance with current, prudent engineering practice.

Anchorage of the seal is provided by the shear strength of the Tekseal and the frictional interlock of the Tekseal with the irregularities in the rock and coal surface of the entry perimeter after all loose material is removed. Construction of the seal consists of the erection of two (2) wooden frame and brattice cloth walls, or equal, for the containment of the Tekseal. Concrete block or Kennedy Metal stoppings or cribs lined with brattice cloth can be used in place of the wooden frame and brattice cloth walls. A mine operator may install the 120-psi Minova Main Line Tekseal provided its installation is approved in the mine ventilation plan, it is constructed following the installation procedures, and the mine operator meets the installation procedures specified in Section 75.336(b).

For detailed information on the use and application of this seal, please contact Mr. David Himes, Project Manager, Minova USA, Inc., 150 Carley Court, Georgetown, Kentucky 40324; phone number 800-626-2948. For more detailed information for mines in the western U.S., the contact is Mr. Joe Burdette, Plant Manager, 2306 Highway 6 & 50, PO Box 3124-1815021, Grand Junction, CO 81505; phone number 970-245-4007.