TELLURIUM

(Data in metric tons of tellurium content unless otherwise noted)

<u>Domestic Production and Use</u>: In the United States, one firm produced commercial-grade tellurium at its refinery complex, mainly from copper anode slimes but also from lead refinery skimmings, both of domestic origin. Primary and intermediate producers further refined domestic and imported commercial-grade metal and tellurium dioxide, producing tellurium and tellurium compounds in high-purity form for specialty applications.

Tellurium's major use is as an alloying additive in steel to improve machining characteristics. It is also used as a minor additive in copper alloys to improve machinability without reducing conductivity; in lead alloys to improve resistance to vibration and fatigue; in cast iron to help control the depth of chill; and in malleable iron as a carbide stabilizer. It is used in the chemical industry as a vulcanizing agent and accelerator in the processing of rubber, and as a component of catalysts for synthetic fiber production. Tellurium was increasingly used in the production of cadmium-tellurium-based solar cells. Other uses include those in photoreceptor and thermoelectric electronic devices, thermal cooling devices, as an ingredient in blasting caps, and as a pigment to produce various colors in glass and ceramics.

Salient Statistics—United States:	2003	2004	2005	<u>2006</u>	2007 ^e
Production, refinery	W	W	W	W	W
Imports for consumption, unwrought,					
waste and scrap	49	63	42	31	38
Exports	10	6	51	4	13
Consumption, apparent	W	W	W	W	W
Price, dollars per kilogram, 99.95% minimum ¹	10	13	96	89	80
Stocks, producer, refined, yearend	W	W	W	W	W
Net import reliance ² as a percentage of					
apparent consumption	W	W	W	W	W

Recycling: There is little or no scrap from which to extract secondary tellurium because the uses of tellurium are nearly all dissipative in nature. Currently, none is recovered in the United States, but a small amount is recovered from scrapped selenium-tellurium photoreceptors employed in older plain paper copiers in Europe and Japan.

Import Sources (2003-06): Belgium, 40%; Canada, 23%; Germany, 18%; United Kingdom, 6%; and other, 13%.

Tariff: Item Number Normal Trade Relations

12-31-07
Tellurium 2804.50.0020 Free.

Depletion Allowance: 14% (Domestic and foreign).

Government Stockpile: None.

TELLURIUM

Events, Trends, and Issues: Estimated domestic tellurium production increased in 2007 as compared with that of 2006 owing to a full year of uninterrupted production from the one domestic producer. Though detailed information on the world tellurium market was not available, world tellurium consumption was estimated to have increased significantly in 2007. There was a sharp increase in demand for high-purity tellurium for cadmium telluride solar cells. Tellurium consumption also increased in thermal cooling applications. The price of tellurium increased in 2007 because growth in consumption worldwide was not matched by growth in production. World production of tellurium, a byproduct of copper refining, was believed to have increased owing to an increase in world copper production. Selenium, a coproduct which was in strong demand, experienced a slight increase in production from waste and anode slimes that contained tellurium.

World Refinery Production, Reserves, and Reserve Base:

<u></u>	Refinery production		Reserves ³	Reserve base ³
	<u>2006</u>	2007 ^e		
United States	W	W	3,000	6,000
Canada	75	75	700	1,500
Japan	24	25	NA	NA
Peru	33	35	1,600	2,800
Other countries ⁴	<u>NA</u> ⁵132	<u>NA</u>	<u>16,000</u>	<u>37,000</u>
World total (rounded)	⁵ 132	⁵ 135	21,000	47,000

<u>World Resources</u>: The figures shown for reserves and reserve base include only tellurium contained in economic copper deposits. These estimates assume that less than one-half of the tellurium contained in unrefined copper anodes is actually recovered.

More than 90% of tellurium is produced from anode slimes collected from electrolytic copper refining, and the remainder is derived from skimmings at lead refineries and from flue dusts and gases generated during the smelting of bismuth, copper, and lead ores. In copper production, tellurium is recovered only from the electrolytic refining of smelted copper. Growth in the global use of the leaching solvent extraction-electrowinning processes for copper extraction has limited the growth of tellurium supply.

<u>Substitutes</u>: Several materials can replace tellurium in most of its uses, but usually with losses in production efficiency or product characteristics. Bismuth, calcium, lead, phosphorus, selenium, and sulfur can be used in place of tellurium in many free-machining steels. Several of the chemical process reactions catalyzed by tellurium can be carried out with other catalysts or by means of noncatalyzed processes. In rubber compounding, sulfur and/or selenium can act as vulcanization agents in place of tellurium. The selenides of the refractory metals can function as high-temperature, high-vacuum lubricants in place of tellurides. The selenides and sulfides of niobium and tantalum can serve as electrically conducting solid lubricants in place of tellurides of those metals.

The selenium-tellurium photoreceptors used in some xerographic copiers and laser printers have been replaced by organic photoreceptors in newer machines. Amorphous silicon and copper indium diselenide are the two principal competitors to cadmium telluride in photovoltaic power cells.

^eEstimated. NA Not available. W Withheld to avoid disclosing company proprietary data.

¹Average price published by Mining Journal for United Kingdom lump and powder, 99.95% tellurium.

²Defined as imports – exports + adjustments for Government and industry stock changes.

³See Appendix C for definitions. Estimates include tellurium contained in copper resources only.

⁴In addition to the countries listed, Australia, Belgium, China, Germany, Kazakhstan, the Philippines, and Russia produce refined tellurium, but output is not reported, and available information is inadequate for formulation of reliable production estimates.

⁵Excludes refinery production from the United States.