

DISPERSANT AIRCRAFT CAPABILITY FORM

PLATFORM

**AIR TRACTOR
AT-502 B**
with 170 gallon fuel tank

Operator: EADC, Inc.
OSRO: -----



Photo compliments of Air Tractor, Inc.

DATA SOURCE LEGEND

1. **(Black):** Indicates the data are based on documented field trials or is a fixed design value
2. **(Blue):** Indicates the data are based on limited field observations or operator's stated practice or stated value (little or no documentation)
3. **(Red):** Indicates the data are based on reasonable calculations or performance of comparable systems

		Unit	U.S. Regulatory Calculation Values	Data Source 1-2-3	Range	Reference(s)
AIRCRAFT PARAMETERS						
1	Swath Width	feet	70	1	45-75	See Other Comments 1*
	a. Application (gallons per acre)	gpa	5	1	1-10	See Other Comments 1*
	b. Altitude	feet	16	1	15-50	See Other Comments 1*
	c. Application Speed	knots	135	1	104-135	EADC operator
	d. Pump Rate (gallons per minute)	gpm	110	1	15-260	EADC operator
	e. Boom Pressure (pounds/square inch)	psi	40	1	30-45	EADC operator
2	Transit Speed at Altitude	knots	122	2	122-142	EADC operator & Air Tractor specifications
	From Base to Staging Airport	feet	8,000		8,000	
3	Transit Speed at Altitude	knots	120	2	120-152	EADC operator & Air Tractor specifications
	Staging Airport to/from spill	feet	1,500		1,500	
4	Dispersion Spraying Reposition Speed	knots	140	2	140	EADC operator
5	Time to Fully Load Dispersion Tank	min	10	2	5-30	EADC operator
6	Time to Fully Load Fuel Tanks	min	5	2	5-30	EADC operator

7	Load Dispersant & Fuel simultaneously (Yes/No)	-----	Yes	1	Yes	EADC operator. See Other Comments below 5*-6*
8	Time to Make U-turn (Turn 180 degrees)	min	0.75	2	0.75	EADC operator
9	Dispersant Payload Maximum	gal	500	1	500	EADC operator
10	Fuel with maximum dispersant payload	lbs	1,139	1	1,139	EADC operator
11	Approach Distance for spraying	nm	0.5	2	0.5	EADC operator
12	Departure Distance for spraying	nm	0.5	2	0.5	EADC operator
13	Taxi Time Take-Off	min	3	2	2-15	EADC operator
14	Taxi Time Landing	min	3	2	2-15	EADC operator
15	On-site Check-In/Safety Time	min	10	2	5-15	Estimated from exercise
CASCADE PARAMETERS*						
16	Take-off with Maximum Payload and Maximum Take-off Weight (assume no wind and VFR fuel reserve)					
	a. Maximum Flight Time	hours	3.0	2	3.0	EADC operator
	b. Maximum Flight Range	nm	360	2	360	EADC operator
	c. Optimal Altitude	feet	8,000	2	8,000	EADC operator
	d. True Air Speed	knots	120	2	120	EADC operator
	e. Fuel Consumption	lbs/hour	312	2	312	EADC operator
17	Take-Off with Maximum Fuel and No Payload (assume no wind and VFR fuel reserve)					
	a. Maximum Flight Time	hours	3.7	2	3.7	EADC operator
	b. Maximum Flight Range	nm	450	2	450	EADC operator
	c. Optimal Altitude	feet	8,000	2	8,000	EADC operator
	d. True Air Speed	knots	122	2	122	EADC operator
	e. Fuel Consumption	lbs/hour	265	2	265	EADC operator
18	Staging area briefing	min	45	2	30-60	Estimate from exercises
AIRPORT PARAMETERS						
19	Runway length - Minimum (For take-off at maximum gross weight assuming sea level, 90° F, no wind using a balanced field concept, i.e., go, no go speed)	feet	1,140	2	1,140	EADC operator
20	Runway weight restrictions for maximum aircraft weight	lbs	9,000	2	9,000	EADC operator

	OTHER COMMENTS					
1*	References: WRK, Inc. field spray system test February 2005					
5*- 6*	The time to load dispersants and fuel are stand alone times independent of each other. If item 7 indicates that fuel and dispersants can be loaded simultaneously, then the longer of fuel or dispersant load time is used in the capability calculations. If item 7 indicates fuel and dispersants can NOT be loaded simultaneously, then the times are added together to calculate the aircrafts capability. To load simultaneously depends upon the airport, aircraft, and support crew. The loading times depend upon the loading system i.e., 5000 tank truck, 55 gallon drums or other means and the pumping system used. The time shown in items 5 and 6 is for loading from a tank truck which is standing by ready to commence loading when the aircraft comes to a stop in the loading area, i.e. the fastest loading time possible.					
16 * & 17 *	Visual Flight Rules (VFR) require a 30 minute reserve fuel supply. AT-502s are not certified for IFR flight conditions.					
*	Cascade Parameters: The aircraft's calculated capability when cascading uses the same fuel loading and taxi times for dispersant operations as listed in items 6, 13 and 14.					