
FIPS 140-2 Validation Certificate



The National Institute of Standards and Technology of the United States of America





The Communications Security
Establishment of the Government
of Canada

Certificate No. 828

The National Institute of Standards and Technology, as the United States FIPS 140-2 Cryptographic Module Validation Authority; and the Communications Security Establishment, as the Canadian FIPS 140-2 Cryptographic Module Validation Authority; hereby validate the FIPS 140-2 testing results of the Cryptographic Module identified as:

RSA BSAFE® Crypto-C Micro Edition (ME) by RSA Security, Inc. (When operated in FIPS mode)

in accordance with the Derived Test Requirements for FIPS 140-2, Security Requirements for Cryptographic Modules. FIPS 140-2 specifies the security requirements that are to be satisfied by a cryptographic module utilized within a security system protecting Sensitive Information (United States) or Protected Information (Canada) within computer and telecommunications systems (including voice systems).

Products which use the above identified cryptographic module may be labeled as complying with the requirements of FIPS 140-2 so long as the product, throughout its life cycle, continues to use the validated version of the cryptographic module as specified in this certificate. The validation report contains additional details concerning test results. No reliability test has been performed and no warranty of the products by both agencies is either expressed or implied.

This certificate includes details on the scope of conformance and validation authority signatures on the reverse.

FIPS 140-2 provides four increasing, qualitative levels of security: Level 1, Level 2, Level 3, and Level 4. These levels are intended to cover the wide range and potential applications and environments in which cryptographic modules may be employed. The security requirements cover eleven areas related to the secure design and implementation of a cryptographic module. The scope of conformance achieved by the cryptographic modules as tested in the product identified as:

RSA BSAFE® Crypto-C Micro Edition (ME) by RSA Security, Inc. (Software Version: 2.1: Software)

(Software Version: 2.1; Software)				
and tested by the Cryptographic Module Te	esting accredited laboratory:	Atlan Laboratories, NVLAP Lab Code 200492-0 CRYPTIK Version 6.0		
to do followo.				
Cryptographic Module Specification:	Level 1	Cryptographic Module Ports and Interfaces:	Level 1	
Roles, Services, and Authentication:	Level 1	Finite State Model:	Level 1	
Physical Security: (Multi-Chip Standalone)	Level N/A	Cryptographic Key Management:	Level 1	
EMI/EMC:	Level 1	Self-Tests:	Level 1	
Design Assurance:	Level 1	Mitigation of Other Attacks:	Level 1	
(64-bit); HP-UX 11.23 Itanium 2 (32-bit); HP- Solaris 10 (32-bit SPARC v8); Solaris 10 (32- SuSE Linux Enterprise Server 9.0 (64-bit x86 604); Windows Mobile 2003; Windows Mobile	UX 11.23 Itanium 2 (64-bit); Re -bit SPARC v8+); Solaris 10 (64 6_64); VxWorks 5.4 (PPC 604); e 2003 SE; Windows Mobile 5.0	tested in the following configuration(s): Microsoft N X 5L v5.3 (64-bit PowerPC); HP-UX 11.1† PA-RISC 2.0 (32-bit); Hd Hat Enterprise Linux AS 4.0 (32-bit x86); Red Hat Enterprise Linux Enterprise Linux Enterprise Linux Enterprise VxWorks 5.5 (PPC 603); VxWorks 5.5 (PPC 604); VxWorks Gene D PocketPC; Windows Mobile 5.0 PocketPC Phone Edition; Windo 2003 Server SP1 (64-bit x86_64); Windows 2003 Server SP1 (Itar	IP-UX 11.23 PA-RISC2.0W nux AS 4.0 (64-bit x86_64); e Server 9.0 (32-bit x86); eral Purpose Platform 6.0 (PPC ws 2003 Server SP1 (32-bit	
The following FIPS approved Cryptogra	phic Algorithms are used:	AES (Cert. #490); DSA (Cert. #199); ECDSA (Cert. #47); HMA RNG (Cert. #270); RSA (Cert. #203); SHS (Cert. #560); Triple		
ECDF stren	RBG (non-compliant); RSA (ke gth); Diffie-Hellman (key agre	pproved algorithms: MD2; MD5; HMAC MD5; DES; DES40; by wrapping; key establishment methodology provides at least ement; key establishment methodology provides at least 80 k key establishment methodology provides between 80 and 28	st 80 bits of encryption bits of encryption strength);	
	Overall L	_evel Achieved: 1		
Signed on behalf of the Government of the United States		Signed on behalf of the Government of Canada		
Signature: Mulan 100	arker_	Signature: / / / Ollsmea	Signature: / the Collsmean	

Chief, Computer Security Division National Institute of Standards and Technology

Dated: 27 August 200 f

A/Director, Industry Program Group Communications Security Establishment