

| Idle Energy Data: Single Tank Conveyor Machines | | | | |
|---|-----------------------|---|---|-----------------------------------|
| Data Point | High Temp or Low Temp | Minimum Tank Temperature During Idle Test | Average Tank Temperature During Idle Test | Tank Heater Idle Energy Rate (kW) |
| 1 | High | 158.3° F | 160° F | 1.5 |
| 2 | High | 160° F | 164° F | 2.373 |
| 3 | High | 156.1° F | 161° F | 1.6 |
| 4 | High | 165.3° F | 169.8° F | 1.398 |
| 5 | High | 165.3° F | 169.8° F | 1.398 |
| 6 | High | 165.3° F | 169.8° F | 1.398 |
| 7 | High | 165.3° F | 169.8° F | 1.398 |
| 8 | High | 163° F | 164.5° F | 1.515 |
| 9 | High | 163° F | 165° F | 1.478 |
| 10 | High | 160° F | 165° F | 2.161 |
| 11 | High | 150.1° F | 152° F | 0.82 |
| 12 | Low | 143° F | 145.1° F | 0.740 |
| 13 | Low | 145.2° F | 150° F | 0.666 |
| 14 | Low | 145.2° F | 150° F | 0.666 |

Number of Manufacturers = 7