



# Conversion Factors for Hydrocarbon Emission Components

EPA420-P-03-002  
May 2003

# **Conversion Factors for Hydrocarbon Emission Components**

## **NR-002a**

Assessment and Standards Division  
Office of Transportation and Air Quality  
U.S. Environmental Protection Agency

## **Purpose**

The purpose of this memorandum is to document the conversion factors for reporting hydrocarbon emissions in different forms. The general forms are total hydrocarbons (THC), total organic gas (TOG), nonmethane hydrocarbons (NMHC), nonmethane organic gas (NMOG), and volatile organic compounds (VOC), all defined in the introduction below. For reporting hydrocarbon emissions from nonroad equipment, it is helpful to provide an accepted means to estimate the hydrocarbons in the different forms. This is not a substitute for full speciation of hydrocarbons in the exhaust.

## **Introduction**

Hydrocarbon emissions can be reported in a variety of styles depending on the end use of the emission estimates and the measurement technique used in the underlying data. Not all emissions are measured for all engines, so a conversion from the most common measurement type to others is needed to supply an estimate in terms required by the user.

Most hydrocarbon emissions data from mobile sources is measured as total hydrocarbon (THC). THC is the measured hydrocarbon emissions using a Flame Ionization Detector (FID) calibrated with propane. The FID is assumed to respond to all hydrocarbons identically as it responds to propane in determining the concentration of carbon atoms in a gas sample. Most hydrocarbons respond nearly identically as propane with notable exceptions being oxygenated hydrocarbons such as alcohols and aldehydes commonly found in engine exhaust.

Because alcohols and especially aldehydes are chemically reactive and therefore ozone-forming hydrocarbons, the California Air Resources Board defined a measurement that adds the THC and the oxygenated components into a new measurement called total organic gas (TOG). [1] The oxygenated components are measured by collecting aldehydes on dinitro- phenylhydrazine impregnated filter traps and alcohols in chilled water impingers. The aldehydes and alcohols are extracted and measured using chromatography to determine emission rates. Each mole of aldehydes and alcohols is added by weight as formaldehyde and methanol.

Methane is an organic gas that is orders of magnitude less reactive than other hydrocarbons, so it is often excluded from emission estimations. The methane is measured by chromatographically separating the methane from the THC and

analyzing the concentrations using a FID calibrated specifically for methane. The methane emissions are subtracted from the THC and TOG emission estimations to produce a nonmethane hydrocarbon (NMHC) and a nonmethane organic gas (NMOG) emission estimate. Some newer instruments can measure the NMHC directly however leading to lower uncertainty.

Some hydrocarbons are less ozone-forming than other hydrocarbons, so EPA has officially excluded them from the definition of regulated hydrocarbons called volatile organic compounds (VOC). This definition excludes methane, ethane, and compounds not commonly found in large quantities in engine exhaust like chlorohydrocarbons from consideration as VOC. For this work the definition of VOC is the result of subtracting methane and ethane from the TOG emission estimates.

### **Conversion Factors**

Because all studies to date have measured THC, all other hydrocarbon types will be given as a proportion of THC. The proportionalities given in the Table below were derived from those studies that measured methane, ethane, and aldehydes. Alcohols are only found if the fuel contains alcohols, so they would have been considered if data were available.

The hydrocarbon speciation data from nonroad engines is sparse. The 2-stroke engine conversions are derived from the study of only one moped engine while the 4-stroke engine results are an averaged result of 11 lawnmower engines studied. The diesel results are the average of two late 70s and early 80s vintage on-highway truck engines. The factors for compressed natural gas (CNG) and liquid petroleum gas (LPG) engines were estimated from data collected using on-highway light-duty vehicles equipped with catalysts. Nonroad equipment does not use this technology but no emissions data from nonroad CNG and LPG engines was available.

Table for Conversion Factors for Hydrocarbon Emission Results

Engine Type	TOG/THC	NMOG/THC	NMHC/THC	VOC/THC
2-Stroke Gasoline [2]	1.044	1.035	0.991	1.034
4-Stroke Gasoline [2, 3]	1.043	0.943	0.900	0.933
Diesel [4]	1.070	1.054	0.984	1.053
LPG [5]	1.099	1.019	0.920	0.995
CNG [5]	1.002	0.049	0.048	0.004

## **Conclusions**

The conversion factor is applied at the end of the model calculation of total hydrocarbons expressed as (THC). Emission factors are generated most typically as THC, so the conversion to other hydrocarbon forms is provided for the user.

## **References**

- [1] Air Resources Board (1996), "California Non-methane Organic Gas Test Procedure," California Environmental Protection Agency, Last Amended June 24, 1996.
- [2] Hare C.T. and White, J.J. (1991), "Toward the Environmentally-Friendly Small Engine, Lubricant, and Emission Measurement Issues", SAE-911222.
- [3] Gabele, P., (1997), "Exhaust emissions from four-stroke lawn mower engines," Journal of the Air & Waste Management Association, pp 642-649, vol.47, Sept., 1997.
- [4] Springer, Karl J. (1979), "Characterization of Sulfates, Odor, Smoke, POM and Particulates from Light and Heavy-Duty Engines -- Part IX," Ann Arbor, Michigan: U.S. Environmental Protection Agency, Office of Mobile Sources. Publication no. EPA-460/3-79-007.
- [5] ARB, (1991), "Proposed Reactivity Adjustment Factors for Transitional Low-Emission Vehicles," Technical Support Document, Sept., 27, 1991.