



United States
Department of
Agriculture

Rural
Development
Utilities
Programs

Informational
Publication
344-2

2008 Edition

LIST OF MATERIALS Acceptable for Use on Systems of USDA Rural Development Telecommunications Borrowers

DISCLAIMER

Every effort has been made to ensure the accuracy of this document. However, in case of discrepancies, records of Technical Standards Committee "A" are the authoritative source.

PREFACE

This List of Acceptable Materials (Telecommunications) supersedes all preceding issues. It reflects all actions of the Technical Standards Committees "A" and "B" (Telecommunications) through July 17, 2008.

The small letters used to designate many construction items listed herein correspond to the letters used on construction drawings to indicate individual items of material; however, many equipment items have been assigned letter combinations only as a means of identification within the List of Acceptable Materials (Telecommunications).

The acceptance of an additional item or the deletion of an existing item is a function of the RUS Administrator and Technical Standards Committees "A" and "B" (Telecommunications). Anyone desiring to have a new item placed on the List of Materials (Telecommunications), or believing an existing item should be removed from the List of Materials (Telecommunications), is invited to submit the matter to Technical Standards Committee "A" (Telecommunications). Any communication calling attention to an error, an obsolete item, etc., will also be appreciated. All communications should be addressed to the Chair, Technical Standards Committee "A" (Telecommunications), Stop 1550, U.S. Department of Agriculture, Rural Utilities Service, 1400 Independence Avenue, SW., Washington, D.C. 20250-1550.

The inclusion of an item in the List of Materials (Telecommunications) does not indicate that that item's manufacturer or its principals have not been debarred, suspended, proposed for debarment, declared ineligible or voluntarily excluded pursuant to Executive Order 12549, Debarment or Suspension, or any rules or regulations issued thereunder, including 7 CFR Part 3017 ("Debarment Regulations".) Therefore, borrowers must comply with the requirements imposed by the Debarment Regulations before entering into any "covered transaction," as defined by 7 CFR Part 3017, involving any item on this List of Materials (Telecommunications.)

RUS Buy American - All materials and equipment financed with loan funds are subject to the "Buy American" provisions (7 U.S.C. 901 *et seq.* as amended in 1938), as amended. For each product for which RUS acceptance as a domestic product is requested, the manufacturer must include a certification stating that the product, as it is sold to RUS borrowers, complies with the following two domestic origin manufacture provisions:

- a) Final assembly or manufacture of the product, as the product would be used by an RUS borrower, is completed in the United States or eligible countries (currently, Mexico, Canada and Israel); and
- b) The cost of United States and eligible countries' components (in any combination) within the product is more than 50 percent of the total cost of all components utilized in the product. The cost of non-domestic components (components not manufactured within the United States or eligible countries) which are included in the finished product must include all duties, taxes, and delivery charges to the point of assembly or manufacture.

Manufacturers should request Technical Acceptance of products of non-domestic origin manufacture.

Products accepted by RUS as domestic products are included in the List of Materials for information purposes. For a system that the manufacturer has certified to RUS that meets the RUS Buy American requirement as a domestic product, please be aware that a system component (hereafter in the paragraph called the "product") may stand alone as a "product" and that when sold by itself it may be a non-domestic "product." If this is the case, the manufacturer must inform the borrower that the "product" is non-domestic. The "product" may be financed by RUS upon the product meeting the RUS Buy American Requirement as a Non-domestic product.

For RUS product acceptance listed manufacturers have certified that an Agency-accepted product, as sold to RUS owner, complies with the Agency "Buy American" requirement as a domestic product. However, there may be particular cases where a product configuration (or for other unique factors) that may cause the product to become non-domestic. When this is the case, the manufacturer shall inform the borrower that for this particular sale the product is a non-domestic product. Manufacturers are responsible to inform product distributors or re-sellers of the particular circumstances that would make their product non-domestic or to have an internal procedure in place as to ensure that the borrower is informed when the product has become non-domestic.

RUS POLICY ON THE FINANCING OF PRODUCTS WHICH HAVE RECEIVED AN RUS LETTER OF TECHNICAL ACCEPTANCE

Products that do not meet the "Buy American" provision of 1938, as amended, are also included in the RUS List of Materials as non-domestic technical acceptance from the Agency. The "Buy American" provision is found at http://www.usda.gov/rus/regs/info/100-1/buy_american.htm.

For RUS financing of a product RUS requires that the product complies with the "Buy American" provision and that the product either has been determined acceptable by RUS or has received an RUS letter of technical acceptance. For more information on RUS requirements for product acceptance or technical acceptance see RUS listing procedures at <http://www.usda.gov/rus/telecom/materials/listing/listing.htm>. A product complying with both of the provisions listed below complies with this "Buy American" provision and is considered a domestic product by RUS. If the product does not meet either of the two conditions, the product is then classified as non-domestic for purposes of RUS financing. These conditions are:

- (1) Final assembly or manufacture of the product, as the product would be used by an RUS borrower, is completed in the United States or eligible countries (currently, Mexico, Canada and Israel); and
- (2) The cost of United States and eligible countries' components (in any combination) within the product is more than 50 percent of the total cost of all components utilized in the product. The cost of non-domestic components (components not manufactured within the United States or eligible countries) which are included in the finished product must include all duties, taxes, and delivery charges to the point of assembly/manufacture.

A bid for a non-domestic product is considered to be in compliance with the "Buy American" provision by RUS if the non-domestic bid is lower than the lowest domestic bid by at least six percent of the cost of the material content of the non-domestic bid. This six percent cost differential is added to the non-domestic bid for the purpose of determining the low bid only

For products classified as non-domestic, there may be particular cases where a product configuration (or for other unique factors) that may cause the product to become domestic. When this is the case, the manufacturer shall inform the borrower that for this particular sale the product is a domestic product. Manufacturers are responsible to inform product distributors or re-sellers of the particular circumstances that would make their product domestic or to have an internal procedure in place as to ensure that the borrower is informed when the product has become domestic to avoid having the product treated as non-domestic for such particular sale.

The following documents have more information on RUS "Buy American" requirements:

- a) IP 100-1 , Rural Electrification Act of 1936, as amended, 7 U.S.C. 901-950b (as of 1/23/2004), available at <http://www.usda.gov/rus/index2/rusreqs.htm> ;
- b) RUS Bulletin 344-3, "Buy American Requirement, available at <http://www.usda.gov/rus/telecom/publications/bulletins.htm> ; and
- c) Buy American Federal Register Notices available at <http://www.usda.gov/rus/telecom/publications/publications.htm#buy>

RUS product acceptance requirements are found at http://www.usda.gov/rus/telecom/listing_procedures/index_listing_procedures.htm .

An application would consist of the information required in two documents:

- General Listing Procedures; and
- The document associated with the product specific requirements.

Index

<u>A</u>	<u>Item Designation</u>	<u>Page</u>
Access equipment	ae	5.1
Anchors, guy - expanding and plate	Z	6.2
Anchors, guy - drive-type	Z	6.2
Anchors, guy - swamp and rock.....	Z	6.2.1
Arresters, gas tube	nh	4.4
Arresters, secondary power	gi	4.5
Arresters, solid-state	nh	4.4
• gas tube	nh-a.....	4.4
• solid-state	nh-b.....	4.4
 <u>B</u> 		
Blocks, terminal, for use in pedestals.....	sh	4.6
Bolts, angle, thimble-eye.....	ba.....	6.13
Bolts, machine.....	c	6.13
Bolts, straight, thimble-eye.....	ao.....	6.13
Building entrance terminal (BET)	ni.....	4.1
• Protected, fuseless, well mount, carbon.....	ni-a.....	4.1
• Protected, fuseless, module, carbon.....	ni-b.....	4.1
• Protected, fuseless, well mount, gas.....	ni-c.....	4.1.1
• Protected, fuseless, module, gas.....	ni-d.....	4.1.2
 <u>C</u> 		
Cable, buried (Expanded Insulation-Filled).....	sc	1.1.1
Cable, buried (Filled).....	sc	1.1
Cable, fiber optic	oc	1.5
Cable fiber optic,		
• Unit Core or Central Core Tube Fiber Core Construction	oc-a	1.5
Cable fiber optic,		
• Gel Filled Multiple Loose Tube Core Construction1		
Cable fiber optic	oc-b	1.5.
• Self-Supporting Filled Fiber Optic Cables		
Cable fiber optic	oc-c	1.5.2
• Dry Filled Multiple Loose Tube Fiber Core Construction		
Cable, fiber optic	oc-d	1.5.3
• slack organizer	oco	2.11
Cable, terminating (TIP)	ct	1.2
Cases, splice closures	pl	2.1
• aerial for copper cables.....	pl-a	2.1
• buried for copper cables.....	pl-b.....	2.1.1
• underground (Manhole) for copper cables - filled	pl-c	2.1.2
• underground (Manhole) for copper cables - pressurized.....	pl-c	2.1.3
• buildings and central office vault splice for copper cables.....	pl-d.....	2.1.4
• aerial for fiber optic cablespl-e	2.1.4	
• buried splice fiber optic cables.....	pl-f	2.1.4
• buildings and central office vault for copper cables	pl-g.....	2.1.5

Clamps,

- suspension mz 6.15
- drop wire mk 6.3
- ground rod and pipe (indoors)..... aj 6.4
- ground rod and pipe (outdoors) aj 6.4.1
- guy..... u 6.14

Conduit, underground hc 2.2

Connectors

- splicing..... cm 3.1.2
- shield bonding..... gh 3.1
- Copper Cable and Wire gh-a 3.1
- Armored Fiber Optic Cable gh-b 3.1
- grounding me 6.5

D

damage repair kits drk 2.10

E

Enclosures

- lashed cables er 2.3
- strand-mounted, two-branch entrances(for lashed cables) er 2.3.1

Equipment

- access ae 5.1
- power service protection..... gg 4.3
- transport..... te 5.2

G

Guards

- buried service..... am 6.6
- cable, plastic wg 6.8
- cable split metal sl 6.7
- riser..... sg 6.8

Guy

- hooks..... br 6.15
- lift plates bk 6.15

H

Handholes hh 2.4

Harnesses, bonding connector gs 3.3

- #6 AWG Stranded Harness Wires gs-a 3.3
- #6 AWG Braid gs-b 3.3
- #14 AWG Insulated Harness Wires gs-a 3.3.1
- #6 AWG Insulated Harness Wires gs-b 3.3.1

Harnesses, shield connector isolation gt 3.3.2

Housings, buried plant	se	2.5
• Type BD Pedestals (Type H)	se	2.5
• Type BD Pedestals (Type M)	se	2.5.1
• Type BDS Serving Area Interface cabinet	se	2.5.2
Housings, central office slice housing.....	sj	2.5.3
• for copper cables	sj-a	2.5.3
• wall mounted for fiber optic cables.....	sj-b	2.5.3
• rack mounted for fiber optic cables.....	sj-c	2.5.3
• wall mounted with patch panels for fiber optic cables.....	sj-d	2.5.4
• rack mounted with patch panels for fiber optic cables.....	sj-e	2.5.4.1
• wall or rack mounted with patch panels for fiber optic... ..	sj-f	2.5.4.2
Housings, fiber optic splice case.....	se	2.5.2

L

Locknuts.....	ek	6.15
---------------	----------	------

M

Markers, cable.....	tm	3.2
Manholes, precast.....	hm	2.7

N

Network Elements	ene	5.5
Network interface devices	nid	4.7
Networks, wireless	wn	5.4
Numbers, pole	az	6.9
Nuts, regular, square	px	6.16

O

Optical fiber cable	oc	1.5
Fiber Cable Slack Organizer.....	oc0	2.11

P

Pedestal, inserts, restricted access	sk	2.5.5
Pedestals (housings, buried plant).....	se	2.5
Posts, mobile home.....	sd	2.8
Power Back-up	pb	4.8
Protectors, mainframe, carbon.....	nm	4.2
Protectors, mainframe, gas.....	nm	4.2
Protectors, mainframe, solid-state	nm	4.2
Protectors, power service, 125/250 volts	gg	4.3

R

Rods, anchor.....	x	6.1
" ground	ai	6.10

S

Sealer, buried plant housing	ps	2.6
" duct	sp	2.6
Screws, lag	j	6.14
Sleeves, filled plastic	sv	3.4
Strand, suspension and guy.....	y	6.11
Straps, reinforcement, suspension clamp.....	nb	6.16
Switching equipment, digital, stored program.....	pc	5.3

T

Terminals, wire, pole-mounted.....	wt	2.9
Thimble-eye nuts.....	ab	6.14
Transport equipment.....	te	5.2

W

Warning signs, stakes and numerals, buried plant.....	sm	3.5
Washers	d	7.14
Wireless Networks	wn	5.4
Wireless Networks - licensed.....	wn-l	5.4
Wireless Networks - unlicensed.....	wn-l	5.4
Wires, aerial service.....	nt	1.4
" buried, filled	sa	1.3
" cable lashing.....	nw	6.12

Index

<u>Item</u> <u>Designation</u>	<u>Description</u>	<u>Page</u>
c	Bolts, machine	6.13
d	Washers	6.14
i	Bolts, carriage	*
j	Screws, lag	6.14
u	Guy clamps	6.14
x	Rods, anchor	6.1
y	Strand, suspension and guy	6.11
z	Anchors, guy	6.2
aa	Oval eye nuts	*
ab	Thimble-eye nuts	6.14
ae	Access equipment	5.1
ai	Rods, ground	6.10
aj	Clamps, ground rod and pipe	6.4
al	Ground wire staples and nails	*
am	Guards, buried service	6.6
ao	Bolts, straight, thimble-eye	6.13
ap	Repellent, ant	*
ar	Alarm reporting systems	*
at	Guy guards	*
az	Numbers, pole	6.9
ba	Bolts, angle, thimble-eye	6.13
bj	Compensators, junction impedance	*
bk	Guy lift plates	6.15
bl	Steel support brackets	*
bm	Guy thimble	*
bo	Capacitors, building-out	*
br	Guy hooks	6.15
btc	Coaxial cable	*
cb	Conductor bundle bags	*
cc	Cable, switchboard	*
cd	Posts, (Concrete) buried plant housings	*
cm	Connectors, splicing	3.1.2
ct	Cable, terminating (TIP)	1.2
cw	Cable, inside wiring	*
df	False deadends	*
dm	Permanent cable identification markers	*
drk	Damage Repair Kits	2.10
dz	Guy wire clips	*
ec	Carrier equipment	*
ef	Repeaters, voice frequency	*
ek	Locknuts	6.15
em	Extenders, central office loop with VF repeater	*
ene	Electronic network elements	5.5

*Item no longer listed.

vi
02-05

ep.....	Concentrators, electronic subscriber line.....	*
er.....	Enclosures, ready-access, cable	2.3
et.....	Trunk circuits, electronic	*
ex.....	Extenders, central office loop	*
gf.....	Fittings, sidewalk guy	*
gg.....	Protectors, power service	4.3
gh.....	Connectors, shield bonding	3.1
gh-a.....	Connectors, Copper Cable and Wire	3.1
gh-b.....	Connectors, Armored Fiber Optic Cable.....	3.1
gi.....	Arresters, secondary power	4.5
gm.....	Equipment, microwave.....	*
gr.....	Generator, ringing.....	*
gs.....	Harnesses, bonding connector	3.3
gs-a.....	Harnesses, bonding connector - #6 AWG Stranded Harness Wires.. ..	3.3
gs-b.....	Harnesses, bonding connector - #6 AWG Braid.....	3.3
gs-a.....	Harnesses, bonding connector - #14 AWG Insulated Harness Wires.....	3.3.1
gs-b.....	Harnesses, bonding connector - #6 AWG Insulated Harness Wires.. ..	3.3.1
gt.....	Harnesses, shield connector isolation	3.3.2
hb.....	Bend, cast iron	*
hc.....	Conduit, underground	2.2
hd.....	Hooks, underground cable.....	*
he.....	Cap, cast iron.....	*
hh.....	Handholes	2.4
hi.....	Irons, pulling-in.....	*
hk.....	Sump, manhole.....	*
hl.....	Plugs, conduit	*
hm.....	Manholes, precast.....	2.7
hr.....	Racks, underground cable	*
hs.....	Supports, cable rack	*
ht.....	Covers and frames, manholes.....	*
lt.....	Lightwave digital transmission systems, Asynchronous	*
	" " " " Synchronous	*
lts.....	Layer Three Switch	5.5
md.....	Brackets, house	*
me.....	Connectors, grounding.....	6.5
mg.....	Drive hooks	*
mh.....	Hardware, modular telephone set.....	*
mi.....	Drop wire support.....	*
mj.....	Drop wire clip	*
mk.....	Clamps, drop wire	6.3
mm.....	Drive rings.....	*
mo.....	Angle screw	*
mu.....	Sleeves, splicing	*
mx.....	Steel pole steps	*
my.....	Drop wire hooks	*
mz.....	Cable suspension clamps.....	6.15

*Item no longer listed.

na	Cable, aerial and underground	*
nb	Suspension clamp reinforcement straps	6.16
nc	Cable extension arms	*
nd	Metal pole keys	*
ne	Bridle rings	*
nh	Arresters, gas tube	4.4
ni	Building entrance terminal (BET) – Protected	4.1
nid	Network interface devices	4.7
nm	Protectors, mainframe	4.2
no	Coils, loading	*
np	Clamps, cable	*
nq	Wires, ground	*
ns	Span clamps	*
nt	Wires, aerial service	1.4
nu	Wires, bridle	*
nw	Wires, cable lashing	6.12
ny	Spacers, cable	*
nz	Supports, lashed cable	*
oc	Cable, fiber optic	1.5
oc-a	Cable fiber optic, Unit Core or Central Core Tube Fiber Core Construction	1.5
oc-b	Cable fiber optic, Gel Filled Multiple Loose Tube Core Construction	1.5.1
oc-c	Cable fiber optic, Self-Supporting Filled Fiber Optic Cables	1.5.2
oc-d	Cable fiber optic, Dry Filled Multiple Loose Tube Fiber Core Construction	1.5.3
oco	Fiber cable slack organizer	2.11
pa	Blocks, pressure, in-line	*
pb	Power Back-up	4.8
pc	Switching equipment, digital, stored program	5.3
pg	Porcelain insulated screweyes	*
ph	Screw anchors	*
pk	Moisture blocks	*
pl	Cases (Closures), splice	2.1
pl-a	aerial for copper cables	2.1
pl-b	buried for copper cables	2.1.1
pl-c	underground (Manhole) for copper cables – filled	2.1.2
pl-c	underground (Manhole) for copper cables – pressurized	2.1.3
pl-d	buildings and central office vault splice for copper cables – Non Filled	2.1.3
pl-e	aerial for fiber optic cables – Filled and non-filled	2.1.4
pl-f	buried splice fiber optic cables - Filled	2.1.4
pl-g	buildings and central office vault for copper cables	2.1.5
pn	Straps, riser guard	*
pr	Blocks, pressure, by-pass	*
ps	Sealer, buried plant housing	2.6
pt	Vinyl tape	*
pv	Arresters, lightning	*
pw	Detachable pole steps	*
px	Regular square nuts	6.16
py	Lashing wire terminal clamps	*

*Item no longer listed.

ra.....	Telephone sets	*
ra.....	Telephone, pay station.....	*
rb.....	Ringers, main station	*
rb.....	Ringers, compact.....	*
rd.....	Ringers, loud ringing.....	*
re.....	Booths, pay station	*
rg.....	Wires, station	*
rh.....	Blocks, connector.....	*
rm.....	Radiotelephone equipment, mobile and fixed	*
rp.....	Repellent, rodent.....	*
sa.....	Wires, buried, filled	1.3
sc.....	Cable, buried (Filled).....	1.1
sc.....	Cable, buried (Expanded Insulation - Filled).....	1.1.1
sd.....	Posts, mobile home	2.8
se.....	Housings, buried plant	2.5
sf.....	Locator, buried splice.....	*
sg.....	Guards, riser	6.8
sh.....	Blocks, terminal, for use in pedestals	4.6
si.....	Isolator, bridged tap	*
sj.....	Housings, central office splice for copper and fiber cables	2.5.3
sj.....	Housings, central office splice with patch panels for fiber optic cables	2.5.4
sk.....	Pedestal, inserts, restricted access	2.5.5
sl.....	Guards, cable, split metal	6.7
sm.....	Warning signs, stakes and numerals, buried plant.....	3.5
sms.....	Subscriber management system	5.6
sp.....	Sealer, duct.....	2.6
st.....	Spacer tape.....	*
sv.....	Sleeves, filled plastic.....	3.4
tc.....	Telephone cords	*
tc.....	Cable ties	*
te.....	Transport equipment.....	5.2
tm.....	Markers, cable	3.2
tp.....	Converters, tone-to-pulse	*
tt.....	Toll ticketing system.....	*
wf.....	Cable, self-supporting	*
wg.....	Guards, cable, plastic	6.8
wk.....	Clamps, support, Figure 8 distribution wire	*
wl.....	Wireless local loop systems.....	*
wn.....	Wireless networks.....	5.4
wp.....	Posts (Wooden) buried plant housings.....	*
wt.....	Terminals, wire, pole-mounted	2.9
wu.....	Enclosures, ready-access, MPDW	*
wy.....	Terminals, connection, support wire-mounted.....	*
za.....	Filler tape	*
ze.....	Sealing compound	*
zz.....	Poles, pressure treatment.....	*
zz.....	Poles, thermal treatment.....	*

	<u>Item Designation</u>	<u>Page</u>
Cable, buried (Expanded Insulation-Filled).....	sc	1.1.1
Cable, buried (Filled).....	sc	1.1
Cable fiber optic	oc	1.5
Cable fiber optic, Unit Core or Central Core Tube Fiber Core Construction.....	oc-a	1.5
Cable fiber optic, Gel Filled Multiple Loose Tube Core Construction	oc-b	1.5.1
Cable fiber optic, Self-Supporting Filled Fiber Optic Cables.....	oc-c	1.5.2
Cable fiber optic Dry Filled Multiple Loose Tube Fiber Core Construction	oc-d	1.5.3
Cable, terminating (TIP).....	ct	1.2
Wires, aerial service.....	nt	1.4
Wires, buried filled	sa	1.3

ORDERING INFORMATION

When ordering wire and cable having a standard RUS Unit Designation, this designation must be specified with the appropriate suffix or combinations of suffixes to indicate the type to be supplied. For example, filled cable with gopher-resistant shield containing copper and having compartmental cores (Screened) would be designated "BFCYH.

sc - Buried Cable

Cables listed below comply 7 CFR 1755.390 or 1755.890.

Manufacturer Name	PE-39	PE-89	Accepted Cables	Suffixes
General Cable	X	X ⁽⁶⁾	PE-__39-AL	A(1)
	X	X ⁽⁶⁾	PE-__39-CU5	C(1)
	X	X ⁽⁶⁾	PE-__39-CBS	Y(1)
	X	X ⁽⁶⁾	PE-__39-CAC	X(1)
	X	X ⁽⁶⁾	__(3)T1	H(1)
	X	X ⁽⁶⁾	__(3)T1C	H1C(2)
		X		
Nacional De Conductores Eléctricos (Condux) ⁽⁵⁾	X	X ⁽⁶⁾	AM__(12)C	A(1)
	X	X ⁽⁶⁾	AM__(12)Q	Y(1)
	X	X ⁽⁶⁾	AM__(12)D	X(1)
Superior/Essex	X		SEALPIC ^R -F	A(1)
		X ⁽⁷⁾	SEALPIC ^R -F__(11)	A(1)
	X		CUPIC ^R -F	C(1)
		X ⁽⁷⁾	CUPIC ^R -F__(11)	C(1)
	X		GOPIC ^R -F	Y(1)
			CUPIC ^R -F10	
		X ⁽⁷⁾	GOPIC ^R -F__(11)	Y(1)
			CUPIC ^R -F__(11)10	
	X		CASPIC ^R -F	X(1)
		X ⁽⁷⁾	CASPIC ^R -F__(11)	X(1)
	X	X ⁽⁷⁾	__(3)T1	H(1)
			__(3)T1	
X	X ⁽⁷⁾	__(3)T1C	H1C(2)	
		__(3)T1C		
X	X ⁽⁷⁾	__(4)P	P(1)	
		__(4)P		

Suffixes

- Coated Aluminum Shield ----- A
- 5 Mil Copper Shield ----- C
- Gopher-Resistant Shield Containing Copper ----- Y
- Gopher-Resistant Shield/Armor Design ----- X
- Screened Cable for T1 Carrier ----- H
- Screened Cable for T1C Carrier ----- H1C
- Pre-connectorized Cable 100 pairs and greater ----- P

See notes on page 1.1.2.

1.1.2
012-27-2005
sc

Notes:

- (1) Available in 19 through 26 AWG conductor sizes.
- (2) Available in 19 through 24 AWG conductor sizes.
- (3) Replace blank with manufacturer's catalog designation shown in the listing for suffixes A through X.
- (4) Replace blank with manufacturer's catalog designation shown in the listing for suffixes A through H1C.
- (5) Not accepted for 19 AWG conductor sizes.
- (6) Accepted for only foam/skin.
- (7) Accepted for foam and foam/skin.
- (10) Replace the blank with the letters AR, CR, JR, or WR to specify shield type.
- (11) Replace blank with either the letter F or the letters SF to specify conductor insulation type.
- (12) Replace blank with either the letter A, M, or T to specify conductor AWG size.

1.2
01-05
ct

ct - Terminating Cable⁽¹⁾

These manufacturers' cables shown by X's comply with 7 CFR 1755.870.

Manufacturer

RUS Standard Designation Suffixes

	<u>A</u>	<u>P</u>
General Cable	X	-

Suffixes:

Coated Aluminum ----- A
Preconnectorized Cable 100 pairs and greater ----- P

Notes: (1) To be supplied in only 22 and 24 AWG sizes.

sa - Filled Buried Wires

These manufacturers' filled buried wires shown by catalog designations comply with 7 CFR 1755.860.

<u>Manufacturer</u>	<u>Catalog Designation</u>			
	<u>Distribution</u> ⁽¹⁾		<u>SEB (service)</u> ⁽²⁾	
RUS Standard Designations:	<u>N</u>	<u>Y</u>	<u>N</u>	<u>Y</u>
RUS Standard Suffixes:	<u>N</u>	<u>Y</u>	<u>N</u>	<u>Y</u>
General Cable	BFWN	BFWY	BFWN	BFWY
Superior/Essex	BDW-B -	BDW-G-CSC -	BDW-B BDWB-DF ⁽³⁾	BDW-G-CSC BDWG-DF ⁽³⁾

Suffixes:

Copper Alloy 220 (Bronze) Shield -----N
Gopher-Resistant Shield -----Y

Notes:

- (1) Available in 22 and 24 AWG conductor sizes.
- (2) Available only in 22 AWG conductor size.
- (3) Wire uses a "Water Blocking Powder" in place of a "Gel Compound" as the filling compound surrounding the twisted pairs in the wire core.

1.4
01-05
nt

nt - Aerial Service Wires

RUS Standard Designation "SEA"

These manufacturers' wires shown by catalog designations comply with 7 CFR 1755.700 through 7 CFR 1755.704

nt-a Copper Covered Steel Reinforced (CCSR) Aerial Service Wires

<u>Manufacturer</u>	<u>Catalog Designations</u>					
	<u>Standard</u>		<u>Reduced</u>		<u>Super-Reduced</u>	
	<u>oval</u>	<u>dumbbell</u>	<u>oval</u>	<u>dumbbell</u>	<u>oval</u>	<u>dumbbell</u>
General Cable	-	ADR-182-PVC	-	-	-	-
Superior/Essex	ADP	ADP-D	-	-	ADP/SR	ADP/SR-D

nt-b Nonmetallic Reinforced (NMR) Aerial Service Wires

<u>Manufacturer</u>	<u>Catalog Designations</u>			
	<u>2-Pair</u>	<u>3-Pair</u>	<u>5-Pair</u>	<u>6-Pair</u>
General Cable	2 TPR 22 AWG GSDW	-	-	6 TPR 22 AWG GSDW
Superior/Essex	2X22_ ⁽¹⁾	3X22_ ⁽¹⁾	5X22_ ⁽¹⁾	6X22_ ⁽¹⁾

⁽¹⁾Replace blank with either "ADP NMS" or "USW-DF."

oc – Fiber Optic Cable

Cable designs a, b, c, and d complies with 7 CFR 1755.900. Cable design e - complies with RUS requirements for Fiber Optic Service Entrance Cables. Cable designs, RUS suffixes and notes are outlined on page 1.5.4. For cable installation, PON users must follow the manufacturer's recommended use and practices.

<i>Manufacturer name and accepted fibers</i>	<i>Accepted Cables</i>	<i>Cable Design</i>	<i>Suffixes</i>
Alcoa Fujikura Ltd Accepted for dispersion-unshifted and dispersion-shifted single mode optical fibers. Also accepted for 50/125 and 62.5/125 micrometer multimode optical fibers.	Dielectric__(Pure) Uni-Tube MicroCore ⁽²⁾⁽⁷⁾	a	B
	AFL ADSS Mini-Span Series	c	J
	AFL Loose Tube Cable	d	F
	AFL Armored Loose Tube Cable	d	H
CommScope/Systimax Solutions Accepted only for dispersion-unshifted single mode optical fibers.	O-XXX-LN-XY-F12NS XXX=002-288 (Arid Core) 5024 XXXA WXBK XXX=002-288 (Arid Core)	d	F
	O-XXX-LA-XY-F12NS XXX=002-288 (Arid Core) 5023 XXXA WXBK XXX=002-288 (Arid Core)	d	H
	O-XXX-L2-XY-F12NS ⁽⁴⁾ XXX=002-288 (Arid Core) 5043 XXXA WXBK ⁽⁴⁾ XXX=002-288 (Arid Core)	d	H
	D-XXX-LN-XY-F12NS XXX=002-288 (Gel-Free, Arid Core) 5028 XXXA WXBK XXX=002-288(Gel-Free, Arid Core)	d*	F
	D-XXX-LA-XY-F12NS XXX=002-288 (Gel-Free, Arid Core) 5027 XXXA WXBK XXX=002-288(Gel-Free, Arid Core)	d*	H
	D-XXX-L2-XY-F12NS ⁽⁴⁾ XXX=002-288 (Gel-Free, Arid Core)	d*	H
	M-XXX-DN-XY-F12NS/GSM/40T XXX=001-012 (Arid Core)	e	J
	M-XXX-MN-XY-F06NS/CCS XXX=001-006 (Arid Core)	e	J
	O-XXX-DA-XY-F12NS XXX=001-012 (Arid Core)	e	M
	Corning Cable Systems SMF-28e (standard single-mode) LEAF (non-zero dispersion shifted single-mode) NexCor (premium single-mode) InfiniCor (50/125 Multi-mode and 62.5/125 Multi-mode)	ALTOS™ Figure-8 Gel-Free and Filled (Lite version included)	c
ALTOS™ Filled and Gel Free* (LST, LST Lite, and Lite versions included)		d	E, F, G, H, P
SOLO All-Dielectric Self Supporting (ADSS Short Span & ADSS Medium-Span)		c	J, P
SST-Drop (Dielectric & Armored - Toneable versions included)		e	B, C, N, P
SST-Ribbon, SST-Ribbon Gel-Free*, SST-UltraRibbon (Dielectric, Armored, Gel-Free* versions accepted)		a	B, C, P

1.5.1
07-17-2008
oc

oc – Fiber Optic Cable

Cable designs a, b, c, and d complies with 7 CFR 1755.900. Cable design e - complies with RUS requirements for Fiber Optic Service Entrance Cables. Cable designs, RUS suffixes and notes are outlined on page 1.5.4. For cable installation, PON users must follow the manufacturer's recommended use and practices.

<i>Manufacturer name and accepted fibers</i>	<i>Accepted Cables</i>	<i>Cable Design</i>	<i>Suffixes</i>
Draka Comteq Standard singlemode, Enhanced Singlemode, BendBright (XS), TeraLight Metro NZDSF, TeraLight Ultra NZDSF, includes 2.65 mm loose tubes.	ezUNITUBE™	a, e	B, C
	ezPREP™ Loose Tube Central	a, e	M
	ezRIBBON™ Central Tube ⁽⁸⁾⁽⁹⁾ (includes Gel Free version*)	a	A, B, C, D
	ezPREP™ Loose Tube Traditional Filled/Dry (includes Heavy Duty versions)	b, d, e	E, F, G, H
	ezPREP™ Loose Tube includes versions: 1. Heavy Duty 2. Gel Free* Figure 8	c, d, e	E, F, G, H, I, K
	ezSPAN™ADSS Short Span	c, e	J
	ezMICRODUCT™ ⁽⁷⁾	d, e	F
	ezSPAN™ADSS Long Span	c	J
	ezDROP™ Dielectric ezDROP™ Toneable ezDROP™ Figure 8	e	B, N, P I
Emtelle ITU-T G.652d ITU-T G.655.A(B)(C) ITU-T G.651 (multimode)	fibreflow™ Optical Fiber Unit System ⁽¹⁰⁾	(10)	(10)
Hitachi Cable Accepted only for dispersion-unshifted and dispersion-shifted single mode optical fibers.	60090	d	F
	60102 ⁽⁵⁾	d	H
	60298 ⁽⁴⁾	d	H

oc – Fiber Optic Cable

Cable designs a, b, c, and d complies with 7 CFR 1755.900. Cable design e - complies with RUS requirements for Fiber Optic Service Entrance Cables. Cable designs, RUS suffixes and notes are outlined on page 1.5.4. For cable installation, PON users must follow the manufacturer's recommended use and practices.

<i>Manufacturer name and accepted fibers</i>	<i>Accepted Cables</i>	<i>Cable Design</i>	<i>Suffixes</i>
NextGen Fiber Optics/ General Cable Accepted only for dispersion-unshifted single mode optical fibers.	4M ⁽³⁾ Y-DWB	c	I
	4H ⁽³⁾ N-DWB	c	K
	4 ⁽⁶⁾ 2A-DWB	d	E
	4 ⁽⁶⁾ 1A-DWB	d	F
	4 ⁽⁶⁾ 2F-DWB	d	G
	4 ⁽⁶⁾ 1F-DWB	d	H
OFS OFS Single Mode Fibers: AllWave®, AllWave® FLEX ZWP, TrueWave® RS, Singlemode Low Water Peak (Contact OFS for Literature)	LightPack® LXE	a	B, C
	Mini C2™	a	C, P
	AccuRibbon® DC	a	B, C
	Single Jacket, Armored (contact OFS for literature), Light-Armored	b	E, F, G, H, P
		d	
	Figure8 (includes Armored version, contact OFS for literature)	c	I, K, P
	PowerGuide® ADSS (includes TTH version)	c	J, P
OFS Multi Mode Fibers: LaserWave™ (50 um), Laser Optimized Fiber 62.5/62.5XL, Standard 62.5um & 50um Multimode Fiber (Contact OFS for Literature)	Fortex™ DT (includes High Density version and both may be Single Jacket, Armored, or Light-Armored as needed)	d	E, F, G, H, P
	AccuRibbon® LXE	a	B, C
	Mini LXE	e	C
	Dielectric Drop	e	B
	Mini LT (toneable version included)	e	B
	Midia FX PLUS ⁽⁷⁾	d, e	F

1.5.3
03-21-2008
oc

oc – Fiber Optic Cable

Cable designs a, b, c, and d complies with 7 CFR 1755.900. Cable design e - complies with RUS requirements for Fiber Optic Service Entrance Cables. Cable designs, RUS suffixes and notes are outlined on page 1.5.4. For cable installation, PON users must follow the manufacturer's recommended use and practices.

<i>Manufacturer name and accepted fibers</i>	<i>Accepted Cables</i>	<i>Cable Design</i>	<i>Suffixes</i>
<u>Prysmian</u> Accepted only for dispersion-unshifted and dispersion-shifted single mode optical fibers.	CentraLink™ ⁽²⁾ (includes CD version)	a, e	D
	AeroLink™ ADSS (includes Short, Medium, and Long versions)	c	J
	FlexLink™ (includes Armored version)	d, d*	F, H
	FusionLink™ XXXXYSTRADESJB (Non-Armored) Dry/Dry	a*	B
	FusionLink™ XXXXYSTRADSAJB (Armored) Dry/Dry	a*	C
	FusionLink™ XXXXYSTRABESJB (Non-Armored) Gel filled	a	B
	FusionLink™ XXXXYSTRABSAJB (Armored) Gel filled	a	C
	XXXXYYHNLADJNVK – ResiLink ADF™	e	B
	XXXXYYHNLTDJNVK – ResiLink TF™	e	B
	XXXXYYHNLEDJNVK – ResiLink™	e	I
<u>Remeo Products</u> Accepted for dispersion-unshifted and dispersion-shifted single mode optical fibers. Also accepted for 50/125 and 62.5/125 micrometer multimode optical fibers.	22 Series ⁽⁵⁾ (Contact Remeo for literature on dry block designs, flooded designs on web)	b,d,e	E, F
	23 Series ⁽⁴⁾ (Contact Remeo for literature on dry block designs, flooded designs on web)	b,d,e	G, H
	25 Series ⁽⁴⁾ (Contact Remeo for literature on dry block designs, flooded designs on web)	b,d,e	E, F
	28 Series ⁽⁴⁾⁽⁵⁾ (Contact Remeo for literature on dry block designs, flooded designs on web)	b,d,e	G, H
	83 Series ⁽⁴⁾⁽⁵⁾ (Contact Remeo for literature on dry block designs, flooded designs on web)	c	K, L
	88 Series ⁽⁴⁾⁽⁵⁾ (Contact Remeo for literature on dry block designs, flooded designs on web)	c	I, J
<u>Sumitomo Electric</u> Accepted for dispersion-unshifted fiber (PureBand and PureAccess) and dispersion-shifted single mode optical fibers (PureGuide and PureMetro). Also accepted for 50/125 and 62.5/125 micrometer multimode optical fibers.	Litepipe™ ADS™ (Ribbon & Fiber Bundle)	a	B
	Litepipe™ Armorlux® (Ribbon & Fiber Bundle)	a	C
	Litepipe™ Armorlux® - LE ⁽²⁾	a	B, D
	DriCore®	d	E, F, G, H
	DriTube (ribbon cable) *	a	B, C
	SE-*LW*, *LV*, *LG*, *LH*	e	N
	SE-*LQ* ⁽²⁾	e	M

oc – Fiber Optic Cable

Cable designs a, b, c, and d complies with 7 CFR 1755.900. Cable design e - complies with RUS requirements for Fiber Optic Service Entrance Cables. Cable designs, RUS suffixes and notes are outlined on page 1.5.4. For cable installation, PON users must follow the manufacturer's recommended use and practices.

<i>Manufacturer name and accepted fibers</i>	<i>Accepted Cables</i>	<i>Cable Design</i>	<i>Suffixes</i>
Superior Essex Matched Clad (MC), FullBand® Low Water Peak, Allwave®, Flex Zero Water Peak, AllWave® Zero Water Peak, Low Water Peak, ASMF 200 AFC, TeraLight, SMF-28 and 28e+, SMF-LS, Leaf NZ-DSF SMF, Dispersion-unshifted SMF, PureBand	SLT ⁽²⁾	a	B, D, P
	SLT-D-R ⁽²⁾ (Ribbon), SLT-D-R * (Dri-Lite™)	a	B, C, D, P
	S2	d	C, D
	MLT	b	E, F, G, H, P
	MLT-8	c	I, K, P
	MLT-D-8	c	I, K, P
	MLT-D	d	E, F, G, H, P
	Universal FTTP OFNR	e	N, P
	Toneable FTTP OFCR	e	N, P
	ADP FTTP Series 57	e	B, P
	Buried FTTP Composite Series 72	e	M, P, Q
	Universal Drop FTTP Series 570Q	e	N, P
	UG FTTP Series 513	e	N, P
	Buried FTTP Series 523	e	M, P, Q
	Toneable Drop FTTP Series 571Q	e	N, P
Figure 8 FTTP Series 573Q	e	I, P	

1.5.5
07-17-2008
oc

Cable Designs:

- a – Unit Core or Central Core Tube Fiber Core Construction
- b – Gel Filled Multiple Loose Tube Core Construction; May contain multiple fibers per tube.
- c – Self-Supporting Filled Fiber Optic Cables
- d – Dry Filled Multiple Loose Tube Fiber Core Construction; May contain multiple fibers per tube.
- e – Complies with Draft RUS Specification for Fiber Optic Service Entrance Cables
- * – Indicates Cable Designs that are fully dry using water blocking elements throughout.

Suffixes:

- A - Nonarmored with Metallic Strength Members Embedded in Jacket
- B - Nonarmored with Dielectric Strength Members Embedded in Jacket for aerial and duct use only
- C- Armored with Metallic Strength Members Embedded in Jacket
- D - Armored with Dielectric Strength Members Embedded in Jacket
- E - Nonarmored with Metallic Central Strength Member for aerial and duct use only
- F - Nonarmored with Dielectric Central Strength Member for aerial and duct use only
- G - Armored with Metallic Central Strength Member
- H - Armored with Dielectric Central Strength Member
- I - Nonarmored with Metallic Support Messenger
- J - Nonarmored with Dielectric Support Messenger
- K - Armored with Metallic Support Messenger
- L - Armored with Dielectric Support Messenger
- M - Armored with additional strength yarns in place of strength members for tensile strength.
- N - Nonarmored Dielectric Cable for aerial, underground and buried use.
- P - Preconnectorized Cable

Notes

- (1) May contain multiple fibers per tube.
- (2) Not embedded in jacket; surrounds central core tube.
- (3) Replace blank with the number 1 or 2.
- (4) Double jacketed design.
- (5) Single jacketed design.
- (6) Replace blank with either the letter M or H.
- (7) For air blown microduct (a duct having a diameter of 10 to 13 millimeters) installations only.
- (8) Toneable ribbon cable accepted
- (9) High count (288-432) 24 fiber splittable ribbon accepted
- (10) Users must follow manufacturer's installation requirements and method. Blown fiber system is accepted through 7 CFR 1755.900, section 1.4: "*Optical cable designs not specifically addressed by this specification may be allowed if accepted by REA. Justification for acceptance of a modified design must be provided to substantiate product utility and long term stability and endurance.*" System includes all accessories and components and is not accepted for individual use without the system.

	<u>Item Designation</u>	<u>Page</u>
Cases, splice.....	pl	2.1
“ (Closure) repair kits.....	drk	2.10
Conduit, underground	hc	2.2
Enclosures, ready-access, cable	er.....	2.3
Fiber cable slack organizer	oco	2.11
Handholes	hh	2.4
Housings, buried plant	se	2.5
• Type BD Pedestals (Type H)	se	2.5
• Type BD Pedestals (Type M)	se	2.5.1
• Type BDS Serving Area Interface cabinet	se	2.5.2
Housings, central office slice housing.....	sj	2.5.3
• for copper cables	sj-a	2.5.3
• wall mounted for fiber optic cables.....	sj-b	2.5.3
• rack mounted for fiber optic cables	sj-c	2.5.3
• wall mounted with patch panels for fiber optic cables.....	sj-d	2.5.4
• rack mounted with patch panels for fiber optic cables.....	sj-e	2.5.4.1
• wall or rack mounted with patch panels for fiber optic... ..	sj-f	2.5.4.2
Manholes, precast concrete	hm	2.7
Pedestal, inserts, restricted access	sk	2.5.5
Posts, mobile home.....	sd	2.8
Sealer, buried plant housing	ps	2.6
Sealer duct	sp	2.6
Terminals, wire, pole-mounted.....	wt	2.9
Damage Repair Kits	drk	2.10
Fiber Cable Slack Organizer.....	oco	2.11

pl - Splice Closure

Cable closure designs, RUS suffixes and notes are outlined on page 2.1.6.

Manufacturer	Accepted Closures	Max. Cable Dia.(6)	Max. Splice Capacity(8)	Encapsulant.(2)	Closure Design	Suffixes
3M Company	SLiC 2x19 FB	1.6"			a1	A,C
	SLiC 2x29 FB	1.6"			a1	A,C
	SLiC 3x33 FB	2.6"			a1	A,C
	SLiC 5x33 FB	3.0"			a1	A,C
	SLiC 7x33 FB	3.8"			a1	A,C
	SLiC 9x36 FB	3.8"			a1	A,C
	GATM92000	1.5"			a1	A,C
	GATM95000	2.5"			a1	A,C
GATM97000	4.0"			a1	A,C	
3M Company (510 Version)	2X2AA	1.0"			a2, b2	A,C
	2Y2AA	1.0"			a2, b2	A,C
	2A2	1.6"			a2, b2	A,C
	2B2	2.9"			a2, b2	A,C
	2C2	3.5"			a2, b2	A,C
	2D2	3.5"			a2, b2	A,C
	2E2	4.5"			a2, b2	A,C
3M Company	8981-4462/GEL	0.58"		8882GEL	b1	A,C
	8982-4462/GEL	1.0"		8882GEL	b1	A,C
	8983-4462/GEL	1.5"		8882GEL	b1	A,C
	8984-4462/GEL	2.0"		8882GEL	b1	A,C
	8985-4462/GEL	2.4"		8882GEL	b1	A,C
	8986-4462/GEL	3.33"		8882GEL	b1	A,C
	BB2 x 24 4462/GELLA SC, DC-LHS	1.2"		8882GEL	b1	A,C
	BB3 x 24 4462/GELLA SC, DC-LHS	1.7"		8882GEL	b1	A,C
	BB4 x 24 4462/GELLA SC, DC-LHS	2.0"		8882GEL	b1	A,C
	BB5 x 26 4462/GELLA SC, DC-LHS	2.4"		8882GEL	b1	A,C
	BB6 x 26 4462/GELLA 2DC-LHS	3.3"		8882GEL	b1	A,C
	BB7 x 26 4462/GELLA 2DC-LHS	3.6"		8882GEL	b1	A,C
	BB9 x 26 4462/GELLA 2DC-LHS	3.8"		8882GEL	b1	A,C
	FSC 2x12	0.58"		8882GEL	b1	A,C
	FSC 3x12S	1.0"		8882GEL	b1	A,C
	FSC 3x12L	1.5"		8882GEL	b1	A,C
	FSC 3x19	1.5"		8882GEL	b1	A,C
	FSC 3x21	1.5"		8882GEL	b1	A,C
	FSC 4x19	2.4"		8882GEL	b1	A,C
	FSC 4x21	2.4"		8882GEL	b1	A,C
	FSC 6x19	3.3"		8882GEL	b1	A,C
	FSC 8x19	3.8"		8882GEL	b1	A,C
FSC 8x19L	3.8"		8882GEL	b1	A,C	
3M Company (Kohler & Besser) * Insert inner diameter and cover length according to manufacturer instructions.	K & B Series Non-Flame Retardant.(9) 2 * 2 (*)				c	
	K & B Series Flame Retardant.(5) 2 * 2 (*)				c	

2.1.1
09-28-07
pl

pl - Splice Closure

Cable closure designs, RUS suffixes and notes are outlined on page 2.1.6.

Manufacturer	Accepted Closures	Max. Cable Dia.(6)	Max. Splice Capacity(8)	Encapsulant.(2)	Closure Design	Suffixes	
(cont.)3M Company	FD06		48		d	B, C	
	FD08		96		d	B, C	
	2178S (non-flame retardant) ⁽⁹⁾		96		d, f	A, B, C	
	2178LS		480		d, e	A, B, C	
	2177-R		64	8882	e	A, B, C	
	2178FR (flame retardant)				f		
	2178XSB		48		d, e	B	
	SLiC Fiber Aerial Closure 530 ⁽¹⁵⁾		12		d	A, B, C	
	SLiC Fiber Aerial Closure 533		144		d	C	
	SLiC Fiber Aerial Closure 733		288		d	C	
	Fiber Dome Closure FDC 08		96		d, e	B, C	
	Fiber Dome Terminal Closure FDT 08 External Drop (w/ HFOC)			72 with 4, 6, or 8 drop ports (14)		d, e	B, C
	Fiber Dome Terminal Closure FDT 08 Direct Splice Drop			96 or 72 with up to 8 drop ports		d, e	B, C
Fiber Dome Terminal Closure FDT 08 Internal Drop			24 with 4, 6, or 8 drop ports		d, e	B, C	
ADC	MST (w/HFOC)		2/4/6/8/12 ports ⁽¹⁴⁾		d, e	B	
AFL	LG-50		18		d	A, B	
	LG-100		36		d	B, C	
	LG-200		96		d	B, C	
	LG-300		384		d	B, C	
	LG-300XL		864		d	B, C	
	LG-410		72		d	A, B, C	
	LG-420		12		d	A, B, C	
	LG-500		72		d	A, B, C	
LG-600		288		d	A, B, C		
Corning Cable Systems ⁽¹⁰⁾	LCA9T34		72		d	A, B, C	
	SCA-9T34		240		d	A, B, C	
	SCA-KT9		48		d	A, B, C	
	SCA-9T24 ⁽¹²⁾		216		d	A, B, C	
	SCA-6T24 ⁽¹²⁾		72		d	A, B, C	
	OptiSheath (w/Optifit)			2/4/6/8/12 ports ⁽¹⁴⁾		d, e	A, B, C
	SCF-6C22		72		e	A, B, C	
	SFC-6C28		288		e	A, B, C	
	SCF-8C28 ⁽¹¹⁾		576		e	A, B, C	
	SCC-6C22		10		e	A, B, C	
	SCC-6C28		20		e	A, B, C	
	SCC-8C28		30		e	A, B, C	
	SCP-6C22		96		e	A, B, C	
	UCA4-XX		72		e	A, B, C	
UCA5-XX		72		e	A, B, C		
Lucent Technologies	UCB1 (flame retardant)				f		

pl - Splice Closure

Cable closure designs, RUS suffixes and notes are outlined on page 2.1.6.

Manufacturer	Accepted Closures	Max. Cable Dia.(6)	Max. Splice Capacity(8)	Encapsulant.(2)	Closure Design	Suffixes	
Multilink Broadband (Starfighter)	1120F-GK01		24		d	A, B, C	
	2000F-GK01		72		d	A, B, C	
	4048-D		96		d, e	B	
	4000-D		192		d, e	B	
	3000F		144		d, e	A, B, C	
Preformed Line Products	8006021	2.2"			a2, b1	A,C	
	8006022	4.1"			a2, b1	A,C	
	8006023	6.85"			a2, b1	A,C	
	8006024	4.1"			a2, b1	A,C	
	8006025	6.85"			a2, b1	A,C	
	8006177	10.1"			a2	A,C	
	8006219	10.1"			a2, b1	A,C	
	8006220	10.1"			a2, b1	A,C	
	8006221	10.1"			a2, b1	A,C	
	8006287	2.2"			RD	b1	A,C
	8006288	4.1"			RD	b1	A,C
	8006289	4.1"			RD	b1	A,C
	8006290	7.1"			RD	b1	A,C
	8006291	7.1"			RD	b1	A,C
	8006292	7.1"			RD	b1	A,C
	8006293	10.1"			RD	b1	A,C
	8006294	10.1"			RD	b1	A,C
	8006295	10.1"			RD	b1	A,C
	8006 Series (non-flame retardant)					c	
	8006 FR Series (flame retardant)					c	
	8001005				RD	d, e	B
	8001006				RD	d, e	A,C
	8006692					d, e	A, B
	8006661 (non-flame retardant)					d, e, f	A, B, C
	8006659 (non-flame retardant)					d, e, f	A, B, C
	8006660 (non-flame retardant)					d, e, f	A, B, C
	8006887					d, e	B, C
	8006946					d, e	B, C
	8006878					d, e	B, C
	8006944					d, e	B, C
	8006945					d, e	B, C
	8006941					d, e	B, C
	8006879					d, e	A, B, C
	8006880					d, e	A, B, C
	8006951					d, e	A, B, C
	8006953					d, e	A, B, C
	8006954					d, e	A, B, C
	8006955					d, e	A, B, C
	8006956					d, e	A, B, C
	80011839					d, e	A, B, C
8001010 (flame retardant)					f		
8001011 (flame retardant)					f		
Telepak	TPIKRU-A	25 - 200pr.		8882GEL	a2, b1, b2	A, C	
	TPIKRU-B	300-400pr.		8882GEL	a2, b1, b2	A, C	
	TPIKRU-C	600pr.		8882GEL	a2, b1, b2	A, C	

2.1.3
05-07
pl

pl - Splice Closure

Cable closure designs, RUS suffixes and notes are outlined on page 2.1.6.

Manufacturer	Accepted Closures	Max. Cable Dia.(6)	Max. Splice Capacity(8)	Encapsulant.(2)	Closure Design	Suffixes
Thomas&Betts	C-3500	1.00"		8882GEL	a1	A, C
	C-3501	1.50"		8882GEL	a1	A, C
	C-3502	1.75"		8882GEL	a1	A, C
	C-3503	2.125"		8882GEL	a1	A, C
	C-3504	2.75"		8882GEL	a1	A, C
	C-3505	3.125"		8882GEL	a1	A, C
	C-3506	4.50"		8882GEL	a1	A, C
	C-3507	6.00"		8882GEL	a1	A, C
	C-3509	7.50"		8882GEL	a1	A, C
	C-3508	9.00"		8882GEL	a1	A, C
	TBTKNKs	6-25 pr.		8882GEL	b1	A, C
	TBTBA-1	25-100 pr.		8882GEL	b1	A, C
	TBTKNKAA			8882GEL	b1	A, C
	TBTKNKA			8882GEL	b1	A, C
	TBTKNKA2	25-200 pr.		8882GEL	b1	A, C
	TBTKNKA4	25-400 pr.		8882GEL	b1	A, C
	TBTA2	100-200 pr.		8882GEL	b1	A, C
	TBTKNKB	100-300 pr.		8882GEL	b1	A, C
	TBTKNKB2	200-400 pr.		8882GEL	b1	A, C
	TBTKNKB4	200-600 pr.		8882GEL	b1	A, C
	TBTBA3	300-900 pr.		8882GEL	b1	A, C
	TBTKNKC2	600-900 pr		8882GEL	b1	A, C
	TBTKNKC4	600-1300pr		8882GEL	b1	A, C
	TBTKNKD2	900-2400pr		8882GEL	b1	A, C
	C-5100	1.0"			b2	A
	C-5101	1.6"			b2	A
	C-5102	2.2"			b2	A
	C-5103	3.0"			b2	A
	C-5104	3.0"			b2	A
	C-5105	1.0"			b2	C
	C-5106	1.6"			b2	C
	C-5107	2.2"			b2	C
	C-5108	3.0"			b2	C
C-5109	3.0"			b2	C	

pl - Splice Closure

Cable closure designs, RUS suffixes and notes are outlined on page 2.1.6.

Manufacturer	Accepted Closures	Max. Cable Dia.(6)	Max. Splice Capacity(8)	Encapsulant.(2)	Closure Design	Suffixes
Tyco Electronics	CST (Cold Sealed Terminal) ⁽¹⁶⁾				b1	B, C
	TRAC – A	1.26"			a1	A, C
	TRAC – B	1.89"			a1	A, C
	TRAC – B+	2.56"			a1	A, C
	TRAC – C	3.27"			a1	A, C
	XAGA 1650-S	.35"		CasChem 165	b1	A, C
	XAGA 1650-A	.48"		CasChem 165	b1	A, C
	XAGA 1650-AA	.48"		CasChem 165	b1	A, C
	XAGA 1650-A2	.48"		CasChem 165	b1	A, C
	XAGA 1650-A4	.48"		CasChem 165	b1	A, C
	XAGA 1650-B2	1.10"		CasChem 165	b1	A, C
	XAGA 1650-B4	1.10"		CasChem 165	b1	A, C
	XAGA 1650-C2	1.85"		CasChem 165	b1	A, C
	XAGA 1650-C4	1.85"		CasChem 165	b1	A, C
XAGA 1650-D2	2.00"		CasChem 165	b1	A, C	
XAGA 1650-D4	2.00"		CasChem 165	b1	A, C	
Tyco Electronics (CERTI-SEAL) Series 6, 59, 7, & 11 for Tel. & Coax	569224-1	.29 - .46"		Sealant 20	b1	A, C
	569661-1	.29 - .46"		Sealant 20	b1	A, C
	569671-1	.29 - .46"		Sealant 20	b1	A, C
	569579-1	.29 - .46"		Sealant 20	b1	A, C
	1116449-1	.29 - .46"		Sealant 20	b1	A, C
	1217195-1	.35 - .57"		Sealant 20	b1	A, C
Tyco Electronics	FOSC400-A4-X-NT-O-NGV-RUS				d	B, C
	FOSC400-B2-X-NT-O-NGV-RUS				d	B, C
	FOSC400-B4-X-NT-O-NGV-RUS				d	B, C
	FOSC400-C5-X-NT-O-NGV-RUS				d	B, C
	FOSC400-D5-X-NT-O-NGV-RUS				d	B, C
	FOSC450-A4-X-NT-O-A1V-RUS				d, e	B, C
	FOSC450-B6-X-NT-O-B3V-RUS				d, e	B, C
	FOSC450-C6-X-NT-O-D6V-RUS				d, e	B, C
	FOSC450-D6-X-NT-O-D6V-RUS				d, e	B, C
FTerm UMT			4/6/8/12 ports ⁽¹⁴⁾		d, e	B, C

2.1.5
05-07
pl

pl - Splice Closure

Cable closure designs, RUS suffixes and notes are outlined on page 2.1.6.

Manufacturer	Accepted Closures	Max. Cable Dia.(6)	Max. Splice Capacity(8)	Encapsulant.(2)	Closure Design	Suffixes
URASEAL *The branch type max. cable dia. 2.2" and 3.0", respectively.	CA1900WE-A1S	1.2"			a1	A, C
	CA1900WE-B1S*	1.87"			a1	A, C
	CA1900WE-C1S*	2.5"			a1	A, C
	CFO40413NG-RUS-01		24		d, e, f	B, C
	CFO40413NG-RUS-02		36		d, e, f	B, C
	CFO40413NG-RUS-03		48		d, e, f	B, C
	CFO40413NG-RUS-04		72		d, e, f	B, C
	CFO40413NG-RUS-05		96		d, e, f	B, C
	CFO40413ND-RUS-01		24		d, e, f	B, C
	CFO40413ND-RUS-02		36		d, e, f	B, C
	CFO40413ND-RUS-03		48		d, e, f	B, C
	CFO40413ND-RUS-04		72		d, e, f	B, C
	CFO40413ND-RUS-05		96		d, e, f	B, C

2.1.6
12-27-2007
pl

Closure Designs:

- a1 – Aerial Splice Closure for Copper Cables Free-Breathing
- a2 – Aerial Splice Closure for Copper Cables Pressurized
- b1– Buried/Underground Splice Closure for Copper Cables
- b2– Buried/Underground Splice Closure for Copper Cables Pressurized
- c – Buildings and Central Office Vault Splice Closure for Copper Cables
- d – Aerial Splice Closure for Fiber Cables
- e– Buried/Underground Splice Closure for Fiber Cables
- f – Buildings and Central Office Vault Splice Closure for Fiber Cables

Suffixes:

- A – In-line
- B – Butt
- C – Branch

Notes:

1. Fiber organizer trays shall be ordered in accordance with manufacturer's instructions.
2. The encapsulant is a component part of the splice closure system and shall be provided by the closure manufacturer. The encapsulant is not accepted on an individual basis.
3. The main cable diameter, cable configuration (number of cables, pair count and gauge), and splice bundle diameter should be specified by the engineer.
4. 3M Better Buried closures are accepted for Branch splicing only.
5. For vertical installations order standard closure with "5925 FireBarrier Shield."
6. Metric sizes available for the following manufacturers: 3M.
7. These closures may also be installed in pedestals.
8. Maximum capacity for fusion splices
9. Non-flame retardant cases shall not be placed in a building or central office, they may be placed in a cable vault.
10. Accepted entire closure series with accessories, couplers, splitters, organizers, etc.
11. Accepted entire closure series except one, SCF-8C28-9F which has been technically accepted as a non-domestic product.
12. Acceptance includes SPAP and Optisheath Advantage terminals.
13. NG designates non-ADSS cables and ND designates ADSS cables.
14. This is a pre-connectorized outside plant hardened PON terminal that may be deployed as a stand alone aerial end user service pole/messenger terminal or in an enclosure for buried or underground end user service distribution. Acceptance includes hardened fiber optic connectors (HFOC) and RDUP/RUS Listed service entrance (drop) cables specifically mated for this terminal's use or for individual purchase as a stand alone pre-connectorized fiber drop for other like terminals using the patented licensed Corning technology.
15. Acceptance includes 4, 6, 8, and 12 external drop cable terminations.
16. Equipped with either 25 pair or 50 pair Dat@Term terminal blocks.

hc - Underground Conduit

<u>Manufacturer</u>	<u>Type Conduit</u>	<u>Catalog Number</u>
Allwire, Inc.	Flexible plastic	ALLDUCT
American Pipe & Plastics	Plastic Plastic Plastic	Type B, C, and D Type EB and DB PVC Multi-Duct (2,3,4 and 6-way)
Apache Plastics, Inc.	Plastic	Type EB and Type DB
Arnco	Flexible plastic	HDPE Conduit
Blue Diamond Industries, LLC	Flexible plastic	HDPE Duct
Bore Flex	Flexible plastic	HDPE Duct
Bristolpipe	Plastic Plastic	Type B, C, and D Type EB and Type DB
Cantex	Plastic Plastic Plastic Plastic	Type EB and Type DB Type B, C, and D Schedule 40 Schedule 80 Cellular Core PVC Sch.40 Cellular Core PVC DB120
Carlton/Pyramid	Plastic Plastic (Telephone Duct) Plastic Flexible Plastic Plastic Plastic Plastic	Type EB, Type DB Type B ⁽¹⁾ , Type C ⁽¹⁾ , and Type D ⁽¹⁾ Multi-Gard ⁽¹⁾ HDPE Conduit BORE-GUARD (Sch. 40 & 80) ⁽¹⁾ PVC Schedule 40 PVC Schedule 80
Certain-Teed Products Corp.	Plastic	Type EB and Type DB
Comfit USA	HDPE	100, 125, 150, & 200
CommScope	Flexible plastic Toneable Smooth/ribbed wall Co-extruded	SDR 13.5, SCH 40 (1/2" – 4") SDR 11, 13.5, SCH 40 (3/4" – 4") SDR 9, 11, 13.5, SCH 40, 80 (13mm- 4") SDR9, 11, 13.5, SCH 40, 80(3/4" -4")
CSR Polypipe	Flexible plastic	HDPE Duct
Dura-line	Flexible plastic	HDPE Duct
Endot Industries	Flexible plastic	HDPE Duct
Flying "W" Plastics	Flexible plastic	HDPE Duct
Freedom Plastics, Inc.	Plastic	Type C

See page 2.2.2 for notes.

2.2.1
09-28-07
hc

hc - Underground Conduit

<u>Manufacturer</u>	<u>Type Conduit</u>	<u>Catalog Number</u>
Heritage Plastics	Plastic	PVC Types EB, DB, Sch. 40 and Sch. 80
Hurlbut Plastic Pipe	Plastic	Type C
Imperial Pipe Corp.	Flexible plastic	HDPE Duct
IPEX, Inc.	Flexible plastic (Fibertel)	EPEC-(B, 40, SDR11, 80)-HDPE 1" – 4"
Ironhed	Stainless Steel FMP	3, 7, 10, 12, & 14 Gauge
J-M Manufacturing Company	Plastic	Types C, EB, and DB
National Pipe & Plastics, Inc.	Plastic Plastic	Type EB and Type DB Type B and Type C
Northern Pipe Products	Plastic	Type B, C, and D
OMNI	Flexible plastic Plastic	HDPE Duct Multiple plastic conduit (3 & 4 Way)
OSI Plastics	Flexible plastic	EPEC-A-HDPE 1" – 4"
Performance Pipe	Flexible plastic	DRISCOPLEX Duct
Petroflex	Flexible plastic Flexible plastic	HDPE Duct Corrugated HDPE Duct
Plastic Industries, Inc.	Plastic	HDPE SDR 9 HDPE SDR 11 HDPE SDR 13.5 HDPE SDR 17
PWPipe	Plastic Flexible plastic	PVC Types EB, DB, and Sch. 40 HDPE Coiled Duct
Queen City Plastics	Plastic Plastic	Type EB and Type DB PVC Schedule 40
Sedco	Plastic	Type EB and Type DB
Southern Pipe, Inc.	Plastic	PVC Types EB, DB, and Sch. 40
Summit Sales, Inc.	Plastic	Type B and Type C

See page 2.2.2 for notes.

Tamaqua Cable Products	Flexible plastic	HDPE Duct
TeraSpan	Rigid PVC	VIF System ⁽²⁾
Wesflex	Flexible plastic	Flex-Con

Note: For fiber and plastic conduit, Type I, Type B or Type EB is for concrete encasement and Type II, Type C or Type DB may be directly buried. Schedule 40 is a high strength conduit that may be used for concrete encasement or direct burial. Type D is for exposed installation, as on bridges.

Notes:

- (1) Carlon brand only
- (2) Vertical Inlaid Fiber (VIF) System includes VDC1, VDC3, VDC4, VDC6, VIF Cables (04, 12, & 24 strands), Cylindrical Access Node, splice enclosure, and miscellaneous components that complete the system. These items may not be purchased separately.

er - Cable Enclosures

er-a Ready Access Enclosures (Enclosures Only)

Lashed Cables

<u>Manufacturer</u>	<u>Main Cable Dia. Range</u>	<u>Straight</u>	<u>Branch</u>
3M	0.40-4.00"	SLIC ⁽⁵⁾	SLIC ⁽⁵⁾
Emerson Network Power, Energy Systems	0.4-1.2"	100 MB ⁽⁷⁾	100 MBY ⁽⁷⁾
	1.2-2.0"	200MB ⁽⁷⁾	200MBY ⁽⁷⁾
	2.0-3.0"	430	430Y
Thomas&Betts	0.50-2.20"	Termax C-2280	-

See page 2.3.2 for notes.

2.3.1
11-05
er

er - Cable Enclosures

er-b Ready-Access Enclosures (Enclosures Only)

Strand-mounted, with two branch entrances (for lashed cables)

<u>Manufacturer</u>	<u>Type E</u>		<u>Type F</u>	
Diameter of main:	1.2" Maximum		2.2" Maximum	
Diameter of branch:	0.75" Maximum		1.6" Maximum	
Type of strand:	<u>Galvanized Steel</u>	<u>Alum.-Clad Steel</u>	<u>Galvanized Steel</u>	<u>Alum.-Clad Steel</u>
Emerson Network Power, Energy Systems	200MBY	200MBY	200MBY	200MBY

**er-c Ready-Access Enclosures e/w with IDC Terminal Blocks
(Fixed Count Enclosures)**

Strand-mounted, with two branch entrances (for lashed cables)

Filled Unprotected

	<u>Main Cable Dia. Range</u>	<u>Branch Cable Dia. Range</u>	<u>Series</u>
3M Company	0.40-4.00" 0.30-4.00" ⁽¹⁾	- 0.30-4.00"	SLIC ⁽²⁾⁽⁶⁾ GATM
Thomas&Betts	0.50-2.20"	-	Termax
Tyco Electronics	0.55-1.90" 0.50-1.50"	0.00-1.50" 0.00-1.00"	DTerminator 2 ICT-B DTerminator 2 ICT-A

Filled Protected

	<u>Main Cable Dia. Range</u>	<u>Branch Cable Dia. Range</u>	<u>Series</u>
Tyco Electronics	0.55-1.90" 0.50-1.50"	0.00-1.50" 0.00-1.00"	DTerminator 2 ICT-B ⁽³⁾ DTerminator 2 ICT-A ⁽³⁾

See page 2.3.2 for notes.

er - Cable Enclosures

er-d Ready-Access Enclosures e/w Binding Post Terminal Blocks (Fixed Count Enclosures)

Strand-mounted, with two branch entrances (for lashed cables)

Manufacturer

Filled Unprotected

	<u>Main Cable Dia. Range</u>	<u>Branch Cable Dia. Range</u>	<u>Variable</u>
Emerson Network	0.40-1.20"	0.40-0.80"	100MBY ⁽³⁾
Power, Energy	1.20-2.20"	0.40-1.60"	200MBY ⁽³⁾
Systems	2.00-3.00"	1.10-2.20"	430MBY ⁽³⁾

Filled Protected

	<u>Main Cable Dia. Range</u>	<u>Branch Cable Dia. Range</u>	<u>Variable</u>
Emerson Network	0.40-1.20"	0.40-0.80"	100MBY ⁽⁴⁾
Power, Energy	1.20-2.20"	0.40-1.60"	200MBY ⁽⁴⁾
Systems	2.00-3.00"	1.10-2.20"	430MBY ⁽⁴⁾

Notes:

1. The diameter range shown only includes the unprotected versions of the RGTA-type Emerson Network Power, Energy Systems terminal blocks.
2. Specify 3M PSI or Raychem (Tyco) terminal blocks when ordering.
3. May be ordered with up to 24 pairs using the 145BG Emerson Network Power, Energy Systems terminal block only.
4. May be ordered with up to 12 pairs using the 381G and 383G Emerson Network Power, Energy Systems terminal blocks only.
5. Includes the following catalog numbers only: 328 & 530 MT, 328 & 530-MT/SES, 328 & 530-MTA/SES, 328 & 530-MTC/RES, 328 & 530-MTC/SES, and 328 & 530-MTPI/SES.
6. Includes the following catalog numbers only: 328-G, 328-PI/SES, and 530-PI/SES.
7. Messenger insulator ordered separately. For 100MB or 100MBY order P10318. For 200MB or 200MBY order P10709.

2.4
03-21-2008
hh

hh - Handholes(1)(2)

Handholes for Fiber & Copper Systems

<u>Manufacturer</u>	<u>Catalog Number</u>
Armorcast	A6001974 (24"x36") A6001946" (13x24") A6001742 (30"x60") A6001691 (39"x30"DI) A6001640 (17"x30") A6001436 (36"x60") A6001430 (30"x48") A6001423 Series (12" X12")
Blue Diamond Industries, LLC	MOV-2S/D(3)
Brooks Products	1324 1730
Carson Industries	1730-13B H910 HLW1212-12 HLW1118-12 H1118-12, 15, 18 H1324-12, 15, 18 H1730-12, 18, 24 H2436-18, 24, 30, 36 H3048-18, 24, 30, 36 H3060-24, 30, 36
CDR Systems (Homac)	TA-1324 TA-1730 TA 2000 TA-2436 TA-2700 TA-3048W TA-3048 TA-3060 TA-3200 TA-3660 TA-3900 TA-4848 TA-4872 TA-4878 TA-4896
Charles Industries, Ltd.	FMH 361 FMH 362 FMH 363

See page 2.4.3 for notes.

hh - Handholes(1)(2)

Handholes for Fiber & Copper Systems

Manufacturer

Catalog Number

Christy Concrete Products

SYN118TBOX__ (12, 18, 24, or 36)
SYN118TLID

SYN1212TBOX__ (12, 18, 24, or 36)
SYN1212TLID

SYN1324TBOX__ (12, 18, 24, or 36)
SYN1324TLID

SYN1730TBOX__ (12, 18, 24 or 36)
SYN1730TLID

SYN2436TBOX__ (18, 24, or 36)
SYN2436TLID

SYN3048TBOX__ (18, 24, or 36)
SYN3048TLID

SYN3660TBOX__ (18, 24, or 36)
SYN3660TLID

Highline

CHA
10x15x__ (12 or 18)
11x18x__ (12 or 18)
12x12x__ (12, 18 or 24)
13x24x__ (12, 15, 18 or 24)
17x30x__ (12, 18, 24 or 30)
24x36x__ (18, 24, 30 or 36)
30x48x__ (18, 24, 30 or 36)

CVA
30x48x__ (various depths from 18" to 48")
30x60x__ (various depths from 18" to 48")
36x36x__ (various depths from 18" to 48")
36x60x__ (various depths from 18" to 48")
36x72x__ (various depths from 18" to 48")
36x96x__ (various depths from 18" to 48")
48x48x__ (various depths from 18" to 48")
48x72x__ (various depths from 18" to 48")
48x78x__ (various depths from 18" to 48")
48x96x__ (various depths from 18" to 48")

PHA
10x15x12
11x18x12
12x12x12
13x24x15
13x24x18
17x30x__ (18 or 24)
24x36x__ (18 or 24)
30x48x36

See page 2.4.4 for notes.

2.4.2
07-17-2008
hh

hh - Handholes(1)(2)

Handholes for Fiber & Copper Systems

Manufacturer

Catalog Number

Highline (Continuation)

PTA
10x15x__ (12 or18)
12x12x12
13x24x18
17x30x__ (12 or 18)
24x36x18

NewBasis

S1324
S1730
FCA/PCA 2436xxxx -20K
FCA/PCA 3048xxxx -20K
FCA/PCA 3048xxxx -20K
FCA/PCA 1324xxxx -20K
FCA/PCA 1730xxxx -20K
FCA/PCA 2436xxxx -20K
FCA/PCA 3048xxxx -20K
FCA/PCA 3048xxxx -20K
SG5400-SW
FCA/PCA 3660xxxx -20K

Northwest Pipe & Tank, Inc.

#8-C124 (4'x10"x3'4"x2'6")⁽⁴⁾

See page 2.4.4 for notes.

hh - Handholes⁽¹⁾(2)

Handholes for Fiber & Copper Systems

<u>Manufacturer</u>	<u>Catalog Number</u>
Pen-Cell Plastics	PE-10 PE-20 (Restricted to cable sizes up to 100 pairs) PE-36 PE-6HD PE-9HD PE-14HD PE-30HD PE-20HD PE-20F PE-20U PE-30HD PE-30F PE-30U PE-36A PE-36HD PEM Series
Quazite	PC1324 PC1730 PX1324 PX1730 PG2436 PG3048 LG3060 LG3660 LR2732
TDB Communications (Common Ground Enclosure)	TDB-GB-T ⁽⁵⁾
Tunnel Mill Polymer, Inc.	R264836
Utility Vault	3642-BL ⁽⁴⁾ (6)(2'8"x3'6"x4') 25-TA (5'2½"x2'3"x2'6")

See page 2.4.4 for notes.

2.4.4
10-19-2007
hh

hh - Handholes⁽¹⁾⁽²⁾

Handholes for Fiber & Copper Systems

<u>Manufacturer</u>	<u>Catalog Number</u>
Synertech	S1118B12FA – 11"x 18"x 12"
	S1118B18FA – 11"x 18"x 18"
	S1212B12FA – 12"x 12"x 12"
	S1212B18FA – 12"x 12"x 18"
	S1324B12FA – 13"x 24"x 12"
	S1324B18FA – 13"x 24"x 18"
	S1324B24FA – 13"x 24"x 24"
	S1730B12FA – 17"x 30"x 12"
	S1730B18FA – 17"x 30"x 18"
	S1730B24FA – 17"x 30"x 24"
	S2436B18FA – 24"x 36"x 18"
	S2436B24FA – 24"x 36"x 24"
	S2436B36FA – 24"x 36"x 36"
	S3048B18FA – 30"x 48"x 18"
	S3048B24FA – 30"x 48"x 24"
	S3048B36FA – 30"x 48"x 36"
	S3660B24FA - 36"x 60"x 24"
	S3660B36FA – 36"x 60"x 36"

- Notes:** (1) Not for use in areas subject to vehicular traffic, unless otherwise noted.
- (2) Consult the manufacturer for ordering procedures for handhole depth and lid/cover locking devices and load bearing capacity.
- (3) Rated for use in areas subject to vehicular traffic
- (4) Light vehicular traffic only (H10)
- (5) Lugs kits available from TDB
- (6) Only the 3642-2436P cover is RUS accepted for use with this handhole.

2.5
07-17-2008
se

se - Buried Plant Housings
(Complies with 7 CFR 1755.910)

Note: (1) PON users must follow the cable manufacturer's recommended use and practices when installing fiber optic cables in optic enclosures.
(2) For vegetation and brush fire control RUS accepts the use of U-TECK's WeedEnder® products

Type BD Pedestals

(Listed manufacturers are accepted to supply housing types as indicated by X's.)

<u>Manufacture</u>	<u>Series</u>	<u>Notes</u>	<u>Pedestal Mounted</u>					<u>Type H Pedestals</u>			
			<u>BD3</u>	<u>BD4</u>	<u>BD5</u>	<u>BD6¹⁸</u>	<u>BD7</u>	<u>BD3A</u>	<u>BD4A</u>	<u>BD5A</u>	<u>BD6A¹⁸</u>
Channell	MAH	15	X	X	X	-	X	-	-	-	-
Charles Industries, Ltd.	(Pedlock BD)	2, 3, 15	X	X	X	X	X	X	X	X	X
	(CP2 Series)	2, 3, 15	X	X	X	X	X	X	X	X	X
	CFDP	15, 19	X	X	X	X	X	X	X	X	X
	BDO	15, 19, 20	X	X	X	X	X	X	X	X	X
Emerson Network Power, Energy Systems	UPC, FLOODPLUG, ProFORM	1, 2, 3, 7, 10 1, 2, 3, 7, 10, 19, 27	X	X	X	-	x	X	X	X	-

See page 2.5.1.3 for notes.

se - Buried Plant Housings
(Complies with 7 CFR 1755.910)

Note: PON users must follow the cable manufacturer's recommended use and practices when installing fiber optic cables in fiber optic enclosures.

Type BD Pedestals

(Listed manufacturers are accepted to supply housing types as indicated by X's.)

Type M Pedestals

Manufacturer	Series	Notes	Pedestal Mounted				Pole Mounted				Pole Mounted (Increased Height, Above Ground)			
			BD14	BD15	BD16	BD17 ¹⁸	BD14A	BD15A	BD16A	BD17A ¹⁸	BD14AG	BD15AG	BD16AG	BD17AG ¹⁸
ADC	OmniReach (FAT) includes 8" non-metallic	19, 20, 23			X	X			X	X			X	X
Channel	MAH		X	X	X	-	-	-	-	-	-	-	-	-
Charles Industries, Ltd.	(Pedlock BD)	2, 3, 15	X	X	X	X	X	X	X	X	X	X	X	X
	(CP2 Series)	2, 3, 15	X	X	X	X	X	X	X	X	X	X	X	X
	CFDP	15, 19	X	X	X	X	X	X	X		X	X	X	X
	BDO	15, 19, 20	X	X	X	X	X	X	X	X	X	X	X	X
Corning Cable Systems	VPED	20	X	X	X	X	X	X	X	X	X	X	X	X
	OptiDrop	19, 21	X	X	X	X	X	X	X	X	X	X	X	X
Emerson Network Power, Energy Systems	FLOODPLUG	2, 3, 10												
	ProFORM	2, 3, 10, 19 27	X	X	X	-	X	X	X	-	X	X	X	-

Large Count Splice Cabinets

Note: PON users must follow the cable manufacturer's recommended use and practices when installing fiber optic cables in fiber optic enclosures.

			BD6000	BD8000	BD10000
Emerson Network Power, Energy Systems	(UPCBD)	(2)(3)(10)(14)	-	X	-
Charles Industries	(CMHP)	(28)	X	-	-

See page 2.5.1.3 for notes.

2.5.1.1.
07-17-2008
se

se - Buried Plant Housings
(Complies with 7 CFR 1755.910)

Note: PON users must follow the cable manufacturer's recommended use and practices when installing fiber optic cables in fiber optic enclosures.

Type BDS Serving Area Interface Cabinet⁽⁴⁾

<u>se - Buried Plant Housings</u> (Complies with 7 CFR 1755.910)		
Note: PON users must follow the cable manufacturer's recommended use and practices when installing fiber optic cables in fiber optic enclosures.		
<u>Manufacturer</u>	<u>Designation</u>	
	<u>Terminal Type</u> ⁽⁵⁾	<u>Cabinet Series</u>
ADC	SC UPC, LC APC	OmniReach ⁽¹⁹⁾
	LC UPC	FDH 3000 Series ^{(19) (25)}
ADC/FONS	SC/UPC	FDH I & II Series ^{(19) (22)}
Clearfield, Inc.	SC, SC APC, LC, LC APC	FSC ^{(19) (24)}
Corning Cable Systems	SC APC, SC UPC ⁽²⁹⁾	OptiTect ⁽¹⁹⁾ (Advantage & Premier)
ofs	SCA, LCA, MPO. SC, LC	Orbital 160 ^{(19) (26)}
	SCA, LCA, MPO. SC, LC	Orbital 288 ^{(19) (26)}
	SCA, LCA, MPO. SC, LC	Orbital 576 ^{(19) (26)}
3M	3M SS Block	4000 ⁽⁶⁾
		4300 ⁽⁶⁾
		4220 ^{(6) (17)}
		4230
		4900
Emerson Network Power Energy Systems	RLS Module	UPC/BDS
		RSK/RSL
		Starburst Aerial
		UltraCab
Tyco Electronics	HubSnap	NGXC ^{(12) (16)}
	Dat@Term	BK/BL ^{(11) (16)}
Tyco Electronics (Technical Acceptance expires on May 15, 2010.)	SC, APC	CSX-2 ⁽¹⁹⁾

Fiber Optic Splice Case Housings

Note: PON users must follow the cable manufacturer's recommended use and practices when installing fiber optic cables in fiber optic enclosures.

	<u>Stake Mounted</u>	<u>Pad Mounted</u>	<u>Pole Mounted</u>
Emerson Network Power, Energy Systems	OPFO-BD7PD (8)(9)	OPFO-BD7PD (8)(9)	OPFO-BD7PL (8)
Charles Industries (28)	CMHP	CMHP	

See page 2.5.1.3 for notes.

Notes:

- (1) Internal offset brackets for the BD3, BD4, and BD5 sizes are available upon request.
- (2) Grounding connectors for field mounting within the housings for terminating #6 AWG solid copper ground wire are available upon request.
- (3) Good housekeeping panels are available upon request, sizes BD3 and above. When ordering, suffix the catalog number with the letter "H".
- (4) SAI housings equipped with two doors, front and back are also available upon request.
- (5) Use the block or module recommended by the SAI manufacturer.
- (6) Only the 4065, 4295, and 4365 may be pole mounted.
- (7) BD7 may be pad mounted.
- (8) Order mounting hardware for the intended splice case in accordance with the manufacturer's Instructions.
- (9) Order pad or stake mounting hardware in accordance with the manufacturer's instructions.
- (10) For additional bonding and grounding requirements, extension brackets GBREXT, GBREXTKIT, and GBRALT are available upon request.
- (11) Pole Mounted Only.
- (12) Beige color may be used.
- (14) UPCBD8000 may be stake mounted.
- (15) These pedestals are type "M" pedestals (dome) that meet the functional criteria of type "H" pedestals.
- (16) If ordered stubbed, cables must be RUS accepted.
- (17) Includes 4220P Add-On-Cabinet.
- (18) Maximum straight splice pair capacity using single pair connectors or multiple pair modules is 900 pairs. Maximum load splice pair capacity using single pair connectors or multiple pair splice modules is 450 pairs.
- (19) Fiber optic housings
- (20) Copper & Fiber Optic cable In-One Housing
- (21) Acceptance includes OptiSheath Advantage Terminals
- (22) Acceptance includes FDH-144 I, FDH-216 I & II, FDH-288 II, FDH-432 I & II, FDH-576 I, FDH-864 I
- (23) Includes handhole option as a fiber optic cable slack organizer with the FAT mounted on top.
- (24) Acceptance includes flood proof design, the 96 with handhole configuration, and the 192, 288 (includes Fieldsmart version), 576 (includes Fieldsmart version), 864 Cross Connect.
- (25) Acceptance includes FD3-AE sizes, FD3-AG sizes, and FD3-AJ sizes
- (26) Order pad or pole mounting hardware in accordance with the manufacturer's instructions.
- (27) Includes NSFDP8 series, NSFDP8 series, NSFDP10 series, NSFDC8 series, NSFDC10 series, and NSFDP10V series.
- (28) Non-Fire retardant models are used at risk of the user. RUS recommends mitigating the risk with fire retardant mats or technology designed for fire retardation in an outside plant environment to comply with RUS.
- (29) The Splitter used inside the cabinet may now be installed into the Eclipse adapter/shelf of the Eclipse product in an indoor application.

2.5.3
01-05
sj

sj - Central Office Splice Housings⁽¹⁾

sj-a Splice Housings for Copper Cables

<u>Manufacturer</u>	<u>Designation</u>		
	<u>Catalog Number</u>	<u>Tip Cable Openings</u>	<u>Cable Capacity</u>
Emerson Network Power, Energy Systems	CRF54ARV	54	5400
	CRF66ARV	66	6600

sj-b Wall Mount Splice Housings for Fiber Optic Cables

	<u>Catalog Number</u>	<u>Mech. Splices</u>	<u>Fiber Capacity</u>	<u>Fusion Splices</u>
3M	8570	144		192
Fiber Optic Network Solutions (FONS)	WSU-72	72		72
	VSC-288	288		288
	ESC-432 ⁽⁴⁾	432		432
	ESC-864A ⁽⁴⁾	864		864

sj-c Rack Mount Splice Housings for Fiber Optic Cables

	<u>Catalog Number</u>	<u>Mech. Splices</u>	<u>Fiber Capacity</u>	<u>Fusion Splices</u>
ADC	FPL-SR2000	96		96
Fiber Optic Network Solutions (FONS)	HRC-5SU	72		72

See page 2.5.4.2 for notes.

sj - Central Office Splice Housings⁽¹⁾

sj-d Wall Mount Splice Housings with Patch Panels for Fiber Optic Cables⁽²⁾

<u>Manufacturer</u>	<u>Designation</u>	<u>Max. Fiber Terminations</u>
	<u>Catalog Number</u>	
ADC	FIP ⁽³⁾	12
	FIPL ⁽³⁾	24
Clearfield, Inc.	FLP-1W	24
3M	8432	12
	8434	24
	8436	48
Fiber Optic Network Solutions (FONS)	LX-1012	12
	TIC-12PS	12
	LX-1024	24
	WPS-24	24
	TIC-24PS	24
	STIC-24PS	24
	TIC8E ⁽³⁾	24
	LX-1048	48
	TIC18E	48
	TIC24E	72
LX-1096	96	
TIC31E	144	

See page 2.5.4.2 for notes.

2.5.4.1
01-31-2008
sj

sj - Central Office Splice Housings⁽¹⁾

sj-e Rack Mount Splice Housings with Patch Panels for Fiber Optic Cables⁽²⁾

<u>Manufacturer</u>	<u>Designation</u>	<u>Catalog Number</u>	<u>Max. Fiber Terminations</u>
3M		8423	48
		8425	144
ADC		FMPS	36
		FMPL	72
		NGF-MDF	up to 1728
		NGF-F3MDF	up to 1728
		NGF-SLM	up to 1728
		NGF-FTB	up to 1728
		NGF-FCB	up to 1728
Clearfield, Inc.		FLP-1	144
Fiber Optic Network Solutions (FONS)		LX-LP12B	12
		LX-LP ⁽⁵⁾	24
		HRC- ⁽⁶⁾	24
		LX-LP36N	36
		LX-MP3U	48
		HRC-7PSF	48
		LX-MP72B	72
		HRC- ⁽⁷⁾	72
		HRC-9P	144
		HR-11 ⁽⁸⁾	216
Leviton		TSCSA-012	12
		RMS1U-002	24
		RMS2U-004	48
		ODF7I-092	1152

See page 2.5.4.2 for notes.

sj – Central Office Splice Housings⁽¹⁾

sj-f Wall or Rack Mount Splice Housings with Patch Panels for Fiber Optic Cables⁽²⁾

<u>Manufacturer</u>	<u>Designation</u>	<u>Max. Fiber Terminations</u>
	<u>Catalog Number</u>	
ADC	FCP-08 ⁽³⁾	8
	FCP-12 ⁽³⁾	12
	FDP	24
Fiber Optic Network Solutions (FONS)	MDC5	24
	MDC7	48
	MDC10	72
	MDC14	144
	MDC18	216
Porta Systems	CPS-12 ⁽³⁾	12
	CPS-24 ⁽³⁾	24
	FOCUS	48
	FOCUS	72

- Notes:**
- ⁽¹⁾Recommended for use only in central offices with restricted access to unauthorized personnel.
 - ⁽²⁾Consult the manufacturer for ordering procedures concerning splice capacity, connector options, pigtails, or jumpers and stub options.
 - ⁽³⁾UL listed and may also be used as a Fiber Optic Cable Building Entrance Terminal.
 - ⁽⁴⁾Does not include “Bullet Bond” Shield Bonding Connector.
 - ⁽⁵⁾Replace blank with 1UB or 24B.
 - ⁽⁶⁾Replace blank with 3.5PS or 5PS.
 - ⁽⁷⁾Replace blank with 7P or 7PS.
 - ⁽⁸⁾Replace blank with letter(s) P or PS.

sk - Pedestal Restricted Access Inserts⁽¹⁾

<u>Manufacturer</u>	<u>Catalog No.</u>	<u>Max. Splice Diameter</u>	<u>Maximum Splice Sizes</u>	
			<u>25xModules</u>	<u>Single Pair Connector</u>
3M	4604	64mm (2.5 in.)	100-Pair	50-Pair
	4606	99mm (3.9 in.)	300-Pair	100-Pair
	4608	135mm (5.3 in.)	600-Pair	300-Pair
	4634	57mm (2.25 in.)	100-Pair	50-Pair
	4635	102mm (4.0 in.)	300-Pair	100-Pair
	4636	137mm (5.4 in.)	600-Pair	300-Pair
	4636-XL	140mm (5.5 in.)	900-Pair	400-Pair
	4637-XL	191mm (7.5 in.)	1200-Pair	400-Pair
Tyco Electronics	PedCap-RE-2G	48mm (1.9 in.)	20-50-Pair	25-50-Pair
	PedCap-RE-3G	76mm (3.0 in.)	25-200-Pair	25-200-Pair
	PedCap-RE-4G	84mm (3.3 in.)	100-400-Pair	100-400-Pair
	PedCap-RE-6G	114mm (4.5 in.)	200-900-Pair	200-900-Pair
	GT-3 ⁽²⁾	66mm (2.6 in.)	25-100-Pair	25-100-Pair
	GT-4 ⁽²⁾	91mm (3.6 in.)	50-400-Pair	50-400-Pair
	GT-6 ⁽²⁾	109mm (4.3 in.)	100-900-Pair	100-900-Pair
Uraseal	SAP-IICPR3N	76mm (3.0 in.)	200-Pair	200-Pair
	SAP-IICPR4N	102mm (4.0 in.)	300-Pair	300-Pair
	SAP-IICPR5N	127mm (5.0 in.)	400-Pair	400-Pair

Notes: ⁽¹⁾Pedestal restricted inserts should not be filled. Splices that require filling should be placed in a splice case.

⁽²⁾Maximum splice sizes will vary with type of connector and/or gauge of cable used.

2.6
06-06
ps;sp

ps - Buried Plant Housing Sealer

<u>Manufacturer</u>	<u>Catalog Number</u>	
Courtaulds Aerospace	Semco PR-820-2	62 Cu. In.
	Semco PR-820-6	224 " "
	Semco PR-820-8	336 " "
	Semco PR-820-20	805 " "
	Semco PR-820	4200 " "
W. R. Grace	Polycel 100	
J.A.D.E., Ltd.	PIG 375 3 oz Volume	54 " "
	" 470 4 " "	84 " "
	" 650 6 " "	126 " "
	" 825 8 " "	171 " "
	" 1050 10 " "	324 " "
	" 1080 16 " "	540 " "
3M	4411 - A Bag	45 " "
	B Bag	95 " "
	C Bag	250 " "
	750 Gram Can	450 " "

sp - Duct Sealer

<u>Manufacturer</u>	<u>Catalog Number</u>	
Courtaulds Aerospace	Semco PR-821-2	27 Cu. In.
	Semco PR-821-6	75 " "
	Semco PR-821-8	110 " "
	Semco PR-821-20	317 " "
	Semco PR-821-1	3337 " "
3M	4416	
Tyco Electronics	TDUX ⁽¹⁾	-
Uruseal	Drain-N-Seal Pedestal Sealing Foam	

Notes:

⁽¹⁾Follow manufacturer's recommendation when ordering for appropriate duct sizes and/or maximum cable(s) outside diameters.

2.7
05-07
hm

hm - Precast Concrete Manholes⁽¹⁾

<u>Manufacturer</u>	<u>Base Size</u>	<u>Catalog Number</u>
Advance Concrete Products	12' x 5' x 6'-6"	A Manhole
	12' x 6' x 7'	A-1 "
	8' x 4' x 6'	SA "
	8' x 4' x 6'	SJ "
	12' x 6' x 7'	J3-1 "
	12' x 6' x 7'	High-Mount T Carrier
	12' x 6' x 9'-6"	Manhole
	4' x 4' x 6'-9"	Telephone Vault
Amcor Inc.	3.5' x 5' x 3'	UV 3.553-REA-H
	3.5' x 5' x 3'	UV 3.553-REA-L
	4' x 6' x 7'	UVMB467
	6' x 8' x 7'	UVMB687-PM
	6' x 12' x 7'	UVMB6127
Armorcast	48" x 48" x 48"	A6000514HTAPC ⁽⁴⁾
	36" X 60"	A6001833HTA Series
Brooks Products	4' x 4'	REA 300FPB42T
	4' x 8'	REA 4080FM72
	4'-6" x 8'-6"	REA 510FM78
	5' x 10'-6"	REA 650FM78
	5' x 12'	REA 6000FM78
	6' x 12'	REA 6000FM84
	6' x 12'	REA 6000DM84
Capitol Concrete Products, Inc.	4' x 8' x 3'	CCPMH 483
	4' x 8' x 6'	CCPMH 486
	4' x 8' x 7'	CCPMH 487
	4' x 8' x 8'	CCPMH 488
Elk River Concrete Products Company of Montana	5' x 5'-2"	EV 505.2-S
	5' x 5'-2"	EV 505.2-D
	5' x 9'-3"	EV 509.3-S
	5' x 9'-3"	EV 509.3-D
	5' x 13'-4"	EV 513.4-S
	5' x 13'-4"	EV 513.4-D
	4' x 6'	EV 406
	48" ROUND	EV 48-D
Foley-Brogdon	2' x 2'	Model 222
	3' x 3'	Model 333
	4'-2" x 4'-2"	Model 444
	6' x 6'	Model 6060
	4'-6" x 8'-6"	Model 8545
	5' x 10'-6"	Model 1050
	5' x 10'-6"	Model 1050S
	6' x 8'	Model 8060
	6' x 12'	Model 1260
	8' x 8'	Model 8080
	9' x 12'	Model 1290
	6' x 10'	Model 1060

See page 2.7.3 for notes.

hm - Precast Concrete Manholes⁽¹⁾

<u>Manufacturer</u>	<u>Base Size</u>	<u>Catalog Number</u>
Hartford Concrete Products ⁽²⁾	5' x 10'	REA 10-5 Series ⁽²⁾
	4' x 8'	REA 8-4 Series
	4' x 4'	REA 4-4-4
Hawaii Precast, Inc.	3' x 5'	3x5 ⁽³⁾
	4' x 6'-6"	4x6
	5' x 10'-6"	5x10
	6' x 12'	6x12
Jensen Pre-Cast Concrete Products Co.	3' x 5' x 3'	REA 3660-TA
	3' x 6' x 3'	REA 3672-TA
	4' x 4' x 4'	REA 4848
	4' x 6'-6" x 3'	REA 466-TA
	4'-6" x 8'-6" x 6'-6"	REA PTS-65
	5' x 10'-6" x 7'	REA 38-5706-U-7
	6' x 12' x 7'	REA 384-4046-1
	6' x variable x 9'	REA PTS-69
6' x variable x 9'	REA PTS-69-I	
LAR-KEN	4'8"x4'8"x4'8"	Series 350, Model LK
A.C. Miller Concrete Products Inc.	3' x 3'	REA-3x3
	4' x 4'	REA-4x4
	4' x 6'	REA-4x6
	4' x 7'-9"	REA-18
	4'-6" x 10'-6"	REA-20
	5' x 12'	REA-38Y
	6' x 12'	REA-38Y
	6' x 6'	REA-6x6
	6' x 8'	REA-6x8
	5' x 10'-6"	REA-5x10.6
	8' x 8'	REA-8x8
	10' x 10'	REA-10x10

See page 2.7.3 for notes.

2.7.2
01-05
hm

hm - Precast Concrete Manholes⁽¹⁾

<u>Manufacturer</u>	<u>Base Size</u>	<u>Catalog Number</u>
Northwest Pipe & Tank, Inc.	4'-10" x 4'-10" x 4' 7' x 5' x 7'	#8-C244 #8-C257 ⁽⁵⁾
Ornamental Poles, Inc.	6'-0" x 12'-0"	REA-Y
Pre Cast Concrete Company, Inc.	5'-10" x 10'-4" x 7'2"	Type AA
Pre-Cast Manufacturing Company	3'-6" x 6' 6' x 12' 5' x 10'	T-36656 T-6127 T-5107
R.C.P. Vaults (Division of Pacific International Pipe & Engineering, Inc.)	2'6" x 2'6" x 2' 2'3" x 5'2-1/2" x 2'6" 4'0" x 6'0" x 6'0" 5'0" x 9'0" x 7'2" 5'0" x 9'0" x 7'2" 5'8" x 11'2" x 7'5" 5'8" x 11'2" x 7'5" 6'0" x 12'0" x 7'0" 6'0" x 12'0" x 7'0" 7'0" x 12'0" x 7'6" 8'0" x 14'0"	76649 Handhole 25-TA Splicing Vault 466-TA 4484-TA 4484-TCA 5106-TA 5106-TCA 612-TA 612-TCA 712-CLS 814 (3)
Rotondo Precast	2' x 2' 3' x 3' 4' x 4' 4' x 6' 6' x 6' 6' x 8' 6' x 10' 6' x 12' 6' x 12' 6' x 12' 8' x 8'	RUS-22- RUS-33- RUS-44- RUS-46- RUS-66- RUS-68- RUS-610- RUS-612- -38Y RUS-6127- -OB RUS-6127- -SB RUS-88-
Southeast Precast Concrete Products Inc.	6' x 12' 4' x 8' 5' x 10' 4' x 4'	REA 127 REA 86 REA 510 REA 504

See page 2.7.3 for notes.

hm - Precast Concrete Manholes⁽¹⁾

<u>Manufacturer</u>	<u>Base Size</u>	<u>Catalog Number</u>	
Utility Concrete	3' x 4' x 4'	34 1/4	
	8' x 4' x 6'	84 1/4	
	22" x 22" x 36"	23 6/8	
	2' x 2' x 2'-10"	22 2/10	
	4' x 4' x 4'	44 1/4	
	4' x 4' x 6'	44 3/4	
	10' x 5' x 7'	105 1/4	
	12' x 6' x 7'	126 1/16	
	12' x 6' x 10'	126 3/16	
	12' x 6' x 12'	126 5/16	
	15' x 6' x 9'	156 1/4	
	15' x 6' x 12'-6"	156 2/4	
	Utility Precast Inc.	6' x 12'	A Series
		5' x 10'	B Series
4-1/2' x 8-1/2'		C Series	
Utility Vault	4' x 6'	466TA	
	4' x 4' x 4'	444-LA	
	4'- 2" x 4'-2"	504-LA	
	4'- 2" x 6'-6"	577-LA	
	5'-10" x 10'-10"	510Y	
	6'-10" x 12'-10"	38-612-Y	
	2'3" x 5'2-1/2" x 2'4"	25 TA	
	2'3" x 5'2-1/2" x 3'4"	253 TA	
	3'1" x 6'7" x 4'1-1/2"	264 TA	
	5' x 9' x 7'2"	4484-type	
	5'4" x 9'4" x 7'6"	4686-type	
	5'8" x 11'2" x 7'2"	5106-type	
	6'1" x 11'7" x 7'5"	38Y-type	
	8'8" x 10'8" x 8'6"	810 TA	
	7'10" x 12'11" x 8'7"	712 LA	
	8' x 14' x 6'6" through 12'	814-66 TA through 814-12 TA	
	8' x 18' x 6'6" through 12'	818-66 TA through 818-12 TA	
	3'8" x 5'8" x 4'9 1/2"	GTE35 Pullbox	
	3'8" x 5'8" x 4'9 1/2"	GTE Intercept Pullbox	
	4'10" x 6'10" x 7'6"	467-TA	

- Notes:**
- (1) Consult manufacturer for ordering procedure concerning depth of the hole (Headroom), type of manhole (A, J, L, T), and extension sections.
 - (2) Equipped with 27-inch frame and cover made by Dewery Brothers Foundry.
 - (3) This manhole comes with an option for a D and L Foundry A1381 cast iron cover with security bolts.
 - (4) This manhole comes with Alhambra Foundry Cover, drawing No. A-1133.
 - (5) This manhole can be 6 feet in height.

sd - Mobile Home Posts

<u>Manufacturer</u>	<u>Catalog Number</u>	
Charles Industries, Ltd.	3518 (Internally mounted protector)	3519 (Trailer mounted protector)
Corning Cable Systems	AMHP-1 (2)	-
Indiana Pressed Steel	THP-1E (1)	-
Emerson Network Power, Energy Systems	MHP (2)	-

Notes: (1)Limited to use in noncorrosive areas only.

(2) Adjustable to 3 feet, 3-1/2 feet, and 4 feet.

2.9
02-06
wt

wt - Pole Mounted Wire Terminals

Manufacturer

Catalog Number

wt-a Unprotected Filled Blocks

	<u>1-Pair</u>	<u>10-Pair</u>	<u>12-Pair</u>	<u>20-Pair</u>	<u>25-Pair</u>	<u>30-Pair</u>	<u>50-Pair</u>
Channell	--	--	--	--	BMT60925B7 Series	--	BMT650B7 Series
Emerson Network Power, Energy Systems	5533G	--	--	--	--	--	--
Thomas&Betts ⁽¹⁾	--	--	--	--	C-2516	--	C-2518
Tyco Electronics ⁽¹⁾ (D Terminator 2)	--	DT2-PMT	DT2-PMT	DT2-PMT	DT2-PMT	DT2-PMT	DT2-PMT

wt-b Protected Filled Blocks

	<u>1-Pair</u>	<u>10-Pair</u>	<u>12-Pair</u>	<u>20-Pair</u>	<u>25-Pair</u>	<u>30-Pair</u>	<u>50-Pair</u>
Thomas&Betts ⁽¹⁾⁽²⁾	--	--	--	--	C-2517	--	--
Tyco Electronics ⁽¹⁾ (D Terminator 2)	--	DT2-PMP	DT2-PMP	DT2-PMP	DT2-PMP	DT2-PMP	DT2-PMP

Note:

1. Order stub cable length in accordance with manufacturer's instructions.
2. These protected blocks use the Energy Network Power, Energy Systems Communications 1557 (R-800) cable-class "medium duty" arrester.
3. These protected blocks use the D Terminator 2 cable-class "heavy duty" arrester. Add details on Tyco types of protection i.e. – (1) Fail-Safe 265-600V 24 AWG protection for OSP applications and (2) Fail-Safe/Vent Safe 265-600V 24 AWG protection, which can be used for primary protection.

drk - Damage Repair Kits ⁽¹⁾

<u>Manufacturer</u>	<u>Type Designation</u>
3M	4561 Armorcast Sheath Repair Kit ⁽²⁾
Preformed Line Products	SERVISEAL Closure Series BLACK-JACK Closure Series
Telepak ⁽³⁾	Splice & Seal System
Thomas&Betts	Kold-N-Klose System
Uraseal	Shake N' Seal FOD-40

Notes:

⁽¹⁾Damage repair kits are for RUS new construction purposes only.

⁽²⁾The Structure Armorcast Material included in this kit can be purchased by itself as “4560 Armorcast Structure Material.”

⁽³⁾Applicable for both pressurized and non-pressurized cable repairs. Must specify repair application.

2.11
12-27-2007
oco

<u>oco - Fiber Cable Slack Organizer</u>		
<u>Manufacturer</u>		<u>Product Series</u>
Armorcast		A600XXX ⁽³⁾
Multilink Broadband		21__ ⁽¹⁾⁽²⁾ (Sno-Shoe)
TDI		6500-XX-X FTTP Piggyback®
Tunnel Mill		BPS182720 Cone
		U304824 ⁽⁴⁾
Tyco Electronics		Lightrax System

Notes:

⁽¹⁾Fill in blanks with available sizes - 10", 16", 21", 24".

⁽²⁾Available with ADSS Versions, staking kits, and extensions.

⁽³⁾Acceptance includes one piece with access panel or split covers for mounting outside plant housing enclosures.

⁽⁴⁾Accepted with the B365406-12 adapter/cover for mounting outside plant housing enclosure

	<u>Item Designation</u>	<u>Page</u>
Connectors, shield bonding.....	gh	3.1
Copper Cable and Wire Connectors	gh-a	3.1
Armored Fiber Optic Cable Connectors.....	gh-b	3.1
Connectors, splicing.....	cm.....	3.1.2
Harnesses, bonding connector	gs.....	3.3
• #6 AWG Stranded Harness Wires	gs-a	3.3
• #6 AWG Braid	gs-b	3.3
• #14 AWG Insulated Harness Wires	gs-a	3.3.1
• #6 AWG Insulated Harness Wires	gs-b	3.3.1
Harnesses, shield connector isolation	gt	3.3.2
Markers, cable.....	tm	3.2
Numerals, decal type	sm.....	3.5
Signs, warning.....	sm.....	3.5
Sleeves, filled plastic.....	sv.....	3.4

gh - Shield Bonding Connectors
(Complies with PE-33)

Manufacturer

Catalog Number

gh-a Copper Cable and Wire Connectors

Cable Connectors

Service Wire Connectors

Outside Cable Diameters

	<u>Less than 1.0 inch</u>	<u>1.0 to 1.5 inch</u>	<u>Greater than 1.5 inch</u>	
A.K. Stamping	400-366-332 ⁽²⁾ (8544 B Bond #1)	400-366-340 (8544 B Bond #2)	400-366-357 (8544 B Bond #3)	-
Electric Motion	EM2__ ⁽⁶⁾ BM ⁽⁷⁾ EM2__ ⁽⁶⁾ B1 ⁽⁸⁾	- EM2__ ⁽⁶⁾ B2 ⁽⁹⁾	- EM2__ ⁽⁶⁾ B3 ⁽¹⁰⁾	- EM-3956__(1)(3)
3M	4462SN	4462SN	4462SN	-
Preformed Line Products	-	-	-	8000733 ⁽¹⁾ (Servi-Bond)

gh-b Armored Fiber Optic Cable Connectors

Outside Cable Diameters

	<u>Less than 0.75 inch</u>	<u>Greater than 0.75 inch</u>
A.K. Stamping	400366332-MB (Mini B Bond)	-
Electric Motion	EM2__ ⁽⁶⁾ BM ⁽⁷⁾ EM2__ ⁽⁶⁾ B1 ⁽⁸⁾	EM2__ ⁽⁶⁾ B2 ⁽⁹⁾ EM2__ ⁽⁶⁾ B3 ⁽¹⁰⁾
3M	4460D ⁽⁴⁾ 4460DFO ⁽⁵⁾	4460D ⁽⁴⁾ 4460DFO ⁽⁵⁾

See page 3.1.1 for notes.

3.1.1
01-05
gh

- Notes:**
- (1) For use only at station protector.
 - (2) Not to be used on cables less than 0.50 inches in diameter.
 - (3) Replace blank with either the letters H, R, RO, RR, RW, or RLB to indicate the type of mounting bracket to be used with the protector of the Network Interface Device (NID)
 - (4) To be used with armored fiber optic cables using the central strength member design.
 - (5) To be used with armored fiber optic cables using the strength member embedded in the outer jacket design.
 - (6) Replace blank with the number 0 to indicate one (1) stud or the letter B to indicate two (2) studs.
 - (7) For use with cables having outdoor diameters less than 0.5 inch.
 - (8) For use with cables having outdoor diameters equal to and greater than 0.5 inch but less than 0.8 inch.
 - (9) For use with cables having outside diameters equal to and greater than 0.8 inch but less than 1.6 inches.
 - (10) For use with cables having outside diameters equal to and greater than 1.6 inches.

cm - Connectors

Manufacturer

Catalog Number

Splicing Connectors for Copper Conductors⁽²⁾

Splicing Connectors (1 Conductor)

	<u>Moisture Resistant</u>	<u>Nonmoisture Resistant⁽¹⁾</u>
3M Company	Scotchlok™ UR2 " UCC ⁽⁴⁾ " UY2 " UB2A " 211	-
Channell	Discrete IDC Connectors ⁽⁸⁾	Discrete IDC Connectors ⁽⁸⁾
Tyco Electronics	552678-2(3 wts) 1-552678-2 552795-2 552966-2 553017-2 (Half-Tap ts) 1-553017-2 555790-1 555791-1 552965-2	552795-4 1-552795-4 552966-4 555790-2 60945-4 60947-3

Splicing Connectors (1-Pair)

	<u>Moisture Resistant</u>	<u>Nonmoisture Resistant⁽¹⁾</u>
Thomas&Betts	709	--

Connector Modules (5-Pair)

	<u>Straight Splice</u>	<u>Bridge Splice</u>	<u>Half-Tap Splice</u>
3M Company ⁽⁵⁾ (22-26 AWG)	710-SC1-5	710-BC1-5	710-TC1-5

Connector Modules (10-Pair)

	<u>Straight Splice</u>	<u>Bridge Splice</u>	<u>Half-Tap Splice</u>
Tyco Electronics ⁽¹¹⁾	737865-2 1-737865-2 737867-2 1-737867-2		737865-2 1-737865-2 737867-2 1-737867-2

(Technical Acceptance expires in May 31, 2010.)

See page 3.1.4 for notes.

3.1.3
07-17-2008
cm

	Connector Modules (20-Pair)		
	<u>Straight Splice</u>	<u>Bridge Splice</u>	<u>Half-Tap Splice</u>
Tyco Electronics ⁽¹¹⁾	737861-2 1-737861-2 737863-2 1-737863-2		737861-2 1-737861-2 737863-2 1-737863-2

(Technical Acceptance expires in May 31, 2010.)

	Connector Modules (25-Pair)		
	<u>Straight Splice</u>	<u>Bridge Splice</u>	<u>Half-Tap Splice</u>
3M Company (22-26 AWG) (19-24 AWG)	710-SC1-25 710-SCL-25 4000-D/TR ⁽³⁾ 4000-DT/TR ⁽³⁾	710-BC1-25 710-BC1-25 4005-DPM/TR ⁽⁶⁾ -	710-TC1-25 710-TCL-25 4008-D/TR ⁽³⁾ -
(22-26 AWG)	4000-G/TR ⁽⁷⁾	4005-GMB/TR ⁽⁷⁾	4000-G/TR ⁽⁷⁾

Tyco Electronics ⁽¹¹⁾	737830-2 1-737830-2 737832-2 1-737832-2 737834-2 1-737834-2		737830-2 1-737830-2 737832-2 1-737832-2 737834-2 1-737834-2
----------------------------------	--	--	--

(Technical Acceptance expires in May 31, 2010.)

See page 3.1.4 for notes.

<u>cm – Connectors</u>			
<u>Manufacturer</u>	<u>Splicing Connectors for Optical Fibers</u>		
	<u>Passive</u>	<u>Tunable</u>	<u>Mass</u>
ADC	MST ⁽⁹⁾ (2/4 & 6/8 ports)		
3M Company	2529 Fibrlok II		
Tyco	RECORDsplice ⁽¹⁰⁾ (Non-Domestic Technical Acceptance expires on December 18, 2009)		

Notes:

1. Non-moisture resistant connectors are to be used only on plastic-insulated non-filled cables utilizing airtight splice enclosures and when moisture protection is provided by pressurization.
2. Connectors in strip form may be used. Always use tool recommended by the manufacturer.
3. Use 4075-S grease box in all applications except pressurized cables.
4. For clearing and capping only.
5. Not to be used on 19-gauge waterproof cable with solid polypropylene or high density polyethylene insulated conductors.
6. Use either 4077-A, 4077-B, 4077-C, or 4077-D grease box in all applications except pressurized cables.
7. Does not require the use of a grease box.
8. Includes 8A, 8A/1, 8B, 8C/1, 11A.
9. The OmniReach FTTX Solution Multipoint Service Terminal (MST) is a pre-connectorized outside plant hardened PON terminal that may be deployed as a stand alone aerial end user service pole/messenger terminal or in an enclosure for buried or underground end user service distribution.
10. Fiber Optic Mechanical Splice System includes RCAT equipment.
11. All listed Tyco Electronics modules may use the appropriate grease boxes (737823-1 and 737823-2).

tm - Cable Markers

Manufacturer

Catalog Number

Cable Route

Lite Industries, Inc.⁽⁵⁾

UIT-11414
UIT-11415
UIT-11416
UIT-11417
UIT-11418

Color-Coded Tags

Brady
Hickory Printing Group, Inc.
Tech Products
U.G. Products

B-871⁽²⁾
PC-2⁽³⁾
EL2(series)
100⁽¹⁾

Wrap Around

ACP International

DN-32
DN-33
DN-34
DN-35
DN-36

Multilink

MFM-12
MFM-15
MFM-20

Sleeves

ACP International

DH-1⁽⁴⁾
DH-6
DH-M⁽⁴⁾

Write-On

Brady
LEM
Panduit Corp.
Thomas & Betts Corp.

PWC-PK
PPCL-BW
PSCB
WM-BW3
WM-BW5

3.2.1
07-05
tm

- Notes:**
1. The catalog number is suffixed with the letter R, B, or W to indicate Red, Blue or White bands.
 2. The catalog number is suffixed with the letter B, G or Y to indicate Blue, Green or Yellow color coded tags.
 3. The catalog number is suffixed with the letter B, G, W or Y to indicate Blue, Green, White or Yellow color coded tags.
 4. Indicate Heat Shrink Sleeve length.
 5. An added "D" to the part number would indicate that (1) a Quick Disconnect comes with the Isolation Terminal in place of the barrel compression splice; and that (2) it includes rubber cold shrink to go over the Quick Disconnect
 6. When ordering specify by color and wording.

3.3
01-05
gs

qs - Bonding Connector Harnesses

Manufacturer

Catalog Number

qs-a - #6 AWG Stranded Harness Wires

Bonding in Aerial, Buried or Underground Splice Cases,
and Ready-Access Enclosures

	<u>Noninsulated</u>			<u>Insulated</u>		
	<u>10" Length</u>	<u>20" Length</u>	<u>22" Length</u>	<u>10" Length</u>	<u>20" Length</u>	<u>22" Length</u>
Electric Motion Company	EM8100-10B.10	EM8100-20B.10	EM8100-22B.10	EM8100-10.10	EM8100-20.10	EM8100-22.10
LSW	LSW 6-10	LSW 6-20	LSW 6-22	LSW 6-10C	LSW 6-20C	LSW 6-22C

Bonding in Buried Plant Housings

	<u>Noninsulated</u>			<u>Insulated</u>		
	<u>6" Length</u>	<u>11" Length</u>	<u>18" Length</u>	<u>6" Length</u>	<u>11" Length</u>	<u>18" Length</u>
Electric Motion Company	EM8100-6B.10	EM8100.11B.10	EM8100-18B.10	EM8100-6.10	EM8100.11.10	EM8100-18.10
LSW	LSW 6-06	LSW 6-11	LSW 6-18	LSW 6-06C	LSW 6-11C	LSW 6-18C

qs-b - #6 AWG Braid

Bonding in Aerial, Buried, or Underground Splice Cases,
Ready-Access Enclosures, and Buried Plant Housings

	<u>Noninsulated</u>	<u>Insulated</u>
A.K. Stamping	A1163	-
Electric Motion Company	EM-2050	EM-2051
Excelco	579203-25	-
3M	25T ⁽⁴⁾	25/4467 ⁽⁴⁾

See page 3.3.1 for notes.

gs - Bonding Connector Harnesses
(Stranded Type Wire)

Buried Service Wire (Bare Metal Shields Only)

Manufacturer

Catalog Number

gs-a - #14 AWG Insulated Harness Wires

Bonding at Station Protector (Network Interface Device)

	<u>7" Length</u>
Corning Cable Systems	GH-13 ⁽¹⁾
Electric Motion Company	EM1407TFFR ⁽¹⁾
Engineered Products Co.	EH-13 ⁽¹⁾
LSW	LSW-5 ⁽¹⁾
Preformed Line Products	8000739 ⁽²⁾

gs-b - #6 AWG Insulated Harness Wires

Bonding in Buried Plant Housings

	<u>15" Length</u>	<u>36" Length</u>
Electric Motion Company	EM3955-6L/8100-15 ⁽³⁾	EM3955-6L/8100-36 ⁽³⁾

- Notes:**
- (1)** Harnesses equipped with AMP's #329860 Termi-Foil^R connector at one end for attachment to the bare metal shield of the service wire.
 - (2)** Harnesses equipped with Preformed Line Products' 8000733 connector at one end for attachment to the bare metal shield of the service wire.
 - (3)** Harnesses equipped with Electric Motion's EM3955 connector at one end for attachment to the bare metal shield of the service wire.
 - (4)** When ordering, state 3-inch eyelets.

3.2
01-05
gt

gt - #6 AWG Shield Connector Isolation Harnesses⁽¹⁾⁽²⁾
(Strand Type Wire)

Buried Service Wire (Bare Metal Shields Only)

Manufacturer

Catalog Number

Buried Plant Housings Only

15" Length

36" Length

Electric Motion Co.

EM 3955-6S/8100-15 BARP⁽³⁾

EM 3955-6S/8100-36 BARP⁽³⁾

Notes:

⁽¹⁾Restricted for use only where location of buried service wire shields is required at dairy or hog farm facilities to help alleviate stray voltage effects.

⁽²⁾When these harness wires are used, a warning tag shall be placed on the buried service wire to alert the technician that a voltage difference may be present and that temporary bond strap shall be applied between the service wire shield and connector plate of the buried plant housing before performing any work in the buried plant housing. The temporary bond shall be removed after work is completed in the buried plant housing.

⁽³⁾Harnesses are equipped with Electric Motion's EM 3955-BARP shield isolation connector at one end for attachment to the bare metal shield of the service wire.

sv - Filled Plastic Sleeves

Manufacturer

Jameson (W. G. Pearson)

Catalog Number

Order by size and description

Note: Splicing connectors and plastic sleeves are to be used only on conductor sizes and types and splicing arrangements as recommended by the connector and sleeve manufacturers.

3.5
01-05
sm

sm - Buried Plant Warning Signs, Stakes and Decal Markings

Manufacturer

Catalog Number

sm-a Decal Type Warning Signs and Markings⁽¹⁾⁽²⁾

Non-Reflective

	<u>Warning Signs</u>	<u>Numerals & Letters</u>	<u>Symbols</u>
3M Company	X	X	-
ACP International	X	X	-
Michael J. Arnold & Co. ⁽¹¹⁾	X	X	X
W. H. Brady	X	X	-
Color Arts, Inc.	X	X	-
Emerson Network Power, Energy Systems	X	X	-
May Advertising Corp.	X	X	-
Tech Products	X	X	X
Vernon Company	X	-	-
Vulcan Signs	X	X	-

sm-b Decal Type Warning Signs and Markings⁽¹⁾⁽²⁾

Reflective

	<u>Warning Signs</u>	<u>Numerals & Letters</u>	<u>Symbols</u>
3M Company	-	No. 5000 ⁽⁵⁾ No. 5005 ⁽⁶⁾ No. 5025 ⁽⁶⁾	No. 5002
ACP International	CBC36RY CBC36RO	CBC36RY CBC36RO	-
Michael J. Arnold & Co. ⁽¹¹⁾	MJADWR	MJAD__ ⁽¹²⁾ R	MJADSR
W. H. Brady	-	5905 Series	-
William Frick & Co.	CAUT-BC/IND	REF1.5 ⁽⁵⁾⁽¹⁶⁾ OREF1.5 ⁽⁶⁾⁽¹⁶⁾ REF3T ⁽⁵⁾ OREF3T ⁽⁶⁾	
Vulcan Signs	UCM Series	UEC Series	-

See page 3.5.3 for notes.

sm - Buried Plant Warning Signs, Stakes and Decal Markings

<u>Manufacturer</u>	<u>Catalog Number</u>		
	<u>sm-c Signs and Stakes</u>		
	<u>Cable Splice</u>	<u>Cable Route</u>	<u>Warning</u>
ACP International ⁽³⁾	PD ⁽²⁾ , PDOC ⁽²⁾ ACP ⁽¹⁸⁾ -66, 72, 78 PV-4, 6, 12	PD ⁽²⁾ , PDOC ⁽²⁾ ACP ⁽¹⁸⁾ -66, 72, 78 PV-4, 6, 12	PD ⁽²⁾ , PDOC ⁽²⁾ ACP ⁽¹⁸⁾ -66, 72, 78 PV-4, 6, 12 ACP-BM-53 ⁽²⁾
Carsonite	-	-	Impactor
Decal Industries ⁽⁴⁾	-	-	FP__ ⁽⁷⁾ ._ ⁽⁸⁾ D__ ⁽⁹⁾
Emerson Network Power, Energy Systems ⁽³⁾	1SP41233	1SP41232	1SP4121
GreenLine ⁽⁴⁾	-	-	FLU1RD96016
J. Miller Industries, Inc. ⁽⁶⁾	-	-	JMI-375-096-OR-100
Lyle Signs Inc. ⁽³⁾⁽⁴⁾	UT-55	UT-54	UT-53
Maloney Technical Products ⁽⁶⁾	-	-	MRKR™
May Advertising Corp. ⁽³⁾⁽⁴⁾	BM55-MABCS 412	BM54-MACR 412	BM53-MABC 412
Michael J. Arnold & Co. ⁽³⁾⁽⁴⁾	MJABCSA -	MJA930615 ⁽¹³⁾ -	MJACBC MJA__ ⁽¹⁴⁾
Pro-Mark	PM-303	PM-303	PM-303
Quantum	-	-	QM-375
Repnet	REA/PSA-1	REA/PSA-2	REA/PSA-3
Rustproof Signs, Inc. ⁽³⁾	R-709 -	R-710 -	R-708 R-666
SArgent-SOwell ⁽³⁾	49PHV067	49PHV069	49PHV068
Vulcan Signs ⁽³⁾⁽⁴⁾	UCM-102	UCM-101	UCM-505
W. H. Brady	B-11 ⁽³⁾ - -	B-13 ⁽³⁾ - -	B-12 ⁽³⁾ BL1 BL2
William Frick & Co. ⁽⁴⁾	BC-SPLICE ⁽³⁾ DM3, DMTS3	CABLE-RT ⁽³⁾ DM3, DMTS3	BC-CAUTION ⁽³⁾ DM3, DMTS3

3.5.2
04-05
sm

sm - Buried Plant Warning Signs, Stakes and Decal Markings

Manufacturer

Catalog Number

sm-c Signs and Stakes

Mounting Stakes

ACP International	UC-8/GR ⁽²⁰⁾ UC-8/GLV ⁽²⁰⁾
Michael J. Arnold & Co.	UPC-8__ ⁽¹⁵⁾
W. H. Brady	96920
Carsonite	CUM-375
Decal Industries	FP__ (7)-__ (9)
William Frick & Co.	POST-8FT ⁽¹⁷⁾
FlexStake	302 303 304 305
GreenLine	FLU1-96
Emerson Network Power, Energy Systems	UP4120__ ⁽¹⁰⁾
J. Miller Industries, Inc.	JMI-375-096-OR
Rustproof Signs, Inc.	RP-208N
Vulcan Signs	82GR

See page 3.5.3 for notes.

- Notes:**
- (1) All decals should be applied using manufacturers recommended materials and practices.
 - (2) Order by size and description.
 - (3) Stake not included.
 - (4) Signs may be ordered with black lettering on orange background.
 - (5) Available only in black lettering on yellow background.
 - (6) Available only in black lettering on orange background.
 - (7) Blank denotes color of marker. Replace blank with W for White, O for Orange, or G for Green.
 - (8) Blank denotes number and color of decals. Replace blank with 1Y for 1 yellow decal, 2Y for 2 yellow decals, 1O for 1 orange decal, or 2O for 2 orange decals.
 - (9) Blank denotes length of marker in inches. Replace blank with 60, 66, 72, or 78.
 - (10) Blank denotes length of stake in inches. Replace blank with either 72 or 96.
 - (11) Decals may be ordered with black lettering on orange background.
 - (12) Replace blank with "N" for numerals and "L" for letters.
 - (13) Add letter "A" to catalog number to obtain sign with arrows. The six-digit number is the manufactured date and identifies the purchaser.
 - (14) Replace blank with "TF" for tri-fold and "QF" for quad-fold.
 - (15) Replace blank with "G" for green painted and "GAL" for galvanized.
 - (16) When ordering specify either 1 decal or 4 decals per sheet.
 - (17) When ordering specify either 2 pound or 1.12 pound post.
 - (18) When ordering specify 1 or 2 decals and wording.
 - (19) When ordering specify by color and wording.
 - (20) Replace "UC" with "DL" for 1.12 pound and replace "8" with desired length in ft. (6.5, 10, etc.)

	<u>Item Designation</u>	<u>Page</u>
Arresters, gas tube.....	nh.....	4.4
" secondary power	gi	4.5
Blocks, terminal, for use in pedestals	sh	4.6
Building entrance terminal (BET) – Protected	ni	4.1
Network interface devices.....	nid	4.7
Power Back-up.....	pb	4.8
Protectors, mainframe.....	nm.....	4.2
" power service	gg.....	4.3

ni – Building Entrance Terminal (BET) - Protected⁽¹⁾⁽²⁾

ni-a Fuseless, Well Mount, Carbon

<u>Manufacturer</u>	<u>Pair Count</u>	
	<u>25-Pair</u>	<u>50-Pair</u>
Emerson Network Power, Energy systems	2BT25PMH/1304S 25P4X4MH/1304S ⁽²⁾	2BT50PMH/1304S 50P4X4MH/1304S ⁽²⁾

ni-b Fuseless, Module, Carbon

<u>Manufacturer</u>	<u>Pair Count</u>		
	<u>25-Pair</u>	<u>50-Pair</u>	<u>100-Pair</u>
3M ⁽³⁾	4188-25 ⁽⁴⁾ /3AB 4 <u>(5)</u> 88 <u>(6)</u> -25/3AB 4990 <u>(7)</u> -25/3AB	4188-50 ⁽⁴⁾ /3AB 4 <u>(5)</u> 88 <u>(6)</u> -50/3AB 4990 <u>(7)</u> -50/3AB	4188-100 ⁽⁴⁾ /3AB 4 <u>(5)</u> 88 <u>(6)</u> -100/3AB 4990 <u>(7)</u> -100/3AB
Emerson Network Power, Energy Systems	--	--	R134C/3AB

Notes:

1. Designations after the slash “/” mark indicate the arrester unit which RUS has accepted for use in the listed protected building entrance terminal (BET). Unless otherwise noted, no other arrester unit is RUS accepted for use in protected building entrance terminals listed here.
2. Restricted to inside mounting.
3. The arrester module accepted for these protected building entrance terminals is the 3AB carbon arrester module manufactured by Emerson Network Power, Energy Systems.
4. Must be supplied with 4188C-25, 50, or 100 protector covers, as appropriate to protected building entrance terminal size provided.
5. Blank space replaced with 2, 4, 5, 6, or 7.
6. Blank space replaced with F or R.
7. Blank space or blank space replaced with 2, 3, 4, 5, or 6.

ni – Building Entrance Terminal (BET) - Protected⁽¹⁾ (7)

ni-c Fuseless, Well Mount, Gas Tube

<u>Manufacturer</u>	<u>25-Pair</u>	<u>50-Pair</u>
Emerson Network Power, Energy Systems	2BT25VSRMH/1304VSR2 ⁽²⁾ (5) 25VSR4X4MH/1304VSR2 ⁽²⁾ (5)(7)	2BT50VSRMH/1304VSR2 ⁽²⁾ (5) 50VSR4X4MH/1304VSR2 ⁽²⁾ (5)(7)

ni-d Fuseless, Module, Gas Tube

<u>Manufacturer</u>	<u>Pair Count</u>						
	<u>6 Pair</u>	<u>12 Pair</u>	<u>25 Pair</u>	<u>50 Pair</u>	<u>100 Pair</u>	<u>300 Pair</u>	
AT&T Network Systems			189-25/3B1ER ⁽²⁾ (5)	189-50/3B1ER ⁽²⁾ (5)	189-100/3B1ER ⁽²⁾ (5)		
Corning Cable Systems			C-552/7X ⁽²⁾ (5)	C-550/7X ⁽²⁾ (5)	C-551/7X ⁽²⁾ (5)		
3M ⁽¹⁰⁾			4188-25 ⁽¹¹⁾ /6U2VS ⁽²⁾ (5) 4188-25 ⁽¹¹⁾ /3GUVS ⁽³⁾ (4) 4__ ⁽⁸⁾ 88__ ⁽⁹⁾ -25/6U2VS ⁽²⁾ (5) 4__ ⁽⁸⁾ 88__ ⁽⁹⁾ -25/3GUVS ⁽³⁾ (4) 4__ ⁽¹²⁾ 88__ ⁽¹³⁾ -25/6U2VS ⁽²⁾ (5) 4__ ⁽¹²⁾ 88__ ⁽¹³⁾ -25/3GUVS ⁽³⁾ (4)	4188-50 ⁽¹¹⁾ /6U2VS ⁽²⁾ (5) 4188-50 ⁽¹¹⁾ /3GUVS ⁽³⁾ (4) 4__ ⁽⁸⁾ 88__ ⁽⁹⁾ -50/6U2VS ⁽²⁾ (5) 4__ ⁽⁸⁾ 88__ ⁽⁹⁾ -50/3GUVS ⁽³⁾ (4) 4__ ⁽¹²⁾ 88__ ⁽¹³⁾ -50/6U2VS ⁽²⁾ (5) 4__ ⁽¹²⁾ 88__ ⁽¹³⁾ -50/3GUVS ⁽³⁾ (4)	4188-100 ⁽¹¹⁾ /6U2VS ⁽²⁾ (5) 4188-100 ⁽¹¹⁾ /3GUVS ⁽³⁾ (4) 4__ ⁽⁸⁾ 88__ ⁽⁹⁾ -100/6U2VS ⁽²⁾ (5) 4__ ⁽⁸⁾ 88__ ⁽⁹⁾ -100/3GUVS ⁽³⁾ (4) 4__ ⁽¹²⁾ 88__ ⁽¹³⁾ -100/6U2VS ⁽²⁾ (5) 4__ ⁽¹²⁾ 88__ ⁽¹³⁾ -100/3GUVS ⁽³⁾ (4)		
Emerson Network Power Energy Systems			BEP__ ⁽¹⁴⁾ 25__ ⁽¹⁵⁾ /__ ⁽¹⁹⁾ BEPB25__ ⁽¹⁷⁾ /__ ⁽¹⁹⁾ BEP__ ⁽¹⁸⁾ 25SC__ ⁽¹⁶⁾ /__ ⁽¹⁹⁾	BEP__ ⁽¹⁴⁾ 50__ ⁽¹⁵⁾ /__ ⁽¹⁹⁾ BEPB50__ ⁽¹⁷⁾ /__ ⁽¹⁹⁾ BEP__ ⁽¹⁸⁾ 50SC__ ⁽¹⁶⁾ /__ ⁽¹⁹⁾	R134C/6U2VS ⁽²⁾ (5) R134C/3GUVS ⁽³⁾ (4) BEP__ ⁽¹⁴⁾ 100__ ⁽¹⁵⁾ /__ ⁽¹⁹⁾ BEPB100__ ⁽¹⁷⁾ /__ ⁽¹⁹⁾ BEP__ ⁽¹⁸⁾ 100SC__ ⁽¹⁶⁾ /__ ⁽¹⁹⁾		

See page 4.1.3 for notes.

ni – Building Entrance Terminal (BET) - Protected^{(1) (7)}

ni-d Fuseless, Module, Gas Tube (Cont'd)

<u>Manufacturer</u>	Pair Count					
	<u>6 Pair</u>	<u>12 Pair</u>	<u>25 Pair</u>	<u>50 Pair</u>	<u>100 Pair</u>	<u>300 Pair</u>
CIRCA Enterprises ⁽²⁰⁾	1880110US	2612QC/QC	1880ECA1	1880ECA1	1880ECA1	RMPXL300BE
	2606QC/QC		1890ECS1	1890ECS1	1890ECS1	
			1890ECT1	1890ECT1	1890ECT1	
			1890ECT1/NSC	1890ECT1/NSC		
			2625QC/QC		4486	
Surge Technologies ⁽³⁾⁽⁵⁾		ST260 66-12/ST3B1	ST260 66-25/ST3B1E	ST188 ENA1-50/ST3B1E	ST188 B1-100/ST3B1E	
			ST260 110-25/ST3B1E	ST188 110-50/ST3B1E	ST188 ENA1-100/ST3B1E	
				ST189 B1-50/ST3B1E	ST188 110-100/ST3B1E	
				ST190 A1-50/ST3B1E	ST189 B1-100/ST3B1E	
				ST250 66-50/ST3B1E	ST190 A1-100/ST3B1E	
					ST250 66-100/ST3B1E	
TII ⁽³⁾ (Non-Domestic Technical Acceptance expires on <u>10/26/08.</u>)			515 25/355M ⁽⁶⁾			
			516 25/356M1 ⁽⁵⁾			

See page 4.1.3 for notes.

Notes:

1. Designations after the slash "/" mark indicate the arrester unit which RUS has accepted for use in the listed protected building entrance terminal (BET). Unless otherwise noted, no other arrester unit is RUS accepted for use in protected building entrance terminals listed here.
2. 2-electrode.
3. 3-electrode.
4. Medium duty.
5. Heavy duty.
6. Maximum duty.
7. Restricted to inside mounting.
8. Blank space replaced with 2, 4, 5, or 6.
9. Blank space replaced with F or R.
10. The arrester modules accepted for these 3M protected building entrance terminals are manufactured by Emerson Network Power, Energy Systems.
11. Must be supplied with 4188C-25, 50, or 100 protector covers, as appropriate to protected building entrance terminal size provided.
12. Blank space replaced with 8 or 9. Also accepted for outdoor mounting.
13. Blank space or blank space replaced with B.
14. Replace the blank space with C, G, or CG.
15. Replace the blank space with C, MM, CF, or FS.
16. Replace the blank space with 6, 12, or 25 feet.
17. Replace the blank space with MM, CF, or FS.
18. Replace the blank space with C or CG.
19. Replace the blank space with 3GUVS⁽³⁾(⁴) or 6U2VS⁽²⁾(⁵).
20. CIRCA arrester units were technically accepted: C3B1E, C4B1E, C3B1S-BAL, C4B1S-BAL, and C4B3S-75

4.2
11-05
nm

nm - Mainframe Protectors⁽¹⁾⁽⁷⁾

<u>Manufacturer</u>	<u>Carbon</u>			
	<u>10 Pair</u>	<u>50 Pair</u>	<u>100 Pair</u>	<u>300 Pair</u>
Emerson Network Power Energy Systems	713/3AB		R399/3AB	
Porta Systems			508PF/35BCN	

<u>Manufacturer</u>	<u>Gas Tube</u>			
	<u>10 Pair</u>	<u>50 Pair</u>	<u>100 Pair</u>	<u>300 Pair</u>
AT&T Network Systems			310/3B1ER ⁽²⁾⁽⁵⁾	
CIRCA Enterprises ⁽¹⁰⁾			4486	RMPXL300BET
Corning Cable Systems			C-388/7A ⁽²⁾⁽⁵⁾	
Emerson Network Power Energy Systems	R713/6A20 ⁽²⁾⁽⁵⁾ R713/3G ⁽³⁾⁽⁴⁾		R399/6A20 ⁽²⁾⁽⁵⁾ R399/3G ⁽³⁾⁽⁴⁾	
Porta Systems			508PF/65BCN ⁽²⁾⁽⁵⁾	

<u>Manufacturer</u>	<u>Solid-State</u> ⁽⁸⁾			
	<u>10 Pair</u>	<u>50 Pair</u>	<u>100 Pair</u>	<u>300 Pair</u>
Corning Cable Systems			⁽⁹⁾ /11A	
CIRCA Enterprises			2500QC2-100/ CT3B1FS 2500QC2-100/ CT3B1S 4486 ⁽¹⁰⁾	RMPXL300BET ⁽¹⁰⁾
Emerson Network Power Energy Systems			R399/S3AB	

Notes:

1. Not to be used at subscribers' premises.
2. 2-electrode.
3. 3-electrode.
4. Medium duty.
5. Heavy duty.
6. Maximum duty.

7. Designations after the slash "/" mark indicates the arrester unit which RUS has accepted for use in the listed protector. Unless otherwise noted, no other arrester unit is RUS accepted for use in protectors listed here.
8. PEG-7, Class I Category.
9. For use with Corning's C-388 mainframe protector.
10. CIRCA arrester units for were technically accepted. These arrester units include: C3B1E, C4B1E, C3B1S-BAL, C4B1S-BAL, and C4B3S-75.

gg - Power Service Protectors

<u>Manufacturer</u>		<u>Catalog Number</u>
	Maximum Service Voltage:	125/250
Alset Corporation	Lightning Shield and Power Guard ⁽¹⁾	LS-200, LS-50, PG-200, PG-50
Atlantic Scientific	ZoneGuardian Plus	#42003
	" "	#43005
	" "	#43006
	ZoneGuardian Series	#35029
	" "	#35030
	" "	#35031
Corning Cable Systems		CP 211
EFI Corporation		DPI 153 DPI 453 Turbo ST EFI 153 EFI 453 Turbo ST
Northern Technologies		PLS-II 2000344 2000345 2000347
TII		410BM 411BM 412BM 422BM

(Non-Domestic Technical Acceptance expires on 10/26/08.)

See notes on page 4.3.1

4.3.1
03-21-2008
gg

gg - Power Service Protectors

Manufacturer

Catalog Number

Maximum Service Voltage: 125/250

Transtector

ACP100BL
CPS 150

Tripp Lite

ISOBLOK 2-0
ISOBAR 2-6
" 4-6
" 8-15

Notes:

1. Acceptance includes Remote Manger, RM-HTTP

nh – Arrester Units⁽¹⁾

<u>nh-a Gas Tubes</u>			
<u>Manufacturer</u>	<u>MDF Module</u>	<u>Station Module</u>	<u>Well Mount</u>
Bourns		125-EW-R ⁽²⁾⁽⁵⁾	
		2374-01 ⁽²⁾⁽⁵⁾	
		2375-01 ⁽²⁾⁽⁵⁾	
		2377-01 ⁽³⁾⁽⁵⁾	
		2377-45-HS/-BC ⁽³⁾⁽⁶⁾	
		2378-35-HS/-BC ⁽³⁾⁽⁵⁾	
Corning Cable Systems	7A ⁽²⁾⁽⁵⁾	7X ⁽²⁾⁽⁵⁾	
		PTD ⁽³⁾⁽⁵⁾	
		PTD ⁽³⁾⁽⁶⁾	
Emerson Network Power Energy Systems	6A20 ⁽²⁾⁽⁵⁾	6U2VS ⁽²⁾⁽⁵⁾	1304VSR ⁽²⁾⁽⁵⁾
	3G ⁽³⁾⁽⁴⁾	3GUVS ⁽³⁾⁽⁴⁾	
		G1200-0-350 ⁽²⁾⁽⁵⁾	
Porta Systems		65BCN ⁽²⁾⁽⁵⁾	
Surge Technologies	ST3B1E ⁽³⁾⁽⁵⁾	ST356-350V ⁽³⁾⁽⁵⁾	
TII (Non-Domestic Technical Acceptance expires on <u>October 26, 2008.</u>)		126M ⁽²⁾⁽⁵⁾	
		355M ⁽³⁾⁽⁶⁾	
		356M1 ⁽³⁾⁽⁵⁾	
		AD-02W-FS ⁽³⁾⁽⁵⁾	
Tyco		GSSP ⁽³⁾⁽⁵⁾	

See page 4.4.1 for notes

4.4.1
12-27-2007
nh

nh – Arrester Units⁽¹⁾

<u>nh-b Solid-State</u>		
<u>Manufacturer</u>	<u>MDF Module</u>	<u>Station Module</u>
Bourns		2380-27-01 ⁽⁷⁾
Circa Telecom	CT3B1FS ⁽⁷⁾⁽¹¹⁾	
	CT3B1S ⁽⁷⁾⁽¹¹⁾	
Corning Cable Systems	11A ⁽⁷⁾⁽⁹⁾	PTD ⁽⁷⁾⁽¹⁰⁾
Surge Technologies	ST3B1E-BAL ⁽⁸⁾	

Notes:

⁽¹⁾Arresters listed under this category are not complete protected building entrance terminals (BET) mainframe protectors, or network interface devices (NID). They are intended for use as components, as accepted and listed, in the protected BETs, mainframe protectors, and network interface device “ni”, “nm”, and “nid” sections of the List of Materials. Arrester units here shall not be used in a BET, mainframe protector or network interface device listed in the “ni”, “nm”, or “nid” sections unless the same arrester unit is listed for use in the particular BET, mainframe protector, or network interface device on the “ni”, “nm”, or “nid” pages.

⁽²⁾2-electrode.

⁽³⁾3-electrode.

⁽⁴⁾Medium duty.

⁽⁵⁾Heavy duty.

⁽⁶⁾Maximum duty.

⁽⁷⁾PEG-7, Class I Category.

⁽⁸⁾PEG-7, Class II Category.

⁽⁹⁾For use with Corning's C-388.

⁽¹⁰⁾For use with Corning's NI-2000 Series NID unit.

⁽¹¹⁾For use with Circa Telecom's 2500QC2-100.

4.5
01-05
gi

gi - Secondary Power Arresters

<u>Manufacturer</u>	<u>Signal and Power</u>		<u>Power Only</u>	
	Main Service Voltage:		125/250	
ACT Communications ⁽⁵⁾	-		452-120-XOX	
			452-240-XOX	
			453-120-XOX	
			453-240-XOX	
			453-277-XOX	
			453-480-XOX	
			454-120-XOX	
			454-240-XOX	
			455-120-XOX	
			455-240-XOX	
			455-277-XOX	
			455-480-XOX	
			472-120-X0X	
			472-240-X0X	
			473-120-X0X	
			473-277-X0X	
Advanced Protection Technologies	-		TE/100	TE/1000
			TE/200	TE/2000
			TE/300	TE/3000
			TE/600	TE/6000
Approved Lightning Protection Co.	-		SA-20	
Atlantic Scientific	ZoneSentinel Series		#12100	
	" "		#12101	
	" "		#12102	
	" "		#12103	
	ZoneMaster 75 Series		#11200	
	" "		#11201	
	" "		#11202	
	" "		#11203	
	ZoneMaster 140 Series		#17100	
	" "		#17101	
	" "		#17102	
	" "		#17103	
EFI Corporation	-		MBP120EFI-Y_	⁽⁴⁾
General Electric	-		9L15DCB002	

See page 5.5.2 for notes

gi - Secondary Power Arresters

Manufacturer

Catalog Number

Main Service Voltage: 125/250 (Cont'd)

Signal and Power

Power Only

Joslyn	-	1250-__ ⁽⁷⁾ 1260-__ ⁽⁸⁾ 1261-__ ⁽⁸⁾ 1265-__ ⁽⁹⁾ 1266-__ ⁽¹⁰⁾ 1450-85 1452-__ ⁽¹¹⁾ 1455-__ ⁽¹²⁾
Northern Technologies, Inc.	-	MMK-BX ⁽⁶⁾ -OA ⁽¹⁾ A DMK-BX ⁽⁶⁾ -__ ⁽²⁾ ⁽¹⁾ A

Other Service Voltages

Signal and Power

Power Only

AC Data Systems	-	Surge Blox
Advanced Protection Technologies	-	TE/400 TE/4000 TE/500 TE/5000
Atlantic Scientific	ZoneSentinel Series " " " " ZoneMaster 75 Series " " " " ZoneMaster 140 Series " " " "	#12104 #12105 #12106 #11204 #11205 #11206 #17104 #17105 #17106
Joslyn	-	1250-32-E 1263-21 1451-85 1456-__ ⁽¹³⁾
Northern Technologies, Inc.	-	MMK-__ ⁽³⁾ X ⁽⁶⁾ -OA ⁽¹⁾ A DMK-__ ⁽³⁾ X ⁽⁶⁾ -__ ⁽²⁾ ⁽¹⁾ A
Tesco	-	TES 1120Y
Transtector	-	ACP3000 CPS Series APEX Series MCP Series SLIM LINE 120V SLIM LINE 240V

See page 5.5.2 for notes.

4.5.2
01-05
gi

Notes:

- ⁽¹⁾Blank space replaced with S, A, B, or C.
- ⁽²⁾Blank space replaced with 10 or 20.
- ⁽³⁾Blank space replaced with C,D, E, G, H, or J.
- ⁽⁴⁾Blank space replaced with 1, 2, or 3.
- ⁽⁵⁾(X) denotes manufacturer's catalog number for optional lamps, alarming, and enclosures.
- ⁽⁶⁾X may be replaced by an E for external enclosure or an I for internal enclosure type.
- ⁽⁷⁾Blank space replaced with 32, 33, or 33-E.
- ⁽⁸⁾Blank space replaced with 21, 41, 45, or 85.
- ⁽⁹⁾Blank space replaced with 21, 41, 45, 85, 85-PM, or 85-PMT.
- ⁽¹⁰⁾Blank space replaced with 45 or 85.
- ⁽¹¹⁾Blank space replaced with 21, 41, 80, 85, or 85-PM.
- ⁽¹²⁾Blank space replaced with 21, 41, 45, 80, 85, or 85-PM.
- ⁽¹³⁾Blank space replaced with 41, 45, 80, 85, or 85-PM.

sh - Terminal Blocks for Use in Pedestals

Manufacturer

Catalog Number

sh-a Unprotected Filled IDC Terminal Blocks

	<u>1-Pair (w/leads)</u>	<u>2-Pair (w/leads)</u>	<u>5-Pair (w/leads)</u>	<u>6-Pair (w/leads)</u>	<u>10-Pair (w/leads)</u>	<u>12-Pair (w/leads)</u>	<u>15-Pair (w/leads)</u>	<u>25-Pair (w/leads)</u>	<u>50-Pair (w/leads)</u>
3M Company ⁽¹⁰⁾	--	--	1D5XXXXXXXXX	--	ID10XXXXXXXXXX	--	ID15XXXXXXXXXX	ID25XXXXXXXXXX	--
Channell	--	--	--	MRB/CMR06 Series	MRT/CMR10 Series	--	--	MRT2/CMR25 Series	--
Emerson Network Power, Energy Systems	--	-- RGIS2SLS ⁽⁴⁾	RPIS5A ⁽⁵⁾ RGIS5A ⁽⁶⁾	RPIS6A ⁽⁵⁾⁽⁸⁾ RGIS6A ⁽⁶⁾	RPIS10A ⁽⁵⁾⁽⁸⁾ RGIS10A ⁽⁶⁾⁽⁸⁾	RPIS12A ⁽⁵⁾⁽⁸⁾ RGIS12A ⁽⁶⁾⁽⁸⁾	-- --	RPIS25A ⁽⁵⁾⁽⁸⁾ RGIS25A ⁽⁶⁾⁽⁸⁾ RTIS25A ⁽⁷⁾⁽⁸⁾	-- --
Thomas&Betts	--	--	54866 ^(1,5,8,9) 2520 ^(1,5,8) 5460002 ⁽²⁾	54867 ^(1,5,8,9) 2521 ^(1,5,8) 5460102 ⁽²⁾	54868 ^(1,5,8,9) 2522 ^(1,5,8) 5460202 ⁽²⁾	54869 ^(1,5,8,9) 2523 ^(1,5,8) 5460302 ⁽²⁾	54070 ^(1,5,8,9) 2524 ^(1,5,8) 5460502 ⁽²⁾	54071 ^(1,5,8,9) 2525 ^(1,5,8) --	-- 2526 ^(1,5,8) --
Tyco Electronics (D Terminator 2)	--	--	PTB-5-AU-4 PTB-5-FS ⁽³⁾	PTB-6-FS-4 PTB-6-FS ⁽³⁾ PTB-6-FU-4	PTB-10-AU-4 PTB-10-FS ⁽³⁾ PTB-10-VT-4	PTB-12-AU-4 PTB-12-FS ⁽³⁾ PTB-12-FU-4 PTB-12-FU-6 PTB-12-VT-6	PTB-15-FS ⁽³⁾ PTB-15-FS-50 PTB-15-VT-4	PTB-25-AU-4 PTB-25-FS ⁽³⁾ PTB-25-FU-6 PTB-25-VT-4	PTB-50-AS-6 PTB-50-AS ⁽³⁾ PTB-5-FS ⁽³⁾

sh - Terminal Blocks for Use in Pedestals

Manufacturer

Catalog Number

sh-b Unprotected Filled Binding Post Terminal Blocks

	<u>1-Pair (w/leads)</u>	<u>2-Pair (w/leads)</u>	<u>5-Pair (w/leads)</u>	<u>6-Pair (w/leads)</u>	<u>10-Pair (w/leads)</u>	<u>12-Pair (w/leads)</u>	<u>15-Pair (w/leads)</u>	<u>25-Pair (w/leads)</u>	<u>50-Pair (w/leads)</u>
Emerson Network Power,	--	--	RPT5A4G ⁽¹⁾	--	RPT10A4G ⁽¹⁾	--	--	RPT25A4G ⁽¹⁾	--
Energy Systems	--	--	RGT5A4G ⁽²⁾	--	RGT10A4G ⁽²⁾	--	--	RGT25A4G ⁽²⁾	--

Notes:

1. E/W bottom exit pigtail stub.
2. E/W rear exit pigtail stub.
3. Stub cables accepted in 12 feet and 25 feet lengths using RUS accepted PE-39 or PE-89 cables. Order stub cable in accordance with manufacturer's instructions.
4. Can only be ordered stubless from the manufacturer.
5. E/W bottom exit pigtail stub available in 4, 12, or 25 foot lengths. Order pigtail stub in accordance with manufacturer's instructions.
6. E/W rear exit pigtail stub available in 4, 12, or 25 foot lengths. Order pigtail stub in accordance with manufacturer's instructions.
7. E/W top exit pigtail stub available in 4, 12, or 25 foot lengths. Order pigtail stub in accordance with manufacturer's instructions.
8. Can be ordered with a filled cable stub using RUS accepted PE-39 or PE-89 cables in 4, 12, or 25 foot lengths. Order stub cable in accordance with manufacturer's instructions.
9. Flat plane block for left and right side drop wire entrance.
10. Contact vendor for pedestal and aerial stub options.
- 11.

nid – Network Interface Devices⁽¹⁾

nid-a Gas Tube Protection

Manufacturer

Catalog Designation

Alcoa
(c/o Petro Comm)

SNI 4600/355M⁽³⁾⁽⁶⁾, 356M1⁽³⁾⁽⁵⁾, or 125-EW-R⁽²⁾⁽⁵⁾

Bourns Inc.

7004, 7090 & 7032 Series NIDs

Corning Cable Systems

NI-2000 Series/PTD⁽³⁾⁽⁵⁾ or PTD⁽³⁾⁽⁶⁾

TII

3600/355M⁽³⁾⁽⁶⁾, 356M1⁽³⁾⁽⁵⁾, 126M⁽²⁾⁽⁵⁾, or AD-02W-FS⁽³⁾⁽⁵⁾
3700/355M⁽³⁾⁽⁶⁾, 356M1⁽³⁾⁽⁵⁾, 126M⁽²⁾⁽⁵⁾, or AD-02W-FS⁽³⁾⁽⁵⁾
6300/355M⁽³⁾⁽⁶⁾, 356M1⁽³⁾⁽⁵⁾, 126M⁽²⁾⁽⁵⁾, or AD-02W-FS⁽³⁾⁽⁵⁾

(Non-Domestic Technical Acceptance expires on 10/26/08.)

Tyco

RAYNID 760 Series/GSSP⁽³⁾⁽⁵⁾
RAYNID 2900 Series/GSSP⁽³⁾⁽⁵⁾

4.7.1
12-27-2007
nid

nid-b Solid-State Protection⁽⁷⁾

Manufacturer

Corning Cable Systems

Catalog Designation

NI-2000 Series/PTD⁽⁸⁾

Notes:

⁽¹⁾Designations after the slash "/" mark indicate the arrester unit or units, which RUS has accepted for use in the listed network interface device. Unless otherwise noted, no other arrester unit or units is RUS accepted for use in network interface devices listed here.

⁽²⁾2-electrode.

⁽³⁾3-electrode.

⁽⁴⁾Medium duty.

⁽⁵⁾Heavy duty.

⁽⁶⁾Maximum duty.

⁽⁷⁾Recommended only for customer access installations of 12 pairs and greater. In addition, all pairs shall be terminated in the network interface device whether or not the pairs are in service.

⁽⁸⁾PEG-7, Class I Category.

4.8
10-19-2007
pb

pb – Power Back-up

pb – Power Back-up

Manufacturer

Product



ReliOn

Hydrogen Fuel Cell Systems⁽¹⁾

Notes:

1. Includes T1000 and T2000 (Users must receive ReliOn training on the National Fire Protection Association (NFPA) 853 (NFPA, 2003) and NFPA 55 (NFPA, 2005) codes that provide guidance for installation of stationary fuel cell power systems and safe storage, use and handling of compressed gases, respectively.)

	<u>Item Designation</u>	<u>Page</u>
Access equipment.....	ae.....	5.1
Electronic Network Elements	ene.....	5.5
Switching equipment, digital, stored program	pc.....	5.3
Transport equipment.....	te.....	5.2
Wireless networks	wn	5.4
Wireless networks licensed.....	wn-l.....	5.4
Wireless networks unlicensed.....	wn-u.....	5.4.1

a – FTTH Systems⁽²¹⁾	
Manufacturer	Product
Alcatel-Lucent	7340 FTTU System ⁽¹⁶⁾
	7342 ISAM FTTU System ⁽²⁸⁾
Allied Telesis	Multiservice Access Platform 7000 & 9000 Series ⁽¹⁵⁾
Alloptic	GigaForce ⁽²⁰⁾
Calix Networks, Inc	FTTH Systems ⁽¹²⁾
Foxcom	FTTx Series 8 ⁽²⁶⁾ (CATV and DBS RF Video Overlay)
Hitachi	AMN 1200 FTTP
	AMN 1220 FTTP
Occam Networks, Inc	FTTP Solution ⁽¹⁴⁾
PacketFront (Non-Domestic Technical Acceptance expires on April 30, 2009.)	BECS, SMT, HMT, SSP, ASR, and DRG ⁽²⁹⁾
Pannaway	Inteleflex 2.488 GPON FTTH Solution
ReadyLinks	RHINORing™ Product Family ⁽³⁴⁾
Telco Systems	Multi-Service Platform ⁽¹³⁾
Tellabs (Non-Domestic Technical Acceptance expires on September 30, 2009.)	1600 SFU ONT ⁽³⁰⁾
Wave7 Optics	Last Mile Link ⁽¹⁰⁾
	Trident7 OLT, Trident7 COLT, 800 ONT Series, and Trident7 Management Suite
	Trident7 200 ONT Series and Trident7 1300 ONT Series (Non-Domestic Technical Acceptance expires on July 15, 2010.)
See pages 5.1.3 and 5.1.4 for notes.	

5.1.1
07-17-2008
ae

<u>b – Multi Service Access</u>			
Manufacturer	Product	Copper	Fiber
Actelis Networks	MetaLIGHT Platform ⁽¹⁷⁾	Y	N
ADC	PG-FlexPlus ⁽¹¹⁾	Y	N
ADTRAN	Access Equipment ⁽⁷⁾	Y	Y
	TA 1100 (Non-Domestic Technical Acceptance expires on May 19, 2010.)		
Alcatel-Lucent	Litespan-2000	Y	Y
	7300 ASAM	Y	N
	7330 ISAM	Y	Y
	AnyMedia	Y	N
	SLC Series 5 ⁽³⁾	Y	N
	SLC-2000 Access System	Y	Y
Alcatel-Lucent (AG Communications)	SuperLine Access	Y	N
Allied Telesis	Multiservice Access Platform 7000 & 9000 Series ⁽¹⁵⁾	Y	Y
Calix	Calix C7	Y	Y
Carrier Access	Adit 600 Platform	Y	N
Charles Industries	Dualine Plus ⁽¹⁾	Y	N
	HVDL 3.1	Y	N
Ciena	CN1000	Y	Y
Conklin	C8000+4 MSSL	Y	N
	FASTmux ADSL Mini-DSLAM		
	Model 2000		
ECI Telecom Ltd.	Hi-FOCuS ^{TM(22)}	Y	N
FibroLAN	MetroStar Systems ⁽³⁶⁾	Y	Y
Fujitsu	FLASHWAVE 4010	N	Y
	FLASHWAVE 4100	N	Y
General Bandwidth	G6 Access & Media Gateway	Y	Y
GoDigital	XCel-4 ^a	Y	N
	XCel-8	Y	N
	XCel-12	Y	N
Hatteras Networks	HN 4000/400 Platforms ⁽²³⁾	Y	N
Lucent Technologies	AnyMedia	Y	N
	SLC Series 5 ⁽³⁾	Y	N
	SLC-2000 Access System	Y	Y
	SuperLine Access	Y	N
Motorola	Multi-Service Unified Access Platform ⁽¹⁸⁾	Y	Y
Occam	BLC 1100	Y	Y
	BLC 1200 System	Y	Y
	BLC 6000	Y	Y
See pages 5.1.3 and 5.1.4 for notes.			

<u>b – Multi Service Access</u>			
Manufacturer	Product	Copper	Fiber
Pannaway	Service Convergence Network (SCN™) ⁽¹⁹⁾	Y	Y
	Inteleflex	Y	N
Pedestal Networks	UBS 2424	Y	N
	UBS 2450	Y	N
Pulsecom	S-24DU ⁽⁴⁾	Y	Y
	PSC Series 5 ⁽²⁾	Y	Y
Siemens Information and Communication Networks	Accession Integrated Access Platform	Y	Y
Telco Systems	EdgeGate VOIP Multi-Service Gateway ⁽¹³⁾	N	Y
	Multi-Service Platform ⁽¹³⁾	N	Y
	Gemini Ethernet Remote ADSL2+ DSLAM ⁽²⁷⁾	Y	N
Tellabs (Non-Domestic Technical Acceptance Expires on September 30, 2009.)	Tellabs@1000 series	Y	Y
	Tellabs@1020 multi-service Access System	Y	Y
Tellabs (Non-Domestic Technical Acceptance Expires on October 31, 2009.)	Tellabs@1100 Multi- Service Access System ⁽³¹⁾	Y	Y
Widearea US (Strowger) Technical Acceptance Expires on December 31, 2009.)	AER800 ADSL Loop Extender Series ⁽²⁵⁾	Y	N
World Wide Packet (Non-Domestic Technical Acceptance Expires on February 2, 2008.)	LighteningEdge ⁽³²⁾	Y	Y
Zhone Technologies	AccessNode ⁽⁶⁾	Y	Y
	MALC ⁽⁹⁾	Y	Y
ZyXEL (Non-Domestic Technical Acceptance Expires on May 30, 2009.)	MSAP Products ⁽³³⁾		
See pages 5.1.3 and 5.1.4 for notes			

5.1.3
07-17-2008
ae

<u>c – BPL Systems</u>	
Manufacturer	Product
CURRENT TECHNOLOGIES	BPL Product Family ⁽³⁵⁾

Notes:

1. Includes the DDL125, DDL135, DDL201, DDL205, DDL210, DDL221, and DDL237 only.
2. Includes the RT 596, RT5 192, RT 384, RT 576, and PSC Series 5 Fiber Kit.
3. Includes the SLC-2000 Multi-Services Distant Terminal and DDM-2000 FiberReach Narrowband Shelf.
4. Includes the S-24DU HUB.
5. The GrandSLam 4200 DSLAM includes the ReachDSL DSLAM and the ADSL DSLAM.
6. Includes the AccessNode Express and UE9000.
7. Includes the Total Access (TA) 5006, TA 5000, TA 4303, TA 3050, TA 3000, TA 1500, TA 1200 DSLAM, TA 1000, TA 850, TA 750, MX3200 Series, MX3112, MX2820, MX2810, MX2800, MX400 Series, OPTI-6100, OPTI-3, and TRACER Series.
8. Includes Multiplexer Uplink Module, ADSL Access Multiplexer Module, SDSL Inverse Multiplexer Module, and T1 Access Multiplexer 1500.
9. Includes Raptor product line.
10. The Last Mile Link (LML) includes Last Mile Core (LMC), Last Mile Tap (LMT), Last Mile Mux (LMM), and Last Mile Gateway (LMG).
11. The PG-FlexPlus includes the COT, RT, Field Shelf, Edge RAM and Edge IAD.
12. This listing includes the FiberDrive OLT, Calix F5 OLT, Calix 400 Series ONTs, Calix 500 Series ONTs, and the 2.4 GPON Blade w/C700 ONTs.
13. This listing includes Models T5C-24F, T5C-24GT, T5-24G, T5C-24T, TC548T, GW-282, GW--282S, GW482S, and GW232..
14. This listing includes the ON2300 ONT Optical Network Terminal family, the 6300 OLT blades, and is supported by the Occam View Element Manager system over Occam's BLC 6000 platform.
15. This acceptance includes the 7101, 7102, 7400, 7700, 9100, 9400, 9700, and iMG 600 CPE.
16. The Alcatel Lucent 7340 FTTU System includes the 7340-H-ONT Home Optical Network Terminal, the 7340 P-OLT Packet Optical Line Terminal, the 7340 V-OLT Video Optical Line Terminal, and the 7340 AMS Access Management System.
17. This acceptance includes the 50, 100E, 150, 130, 1300 and 1500
18. Includes the following Quantum Bridge Communications' products: QB3000 OAS, QB5000 OAS (includes the Motorola ONT1000 Optical Network Terminal), QB622 IOT, and QB100 IOT; and the following Next Level Communications' products: BDT, BSAM, USAM, BNU, MDU, SSU, and N3 View-1 only; and the AXS2200.
19. Accepted the NMX-SS7, CCM, BAR-GE12, BAS-ADSL16R, BAS-ADSL32R, BAS-100BX24, BAS-ADSL48R, BAS-ADSL48R-SPL, BAS-POTS48R, RGN-ADSL, RGN 410 series, RGN 510 series, RGN 520 series, RGN 550 series, RGN 560 series, PBG-10/100TX, and RetroCAB (updated RSC/48 enclosure along with the BAS unit installed.)
20. Gigabit Ethernet Access Routers (GEAR) includes edgeGEAR, homeGEAR, bizGEAR, and mduGEAR.
21. FTTH Systems using IP signaling may not be able to complete loop back tests for leased line circuits, borrowers should consult the manufacturer for further details.

22. Acceptance is for Hi-FOCuS MiniRAM, MiniRAM Extension, Hi-FOCuS Micro, MiniSplitter, Remote Line Power (RLP) Feeder and Cabinet unit, Hi-FOCuS MiniCAB System, Hi-FOCuS MicroRAM 24V, Hi-FOCuS M41 & M82, Hi-FOCuS 16 Slot xDSL Splitter Shelf, and the OPS management systems.
23. This acceptance includes the HN 4000, HN-404 CP, HN-408-CP, HN-404 CO, HN-408-CO, HN-404 U, and HN-408-U.
24. Listed 1.2 GHz PON solution is expected to be changed out by late 11/2007, call RUS for details.
25. Includes the AER800-1P, AER800-2P, AER800-6P/8P-O, and the AER800-6P/8P-I only.
26. This listing includes 810 Series Transmitter, 82 Series EDFA, 800 Series FTTH HONU, SCD-4P54W, SWDT-2, and LMX-42.
27. Gemini Ethernet Remote ADSL2+ DSLAM
28. The Alcatel Lucent 7342 FTTU System includes the 7342 P-OLT, the 7342 H-ONT, 7342 Video Coupler (also referenced as WDM), and the 5526 AMS elements.
29. Includes ASR 4000 Series, ASR 4100 Series, ASR 4200 Series, ASR 4600 Series, ASR 4700 Series, DRG 200 Series, DRG 300 Series, DRG 500 Series, FTU, and CATV.
30. The following models are included in the series: 1600-610, 1600-610X, 1600-611, 1600-612, 1600-712, 1600-621, 1600-625, 1600-631, and 1600-641. The Tellabs 1000 requires a PON plug-in card and couple a set of common control cards functions as a BPON optical line terminal (OLT.)
31. Tellabs®1100 Multi-Service Access Platform (MSAP) is an IP-based solution that combines the Tellabs 1150 and 1134 common equipment, the Tellabs®1600 family of ONTs/MDUs, and the Tellabs® 1191/1090 Network Management System along with a host of 1150 ONUS and a Tellabs® 1100Voice Gateway to simultaneously support FTTC and FTTN with ADSL2+/VDSL2, and ITU-T G.984 GPON 2.4 applications.
32. Acceptance includes LE-38SFP, LE-42H, LE-46, LE-17, LE-46H, LE-307, LE-327, E-427, LE-310, LE-311, LE-311v, and LE-NS.
33. Includes IES5000 Series, IES5005 Series, 1E54248 IP DSLAM Series, VES4600 Series, P600 Series, P700 Series, and P800 Series.
34. Includes the Rhino ONT models, Rhino OSG models, Rhino GTO models, Rhino IPC models.
35. Includes Overhead Systems, URD Repeated Systems, URD Amplified Systems, MDU Systems, and miscellaneous equipment
36. Includes modules, S.CON, H.CON, F.CON, CTF, LTA, DLA, GTA, FALCON, ProxiMA, U.CON, GSM, FCxx, FETX, F.CON, mS.CON, CTF, GA10, and ATARA products.

22. Acceptance is for Hi-FOCuS MiniRAM, MiniRAM Extension, Hi-FOCuS Micro, MiniSplitter, Remote Line Power (RLP) Feeder and Cabinet unit, Hi-FOCuS MiniCAB System, Hi-FOCuS MicroRAM 24V, Hi-FOCuS M41 & M82, Hi-FOCuS 16 Slot xDSL Splitter Shelf, and the OPS management systems.
23. This acceptance includes the HN 4000, HN-404 CP, HN-408-CP, HN-404 CO, HN-408-CO, HN-404 U, and HN-408-U.
24. Listed 1.2 GHz PON solution is expected to be changed out by late 11/2007, call RUS for details.
25. Includes the AER800-1P, AER800-2P, AER800-6P/8P-O, and the AER800-6P/8P-I only.
26. This listing includes 810 Series Transmitter, 82 Series EDFA, 800 Series FTTH HONU, SCD-4P54W, SWDT-2, and LMX-42.
27. Gemini Ethernet Remote ADSL2+ DSLAM
28. The Alcatel Lucent 7342 FTTU System includes the 7342 P-OLT, the 7342 H-ONT, 7342 Video Coupler (also referenced as WDM), and the 5526 AMS elements.
29. Includes ASR 4000 Series, ASR 4100 Series, ASR 4200 Series, ASR 4600 Series, ASR 4700 Series, DRG 200 Series, DRG 300 Series, DRG 500 Series, FTU, and CATV.
30. The following models are included in the series: 1600-610, 1600-610X, 1600-611, 1600-612, 1600-712, 1600-621, 1600-625, 1600-631, and 1600-641. The Tellabs 1000 requires a PON plug-in card and couple a set of common control cards functions as a BPON optical line terminal (OLT.)
31. Tellabs®1100 Multi-Service Access Platform (MSAP) is an IP-based solution that combines the Tellabs 1150 and 1134 common equipment, the Tellabs®1600 family of ONTs/MDUs, and the Tellabs® 1191/1090 Network Management System along with a host of 1150 ONUS and a Tellabs® 1100Voice Gateway to simultaneously support FTTC, and FTTN with ADSL2+/VDSL2, and ITU-T G.984 GPON 2.4 applications.
32. Acceptance includes LE-38SFP, LE-42H, LE-46, LE-17, LE-46H, LE-307, LE-327, E-427, LE-310, LE-311, LE-311v, and LE-NS.
33. Includes IES5000 Series, IES5005 Series, 1E54248 IP DSLAM Series, VES4600 Series, P600 Series, P700 Series, and P800 Series.
34. Includes the Rhino ONT models, Rhino OSG models, Rhino GTO models, Rhino IPC models.
35. Includes Overhead Systems, URD Repeated Systems, URD Amplified Systems, MDU Systems, and miscellaneous equipment.

te - Transport Equipment		
Manufacturer	Product	Interface Rate
ADC	QFLC	6.312 Mb/s
	DS3/OC1 FLC	OC-1
Alcatel	1603 SMX	OC-3/12/48
	1677 SL	OC-3/12/48/192
BTI Photonic Systems, Inc.	Netstender ⁽¹⁵⁾	OC-3/12/48/192
Carrier Access	Access Navigator® ⁽¹⁴⁾	T1/DS1/DS3
Charles Industries	T1	
Ciena	MultiWave CoreStream	OC-12/48/192
	MetroDirector K2	OC-3/12/48/192
	ONLINE Metro Transport Platform ⁽⁷⁾	OC-3/12/48/192
	DN Multiservice Switching Platform ⁽¹¹⁾	OC-3/12/48
	ONLINE Edge Multiservice CWDM Platform	OC-3/12/48
Ciena (Non-Domestic Technical Acceptance expires on 03/31/09.)	CN 4200 FlexSelect (Includes CN 4200 RS and Release 5.0)	OC-3/12/48/192
Cisco Systems	Cisco ONS 15454	OC-3/12/48/192
Copper Mountain Networks, Inc	VantEdge 3000 ⁽¹⁰⁾	OC-3
ECI Telecom Ltd.	XDM Platform ⁽¹⁶⁾	OC-3/12/48/192
fSONA	SONAbeam™ ⁽¹³⁾ (M & S series)	OC-1/3/12
Fujitsu	FLASHWAVE® 4300	OC-3/12/48
	FLASHWAVE® 7120 Large Shelf	OC-3/12/48/192
	FLASHWAVE® 7120 Small Shelf	OC-3/12/48/192
Fujitsu (Non-Domestic Technical Acceptance expires on 04/30/10.)	FLASHWAVE® 4500	OC-48/192
Fujitsu (Non-Domestic Technical Acceptance expires on 04/30/10.)	FLASHWAVE® 7420	OC-3/48/192
See page 5.2.2 for notes.		

5.2.1
07-17-2008
te

te - Transport Equipment		
Manufacturer	Product	Interface Rate
FutureWei (Non-Domestic Technical Acceptance expires on 04/27/09.)	Optix Metro 1600	OC-48/192
Lucent Technologies	DDM-2000	OC-3/12
	Metropolis DMX	OC-3/12/48
	WaveStar TDM 2.5G/10G	OC-3/12/48/192
Haliplex (OEM – Bayly, Coastcom, Turin) (Non-Domestic Technical Acceptance expires on 06/15/10.)	HPX-1600 products (and corresponding OEM versions) ⁽¹⁷⁾	OC-3/12
Marconi	MAS	OC-3/12
	ASX 200 BX	OC-3/12
	ASX 1000	OC-3/12
	ASX 1200	OC-3/12/48
Movaz Networks, Inc	RAYexpress	OC-3/12/48/192
	RAYextender	OC-3/12/48/192
Meriton Networks	6400 OTP	OC-3/12/48/192
MRV Communications, Inc.	Fiber Drive® Product Family ⁽¹⁷⁾	OC-1, OC-3, OC-48, Gigabit Ethernet
Nortel Networks, Inc.	OC-3 Express ⁽¹⁾	OC-3
	OPTera 3500	OC-3/12/48/192
	OPTera Metro 5000 ⁽⁶⁾	OC-3/12/48/192
	OME 6500	OC-3/12/48/192
OpVista, Inc.	OpVista2000	OC-3/12/48/192
RBN (Non-Domestic Technical Acceptance expires on 05/27/08.)	GigaEdge 8200	OC-1/3/12/48, DVB-ASI; GigE, AFC FOXCVR
Redback	SmartEdge 800 Intelligent Terminal	OC-3/12/48
Siemens Information and Communication Networks	XpressPass ⁽²⁾	OC-3/12/48
Tellabs North America, Inc	Telliant 5000 ⁽⁵⁾	OC-3
See page 5.2.2 for notes.		

te - Transport Equipment		
Manufacturer	Product	Interface Rate
Turin Networks	Traverse ⁽⁴⁾	OC-3/12/48/192
Xtera Communications, Inc	CityStream 5000	OC-3/12/48
Zhone Technologies	VISTA	OC-3/12
	GigaMux (GM) 50	OC-3/12/48
	GigaMux (GM) 1600 ⁽⁸⁾	OC-3/12/48
	GigaMux (GM) 3200 ⁽⁹⁾	OC-3/12/48
	GM 6400	OC-3/12/48/192
See page 5.2.2 for notes.		

Notes:

01. Includes the CX (Compact Express).
02. Includes the 140, 140HD, 142 and 144.
03. The VLX2020 listing includes the VLX2020 Main Shelf, and the following tributary shelves: DS3/EC1, ETS2, OTS2, and VLX1010 WDM; and the VLX2006™ Multi-Service Access Platform.
04. Includes Traverse 600, 1600, 2000 and the TraverseEdge 100.
05. The Telliant 5000 can provide xDSL lines.
06. This listing includes Models 5100 and 5200.
07. This listing includes Models 7000, 9000 and 11000.
08. The LuxN GigaMux (GM) 1600 series includes the GM 1602 and GM 1608 DWDM/CWDM products.
09. The LuxN GigaMux (GM) 3200 series includes the GM 3217 and GM 3234 DWDM/CWDM products.
10. The VantEdge 3000 can provide T-1 circuits and xDSL lines.
11. This listing includes Models 7000, 7050, 7100, and 7200.
12. This listing includes PacketWave M, C, and E Series (E200, E510 and E520).
13. Accepted 155-M/S, 622-M/S, and 1250-M/S.
14. Includes the Access Navigator® GR-303 + Data Host, Wide Bank® 28 DS3 Multiplexer and Wide Bank® 28 STS-1 Multiplexer. Equipment may be used with the NetworkValet® Element Management System
15. Acceptance includes the 2060 and 1030 Optical Transmission Platforms.
16. Acceptance includes XDM 100, 200, 400, 500, 1000, and 2000 models.
17. Includes the Chassis and Management Modules, Plug-In Interface Modules, Media Converters, Repeaters, Optical Ethernet Services Demarcation, Ethernet Switches, Single-Fiber Links, Fiber Multiplexers, Application Specific Modules, CWDM Modules, and Console Server Modules. Fiber Drive products also provide Access Services for Ethernet, Ethernet and T1/E1 lines and other protocol services.

pc - Stored Program Digital Switching Equipment

pc-a- CLASS 5 Switches that meet BULLETIN 1753E-001 (Form 522)

<u>Manufacturer</u>	<u>Base</u>	<u>Accepted System Release</u> ⁽⁵⁾	<u>Acceptance Classification</u> ⁽¹⁾	<u>RST(s)</u>
AG Communications Systems	GTD-5EAX	1732	A	RSU
Lucent Technologies	5ESS-2000 ⁽⁶⁾	5E16.2	A	EAIU BZ-RS/EAIU RSM ORM TRM
Nortel Networks, Inc.	DMS-10 ⁽²⁾	602.20	A	RLCM (OPAC) RSC-S Star Remote Hub
Nortel Networks, Inc	DMS-100 ⁽³⁾	LEC00017	A	RLCM (OPAC) RSC-S RSC Star Remote Hub
Redcom Lab., Inc.	MDX	17.0	A	MDX-R
	MDX-I ⁽⁷⁾	6.1	A	MDX-IR
	HDX	1.0	A	HDX-R
Siemens Information and Communication Networks	DCO ⁽⁴⁾	24.0 O-N-E UP	A	RLS-450 RLS-1080 RLS-4000
Siemens Information and Communication Networks	EWSD ⁽⁸⁾	20.0	A	RCU RCU-160C RCU-800C
Taqua	7000 Class 5 Packet Switch	5.0	A	7000 Class 5 Packet Switch
Taqua	7000 EVS, Enhanced VoIP Switch ⁽¹¹⁾	5.0	A	7000 EVS, Enhanced VoIP Switch

See notes on page 5.3.2.

5.3.1
12-27-2007
pc

**pc-b- Softswitch Solutions with adjunct equipment
that meet BULLETIN 1753E-001 (Form 522)**

Accepted

<u>Manufacturer</u>	<u>Base</u>	<u>System Release</u> ⁽⁵⁾	<u>Acceptance Classification</u> ^{(1) (9)}	<u>RST(s)</u>
Lucent Technologies	Lucent Compact Switch	3.8	C	Lucent Compact Switch
MetaSwitch	VP3510	4.1	C	VP3510
	VP2510	4.1	C	VP2510
NewCross Technologies	CSS™ Service Manager (NXT4000)	R2.6.0.6	C	CSS™ Service Manager (NXT4000)
Nortel	CS1500	2.0	C	CS1500
Sonus Networks	GSX9000 ⁽¹²⁾	6,4	C	GSX9000 ⁽¹¹⁾

See notes on page 5.3.2.

Notes:

- (1) Acceptance Classification: C-Conditionally Accepted, A-Accepted.
- (2) The DMS-10 listing includes the one and two bay version and its application as an HSO, SSO or LCC.
- (3) The DMS-100 listing includes its application as a DMS-200 tandem office and the smaller version of the SuperNode configuration, the DMS-SuperNode SE.
- (4) DCO listing includes the DCO-SE one and two bay configurations and DCO RNS.
- (5) The listed software/firmware system release is the most recent system release that was reviewed by RUS and found to be fully compliant with all requirements of 7 CFR 1755.522, RUS General Specification for Digital, Stored Program Controlled Central Office Equipment (Form 522). Other system releases may also be acceptable. For information on specific releases, please contact the Chairman, Technical Standards Committee "A" (Telecommunications), Rural Utilities Service, Stop 1598, 1400 Independence Avenue, SW., Washington, D.C. 20250-1598.
- (6) The 5ESS-2000 digital exchange listing includes the compact digital exchange 5ESS-2000 (CDX) and the very compact digital exchange 5ESS-2000 (VCDX) in host and remote switching terminal configurations (DRM). The listing also includes the EAIU/BZ-RS Unit, also called the 5E-XC Remote Line Unit. When a VCDX is upgraded to a CDX or full sized 5ESS-2000, it can host the listed RSTs. Unless it is upgraded it can only host the EAIU. Emergency call processing using the BZ-RS is only offered for EAIU Units that are hosted from a full sized 5ESS-2000 or from a DRM. The BZ-RS cannot be used to provide emergency call processing on EAIU Units hosted from a CDX or from a VCDX. System Release 5E16.2 is designated 5E-XC Service Rich Software by Lucent.
- (7) The MDX-I listing is for a minimum system configuration of four shelves, each containing no more than 100 lines or 25 percent of the total equipped lines, whichever is less.
- (8) The EWSD listing includes the EWSD Small Exchange (EWSD-SX) and the Line Trunk Group-O (LTGO).
- (9) Systems used for line access for this switch must be included in the RUS *List of Materials Acceptable for Use on Telecommunications Systems of RUS Borrowers* in category ae – Access Equipment.
- (11) Consists of the Taqua T7000 Class 5 Packet Switch and VoIP Software application
- (12) This system includes PSX, SGX and EMS deployed on Sun Netra servers.

5.3.3
07-17-2008
pc

APPROVAL-TO-BID STATUS OF DIGITAL SWITCHING SYSTEMS

Digital central office switching systems, which have Agency acceptance, are listed by software generic. To bid generics which are not listed requires an approval-to-bid. Such an approval can be obtained up to five years prior to the general availability of the generic. An unlisted generic may not be delivered to an Agency funded site until it receives full acceptance.

Manufacturer	Model	Software Generic	Expiration Date ⁽¹⁾
AG Communications Systems	GTD-5EAX		
Lucent Technologies	5ESS-2000		
MetaSwitch	VP2510	6.1	07/31/2013
	VP2510		
Nortel Networks, Inc.	DMS-10		
	DMS-100		
Redcom Lab., Inc.	HDX	3.0	04/30/2013
	MDX	18.1	04/17/2008
	MDX-I	7.0	05/26/2011
Siemens Information & Communications Networks	DCO	25.0	02/01/2010
	EWSD	20E04	02/23/2009
Taqua	7000 Class 5 Packet Switch	6.0	11/30/2012
Taqua	7000 EVS, Enhanced VoIP Switch	6.0	11/30/2012

Notes:

1. Indicates the expiration date of the approval-to-bid.

5.4
07-17-2008
wn

wn – Wireless Networks		
wn-I - Licensed		
Manufacturer	Product	Technology
ADC	Digivance LRCS	800 & 1900 MHz
AirNet	GSM BSS ⁽¹⁾	GSM
AIRAYA Corp	WirelessGRID Bridge Series (AI108-4958-XX ⁽¹⁹⁾)	PTP, PTMP 4.940-4.990 GHz
Airspan Networks	ASWipLL 700 ⁽⁷⁾	Broadband
Alcatel-Lucent	CDMA/CDMA2000 Flexent® Network Solution ⁽²⁴⁾	CDMA
Alvarion	BreezeMAX 2300 TDD BreezeMAX 2500 TDD	Broadband
DragonWave, Inc.	AirPair 50 & 100 Wireless Ethernet Bridges	18 & 23 GHz
	Horizon Compact	6, 11, 18, 23, 24, and 28 GHz
Exalt Communications	4.9i EX-4.9r/EX-4.9r-c	PTP (4.9GHz)
iDirect Technologies ⁽¹⁴⁾	Hub & NetModem II Plus 3000 Series router	VSAT
interWAVE	GSM Network ⁽²⁾	GSM
IP Wireless (Nextwave) (Non-Domestic Technical Acceptance expires on 01/17/2010.)	V4 NodeB	TD-CDMA
	V5 NodeB	
	Integrated Network Controller (INC)	
	P1D modem	
	PCMCIA modem	
MDS	MDS LEDR700	746-794 MHz
	MDS LEDR900 932.5	960 MHz
Motorola	MotoMesh ⁽¹⁵⁾ (4.9 GHz)	MEA (public safety)
Navini Networks TM	Ripwave TM ⁽⁶⁾	Broadband
NextNet Wireless	Expedience® BWAS ⁽⁵⁾	Broadband
RAD Data Communications	AirMux 200 ⁽¹³⁾	PTP
SOMA Networks	SoftAir System ⁽¹²⁾	PTMP
UTStarcom ⁽²⁵⁾	MovingMedia®2000 Total Control® PDSN	GSM and CDMA Core ONLY solutions (MSC, PDSN, VAS components)
UTStarcom ⁽²⁵⁾ (Non-Domestic Technical Acceptance expires on 05/28/2010.)	MovingMedia®2000 Total Control® PDSN	CDMA Core plus Radio Access Network solutions (MSC plus Base Stations)
		Broadband
Vyyo	700 MHz System ⁽⁸⁾	Broadband
ZTE USA Inc. (Non-Domestic Technical Acceptance expires on 10/26/2008.)	CDMA 2000 1x EV/DO (Rev A)	CDMA
See pages 5.4.2 and 5.4.3 for notes.		

wn-u – Unlicensed		
Manufacturer	Product	Technology
ADTRAN	TRACER Series	Microwave 2.4 & 5.8 GHz
AIRAYA Corp	WirelessGRID Bridge Series (AI108-4958-XX ⁽¹⁹⁾)	PTP, PTMP 5.25-5.85 GHz
Airspan Networks ⁽⁷⁾	ASWipLL 900 ASWipLL 2.4 ASWipLL 5.8 AS3030 IP + TDM AS3030 IP	PTP, PTMP
	MicroMAX ⁽²³⁾	
Alvarion	BreezeACCESS ^{®(9)} BreezeNET ^{®(10)}	Broadband
DigitalPath [™]	DenseNode [™] & BroadNode [™]	PTP, PTMP 2.4, 5.3, 5.5 or 5.8GHz
Exalt Communications	EX-2.4i-16 EX-2.4i	PTP (2.4 GHz)
	EX-5i-16 EX-5i EX-5r/EX-5r-c	PTP (5.3, 5.7, 5.8 GHz)
Go Networks	Broadband Wireless Cellular- Mesh Wi-Fi Base Stations ⁽²²⁾	PTP, PTMP (2.4 & 5.8 GHz)
MDS	MDS iNET & iNEII	902-928 MHz
	MDS Series Five Transceivers	5.3 or 5.8GHz
Motorola	Canopy [™] Platform ⁽⁴⁾	Broadband
	MotoMesh ⁽¹⁵⁾ (2.4 GHz)	MEA (WiFi)
Navini Networks [™]	Ripwave ^{™(6)}	Broadband
Nortel Networks	Wireless Mesh Network ¹⁷	PTP, PTMP (2.4 & 5.8 GHz)
	BTS 1060 ⁽²³⁾	5.8 GHz, 2.4 GHz
Proxim	Tsunami MP.11 ⁽¹⁸⁾	PTP, PTMP (5 GHz)
RAD Data Communications	AirMux 200 ⁽¹³⁾	PTP
Redline Communications	AN30e and AN50e (Includes RedAccess)	PTP, PTMP (5.4 & 5.8 GHz)
Strix Systems	Access/One [®] OWS/IWS ⁽²¹⁾	Mesh, PTP, PTMP (IEEE 802.11a/b/g)
Trango ⁽²⁰⁾	Access5830 Atlas Series FOX5800 FOX5580 FOX5300	PTP, PTMP (5.8/5.3 & 2.4 GHz, 900 MHz)
WaveIP	GigAccess ⁽¹⁶⁾ (Includes OFDM units)	PTP, PTMP
WaveRider	LMS4000 900 MHz ⁽¹¹⁾	Broadband
See pages 5.4.2 and 5.4.3 for notes.		

5.4.2
01-31-2008
wn

Notes:

1. Includes AdaptaCell BTS 3000, AirSite BS, BSC 3000, TRAU, and AirNet OMC-R.
2. Includes WAVEXchange MSC, WAVETransit, WAVEXpress BSC and BTS, and NIB.
3. Accepted the 700 Broadband Wireless Internet (BWIN™) system based on the Data Over Cable System Interface Specification (DOCSIS). This system must be a complete system end-to-end system from base station to the cable modem.
4. Accepted the 900 MHz, 2.4, 5.2 and 5.7 GHz wireless systems based on the Canopy™ Platform. Acceptance includes Canopy Advantage and Canopy Lite Subscriber Module units, bundle packs, Demo & Starter Kits. Manufacturer's recommended shielded cables are acceptable for this platform's use only.
5. Accepted the 2.5 GHz and 3.5 GHz Broadband Wireless Access System (BWAS) based on the Expedience® Platform.
6. Accepted Wide Area Broadband Networks in unlicensed 2.4 GHz ISM band, or the licensed 2.3 GHz WCS, 2.5/2.6 GHz ITFS/MMDS bands.
7. Accepted 700 MHz, 900 MHz, 2.4GHz, 5.4 GHz, and 5.8 GHz with a network management platform (WipManage).
8. The system accepted consists of the following units: V3000, V700DT, V700BAM, V389D, V284, V280, V300, V313, V290UA, V7027PS, V700Y, and V700T.
9. Includes the BreezeACCESS II, BreezeACCESS 900, and BreezeACCESS VL. The BreezeACCESS VL is available in the 5.725-5.850, 5.47-5.725, 5.15-5.35, 5.03-5.091 bands, and includes the following customer premises equipment: SU-A -ff-3-1D-VL , SU- A-ff-6-1D-VL , SU- A-ff-6-BD-VL, and SU- A-ff-54-BD-VL. The BreezeACCESS 900 operates in the 902-928 MHz ISM band and includes the following CPU equipment: the SU-I-1D900, and SU-M5-900-8D units. The BreezeACCESS II operates in the ISM 2.400-2.4835 GHz band and includes the following CPU equipment: SU-A , SU-RA, SU-E, SU-RE, SU-A-1d-2.4, SU-A-BD-2.4, SU-A-1D1V-2.4, SU-A-BD1V-2.4, SU-E-1D-2.4, SU-E-BD-2.4, SE-1D1V-2.4, SU-E-BD-1V-2.4, SU-ID-1D -2.4, SU-ID-BD-2.4, SU-R, and SU-M5-2.4.
10. Includes the BreezeNET® B, BreezeNET® CX, and BreezeNET® SU-M. The BreezeNET® B operates in the 5.72-5.850, 5.47-5.75, and 5.1-5.35 GHz bands. The BreezeNET® CX operates in the 2.4-2.4835 ISM frequency band. BreezeNET® SU-M operates in the 2,400-2.4835 and 902-928 GHz bands.
11. Accepted CCU3000 base station, NCL1900 base station, EUM3005 indoor modem, EUM3006 outdoor modem, MMT9000 mobile terminal, and 902-928 MHz Bandpass Cavity Filters.
12. Includes NPM Platform, SOMAPort models, Voice Software Systems (AMOS), and frequencies: 700 MHz, PCS (1.9 GHz), WCS (2.3 GHz), MMDS (2.6 GHz), and 3.5 GHz.
13. Accepted 5.8 GHz (5.725–5.850 GHz), 5.4 GHz (5.470–5.725 GHz), 5.3 GHz (5.250–5.350GHz), 4.9 GHz (4.940–4.990 GHz), and 2.4 GHz (2.400–2.4835 GHz)

Notes:

14. Only manufacturer recommended third party vendors are acceptable for deployment of these listed materials.
15. Includes IAP7300, EWR7300, VMM6300, VMM7300, WMC6300, WMC7300, Mobile Switching Controller, and Mesh Manager EMS.
16. Includes GA 2.4 GHz, GA 900 MHz, GA OFDM 700 MHz, GA OFDM 900 MHz, GA OFDM 5.8 GHz, and Network Management System.
17. Includes the Wireless Gateway 7250, Wireless Bridge 7230, and the Wireless Access Points 7215 and 7220.
18. Includes the 5054-BSUR-LR-US, 5054-SUR-LR-US; 5054-SUA-LR-US, and the 5054-QB-LR-US.
19. XX identifies various models / configurations accepted.
20. Accepted M5830S-AP-60, M5830S-AP-EXT, M5580-FSU, M5800S-FSU, M5300S-FSU, M5830S-SU, M5830S-SU-EXT, M2400S-AP, M2400S-SU, M900S-AP, M900S-SU, M915S-SU-EXT, ATLAS5010-INT, ATLAS5010-EXT, TLINK-10, TLINK-10-EXT.
21. The equipment consists of several modules: Base, Client Connect, Network Connect, Antenna, and Network Server. The listing includes the Outdoor Wireless System 2400 Series (2400-10, 2400-20, and 2400-30), 3600 Series(3600-20 and 3600-30), OWS Network Servers (OWS-Ns8, OWS-NS24, and OWS-NS48), and EDGE Wireless System -100 (EWS-100), OWS accessories. The EWS is for indoor use.
22. The listing includes the MBW WLS 2000 (with the WLS 2100 Micro Cellular-Mesh Wi-Fi Sector Base Station,) MBW WLP 1000 (with the WLP 1100 Pico Cellular-Mesh Wi-Fi Base Station,) MBW WNC Wireless Network Controller (Base Station Controller,) MBW Wireless Media Gateway, power supply, antennas (ANT-4047S and 5810 X2,) and miscellaneous hardware.
23. Includes subscriber terminals EasyST and ProST. Products are not WiMAX certified, but are in queue with the WiMAX Forum as of 2007 (contact RUS for details).
24. Includes Mobile Switching Center (MSC), Modular Cell 4.0B (includes Compact version), CDMA2000® 1xEV-DO (up to Rev. A), CDMA450 Modcell 4.0 – Compact.
25. Includes: Sonata® MSC Server, Sonata® HLR, Sonata® IMG, Sonata® SSVR, Sonata® MRF, Sonata® Conference Server, Sonata® OMC, iCell® IP RAN Products (including Pico, Micro, and Macro products), All-IP Portable CDMA2000 Network, Total Control® PDSN Products (including TC200, TC3100, TC1000, TC800), Common Element Manager, and PCMS Voicemail platform

5.5
07-17-2008
ene

ene – Electronic Network Elements

Ene-a- Routers/Switches

<u>Manufacturer</u>	<u>Product</u>
Alcatel-Lucent	Omni Switch/Router(Layer 3 Switch) 7750 SR Service Router 7450 ESS
Aztek Networks	5000 Emergency Stand Alone Switch
ECI Telecom Ltd.	ST Series IP Service Edge Routers ⁽⁵⁾
Foundry Networks ⁽⁷⁾	BigIron® RX Series, FastIron® SuperX/SX and Edge Switches, NetIron®, & ServalIron®
MRV Communications	OptiSwitch® (OS) 9000 Platform ⁽⁶⁾
Redback	SmartEdge 400 & 800 Gateway/Router (With NetOp Policy Manager)
Riverstone Networks (Lucent)	Metro & Ethernet Edge Router Series ⁽¹⁾
Tellabs	8800 MSR Series ⁽⁸⁾

Ene-b- Headends

<u>Manufacturer</u>	<u>Product</u>
Minerva Networks	Video Concentrator (VC) 8000 Platform ⁽⁴⁾

See note on page 5.5.1.

Ene-c- Gateways/Controllers/Management Systems

<u>Manufacturer</u>	<u>Product</u>
Acme Packet	Net-Net 4250 Session Director Session Border Controller
Cedar Point Communications	SAFARI C3™ Media Switching
Ditech Networks	PeerPoint C100 SBC
Fine Point Networks	ServPoet BMS Series ⁽³⁾ (Broadband Management Server)
NexTone Communications	MSX and SBC Platforms
Redback	SMS-500 and 1800 (Subscriber Management System)
Versatel Networks	EdgeIQ Platform ⁽²⁾

Notes:

1. Includes the RS 1000/1100, RS 3000/3100/3200, RS 8000/8600, RS 38000, and Riverstone 15008, may use Management Center & Service Activator for these routers only.
2. Includes the IQ1500 and IQ4000 media gateways.
3. Includes the ServPoet BMS 200, 500, 800, & 1000.
4. Includes iTVMANAGER 2 middleware and RMS system.
5. Acceptance includes ST200, ST50, and the ShadeTree/LPS element manager.
6. Includes the OS9012C – 10Gx, OS9012 – M, OS9024 – 4C, OS9024FX – 4GC, and OS9024 – M.
7. Includes BigIron® RX (BI-RX-4, BI-RX-8, & BI-RX-16), FastIron® SuperX/SX Family of Switches (FESX424, FESX448, FESX424HF, FI-SX1 thru 4, FI-SX800, & FI-SX1600), NetIron® Routers and Switches (NI-4802 Router, NI-M2404 Metro Access Switches, NI-MLX Metro Switching Routers, & NI-XMR Core Router), ServerIron Application Switches (SI350(-Plus), SI450(-Plus), & SI850(-Plus)), ServerIron XL Application Switches (FCSLB16 & FCSLB24), ServerIron 4G Applications Switches (SI-4G), ServerIronGT C Series Switches (SI-GT-CGx2, SI-GT-C2404CF, SI-GT-CGC16, & SI-GT-C10Gx2P), & ServerIronGT E Series Switches (SI-GT-E-Gx2, SI-GT-E-GC16, SI-GT-E-2404CF, SI-GT-E-Gx4P, SI-GT-E-GC16P, SI-GT-E-2404CFP, & SI-GT-E-10Gx2.)
8. Includes the 8830, 8840, 8860 routers.

	<u>Item Designation</u>	<u>Page</u>
Anchor rods.....	X.....	6.1
Anchors, guy - expanding and plate	Z.....	6.2
" " - drive-type	Z.....	6.2
" " - swamp and rock.....	Z.....	6.2.1
Bolts, angle, thimble-eye.....	ba.....	6.13
" machine.....	c.....	6.13
" straight, thimble-eye.....	ao.....	6.13
Clamps, cable suspension	mz.....	6.15
" drop wire.....	mk.....	6.3
" ground rod and pipe (indoors).....	aj.....	6.4
" ground rod and pipe (outdoors).....	aj.....	6.4.1
" guy.....	u.....	6.14
Connectors, grounding.....	me.....	6.5
Guards, buried service.....	am.....	6.6
" cable, plastic.....	wg.....	6.8
" " split metal.....	sl.....	6.7
" riser.....	sg.....	6.8
Guy hooks.....	br.....	6.15
Guy lift plates	bk.....	6.15
Locknuts.....	ek.....	6.15
Numbers, pole.....	az.....	6.9
Nuts, regular, square.....	px.....	6.16
Rods, anchor.....	x.....	6.1
" ground.....	ai.....	6.10
Screws, lag.....	j.....	6.14
Strand, suspension and guy.....	y.....	6.11
Straps, reinforcement, suspension clamp.....	nb.....	6.16
Thimble-eye nuts.....	ab.....	6.14
Washers.....	d.....	6.14
Wires, cable lashing.....	nw.....	6.12
Miscellaneous items removed from the list.....		6.17

The manufacturers listed below have shown compliance with RUS requirements for the following anchor rods. Some manufacturers cannot supply all sizes listed. Check with manufacturer or distributor for availability.

x - Anchor Rods

<u>Types</u>	<u>Diameters</u>	<u>Lengths</u>
Single Guy	1/2"	7 ft.
Single and Double Guys	5/8"	7 & 8 ft.
Single and Double Guys	3/4"	8, 9, & 10 ft.
Single and Double Guys	1"	8, 9, & 10 ft.

Manufacturers

Eritech, Inc.
(Carolina Galvanizing Corp.)
A. B. Chance Company
Joslyn Manufacturing and Supply Company
Kortick Manufacturing Company
McGraw-Edison
Utilities Service Company

6.2
01-05
z

z - Anchors, Guy⁽¹⁾

Manufacturer

Catalog Number

Expanding and Plate Anchors

		6000	10,000	16,000
Holding Power - Lbs.:		90	120	200
Min. Required Area, Proj. Sq. In.:		5/8	3/4	1
Rod Diameter, Inches:		7	8	10
Rod Length, Feet:				
A. B. Chance	8 Way	-	88135G	1082G
Grip-Tite	8 Way	A322086-G	A322812-G	A322102-G
Joslyn	8 Way Plate	J8115G -	J8135G J7503G	J8200-1G -
McGraw-Edison	4 Way 6 Way Plate	DA1E5 - DA1P7	DA1E7 - DA1P9	- DA6E3 DA2P2
South Central	8 Way 4 Way	84115AG -	84135AG -	- 1042001G

Drive-Type

	6,000	10,000	16,000
Holding Power - Lbs.:	5/8	3/4	1
Rod Diameter - Inches:			
Foresight Products	MR-3	MR-2	MR-I MR-SR ⁽²⁾

Notes: ⁽¹⁾Where galvanized anchors are listed, the same anchors ungalvanized (black asphalt coated) are also acceptable.

⁽²⁾Swamp anchor.

z - Anchors, Guy

<u>Manufacturer</u>	<u>Catalog Number⁽¹⁾</u>			
	<u>Swamp Anchors</u>			
	<u>10" dia.</u>	<u>12" dia.</u>	<u>15" dia.</u>	
A. B. Chance	10150AS	132AS	152AS	
Foresight Products	-	MR-SR ⁽²⁾	-	
Joslyn	J2871SG	J2872SG	J2873SG	
	<u>Rock Anchors</u>			
	<u>Expanding Type</u>			<u>Split Wedge Type</u>
Anchor Size - Inches:	1-3/4	1-3/4	1-3/4	-
Rod Length - Inches:	15	30	53	18
Rod Diameter - Inches:	<u>3/4</u>	<u>3/4</u>	<u>3/4</u>	<u>1</u>
A. B. Chance	R315	R330	R353	-
Joslyn	J3436	J3437	J3438	-
Kortick	K5503	K5504	K5505	K2377
Utilities Service	CR315	CR330	CR353	-

Notes: ⁽¹⁾Where galvanized anchors are listed, the same anchors ungalvanized (black asphalt coated) are also acceptable.

⁽²⁾Drive type swamp anchor (see drive anchor category).

6.3
01-05
mk

mk - Drop Wire Clamps

Manufacturer

Catalog Number

Diamond Communications

23-44441
23-88881*

General Machine Products

7380-B

Reliable

2PRS*

*Suitable for use in corrosive areas.

aj - Ground Rod and Pipe Clamps

Station Installations (Indoors Only)

<u>Manufacturer</u>	<u>Catalog Number</u>		
This conductor:	.162" (#6 AWG) Copper	.102" (#10 AWG) Copper	.081" (#12 AWG) Copper
Connected to:	Pipe Ground (Copper or Steel) <u>5/8"-1-1/4" O.D.</u>	Pipe Ground (Copper or Steel) <u>5/8"-1-1/4" O.D.</u>	Pipe Ground (Copper or Steel) <u>5/8"-1-1/4" O.D.</u>
Electric Motion	EM5507 EM5517(3)	EM5507 EM5517(3)	EM5507 EM5517(3)
Reliable	13(1) --	13(1) 1(1)(2)	13(1) 1(1)(2)

- Notes:** (1)Smallest size pipe this clamp can be used on is 3/4".
 (2)Can only be used on copper pipe.
 (3)Can accommodate one #6 to #14 AWG and one #10 to #14 AWG copper conductor.

6.4.1
01-31-2008
aj

aj - Ground Rod and Pipe Clamps

Station Installations (Outdoors)

<u>Manufacturer</u>	<u>Catalog Number</u>			
	<u>.081" (#12 AWG), .102" (#10 AWG) and .162" (#6 AWG) Copper</u>			
Connected to:	<u>Ground Rod (Galvanized Steel)</u>		<u>Ground Rod (Copper-Covered Steel)</u>	
	<u>1/2"</u>	<u>5/8"</u>	<u>1/2"</u>	<u>5/8"</u>
H. L. Boggs	CR-1, M2009 ⁽¹⁾	CR-1, M2012 ⁽⁴⁾	CR-1, 2009 ⁽¹⁾	CR-1, M2012 ⁽⁴⁾
Burndy	GRC12 ⁽¹⁾	--	GRC12 ⁽¹⁾	--
Connector Castings ⁽¹⁾	--	--	G-4	G-5
Electric Motion	EM5507 EM5517 ⁽³⁾ EM1DB EM4DB ⁽¹⁾⁽⁸⁾	EM5507 EM5517 ⁽³⁾ EM2DB EM4DB ⁽¹⁾⁽⁸⁾	EM5507 EM5517 ⁽³⁾ EM1DB EM4DB ⁽¹⁾⁽⁸⁾	EM5507 EM5517 ⁽³⁾ EM2DB EM4DB ⁽¹⁾⁽⁸⁾
Erico, Inc	GR1-141G ⁽¹⁾⁽²⁾ GR1-141A ⁽¹⁾⁽²⁾ CP58	GR1-161G ⁽¹⁾⁽²⁾ GR1-161A ⁽¹⁾⁽²⁾ CP58	GR1-141G ⁽¹⁾⁽²⁾ GR1-141A ⁽¹⁾⁽²⁾ CP58	GR1-161G ⁽¹⁾⁽²⁾ GR1-161A ⁽¹⁾⁽²⁾ CP58 EHL58C1G ⁽⁴⁾
Galvan	G4P ⁽¹⁾	G5P ⁽¹⁾	G4 ⁽¹⁾	G5 ⁽¹⁾
Joslyn	--	--	J8491	J8492 ⁽⁴⁾
Penn-Union	CEB-1-TN ⁽⁴⁾	CEB-2-TN ⁽⁴⁾	CEB-1 ⁽⁴⁾	CEB-2 ⁽⁴⁾
Thomas & Betts	--	--	--	DGC58-66 ⁽⁴⁾
Tyco Electronics	1-83017-1 ⁽⁵⁾ 83017-5 ⁽⁴⁾ --	1-83017-3 ⁽⁵⁾ 83017-2 ⁽⁴⁾ --	1-81713-1 ⁽⁵⁾ 81713-5 ⁽⁴⁾ -- 81405-1	1-81713-3 ⁽⁶⁾ 1-81713-2 ⁽⁷⁾ 81713-1 ⁽⁴⁾ 81406-1

Notes:

- ⁽¹⁾Accepted only for use with 0.102" (#10 AWG) and 0.162" (#6 AWG) wire.
- ⁽²⁾Includes disposable mold.
- ⁽³⁾Can accommodate one #6 to #14 AWG and one #10 to #14 AWG copper conductor.
- ⁽⁴⁾Accepted only for use with .162" (#6 AWG) wire.
- ⁽⁵⁾Accepted only for use with 0.102" (#10 AWG) or 0.081" (#12 AWG) wire.
- ⁽⁶⁾Accepted only for use with 0.102" (#10 AWG) wire.
- ⁽⁷⁾Accepted only for use with 0.081" (#12 AWG) wire.
- ⁽⁸⁾Can be used on a ground that is already occupied by another ground rod clamp on top.

me - Grounding Connectors

<u>Manufacturer</u>	<u>Catalog Number</u>		
	<u>.162" (#6 AWG) Copper</u>	<u>.102" (#10 AWG) Copper</u> <u>.162" (# 6 AWG) Copper</u>	<u>.102" (#10 AWG) Copper</u>
<u>Connected to:</u>	<u>.162" (#6 AWG) Copper</u>	<u>.257" (#4 AWG)</u> <u>ACSR</u>	<u>.102" (#10 AWG) Copper</u>
Anderson Electric	C-6	--	C-10
Burndy	KS17	--	KS90
Dossert	DS2F	--	DS09F
Erico ⁽¹⁾	PGT-1G1G (Solid-to-Solid) PGT-1H1H (Stranded-to-Stranded) PGT-1H1G (Solid-to-Stranded)	-- --	PGT-1B1A (Stranded-to-Solid) PGT-1A1A (Solid-to-Solid)
Electric Motion	EM 2371	--	EM 2371
Fargo	GC-5006	--	GC-5008
Galvan	K-6	--	--
Joslyn	J3606	--	J3657F
Kearney	118102	--	118100
Penn-Union	S-6	SW-5	S-10
Tyco Electronics	81663-1 ⁽²⁾	--	--

⁽¹⁾Additional Erico CADWELD connectors are available for other combinations of ground wire.

⁽²⁾For use with two stranded #6 conductors only.

6.5.1
04-05
me

me - Grounding Connectors

(Compression Type)

Manufacturer

Catalog Number

.102" (#10 AWG) Copper
to
.109" (#12 BWG) (MPDW)

Burndy

YC8C8-ET

National Tel.

T2-109D

#6 Copper to
#4 & #6 Alum.

#6 Copper to
#2 & #4 Alum.

Burndy

KSA4

KSA2

Penn-Union

SW-5

SW-6

me - Grounding Connectors

<u>Manufacturer</u>	<u>Catalog Number</u>	
Connected to:	<u>.102" (#10 AWG) Copper</u> <u>.109" (#12 BWG) Steel (MPDW)</u>	<u>#10 AWG Copper</u> <u>.134" Steel (MPDW)</u>
Burndy	KSL-15	-
Dossert	DSN1F	-
Penn-Union	SW-1	SW-2

.102" (#10 AWG) Copper

Connected to galvanized steel strand:	<u>6M</u>	<u>10M</u>	<u>16M</u>
Aberdeen	AB 438	AB 438	AB 438
Burndy	-	KSU25	KSU26
Dossert	DSNS6F	DSNS10F	DSNS13F
Electric Motion	EM GC8010P EM GC8020P	EM GC8010P EM GC8020P	EM GC8010P EM GC8020P
Fargo	GC8010P	GC8020P	GC8020P
Joslyn	J-3030	J-3030	J-3030
MacLean Power	438ALC	438ALC	438ALC
Penn-Union	SW-6	SW-7	SW-8

.102" (#10 AWG) Copper

Connected to:	<u>Aluminum-Clad Steel Strand</u>		
	<u>6M</u>	<u>10M</u>	<u>16M</u>
Electric Motion	EM GC8010P EM GC8020P	EM GC8010P EM GC8020P	EM GC8010P EM GC8020P
Fargo	GA-620C	GA-620C	GA-620C
MacLean Power	438ALC	438ALC	438ALC
Penn-Union	PCA-010-H	PCA-010-H	PCA-010-H

For Buried Plant Housings (PE-91)

#6 AWG

Electric Motion	EM 0164(1) EM 2371T
Fargo	GC-164SHP(1) GC-5006SHP

(1)Connector will accept braid.

am - Buried Service House Riser Guards

<u>Manufacturer</u>	<u>Catalog Number</u>								
Type:	<u>Conduit</u>	<u>Conduit</u>	<u>Conduit</u>	<u>Conduit</u>	<u>Conduit</u>	<u>Conduit</u>	<u>Conduit</u>	<u>Conduit</u>	<u>Closed "U"</u>
Standard Length and Size:	<u>5' x 3/8"</u>	<u>5' x 1/2"</u>	<u>5' x 5/8"</u>	<u>5' x 7/8"</u>	<u>5' x .9"</u>	<u>5' x 1.13"</u>	<u>5' x 1.25"</u>	<u>20' x 1"</u>	<u>5' x 5/8"</u>
Charles Industries, Ltd.	--	--	12-119R	--	--	--	--	--	--
HMS Inc.	--	R-061	R-070	--	R-080	--	R-125	--	--
OSI Plastics Division of Ohio Steel Industries, Inc.	--	--	--	723181 723181 723198	--	723609 723567	--	--	--
Virginia Plastics	VP-38-5*	--	--	--	--	--	--	VP-1-EC	VP-B58*

*Staples will be required for mounting conduit. Double headed nails will be required for mounting Closed "U" type moulding. The mounting hardware shall be ordered separately from this manufacturer.

sl - Split Metal Cable Guards

Manufacturer

Catalog Number

10-Foot Straight Section

1" I.D.

3" I.D.

5-Foot Straight Section

1" I.D.

3" I.D.

5-Foot Curved Section

1" I.D.

3" I.D.

2-1/2-Foot Straight Section

1" I.D.

3" I.D.

2-1/2-Foot Curved Section

1" I.D.

3" I.D.

6.8
01-05
sg;wg

sg - Riser Guards (Pole)⁽¹⁾

Inside diameter, inches:	<u>1</u>	<u>2</u>	<u>3</u>
<u>Manufacturer</u>	<u>Catalog Number</u>		
Carlton Products	-	59011	59013
A. B. Chance	6531-1/2	6533	6535
Custom Plastics ⁽²⁾	CPU1	CPU2	CPU3
Electrical Materials Co.	51-2	52-2	53-2
Fargo	UP-843G*	UP-844G*	UP-845G*
Inwesco	54B01	54B03	54B04
Joslyn	J984	J987	J989
McGraw-Edison	DU7P4	DU7P6	DU7P8
Emerson Network Power, Energy Systems	UP125-8G*	UP225-8G*	UP325-8G*
Nordic Fiberglass	U-101 ⁽²⁾	-	-

*Numbers shown identify painted guards. Use of riser guard straps with these guards not needed.

⁽¹⁾Order by inside diameter and length.

⁽²⁾Mounting staples must be purchased separately.

wg - Plastic Cable Guards

<u>Manufacturer</u>	<u>Catalog Number</u>		
	<u>Longitudinally Split</u>		
Sizes, inches:	<u>1 x 8</u>	<u>1-1/2 x 8</u>	<u>2 x 8</u>
General Machine Products	7422-1	7422-1-1/2	7422-2

Spirally Cut

General Machine Products	Type P (Specify diameter and length)			
Preformed Line	Type PTG	"	"	"
Tyco Electronics	*Spirap	"	"	"

*Specify black outdoor polyethylene.

az - Numbers, Pole

<u>Manufacturer</u>	<u>Catalog Number</u>			
	<u>Metal</u>			
	<u>1"</u>	<u>1-1/2"</u>	<u>3"</u>	<u>6"</u>
Almetek ⁽¹⁾	X	-	X	X
Premax ⁽¹⁾	-	X	-	-
	<u>Plastic</u>			
3M Company	No. 5012 (Use 3M decals from 3M-b)			

Note: (1) Order by size and description.

6.10
02-06
ai

ai - Ground Rods
(without pigtails)

<u>Manufacturer</u>	<u>Catalog Number</u>			
	<u>1/2" x 5'</u>	<u>5/8" x 8'</u>	<u>5/8" x 10' Sectional</u>	<u>Sectional Coupling</u>
Apache	G125* GR125-R**	G588* GR588-R**	GRS5810-R	GRC58
A. B. Chance	8565*	8578*	8512*	8611*
Eritech, Inc. (Carolina Galvanizing/ Knight Metalcraft)	811350* 611353**	815880* 615883(1)**	835800* 635803**	GSC-58* CR58**
Galvan	GR5005* 5005G13	GR6258* 6258G13**	- 6260G13S**	60-C** 60-TC** GRC-58G* GRC-54G*
Joslyn	J5315*	J5328*	J23282.10* J9160-13**	J23282-A* J9182**
Kortick	-	K4658-F*	-	-
McGraw-Edison	-	DN5S8*	DN13S110*	DN1K2*
Utilities Service	-	5307*	-	-
Wilcor	-	WA8580G*	-	-

*Galvanized Steel

**Copper-Covered Steel

Notes:

(1) Pigtail version part no. 6158839 is accepted.

y - Suspension and Guy Strand

These manufacturers' strands shown by X's comply with
RUS 7 CFR Part 1755.370

Manufacturer

Catalog Number

Utilities grade, steel, seven wire

(For use as suspension or for guys)

	<u>5/16"(6M)</u>	<u>3/8"(10M)</u>	<u>7/16"(16M)</u>	<u>Class</u>
Bekaert Corporation	X	X	X	A,B,C
Cal-Wire Stranding	X	X	X	A,B,C
CF&I Steel Corporation	X	X	X	A
Davis Walker Corporation	X	X	X	A
Florida Wire and Cable	X	X	X	A,B,C
Indiana Steel & Wire	X	X	X	A,B,C
Mitchell Industries, Inc.	X	X	X	A,B,C
National Strand Products	X	X	X	A,B,C
Seal Wire	X	X	X	A

Extra High Strength Grade, steel, seven wire

(For use as suspension or for guys)

	<u>1/4"(6M)</u>	<u>5/16"(10M)</u>	<u>7/16"(16M)</u>	<u>Class</u>
Aceros Camesa	X	X	X	A,B,C
Bekaert Corporation	X	X	X	A,B,C
Cal-Wire Stranding	X	X	X	A,B,C
CF&I Steel Corporation	X	X	X	A
Davis Walker Corporation	X	X	-	A
Florida Wire and Cable	X	X	X	A,B,C
Indiana Steel & Wire	X	X	X	A,B,C
Mitchell Industries, Inc.	X	X	X	A,B,C
National Strand Products	X	X	X	A,B,C
Paulsen Wire Rope Corp.	X	-	-	A
Seal Wire	X	-	-	A
Wire Rope Corporation of America (WRCA)	X	X	X	A

6.12
09-28-07
nw

nw - Cable Lashing Wires

<u>Manufacturer</u>	<u>Catalog Number</u>					
	<u>Aluminum-Clad Steel</u>			<u>Type 430 Stainless Steel</u>		<u>Aluminum*</u>
Diameter, Inches:	.064	.045	.061	.045	.061	.080
Coil Length, Feet:	<u>600</u>	<u>1200</u>	<u>650</u>	<u>1200</u>	<u>650</u>	<u>375</u>
Aberdeen	-	-	-	45AC	61AC	-
Cable Spinning Equipment Company	-	-	-	13A	11A	16A
Central Wire	-	-	-	S4300004500LWA	S4300006100LWA	-
Century Wire	-	-	-	SS43ACW	-	-
ECS Metals Limited	-	-	-	X	X	-
General Machine Products	-	-	-	7153A	-	-
Greening Donald Co., Ltd.	-	-	-	80608	80363	-
Industrial Alloys, Inc.	-	-	-	072-430-045-S	072-430-061-S	-
Loos & Company	-	-	-	045SA430LP	061SA430LP	-
Maryland Specialty Wire, Inc.	-	-	-	958-45M	958-61M	-
National Standard	-	-	-	03811	18815	-
Senior Industries	-	-	-	SI-9603	SI-9606	-
ZAPP, Inc.	-	-	-	2355	2356	-

*This type of wire only, is to be used with aluminum-clad steel strand in seacoast areas.

Manufacturer

Catalog Number

c - Bolts, machine

	<u>5/8"</u>	<u>3/4"</u>
Chance	C88XX(1)	C89XX(2)
Joslyn	J88XX(6)	J89XX(7)

ao - Bolts, straight, thimble-eye

	<u>5/8"</u>	<u>3/4"</u>
Chance	C55XX(3)	C56XX(4)
Joslyn	J80XX(8)	J80XX(9)

ba - Bolts, angle, thimble-eye

	<u>5/8"</u>	<u>3/4"</u>
Chance	C50XX(3)	C51XX(5)
Joslyn	J81XX(8)	J81XX(9)

See page 7.13.1 for notes.

6.13.1
01-05
c;ao;ba

Notes:

- (1)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 5", 6", 7", 8", 9", 10", 12", 14", 16", 18", 20", 22", and 24".
- (2)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 8", 10", 12", 14", 16", 18", 20", 22", 24", and 26".
- (3)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 10", 12", 14", and 16".
- (4)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 12" and 14".
- (5)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 10", 12", and 14".
- (6)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 5", 6", 7", 8", 9", 10", 11", 12", 13", 14", 15", 16", 18", 20", 22", and 24".
- (7)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 5", 6", 7", 8", 9", 10", 12", 14", 16", 18", 20", 22", 24", and 26".
- (8)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 6", 8", 10", and 12".
- (9)**Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 8", 10", and 12".

6.15
01-05
bk;br;ek;mz

Manufacturer

Catalog Number

bk - Guy Lift Plates

	<u>For 5/8" Bolts</u>	<u>For 3/4" Bolts</u>
Chance	-	7897
Joslyn	J7896	J7894

br - Guy Hooks

Bolt size (inches):	<u>5/8</u>	<u>3/4</u>
Continental Electric Company	GA-5X	GA-64
Stanley G. Flagg	P135AX	P134AX
Joslyn	J6555	J6556
Power Play Products	B58GH	-

ek - Locknuts

Size:	<u>5/8"</u>	<u>3/4"</u>
Joslyn	J8583	J8584

mz - Cable Suspension Clamps

Type:	<u>Straight</u>	<u>Angle</u>
Chance	C7903	C7902L
Joslyn	J1096	J7902-B

Manufacturer

Catalog Number

nb - Suspension Clamp Reinforcement Straps

Size:	<u>1-3/4"</u>	<u>2"</u>
Chance	C7905	-
Joslyn	J7905	J7908

px - Regular Square Nuts

Size:	<u>5/8"</u>	<u>3/4"</u>
Chance	C55084P	C55085P
Joslyn	J8563	J8564

6.17
01-05

The following items have been removed from the List of Materials because of their limited use and not because of their inability to meet applicable requirements. Their removal from the list does not relieve borrowers of their responsibility to use materials that meet RUS requirements, ASTM or other national specifications.

- i - Bolts, carriage
- aa - Oval eye nuts
- al - Ground wire staples and nails
- at - Guy guards
- bl - Steel support brackets
- bm - Guy thimble
- cb - Conductor bundle bags
- df - False deadends
- dm - Permanent cable identification markers
- dz - Guy wire clips
- mf - Drive hooks
- mi - Drop wire support
- mj - Drop wire clip
- mm - Drive rings
- mo - Angle screw
- mx - Steel pole steps
- my - Drop wire hooks
- na - Aerial and underground cable
- nc - Cable extension arms
- nd - Metal pole keys
- ne - Bridle rings
- ns - Span clamps
- pg - Porcelain insulated screweyes
- ph - Screw anchors
- pk - Moisture blocks
- pt - Vinyl tape
- pw - Detachable pole steps
- py - Lashing wire terminal clamps
- st - Spacer tape
- tc - Cable ties
- wf - Self-supporting cable
- za - Filler tape
- ze - Sealing compound

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, sex, religion, age, disability, political beliefs, sexual orientation, and marital or family status. (Not all prohibited bases apply to all programs.) Persons with disabilities who require alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA'S TARGET Center at (202) 720-2600 (voice and TDD).

To file a complaint of discrimination, write USDA, Director, Office of Civil Rights, Room 326-W, Whitten Building, 14th and Independence Avenue, SW, Washington, D.C. 20250-9410 or call (202) 720-5964 (voice or TDD). USDA is an equal opportunity provider and employer.