


REG	STATE	PROJECT	SHEET NO.	TOTAL SHEETS

NOTE:

- Top of wall will be as shown on wall Lavout 1. Drawings. No steps will be allowed.
- Survey MSE wall locations according to section 152 to acquire current terrain data. Prepare and submit 2. for approval Preliminary Drawings according to 104.03. See subsection 255.03.
- Furnish select wall backfill consisting of soil meeting the requirements of Subsection 704.13(a) of the З. Special Contract Requirement.
- Furnish wall backfill consisting of backfill soil meeting the requirements of subsection 704.13(b) 4. of the Special Contract Requirement.
- Furnish wall facing fill conforming to the requirements of subsection 704.13(c) of the 5. Special Contract Requirement.
- 6. Install guardrail posts per Subsection 617.03.
- 7. Design data:

Unit weight of select wall backfill = 125 lb/ft3 $\emptyset = 34^{\circ}$ for select wall backfill. Use the maximum cover dimension for all design calculations.

- See Detail C255-51 for drainage details. 8.
- Place hardware cloth according to Subsection 255.04. 9.
- Terminate wire-face wall at the beginning and end of each lift with a return of the wall facing material 10. (backing mat & hardware cloth) a minimum of 4' into the backfill. The returns are not measured for payment and are subsidiary to the MSE wall.



NO SCALE