GOMPPF Auxillary

GOMPPF

PURPOSE

Compute the Gompertz percent point function.

DESCRIPTION

The Gompertz distribution has the following percent point function:

$$f(x, c, b) = bc^x e^{\frac{-b(c^{x-1})}{\log(c)}}$$
 $x \ge 0, b > 0, c \ge 1$ (EQ Aux-186)

where b and c are shape parameters. It has the following percent point function:

$$G(p, c, b) = \frac{\log(1 + \log(c)\log(1 - p))}{\log(c)}$$
 b > 0, c \ge 1 (EQ Aux-187)

SYNTAX

LET < y> = GOMPPF(, < c>, < b>)

<SUBSET/EXCEPT/FOR qualification>

where is a number, a parameter, or a variable in the range 0 to 1;

- <y> is a variable or a parameter (depending on what <x> is where the computed Gompertz ppf value is saved;
- <c> is a number, parameter, or variable (greater than 1) that specifies the first shape parameter;
-
 is a positive number, parameter, or variable that specifies the second shape parameter;

and where the <SUBSET/EXCEPT/FOR qualification> is optional.

EXAMPLES

LET A = GOMPPF(0.9,2,3)LET X2 = GOMPPF(X1,C,B)

NOTE 1

If c is 1, this distribution reduces to the exponential distribution. The Gompertz distribution can be interpreted as a truncated extreme value type I distribution.

NOTE 2

There are several forms given for the Gompertz distribution in the literature. Some of these are given in Johnson, Kotz, and Balakrisnan (see the Reference section below). In particular, one common form uses the parameter α where $\alpha = \log(c)$. Simply replace c with $\text{EXP}(\alpha)$ in the pdf formula given above.

DEFAULT

None

SYNONYMS

None

RELATED COMMANDS

GOMPDF	=	Compute the Gompertz probability density function.
GOMPPF	=	Compute the Gompertz percent point function.
EXPCDF	=	Compute the exponential cumulative distribution function.
EXPPDF	=	Compute the exponential probability density function.
EXPPPF	=	Compute the exponential percent point function.
EV1CDF	=	Compute the extreme value type I cumulative distribution function.
EV1PDF	=	Compute the extreme value type I probability density function.
EV1PPF	=	Compute the extreme value type I percent point function.
WEICDF	=	Compute the Weibull cumulative distribution function.
WEIPDF	=	Compute the Weibull probability density function.
WEIPPF	=	Compute the Weibull percent point function.
EV2CDF	=	Compute the extreme value type II cumulative distribution function.
EV2PDF	=	Compute the extreme value type II probability density function.
EV2PPF	=	Compute the extreme value type II percent point function.

Auxillary GOMPPF

REFERENCE

"Continuous Univariate Distributions," 2nd. ed., Johnson, Kotz, and Balakrishnan, John Wiley and Sons, 1994 (pp. 25-26, 81-85).

APPLICATIONS

Life Testing

IMPLEMENTATION DATE

95/10

PROGRAM

```
LET C1 = DATA 1.1 1.1 1.1 2 2 2 5 5 5 

LET B1 = DATA 0.5 1 2 0.5 1 2 0.5 1 2 ...

MULTIPLOT 3 3; MULTIPLOT CORNER COORDINATES 0 0 100 100 

TITLE AUTOMATIC 

LOOP FOR K = 1 1 9 

LET C = C1(K) 

LET B = B1(K) 

X1LABEL C = ^C, B = ^B 

PLOT GOMPPF(P,C,B) FOR P = 0.01 0.01 0.99 

END OF LOOP 

END OF MULTIPLOT
```

