Oak Ridge National Laboratory (ORNL) Transportation and Packaging Management (TPM) **Container Preparation and Filling Instructions/Checklist**

| UN 7 Gallon Open Head (OH) Fiber Drum | | ORNL-CHK-40, Rev. 2 |
|---------------------------------------|-------------------|---------------------|
| Issued: 5/15/1997 | Revised: 2/1/2006 | Page 1 of 4 |

INSTRUCTIONS: Complete the activities requested following the instructions below. Activities should be checked off as performed. The completed checklist should then be signed by the Operating Personnel completing the checklist and submitted to the Operations Supervisor for approval for shipment.

NOTE 1: The 7 gallon open head fiber drum is UN marked for filling with solid hazardous materials.

NOTE 2: The maximum allowable gross weight is printed on the side of each drum in kilograms [ex., 60 kg (132 lbs)]. Allowable weight applies to Packaging Groups II or III solid materials. [PG I is not authorized.]

NOTE 3: Drums must be closed in accordance with the specific instructions furnished, and tested, by the manufacturer for each specific type/size drum, in order to be in compliance with DOT HAZMAT regulations. [49 CFR, §178.2(c)(1)]

> A. PRE-LOADING INSTRUCTIONS FOR UN 1G/Y 7 Gallon (OH) Fiber Drum Stores Catalog No. 02-113-5737

Note: Items marked (#) are solely generator's/filler's responsibility.

- (#) Inspect the drum to be filled to ensure that it is in good physical Operating 1. Personnel condition and that no critical dents/damages, fiberboard tears/cuts, etc. exist that could cause or develop into a leak during normal storage or in transportation. Special attention is required for the gasket.
 - _____ 2. (#) Ensure that the material being filled into the drum is compatible with (will not react, soften, attack) the drum's internal fiber surface.
 - 3. IF the drum is to be filled with solid hazardous materials/waste, THEN Ensure limits specified in **NOTE 2** are followed.
 - **B. CLOSING INSTRUCTIONS FOR** UN 1G/Y 7 Gallon (OH) Fiber Drum Stores Catalog No. 02-113-5737
 - _____ 1. For drums supplied by Skolnik Industries (drums marked BR####) see Attachment #1.
 - For drums from Greif Bros. (drums marked GBC) see Attachment #2. 2.

| Container Preparation and Filling Instructions/Checklist | | | | | | |
|--|----|--|------------------------------|--|--|--|
| UN 7 Gallon Open Head (OH) Fiber Drum | | Fiber Drum | ORNL-CHK-40, Rev. 2 | | | |
| Issued: 5/15/1997 | | Revised: 2/1/2006 | Page 2 of 4 | | | |
| | L | OST-LOADING INSTRUCTIONS FOR IN 1G/Y 7 Gallon (OH) Fiber Drum Stores Catalog No. 02-113-5737 | | | | |
| Operating transport | 1. | IF generator/filler is responsible for preparing package for THEN Label and mark the drum in accordance with the current ORNL/Department of Transportation (DOT) requirements. For off-site shipments, contact the ORNL Transportation and Packaging Management organization for appropriate DOT marking and labeling. | | | | |
| transport, Personnel | | | | | | |
| | | IF generator/filler is <i>not</i> responsible transport, THEN This item is not applicable and shou | | | | |
| | 2. | Sign and date the checklist in the verifying that the activities have been completed. | | | | |
| | 3. | Submit this completed checklist to the approval for shipment. | ne Operations Supervisor for | | | |
| Operations Supervisor | 4. | Verify that all defined activities have b | een successfully completed. | | | |
| | 5. | Sign and date the checklist in the approving the container for shipment. | appropriate signature block, | | | |

APPROVED FOR SHIPMENT:

| Operating Personnel: | Date: |
|------------------------|-------|
| Operations Supervisor: | Date: |

Prepared by: ORNL TPM Organization

Approved by:

(F) $\cdot \times$ m

Jeff Shelton, Manager (576-6401) ORNL TPM - Packaging Operations February 1, 2006

FOR INTERNAL USE ONLY

Container Preparation and Filling Instructions/Checklist

UN 7 Gallon Open Head (OH) Fiber Drum Issued: 5/15/1997 Revise

Revised: 2/1/2006

ORNL-CHK-40, Rev. 2 Page 3 of 4

ATTACHMENT #1

MICHAEL'S COOPERAGE COMPANY, INC. Manufacturers of Industrial Containers est. 1939 363 West Pershing Road Chicago, Illinois 50609 USA Corporate Phone: 1-800-262-6281 Fax: 1-773-268-9609 e-mail: 'sales@michaelscooperage.com Chicago October 26, 2005 California Mr. Bill Fitzgerald Skolnik Industries 4900 South Kilbourne Chicago, IL 60632-4593 Kentucky Closure of Lock Rim Drums HINN'S. In order for these drums to be in compliance with applicable sections of 49 CFR, the following closure directions must be followed. Pennsylvania 1. Insert bag. 2. Fill bag with product. 3. Apply twist tie to close bag. Put cover on.
 Attach ring to cover - tab town; 6. Fold over lever to close. 7. Push up locking tab until it locks. Sincerely; Mark J. Duske Quality Manager

FOR INTERNAL USE ONLY

| Gallon Open Head (OH) Fit | | ORNL-CHK-40, Rev. 2 | | |
|--|--|---|--|--|
| l: 5/15/1997 | Revised: 2/1/2006 | Page 4 of 4 | | |
| ATTACHMENT #2 | | | | |
| Date : 02-23-05 [09:02] Page : 1 Company : USA | CLOSURE NOTIF | FICATION | | |
| Product Type | | | | |
| F11 | | | | |
| ************************************** | M CLOSURE NOTIFICATION e Department of Transportation method used for the containers | in CFR 49 Part 178.2(c)(1), this | | |
| To be UN certified, this drum mus certification. If drum is purchased the correct cover and closing ring. | d without these parts, contact the | | | |
| Your product may adversely affect compatibility with the container is | et container materials, bung threas s the shipper's responsibility. | ads, or closing devices. Product | | |
| These instructions for closure are to pass the United Nations test req | | | | |
| The closure recommendations do handling, filling or shipping of yo | | ds present in your facility, or the | | |
| Any containers used for packaging shipment. Containers with obviou | is damage or deterioration should | ld not be filled or shipped. | | |
| To Close: Place cover on drum. Snap the closing ring over the the closing lever is right side up under the top lip of the drum. Pull the locking lever closed. ring with a mallet, beginning diagainst the edge of the ring. Snap the latch into the lever up through the holes on the latch lever | p. Also, make sure the bottom e At the same time, tap along the irectly opposite the closing lever ntil it locks, then apply a sealing ever. | Make sure that the writing on edge of the closing ring engages entire outside edge of the closing r, until the lever is fully closed | | |

Container Preparation and Filling Instructions/Checklist

FOR INTERNAL USE ONLY