

3.3
01-05
gs

gs - Bonding Connector Harnesses

Manufacturer

Catalog Number

gs-a - #6 AWG Stranded Harness Wires

Bonding in Aerial, Buried or Underground Splice Cases,
and Ready-Access Enclosures

	<u>Noninsulated</u>			<u>Insulated</u>		
	<u>10" Length</u>	<u>20" Length</u>	<u>22" Length</u>	<u>10" Length</u>	<u>20" Length</u>	<u>22" Length</u>
Electric Motion Company	EM8100-10B.10	EM8100-20B.10	EM8100-22B.10	EM8100-10.10	EM8100-20.10	EM8100-22.10
LSW	LSW 6-10	LSW 6-20	LSW 6-22	LSW 6-10C	LSW 6-20C	LSW 6-22C

Bonding in Buried Plant Housings

	<u>Noninsulated</u>			<u>Insulated</u>		
	<u>6" Length</u>	<u>11" Length</u>	<u>18" Length</u>	<u>6" Length</u>	<u>11" Length</u>	<u>18" Length</u>
Electric Motion Company	EM8100-6B.10	EM8100.11B.10	EM8100-18B.10	EM8100-6.10	EM8100.11.10	EM8100-18.10
LSW	LSW 6-06	LSW 6-11	LSW 6-18	LSW 6-06C	LSW 6-11C	LSW 6-18C

gs-b - #6 AWG Braid

Bonding in Aerial, Buried, or Underground Splice Cases,
Ready-Access Enclosures, and Buried Plant Housings

	<u>Noninsulated</u>	<u>Insulated</u>
A.K. Stamping	A1163	-
Electric Motion Company	EM-2050	EM-2051
Excelco	579203-25	-
3M	25T (4)	25/4467 (4)

See page 3.3.1 for notes.

gs - Bonding Connector Harnesses
(Stranded Type Wire)

Buried Service Wire (Bare Metal Shields Only)

Manufacturer

Catalog Number

gs-a - #14 AWG Insulated Harness Wires

Bonding at Station Protector (Network Interface Device)

	<u>7" Length</u>
Corning Cable Systems	GH-13 ⁽¹⁾
Electric Motion Company	EM1407TFFR ⁽¹⁾
Engineered Products Co.	EH-13 ⁽¹⁾
LSW	LSW-5 ⁽¹⁾
Preformed Line Products	8000739 ⁽²⁾

gs-b - #6 AWG Insulated Harness Wires

Bonding in Buried Plant Housings

	<u>15" Length</u>	<u>36" Length</u>
Electric Motion Company	EM3955-6L/8100-15 ⁽³⁾	EM3955-6L/8100-36 ⁽³⁾

- Notes:**
- (1)** Harnesses equipped with AMP's #329860 Termi-Foil^R connector at one end for attachment to the bare metal shield of the service wire.
 - (2)** Harnesses equipped with Preformed Line Products' 8000733 connector at one end for attachment to the bare metal shield of the service wire.
 - (3)** Harnesses equipped with Electric Motion's EM3955 connector at one end for attachment to the bare metal shield of the service wire.
 - (4)** When ordering, state 3-inch eyelets.