

SECTION 7 -- REACTIVITY DATA

Stability:	Stable
Conditions to Avoid:	Heat, sparks and open flame
Incompatibility (Materials to Avoid):	Strong oxidizing agents like liquid chlorine or concentrated oxygen.
Hazardous Decomposition Products:	Thermal decomposition may yield carbon monoxide.
Hazardous Polymerization:	Will not occur

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapor or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection:	Appropriate vapor canister, self-contained breathing apparatus or supplied-air hose mask, if needed.
Ventilation:	Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements. See Section 2. Use explosion-proof equipment. No smoking or open lights.
Protective Gloves:	Rubber or neoprene
Eye Protection:	Chemical safety goggles
Other Protective Equipment:	Impervious clothing or boots, if needed.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category:	Combustible Liquid Class II
Hygienic Practices:	Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.
Additional Precautions:	Ground containers when transferring liquid to prevent static accumulation and discharge.
Empty Container Warning:	"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

37

SPECS
PAINT
THINNER

sunnyside

specs

paint thinner

(LOW-ODOR MINERAL SPIRITS)



SPECS
PAINT
THINNER

83

Sunnyside Specs Paint Thinner is specially formulated to meet the requirements of a wide variety of paints, varnishes, and enamels—wherever mineral spirits or turpentine is recommended as a thinner. Its high solvency allows Specs Paint Thinner to blend thoroughly and quickly with a minimum of stirring. Correct evaporation rate helps prevent brush and lap marks and provides uniform film thickness and surface adhesion.

Specs is ideal for cleaning brushes and equipment after painting and is an excellent solvent for oil, grease, tar and wax. Because it dries completely, leaving no residue or odor, it is widely used as a dry cleaner and spot remover for fabrics, and for cleaning tools, machinery, porcelain, guns and sporting equipment.

NOTE: Specs Paint Thinner may be harmful to some plastics, synthetic fabrics and tile. Always test on sample before allowing contact.

Caution. CONTAINS PETROLEUM DISTILLATE. Harmful or fatal if swallowed. Keep away from heat and open flame. Avoid contact with eyes and prolonged contact with skin. Avoid breathing of vapor or spray mist. Do not transfer contents to unlabeled containers. Close container after each use.

Brush & roller cleaner.
Cleaning solvent.



First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly.
Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.

32 FL. OZ. (1 QT.)

9463 LITER

SWALLOWED, COMBUSTIBLE
DANGER
1-800-4-A-SUNNY
SUNNYSIDE CORPORATION
P.O. Box 1000
Cleveland, Ohio 44110

SUNNYSIDE
CORPORATION

0
16542 00142

SPES
PAINT
THINNER



sunnyside

specs

paint thinner

(LOW-ODOR MINERAL SPIRITS)



Brush & roller cleaner.

Cleaning solvent.



DANGER!
FLAMMABLE OR FATAL IF SWALLOWED. COMBUSTIBLE.
Read safety data & follow all cautions shown on this container.
32 FL OZ (1QT) ■ 9463 LITER

Sunnyside Specs Paint Thinner is specially formulated to meet the requirements of a wide variety of paints, varnishes, and enamels—wherever mineral spirits or turpentine is recommended as a thinner its high solvency allows Specs Paint Thinner to blend thoroughly and quickly with a minimum of stirring. Correct evaporation rate helps prevent brush and lap marks and provides uniform film thickness and surface adhesion.

Specs is ideal for cleaning brushes and equipment after painting and is an excellent solvent for oil, grease, tar and wax. Because it dries completely, leaving no residue or odor, it is widely used as a dry cleaner and spot remover for fabrics, and for cleaning tools, machinery, porcelain, guns and sporting equipment.

NOTE: Specs Paint Thinner may be harmful to some plastics, synthetic fabrics and tile. Always test on sample before allowing contact.

SPES
PAINT
THINNER

Caution. CONTAINS PETROLEUM DISTILLATE. Harmful or fatal if swallowed. Keep away from heat and open flame. Avoid contact with eyes and prolonged contact with skin. Avoid breathing of vapor or spray mist. Do not transfer contents to unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly.

Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.



EXHIBIT #: 5

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

39

BACK PANEL
SPECS PAINT THINNER 704

January 22, 1992
Susan

Sunnyside Specs Paint Thinner is specially formulated to meet the requirements of a wide variety of paints, varnishes, and enamels - wherever mineral spirits or turpentine is recommended as a thinner. Its high solvency allows Specs Paint Thinner to blend thoroughly and quickly with a minimum of stirring. Correct evaporation rate helps prevent brush and lap marks and provides uniform film thickness and surface adhesion.

Specs is ideal for cleaning brushes and equipment after painting and is an excellent solvent for oil, grease, tar and wax. Because it dries completely, leaving no residue or odor, it is widely used as a dry cleaner and spot remover for fabrics, and for cleaning tools, machinery, porcelain, guns and sporting equipment.

NOTE: Specs Paint Thinner may be harmful to some plastics, synthetic fabrics and tile. Always test on sample before allowing contact.

CAUTIONS: CONTAINS PETROLEUM DISTILLATE. Keep away from heat and flame. Prevent vapor build-up. Open all doors and windows to provide plenty of fresh air equal to outdoor conditions. Do not use without fresh air ventilation. Do not smoke. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention. Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode.

Health Hazards. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air.

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090

UPC Codes
0 76542 00042-6-QT
0 76542 00038-9-GAL
0 76542 00041-9-PT

40

SIDE PANEL
SPECS PAINT THINNER 704

January 22, 1992

Add Recycle Symbol

SPECS

**WARNING: This product contains
a chemical(s) known to the state of
California to cause cancer or birth defects
or other reproductive harm.**

California SCAQMD Rule 443.1
Max. VOC: 772 g/l
Max. Vapor Pressure
of VOC: 3mmHg
Non-photochemically Reactive

41

FRONT PANEL
SPECS PAINT THINNER 704

January 22, 1992

sunnyside
specs paint thinner
(low odor mineral spirits)

Brush and roller cleaner
Cleaning solvent

DANGER!

**HARMFUL OR FATAL IF SWALLOWED.
COMBUSTIBLE LIQUID AND VAPOR.**

Carefully read and follow all cautions elsewhere on this container.

**32 FL. OZ. (1 QT.) .9463 LITER
ONE GALLON 3.785 LITERS
16 FL. OZ. (1 PT.) .473 LITER**

42

EXHIBIT #: 6

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

23

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 07/01/89

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 80090
EMERGENCY TELEPHONE

FOR INFORMATION: (708) 541-5700

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

Product Class: Petroleum Hydrocarbon
Trade Name: SUNNYSIDE PAINT THINNER
(Plastic Container)

Manufacturer's Code:
NPCA HMIS:

701
H1 F2 RO

Product Appearance and Odor: Clear, water-white liquid; petroleum odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Mineral Spirits	64742-47-8 (For Stoddard Solvent - CAS #8052-41-3)		100 PPM		100 PPM		2.0 MM Hg @ 20° C.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

If overcome by vapors, move patient to fresh air and call physician. Apply artificial respiration. If necessary, for skin or eye contact, flush with copious quantities of water. Get medical attention. If swallowed, do not induce vomiting. Call a physician.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	315-395° (F)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	100%
Weight Per Gallon:	6.62 lbs.		
Solubility in Water:	Negligible; less than 0.1%.		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification:	Combustible Liquid Class II
Flash Point:	102° (F) Tag. Closed Cup
Lower Explosive Limit:	0.9%
Extinguishing Media:	Carbon Dioxide, foam, dry chemical, water spray. Do not use direct water stream; it will spread fire.
Unusual Fire and Explosion Hazards:	Do not store or mix with strong oxidants.
Special Fire Fighting Procedures:	Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water.

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:	100 PPM (Recommended by ACGIH for Stoddard Solvent).
EFFECTS OF OVEREXPOSURE	Breathing high vapor concentrations may result in mild depression, dizziness, headache, respiratory irritation, convulsions, or loss of consciousness. Contact may irritate eyes or skin.

44

Primary route of entry: Inhalation
Chronic Effects: None expected when good hygienic practices are employed.

SECTION 7 -- REACTIVITY DATA

Stability: Stable.
Conditions to Avoid: Heat, sparks and open flame.
Incompatibility (Materials to Avoid): Strong oxidizing agents like liquid chlorine or concentrated oxygen.
Hazardous Decomposition Products: Thermal decomposition may yield carbon monoxide.
Hazardous Polymerization: Will not occur.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapors or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: Appropriate vapor canister, self contained breathing apparatus or supplied-air hose mask, if needed.
Ventilation: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSH safety and health requirements. See section II. Use explosion-proof equipment. No smoking or open lights.
Protective Gloves: Rubber or Neoprene.
Eye Protection: Chemical safety goggles.
Other Protective Equipment: Impervious clothing or boots, if needed.

SECTION 10 -- SPECIAL PRECAUTIONS


Dept. of Labor Storage Category: Combustible liquid class II.
Hygienic Practices: Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.
Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge.
Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

45



sunnyside
paint thinner
(LOW ODOR-MINERAL SPIRITS)

Brush & roller cleaner.
Cleaning solvent.



DANGER!
HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.
Carefully read & follow cautions on back panel.

ONE GALLON ■ 3.785 LITERS

46

Sunnyside Paint Thinner (Mineral Spirits) is an economical solvent for thinning most oil base paints and stains. Its low odor and high solvent power make it ideal for cleaning brushes, rollers and equipment after painting. Always consult paint manufacturer's directions for thinning.

This versatile product is also an excellent choice for cleaning tar, grease, oil and grime from cars, car parts, lawn mowers, tools and machinery. It can also be used as a spot cleaner for fabrics.

NOTE: Paint Thinner may be harmful to some plastics, linoleum, tile and other synthetic surfaces if allowed to remain in contact. Always test before using.

NON-PHOTOCHEMICALLY REACTIVE

Caution. CONTAINS PETROLEUM DISTILLATE. Harmful or fatal if swallowed. Keep away from heat and open flame. Avoid contact with eyes and prolonged contact with skin. Avoid breathing of vapor or spray mist. Do not transfer contents to unlabeled containers. Close container after each use. Do not re-use container.

First Aid: If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly.

Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

**SUNNYSIDE
CORPORATION**

Consumer Products Division
Wheeling, IL 60090



California SCAQMD Rule 443.1
Max. VOC 772 g/L
Max. Vapor Pressure of VOC 3 mm Hg
Non-photochemically Reactive

76542 00030

47

EXHIBIT #: 7

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

48

**BACK PANEL
PLASTIC BOTTLE PAINT THINNER 701**

February 3, 1992
Susan

Sunnyside Paint Thinner (Mineral Spirits) is an economical solvent for thinning most oil base paints and stains. Its low odor and high solvent power make it ideal for cleaning brushes, rollers and equipment after painting. Always consult paint manufacturer's directions for thinning.

This versatile product is also an excellent choice for cleaning tar, grease, oil and grime from cars, car parts, lawn mowers, tools and machinery. It can also be used as a spot cleaner for fabrics.

NOTE: Paint Thinner may be harmful to some plastics, linoleum, tile, and other synthetic surfaces if allowed to remain in contact. Always test before using.

CAUTIONS: CONTAINS PETROLEUM DISTILLATE. Keep away from heat and flame. Prevent vapor build-up. Open all doors and windows to provide plenty of fresh air equal to outdoor conditions. Do not use without fresh air ventilation. Do not smoke. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention. Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the bottle and explode.

Health Hazards. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air.

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

WARNING: This product contains a chemical(s) known to the state of California to cause cancer or birth defects or other reproductive harm.
(California SCAQMD Rule 443.1)(Max. VOC: 772 g/l)(Max. Vapor Pressure of VOC: 3mm Hg)(Non-photochemically reactive).

**Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.**

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090

UPC Codes

0 76542 00030-3-GAL

4A

FRONT PANEL
PLASTIC BOTTLE PAINT THINNER 701

February 3, 1992

sunnyside
paint thinner
(low odor mineral spirits)

Brush and roller cleaner
Cleaning solvent

DANGER!
HARMFUL OR FATAL IF SWALLOWED.
COMBUSTIBLE LIQUID AND VAPOR.
Carefully read and follow all cautions elsewhere on this container.
ONE GALLON 3.785 LITERS

50

EXHIBIT #: 8

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

51

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 7/1/89

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

FOR INFORMATION: (708) 541-5700

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

Product Class: Petroleum Hydrocarbon Manufacturer's Code: 705
Trade Name: ODORLESS PAINT THINNER NPCA HMIS: H1 F2 RO

Product Appearance and Odor: Clear, water-white liquid; little, if any odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
C10-C11 Paraffins Cyclo-Paraffins	64741-85-7		Not Est.		Not Est.		<10 MM Hg @ 25° C.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

If overcome by vapors, move patient to fresh air and call physician. Apply artificial respiration, if necessary. For skin or eye contact, flush with copious quantities of water. Get medical attention. If swallowed, do not induce vomiting. Call a physician.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	346-406° (F)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	100%
Weight Per Gallon:	6.34 lbs.		
Solubility in Water:	Negligible		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification: Combustible Liquid Class II
Flash Point: 115° (F) Tag. Closed Cup
Lower Explosive Limit: 0.7%

Extinguishing Media: Carbon dioxide, foam, dry chemical, water spray. Do not use direct water stream; it will spread fire.

Unusual Fire and Explosion Hazards: Do not store or mix with strong oxidants.
Special Fire Fighting Procedures: Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water.

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 300 PPM (Suggested by Exxon Corp. Medical Research.)
EFFECTS OF OVEREXPOSURE: Breathing high vapor concentrations may result in mild depression, dizziness, headache, respiratory irritation, convulsions, or loss of consciousness. Contact may irritate eyes or skin.
Primary Route of Entry: Inhalation.
Chronic Effects: None expected when good hygienic practices are employed.

SECTION 7 -- REACTIVITY DATA

Stability: Stable
Conditions to Avoid: Heat, sparks and open flame
Incompatibility (Materials to Avoid): Strong oxidizing agents like liquid chlorine or concentrated oxygen.
Hazardous Decomposition Products: Thermal decomposition may yield carbon monoxide.
Hazardous Polymerization: Will not occur.

52

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapor or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: Appropriate vapor canister, self-contained breathing apparatus or supplied-air hose mask, if needed.

Ventilation: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements. See Section 2. Use explosion-proof equipment. No smoking or open lights.

Protective Gloves: Rubber or neoprene

Eye Protection: Chemical safety goggles

Other Protective Equipment: Impervious clothing or boots, if needed.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category: Combustible Liquid Class II

Hygienic Practices: Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.

Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge.

Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

53

ODORLESS
PAINT
THINNER



sunnyside

odorless

paint thinner

ODORLESS
PAINT
THINNER

55

Sunnyside Odorless Paint Thinner is a completely odorless solvent particularly designed for thinning odorless paints, varnishes and enamels. It is not intended for use in ordinary paint, enamel or varnish. Follow the paint manufacturers' directions for thinning to desired consistency.

Odorless Paint Thinner is excellent for cleaning brushes and painting equipment after use with odorless paint. It is also suitable as a general cleaning solvent for use on fabrics, rugs, metal parts, wood, porcelain, and glass.

Caution. CONTAINS PETROLEUM DISTILLATE. Harmful or fatal if swallowed. Keep away from heat and open flame. Avoid contact with eyes and prolonged contact with skin. Avoid breathing of vapor or spray mist. Do not transfer contents to unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN

For use with odorless
paints & enamels.



32 FL. OZ. (1 QT.) ■ 9463 LITER

0
16542 U0045



347-2262-B

**ODORLESS
PAINT
THINNER**



sunnyside odorless paint thinner



For use with odorless
paints & enamels.

**ODORLESS
PAINT
THINNER**

Sunnyside Odorless Paint Thinner is a completely odorless solvent particularly designed for thinning odorless paints, varnishes and enamels. It is not intended for use in ordinary paint, enamel or varnish. Follow the paint manufacturers' directions for thinning to desired consistency.

Odorless Paint Thinner is excellent for cleaning brushes and painting equipment after use with odorless paint. It is also suitable as a general cleaning solvent for use on fabrics, rugs, metal parts, wood, porcelain, and glass.

Caution. CONTAINS PETROLEUM DISTILLATE. Harmful or fatal if swallowed. Keep away from heat and open flame. Avoid contact with eyes and prolonged contact with skin. Avoid breathing of vapor or spray mist. Do not transfer contents to unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention, for skin contact, wash thoroughly. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

32 FL. OZ. (1 QT.) ■ .9463 LITER

0

7654211142

EXHIBIT #: 9

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

55

BACK PANEL
ODORLESS PAINT THINNER 705

January 22, 1992
Susan

Sunnyside Odorless Paint Thinner is a completely odorless solvent particularly designed for thinning odorless paints, varnishes and enamels. It may also be used with many ordinary paints and varnishes, however thinning will require more stirring than normal. Having no odor and lower toxicity than common paint thinner or turpentine, this product is a desirable choice for use indoors.

Odorless Paint Thinner is excellent for cleaning brushes and painting equipment. It is also suitable as a general cleaning solvent for use on fabrics, rugs, metal parts, wood, porcelain, and glass.

Always test in an inconspicuous area for possible damage before using.

CAUTIONS: CONTAINS PETROLEUM DISTILLATE. Keep away from heat and flame. Do not use without fresh air ventilation. Do not smoke. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention. Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode.

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090

UPC Codes
0 76542 00045-7-QT
0 76542 00044-0-GAL

56

**SIDE PANEL
ODORLESS PAINT THINNER 705**

January 22, 1992

Add Recycle Symbol

ODORLESS PAINT THINNER

**WARNING: This product contains
a chemical(s) known to the state of
California to cause cancer or birth defects
or other reproductive harm.**

**California SCAQMD Rule 443.1
Max. VOC: 761 g/l
Max. Vapor Pressure
of VOC: 2 mmHg
Non-photochemically Reactive**

57

FRONT PANEL
ODORLESS PAINT THINNER 705

January 22, 1992

sunnyside
odorless paint
thinner

Designed with Indoor Use in Mind

**No Solvent Odor
Low Health Hazard
Low Volatility**

DANGER!
HARMFUL OR FATAL IF SWALLOWED.
COMBUSTIBLE LIQUID AND VAPOR.
Carefully read and follow all cautions elsewhere on this container.
32 FL. OZ. (1 QT.) .9463 LITER
ONE GALLON 3.785 LITERS

58

EXHIBIT #: 10

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

59

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 7/1/89

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

FOR INFORMATION: (708) 541-5700

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

Product Class: Petroleum Hydrocarbon Manufacturer's Code: 800
Trade Name: VM&P NAPHTHA NPCA HMIS: HI F3 RO

Product Appearance and Odor: Clear, water-white liquid; mild, bland petroleum odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Light Aliphatic Solvent Naphtha	64742-89-8 (For VM&P Naphtha - CAS #8032-32-4)		300 PPM		300 PPM	400 PPM	Approx. 45 MM Hg @ 25° C.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

If overcome by vapors, move patient to fresh air and call physician. Apply artificial respiration, if necessary. For skin or eye contact, flush with copious quantities of water. Get medical attention. If swallowed, do not induce vomiting. Call physician.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	235-286° (F)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	100%
Weight Per Gallon:	6.31 lbs.		
Solubility in Water:	Negligible; less than 0.1%.		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification:	Flammable Liquid; Class IB.
Flash Point:	50° F (Tag. Closed Cup)--Minimum
Lower Explosive Limit:	0.9% (estimated)
Extinguishing Media:	Carbon dioxide, foam, dry chemical, water spray. Do not use direct water stream; it will spread fire.
Unusual Fire and Explosion Hazards:	Do not store or mix with strong oxidants.
Special Fire Fighting Procedures:	Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water.

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 300 PPM (ACGIH-8 hour time weighted average)
EFFECTS OF OVEREXPOSURE: Breathing high vapor concentrations may result in mild depression, dizziness, headache, respiratory irritation, convulsions, or loss of consciousness. Contact may irritate eyes or skin.

Primary Route of Entry: Inhalation
Chronic Effects: None expected when good hygienic practices are employed.

60

SECTION 7 -- REACTIVITY DATA

Stability:	Stable
Conditions to Avoid:	Heat, sparks and open flame.
Incompatibility (Materials to Avoid):	Strong oxidizing agents like liquid chlorine or concentrated oxygen.
Hazardous Decomposition Products:	Thermal decomposition may yield carbon monoxide.
Hazardous Polymerization:	Will not occur.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapors or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water. Avoid contaminating ground and surface waters.

Waste disposal method: Send to a licensed reclaimer or incinerator. Dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection:	Appropriate vapor canister, self-contained breathing apparatus or supplied-air hose mask, if needed.
Ventilation:	Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements. See Section 2. Use explosion-proof equipment. No smoking or open lights.
Protective Gloves:	Rubber or Neoprene
Eye Protection:	Chemical safety goggles.
Other Protective Equipment:	Impervious clothing or boots, if needed.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category:	Flammable Liquid-Class IB.
Hygienic Practices:	Keep away from heat, sparks and open flame. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.
Additional Precautions:	Ground containers when transferring liquid to prevent static accumulation and discharge.
Empty Container Warning:	"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

b1

NAPHTHA



sunyside

NAPHTHA

29

Sunyside VMA-P Naphtha is a specially refined petroleum product. It has good solvent power, mild odor and dries fast, leaving no residue. Naphtha is especially useful for thinning fast drying paints, stains, enamels and varnishes in spraying or brushing applications. It is also excellent for cleaning brushes and equipment.

In general use, naphtha dissolves and removes oil, grease, tars and waxes. It cleans metal, porcelain, wood and painted surfaces and is used as a thinner and solvent for adhesives, rubber cements and polishes.

NOTE: Always test on a sample before using, as naphtha may be harmful to some plastics, tiles and synthetic materials. Naphtha is not recommended as a dry cleaning solvent. When cleaning and removing spots from fabrics, use our completely non-flammable Sunyside Carbo-Chlor.

Caution. CONTAINS PETROLEUM DISTILLATE. Keep away from heat, sparks, and open flame. Concentrated vapors can cause a flash fire. Avoid vapor accumulation by providing plenty of fresh air ventilation. Avoid rubbing, friction may cause static electric sparks. Harmful or fatal if swallowed. Avoid contact with skin or eyes. Avoid breathing of vapor or spray mist. Do not transfer contents to unlabeled containers. Close container after each use.

Fast evaporating
degreasing solvent
& paint thinner.



First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention, for skin contact, wash thoroughly.
Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN

32 FL. OZ. (1 QT.) ■ 9463 LITER



16542 JUU'9

NAPHTHA



sunyside

NAPHTHA

29

Sunyside VM&P Naphtha is a specially refined petroleum product. It has good solvent power, mild odor and dries fast, leaving no residue. Naphtha is especially useful for thinning fast drying paints, stains, enamels and varnishes, in spraying or brushing applications. It is also excellent for cleaning brushes and equipment. In general use, naphtha dissolves and removes oil, grease, tars and waxes. It cleans metal, porcelain, wood and painted surfaces and is used as a thinner and solvent for adhesives, rubber cements and polishes.

NOTE: Always test on a sample before using, as naphtha may be harmful to some plastics, tiles and synthetic materials. Naphtha is not recommended as a dry cleaning solvent. When cleaning and removing spots from fabrics, use our completely non-flammable Sunyside Carbdo-Chlor.

Caution. CONTAINS PETROLEUM DISTILLATE. Keep away from heat, sparks, and open flame. Concentrated vapors can cause a flash fire. Avoid vapor accumulation by providing plenty of fresh air ventilation. Avoid rubbing, friction may cause static electric sparks. Harmful or fatal if swallowed. Avoid contact with skin or eyes. Avoid breathing of vapor or spray mist. Do not transfer contents to unlabeled containers. Close container after each use.

Fast evaporating
degreasing solvent
& paint thinner.



First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention, for skin contact, wash thoroughly. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN

32 FL. OZ. (1 QT.) ■ 9463



0
76542 00079

EXHIBIT #: 11

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

63

BACK PANEL
VM&P NAPHTHA 800

January 22, 1992
Susan

Sunnyside VM&P Naphtha is a specially refined petroleum product. It has good solvent power, mild odor and dries fast, leaving no residue. It is especially useful for thinning fast drying paints, stains, enamels and varnishes in spraying or brushing applications and is also excellent for cleaning brushes and painting equipment. In general use, naphtha dissolves and removes oil, grease, tars and waxes. It cleans metal, porcelain, wood and painted surfaces and is used as a thinner and solvent for adhesives, rubber cements and polishes.

NOTE: Naphtha is flammable. Carefully read and follow all cautions on this label. Always test on a sample before using, as naphtha may be harmful to some plastics, tiles and synthetic materials. Naphtha is not recommended as a dry cleaning solvent. For cleaning and removing spots from fabrics, we recommend using Sunnyside Carbo Clean.

Cautions: CONTAINS PETROLEUM DISTILLATE. Keep away from heat, sparks and flame. Vapors may ignite explosively. Prevent vapor build-up. Open all doors and windows to provide plenty of fresh air equal to outdoor conditions. Do not use without fresh air ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Avoid rubbing; friction may cause static electric sparks which may ignite vapors. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention. Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode.

Health Hazards. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air.

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

**Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.**

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090

UPC Codes
0 76542 00079-2-QT
0 76542 00077-8-GAL

64

SIDE PANEL
VM&P NAPHTHA

January 22, 1992

Add Recycle Symbol

NAPHTHA

**WARNING: This product contains
a chemical(s) known to the state of
California to cause cancer or birth defects
or other reproductive harm.**

**California SCAQMD Rule 443.1
Max. VOC: 755 g/L
Max. Vapor Pressure
of VOC: 6mm Hg
Non-photochemically Reactive**

A handwritten signature or set of initials in black ink, located in the bottom right corner of the page. The characters appear to be 'S' and 'P' or similar, written in a stylized, cursive-like font.

FRONT PANEL
VM&P NAPHTHA

January 22, 1992

NAPHTHA

sunnyside

naphtha

Fast evaporating
degreasing solvent
& paint thinner.

DANGER!

FLAMMABLE LIQUID AND VAPOR.
HARMFUL OR FATAL IF SWALLOWED.
VAPORS MAY CAUSE FLASH FIRE.

Carefully read & follow all cautions elsewhere on this container.

32 FL. OZ. (1 QT.) .9463 LITER

ONE GALLON 3.785 LITERS

66

EXHIBIT #: 12

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

b7

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 9/4/91

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

FOR INFORMATION: (708) 541-5700

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

Product Class: Mixed Solvents
Trade Name: 457 LACQUER THINNER

Manufacturer's Code:
NPCA HMIS:

457
Health: 2
Flammability: 3
Reactivity: 0

Product Appearance and Odor: Clear, colorless liquid; mild solvent odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH	ACGIH	OSHA	OSHA	VAPOR PRESSURE
			TLV (TWA)	TLV (STEL)	PEL (TWA)	PEL (STEL)	
Acetone	67-64-1		750 PPM	1000 PPM	750 PPM	1000 PPM	213 MM Hg @ 75° F.
Ethyl Acetate	141-78-6		400 PPM		400 PPM		86 MM Hg @ 20° C.
Isopropyl Alcohol	67-63-0		400 PPM	500 PPM	400 PPM	500 PPM	30.0 MM Hg @ 68° F.
Light Aliphatic Solvent Naphtha	64742-89-8 (For VM&P Naphtha - CAS # 8032-32-4)		300 PPM		300 PPM	400 PPM	Approx. 60 MM Hg @ 25° C.
Toluene	108-88-3		100 PPM	150 PPM	100 PPM	150 PPM	Approx. 54 MM Hg @ 25° C.
2-Butoxyethanol	111-76-2		25 PPM (SKIN)		25 PPM (SKIN)		0.6 MM Hg @ 20° C

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

EYE CONTACT: Immediately flush eyes with large amounts of water for at least 15 minutes. Get prompt medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

INGESTION: If swallowed, do not induce vomiting. Keep at rest. Get prompt medical attention.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range: 133-304° F.
Evaporation Rate: Slower than ether
Weight Per Gallon: 6.64 lbs.
Solubility in Water: Moderate

Vapor Density: Heavier than air
% Volatile By Volume: 100%

SECTION 5: -- FIRE AND EXPLOSION DATA

Flammability Classification: Flammable liquid - Class IB.
Flash Point: 0° F. (Tag, Closed Cup)
Lower Explosive Limit: 2.6% @ 25°C
Extinguishing Media: Either allow fire to burn under controlled conditions or extinguish with alcohol type foam and dry chemical. Try to cover liquid spills with foam.
Unusual Fire and Explosion Hazards: Extremely flammable. Material will readily ignite at ambient temperatures. Releases vapors that form flammable mixtures at or above the flash point.
Special Fire Fighting Procedures: Use water spray to cool fire exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

68

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section 2.
EFFECTS OF OVEREXPOSURE:

Inhalation: Breathing high vapor concentrations may result in respiratory tract irritation, central nervous system depression, liver and kidney damage. Brain cell damage may result from long-term vapor inhalation.
Skin Contact: Prolonged or repeated skin contact can cause drying, cracking, or irritation of the skin.
Eye Contact: Severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.
Ingestion: Small amounts of the liquid aspirated into the respiratory system during ingestion, or from vomiting, may cause bronchiopneumonia or pulmonary edema.
Carcinogenicity: None of the solvents in this product are listed as carcinogens or potential carcinogens by the NTP, IARC, or OSHA.

Studies in experimental animals with 2-Butoxyethanol have produced damage to the red blood cell by inhalation, skin absorption and ingestion. Toxic liver effects in male rats were also observed.

SECTION 7 -- REACTIVITY DATA

Stability: Stable
Conditions to Avoid: Heat, sparks, and open flame.
Incompatibility (Materials to Avoid): Strong oxidizing agents like liquid chlorine or concentrated oxygen.
Hazardous Decomposition Products: Thermal decomposition may yield carbon monoxide.
Hazardous Polymerization: Will not occur.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapors or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Send to a licensed reclaimer or incinerator. Dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: Appropriate vapor canister, self-contained breathing apparatus or supplied-air hose mask, if needed.
Ventilation: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements. See Section 2. Use explosion-proof equipment. No smoking.
Protective Gloves: Wear resistant gloves such as nitrile rubber.
Eye Protection: Chemical Safety Goggles
Other Protective Equipment: Impervious clothing or boots, if needed.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category: Flammable liquid - Class IB.
Hygienic Practices: Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged contact with skin. Wash skin with soap and water after contact.
Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge.
Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 11 -- ADDITIONAL INFORMATION

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
Acetone	67-64-1	25.41%
Toluene	108-88-3	21.84%
Glycol Ethers (Ethylene Glycol Monobutyl Ether)	111-76-1	2.31%

69

LACQUER THINNER



sunnside

LACQUER THINNER

lacquer thinner

Specially formulated.



Sunnside Lacquer Thinner is a premium quality product, formulated for general use with a variety of high quality lacquers and epoxies. It has a medium evaporation rate and can be related to control blushing. Because temperature and humidity affect finish characteristics of lacquer, always test prior to starting. NOTE: Lacquer Thinner may be harmful to synthetic materials. Avoid contact or test for possible damage before using.

20

Caution, CONTAINS TOLUENE, ACETONE, ETHYL ACETATE, ISOPROPYL ALCOHOL AND PETROLEUM DISTILLATES. Keep away from heat, sparks and flame. Vapors may ignite explosively if allowed to accumulate. Avoid rubbing; friction may cause static electric sparks. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, fans, electric motors, and all other sources of ignition during use and until all vapors are gone.


Health Hazard. Repeated or prolonged overexposure to solvent vapor or deliberate misuse by concentrating and inhaling may be harmful or fatal. Avoid breathing vapor or spray mist. Provide plenty of fresh air by opening doors and windows or use explosion proof ventilation equipment. If you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. Avoid contact with skin and eyes. Do not transfer contents to bottles or unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

EXTRA FLAMMABLE VAPOR HARMFUL
HARMFUL OR FATAL IF SWALLOWED
SUNNSIDE THINNER VAPORS MAY CAUSE FLASH FIRE
See Safety Data Sheet on the container

32 FL. OZ. (1 QT.) ■ 9463 LITER

SUNNSIDE
CORPORATION
10000 W. 10TH AVENUE
DENVER, CO 80231



LACQUER
THINNER



LACQUER
THINNER

lacquer thinner

for use with the finest lacquers & epoxies

Specially formulated.

EXTREMELY FLAMMABLE VAPOR HARMFUL OR FATAL IF SWALLOWED

SON & EYE IRRITANT VAPORS MAY CAUSE FLASH FIRE
REFLOZ (101) ■ 9463 L

Sunbyside Lacquer Thinner is a premium quality product, formulated for general use with a variety of high quality lacquers and epoxies. It has a medium evaporation rate and can be retarded to control dusting. Because temperature and humidity affect finish characteristics of lacquer, always test prior to staining. NOTE: Lacquer thinner may be harmful to synthetic materials. Avoid contact or test for possible damage before using.

Safety Note: Do not attempt to start or rekindle charcoal, wood or any other fire with this product. Keep away from fire, heat and sparks. Fire may flash back into the can and explode.

Caution: CONTAINS TOLUENE, ACETONE, ETHYL ACETATE, ISOPROPYL ALCOHOL AND PETROLEUM DISTILLATES. Keep away from heat, sparks and flame. Vapors may ignite explosively if allowed to accumulate. Avoid rubbing, friction may cause static electric sparks. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, fans, electric motors, and all other sources of ignition during use and until all vapors are gone.

Health Hazard: Repeated or prolonged overexposure to solvent vapor or deliberate misuse by concentrating and inhaling may be harmful or fatal. Avoid breathing vapor or spray mist. Provide plenty of fresh air by opening doors and windows or use explosion proof ventilation equipment. If you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. Avoid contact with skin and eyes. Do not transfer contents to bottles or unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention, for skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN

SUNBYSIDE CORPORATION
10000 W. 10th St.
Overland Park, KS 66210
Manufactured in U.S.A.




EXHIBIT #: 13

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

71

**BACK PANEL
LACQUER THINNER 457**

January 22, 1992

Sunnyside Lacquer Thinner is a premium quality product, formulated for general use with a variety of high quality lacquers and epoxies. It has a medium evaporation rate and can be retarded to control blushing. Because temperature and humidity affect finish characteristics of lacquer, always test prior to starting.

Cautions: CONTAINS TOLUENE, ACETONE, ETHYL ACETATE, ISOPROPYL ALCOHOL AND PETROLEUM DISTILLATES. Keep away from heat, sparks and flame. Vapors may ignite explosively. Prevent vapor build-up. Open all doors and windows to provide plenty of fresh air equal to outdoor conditions. Do not use without fresh air ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Avoid rubbing; friction may cause static electric sparks which may ignite vapors. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention. Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode.

Health Hazards. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air. ...

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

**Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.**

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090

UPC Codes
0 76542 00019-8-QT
0 76542 00014-3-GAL
0 76542 00017-4-PT

72

SIDE PANEL
LACQUER THINNER 457

January 22, 1992

Add Recycle Symbol

**LACQUER
THINNER**

**WARNING: This product contains
a chemical(s) known to the state of
California to cause cancer or birth defects
or other reproductive harm.**

**California SCAQMD Rule 443.1
Max. VOC: 794 g/L
Max. Vapor Pressure
of VOC: 181 mmHg
Non-photochemically Reactive**

73

FRONT PANEL
LACQUER THINNER 457

January 22, 1992

sunnyside
lacquer
thinner

Specially formulated

for use
with the
finest lacquers
and epoxies

DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR.
HARMFUL OR FATAL IF SWALLOWED.
VAPOR HARMFUL. SKIN AND EYE IRRITANT.
VAPORS MAY CAUSE FLASH FIRE.

Carefully read and follow all cautions elsewhere on this container.

32 FL. OZ. (1 QT.) .9463 LITER
ONE GALLON 3.785 LITERS
16 FL. OZ. (1 PT.) .473 LITER

74

EXHIBIT #: 14

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

75

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

- Date of Prep: 7/1/89

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

FOR INFORMATION: (708) 541-5700

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

Product Class: Alcohol-mixture Manufacturer's Code: 834
Trade Name: DENATURED ALCOHOL SOLVENT NPCA HMIS: H1 F3 R0

Product Appearance and Odor: Clear, colorless liquid; characteristic alcohol odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH	ACGIH	OSHA	OSHA	VAPOR PRESSURE
			TLV (TWA)	TLV (STEL)	PEL (TWA)	PEL (STEL)	
Ethyl Acetate	141-78-6		400 PPM		400 PPM		86 MM Hg @ 20° C.
Ethyl Alcohol	64-17-5		1000 PPM		1000 PPM		40 MM Hg @ 55° F.
Heptane	142-82-5		400 PPM	500 PPM	400 PPM	500 PPM	Approx. 50 MM Hg @ 25° C.
Methyl Isobutyl Ketone	108-10-1		50 PPM	75 PPM	50 PPM	75 PPM	0.75 MM Hg @ 50° F.
Methyl Alcohol	67-56-1		200 PPM (SKIN)	250 PPM	200 PPM (SKIN)	250 PPM	96 MM Hg @ 20° C.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

POISON! GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: Remove to fresh air. If breathing has stopped, administer artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen.

EYES: Flush eyes immediately with water for at least 15 minutes. Get medical attention.

SKIN: Flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation persists.

INGESTION: If swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	165° F. (I.B.P.)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	100 %
Weight Per Gallon:	6.78 Lbs.		
Solubility in Water:	Complete		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification:	Flammable liquid Class IB.
Flash Point:	56° F. Tag. Closed Cup
Lower Explosive Limit:	3.5% @ 77° F.
Extinguishing Media:	Water spray, dry chemical, CO2, "Alcohol" Foam.
Unusual Fire and Explosion Hazards:	Flammable liquid. Vapors are heavier than air and may travel considerable distance to a source of ignition and flash back.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Water may be ineffective for fire fighting, use water spray to keep fire-exposed containers cool.

76

SECTION 6 -- HEALTH HAZARD DATA

**THRESHOLD LIMIT VALUE:
EFFECTS OF EXPOSURE:**

See Section 2.
Prolonged exposure to excessive concentrations of ethanol may result in irritation of mucous membranes, headache, drowsiness, fatigue and narcosis. Methanol is also narcotic in effect and its effects are cumulative. Overexposure to methanol can result in acidosis and visual disturbances which may progress to permanent loss of vision.

Routes of Exposure:

Inhalation: May be harmful if inhaled.
Skin: May be harmful if absorbed through the skin.
Eyes: Liquid or vapor may cause irritation.
Ingestion: May be fatal or cause blindness if swallowed.

SECTION 7 -- REACTIVITY DATA

Stability: Stable
Conditions to Avoid: Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid): Oxidizing materials can cause a vigorous reaction.
Hazardous Decomposition Products: Combustion will produce carbon dioxide and probably carbon monoxide.
Hazardous Polymerization: Will not occur.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Eliminate all ignition sources. Small spills may be collected with absorbent materials. For large spills flush area with water spray, prevent run off from entering drains, sewers or streams.

Waste disposal method: Incinerate under safe conditions, observe all federal, state and local laws concerning health and environment.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: An appropriate NIOSH-approved respirator for organic vapor should be worn if needed.
Ventilation: Recommend at least ten air changes per hour for good general room ventilation.
Protective Gloves: Solvent resistant protective gloves.
Eye Protection: Safety glasses should be worn in any industrial operation.
Other Protective Equipment: Safety shower, eye wash, and washing facilities should be available.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category: Flammable Liquid Class IB.
Hygienic Practices: Keep away from heat, sparks and open flame, keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.
Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge.
Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 11 -- ADDITIONAL INFORMATION

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
Methanol	67-56-1	3.6%
Methyl Isobutyl Ketone	108-10-1	1.9%

77

DENATURED
ALCOHOL
SOLVENT



sunnyside

denatured

alcohol solvent

Shellac Thinner.
Alcohol Appliance Fuel.
Cleaning Solvent.

DENATURED
ALCOHOL
SOLVENT




Sunnyside Denatured Alcohol Solvents. Excellent solvent and cleaning properties give this versatile product a wide variety of uses.
Directions for use:
With stains: Use as a reducer, remover and equipment cleanup solvent. Refer to product label for finishing instructions.
As a cleaner: Use on paint, alcohol-free parts, water for windows, glassware, mirrors and porcelain. Add soap if desired. Use undiluted to clean unacquainted jewelry.
On ink stains: Dampen rag with alcohol and wipe stain. Do not soak stain. Repeat until stain is removed. Then wash with soap and water.
As a fuel: Use only in appliances designed to burn liquid alcohol. For use and chafing dish burners must be wick or absorbent material type only. Always use a flame snuffer and be sure flame is out before lighting burner. Small burners should be carefully filled over a sink, away from any flame or heat. Do not overfill if burner is overfilled, pour off excess alcohol, no sink. Immediately clean up spilled or excess alcohol. Close container and replace burner in stand before lighting burner. When filling an alcohol stove, use a funnel and close fuel tank and can before opening stove.
Safety Note: Alcohol and its vapors are very flammable and burn with a virtually invisible flame. Do not let any alcohol burning device while ignited or hot. Do not attempt to rest or re-handle charcoal, wood or any other fuel with the product. Keep container away from heat, sparks or fire. Fire may flash back into can and explode. Do not use in kerosene or oil burning devices, such as lamps, patio heaters, or fog igniters.

Caution. CONTAINS DENATURED ETHYL ALCOHOL AND LESS THAN 4% METHANOL. Keep away from heat, sparks, and flame. Vapors may ignite explosively if allowed to accumulate. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, fans, electric motors, and all other sources of ignition during use and until all vapors are gone. Avoid contact with eyes or prolonged contact with skin. Avoid breathing vapor or spray mist. Do not transfer contents to bottles or other unlabeled containers. Close container after each use. Do not take internally.

First Aid: In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly. Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

32 FL. OZ. (1 QT.) ■ .9463 LITER



DENATURED
ALCOHOL
SOLVENT



sunmyside

denatured

alcohol solvent

Shellac Thinner.
Alcohol Appliance Fuel.
Cleaning Solvent.

DENATURED
ALCOHOL
SOLVENT



Sunmyside Denatured Alcohol Solvent: Excellent solvent and cleaning
Properties give this versatile product a wide variety of uses.
Directions for use

With etchings: Use as a reducer, remover and equipment cleanup solvent.
Refer to Shellac label for thinning instructions.

As a cleaner: Use one part alcohol—three parts water for windows,
glassware, mirrors and porcelain. Add soap if desired. Use undiluted to clean
unacquired jewelry.

On ink stains: Dampen rag with alcohol and wipe stain. Do not soak stain.
Repeat until stain is removed. Then wash with soap and water.

As a fuel: Use only in appliances designed to burn liquid alcohol. Fondle
and chafing dish burners must be wick or absorbent material type only.
Always use a flame snuffer and be sure flame is out before filling burner. Small
burners should be carefully filled over a sink, away from any flame or heat.

Do not overfill. If burner is overfilled, pour off excess alcohol into sink.
Immediately clean up spilled or excess alcohol. Close container and replace
burner in stand before igniting burner. When filling an alcohol stove, use a
funnel and close fuel tank and can before igniting stove.

Safety Note: Alcohol and its vapors are very flammable and burn with a
vividly visible flame. Do not fill any alcohol burning device while ignited or
hot. Do not attempt to stain or to kindle charcoal, wood or any other fire with
this product. Keep container away from heat, sparks or fire. Fire may flash
back into can and explode. Do not use in kerosene or oil burning devices,
such as lamps, patio torches or log burners.

Caution: CONTAINS DENATURED ETHYL ALCOHOL AND
LESS THAN 4% METHANOL. Keep away from heat, sparks,
and flame. Vapors may ignite explosively if allowed to
accumulate. Do not smoke. Extinguish all flames and pilot
lights and turn off stoves, heaters, fans, electric motors, and
all other sources of ignition during use and until all vapors are
gone. Avoid contact with eyes or prolonged contact with skin.
Avoid breathing vapor or spray mist. Do not transfer contents
to bottles or other unlabeled containers. Close container after
each use. Do not take internally.

First Aid: In case of eye contact, flush thoroughly with water
and get medical attention; for skin contact, wash thoroughly.
Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN

32 FL. OZ. (1 QT.) ■ 9463 LITER



EXHIBIT #: 15

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

74

**BACK PANEL
DENATURED ALCOHOL SOLVENT 834**

January 28, 1992
Susan

Sunnyside Denatured Alcohol Solvent. Directions for use.

As a fuel: Use only in appliances designed to burn liquid alcohol. Fondue and chafing dish burners must be wick or absorbent material type only. Always use a flame snuffer and be sure flame is out before filling burner. Small burners should be carefully filled over a sink, away from any flame or heat. Do not overfill. If burner is overfilled, pour off excess alcohol into sink. Immediately clean up spilled or excess alcohol. Close container and replace burner in stand before igniting burner. When filling an alcohol stove, use a funnel and close fuel tank and can before igniting stove.

Safety Note: Alcohol and its vapors are very flammable and burn with a virtually invisible flame. Do not fill any alcohol burning device while ignited or hot. Do not attempt to start or re-kindle: charcoal, wood or any other fire with this product. Keep container away from heat, sparks or fire. Fire may flash back into can and explode. Do not use in kerosene or oil burning devices, such as lamps, patio torches, or log lighters.

Cautions: CONTAINS DENATURED ETHYL ALCOHOL AND LESS THAN 4% METHANOL. Keep away from heat, sparks and flame. Vapors may ignite explosively. Prevent vapor build-up. Open all doors and windows to provide plenty of fresh air equal to outdoor conditions. Do not use without fresh air ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Avoid rubbing; friction may cause static electric sparks which may ignite vapors. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Health Hazards. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air.

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed, get medical attention immediately. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

**Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.**

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090

UPC Codes
0 76542 00096-3-QT
0 76542 00093-6-GAL
0 76542 00095-0-PT

80

**SIDE PANEL
DENATURED ALCOHOL SOLVENT 834**

January 28, 1992

Add Recycle Symbol

**DENATURED
ALCOHOL
SOLVENT**

**WARNING: This product contains
a chemical(s) known to the state of
California to cause cancer or birth defects
or other reproductive harm.**

**California SCAQMD Rule 443.1
Max. VOC: 815 g/L
Max. Vapor Pressure
of VOC: 40 mmHg
Non-photochemically Reactive**

81

FRONT PANEL
DENATURED ALCOHOL SOLVENT 834

January 28, 1992

sunnyside
denatured alcohol solvent

Shellac Thinner.
Alcohol Appliance Fuel.
Ink Stain Remover.

WARNING!
FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE.
EYE IRRITANT.

Carefully read and follow all cautions elsewhere on this container.

As a fuel, use only as directed.

32 FL. OZ. (1 QT.) .9463 LITER
ONE GALLON 3.785 LITERS
16 FL. OZ. (1 PT.) .473 LITER

82

EXHIBIT #: 16

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

83

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 7/1/89

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

FOR INFORMATION: (708) 541-5700

Product Class: Terpene Hydrocarbons Manufacturer's Code: 870
Trade Name: GUM SPIRITS OF TURPENTINE NPCA HMIS: H1 F3 R0

Product Appearance and Odor: Clear, colorless liquid with characteristic pugnacious odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH	ACGIH	OSHA	OSHA	VAPOR PRESSURE
			TLV (TWA)	TLV (STEL)	PEL (TWA)	PEL (STEL)	
Gum Turpentine	9005-90-7		100 PPM		100 PPM		4 MM Hg @ 20° C.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove victim to fresh air. Get medical attention if irritation persists or for excessive exposures.
EYE CONTACT: Promptly flush eyes with copious quantities of running water for at least 15 minutes. Get medical attention promptly.
SKIN CONTACT: Wash exposed areas with warm water and soap. Remove contaminated clothing promptly (launder before reuse). Get medical attention if irritation persists.
INGESTION: Get medical help promptly. Stomach pumping and lavage may be required. Give edible oil or white mineral oil to drink.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	311-346° F.	Vapor Density:	Heavier Than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	99% +
Weight Per Gallon:	7.20 Lbs.		
Solubility in Water:	Negligible; 0.02% by weight.		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification:	Flammable Liquid - Class IC.
Flash Point:	91° F. (Tag. Closed Cup)
Lower Explosive Limit:	0.8 % (By Volume)
Extinguishing Media:	Carbon Dioxide, dry chemical, or foam. Water may be ineffective.
Unusual Fire and Explosion Hazards:	Do not store or mix with acids or strong oxidants.
Special Fire Fighting Procedures:	When heated, material is a moderate fire and explosion hazard, use water spray to cool fire exposed containers. Firefighters and others exposed to products of combustion should wear self-contained breathing apparatus and full firefighting protective clothing. Dike area to prevent runoff.

84

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 100 PPM (ACGIH Time weighted average.)
EFFECTS OF OVEREXPOSURE
Skin Contact: Can cause dermatitis or chemical burns. It can penetrate the skin to produce systemic effects. Is irritating and damaging. It can cause conjunctivitis or corneal burns. Can irritate the eyes.
Eye Contact: Vapors or mist are irritating and can produce headaches, dizziness, vertigo, chest pain, bronchitis, pulmonary edema, cyanosis, narcosis, accelerated pulse.
Inhalation: May cause predisposition to pneumonia and chronic nephritis. Chronic exposure can produce allergic sensitization. Possibility of teratogenic effects exists for pregnant women.
Chronic Exposure: Not listed by NTP, IARC or OSHA.
Carcinogenicity:

SECTION 7 -- REACTIVITY DATA

Stability: Reasonably stable when stored in a well ventilated, cool place in suitable containers sealed to exclude air.
Conditions to Avoid: Turpentine can undergo autooxidation in air and generate heat which can build up in a confined space, causing spontaneous combustion.
Incompatibility (Materials to Avoid): Acids or acidic materials and strong oxidizing agents.
Hazardous Decomposition Products: Carbon monoxide and/or carbon dioxide.
Hazardous Polymerization: May occur from contamination with acids.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Provide adequate explosion proof ventilation to remove fumes from spill area. Where exposure level is not known, wear NIOSH approved positive pressure self-contained respirator. Personnel should use protection against contact with liquids as well as against breathing vapors. Pick up with absorbent material and place in a waste disposal container. Due to spontaneous combustion hazard, use sand rather than oil dri. Flush area with water.
Waste disposal method: Burning is recommended for waste disposal, using an approved incinerator. Dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: For high exposures use NIOSH approved air line or self-contained respirators. A full face mask is needed to prevent eye irritation from vapors. NIOSH approved organic-vapor respirator may be used for low exposure levels.
Ventilation: Good enclosure and local exhaust. Ventilation should be used to maintain air concentrations below occupational exposure limits.
Protective Gloves: Wear impervious gloves to minimize skin contact.
Eye Protection: Wear chemical splash goggles. Provide eye bath.
Other Protective Equipment: Provide safety shower in area of use.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category: Flammable liquid - Class 1C.
Hygienic Practices: Store in well ventilated, cool dry place away from sources of heat and ignition. No smoking in areas of storage or use.
Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge.
Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

**PURE GUM
SPIRITS OF
TURPENTINE**



**sunnyside
pure gum
spirits of
turpentine**

Paint & varnish thinner.
Versatile cleaning solvent.



**PURE GUM
SPIRITS OF
TURPENTINE**

78


Sunnyside Pure Gum Spirits of Turpentine is a clear, water-white solvent obtained from the sap of living pine trees. It is an excellent thinner for paints and varnishes, and is useful for cleaning paint brushes and equipment and for general cleanup after painting. As a solvent, it cleans woodwork, wood furniture, stoves, bathtubs, tools and machinery. To insure the uniformity and chemical purity of this turpentine, the raw gum has been refined by carefully controlled distillation methods, resulting in a quality finished product, free of adulterants, and conforming to government and commercial standards.

NOTE: Turpentine may be harmful to some plastics, synthetic fabrics and the like. Always test on sample before allowing contact.
Meets Federal Specification TTT-801

Caution. CONTAINS PURE GUM SPIRITS OF TURPENTINE. Keep away from heat and flame.
Health Hazard. Repeated and prolonged overexposure to turpentine vapor or deliberate misuse by concentrating and inhaling may be harmful or fatal. Avoid breathing vapor or spray mist. Provide plenty of fresh air by opening doors and windows or use explosion proof ventilation equipment. If you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. Avoid contact with eyes and skin. Do not transfer contents to bottles or unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Give 1 or 2 glasses of water or milk and CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush with plenty of water for 15 minutes and get medical attention for skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention.
Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.

32 FL. OZ. (1 QT.) ■ 9463 LITER



PURE GUM
SPIRITS OF
TURPENTINE



sunnyside pure gum spirits of turpentine

Paint & varnish thinner
Versatile cleaning solvent.



PURE GUM
SPIRITS OF
TURPENTINE

38

Sunnyside Pure Gum Spirits of Turpentine is a clear, water-white solvent obtained from the sap of living pine trees. It is an excellent thinner for paints and varnishes, and is useful for cleaning paint brushes and equipment and for general cleanup after painting. As a solvent, it cleans woodwork, wood furniture, sinks, bathtubs, tools and machinery. To insure the uniformity and chemical purity of this turpentine, the Sunnyside Pure Gum has been refined by carefully controlled distillation methods, resulting in a quality finished product, free of adulterants, and conforming to government and commercial standards.

NOTE: Turpentine may be harmful to some plastics, synthetic fabrics and the
Always test on sample before allowing contact.
Meets Federal Specification TTT-801

Caution. CONTAINS PURE GUM SPIRITS OF TURPENTINE. Keep away from heat and flame.
Health Hazard: Repeated and prolonged overexposure to turpentine vapor or deliberate misuse by concentrating and inhaling may be harmful or fatal. Avoid breathing vapor or spray mist. Provide plenty of fresh air by opening doors and windows or use explosion proof ventilation equipment. If you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. Avoid contact with eyes and skin. Do not transfer contents to bottles or unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Give 1 or 2 glasses of water or milk and CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush with plenty of water for 15 minutes and get medical attention, for skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention.
Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN

32 FL. OZ. (1 QT.) ■ 9463 LITER




EXHIBIT #: 17

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

87

**BACK PANEL
GUM TURPENTINE 870**

January 22, 1992
Susan

Sunnyside Pure Gum Spirits of Turpentine is derived from the sap of living pine trees and is the oldest known paint solvent. It has unique solvent properties, making it an excellent thinner for oil based paints and varnishes, and it is an effective clean-up solvent for painting equipment.

NOTE: Rags or other waste materials containing turpentine, paint or varnish are subject to spontaneous combustion (may ignite without an ignition source such as a spark or flame). To avoid possible fire hazard, promptly discard waste materials in a water filled, closed metal container.

Turpentine may be harmful to some plastics, synthetic fabrics and tile. Always test on sample before allowing contact.

Meets Federal Specification TT-T-801

CAUTIONS: CONTAINS PURE GUM SPIRITS OF TURPENTINE. Keep away from heat, sparks and flame. Do not use without fresh air ventilation. Do not smoke. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention. Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode.

Health Hazards. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air.

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed, do not induce vomiting. Give 1 or 2 glasses of water or milk and CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush with plenty of water for 15 minutes and get medical attention; for skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention.

**Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.**

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090

UPC Codes
0 76542 00109-1-QT
0 76542 00107-2-GAL
0 76542 00108-4-PT

88

**SIDE PANEL
GUM TURPENTINE 870**

January 22, 1992

Add Recycle Symbol

**PURE GUM SPIRITS OF
TURPENTINE**

**California SCAQMD Rule 443.1
Max. VOC: 965 g/L
Max. Vapor Pressure
of VOC: 4 mmHg
Photochemically Reactive**

89

FRONT PANEL
GUM TURPENTINE 870

January 22, 1992

sunnyside
pure gum spirits of
turpentine

Paint & Varnish Thinner
Versatile Cleaning Solvent.

DANGER!

VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
FLAMMABLE LIQUID AND VAPOR.
SKIN AND EYE IRRITANT.

Carefully read and follow all cautions elsewhere on this container.

32 FL. OZ. (1 QT.) .9463 LITER
ONE GALLON 3.785 LITERS
16 FL. OZ. (1PT.) .473 LITERS

90

EXHIBIT #: 18

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

a1

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 3/11/91

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

FOR INFORMATION: (708) 541-5700

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

Product Class:
Trade Name:

Terpene Hydrocarbons
**STEAM DISTILLED WOOD
TURPENTINE**

Manufacturer's Code:
NPCA HMIS:

876
H2 F3 R0

Product Appearance and Odor: Clear, colorless liquid with characteristic pugnacious odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH	ACGIH	OSHA	OSHA	VAPOR PRESSURE
			TLV (TWA)	TLV (STEL)	PEL (TWA)	PEL (STEL)	
Turpentine	8006-64-2		100 PPM		100 PPM		4 MM Hg @ 20° C.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

INHALATION:
EYE CONTACT:
SKIN CONTACT:

Remove victim to fresh air. Get medical attention if irritation persists or for excessive exposures.
Promptly flush eyes with copious quantities of running water for at least 15 minutes. Get medical attention promptly.
Wash exposed areas with warm water and soap. Remove contaminated clothing promptly (launder before reuse). Get medical attention if irritation persists.

INGESTION:

Get medical help promptly. Stomach pumping and lavage may be required. Give edible oil or white mineral oil to drink.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range: 311-345° F.
Evaporation Rate: Slower than ether
Weight Per Gallon: 7.20 Lbs.
Solubility in Water: Negligible; 0.02% by weight.

Vapor Density: Heavier Than air
% Volatile By Volume: 99% +

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification:
Flash Point:
Lower Explosive Limit:
Extinguishing Media:
Unusual Fire and Explosion Hazards:

Flammable Liquid - Class IC.
91° F. (Tag, Closed Cup)
0.8 % (By Volume)
Carbon Dioxide, dry chemical, or foam. Water may be ineffective.
Do not store or mix with acids or strong oxidants.

Special Fire Fighting Procedures:

When heated, material is a moderate fire and explosion hazard, use water spray to cool fire exposed containers. Firefighters and others exposed to products of combustion should wear self-contained breathing apparatus and full firefighting protective clothing. Dike area to prevent runoff.

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:
EFFECTS OF OVEREXPOSURE
Skin Contact:

100 PPM (ACGIH Time weighted average. STEL is 150 PPM)

Can cause dermatitis or chemical burns. It can penetrate the skin to produce systemic effects.

Eye Contact:

Is irritating and damaging. It can cause conjunctivitis or corneal burns. Can irritate the eyes.

Inhalation:

Vapors or mist are irritating and can produce headaches, dizziness, vertigo, chest pain, bronchitis, pulmonary edema, cyanosis, narcosis, accelerated pulse.

Ingestion:

Can produce nausea, serious illness or even death.

Chronic Exposure:

May cause predisposition to pneumonia and chronic nephritis. Chronic exposure can produce allergic sensitization. Possibility of teratogenic effects exists for pregnant women.

Carcinogenicity:

Not listed by NTP, IARC or OSHA.

SECTION 7 -- REACTIVITY DATA

Stability: Reasonably stable when stored in a well ventilated, cool place in suitable containers sealed to exclude air.

Conditions to Avoid: Turpentine can undergo autooxidation in air and generate heat which can build up in a confined space, causing spontaneous combustion.

Incompatibility (Materials to Avoid): Acids or acidic materials and strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide and/or carbon dioxide.

Hazardous Polymerization: May occur from contamination with acids.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Provide adequate explosion proof ventilation to remove fumes from spill area. Where exposure level is not known, wear NIOSH approved positive pressure self-contained respirator. Personnel should use protection against contact with liquids as well as against breathing vapors. Pick up with absorbent material and place in a waste disposal container. Due to spontaneous combustion hazard, use sand rather than oil dri. Flush area with water.

Waste disposal method: Burning is recommended for waste disposal, using an approved incinerator. Dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: For high exposures use NIOSH approved air line or self-contained respirators. A full face mask is needed to prevent eye irritation from vapors. NIOSH approved organic-vapor respirator may be used for low exposure levels.

Ventilation: Good enclosure and local exhaust ventilation should be used to maintain air concentrations below occupational exposure limits.

Protective Gloves: Wear impervious gloves to minimize skin contact.

Eye Protection: Wear chemical splash goggles. Provide eye bath.

Other Protective Equipment: Provide safety shower in area of use.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category: Flammable liquid - Class 1C.

Hygienic Practices: Store in well ventilated, cool dry place away from sources of heat and ignition. No smoking in areas of storage or use.

Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge.

Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

97

STEAM
DISTILLED
TURPENTINE



sunnyside

steam distilled

wood

turpentine

For thinning paint & varnish.
For many cleaning uses.

STEAM
DISTILLED
TURPENTINE



Sunnyside Steam Distilled Wood Turpentine is a sparkling, crystal clear liquid with characteristic terpene odor. In both quality and performance it is comparable to or exceeds turpentine of other grades. Superior solvent characteristics and proper drying rate make turpentine an excellent thinner for paints, varnishes and enamels. It is also recommended for general clean-up of brushes and equipment after painting, and for removal of grease, oil and tar from metal surfaces.

NOTE: Turpentine may be harmful to some plastics, synthetic fabrics and tile. Always test on sample before allowing contact.


Complies fully with Federal Specification TT-1-901

Caution. CONTAINS STEAM DISTILLED WOOD TURPENTINE. Keep away from heat and flame.
Health Hazard. Repeated and prolonged overexposure to turpentine vapor or deliberate misuse by concentrating and inhaling may be harmful or fatal. Avoid breathing vapor or spray mist. Provide plenty of fresh air by opening doors and windows or use explosion proof ventilation equipment. If you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. Avoid contact with eyes and skin. Do not transfer contents to bottles or unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Give 1 or 2 glasses of water or milk and CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush with plenty of water for 15 minutes and get medical attention—for skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention.

Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.

32 FL. OZ. (1 QT.) ■ .9463 LITER



STEAM
DISTILLED
TURPENTINE



sunmyside

steam distilled
wood
turpentine

For thinning paint & varnish.
For many cleaning uses.

32 FL. OZ. (1 QT.) ■ 9463 LITER

STEAM
DISTILLED
TURPENTINE



Sunmyside Steam Distilled Wood Turpentine is a sparkling, crystal clear liquid with characteristic terpene odor. In both quality and performance it is comparable to or exceeds turpentine of other origins. Superior solvent characteristics and proper drying rate make turpentine an excellent thinner for paints, varnishes and enamels. It is also recommended for general clean-up of brushes and equipment after painting, and for removal of grease, oil and tar from metal surfaces.

NOTE: Turpentine may be harmful to some plastics, synthetic fabrics and tile. Always test on sample before allowing contact.

Complies fully with Federal Specification TT-T-901

Caution: CONTAINS STEAM DISTILLED WOOD TURPENTINE. Keep away from heat and flame.

Health Hazard. Repeated and prolonged overexposure to turpentine vapor or deliberate misuse by concentrating and inhaling may be harmful or fatal. Avoid breathing vapor or spray mist. Provide plenty of fresh air by opening doors and windows or use explosion proof ventilation equipment. If you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. Avoid contact with eyes and skin. Do not transfer contents to bottles or unlabeled containers. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Give 1 or 2 glasses of water or milk and CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush with plenty of water for 15 minutes and get medical attention. For skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention.

Use only with adequate ventilation
KEEP OUT OF REACH OF CHILDREN




EXHIBIT #: 19

DATE: 02-04-92

**FIRM: Sunnyside Corporation
255 Carpenter Avenue
Wheeling, Illinois 60090**

CASE #:

INVESTIGATOR: PCF

95

**BACK PANEL
STEAM DISTILLED WOOD TURPENTINE 876**

January 22, 1992
Susan

Sunnyside Steam Distilled Wood Turpentine is a sparkling, crystal clear liquid with characteristic terpene odor. In both quality and performance it is comparable to or exceeds turpentine of other origins. Superior solvent characteristics and a proper drying rate make turpentine an excellent thinner for paints, varnishes, and enamels. It is also recommended for general clean-up of brushes and equipment after painting, and for removal of grease, oil and tar from metal surfaces.

NOTE: Rags or other waste materials containing turpentine, paint or varnish are subject to spontaneous combustion (may ignite without an ignition source such as a spark or flame). To avoid possible fire hazard, promptly discard waste materials in a water filled, closed metal container.

Turpentine may be harmful to some plastics, synthetic fabrics and tile. Always test on sample before allowing contact.

Meets Federal Specification TT-T-801

CAUTIONS: CONTAINS STEAM DISTILLED WOOD TURPENTINE. Keep away from heat, sparks and flame. Do not use without fresh air ventilation. Do not smoke. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention. Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode.

Health Hazards. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air.

Note. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

First Aid: If swallowed, do not induce vomiting. Give 1 or 2 glasses of water or milk and CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush with plenty of water for 15 minutes and get medical attention; for skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention.

**Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.**

For questions or comments
about this product call:
1-800-323-8611
SUNNYSIDE CORPORATION

Consumer Products Division
Wheeling, IL 60090

UPC Codes
0 76542 -00123-2 QT
0 76542 -00121-8 GAL
0 76542 -00122-5 PT

ab

SIDE PANEL
STEAM DISTILLED WOOD TURPENTINE 876

January 22, 1992

Add Recycle Symbol

**STEAM DISTILLED WOOD
TURPENTINE**

California SCAQMD Rule 443.1
Max. VOC: 865 g/L
Max. Vapor Pressure
of VOC: 4 mmHg
Photochemically Reactive

97