

CEXP**PURPOSE**

Compute the real or complex component of the exponential function for a complex number.

SYNTAX 1

LET <yr> = CEXP(<xr>,<xc>) <SUBSET/EXCEPT/FOR qualification>
 where <xr> is a number, parameter, or variable that specifies the real component of the the complex number;
 <xc> is a number, parameter, or variable that specifies the complex component of the the complex number;
 <yr> is a variable or a parameter (depending on what <xr> and <xc> are) where the real component of the computed exponential value is stored;
 and where the <SUBSET/EXCEPT/FOR qualification> is optional.

This syntax computes the real component of the complex exponential function.

SYNTAX 2

LET <yc> = CEXP(<xr>,<xc>) <SUBSET/EXCEPT/FOR qualification>
 where <xr> is a number, parameter, or variable that specifies the real component of the the complex number;
 <xc> is a number, parameter, or variable that specifies the complex component of the the complex number;
 <yc> is a variable or a parameter (depending on what <xr> and <xc> are) where the complex component of the computed exponential value is stored;
 and where the <SUBSET/EXCEPT/FOR qualification> is optional.

This syntax computes the complex component of the complex exponential function.

EXAMPLES

```
LET AR = CEXP(14,-2)
LET AC = CEXPI(14,-2)
LET XR = CEXP(XR,XC)
LET XC = CEXPI(XR,XC)
```

NOTE

DATAPLOT uses the Fortran intrinsic function CEXP to compute this function.

DEFAULT

None

SYNONYMS

None

RELATED COMMANDS

EXP	=	Compute the exponential of a real number.
CCOS	=	Compute the real component of the cosine of a complex number.
CCOSI	=	Compute the complex component of the cosine of a complex number.
CLOG	=	Compute the real component of the logarithm of a complex number.
CLOGI	=	Compute the complex component of the logarithm of a complex number.
CSIN	=	Compute the real component of the sine of a complex number.
CSINI	=	Compute the complex component of the sine of a complex number.
CSQRT	=	Compute the real component of the square root of a complex number.
CSQRTI	=	Compute the complex component of the square root of a complex number.

APPLICATIONS

Elementary functions

IMPLEMENTATION DATE

94/10

PROGRAM

```

X1LABEL SOLID = REAL COMPONENT
X2LABEL DASH = COMPLEX COMPONENT
LINE SOLID DASH
MULTILOT 2 2; MULTILOT CORNER COORDINATES 0 0 100 100
LET C = 1
TITLE CEXP, COMPLEX COMPONENT = ^C
PLOT CEXP(X,C) FOR X = -3 0.01 3 AND
PLOT CEXPI(X,C) FOR X = -3 .01 3
LET C = -1
TITLE CEXP, COMPLEX COMPONENT = ^C
PLOT CEXP(X,C) FOR X = -3 0.01 3 AND
PLOT CEXPI(X,C) FOR X = -3 .01 3
LET C = 2
TITLE CEXP, COMPLEX COMPONENT = ^C
PLOT CEXP(X,C) FOR X = -3 0.01 3 AND
PLOT CEXPI(X,C) FOR X = -3 .01 3
LET C = -2
TITLE CEXP, COMPLEX COMPONENT = ^C
PLOT CEXP(X,C) FOR X = -3 0.01 3 AND
PLOT CEXPI(X,C) FOR X = -3 .01 3
END OF MULTILOT

```

