

Transport Compartment Blend Calculations

| Total Quantity Desired | 90% | 10% | 45% |
|---------------------------------------|------------|------------|------------|
| 1000 | 900 | 100 | 450 |
| 1100 | 990 | 110 | 495 |
| 1200 | 1080 | 120 | 540 |
| 1300 | 1170 | 130 | 585 |
| 1400 | 1260 | 140 | 630 |
| 1500 | 1350 | 150 | 675 |
| 1600 | 1440 | 160 | 720 |
| 1700 | 1530 | 170 | 765 |
| 1800 | 1620 | 180 | 810 |
| 1900 | 1710 | 190 | 855 |
| 2000 | 1800 | 200 | 900 |
| 2100 | 1890 | 210 | 945 |
| 2200 | 1980 | 220 | 990 |
| 2300 | 2070 | 230 | 1035 |
| 2400 | 2160 | 240 | 1080 |
| 2500 | 2250 | 250 | 1125 |
| 2600 | 2340 | 260 | 1170 |
| 2700 | 2430 | 270 | 1215 |
| 2800 | 2520 | 280 | 1260 |
| 2900 | 2610 | 290 | 1305 |
| 3000 | 2700 | 300 | 1350 |
| 3100 | 2790 | 310 | 1395 |
| 3200 | 2880 | 320 | 1440 |
| 3300 | 2970 | 330 | 1485 |
| 3400 | 3060 | 340 | 1430 |
| 3500 | 3150 | 350 | 1575 |

To blend midgrade from regular and premium, use
45% subgrade + 45% premium + 10% ethanol