

EXPLANATION


| | |
|---|--|
| Reich Farm NPL Site | Water pipeline |
| Ciba-Geigy NPL Site | Major road |
| Dover Township | Hydrography |
| Water body | Municipal well |
| | Storage tank |

E Pipeline location and letter. Percent contribution is reported in text

Percentage of water contributed by Route 70 well (31), 24-hour average

| | |
|---|--|
| 1 to 10 | 50 to 75 |
| 10 to 25 | 75 to 90 |
| 25 to 50 | 90 to 100 |

Notes: (1) Water pipelines range in diameter from 2 inches to 16 inches
 (2) Roads, hydrography, and boundaries based on 1995 TIGER/Line data
 (3) Pipeline from water-utility database (Flegal 1997)
 (4) Percentage of water based on model reaching dynamic equilibrium after 1,200 hours of simulation time



**Dover Township Area, New Jersey
 Water-Distribution System Model
 Historical Reconstruction Analysis**

Maslia ML, Sautner JB, Aral MM, Gillig RE, Reyes JJ, Williams RC. 2001. Historical reconstruction of the water-distribution system serving the Dover Township area, New Jersey: January 1962–December 1996. Atlanta: Agency for Toxic Substances and Disease Registry.

PLATE 121. AREAL DISTRIBUTION OF SIMULATED PROPORTIONATE CONTRIBUTION OF WATER FROM THE ROUTE 70 WELL (31) TO LOCATIONS IN THE DOVER TOWNSHIP AREA, NEW JERSEY, FEBRUARY 1995 CONDITIONS
 By Morris L. Maslia, Jason B. Sautner, Mustafa M. Aral, Richard E. Gillig, Juan J. Reyes, and Robert C. Williams