

PLATE 145. AREAL DISTRIBUTION OF SIMULATED PROPORTIONATE CONTRIBUTION OF WATER FROM THE PARKWAY WELLS (22, 24, 26, 28, 29, 42) TO LOCATIONS IN THE DOVER TOWNSHIP AREA, NEW JERSEY, JUNE 1996 CONDITIONS

By Morris L. Maslia, Jason B. Sautner, Mustafa M. Aral, Richard E. Gillig, Juan J. Reyes, and Robert C. Williams

## **EXPLANATION**

Reich Farm NPL Site Ciba-Geigy NPL Site

**Dover Township** 

Water body

Water pipeline Major road Hydrography Municipal well

Storage tank

E ☐ Pipeline location and letter. Percent contribution is reported in text

> Percentage of water contributed by Parkway wells (22, 24, 26, 28, 29, 42), 24-hour average

> > • 1 to 10 • 10 to 25

• 50 to 75 • 75 to 90

25 to 50

• 90 to 100

Notes: (1) Water pipelines range in diameter from 2 inches to 16 inches (2) Roads, hydrography, and boundaries based on 1995 TIGER/Line data

(3) Pipeline from water-utility database (Flegal 1997)

(4) Percentage of water based on model reaching dynamic equilibrium after 1,200 hours of simulation time

> 2 MILES 1.5



## **Dover Township Area, New Jersey Water-Distribution System Model Historical Reconstruction Analysis**

Maslia ML, Sautner JB, Aral MM, Gillig RE, Reyes JJ, Williams RC. 2001. Historical reconstruction of the water-distribution system serving the Dover Township area, New Jersey: January 1962-December 1996. Atlanta: Agency for Toxic Substances and Disease Registry.