CONTRACT TENDER - INCIDENT INSPECTION FORM								
CONTRACTOR: (Including Unique Tender #)	AGREEMENT NO:	RESOURCE E -		DATE:				
	ORDER NO:			TIME:				
INCIDENT NAME:	INCIDENT NO:	VIN NUMBER:	LICENSE NO:					
POINT OF HIRE:	TENDER TYPE:	GALLONS:	DAILY RATE:					
WTOP-OPERATOR NAME &ID NUMBER:	DRIVER LICENSE NO:	CDL LICENSE NO:	MEDICAL CARD:					
WTOP OPERATOR NAME &ID NUMBER:	DRIVER LICENSE NO:	CDL LICENSE NO:	MEDICAL CARD:					
MINIMUM TENDER INVENTORY				PRE-USE RELEASE YES NO YES NO				
1 – 1 ½" NOZZLE NH COMBINATION FOG/STRAIGHT STREAM						-,,		
1 – 1 ½" NH FEMALE TO 1" NPSH MALE REDUCER								
2 – ADAPTERS 1 ½" NPSH FEMALE TO 1 ½" NH MALE								
2 - ADAPTERS, ¼ TURN TO 1 ½" NH (1 FEMALE and 1 MALE)								
2 – ADAPTERS 1 ½" NH FEMALE TO 1 ½" NPSH MALE								
2 – REDUCERS 2 ½" NH FEMALE TO 1 ½" NH MALE								
1 – DOUBLE MALE 1 ½" NH								
1 – DOUBLE FEMALE 1 ½" NH								
1 – GATED WYE 1 ½" NH	NIED OD CODEENIED FOOT	NAL ME						
HOSE - 20' SUCTION (MINIMUM)W/STRAINER OR SCREENED FOOT VALVE								
HOSE – 100' OF 1 ½" COTTON/SYNTHETIC HOSE NH THREAD  HOSE – 50' OF 2 ½" COTTON/SYNTHETIC HOSE NH								
1 – SPANNER WRENCH, COMBINATION 1								
1 – SPANNER WRENCH, COMBINATION 1 ½ to 2 ½ **  1 – ADJUSTABLE HYDRANT WRENCH								
1 – FIRE HOSE CLAMP 1 ½"								
2 DISCHARGE OUTLETS 1/12"NH								
1 DISCHARGE OUTLET 2 ½" NH								
4" GRAVITY DUMP VALVE REAR OF TAN								
2 1/2" RAPID SHUT-OFF VALVE NH								
1 – HANDHELD PROGRAMMABLE RADIO								
MAKE: SERIAL								
REFLECTIVE TRIANGLES, BI-DIRECTIONAL, SET OF 3								
FIRE EXTINGUISHER, (1A-10BC OR BETTER)								
2 – PORTABLE HAND LIGHTS 1 – FIRST AID KIT (5 PERSON)								
1 – FIRST AID KIT (5 PERSON) 1 – SHOVEL, SIZE 0 OR 1								
1 – SHOVEL, SIZE 0 OR 1 1 – PULASKI								
2 – WHEEL CHOCKS (NFPA 1906 STANDARDS)								
SPRAY BAR or EQUIVALENT – PUMP or PTO and/or GRAVITY on FRONT and/or REAR								
FUEL TO OPERATE PUMP FOR 12 HOURS (IF AUXILIARY PUMP)								
VEHICLE IDENTIFICATION: (INCLUDING COMPANY NAME AND UNIQUE ID #)								
BACKUP ALARM (REVERSE WARNING DEVICE ACTIVATED WHEN VEHICLE IS PUT INTO								
REVERSE. NO OTHER SWITCHES TO ACTIVAT		·						
	TECTIVE EQUIPMEN	T	PRE		RELI			
	ERATOR or CREWMEMBER)		YES	NO	YES	NO		
FIRE SHELTER: National Fire Protection Association	on (NFPA) Approved.							
2 CONTAINERS – 1 Quart Minimum Per Person  BOOTS: Leather, lace-up type. Minimum 8" with Lug Soles (Steel Toed Boots are Not Acceptable)								
HARDHAT: (w/Chin Strap) 1 PER PERSON MEETING NFPA STANDARD 1998 EDITION								
GLOVES: LEATHER - 1 PAIR PER PERSON								
EYE PROTECTION: One Pair (Meets Standards ANSI Z87 Latest Edition)								
FLAME RESISTANT CLOTHING (Shirt and Trousers) Two Sets Per Firefighter.								
REMARKS:								
		_						

PRE-USE:		RELEASE:		
		NO DAMAGE	E NO CLAIMS	
DATE:	TIME:	DATE:	TIME:	
INSPECTOR:		INSPECTOR:		
INSPECTOR HOME UNIT:		INSPECTOR HOME UNIT:		
INSPECTOR PHONE NO:		INSPECTOR PHONE NO:		
CONTRACTOR REPRESENTATIVE:		CONTRACTOR REPRESENTATIVE:		
TITLE:		TITLE:		
PHONE NO:		PHONE NO:		