

DaimlerChrysler has advised ODI that Federal Motor Vehicle Safety Standard (FMVSS) No. 207, "Seating Systems," compliance testing was conducted on the T-300 seats used on the subject vehicles. For all model years, the seats used in the Dodge Ram passed the Federal requirements for seat back strength. NHTSA's Office of Vehicle Safety Compliance did not conduct testing on the subject vehicles.

DaimlerChrysler did conduct an FMVSS No. 301, "Fuel System Integrity," rear impact test with instrumented anthropomorphic dummies in both front seat positions at 48 km/h on a Club Cab Dodge Ram. During the test, both front seats collapsed rearward.

DaimlerChrysler has stated that this was part of the designed energy absorption capabilities of the T-300 seating system. The head injury criteria or HIC for the driver dummy was 116 and for the passenger dummy was 120. This is well below the HIC value of 1,000 which is the NHTSA benchmark for measuring serious head injury in other safety standards.

In view of the foregoing, it is unlikely that NHTSA would issue an order for the notification and remedy of the alleged defect as defined by the petitioner at the conclusion of the investigation requested in the petition. Therefore, in view of the need to allocate and prioritize NHTSA's limited resources to best accomplish the agency's safety mission, the petition is denied.

Authority: 49 U.S.C. 30162(d); delegations of authority at CFR 1.50 and 501.8.

Issued on: March 23, 2004.

Kenneth N. Weinstein,

Associate Administrator for Enforcement.

[FR Doc. 04-6902 Filed 3-26-04; 8:45 am]

BILLING CODE 4910-59-P

DEPARTMENT OF TRANSPORTATION

Research and Special Programs Administration

[Docket No. RSPA-04-17375; Notice 1]

Pipeline Safety: Request for Waiver; GulfTerra Field Services LLC

AGENCY: Research and Special Programs Administration (RSPA); U.S. Department of Transportation (DOT).

ACTION: Notice of intent to consider waiver request.

SUMMARY: GulfTerra Field Services LLC (GTFS), requested a waiver of compliance with the regulatory requirements at 49 CFR 192.619(a)(2)(ii), 192.503, and 192.505 for certain

offshore pipeline segments of the deepwater Phoenix Gas Gathering System (Phoenix). GTFS is requesting a waiver from the post-construction hydrotesting requirement for selected segments of the Phoenix system.

DATES: Persons interested in submitting written comments on the waiver request described in this Notice must do so by April 28, 2004. Late filed comments will be considered as far as practicable.

ADDRESSES: You may submit written comments by mailing or delivering an original and two copies to the Dockets Facility, U.S. Department of Transportation (DOT), Room PL-401, 400 Seventh Street, SW., Washington, DC 20590-0001. The Dockets Facility is open from 10 a.m. to 5 p.m., Monday through Friday, except on Federal holidays when the facility is closed. Alternatively, you may submit written comments to the docket electronically at the following web address: <http://dms.dot.gov>.

All written comments should identify the docket and notice numbers stated in the heading of this notice. Anyone who wants confirmation of mailed comments must include a self-addressed stamped postcard. To file written comments electronically, after logging on to <http://dms.dot.gov>, click on "Comment/Submissions." You can also read comments and other material in the docket. General information about the Federal pipeline safety program is available at <http://ops.dot.gov>.

Anyone is able to search the electronic form of all comments received into any of our dockets by the name of the individual submitting the comment (or signing the comment, if submitted on behalf of an association, business, labor union, etc.). You may review DOT's complete privacy Act Statement in the **Federal Register** published on April 11, 2000 (Volume 65, Number 70; Pages 19477-78) or you may visit <http://dms.dot.gov>.

FOR FURTHER INFORMATION CONTACT: James Reynolds by telephone at 202-366-2786, by fax at 202-366-4566, by mail at DOT, Research and Special Programs Administration (RSPA) Office of Pipeline Safety (OPS), 400 7th Street, SW., Washington, DC 20590, or by e-mail at james.reynolds@rspa.dot.gov.

SUPPLEMENTARY INFORMATION:

Background

GTFS, a wholly owned subsidiary of GulfTerra Energy Partners L.P., has entered into a gas gathering agreement with Kerr McGee Oil & Gas Corporation and the Devon Louisiana Corporation to design, build, own, and operate the Phoenix Gas Gathering System

(Phoenix). GTFS will transport natural gas from the Red Hawk Spar, a deepwater production facility, to the Pioneer Platform, an existing downstream pipeline facility.

System Description

The GTFS pipeline will extend 76 miles through Federal waters on the Gulf of Mexico Outer Continental Shelf (OCS) and will cross one shipping channel, known as a "fairway." The pipeline will include a subsea 'wye' and a subsea 'tee' for future interconnections to other pipelines. The planned maximum allowable operating pressure (MAOP) of this pipeline and the associated platform facilities is 2,875 pounds per square inch gauge (psig). The system will normally operate at pressures up to 2,500 psig.

The Phoenix system will consist of the following primary components, in order of occurrence from deep to shallow water:

1. A steel catenary riser (SCR) consisting of 16-inch outside diameter (O.D.) × 1.00-inch wall thickness (w.t.), API 5L X65 seamless pipe, on the Red Hawk Spar at a depth of 5,300 feet. The SCR will be coated with triple-layer polypropylene at the touchdown point and 14 to 16 mils of thin film fusion bonded epoxy (FBE) and 2 to 3 mils of rough coat FBE through the midsection. There will be 23 mils of thin film FBE in the vortex induced vibration (VIV) suppression strake section, and a 1-inch thick sleeve of Splashton coating in the pull-tube;

2. A 76-mile pipeline from the Red Hawk platform to the Vermilion riser (VR). Beginning at the deepwater end, approximately 40 miles of pipe will be 18-inch O.D. × 0.791-inch w.t., API 5L X65 double submerged arch weld (DSAW) pipe, followed by approximately 36 miles of 18-inch O.D. × 750-inch w.t., API 5L DSAW pipe. All joints will be coated with 14 to 16 mils of thin film FBE with an additional 2 to 3 mils of FBE rough coating;

3. An 18-inch diverless, piggable 'wye' assembly downstream of the Red Hawk Spar in Garden Banks to accommodate future connection(s) to the pipeline;

4. An 18-inch O.D. × 16-inch diverless 'tee' assembly in Garden Banks to accommodate future connection(s) to the pipeline; and

5. Pipeline support facilities located on the VR 397 "A" platform, including a pig receiver and related piping and safety controls. The platform riser will be 18-inch O.D. × 0.875-inch w.t., API 5L X60 DSAW pipe coated with 14 to 16 mils of thin film FBE. In the wave (splash zone) area, the riser pipe will be

protected with a 1/2-inch thick sleeve of Splashtron coating.

Need for Hydrotest

GTFSS contends it is unnecessary to hydrostatically test this pipeline. GTFSS asserts that a hydrostatic test will not demonstrate the strength and integrity of the pipeline because the pipeline is designed of heavier wall pipe and it will never experience the wall stress intended to be produced by a hydrotest. The heavier wall pipe is used to prevent the collapse of the pipeline in the face of the huge external pressures exerted on it at a water depth of 5,300 feet.

Proposed Alternative Risk Control Activities

GTFSS proposes the following alternative risk control activities to provide a margin of safety and environmental protection comparable to that required by the pressure-test regulations:

1. Utilize thick wall, high strength, and high quality DSAW pipe;
2. Perform a pipe mill hydrotest on each length of fabricated pipe equivalent to 95% specified minimum yield strength (SMYS) to detect defects in the seam weld and prevent the deployment of defective pipe joints;
3. Perform extensive inspection and quality control during the line pipe manufacture, transport, fabrication, and installation to prevent pipe damage;
4. Utilize Automated Ultrasonic Inspection (AUT) for inspection of offshore welds to improve defect detection in the girth weld and to improve the weld quality during the pipeline and SCR fabrication;
5. Subject all buckle arrestors to complete radiographic and magnetic particle inspection, including radiographic inspection of all buckle arrestor to line pipe welds;
6. Perform complete radiographic inspection and hydrotesting of all welds connecting subsea valves and assemblies to the pipeline;
7. Perform a leak test of the pipeline's subsea tie-in flange that connects to the VR 397 riser flange; and
8. Perform factory acceptance hydrotests of all subsea 'wye', 'tee', ball valve, and check valve assemblies.

Intent To Consider Waiver

Although performing an in situ hydrotest on this pipeline would comply with the plain language of the regulation, GTFSS believes the intent of the regulations cannot be met by hydrostatic testing. Due to the heavier wall thickness requirements and external hydrostatic pressures in deep water, the traditional pipeline

hydrostatic test generates stresses as a percentage of SMYS that are well below those typically experienced in a pipeline test. GTFSS asserts that the hydrostatic test cannot demonstrate the strength or integrity of the system.

Therefore, RSPA/OPS will consider whether a hydrotest of this pipeline is necessary and whether the alternative risk control activities proposed by GTFSS will yield an equivalent or greater degree of safety. This Notice is RSPA/OPS' only request for public comment before making its final decision in this matter. After considering any comments, RSPA/OPS will make a final determination to grant or deny the waiver as proposed or with modifications and conditions. If the waiver is granted and RSPA/OPS subsequently determines that the effect of the waiver is inconsistent with pipeline safety, RSPA/OPS may revoke the waiver at its sole discretion.

Issued in Washington, DC on March 23, 2004.

Stacey L. Gerard,

Associate Administrator for Pipeline Safety.

[FR Doc. 04-6903 Filed 3-26-04; 8:45 am]

BILLING CODE 4910-60-P

DEPARTMENT OF TRANSPORTATION

Research and Special Programs Administration

[Docket No. RSPA-03-16841; Notice 2]

Pipeline Safety: Grant of Waiver; Columbia Gas Transmission

AGENCY: Research and Special Programs Administration (RSPA); Department of Transportation (DOT).

ACTION: Notice; grant of waiver.

SUMMARY: Columbia Gas Transmission requested a waiver of compliance with the regulatory requirements at 49 CFR 192.611(d) which require natural gas pipeline operators to confirm or revise the maximum allowable operating pressure (MAOP) of their natural gas pipelines within 18-months after a class location change.

SUPPLEMENTARY INFORMATION:

Background

Columbia Gas Transmission submitted a request to RSPA's Office of Pipeline Safety (RSPA/OPS) seeking a waiver of compliance with the regulatory requirements at 49 CFR 192.611(d) to confirm or revise the MAOP of its natural gas pipeline within 18-months after a class location change. Two segments of Columbia's Line MC pipeline changed from Class 2 to Class

3 locations. To maintain the current MAOP of 899 psig, Columbia elected to replace 9,500 feet of its pipeline with new, heavier wall pipe. The two segments of the pipeline, totaling approximately 1,700 feet, involve stream crossings or wetland areas. The two segments are 1,506 feet and 200 feet in length, respectively.

Columbia anticipated that 7,800 feet of its replacement project would be complete by October 31, 2003. However, due to unforeseen delays in obtaining joint State/Federal environmental permits for the pipe replacement in stream crossings and wetlands areas, Columbia was unable to complete the replacement of the remaining 1,700 feet of pipe prior to the expiration of the 18-month period allowed by § 192.611(d).

Columbia discontinued its pipe replacement project at the start of the winter heating season and intends to resume the project in May 2004. Columbia expects all 9,500 feet of its Line MC will be replaced not later than July 1, 2004. For this reason, Columbia requested a time extension until July 1, 2004, to comply with § 192.611(d).

Columbia provided the following justification for the waiver of their 30-inch Line MC pipeline:

- The 30-inch pipeline was internally inspected in 1999 using both geometry and high resolution magnetic flux leakage tools; no anomalies or dents were identified on the two pipeline segments in the stream crossing and wetland areas of Line MC.
- The cathodic protection test stations on these two segments of Line MC are above the minimum criteria.
- There have been no leaks on these two segments of Line MC.
- The existing pipe and coating on these two segments of Line MC appear in satisfactory condition.
- The existing Line MC was manufactured using a double submerged arc welding process.
- The existing Line MC was pressure tested twice; in 1962 during construction and again in 1974. The pipeline was tested above 100% specified minimum yield strength during both pressure tests.

After reviewing the waiver request, RSPA/OPS published a notice inviting interested persons to comment on whether a waiver should be granted (Notice 1) (68 FR 66156; Jan. 9, 2004). No comments were received from the public in response to the notice.

For the reasons explained above and those explained in Notice 1, RSPA/OPS finds that the requested waiver is not inconsistent with pipeline safety. Therefore, Columbia Gas's request for a waiver is granted until July 1, 2004.