

10/11/78) and expanded in June 1982 (Board Order 194, 47 FR 27579, 6/25/82); April 1992 (Board Order 574, 57 FR 13694, 4/17/92); February 1997 (Board Order 870, 62 FR 7750, 2/20/97); June 1999 (Board Order 1040, 64 FR 33242, 6/22/99); and, April 2002 (Board Order 1224, 67 FR 20087, 4/15/02). The general-purpose zone project currently consists of the following sites in the Cleveland, Ohio, area: *Site 1* (94 acres)—Port of Cleveland complex on Lake Erie at the mouth of the Cuyahoga River, Cleveland; *Site 2* (128 acres)—the IX Center (formerly the “Cleveland Tank Plant”), in Brook Park, adjacent to the Cleveland Hopkins International Airport; *Site 3* (1,900 acres)—Cleveland Hopkins International Airport complex; *Site 4* (450 acres)—Burke Lakefront Airport, 1501 North Marginal Road, Cleveland; *Site 5* (298 acres)—Emerald Valley Business Park, Cochran Road and Beaver Meadow Parkway, Glenwillow; *Site 6* (30 acres)—Collinwood site, South Waterloo (South Marginal) Road and East 152nd Street, Cleveland; *Site 7* (47 acres)—Water Tower Industrial Park, Coit Road and East 140th Street, Cleveland; *Site 8* (83 acres)—Strongsville Industrial Park, Royalton Road (State Route 82), Strongsville; *Site 9* (13 acres)—East 40th Street between Kelley & Perkins Avenues (3830 Kelley Avenue), Cleveland; and, *Site 10* (15 acres)—Frane Industrial Park, Forman Road, Ashtabula; *Temporary Site 11* (15 acres)—Snow Road Industrial Park, 18901 Snow Road, Brook Park; and, *Temporary Site 12* (32 acres)—Tow Path Valley Business Park, 3060 Eggers Avenue, Cleveland. Applications are pending with the FTZ Board to expand existing Site 3 (Docket 38–2002), and to expand existing Site 1 (Docket 6–2003).

The applicant is now requesting authority to expand existing Site 8 by adding an additional 91 acres within the Strongsville Industrial Park, near the intersection of Foltz Industrial Parkway and Lunn Road, Strongsville. This increases the total acreage at this site to 174 acres. The site is owned by Duke Realty Corp., Astro Instrumentation L.L.C. and Arthur Properties Ltd. The site will provide public warehousing and distribution services to area businesses. It will also offer sites suitable for manufacturing activity, though no specific manufacturing requests are being made at this time. Such requests would be made to the Board on a case-by-case basis.

In accordance with the Board’s regulations, a member of the FTZ Staff has been designated examiner to investigate the application and report to the Board.

Public comment on the application is invited from interested parties. Submissions (original and 3 copies) shall be addressed to the Board’s Executive Secretary at one of the following addresses:

1. Submissions via Express/Package Delivery Services: Foreign-Trade Zones Board, U.S. Department of Commerce, Franklin Court Building—Suite 4100W, 1099 14th Street, NW., Washington, DC 20005.

2. Submissions via the U.S. Postal Service: Foreign-Trade Zones Board, U.S. Department of Commerce, FCB—Suite 4100W, 1401 Constitution Avenue, NW., Washington, DC 20230.

The closing period for their receipt is May 19, 2003. Rebuttal comments in response to material submitted during the foregoing period may be submitted during the subsequent 15-day period (to June 2, 2003).

A copy of the application and accompanying exhibits will be available during this time for public inspection at address Number 1 listed above, and at the U.S. Department of Commerce Export Assistance Center, 600 Superior Avenue East, Suite 700, Cleveland, OH 44114.

Dated: March 10, 2003.

Dennis Puccinelli,

Executive Secretary.

[FR Doc. 03–6482 Filed 3–18–03; 8:45 am]

BILLING CODE 3510–DS–P

DEPARTMENT OF COMMERCE

Bureau of Industry and Security

Materials Technical Advisory Committee; Notice of Partially Closed Meeting

The Materials Technical Advisory Committee will meet on April 8, 2003, 10:30 a.m., Herbert C. Hoover Building, Room 3884, 14th Street between Constitution & Pennsylvania Avenues, NW., Washington, DC. The Committee advises the Office of the Assistant Secretary for Industry and Security with respect to technical questions that affect the level of export controls applicable to materials and related technology.

Agenda

Public Session

1. Opening remarks and introductions.
2. Presentation of papers and comments by the public.
3. Discussion on list of chemicals proposed for the Australia Group control list:
 - Tri-isopropyl phosphite (CAS # 116–17–6)
 - Di-isopropyl phosphite (CAS # 1809–20–7)
 - Methylphosphonic acid (CAS # 993–13–5)
 - Oxalyl chloride [ethanedioyl dichloride] (CAS # 79–37–8)

Diethyl methylphosphonate (CAS # 683–08–9)

N, N-Dimethylamido phosphoryldichloride [dimethylphosphoramidic dichloride] (CAS # 677–43–0)

Thiophosphoryl chloride (CAS # 3982–91–0)

Closed Session

4. Discussion of matters properly classified under Executive Order 12958, dealing with U.S. export control programs and strategic criteria related thereto.

A limited number of seats will be available during the public session of the meeting. Reservations are not accepted. To the extent time permits, members of the public may present oral statements to the Committee. Written statements may be submitted at any time before or after the meeting. However, to facilitate distribution of public presentation materials to Committee members, the materials should be forwarded prior to the meeting to the following address: Ms. Lee Ann Carpenter, OSIES/EA/BIS MS: 3876, U.S. Department of Commerce, 14 St. and Constitution Ave., NW., Washington, DC 20230.

The Assistant Secretary for Administration, with the concurrence of the delegate of the General Counsel, formally determined on February 6, 2002, pursuant to section 10(d) of the Federal Advisory Committee Act, as amended, that the series of meetings or portions of meetings of the Committee and of any Subcommittee thereof dealing with the classified materials listed in 5 U.S.C. 552(c)(1) shall be exempt from the provisions relating to public meetings found in section 10(a)(1) and (a)(3) of the Federal Advisory Committee Act. The remaining series of meetings or portions thereof will be open to the public. For more information, call Lee Ann Carpenter at (202) 482–2583.

Dated: March 14, 2003.

Lee Ann Carpenter,

Committee Liaison Officer.

[FR Doc. 03–6513 Filed 3–18–03; 8:45 am]

BILLING CODE 3510–JT–M

DEPARTMENT OF COMMERCE

International Trade Administration

[A–588–824]

Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Initiation and Preliminary Results of Changed Circumstances Review of the Antidumping Order, and Intent To Revoke Order in Part

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

ACTION: Notice of initiation and preliminary results of changed circumstances antidumping duty review, and intent to revoke order in part.

SUMMARY: In accordance with 751(b) of the Tariff Act of 1930, as amended (“the

Act”) and section 351.216(b) of the Department of Commerce’s (“the Department”) regulations, Nippon Steel (“Nippon”) filed a request for a changed circumstances review of the antidumping order on certain corrosion-resistant carbon steel flat products from Japan with respect to the carbon steel flat products as described below.

Domestic producers of the like product have affirmatively expressed no interest in continuation of the order with respect to these particular products. In response to Nippon’s request, the Department is initiating a changed circumstances review and issuing a notice of intent to revoke in part the antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. Interested parties are invited to comment on these preliminary results.

EFFECTIVE DATE: March 19, 2003.

FOR FURTHER INFORMATION CONTACT:

Catherine Bertrand or Peter Mueller, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, NW., Washington, DC 20230; telephone: (202) 482-3207, and (202) 482-5811, respectively.

SUPPLEMENTARY INFORMATION:

Background

On January 31, 2003, Nippon requested that the Department revoke in part the antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. Specifically, Nippon requested that the Department revoke the order with respect to imports meeting the following specifications: (1) flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as “ASE Iron Flash” and either: (A) Having a base layer of zinc-based zinc-iron alloy applied by hot-dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40 percent by weight of zinc; or (B) two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer of iron-zinc alloy by electro-galvanizing process, having an effective amount of zinc up to 40 percent by weight, and (2) corrosion resistant continuously annealed flat-rolled products, continuous cast, the foregoing with chemical composition (percent by weight): carbon not over 0.06 percent by weight, manganese 0.20 or more but not over 0.40, phosphorus not over 0.02, sulfur not over 0.023, silicon not over 0.03, aluminum 0.03 or more but not over 0.08, arsenic not over

0.02, copper not over 0.08 and nitrogen 0.003 or more but not over 0.008; and meeting the characteristics described below: (A) Products with one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a two-layer coating composed of a base nickel-iron-diffused coating layer and a surface coating layer of annealed and softened pure nickel, with total coating thickness for both layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with scanning electron microscope (SEM) not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (B) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a four-layer coating composed of a base nickel-iron-diffused coating layer; with an inner middle coating layer of annealed and softened pure nickel, an outer middle surface coating layer of hard nickel and a topmost nickel-phosphorus-plated layer; with combined coating thickness for the four layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (C) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, luster-agent-added nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; or (D) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, pure nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length.

Scope of Review

The products covered by the antidumping duty order include flat-rolled carbon steel products, of rectangular shape, either clad, plated, or coated with corrosion-resistant metals such as zinc, aluminum, or zinc-, aluminum-, nickel- or iron-based alloys, whether or not corrugated or painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating, in coils (whether or not in successively superimposed layers) and of a width of 0.5 inch or greater, or in straight lengths which, if of a thickness less than 4.75 millimeters, are of a width of 0.5 inch or greater and which measures at least 10 times the thickness or if of a thickness of 4.75 millimeters or more are of a width which exceeds 150 millimeters and measures at least twice the thickness, as currently classifiable in the HTSUS under item numbers

7210.30.0030, 7210.30.0060, 7210.41.0000, 7210.49.0030, 7210.49.0090, 7210.61.0000, 7210.69.0000, 7210.70.6030, 7210.70.6060, 7210.70.6090, 7210.90.1000, 7210.90.6000, 7210.90.9000, 7212.20.0000, 7212.30.1030, 7212.30.1090, 7212.30.3000, 7212.30.5000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7212.60.0000, 7215.90.1000, 7215.90.3000, 7215.90.5000, 7217.20.1500, 7217.30.1530, 7217.30.1560, 7217.90.1000, 7217.90.5030, 7217.90.5060, 7217.90.5090. Included in this order are corrosion-resistant flat-rolled products of non-rectangular cross-section where such cross-section is achieved subsequent to the rolling process (*i.e.*, products which have been “worked after rolling”)—for example, products which have been beveled or rounded at the edges.

Excluded from this order are flat-rolled steel products either plated or coated with tin, lead, chromium, chromium oxides, both tin and lead (“terne plate”), or both chromium and chromium oxides (“tin-free steel”), whether or not painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating.

Also excluded from this order are clad products in straight lengths of 0.1875 inch or more in composite thickness and of a width which exceeds 150 millimeters and measures at least twice the thickness.

Also excluded from this order are certain clad stainless flat-rolled products, which are three-layered corrosion-resistant carbon steel flat-

rolled products less than 4.75 millimeters in composite thickness that consist of a carbon steel flat-rolled product clad on both sides with stainless steel in a 20%–60%–20% ratio.

Also excluded from this order are certain corrosion-resistant carbon steel flat products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of chromate, and finally a layer consisting of silicate.

Also excluded from this order are carbon steel flat products measuring 1.84 millimeters in thickness and 43.6 millimeters or 16.1 millimeters in width consisting of carbon steel coil (SAE 1008) clad with an aluminum alloy that is balance aluminum, 20% tin, 1% copper, 0.3% silicon, 0.15% nickel, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Also excluded from this order are carbon steel flat products measuring 0.97 millimeters in thickness and 20 millimeters in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% to 11% tin, 9% to 11% lead, less than 1% zinc, less than 1% other materials and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 45% to 55% lead, 38% to 50% PTFE, 3% to 5% molybdenum disulfide and less than 2% other materials.

Also excluded from this order are doctor blades meeting the following specifications: carbon steel coil or strip, plated with nickel phosphorous, having a thickness of 0.1524 millimeters (0.006 inches), a width between 31.75 millimeters (1.25 inches) and 50.80 millimeters (2.00 inches), a core hardness between 580 to 630 HV, a surface hardness between 900–990 HV; the carbon steel coil or strip consists of the following elements identified in percentage by weight: 0.90% to 1.05% carbon; 0.15% to 0.35% silicon; 0.30%

to 0.50% manganese; less than or equal to 0.03% of phosphorous; less than or equal to 0.006% of sulfur; other elements representing 0.24%; and the remainder of iron.

Also excluded from this order are products meeting the following specifications: carbon steel flat products measuring 1.64 millimeters in thickness and 19.5 millimeters in width consisting of carbon steel coil (SAE 1008) with a lining clad with an aluminum alloy that is balance aluminum; 10 to 15% tin; 1 to 3% lead; 0.7 to 1.3% copper; 1.8 to 3.5% silicon; 0.1 to 0.7% chromium, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring 1.93 millimeters or 2.75 millimeters (0.076 inches or 0.108 inches) in thickness, 87.3 millimeters or 99 millimeters (3.437 inches or 3.900 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 0.3% antimony, 2.5% silicon, 1% maximum total other (including iron), and remainder aluminum.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, clad with aluminum, measuring 1.75 millimeters (0.069 inches) in thickness, 89 millimeters or 94 millimeters (3.500 inches or 3.700 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 2.5% silicon, 0.3% antimony, 1% maximum total other (including iron), and remainder aluminum.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring a minimum of and including 1.10mm to a maximum of and including 4.90mm in overall thickness, a minimum of and including 76.00mm to a maximum of and including 250.00mm in overall width, with a low carbon steel back comprised of: Carbon under 0.10%, manganese under 0.40%, phosphorous under 0.04%, sulfur under 0.05%, and silicon under 0.05%; clad with aluminum alloy comprised of: under 2.51% copper, under 15.10% tin, and remainder aluminum as listed on the mill specification sheet.

Also excluded from this order are products meeting the following specifications: (1) Diffusion annealed, non-alloy nickel-plated carbon products, with a substrate of cold-rolled battery grade sheet ("CRBG") with both sides of the CRBG initially electrolytically plated with pure, unalloyed nickel and subsequently annealed to create a diffusion between the nickel and iron substrate, with the nickel plated coating having a thickness of 0–5 microns per side with one side equaling at least 2 microns; and with the nickel carbon sheet having a thickness of from 0.004" (0.10mm) to 0.030" (0.762mm) and conforming to the following chemical specifications (%): C ≤ 0.08; Mn ≤ 0.45; P ≤ 0.02; S ≤ 0.02; Al ≤ 0.15; and Si ≤ 0.10; and the following physical specifications: Tensile = 65 KSI maximum; Yield = 32–55 KSI; Elongation = 18% minimum (aim 34%); Hardness = 85–150 Vickers; Grain Type = Equiaxed or Pancake; Grain Size (ASTM) = 7–12; Delta r value = aim less than +/- 0.2; Lankford value = ≥ 1.2; and (2) next generation diffusion-annealed nickel plate meeting the following specifications: (a) nickel-graphite plated, diffusion annealed, tin-nickel plated carbon products, with a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed tin-nickel plated carbon steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of mixture of natural nickel and graphite then electrolytically plated on the top side of the strip of the nickel-tin alloy; having a coating thickness: top side: nickel-graphite, tin-nickel layer ≥ 1.0 micrometers; tin layer only ≥ 0.05 micrometers, nickel-graphite layer only > 0.2 micrometers, and bottom side: nickel layer ≥ 1.0 micrometers; (b) nickel-graphite, diffusion annealed, nickel plated carbon products, having a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; with both sides of the cold rolled base metal initially electrolytically plated with natural nickel, and the material then annealed

to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-graphite, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: nickel-graphite, tin-nickel layer ≥ 1.0 micrometers; nickel-graphite layer ≥ 0.5 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (c) diffusion annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer ≥ 1.0 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (d) nickel-phosphorous plated diffusion annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer ≥ 1.0 micrometers; nickel-phosphorous layer ≥ 0.1 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (e) diffusion annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion annealed tin-nickel plated cold rolled or tin mill black plate

base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip initially electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: top side: nickel-tin-nickel combination layer ≥ 1.0 micrometers; tin layer only ≥ 0.05 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer ≥ 1 micrometer; tin layer alone ≥ 0.05 micrometers; bottom side: nickel layer ≥ 1.0 micrometer.

Also excluded from this order are products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of phosphate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of phosphate, and finally a layer consisting of silicate.

Initiation of Changed Circumstances Antidumping Duty Administrative Review, and Intent To Revoke Order in Part

Pursuant to sections 751(d)(1) and 782(h)(2) of the Act, the Department may revoke an antidumping or countervailing duty order, in whole or in part, based on a review under section 751(b) of the Act (*i.e.*, a changed circumstances review) where the Department determines that "producers accounting for substantially all of the production of that domestic like product have expressed a lack of interest in issuance of an order." See section 782(h)(2) of the Act. See *e.g.*, *Certain Cold-Rolled Carbon Steel Flat Products From the Netherlands: Initiation and Preliminary Results of Changed Circumstances Review*, 66 FR 57415, 57416 (November 15, 2001).

Furthermore, 19 CFR 351.222(g)(1) provides that the Department will conduct a changed circumstances administrative review under 19 CFR 351.216, and may revoke an order (in whole or in part), if it determines that producers accounting for substantially all of the production of the domestic like product to which the order pertains have expressed a lack of interest in the relief provided by the order, in whole or in part, or if other changed circumstances sufficient to warrant revocation exist. In addition, in the event that the Department concludes that expedited action is warranted, 19 CFR 351.221(c)(3)(ii) permits the Department to combine the notices of initiation and preliminary results.

In accordance with sections 751(d)(1) and 782(h)(2) of the Act, and 19 CFR 351.216 and 351.222(g), based on affirmative statements by domestic producers of the like product, Bethlehem Steel Corporation, National Steel Corporation, and United States Steel Corporation ("Domestic Producers"), no further interest exists in continuing the order with respect to certain corrosion-resistant carbon steel flat products meeting the following specifications: (1) Flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as "ASE Iron Flash" and either: (A) Having a base layer of zinc-based zinc-iron alloy applied by hot-dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40 percent by weight of zinc; or (B) two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer

of iron-zinc alloy by electro-galvanizing process, having an effective amount of zinc up to 40 percent by weight, and (2) corrosion resistant continuously annealed flat-rolled products, continuous cast, the foregoing with chemical composition (percent by weight): carbon not over 0.06 percent by weight, manganese 0.20 or more but not over 0.40, phosphorus not over 0.02, sulfur not over 0.023, silicon not over 0.03, aluminum 0.03 or more but not over 0.08, arsenic not over 0.02, copper not over 0.08 and nitrogen 0.003 or more but not over 0.008; and meeting the characteristics described below: (A) Products with one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a two-layer coating composed of a base nickel-iron-diffused coating layer and a surface coating layer of annealed and softened pure nickel, with total coating thickness for both layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with scanning electron microscope (SEM) not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (B) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a four-layer coating composed of a base nickel-iron-diffused coating layer; with an inner middle coating layer of annealed and softened pure nickel, an outer middle surface coating layer of hard nickel and a topmost nickel-phosphorus-plated layer; with combined coating thickness for the four layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (C) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, luster-agent-added nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; or (D) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer

coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, pure nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length. *See* Domestic Producers' February 13, 2003, letter to the Department. Therefore, we are initiating this changed circumstances administrative review.

Furthermore, because domestic producers have expressed a lack of interest, we determine that expedited action is warranted, and we preliminarily determine that continued application of the order with respect to certain corrosion-resistant carbon steel flat products falling within the description above is no longer of interest to domestic interested parties. Because we have concluded that expedited action is warranted, we are combining these notices of initiation and preliminary results. Therefore, we are hereby notifying the public of our intent to revoke in part the antidumping duty order with respect to imports of certain corrosion-resistant carbon steel flat products meeting the above-mentioned specifications from Japan.

If the final revocation in part occurs, we intend to instruct the U.S. Customs Service ("Customs") to liquidate without regard to antidumping duties, as applicable, and to refund any estimated antidumping duties collected for all unliquidated entries of certain corrosion-resistant carbon steel flat products meeting the specifications indicated above, not subject to final results of administrative review as of the date of publication in the **Federal Register** of the final results of this changed circumstances review in accordance with 19 CFR 351.222. We will also instruct Customs to pay interest on such refunds in accordance with section 778 of the Act. The current requirement for a cash deposit of estimated antidumping duties on certain corrosion-resistant carbon steel flat products meeting the above specifications will continue unless and until we publish a final determination to revoke in part.

Public Comment

Interested parties are invited to comment on these preliminary results. Parties who submit argument in this proceeding are requested to submit with the argument (1) a statement of the issue, and (2) a brief summary of the

argument. Parties to the proceedings may request a hearing within 14 days of publication. Any hearing, if requested, will be held no later than two days after the deadline for the submission of rebuttal briefs, or the first workday thereafter. Case briefs may be submitted by interested parties not later than 14 days after the date of publication of this notice. Pursuant to 19 CFR 351.309(d)(1), rebuttal briefs and rebuttals to written comments, limited to the issues raised in those comments, may be filed not later than five days after the deadline for submission of case briefs. All written comments shall be submitted in accordance with 19 CFR 351.303 and shall be served on all interested parties on the Department's service list in accordance with 19 CFR 351.303. Persons interested in attending the hearing should contact the Department for the date and time of the hearing.

This notice is published in accordance with section 751(b)(1) of the Act and 19 CFR 351.216 and 351.222.

Dated: March 11, 2003.

Joseph A. Spetrini,

Acting Assistant Secretary for Import Administration.

[FR Doc. 03-6477 Filed 3-18-03; 8:45 am]

BILLING CODE 3510-DS-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-201-809]

Certain Cut-to-length Carbon Steel Plate From Mexico: Final Results of Antidumping Duty Administrative Review

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

ACTION: Notice of final results of antidumping duty administrative review.

SUMMARY: The Department of Commerce (the Department) has conducted an administrative review of the antidumping duty order on certain cut-to-length carbon steel plate (steel plate) from Mexico (A-201-809) manufactured by Altos Hornos de Mexico, S.A. de C.V. (AHMSA). The period of review (POR) is August 1, 2000, through July 31, 2001. We determine that AHMSA made no sales of steel plate below the normal value (NV). We will instruct the U.S. Customs Service to assess no antidumping duties on AHMSA's entries.

EFFECTIVE DATE: March 19, 2003.