

Rules and Regulations

Federal Register

Vol. 70, No. 119

Wednesday, June 22, 2005

This section of the FEDERAL REGISTER contains regulatory documents having general applicability and legal effect, most of which are keyed to and codified in the Code of Federal Regulations, which is published under 50 titles pursuant to 44 U.S.C. 1510.

The Code of Federal Regulations is sold by the Superintendent of Documents. Prices of new books are listed in the first FEDERAL REGISTER issue of each week.

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 23

[Docket No. 229, Special Condition 23–168–SC]

Special Conditions; Duncan Aviation Inc., EFIS on the Raytheon 300 King Air; Protection of Systems for High Intensity Radiated Fields (HIRF)

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions; request for comments.

SUMMARY: These special conditions are issued to Duncan Aviation Inc., 15745 S Airport Rd Battle Creek, MI 49015, for a Supplemental Type Certificate for the Raytheon 300 King Air. This airplane will have novel and unusual design features when compared to the state of technology envisaged in the applicable airworthiness standards. These novel and unusual design features include the installation of an electronic flight instrument system (EFIS). The EFIS consists of the Universal Avionics, Inc. EFI–890R system for which the applicable regulations do not contain adequate or appropriate airworthiness standards for the protection of these systems from the effects of high intensity radiated fields (HIRF). The installation includes three EFI–890R Flat Panel Displays (two Primary Flight Displays Pilot/Copilot and one Navigational Displays Pilot), and supporting equipment. These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to the airworthiness standards applicable to these airplanes.

DATES: The effective date of these special conditions is June 15, 2005. Comments must be received on or before July 22, 2005.

ADDRESSES: Comments may be mailed in duplicate to: Federal Aviation Administration, Regional Counsel, ACE–7, Attention: Rules Docket Clerk, Docket No. 229, Room 506, 901 Locust, Kansas City, Missouri 64106. All comments must be marked: Docket No. CE229. Comments may be inspected in the Rules Docket weekdays, except Federal holidays, between 7:30 a.m. and 4 p.m.

FOR FURTHER INFORMATION CONTACT: Wes Ryan, Aerospace Engineer, Standards Office (ACE–110), Small Airplane Directorate, Aircraft Certification Service, Federal Aviation Administration, 901 Locust, Room 301, Kansas City, Missouri 64106; telephone (816) 329–4127.

SUPPLEMENTARY INFORMATION: The FAA has determined that notice and opportunity for prior public comment hereon are impracticable because these procedures would significantly delay issuance of the design approval and thus delivery of the affected aircraft. In addition, the substance of these special conditions has been subject to the public comment process in several prior instances with no substantive comments received. The FAA, therefore, finds that good cause exists for making these special conditions effective upon issuance.

Comments Invited

Interested persons are invited to submit such written data, views, or arguments, as they may desire. Communications should identify the regulatory docket or notice number and be submitted in duplicate to the address specified above. All communications received on or before the closing date for comments will be considered by the Administrator. The special conditions may be changed in light of the comments received. All comments received will be available in the Rules Docket for examination by interested persons, both before and after the closing date for comments. A report summarizing each substantive public contact with FAA personnel concerning this rulemaking will be filed in the docket. Commenters wishing the FAA to acknowledge receipt of their comments submitted in response to this notice must include a self-addressed, stamped postcard on which the following statement is made: “Comments to Docket No. 229.” The postcard will be

date stamped and returned to the commenter.

Background

Duncan Aviation made application to the FAA for a new Supplemental Type Certificate for the Raytheon Model 300. The Raytheon Model 300 is currently approved under TC No. A24CE. The proposed modification incorporates a novel or unusual design features, such as a digital Primary Flight Display, that may be vulnerable to HIRF external to the airplane.

Type Certification Basis

Under the provisions of 14 CFR part 21, § 21.101, Duncan Aviation must show that the Raytheon Model 300 aircraft meets the original certification basis for the airplane, as listed on Type Data Sheet A24CE, additional certification requirements added for the Universal Avionics EFI–890 system, exemptions, if any; and the special conditions adopted by this rulemaking action. The rules that were applied at Part 23 Amendment 54 for this STC include 23.1301, 23.1311, 23.1309, 23.1321, 23.1322, 23.1325, and 23.1543.

Discussion

If the Administrator finds that the applicable airworthiness standards do not contain adequate or appropriate safety standards because of novel or unusual design features of an airplane, special conditions are prescribed under the provisions of § 21.16.

Special conditions, as appropriate, as defined in § 11.19, are issued in accordance with § 11.38 after public notice and become part of the type certification basis in accordance with § 21.101.

Special conditions are initially applicable to the model for which they are issued. Should the applicant apply for a supplemental type certificate to modify any other model already included on the same type certificate to incorporate the same novel or unusual design feature, the special conditions would also apply to the other model under the provisions of § 21.101.

Novel or Unusual Design Features

Duncan Aviation plans to incorporate certain novel and unusual design features into the Raytheon Model 300 airplane for which the airworthiness standards do not contain adequate or appropriate safety standards for

protection from the effects of HIRF. These features include EFIS, which are susceptible to the HIRF environment, that were not envisaged by the existing regulations for this type of airplane.

Protection of Systems from High Intensity Radiated Fields (HIRF): Recent advances in technology have given rise to the application in aircraft designs of advanced electrical and electronic systems that perform functions required for continued safe flight and landing. Due to the use of sensitive solid-state advanced components in analog and digital electronics circuits, these advanced systems are readily responsive to the transient effects of induced electrical current and voltage caused by the HIRF. The HIRF can degrade electronic systems performance by damaging components or upsetting system functions.

Furthermore, the HIRF environment has undergone a transformation that was not foreseen when the current requirements were developed. Higher energy levels are radiated from transmitters that are used for radar, radio, and television. Also, the number of transmitters has increased significantly. There is also uncertainty concerning the effectiveness of airframe shielding for HIRF. Furthermore, coupling to cockpit-installed equipment through the cockpit window apertures is undefined.

The combined effect of the technological advances in airplane design and the changing environment has resulted in an increased level of vulnerability of electrical and electronic systems required for the continued safe flight and landing of the airplane. Effective measures against the effects of exposure to HIRF must be provided by the design and installation of these systems. The accepted maximum energy levels in which civilian airplane system installations must be capable of operating safely are based on surveys and analysis of existing radio frequency emitters. These special conditions require that the airplane be evaluated under these energy levels for the protection of the electronic system and its associated wiring harness. These external threat levels, which are lower than previous required values, are believed to represent the worst case to which an airplane would be exposed in the operating environment.

These special conditions require qualification of systems that perform critical functions, as installed in aircraft, to the defined HIRF environment in paragraph 1 or, as an option to a fixed value using laboratory tests, in paragraph 2, as follows:

(1) The applicant may demonstrate that the operation and operational capability of the installed electrical and electronic systems that perform critical functions are not adversely affected when the aircraft is exposed to the HIRF environment defined below:

Frequency	Field strength (volts per meter)	
	Peak	Average
10 kHz–100 kHz	50	50
100 kHz–500 kHz	50	50
500 kHz–2 MHz	50	50
2 MHz–30 MHz	100	100
30 MHz–70 MHz	50	50
70 MHz–100 MHz	50	50
100 MHz–200 MHz	100	100
200 MHz–400 MHz	100	100
400 MHz–700 MHz	700	50
700 MHz–1 GHz	700	100
1 GHz–2 GHz ...	2000	200
2 GHz–4 GHz ...	3000	200
4 GHz–6 GHz ...	3000	200
6 GHz–8 GHz ...	1000	200
8 GHz–12 GHz	3000	300
12 GHz–18 GHz	2000	200
18 GHz–40 GHz	600	200

The field strengths are expressed in terms of peak root-mean-square (rms) values.

or,

(2) The applicant may demonstrate by a system test and analysis that the electrical and electronic systems that perform critical functions can withstand a minimum threat of 100 volts per meter, electrical field strength, from 10 kHz to 18 GHz. When using this test to show compliance with the HIRF requirements, no credit is given for signal attenuation due to installation.

A preliminary hazard analysis must be performed by the applicant for approval by the FAA to identify either electrical or electronic systems that perform critical functions. The term “critical” means those functions, whose failure would contribute to, or cause, a failure condition that would prevent the continued safe flight and landing of the airplane. The systems identified by the hazard analysis that perform critical functions are candidates for the application of HIRF requirements. A system may perform both critical and non-critical functions. Primary electronic flight display systems, and their associated components, perform critical functions such as attitude, altitude, and airspeed indication. The HIRF requirements apply only to critical functions.

Compliance with HIRF requirements may be demonstrated by tests, analysis,

models, similarity with existing systems, or any combination of these. Service experience alone is not acceptable since normal flight operations may not include an exposure to the HIRF environment. Reliance on a system with similar design features for redundancy as a means of protection against the effects of external HIRF is generally insufficient since all elements of a redundant system are likely to be exposed to the fields concurrently.

Applicability

As discussed above, these special conditions are applicable to the Raytheon Model 300. Should Duncan Aviation apply at a later date for a supplemental type certificate to modify any other model on the same type certificate to incorporate the same novel or unusual design feature, the special conditions would apply to that model as well under the provisions of § 21.101.

Conclusion

This action affects only certain novel or unusual design features on one model of airplane. It is not a rule of general applicability and affects only the applicant who applied to the FAA for approval of these features on the airplane.

The substance of these special conditions has been subjected to the notice and comment period in several prior instances and has been derived without substantive change from those previously issued. It is unlikely that prior public comment would result in a significant change from the substance contained herein. For this reason, and because a delay would significantly affect the certification of the airplane, which is imminent, the FAA has determined that prior public notice and comment are unnecessary and impracticable, and good cause exists for adopting these special conditions upon issuance. The FAA is requesting comments to allow interested persons to submit views that may not have been submitted in response to the prior opportunities for comment described above.

List of Subjects in 14 CFR Part 23

Aircraft, Aviation safety, Signs and symbols.

Citation

■ The authority citation for these special conditions is as follows:

Authority: 49 U.S.C. 106(g), 40113 and 44701; 14 CFR 21.16 and 21.101; and 14 CFR 11.38 and 11.19.

The Special Conditions

■ Accordingly, pursuant to the authority delegated to me by the Administrator, the following special conditions are issued as part of the type certification basis for the Raytheon Model 300 airplane modified by Duncan Aviation to add the Universal Avionics EFI-890 system.

1. Protection of Electrical and Electronic Systems from High Intensity Radiated Fields (HIRF). Each system that performs critical functions must be designed and installed to ensure that the operations, and operational capabilities of these systems to perform critical functions, are not adversely affected when the airplane is exposed to high intensity radiated electromagnetic fields external to the airplane.

2. For the purpose of these special conditions, the following definition applies: *Critical Functions*: Functions whose failure would contribute to, or cause, a failure condition that would prevent the continued safe flight and landing of the airplane.

Issued in Kansas City, Missouri on June 15, 2005.

John R. Colomy,

Acting Manager, Small Airplane Directorate, Aircraft Certification Service.

[FR Doc. 05-12363 Filed 6-21-05; 8:45 am]

BILLING CODE 4910-13-P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

[Docket No. FAA-2004-19754; Directorate Identifier 2004-NM-181-AD; Amendment 39-14138; AD 2005-13-02]

RIN 2120-AA64

Airworthiness Directives; Bombardier Model CL-600-2C10 (Regional Jet Series 700 & 701) Series Airplanes, and Model CL-600-2D24 (Regional Jet Series 900) Series Airplanes

AGENCY: Federal Aviation Administration (FAA), Department of Transportation (DOT).

ACTION: Final rule.

SUMMARY: The FAA is adopting a new airworthiness directive (AD) for certain Bombardier Model CL-600-2C10 (Regional Jet series 700 & 701) series airplanes, and Model CL-600-2D24 (Regional Jet series 900) series airplanes. This AD requires revising the Airworthiness Limitations section of the Instructions of Continued Airworthiness by incorporating new repetitive inspections and an optional terminating

action for the repetitive inspections, and repairing any crack. This AD is prompted by reports of hydraulic pressure loss in either the number 1 or number 2 hydraulic system due to breakage or leakage of hydraulic lines in the aft equipment bay and reports of cracks on the aft pressure bulkhead web around these feed-through holes. We are issuing this AD to prevent loss of hydraulic pressure, which could result in reduced controllability of the airplane, and to detect and correct cracks on the aft pressure bulkhead web, which could result in reduced structural integrity of the aft pressure bulkhead.

DATES: This AD becomes effective July 27, 2005.

The incorporation by reference of a certain publication listed in the AD is approved by the Director of the Federal Register as of July 27, 2005.

ADDRESSES: For service information identified in this AD, contact Bombardier, Inc., Canadair, Aerospace Group, P.O. Box 6087, Station Centre-ville, Montreal, Quebec H3C 3G9, Canada.

Docket: The AD docket contains the proposed AD, comments, and any final disposition. You can examine the AD docket on the Internet at <http://dms.dot.gov>, or in person at the Docket Management Facility office between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays. The Docket Management Facility office (telephone (800) 647-5227) is located on the plaza level of the Nassif Building at the U.S. Department of Transportation, 400 Seventh Street SW., room PL-401, Washington, DC. This docket number is FAA-2004-19754; the directorate identifier for this docket is 2004-NM-181-AD.

FOR FURTHER INFORMATION CONTACT:

Serge Napoleon, Aerospace Engineer, Airframe and Propulsion Branch, ANE-171, FAA, New York Aircraft Certification Office, 1600 Stewart Avenue, suite 410, Westbury, New York 11590; telephone (516) 228-7312; fax (516) 794-5531.

SUPPLEMENTARY INFORMATION: The FAA proposed to amend 14 CFR part 39 with an AD for certain Bombardier Model CL-600-2C10 (Regional Jet series 700 & 701) series airplanes, and Model CL-600-2D24 (Regional Jet series 900) series airplanes. That action, published in the **Federal Register** on December 1, 2004 (69 FR 69842), proposed to require revising the Airworthiness Limitations section of the Instructions of Continued Airworthiness by incorporating new repetitive inspections and an optional terminating action for the repetitive inspections, and repairing any crack.

Comments

We provided the public the opportunity to participate in the development of this AD. We have considered the comments that have been submitted on the proposed AD.

Request To Remove Airplanes From the Applicability

One commenter requests that certain airplane serial numbers be excluded from the applicability specified in paragraph (c) of the proposed AD. The commenter states that the inspection of the hydraulic tube adapters specified in Bombardier CRJ 700/900 Series Temporary Revision (TR) MRM2-129, dated June 1, 2004 (referenced in the proposed AD as the appropriate source of service information), should be applicable to Bombardier Model CL-600-2C10 (Regional Jet Series 700 & 701) series airplanes having serial numbers 10003 through 10099 inclusive, since Modification Summary 670T11944 was introduced in production at serial number 10100. The commenter also states the two remaining inspections of the bulkhead assembly and pylon pressure pan specified in TR MRM2-129 should be applicable to only airplanes having serial numbers 10003 through 10156 inclusive, since Modification Summary 670T11508 was incorporated in production at serial number 10157.

We agree. Bombardier CRJ 700/900 Series MRM2-129, dated June 1, 2004, identifies Modification Summaries 670T00494 or 670T11944; and Modification Summary 670T11508 or Bombardier Service Bulletin 670BA-29-008, dated March 12, 2004, or Revision A, dated May 5, 2004; as terminating modification for the applicable repetitive inspections. Therefore, we have revised the applicability of this AD to "exclud[e] those airplanes on which Modification Summaries 670T00494 or 670T11944; and Modification Summary 670T11508 or Bombardier Service Bulletin 670BA-29-008, dated March 12, 2004, or Revision A, dated May 5, 2004; has been incorporated in production."

Request To Refer to Latest Revision of Maintenance Requirement Manual

One commenter requests that paragraph (f) of the proposed AD refer to Revision 4, dated September 9, 2004, of the general revisions of the Maintenance Requirement Manual instead of Bombardier CRJ 700/900 Series TR MRM2-129, dated June 1, 2004. The commenter states that TR MRM2-129 was superseded by Revision 4 of the general revisions before