Airbus Service Bulletin A310–53–2037, Revision 1, dated April 29, 1992, contains the following effective pages:

Page No.	Revision level shown on page	Date shown on page
1, 4, 6, 11–15, 18, 29, 39–44, 46, 57	Revision 1	April 29, 1992. December 11, 1990.

(2) On September 4, 1998 (63 FR 40819, July 31, 1998), the Director of the Federal Register approved the incorporation by reference of the service information listed in Table 6 of this AD.

TABLE 6.—MATERIAL PREVIOUSLY INCORPORATED BY REFERENCE

Airbus Service Bulletin	Revision level	Date
A310-53-2030	5 02	March 6, 1991. July 2, 1996.

(3) Contact Airbus, 1 Rond Point Maurice Bellonte, 31707 Blagnac Cedex, France, for a copy of this service information. You may review copies at the FAA, Transport Airplane Directorate, 1601 Lind Avenue, SW., Renton, Washington; or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202–741–6030, or go to: http://www.archives.gov/federal-register/cfr/ibr-locations.html.

Issued in Renton, Washington, on May 15, 2007.

Ali Bahrami,

Manager, Transport Airplane Directorate, Aircraft Certification Service.

[FR Doc. E7–10028 Filed 5–29–07; 8:45 am] BILLING CODE 4910–13–P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

[Docket No. FAA-2007-27494; Directorate Identifier 2006-NM-269-AD; Amendment 39-15071; AD 2007-11-14]

RIN 2120-AA64

Airworthiness Directives; Empresa Brasileira de Aeronautica S.A. (EMBRAER) Model EMB-135BJ Airplanes

AGENCY: Federal Aviation Administration (FAA), Department of Transportation (DOT).

ACTION: Final rule.

SUMMARY: We are adopting a new airworthiness directive (AD) for the products listed above. This AD results from mandatory continuing airworthiness information (MCAI) originated by an aviation authority of another country to identify and correct an unsafe condition on an aviation

product. The MCAI describes the unsafe condition as:

It has been found that both fuel level control units (LCU) and their associated harnesses throughout the aircraft does not comply with the requirements of proper segregation, in order to preclude a possible ignition source in the vicinity of the fuel tanks, as required by SFAR (Special Federal Aviation Regulation) 88 regulations.

We are issuing this AD to require actions to correct the unsafe condition on these products.

DATES: This AD becomes effective July 5, 2007.

The Director of the Federal Register approved the incorporation by reference of a certain publication listed in this AD as of July 5, 2007.

ADDRESSES: You may examine the AD docket on the Internet at http://dms.dot.gov or in person at the Docket Management Facility, U.S. Department of Transportation, 400 Seventh Street, SW., Nassif Building, Room PL-401, Washington.

FOR FURTHER INFORMATION CONTACT: Dan Rodina, Aerospace Engineer, International Branch, ANM-116, FAA, Transport Airplane Directorate, 1601 Lind Avenue, SW., Renton, Washington 98057-3356; telephone (425) 227-2125; fax (425) 227-1149.

SUPPLEMENTARY INFORMATION:

Streamlined Issuance of AD

The FAA is implementing a new process for streamlining the issuance of ADs related to MCAI. This streamlined process will allow us to adopt MCAI safety requirements in a more efficient manner and will reduce safety risks to the public. This process continues to follow all FAA AD issuance processes to meet legal, economic, Administrative Procedure Act, and Federal Register

requirements. We also continue to meet our technical decision-making responsibilities to identify and correct unsafe conditions on U.S.-certificated products.

This AD references the MCAI and related service information that we considered in forming the engineering basis to correct the unsafe condition. The AD contains text copied from the MCAI and for this reason might not follow our plain language principles.

Discussion

We issued a notice of proposed rulemaking (NPRM) to amend 14 CFR part 39 to include an AD that would apply to the specified products. That NPRM was published in the **Federal Register** on March 8, 2007 (72 FR 10429). That NPRM proposed to correct an unsafe condition for the specified products. The MCAI states:

It has been found that both fuel level control units (LCU) and their associated harnesses throughout the aircraft does not comply with the requirements of proper segregation, in order to preclude a possible ignition source in the vicinity of the fuel tanks, as required by SFAR (Special Federal Aviation Regulation) 88 regulations.

The MCAI requires replacing the fuel LCU 1 and LCU 2; reworking the LCU 1 and LCU 2 supports; and segregating, replacing, and reworking some harnesses.

Comments

We gave the public the opportunity to participate in developing this AD. We received no comments on the NPRM or on the determination of the cost to the public.

Conclusion

We reviewed the available data and determined that air safety and the

public interest require adopting the AD as proposed.

Differences Between This AD and the MCAI or Service Information

We have reviewed the MCAI and related service information and, in general, agree with their substance. But we might have found it necessary to use different words from those in the MCAI to ensure the AD is clear for U.S. operators and is enforceable. In making these changes, we do not intend to differ substantively from the information provided in the MCAI and related service information.

We might also have required different actions in this AD from those in the MCAI in order to follow our FAA policies. Any such differences are highlighted in a NOTE within the AD.

Costs of Compliance

We estimate that this AD will affect 2 products of U.S. registry. We also estimate that it will take about 60 workhours per product to comply with the basic requirements of this AD. The average labor rate is \$80 per work-hour. Required parts will cost about \$6,931 per product. Where the service information lists required parts costs that are covered under warranty, we have assumed that there will be no charge for these costs. As we do not control warranty coverage for affected parties, some parties may incur costs higher than estimated here. Based on these figures, we estimate the cost of the AD on U.S. operators to be \$23,462, or \$11,731 per product.

Authority for This Rulemaking

Title 49 of the United States Code specifies the FAA's authority to issue rules on aviation safety. Subtitle I, section 106, describes the authority of the FAA Administrator. "Subtitle VII: Aviation Programs," describes in more detail the scope of the Agency's authority.

We are issuing this rulemaking under the authority described in "Subtitle VII, Part A, Subpart III, Section 44701: General requirements." Under that section, Congress charges the FAA with promoting safe flight of civil aircraft in air commerce by prescribing regulations for practices, methods, and procedures the Administrator finds necessary for safety in air commerce. This regulation is within the scope of that authority because it addresses an unsafe condition that is likely to exist or develop on products identified in this rulemaking action.

Regulatory Findings

We determined that this AD will not have federalism implications under Executive Order 13132. This AD will not have a substantial direct effect on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government.

For the reasons discussed above, I certify this AD:

- 1. Is not a "significant regulatory action" under Executive Order 12866;
- 2. Is not a "significant rule" under the DOT Regulatory Policies and Procedures (44 FR 11034, February 26, 1979); and
- 3. Will not have a significant economic impact, positive or negative, on a substantial number of small entities under the criteria of the Regulatory Flexibility Act.

We prepared a regulatory evaluation of the estimated costs to comply with this AD and placed it in the AD docket.

Examining the AD Docket

You may examine the AD docket on the Internet at http://dms.dot.gov; or in person at the Docket Management Facility between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays. The AD docket contains the NPRM, the regulatory evaluation, any comments received, and other information. The street address for the Docket Office (telephone (800) 647–5227) is in the ADDRESSES section. Comments will be available in the AD docket shortly after receipt.

List of Subjects in 14 CFR Part 39

Air transportation, Aircraft, Aviation safety, Incorporation by reference, Safety.

Adoption of the Amendment

■ Accordingly, under the authority delegated to me by the Administrator, the FAA amends 14 CFR part 39 as follows:

PART 39—AIRWORTHINESS DIRECTIVES

■ 1. The authority citation for part 39 continues to read as follows:

Authority: 49 U.S.C. 106(g), 40113, 44701.

§ 39.13 [Amended]

■ 2. The FAA amends § 39.13 by adding the following new AD:

2007–11–14 Empresa Brasileira de Aeronautica S.A. (EMBRAER): Amendment 39–15071. Docket No. FAA–2007–27494; Directorate Identifier 2006–NM–269–AD.

Effective Date

(a) This airworthiness directive (AD) becomes effective July 5, 2007.

Affected ADs

(b) None.

Applicability

(c) This AD applies to EMBRAER Model EMB–135BJ airplanes, certificated in any category, serial numbers 145484, 145540, 145555, 145706, and 145711.

Subject

(d) Fuel.

Reason

(e) The mandatory continuing airworthiness information (MCAI) states:

It has been found that both fuel level control units (LCU) and their associated harnesses throughout the aircraft does not comply with the requirements of proper segregation, in order to preclude a possible ignition source in the vicinity of the fuel tanks, as required by SFAR (Special Federal Aviation Regulation) 88 regulations.

The MCAI requires replacing the fuel LCU 1 and LCU 2; reworking the LCU 1 and LCU 2 supports; and segregating, replacing, and reworking some harnesses.

Actions and Compliance

(f) Within 48 months or 5,000 flight hours after the effective date of this AD, whichever occurs first, unless already done, do the following actions: Replace LCU 1 and LCU 2 by new ones bearing P/N (part number) 367–340–001, rework the LCU 1 and LCU 2 supports, rework and segregate electrical harnesses W102S and W102P, replace harnesses W164 and W221, and route electrical harnesses W164 and W2620 segregating W1614, according to the detailed instructions and procedures described in EMBRAER Service Bulletin 145LEG–28–0020, dated February 18, 2005.

FAA AD Differences

Note: This AD differs from the MCAI and/or service information as follows: No differences.

Other FAA AD Provisions

- (g) The following provisions also apply to this AD:
- (1) Alternative Methods of Compliance (AMOCs): The Manager, International Branch, ANM–116, Transport Airplane Directorate, FAA, ATTN: Dan Rodina, Aerospace Engineer, 1601 Lind Avenue, SW., Renton, Washington 98057–3356, has the authority to approve AMOCs for this AD, if requested using the procedures found in 14 CFR 39.19. Before using any AMOC approved in accordance with § 39.19 on any airplane to which the AMOC applies, notify the appropriate principal inspector in the FAA Flight Standards Certificate Holding District Office.
- (2) Airworthy Product: For any requirement in this AD to obtain corrective actions from a manufacturer or other source, use these actions if they are FAA-approved. Corrective actions are considered FAA-approved if they

are approved by the State of Design Authority (or their delegated agent). You are required to assure the product is airworthy before it is returned to service.

(3) Reporting Requirements: For any reporting requirement in this AD, under the provisions of the Paperwork Reduction Act, the Office of Management and Budget (OMB) has approved the information collection requirements and has assigned OMB Control Number 2120–0056.

Related Information

(h) Refer to MCAI Brazilian Airworthiness Directive 2006–09–05, effective October 18, 2006; and EMBRAER Service Bulletin 145LEG–28–0020, dated February 18, 2005, for related information.

Material Incorporated by Reference

- (i) You must use EMBRAER Service Bulletin 145LEG–28–0020, dated February 18, 2005, to do the actions required by this AD, unless the AD specifies otherwise.
- (1) The Director of the Federal Register approved the incorporation by reference of this service information under 5 U.S.C. 552(a) and 1 CFR part 51.
- (2) For service information identified in this AD, contact Empresa Brasileira de Aeronautica S.A. (EMBRAER), P.O. Box 343—CEP 12.225, Sao Jose dos Campos—SP, Brazil.
- (3) You may review copies at the FAA, Transport Airplane Directorate, 1601 Lind Avenue, SW., Renton, Washington; or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call (202) 741–6030, or go to: http://www.archives.gov/federal-register/cfr/ibrlocations.html.

Issued in Renton, Washington, on May 21, 2007.

Ali Bahrami,

Manager, Transport Airplane Directorate, Aircraft Certification Service.

[FR Doc. E7-10108 Filed 5-29-07; 8:45 am]

BILLING CODE 4910-13-P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

[Docket No. FAA-2007-27340; Directorate Identifier 2006-NM-271-AD; Amendment 39-15072; AD 2007-11-15]

RIN 2120-AA64

Airworthiness Directives; McDonnell Douglas Model DC-10-30 and DC-10-30F (KC-10A and KDC-10) Airplanes, Model DC-10-40 and DC-10-40F Airplanes, and Model MD-10-30F Airplanes

AGENCY: Federal Aviation Administration (FAA), Department of Transportation (DOT).

ACTION: Final rule.

SUMMARY: The FAA is adopting a new airworthiness directive (AD) for certain McDonnell Douglas Model DC-10-30 and DC-10-30F (KC-10A and KDC-10) airplanes, Model DC-10-40 and DC-10-40F airplanes, and Model MD-10-30F airplanes. This AD requires installing bracket assemblies and jumper wires in the center main wheel well to improve the bonding path between the structure (wall) of the lower auxiliary fuel tank and its internal fuel pumps; measuring the electrical resistance between the fuel pump housings and the fuel tank structure; and doing corrective actions if necessary. This AD results from fuel system reviews conducted by the manufacturer. We are issuing this AD to detect and correct an inadequate bond between the internal fuel pump housings and the structure of the lower auxiliary fuel tank. This condition, if not corrected, could fail to meet fault current requirements and result in a potential ignition source that, in combination with flammable fuel vapors, could cause a fuel tank explosion and consequent loss of the airplane.

DATES: This AD becomes effective July 5, 2007.

The Director of the Federal Register approved the incorporation by reference of a certain publication listed in the AD as of July 5, 2007.

ADDRESSES: You may examine the AD docket on the Internet at http://dms.dot.gov or in person at the Docket Management Facility, U.S. Department of Transportation, 400 Seventh Street, SW., Nassif Building, Room PL-401, Washington, DC.

Contact Boeing Commercial Airplanes, Long Beach Division, 3855 Lakewood Boulevard, Long Beach, California 90846, Attention: Data and Service Management, Dept. C1–L5A (D800–0024), for service information identified in this AD.

FOR FURTHER INFORMATION CONTACT:

Samuel Lee, Aerospace Engineer, Propulsion Branch, ANM-140L, FAA, Los Angeles Aircraft Certification Office, 3960 Paramount Boulevard, Lakewood, California 90712-4137; telephone (562) 627-5262; fax (562) 627-5210.

SUPPLEMENTARY INFORMATION:

Examining the Docket

You may examine the airworthiness directive (AD) docket on the Internet at http://dms.dot.gov or in person at the Docket Management Facility office

between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays. The Docket Management Facility office (telephone (800) 647–5227) is located on the plaza level of the Nassif Building at the street address stated in the ADDRESSES section.

Discussion

The FAA issued a notice of proposed rulemaking (NPRM) to amend 14 CFR part 39 to include an AD that would apply to certain McDonnell Douglas Model DC-10-30 and DC-10-30F (KC-10A and KDC-10) airplanes, Model DC-10-40 and DC-10-40F airplanes, and Model MD-10-30F airplanes. That NPRM was published in the Federal Register on February 26, 2007 (72 FR 8305). That NPRM proposed to require installing bracket assemblies and jumper wires in the center main wheel well to improve the bonding path between the structure (wall) of the lower auxiliary fuel tank and its internal fuel pumps; measuring the electrical resistance between the fuel pump housings and the fuel tank structure; and doing corrective actions if necessary.

Comments

We provided the public the opportunity to participate in the development of this AD. We received no comments on the NPRM or on the determination of the cost to the public.

Clarification of Alternative Method of Compliance (AMOC) Paragraph

We have revised this action to clarify the appropriate procedure for notifying the principal inspector before using any approved AMOC on any airplane to which the AMOC applies.

Conclusion

We have carefully reviewed the available data and determined that air safety and the public interest require adopting the AD with the change described previously. We have determined that this change will neither increase the economic burden on any operator nor increase the scope of the AD.

Costs of Compliance

There are about 242 airplanes of the affected design in the worldwide fleet. This AD affects about 178 airplanes of U.S. registry. The following table provides the estimated costs for U.S. operators to comply with this AD, at an average labor rate of \$80 per work hour.