EPA's Plan for MOVES: A Comprehensive Mobile Source Emissions Model

12th CRC On-Road Vehicle Emissions Workshop San Diego, California April 15, 2002

John Koupal, Harvey Michaels, Mitch Cumberworth, Chad Bailey, Dave Brzezinski

U.S. EPA Office of Transportation and Air Quality

MOVES

- Multiscale
- mOtor
- Vehicle & equipment
- Emission
- System


MOVES "Use Cases"

- Multi-scale analysis
 - Macroscale Inventories (EPA Reports, SIPs)
 - Mesoscale Inventories (SIPs, Conformity)
 - Microscale Analyses (e.g. hot spot / project level)
- Transportation/AQ model linkage
- Policy evaluation
- Model validation and uncertainty
- Model updates and expansion


Judging the Shootout

- Criteria 1: Performance
 - On-Road Validation
 - 3 independent vehicles/ 6 trips each for LD & HD
 - Prediction of trip-average emissions across all pollutants
 - Off-Road Validation
 - Same 3 equipment pieces, 1 additional hour of operation
 - Prediction of total emission across 3 equipment pieces
- Criteria 2: Feasibility of Application

Summary Results: On-Road



Summary Results: Off-Road



Observations

- VSP is an excellent metric for characterizing emissions
- Empirical modal binning approaches simple & effective
 - VSP Binning
 - Modal Bins / OLS
- Database approach hurt by small dataset
- Aggregate approach may be sufficient for offroad

Assessing Feasibility Criteria


Feasibility Criteria	Physical Model	Modal Binning	Database	Microtrip
Consistent Across Scales?	X	X		
Easily Updated?		X	X	X
Can Incorporate Many Data Sources?		X	X	
Software Efficiency?	X	X		X

Preliminary Conclusion:

Modal binning shows most overall promise for MOVES

Applying Modal Emissions

Running Exhaust Process



Phase 2 Evaluation

- Competitive contract (one award)
- Evaluate binning methods on several data sources
 - Laboratory second-by-second (EPA MOBILE6 Cycles)
 - On-Board Data (Shootout)
 - IM240 Data (Denver)
 - RSD Data (CRC Denver 2000)
 - Laboratory bag (CMEM Dataset)
- Evaluate uncertainty methodologies
- Validate with independent test results

Emission Processes

Combustion Products	Hydrocarbon	Other
	Evaporation	
Tailpipe Running Exhaust	Diurnal	A/C Refrigerant Leakage
Tailpipe Start Exhaust	Hot Soak	Brake Wear
Crankcase	Resting Loss	Tire Wear
	Running Loss	
	Vehicle Refueling	
	Fuel Leakage	
	Offgassing	


Generic Core Model Design

Core model steps (apply to any scale/source/process):

Loop By Space & Time

- 1. Estimate total activity
 e.g. Vehicle Hours Operating (VHO)
- 2. Distribute across fleet bins/operating modes e.g. Mileage Bin, VSP Bin
- 3. Get emission rate for each fleet bin/operating mode e.g. Gram/Second emission rate by Mileage Bin, VSP bin
- 4. Aggregate across all fleet bin/operating modes
 - \sum (Total Activity * Frequency _{BIN/MODE} * Emission Rate _{BIN/MODE})
- Add front & back ends to implement use cases

MOVES Data Flow Overview



Model Quality

- New EPA guidance on model quality planning requires Quality Assurance Project Plan:
 - Model quality objectives and assessment
 - Coding and documentation standards
 - Stakeholder and scientific peer review
- **EPA Peer Review Guidelines**
 - Recommends Independent Peer Review Panel

Implementation Plan

- Interim Product: Fall 2002
 - Macroscale (county-level) inventory generation w/ MOBILE6.3 and NONROAD
- GHG On-Road Implementation: Fall 2003
 - CO₂, Air Conditioning HFCs, N₂0, CH₄
 - Macroscale only
- Full On-Road Implementation: Fall 2005
 - Adds HC, CO, NOx SOx, PM, NH₃, air toxics
 - Mesoscale/Microscale capability

Next Steps

Planning Documents

- Conceptual Design & Theory: Summer 2002
- Emission Analysis Methodology: Fall 2002
- Quality Assurance Project Plan: Fall 2002

More Information

- http://www.epa.gov/otaq/ngm.htm
- Posted soon:
 - Shootout Contractor Reports and EPA Overview/Results
 - **EPA-OAQPS** Emission Inventory Conference Paper