

§ 236.708

§ 236.708 **Block.**

A length of track of defined limits, the use of which by trains is governed by block signals, cab signals, or both.

§ 236.709 **Block, absolute.**

A block in which no train is permitted to enter while it is occupied by another train.

§ 236.710 **Block, latch.**

The lower extremity of a latch rod which engages with a square shoulder of the segment or quadrant to hold the lever in position.

§ 236.711 **Bond, rail joint.**

A metallic connection attached to adjoining rails to insure electrical conductivity.

§ 236.712 **Brake pipe.**

A pipe running from the engineman's brake valve through the train, used for the transmission of air under pressure to charge and actuate the automatic brake equipment and charge the reservoirs of the electro-pneumatic brake equipment on each vehicle of the train.

§ 236.713 **Bridge, movable.**

That section of a structure bridging a navigable waterway so designed that it may be displaced to permit passage of traffic on the waterway.

§ 236.714 **Cab.**

The compartment of a locomotive from which the propelling power and power brakes of the train are manually controlled.

§§ 236.715–236.716 [Reserved]

§ 236.717 **Characteristics, operating.**

The measure of electrical values at which electrical or electronic apparatus operate (e.g., drop-away, pick-up, maximum and minimum current, and working value).

[49 FR 3387, Jan. 26, 1984]

§ 236.718 **Chart, dog.**

A diagrammatic representation of the mechanical locking of an interlocking machine, used as a working plan in making up, assembling and fitting the locking.

49 CFR Ch. II (10–1–02 Edition)

§ 236.719 **Circuit, acknowledgment.**

A circuit consisting of wire or other conducting material installed between the track rails at each signal in territory where an automatic train stop system or cab signal system of the continuous inductive type with 2-indication cab signals is in service, to enforce acknowledgement by the engineman at each signal displaying an aspect requiring a stop.

§ 236.720 **Circuit, common return.**

A term applied where one wire is used for the return of more than one electric circuit.

§ 236.721 **Circuit, control.**

An electrical circuit between a source of electric energy and a device which it operates.

§ 236.722 **Circuit, cut-in.**

A roadway circuit at the entrance to automatic train stop, train control or cab signal territory by means of which locomotive equipment of the continuous inductive type is actuated so as to be in operative condition.

§ 236.723 **Circuit, double wire; line.**

An electric circuit not employing a common return wire; a circuit formed by individual wires throughout.

§ 236.724 **Circuit, shunt fouling.**

The track circuit in the fouling section of a turnout, connected in multiple with the track circuit in the main track.

§ 236.725 **Circuit, switch shunting.**

A shunting circuit which is closed through contacts of a switch circuit controller.

§ 236.726 **Circuit, track.**

An electrical circuit of which the rails of the track form a part.

§ 236.727 **Circuit, track; coded.**

A track circuit in which the energy is varied or interrupted periodically.

§ 236.728 **Circuit, trap.**

A term applied to a circuit used where it is desirable to provide a track