

**H-3150-1 – ONSHORE OIL AND GAS GEOPHYSICAL EXPLORATION
SURFACE MANAGEMENT REQUIREMENTS (PUBLIC)**

**Offset in Feet, from Certain Objects
(based on pounds of explosive charge)**

Object	½ lb	1 lb	2 lbs	3 lbs	5 lbs	6 to 10 lbs	11 to 15 lbs	16 to 20 lbs
Pipeline less than 6" diameter	50'	100'	150'	150'	200'	250'	300'	400'
Pipeline 6" to 12" diameter	75'	150'	200'	200'	300'	400'	500'	600'
Pipeline greater than 12" diameter	100'	200'	250'	250'	300'	500'	600'	800'
Telephone line	20'	20'	30'	40'	40'	50'	50'	50'
Railroad Track or main paved Highway	50'	100'	150'	150'	150'	220'	280'	350'
Electric Powerline (Shot holes not to exceed 200' depth)	75'	100'	200'	200'	200'	200'	250'	300'
Water wells, buildings, underground cistern, and all other similar objects	225'	300'	400'	450'	700'	800'	1000'	1200'
Brick and/or concrete block buildings	275'	400'	500'	600'	800'	1000'	1200'	1500'
Producing oil and gas well	250'	450'	600'	700'	800'	900'	1000'	1000'
Irrigation wells	500'	800'	1000'	1200'	1500'	2000'	2500'	2500'

Minimum Safe Offset In Feet for Vibrator Truck Operations

Structures	Distance (ft)
Residences, Buildings, Concrete Base Structures	300
Water Wells	350
Concrete Water Pipeline	100
PVC/Plastic Water Pipeline	20
Oil or Gas Well	250
Oil or Gas High Pressure Pipelines	30
High Voltage Power Lines	0
Local Transmission Power Lines	0

15. No equipment, only foot traffic laying receiver lines, will be used in swampy/wetland areas.