

Multi-hazard Loss Estimation Methodology

Hurricane Model

HAZUS[®]*MH* MR2

Technical Manual - Appendices

Developed by:

Department of Homeland Security
Federal Emergency Management Agency
Mitigation Division
Washington, D.C.

Under a contract with:

National Institute of Building Sciences
Washington, D.C.

FOREWORD

The research and development and studies that provided the basis for this publication were conducted pursuant to a contract with the Federal Emergency Management Agency (FEMA) by the:



The National Institute of Building Sciences (NIBS), located in Washington, DC, is a non-governmental, non-profit organization, authorized by Congress to encourage a more rational building regulatory environment, to accelerate the introduction of existing and new technology into the building process and to disseminate technical information.

Copies of this report are available through the Federal Emergency Management Agency. For information contact FEMA @ www.fema.gov/hazus or:

FEMA Distribution Center
P.O. Box 2012
Jessup, Maryland 20794-2012
Tel.: 1 800-480-2520
Fax: 301-362-5335

HAZUS® is a trademark of the Federal Emergency Management Agency.

ACKNOWLEDGMENTS

HAZUS-MH, HAZUS-MH MR1 and HAZUS-MH MR2

Hurricane Model Methodology Development

Wind Committee

Chairman, Joseph Minor, Consultant, Rockport, Texas
Arthur Chiu, University of Hawaii, Honolulu, Hawaii
Mark Levitan, Louisiana State University, Baton Rouge, Louisiana
Richard Marshall, Consultant, Poolesville, Maryland
Robert McComb, Texas Tech University, Lubbock, Texas
Kishor Mehta, Texas Tech University, Lubbock, Texas
Dale Perry, Texas A&M University, College Station, Texas
Mark Powell, National Oceanic and Atmospheric Administration, Miami, Florida
Douglas Smits, City of Charleston, Charleston, South Carolina
Masoud Zadeh, Consultant, San Jose, California

Applied Research Associates, Inc., Raleigh, North Carolina

Peter Vickery, Project Manager; Lawrence Twisdale, Jr., Project Manager; Jason Lin, Peter Skerlj, Michael Young, Francis Lavelle, Reddy Kadasani, Chris Driscoll, Kevin Huang, Peter Montpellier, Andrew Steckley, Jeffrey Sciaudone, Yingzhao Chen, Dhiraj Wadhera

Consultants

Impact Forecasting, Chicago; Illinois, Sethu Raman, North Carolina State University, Raleigh, North Carolina; Thomas Smith, TlSmith Consulting, Rockton, Illinois; Timothy Reinhold, Clemson University, Clemson, South Carolina

Hurricane Model Software Development

Software Committee

Chairman, Dick Bilden, Consultant, Reston, Virginia
Co-Chairman, Mike Haecker, Consultant, Austin, Texas
Dan Cotter, Terrapoint, The Woodlands, Texas
Gerry Key, Computer Sciences Corporation, San Diego, California
Tracy Lenocker, Lenocker and Associates, Inc., Orange, California
Ken Lewis, KVL and Associates, Inc., Scottsdale, Arizona
Frank Opporto, DHS, EP&R Directorate (FEMA), Information Services Technology Division, Washington, D.C.
Dirk Vandervoort, POWER Engineers, Inc., Boise Idaho
Leslie Weiner-Leandro, DHS, EP&R Directorate (FEMA), Information Services Technology Division, Washington, D.C.

Applied Research Associates, Inc., Raleigh, North Carolina

Francis Lavelle, Project Manager; Chris Driscoll, Reddy Kadasani, Richard Pearson, Jr., Peter Vickery, Steve Brooks, Andrew Steckley

Beta Test Subcommittee – HAZUS-MH

*Darryl Davis, Corps of Engineers Hydrologic Engineering Center, Davis, California
Neil Grigg, Colorado State University, Fort Collins, Colorado
Charles Kircher, Kircher & Associates, Palo Alto, California
Tracy Lenocker, Lenocker and Associates, Inc., Orange, California
Kenneth Lewis, KVL and Associates, Inc., Scottsdale, Arizona
Masoud Zadeh, Consultant, San Jose, California*

Beta Test Communities – HAZUS-MH

Division of Emergency Management, Tallahassee, Florida; Washington State Emergency Management, Camp Murray, Washington; Whatcom County Public Works, Bellingham, Washington; Johnson County, Olathe, Kansas; Mecklenburg County Stormwater Services, Charlotte, North Carolina; Louisiana State University, Baton Rouge, Louisiana; Charleston County Building Services, North Charleston, South Carolina

Beta Test Subcommittee – HAZUS-MH MR1

*Douglas Bausch, Department of Homeland Security, Federal Emergency Management Agency, Washington, D.C.
Richard Eisner, Governor's Office of Emergency Services, Oakland, California
John Knight, South Carolina Emergency Management Division, Columbia, South Carolina
Kevin Mickey, The Polis Center, Indianapolis, Indiana
Mark Neimeister, Delaware Geological Survey, Newark, Delaware
Lynn Seirup, New York City Office of Emergency Management, New York, New York*

Beta Test Subcommittee – HAZUS-MH MR2

*Douglas Bausch, Department of Homeland Security, Federal Emergency Management Agency, Washington, D.C.
John Knight, South Carolina Emergency Management Division, Columbia, South Carolina
Kevin Mickey, The Polis Center, Indianapolis, Indiana
Joe Rachel, Department of Homeland Security, Federal Emergency Management Agency, Washington, D.C.
Ken Wallace, Department of Homeland Security, Federal Emergency Management Agency, Washington, D.C.
Bryan Siltanen, Advanced Systems Development, Inc., Arlington, VA*

HAZUS-MH and HAZUS-MH MR1 Shell Development*PBS&J, Atlanta, Georgia*

Mourad Bouhaf, Program Manager; Pushpendra Johari, Sandeep Mehndiratta

Special thanks to ESRI for its assistance in coordinating ArcGIS with HAZUS-MH

Project Sponsorship and Oversight

Department of Homeland Security, FEMA, Mitigation Division, Washington, D.C.

Frederick Sharrocks, Section Chief, Assessment & Plan for Risk; Cliff Oliver, Chief, Risk Assessment Branch; Edward Laatsch, Chief, Building Science and Technology; Eric Berman, Project Officer; Claire Drury, Project Officer; Paul Tertell, Michael Mahoney, Stuart Nishenko, ScottMcAfee, Paul Bryant

FEMA Technical Monitors

Douglas Bausch, FEMA Region 8; Mark Crowell, Physical Scientist; John Ingargiola, Douglas Bellemo, Allyson Lichtenfels, Divisional Coordination

Special thanks to the National Aeronautics and Space Administration for providing financial assistance for developing tree debris estimation capability in the Hurricane Model

Program Management

National Institute of Building Sciences, Washington, D.C.

Philip Schneider, Director, Multihazard Loss Estimation Methodology Program; Barbara Schauer, Senior Project Manager

MESSAGE TO USERS

The HAZUS Hurricane Model is designed to produce loss estimates for use by federal, state, regional and local governments in planning for hurricane risk mitigation, emergency preparedness, response and recovery. The methodology deals with important aspects of the built environment, and a wide range of different types of losses. Extensive national databases are embedded within HAZUS, containing information such as demographic aspects of the population in a study region, square footage for different occupancies of buildings, and numbers and locations of bridges. Embedded parameters have been included as needed. Using this information, users can carry out general loss estimates for a region. The HAZUS methodology and software are flexible enough so that locally developed inventories and other data that more accurately reflect the local environment can be substituted, resulting in increased accuracy.

Uncertainties are inherent in any loss estimation methodology. They arise in part from incomplete scientific knowledge concerning hurricanes and their effects upon buildings and facilities. They also result from the approximations and simplifications that are necessary for comprehensive analyses. Incomplete or inaccurate inventories of the built environment, demographics and economic parameters add to the uncertainty. Where inventories, demographics and economic parameters track closely those assumed and built into the basic methodology, estimates of loss should be within a factor of two. Where one or more of these parameters are incomplete or inaccurate the range of uncertainty may exceed a factor of two or more.

The hurricane loss estimation methodology is based on sound scientific and engineering principals and experimental and experience data. The methodology has been tested against the judgment of experts and, to the extent possible, against records from several past hurricanes. However, limited and incomplete data about actual hurricane damage precludes complete calibration of the methodology. Nevertheless, when used with embedded inventories and parameters, the HAZUS Hurricane Model has provided a credible estimate of such aggregated losses as the total cost of damage.

Users should be aware of the following specific limitations:

- While the HAZUS Hurricane Model can be used to estimate losses for an individual building, the results must be considered as average for a group of similar buildings. It is frequently noted that nominally similar buildings have experienced vastly different damage and losses during a hurricane.
- The Hurricane model contains definitions and assumptions regarding building strengths that represent a norm for construction in hurricane zones. These norms are defined in the technical manual. Where construction quality is known to be different from the defined norms, larger uncertainties in loss projections may be realized.

HAZUS should still be regarded as a work in progress. Additional damage and loss data from actual hurricanes and further experience in using the software will contribute to

improvements in future releases. To assist us in further improving HAZUS, users are invited to submit comments on methodological and software issues by letter, fax or e-mail to:

Philip Schneider
National Institute of Building Sciences
1090 Vermont Ave., N.W.
Washington, DC 20005
Tel: 202-289-7800 ext. 127
Fax: 202-289-1092
E-Mail: HAZUSGenHelp@nibs.org

Eric Berman
Department of Homeland Security
Federal Emergency Management Agency
Mitigation Division
500 C Street, S.W.
Washington, DC 20472
Tel: 202-646-3427
Fax: 202-646-2787
E-Mail: Eric.Berman@dhs.gov

LIMITATIONS OF THE HAZUS-MH MR2 SOFTWARE

Installation

- HAZUS-MH MR2 is certified to run on ArcGIS 9.1 SP1. Tests have shown that HAZUS-MH MR2 is unable to fully function on the ArcGIS 9.1 platform only, SP1 is required. ArcGIS 9.1 SP1 is available from the ESRI website.
- HAZUS-MH MR2 is certified to run on MS Windows 2000 SP2, SP3 and SP 4 and Windows XP SP1 and SP2. A user is allowed to install HAZUS-MH MR2 on MS Windows 2000 and XP for Service Packs higher than SP4 and SP2 respectively, but HAZUS-MH MR2 is not certified to work flawlessly with those service packs.
- HAZUS-MH MR2 must be uninstalled only with the Windows Add/Remove Programs utility. For details on uninstalling, please consult the User Manuals.
- Users who plan to operate HAZUS-MH MR2 in a network environment will be able to perform HAZUS operations, such as importing, but not study region creation.

Study Region Size

- The database management system of HAZUS-MH MR2 is SQL Server MSDE. This system has a size limit of 2 GB per database, which limits the size of the regions to 2,000 census tracts or 90,000 census blocks if the study region also utilizes the Flood Model. Two thousand census tracts and 90,000 census blocks are equivalent to an area with a population of about 9 million. For a multi-hazard study region that includes data for all three hazards, the 2 GB limit will permit an even smaller study region. To work around this, the full version of Microsoft SQL Server 2000 Personal and Developer Editions must be used (see Appendix N in the user manuals).
- Multihazard loss analysis capability is limited to the 23 states that experience hurricane, flood and earthquake hazards and requires that the user first run annualized losses for each of the three hazards.
- To maximize the size of a study region that may be analyzed, set the virtual memory size from a minimum of 2048 MB to a maximum of 4096 MB. For the earthquake model, the virtual memory size may be increased from a minimum of 1024 MB to a maximum of 2048 MB for optimal operation. Here are the steps for setting the virtual memory size:
 1. Click on Start | Settings | Control Panel | System |
 2. Click on the Advanced Tab
 3. Click on the Performance Options button
 4. Click the Change button under Virtual Memory
 5. Replace the initial and maximum values
 6. Click Apply
- The HAZUS-MH MR2 installation allows the user to specify the folder where the state data will be copied through the "Choose Data Path" dialog in the installation wizard. If, at the time of installation, the user specifies the folder where the data will be copied after

installation, they only need to perform Step 1 as described below. If at the time of installation the User does not specify the folder where the state data will be copied by the user after installation, or if they want to change the folder specified during installation, then Steps 2 through 4 for updating the Registry should be completed.

NOTE: The "Choose Data Path" dialog in the installation process only specifies the folder where the state data will be copied by the user from the DVD after installation has completed. This dialog doesn't copy the data from the DVD to the specified folder; that has to be done manually by the user after installation.

1. Copy one or more of the state data folders (e.g., NC1), both the DVD identification files (e.g., D1.txt ^ 4.txt) and "syBoundary.mdb" from the Data DVD to a folder on your hard drive (e.g., D:\HAZUSData\). As an example, the following graphic illustrates how the data for the state of South Carolina would be organized under the HAZUS Data folder.

2. Next, point the program to the data folder on your local hard drive. To do this, click the "Start" button and select "Run" to open the Run window, type "regedit" in the Run window edit box and click the "OK" button to open the Registry Editor. Navigate through the folders listed in the Registry Editor to the following location:

HKEY_LOCAL_MACHINE | SOFTWARE | FEMA | HAZUS-MH | General

3. Now look at the right side of the window and find the entry called "DataPath1". Double click on "DataPath1" to open the Edit String window and enter the full name of the folder on the hard drive that contains the data copied from the DVDs in the edit box. Click the OK button to update the DataPath1 value.

IMPORTANT: Make sure the path ends with a "\" and do not change any of the other registry settings.

4. Close the Registry Editor by choosing Exit from the File menu of the Registry Editor.

Capabilities

- Transferring data, including importing study regions, from HAZUS-MH to HAZUS-MH MR2 will require the assistance of technical support.
- Inventory data and subsequently the Level 1 analysis functionality are unavailable for the US held territories.
- Components of independently developed data sets in the default inventory data might not line up on maps, for example, the placement of bridges and roads, and facilities. This situation can be addressed by updating the default inventory data with user supplied data.
- The Hurricane Model can be run for 22 states on the Gulf and Atlantic coasts and for the state of Hawaii. Default tree inventory data is not available for Hawaii.
- Loss estimates for large study regions of 2,000 census tracts or blocks might require 4 hours analysis time.

BIT and InCAST

- In the Hurricane Model, BIT does not allow mapping from specific to general building types.
- Since InCAST development predated the development of the Hurricane Model in HAZUS-MH, data types used for different types of hazard specific data in InCAST are not compatible with those used in HAZUS-MH MR2. Additionally, InCAST does not capture all hazard specific attributes used in HAZUS-MH MR2.
- InCAST can be used to capture hurricane hazard data which can be imported into HAZUS-MH MR2 from hzIncast table. However, the following fields should not be imported: BldgType, Kitchen, Dinning and Sleeping.

Technical Support

- Technical support is available via telephone, e-mail, or FAX. The numbers and addresses are listed on the HAZUS software package and under the Help menu in the software. Information on HAZUS updates, software patches, and FAQs are available at www.fema.gov/hazus/.

WHAT'S NEW IN HAZUS-MH MR1 – HURRICANE MODEL

Data

- Updated valuations for the general building stock.

Methodology

- Capability to assess hurricane mitigation options for multi-unit buildings and manufactured housing.
- Capability to define hurricanes with NWS forecasts/advisories downloaded directly from the Internet.

Other Features

- Operation on the new ArcGIS 9.0 SP1 platform.
- Capability to utilize third-party tools.
- Optimized software for rapid loss assessment.

WHAT'S NEW IN HAZUS-MH MR 2 – HURRICANE MODEL

Data

- 2005 valuation data for all occupancy classes.
- Means location factors for residential and non-residential occupancies on a county basis.
- Updated and validated valuation data for single-family residential housing and manufactured housing based on comparisons with other national databases.
- Zeros substituted for any negative values calculated for the daytime, nighttime, working commercial, working industrial and commuting populations.
- Construction age and values by decade for every census block with floor area (square footage).

Methodology

- Availability of mitigation analysis options for all building classes and capability to specify the percentages of each building class that have one or more mitigation features.
- Capability to estimate tree debris weight or volume that is likely to be collected and discarded at public expense.
- Capability through an “Automatic Outputs” tool in the analysis options window to specify a standard set of summary reports and map layers that will be generated after each analysis and automatically exported to the study region folder.
- Capability to generate a range, representing the 5th and 95th percentiles, of potential damage and loss estimates for a given hurricane forecast, based on track and intensity errors in forecast advisories issued during the past 12 years, and to include the results in a new rapid loss summary report.
- Minor adjustments to the Hurricane Model Summary Reports to improve consistency among the three models.

Other Features

- Keyboard operation of all user interface operations with some exceptions.
- Operation on the ArcView 9.1 SP1 platform.
- Certified on Windows XP SP2.
- Operation on the MDAC 2.8 data access engine from Microsoft.

TABLE OF CONTENTS

VOLUME I

CHAPTER 1. INTRODUCTION.....	1-1
1.1 Background	1-1
1.2 Scope	1-1
1.3 Technical Approach	1-3
1.4 Technical Manual Organization.....	1-5
CHAPTER 2. HURRICANE RISK MODEL.....	2-1
2.1 Review of Hurricane Wind Models	2-1
2.2 Hurricane Wind Field Model.....	2-2
2.2.1 Mean Wind Field Model	2-3
2.2.2 Surface Level Winds	2-3
2.2.3 Pressure Profile Parameter.....	2-4
2.2.4 Wind Field Model Validation.....	2-11
2.2.5 Summary.....	2-11
2.3 Hurricane Simulation Methodology	2-11
2.3.1 Introduction.....	2-11
2.3.2 Storm Track Modeling	2-15
2.3.3 Modeling of Radius to Maximum Winds and Pressure Profile Parameter....	2-16
2.3.4 Hurricane Model Updates	2-17
2.3.5 Track and Central Pressure Model Evaluation	2-18
2.3.6 Landfalling Hurricanes	2-19
2.3.7 Predicted Wind Speeds vs. Return Period	2-30
2.3.8 Summary	2-31
2.4 Hurricane Rainfall Rate Model	2-34
2.4.1 Introduction.....	2-34
2.4.2 Data and Prior Studies	2-34
2.4.3 Model Development	2-36
2.4.4 Hurricane Rainfall Rate Model Implementation and Calibration.....	2-40
2.4.5 Summary.....	2-45
CHAPTER 3. SURFACE ROUGHNESS MODELING3-1	
3.1 Introduction.....	3-1
3.2 Land Use Databases.....	3-3
3.2.1 Florida Water Management District Data.....	3-4
3.2.2 MRLC-NLCD Database.....	3-7
3.3 Surface Roughness Lengths in the Southeast Florida Area.....	3-12
3.4 Surface Roughness Lengths in the Florida Panhandle Area.....	3-16
3.5 Roughness Length Database Development for All Coastal States	3-21
3.5.1 The National Land Cover Data.....	3-21
3.5.2 Mapping NLCD Land Cover Codes to Roughness Lengths	3-27
3.5.3 Census Tract-Averaged Roughness Length.....	3-34
3.5.4 Comparisons of z_0 Values Computed from NLCD Data on Rectangular Grids with Empirically Assigned z_0 Values.....	3-36

3.6	Example of Roughness Length (z_0) Calculation Using Lettau's Formula	3-40
3.7	Effect of Surface Roughness on Near Ground Gust Wind Speeds	3-49
CHAPTER 4.	WIND LOADS	4-1
4.1	Introduction.....	4-1
4.2	Wall Pressures-Low-Rise Buildings	4-2
4.3	Roof Pressures - Low-Rise Buildings	4-4
4.4	Wind Loads on Low-Rise Buildings - Effect of Nearby Buildings.....	4-16
4.5	Integrated (Overall) Wind Loads on Low-Rise Buildings	4-17
4.6	Wind Loads on High-Rise Buildings.....	4-28
CHAPTER 5.	WINDBORNE DEBRIS	5-1
5.1	Windborne Debris - Residential Missile Model	5-1
5.2	Windborne Debris - Commercial Missile Model	5-7
5.2.1	Windborne Gravel Debris Simulation and Case Studies	5-8
5.2.2	Probability of Damage to Building Envelopes by Windborne Gravel Debris	5-25
CHAPTER 6.	PHYSICAL DAMAGE MODELING	6-1
6.1	General Approach	6-1
6.2	Resistance Models for Residential Buildings	6-3
6.2.1	Roof Sheathing in Wood Frame Construction	6-3
6.2.2	Air Permeable Roof Cover Systems	6-4
6.2.3	Windows and Sliding Glass Doors	6-5
6.2.4	Roof-Wall Connections	6-6
6.2.5	Masonry Walls.....	6-7
6.2.6	Wood Frame Walls.....	6-16
6.3	Damage Model Validation for Residential Buildings	6-32
6.3.1	Roof Cover and Roof Deck Damage	6-32
6.3.1.1	Hurricane Andrew (1992)	6-32
6.3.1.2	Hurricane Erin (1995)	6-42
6.3.1.3	Hurricane Fran (1996)	6-43
6.3.2	Window Damage.....	6-44
6.3.3	Whole Roof Failures.....	6-44
6.4	Damage Model Results for Residential Buildings	6-46
6.4.1	Effect of Mitigation on Residential Building Damage	6-59
6.5	Manufactured Homes	6-62
6.5.1	Resistance Models for Manufactured Homes	6-64
6.5.2	Damage Model Validation for Manufactured Homes	6-67
6.5.3	Damage Model Results for Manufactured Homes	6-72
6.6	Roof Covers on Flat Roofs.....	6-73
6.6.1	Resistance Model for Roof Covers on Flat Roofs.....	6-74
6.6.2	Damage Model Validation for Roof Covers on Flat Roofs	6-76
6.7	Open-Web Steel Joist Roof System	6-78
6.7.1	Resistance Model for Open-Web Steel Joists	6-80
6.7.2	Resistance Model for Metal Deck on Open-Web Steel Joists	6-83

6.8	Pre-Engineered Metal Buildings.....	6-95
6.8.1	Resistance Model for Metal Building Wall System	6-96
6.8.2	Resistance Model for Metal Building Roof System.....	6-101
6.9	Damage Model Results for Marginally- or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings	6-102
6.10	Damage Model Results for Low-Rise Masonry Strip Mall Buildings.....	6-105
6.11	Damage Model Results for Pre-Engineered Metal Buildings	6-125
6.12	Damage Model Results for Engineered Residential and Commercial Buildings	6-129
6.13	Damage Model Results for Industrial Buildings	6-134
CHAPTER 7. DIRECT ECONOMIC LOSSES		7-1
7.1	Introduction.....	7-1
7.2	Residential Input Parameters.....	7-1
7.3	Residential Subassembly Costs.....	7-3
7.3.1	Default Residence.....	7-3
7.3.2	Subassembly Cost Ratios	7-4
7.4	Explicit Costing of Residential Losses	7-5
7.5	Modeling of Residential Interior and Content Losses and Loss of Use	7-7
7.5.1	Economic Damage to the Building Interior.....	7-7
7.5.2	Economic Damage to Contents	7-9
7.5.3	Loss of Use for Residential Buildings	7-11
7.6	Residential Loss Model Validation Examples	7-11
7.7	Loss Model Results for Residential Buildings	7-14
7.8	Manufactured Home Loss Model	7-19
7.8.1	Manufactured Home Loss Model Costing.....	7-19
7.8.2	Fast Running Manufactured Home Loss Functions.....	7-36
7.9	Economic Loss Model for Commercial Buildings	7-36
7.9.1	Subassembly Cost Ratios	7-37
7.9.2	Building Loss Model.....	7-39
7.9.3	Content Loss Model	7-43
7.9.4	Business Interruption Model.....	7-44
7.10	Loss Model Results for Marginally-Engineered or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings	7-46
7.11	Loss Model Results for Low-Rise Masonry Strip Mall Buildings.....	7-46
7.12	Loss Model Results for Pre-Engineered Metal Buildings	7-79
7.13	Loss Model Results for Engineered Residential and Commercial Buildings	7-79
7.14	Loss Model Results for Industrial Buildings	7-95
CHAPTER 8. BUILDING STOCK CLASSIFICATION METHODS.....		8-1
8.1	Introduction.....	8-1
8.2	Aerial Photography Samples.....	8-1
8.3	Contractor Survey	8-4

CHAPTER 9. LOSS MODEL VALIDATION STUDIES FOR HURRICANES ANDREW, ERIN, OPAL AND HUGO.....	9-1
9.1 Introduction.....	9-1
9.2 Example Results - Hurricane Andrew	9-1
9.3 Example Results - Hurricanes Erin and Opal	9-10
9.4 Example Results - Hurricane Hugo.....	9-15
9.5 Summary	9-23
CHAPTER 10. DEBRIS GENERATED FROM DAMAGED BUILDINGS.....	10-1
10.1 Introduction.....	10-1
10.2 Description of Methodology.....	10-2
10.3 Validation Studies	10-8
10.4 Final Remarks	10-15
CHAPTER 11. SHORT TERM SHELTER REQUIREMENTS	11-1
11.1 Introduction	11-1
11.2 Description of Methodology.....	11-1
11.3 Simplified Methodology.....	11-4
CHAPTER 12. TREE BLOWDOWN	12-1
12.1 Introduction and Background	12-1
12.2 Related Research	12-2
12.3 Wind Throw Model	12-2
12.3.1 Wind Load Response and Breakage Model	12-2
12.3.2 Wind Modeling for Simple Terrains.....	12-7
12.3.3 Example Tree Response - Ponderosa Pine.....	12-10
12.3.4 Wind Modeling in Forested Areas.....	12-13
12.3.4.1 Canopy Modeling.....	12-14
12.3.4.2 Effective Windspeeds in Forested Areas	12-16
12.3.5 Simulation Methodology.....	12-19
12.3 Simulation Methodology.....	12-20
12.4 Blowdown Results.....	12-20
12.4.1 Tree Blowdown Curves	12-20
12.4.2 Tree Blowdown Validation.....	12-20
12.5 Tree Inventory Data by County	12-24
12.5.1 Forest Inventory Analysis (FIA) Program and Database	12-24
12.5.2 Average Tree Density and Tree Height Distribution at County Level	12-25
12.6 HAZUS Tree Coverage Database.....	12-27
12.6.1 MRLC National Land Cover Data	12-27
12.6.2 Tree Density, Tree Height, and Predominant Tree Type by Census Tract	12-28
12.7 Debris Generated from Tree Blowdown.....	12-29
12.7.1 Total Weight and Volume of Downed Trees	12-30
12.7.2 Tree Debris Collection Models	12-32
12.7.2.1 Tree Debris Collection Model Description	12-32
12.7.2.2 Implementing into HAZUS-MH	12-35

12.7.2.3	Other Considerations for HAZUS-MH	12-37
12.7.3	Comparison of Modeled and Reported Tree Debris	12-38
12.7.3.1	Example Tree Collection Data – Hurricane Isabel, North Carolina	12-38
12.7.3.2	Example Tree Collection Data – Hurricane Isabel, Virginia	12-39
12.7.3.3	Comparison to Other Collection Data.....	12-43
12.8	Tree Blowdown Damage to Buildings	12-44
12.8.1	Overview	12-44
12.8.2	Tree Drop Tests	12-44
12.8.3	Relationship between Damage Severity and Impact Energy.....	12-45
12.9	Estimation of Direct Economic Loss from Physical Damage States.....	12-48
12.10	Mean Loss as a Function of Wind Speed	12-54
12.10.1	Losses Due to Tree Blow-Down	12-54
12.10.2	Loss Function for a Specific Building Type in Given Census Tract	12-55
12.10.3	Combining Tree Blowdown Normalized Loss Functions with the Basic Fast- Running Building and Contents Loss Functions	12-55
CHAPTER 13.	REFERENCES.....	13-1
VOLUME II		
APPENDIX A.	Damage State Functions for Residential Buildings	A-1
APPENDIX B.	Damage State Functions for Manufactured Homes	B-1
APPENDIX C.	Damage State Functions for Marginally- or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings	C-1
APPENDIX D.	Damage State Functions for Low Rise Masonry Strip Mall Buildings.....	D-1
APPENDIX E.	Damage State Functions for Pre-Engineered Metal Buildings.....	E-1
APPENDIX F.	Damage State Functions for Engineered Residential and Commercial Buildings.....	F-1
APPENDIX G.	Damage State Functions for Industrial Buildings	G-1
APPENDIX H.	Loss Functions for Residential Buildings.....	H-1
APPENDIX I.	Loss Functions for Manufactured Homes	I-1
APPENDIX J.	Loss Functions for Marginally- or Non-Engineered Hotel/Motel and Multi- Family Residential Buildings	J-1
APPENDIX K.	Loss Functions for Pre-Engineered Metal Buildings	L-1
APPENDIX M.	Loss Functions for Engineered Residential and Commercial Buildings	M-1
APPENDIX N.	Loss Functions for Industrial Buildings	N-1

Appendix A.
Damage State Functions for Residential Buildings

Appendix A. Damage State Functions for Residential Buildings

This appendix presents damage state curves for residential buildings (see Section 6.4). The damage state curves show the probability of achieving a certain damage state versus storm-maximum peak gust speed (open terrain at 10m above ground). Plots are presented for the overall building damage states and for the individual building component damage states (refer to Table 6.4-1 for damage state definitions). Table A.1 summarizes the figures included in this appendix.

Table A.1. Sample Damage State Functions for Residential Buildings

Figure	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Terrain
A.1	URM	1	No	Gable	6d	Strap	No	No	0.03
A.2	URM	1	No	Gable	6d	Strap	No	No	0.35
A.3	URM	1	No	Gable	6d	Strap	No	No	0.70
A.4	URM	1	No	Gable	6d	Strap	No	No	1.00
A.5	URM	1	No	Hip	6d	Strap	No	No	0.03
A.6	URM	1	No	Hip	6d	Strap	No	No	0.35
A.7	URM	1	No	Hip	6d	Strap	No	No	0.70
A.8	URM	1	No	Hip	6d	Strap	No	No	1.00
A.9	URM	1	No	Gable	6d	Toe-Nail	No	No	0.03
A.10	URM	1	No	Gable	6d	Toe-Nail	No	No	0.35
A.11	URM	1	No	Gable	6d	Toe-Nail	No	No	0.70
A.12	URM	1	No	Gable	6d	Toe-Nail	No	No	1.00
A.13	URM	1	No	Hip	6d	Toe-Nail	No	No	0.03
A.14	URM	1	No	Hip	6d	Toe-Nail	No	No	0.35
A.15	URM	1	No	Hip	6d	Toe-Nail	No	No	0.70
A.16	URM	1	No	Hip	6d	Toe-Nail	No	No	1.00
A.17	WFR	2	No	Gable	6d	Strap	No	No	0.03
A.18	WFR	2	No	Gable	6d	Strap	No	No	0.35
A.19	WFR	2	No	Gable	6d	Strap	No	No	0.70
A.20	WFR	2	No	Gable	6d	Strap	No	No	1.00
A.21	WFR	2	No	Hip	6d	Strap	No	No	0.03
A.22	WFR	2	No	Hip	6d	Strap	No	No	0.35
A.23	WFR	2	No	Hip	6d	Strap	No	No	0.70
A.24	WFR	2	No	Hip	6d	Strap	No	No	1.00
A.25	WFR	2	No	Gable	6d	Toe-Nail	No	No	0.03
A.26	WFR	2	No	Gable	6d	Toe-Nail	No	No	0.35
A.27	WFR	2	No	Gable	6d	Toe-Nail	No	No	0.70
A.28	WFR	2	No	Gable	6d	Toe-Nail	No	No	1.00
A.29	WFR	2	No	Hip	6d	Toe-Nail	No	No	0.03
A.30	WFR	2	No	Hip	6d	Toe-Nail	No	No	0.35
A.31	WFR	2	No	Hip	6d	Toe-Nail	No	No	0.70
A.32	WFR	2	No	Hip	6d	Toe-Nail	No	No	1.00

Table A.1. Sample Damage State Functions for Residential Buildings (continued)

Figure	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Terrain
A.33	URM	2	No	Gable	6d	Strap	No	No	0.03
A.34	URM	2	No	Gable	6d	Strap	No	No	0.35
A.35	URM	2	No	Gable	6d	Strap	No	No	0.70
A.36	URM	2	No	Gable	6d	Strap	No	No	1.00
A.37	URM	2	No	Hip	6d	Strap	No	No	0.03
A.38	URM	2	No	Hip	6d	Strap	No	No	0.35
A.39	URM	2	No	Hip	6d	Strap	No	No	0.70
A.40	URM	2	No	Hip	6d	Strap	No	No	1.00
A.41	URM	2	No	Gable	6d	Toe-Nail	No	No	0.03
A.42	URM	2	No	Gable	6d	Toe-Nail	No	No	0.35
A.43	URM	2	No	Gable	6d	Toe-Nail	No	No	0.70
A.44	URM	2	No	Gable	6d	Toe-Nail	No	No	1.00
A.45	URM	2	No	Hip	6d	Toe-Nail	No	No	0.03
A.46	URM	2	No	Hip	6d	Toe-Nail	No	No	0.35
A.47	URM	2	No	Hip	6d	Toe-Nail	No	No	0.70
A.48	URM	2	No	Hip	6d	Toe-Nail	No	No	1.00
A.49	URM	1	No	Gable	8d	Strap	No	No	0.03
A.50	URM	1	No	Gable	8d	Strap	No	No	0.35
A.51	URM	1	No	Gable	8d	Strap	No	No	0.70
A.52	URM	1	No	Gable	8d	Strap	No	No	1.00
A.53	URM	1	No	Hip	8d	Strap	No	No	0.03
A.54	URM	1	No	Hip	8d	Strap	No	No	0.35
A.55	URM	1	No	Hip	8d	Strap	No	No	0.70
A.56	URM	1	No	Hip	8d	Strap	No	No	1.00
A.57	URM	1	No	Gable	8d	Toe-Nail	No	No	0.03
A.58	URM	1	No	Gable	8d	Toe-Nail	No	No	0.35
A.59	URM	1	No	Gable	8d	Toe-Nail	No	No	0.70
A.60	URM	1	No	Gable	8d	Toe-Nail	No	No	1.00
A.61	URM	1	No	Hip	8d	Toe-Nail	No	No	0.03
A.62	URM	1	No	Hip	8d	Toe-Nail	No	No	0.35
A.63	URM	1	No	Hip	8d	Toe-Nail	No	No	0.70
A.64	URM	1	No	Hip	8d	Toe-Nail	No	No	1.00
A.65	URM	1	No	Gable	8d	Strap	Yes	No	0.03
A.66	URM	1	No	Gable	8d	Strap	Yes	No	0.35
A.67	URM	1	No	Gable	8d	Strap	Yes	No	0.70
A.68	URM	1	No	Gable	8d	Strap	Yes	No	1.00
A.69	URM	1	No	Hip	8d	Strap	Yes	No	0.03
A.70	URM	1	No	Hip	8d	Strap	Yes	No	0.35
A.71	URM	1	No	Hip	8d	Strap	Yes	No	0.70
A.72	URM	1	No	Hip	8d	Strap	Yes	No	1.00
A.73	URM	1	No	Gable	8d	Toe-Nail	Yes	No	0.03
A.74	URM	1	No	Gable	8d	Toe-Nail	Yes	No	0.35
A.75	URM	1	No	Gable	8d	Toe-Nail	Yes	No	0.70
A.76	URM	1	No	Gable	8d	Toe-Nail	Yes	No	1.00

Table A.1. Sample Damage State Functions for Residential Buildings (concluded)

Figure	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Terrain
A.77	URM	1	No	Hip	8d	Toe-Nail	Yes	No	0.03
A.78	URM	1	No	Hip	8d	Toe-Nail	Yes	No	0.35
A.79	URM	1	No	Hip	8d	Toe-Nail	Yes	No	0.70
A.80	URM	1	No	Hip	8d	Toe-Nail	Yes	No	1.00
A.81	URM	1	No	Gable	8d	Strap	No	Yes	0.03
A.82	URM	1	No	Gable	8d	Strap	No	Yes	0.35
A.83	URM	1	No	Gable	8d	Strap	No	Yes	0.70
A.84	URM	1	No	Gable	8d	Strap	No	Yes	1.00
A.85	URM	1	No	Hip	8d	Strap	No	Yes	0.03
A.86	URM	1	No	Hip	8d	Strap	No	Yes	0.35
A.87	URM	1	No	Hip	8d	Strap	No	Yes	0.70
A.88	URM	1	No	Hip	8d	Strap	No	Yes	1.00
A.89	URM	1	No	Gable	8d	Toe-Nail	No	Yes	0.03
A.90	URM	1	No	Gable	8d	Toe-Nail	No	Yes	0.35
A.91	URM	1	No	Gable	8d	Toe-Nail	No	Yes	0.70
A.92	URM	1	No	Gable	8d	Toe-Nail	No	Yes	1.00
A.93	URM	1	No	Hip	8d	Toe-Nail	No	Yes	0.03
A.94	URM	1	No	Hip	8d	Toe-Nail	No	Yes	0.35
A.95	URM	1	No	Hip	8d	Toe-Nail	No	Yes	0.70
A.96	URM	1	No	Hip	8d	Toe-Nail	No	Yes	1.00
A.97	URM	1	No	Gable	8d	Strap	Yes	Yes	0.03
A.98	URM	1	No	Gable	8d	Strap	Yes	Yes	0.35
A.99	URM	1	No	Gable	8d	Strap	Yes	Yes	0.70
A.100	URM	1	No	Gable	8d	Strap	Yes	Yes	1.00
A.101	URM	1	No	Hip	8d	Strap	Yes	Yes	0.03
A.102	URM	1	No	Hip	8d	Strap	Yes	Yes	0.35
A.103	URM	1	No	Hip	8d	Strap	Yes	Yes	0.70
A.104	URM	1	No	Hip	8d	Strap	Yes	Yes	1.00
A.105	URM	1	No	Gable	8d	Toe-Nail	Yes	Yes	0.03
A.106	URM	1	No	Gable	8d	Toe-Nail	Yes	Yes	0.35
A.107	URM	1	No	Gable	8d	Toe-Nail	Yes	Yes	0.70
A.108	URM	1	No	Gable	8d	Toe-Nail	Yes	Yes	1.00
A.109	URM	1	No	Hip	8d	Toe-Nail	Yes	Yes	0.03
A.110	URM	1	No	Hip	8d	Toe-Nail	Yes	Yes	0.35
A.111	URM	1	No	Hip	8d	Toe-Nail	Yes	Yes	0.70
A.112	URM	1	No	Hip	8d	Toe-Nail	Yes	Yes	1.00




Figure A.1. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.2. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.3. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.4. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.5. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.6. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.7. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.8. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.9. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.10. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.11. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.12. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.13. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.14. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.15. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.16. Damage States versus Maximum Peak Gust Wind Speed – One Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.17. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Wood Frame Walls, $z_0 = 0.03$ m.




Figure A.18. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Wood Frame Walls, $z_0 = 0.35$ m.




Figure A.19. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Wood Frame Walls, $z_0 = 0.70$ m.




Figure A.20. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 1.0$ m.




Figure A.21. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 0.03$ m.




Figure A.22. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 0.35$ m.




Figure A.23. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 0.70$ m.




Figure A.24. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 1.0$ m.




Figure A.25. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Wood Frame Walls, $z_0 = 0.03$ m.




Figure A.26. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Wood Frame Walls, $z_0 = 0.35$ m.




Figure A.27. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Wood Frame Walls, $z_0 = 0.70$ m.




Figure A.28. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Wood Frame Walls, $z_0 = 1.0$ m.




Figure A.29. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 0.03$ m.




Figure A.30. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 0.35$ m.




Figure A.31. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 0.70$ m.




Figure A.32. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Wood Frame Walls, $z_0 = 1.0$ m.




Figure A.33. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.34. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.35. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.36. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.37. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.38. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.39. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.40. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.41. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.42. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.43. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.44. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.45. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.46. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.47. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.48. Damage States versus Maximum Peak Gust Wind Speed – Two Story, 6d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.49. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.50. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.51. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.52. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.53. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03 m$.




Figure A.54. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35 m$.




Figure A.55. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m.




Figure A.56. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m.




Figure A.57. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03 m$.




Figure A.58. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35 m$.




Figure A.59. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70\text{ m}$.




Figure A.60. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0\text{ m}$.




Figure A.61. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m.




Figure A.62. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m.




Figure A.63. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70\text{ m}$.




Figure A.64. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0\text{ m}$.




Figure A.65. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m, Shutters




Figure A.66. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m, Shutters




Figure A.67. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Shutters




Figure A.68. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Shutters




Figure A.69. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03\text{ m}$, Shutters




Figure A.70. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35\text{ m}$, Shutters




Figure A.71. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Shutters




Figure A.72. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Shutters




Figure A.73. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03\text{ m}$, Shutters




Figure A.74. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35\text{ m}$, Shutters




Figure A.75. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70\text{ m}$, Shutters




Figure A.76. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0\text{ m}$, Shutters




Figure A.77. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m, Shutters




Figure A.78. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m, Shutters




Figure A.79. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Shutters




Figure A.80. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Shutters




Figure A.81. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m, Dade County Roof




Figure A.82. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m, Dade County Roof




Figure A.83. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Dade County Roof




Figure A.84. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Dade County Roof




Figure A.85. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03 \text{ m}$, Dade County Roof




Figure A.86. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35 \text{ m}$, Dade County Roof




Figure A.87. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Dade County Roof




Figure A.88. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Dade County Roof




Figure A.89. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03\text{ m}$, Dade County Roof




Figure A.90. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35\text{ m}$, Dade County Roof




Figure A.91. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Dade County Roof




Figure A.92. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Dade County Roof




Figure A.93. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m, Dade County Roof




Figure A.94. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m, Dade County Roof




Figure A.95. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Dade County Roof




Figure A.96. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Dade County Roof




Figure A.97. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m, Shutters and Dade County Roof




Figure A.98. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m, Shutters and Dade County Roof




Figure A.99. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Shutters and Dade County Roof




Figure A.100. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Shutters and Dade County Roof




Figure A.101. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m, Shutters and Dade County Roof




Figure A.102. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m, Shutters and Dade County Roof




Figure A.103. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Shutters and Dade County Roof




Figure A.104. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Strapped Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Shutters and Dade County Roof




Figure A.105. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03\text{ m}$, Shutters and Dade County Roof




Figure A.106. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35\text{ m}$, Shutters and Dade County Roof




Figure A.107. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Shutters and Dade County Roof




Figure A.108. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Gable Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Shutters and Dade County Roof




Figure A.109. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.03$ m, Shutters and Dade County Roof




Figure A.110. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.35$ m, Shutters and Dade County Roof




Figure A.111. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 0.70$ m, Shutters and Dade County Roof




Figure A.112. Damage States versus Maximum Peak Gust Wind Speed – One Story, 8d Roof Sheathing Nails, Toe-Nailed Roof Trusses, Hip Roof, No Garage, Unreinforced Masonry Walls, $z_0 = 1.0$ m, Shutters and Dade County Roof

Appendix B.
Damage State Functions for Manufactured Homes

Appendix B. Damage State Functions for Manufactured Homes

This appendix presents damage state curves for manufactured homes (see Section 6.5). The damage state curves show the probability of achieving a certain damage state versus storm-maximum peak gust speed (open terrain at 10m above ground). Plots are presented for the overall building damage states and for the individual building component damage states (refer to Table 6.5-6 for damage state definitions). As shown in Table B.1, separate figures are provided for five different terrains.

Table B.1. Damage State Functions for Manufactured Homes

Figure	Terrain
B.1	0.03
B.2	0.15
B.3	0.35
B.4	0.70
B.5	1.00




Figure B.1. Damage State Curves for Manufactured Homes Located in Typical Open Terrain described by $z_0 = 0.03$ m.




Figure B.2. Damage State Curves for Manufactured Homes Located in a Relatively Open Terrain Described by $z_0 = 0.15$ m.




Figure B.3. Damage State Curves for Manufactured Homes Located in Typical Suburban Terrain Described by $z_0 = 0.35$ m.




Figure B.4. Damage State Curves for Manufactured Homes Located in Lightly Treed Terrain Described with $z_0 = 0.70$ m.




Figure B.5. Damage State Curves for Manufactured Homes Located in Typical Treed Terrain Described with $z_0 = 1.0$ m.

Appendix C.
Damage State Functions for Marginally- or Non-
Engineered Hotel/Motel and Multi-Family Residential
Buildings

Appendix C. Damage State Functions for Marginally- or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings

This appendix presents damage state curves for marginally-engineered or non-engineered hotel/motel and multi-family/residential buildings (see Section 6.9). The damage state curves show the probability of achieving a certain damage state versus storm-maximum peak gust speed (open terrain at 10m above ground). Plots are presented for the overall building damage states and for the individual building component damage states (refer to Table 6.4-1 for damage state definitions).

As shown in Table C.1, two sets of thirteen figures are given in this appendix. The first set of thirteen figures (Figures C.1 through C.13) are for buildings located in an open terrain ($z = 0.03$ m) and the second set (Figures C.14 through C.26) are for buildings situated in a typical suburban environment ($z_0 = 0.35$ m). The first figure in each set of thirteen shows damage state results for a one-story building with 8d roof sheathing nails, strapped roof-wall connections, wood frame walls and a gable roof with shingles. The remaining twelve plots in each set show damage state results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles). Figures C.27 and C.28 show the reference building situated in two additional terrain environments (i.e., $z_0 = 0.7$ m and 1.0 m).

Table C.1. Sample Damage State Functions for Marginally or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings

Figure	Walls	Stories	Sheathing	Roof/Wall	Roof Shape	Roof Cover	Terrain
C.1	WFR	1	8d	Strap	Gable	Shingles	0.03
C.2	WFR	1	8d	Strap	Hip	Shingles	0.03
C.3	WFR	1	8d	Strap	Flat	BUR, Average	0.03
C.4	WFR	1	8d	Strap	Flat	BUR, Poor	0.03
C.5	WFR	1	8d	Strap	Flat	EPDM, Average	0.03
C.6	WFR	1	8d	Strap	Flat	EPDM, Poor	0.03
C.7	WFR	1	6d	Strap	Gable	Shingles	0.03
C.8	WFR	1	8d	Toe-Nail	Gable	Shingles	0.03
C.9	URM	1	8d	Strap	Gable	Shingles	0.03
C.10	RM	1	8d	Strap	Gable	Shingles	0.03
C.11	WFR	2	8d	Strap	Gable	Shingles	0.03
C.12	WFR	3	8d	Strap	Gable	Shingles	0.03
C.13	WFR	4	8d	Strap	Gable	Shingles	0.03

Table C.1. Sample Damage State Functions for Marginally or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings (concluded)

Figure	Walls	Stories	Sheathing	Roof/Wall	Roof Shape	Roof Cover	Terrain
C.14	WFR	1	8d	Strap	Gable	Shingles	0.35
C.15	WFR	1	8d	Strap	Hip	Shingles	0.35
C.16	WFR	1	8d	Strap	Flat	BUR, Average	0.35
C.17	WFR	1	8d	Strap	Flat	BUR, Poor	0.35
C.18	WFR	1	8d	Strap	Flat	EPDM, Average	0.35
C.19	WFR	1	8d	Strap	Flat	EPDM, Poor	0.35
C.20	WFR	1	6d	Strap	Gable	Shingles	0.35
C.21	WFR	1	8d	Toe-Nail	Gable	Shingles	0.35
C.22	URM	1	8d	Strap	Gable	Shingles	0.35
C.23	RM	1	8d	Strap	Gable	Shingles	0.35
C.24	WFR	2	8d	Strap	Gable	Shingles	0.35
C.25	WFR	3	8d	Strap	Gable	Shingles	0.35
C.26	WFR	4	8d	Strap	Gable	Shingles	0.35
C.27	WFR	1	8d	Strap	Gable	Shingles	0.70
C.28	WFR	1	8d	Strap	Gable	Shingles	1.00




Figure C.1. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.03$ m.




Figure C.2. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Hip Roof with Shingles, $z_{\theta}=0.03$ m.




Figure C.3. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality BUR, $z_0=0.03$ m.




Figure C.4. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality BUR, $z_{\theta}=0.03$ m.




Figure C.5. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality EPDM, $z_0=0.03$ m.




Figure C.6. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality EPDM, $z_0=0.03$ m.




Figure C.7. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 6d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.03$ m.




Figure C.8. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Toe-Nailed Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{0f}=0.03$ m.




Figure C.9. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Unreinforced Masonry Walls, Gable Roof with Shingles, $z_0=0.03$ m.




Figure C.10. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Reinforced Masonry Walls, Gable Roof with Shingles, $z_0=0.03$ m.




Figure C.11. Damage States vs. Maximum Peak Gust Wind Speed – Two-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.03$ m.




Figure C.12. Damage States vs. Maximum Peak Gust Wind Speed – Three-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{0}=0.03$ m.




Figure C.13. Damage States vs. Maximum Peak Gust Wind Speed – Four-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.03$ m.




Figure C.14. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.35$ m.




Figure C.15. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Hip Roof with Shingles, $z_{\theta}=0.35$ m.




Figure C.16. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality BUR, $z_0=0.35$ m.




Figure C.17. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality BUR, $z_0=0.35$ m.




Figure C.18. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality EPDM, $z_0=0.35$ m.




Figure C.19. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality EPDM, $z_0=0.35$ m.




Figure C.20. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 6d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.35$ m.




Figure C.21. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Toe-Nailed Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{0}=0.35$ m.




Figure C.22. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Unreinforced Masonry Walls, Gable Roof with Shingles, $z_0=0.35$ m.




Figure C.23. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Reinforced Masonry Walls, Gable Roof with Shingles, $z_0=0.35$ m.




Figure C.24. Damage States vs. Maximum Peak Gust Wind Speed – Two-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.35$ m.




Figure C.25. Damage States vs. Maximum Peak Gust Wind Speed – Three-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_0=0.35$ m.




Figure C.26. Damage States vs. Maximum Peak Gust Wind Speed – Four-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.35$ m.




Figure C.27. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_{\theta}=0.70$ m.




Figure C.28. Damage States vs. Maximum Peak Gust Wind Speed – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles, $z_0=1.0$ m.

Appendix D.
Damage State Functions for Low Rise Masonry Strip
Mall Buildings

Appendix D. Damage State Functions for Low Rise Masonry Strip Mall Buildings

This appendix presents damage state curves for low rise masonry strip mall buildings. The damage state curves show the probability of achieving a certain damage state versus storm-maximum peak gust speed (open terrain at 10m above ground). Plots are presented for the overall building damage states and for the individual building component damage states (refer to Table 6.10-1 for damage state definitions). As shown in Table D.1, Figures D.1 through D.20 give example results for buildings modeled with a wood roof system. Figures D.21 through D.44 give example results for buildings modeled with a steel roof system.

Table D.1. Sample Damage State Functions for Low Rise Masonry Strip Mall Buildings

Figure	Walls	Height	Number of Units	Roof Frame	Frame Spacing	Roof/Wall	Deck Mat'l.	Deck Attachment	Design Code	Roof Cover	Missile Environ.	Terrain
D.1	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	0.03
D.2	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	B	0.03
D.3	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	C	0.03
D.4	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	D	0.03
D.5	URM	12'	6	Wood	2'	Strap	Wood	8d	-	EPDM	A	0.03
D.6	URM	12'	6	Wood	2'	Strap	Wood	6d	-	BUR	A	0.03
D.7	RM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	0.03
D.8	URM	12'	6	Wood	2'	Toe-Nail	Wood	8d	-	BUR	A	0.03
D.9	URM	20'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	0.03
D.10	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	0.35
D.11	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	B	0.35
D.12	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	C	0.35
D.13	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	D	0.35
D.14	URM	12'	6	Wood	2'	Strap	Wood	8d	-	EPDM	A	0.35
D.15	URM	12'	6	Wood	2'	Strap	Wood	6d	-	BUR	A	0.35
D.16	RM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	0.35
D.17	URM	12'	6	Wood	2'	Toe-Nail	Wood	8d	-	BUR	A	0.35
D.18	URM	20'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	0.35
D.19	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	0.70
D.20	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A	1.00
D.21	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.22	URM	20'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.23	URM	20'	1	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.24	URM	12'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.25	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	B	0.03
D.26	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	C	0.03
D.27	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	D	0.03
D.28	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	EPDM	A	0.03

Table D.1. Sample Damage State Functions for Low Rise Masonry Strip Mall Buildings (concluded)

Figure	Walls	Height	Number of Units	Roof Frame	Frame Spacing	Roof/Wall	Deck Mat'l.	Deck Attachment	Design Code	Roof Cover	Missile Environ.	Terrain
D.29	URM	20'	6	OWSJ	6'	-	Metal	Weld, 50%	SBCCI, 100	BUR	A	0.03
D.30	URM	20'	6	OWSJ	6'	-	Metal	Screw	SBCCI, 100	BUR	A	0.03
D.31	URM	20'	6	OWSJ	6'	-	Metal	Weld	ASCE, 100	BUR	A	0.03
D.32	RM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.33	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	0.35
D.34	URM	20'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.35	URM	20'	1	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.36	URM	12'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.37	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	B	0.03
D.38	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	C	0.03
D.39	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	D	0.03
D.40	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	EPDM	A	0.03
D.41	URM	20'	6	OWSJ	6'	-	Metal	Weld, 50%	SBCCI, 100	BUR	A	0.03
D.42	URM	20'	6	OWSJ	6'	-	Metal	Screw	SBCCI, 100	BUR	A	0.03
D.43	URM	20'	6	OWSJ	6'	-	Metal	Weld	ASCE, 100	BUR	A	0.03
D.44	RM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	0.03
D.45	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	0.70
D.46	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A	1.00

Two sets of nine figures are given for the buildings modeled with a wood roof system. The first set of nine figures (Figures D.1 through D.9) are for buildings located in an open terrain ($z_0=0.03$ m) and the second set (Figures D.10 through D.18) are for buildings situated in a typical suburban environment ($z_0=0.35$ m). The first figure in each set of nine shows damage state results for the 12' high building with 6 units, 8d roof sheathing nails, strapped roof-wall connections, built-up roof cover, Unreinforced masonry walls, and situated in Missile Environment A. The remaining eight plots in each set show damage state results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles). Figures D.19 and D.20 show results of the reference building situated in two additional terrain environments (i.e., $z_0=0.70$ m and 1.0 m).

Two sets of twelve figures are given for the buildings modeled with a metal roof system. The first set of twelve figures (Figures D.21 through D.32) are for buildings located in an open terrain ($z_0=0.03$ m) and the second set (Figures D.33 through D.44) are for buildings situated in a typical suburban environment ($z_0=0.35$ m). The first figure in each set of twelve shows damage state results for the 20' high building with 6 units, a joist spacing of 6', metal deck fastened with welds, SBCCI roof design criteria, built-up roof cover, Unreinforced masonry walls, and situated in Missile Environment A. The remaining eleven plots in each set show damage state results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles). Figures D.45 and D.46 show results of the reference building situated in two additional terrain environments (i.e., $z_0=0.70$ m and 1.0 m).




Figure D.1. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.2. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B, $z_0=0.03$ m.




Figure D.3. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C, $z_0=0.03$ m.




Figure D.4. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D, $z_0=0.03$ m.




Figure D.5. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.6. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 6d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.7. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.8. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Toe-Nailed Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.9. Damage States vs. Peak Gust Wind Speed – Strip Mall Building B – Height=20', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.10. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.11. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B, $z_0=0.35$ m.




Figure D.12. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C, $z_0=0.35$ m.




Figure D.13. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D, $z_0=0.35$ m.




Figure D.14. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.15. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 6d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.16. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.17. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Toe-Nailed Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.18. Damage States vs. Peak Gust Wind Speed – Strip Mall Building B – Height=20', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.19. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.70$ m.




Figure D.20. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=1.0$ m.




Figure D.21. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.22. Damage States vs. Peak Gust Wind Speed – Strip Mall Building B – Height=20', No. of Units=6, Joist Spacing=4', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.23. Damage States vs. Peak Gust Wind Speed – Strip Mall Building D – Height=20', No. of Units=1, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.24. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12', No. of Units=6, Joist Spacing=4', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.25. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B, $z_0=0.03$ m.




Figure D.26. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C, $z_0=0.03$ m.




Figure D.27. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D, $z_0=0.03$ m.




Figure D.28. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.29. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists with 50% Reduction in Resistance, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.30. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Screwed to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.31. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, ASCE 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.32. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure D.33. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.34. Damage States vs. Peak Gust Wind Speed – Strip Mall Building B – Height=20', No. of Units=6, Joist Spacing=4', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.35. Damage States vs. Peak Gust Wind Speed – Strip Mall Building D – Height=20', No. of Units=1, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.36. Damage States vs. Peak Gust Wind Speed – Strip Mall Building A – Height=12’, No. of Units=6, Joist Spacing=4’, Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.37. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B, $z_0=0.35$ m.




Figure D.38. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C, $z_0=0.35$ m.




Figure D.39. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D, $z_0=0.35$ m.




Figure D.40. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.41. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists with 50% Reduction in Resistance, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.42. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Screwed to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.43. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, ASCE 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.44. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A, $z_0=0.35$ m.




Figure D.45. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.70$ m.




Figure D.46. Damage States vs. Peak Gust Wind Speed – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A, $z_0=1.0$ m.

Appendix E.
Damage State Functions for Pre-Engineered Metal
Buildings

Appendix E

Damage State Functions for Pre-Engineered Metal Buildings

This appendix presents damage state curves for pre-engineered metal buildings. The damage state curves show the probability of achieving a certain damage state versus storm-maximum peak gust speed (open terrain at 10m above ground). Plots are presented for the overall building damage states and for the individual building component damage states (refer to Table 6.11-1 for damage state definitions).

As shown in Table E.1, two sets of five figures are given for the metal buildings. The first set of five figures (Figures E.1 through E.5) is for buildings located in an open terrain ($z_0=0.03$ m) and the second set (Figures E.6 through E.10) is for buildings situated in a typical suburban environment ($z_0=0.35$ m). The first figure in each set of five shows damage state results for the small metal building designed using a 100 mph design speed and with no reduction in the metal roof panel capacity. The remaining four plots in each set show damage state results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles). Figures E.11 and E.12 show results of the reference building situated in two additional terrain environments (i.e., $z_0=0.70$ m and 1.0 m).

Table E.1. Damage State Functions for Pre-Engineered Metal Buildings

Figure	Model Building	Design Wind Speed	Metal Panel Capacity	Terrain
E.1	Small	100 mph	Full	0.03
E.2	Medium	100 mph	Full	0.03
E.3	Large	100 mph	Full	0.03
E.4	Small	90 mph	Full	0.03
E.5	Small	100 mph	50%	0.03
E.6	Small	100 mph	Full	0.35
E.7	Medium	100 mph	Full	0.35
E.8	Large	100 mph	Full	0.35
E.9	Small	90 mph	Full	0.35
E.10	Small	100 mph	50%	0.35
E.11	Small	100 mph	Full	0.70
E.12	Small	100 mph	Full	1.00




Figure E.1. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, $z_0=0.03$ m, No Reduction in Metal Panel Capacity.




Figure E.2. Damage States vs. Peak Gust Wind Speed – Medium-Sized Metal Building, 100 mph Design Speed, $z_0=0.03$ m, No Reduction in Metal Panel Capacity..




Figure E.3. Damage States vs. Peak Gust Wind Speed – Large Metal Building, 100 mph Design Speed, $z_0=0.03$ m, No Reduction in Metal Panel Capacity.




Figure E.4. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 90 mph Design Speed, $z_0=0.03$ m, No Reduction in Metal Panel Capacity.




Figure E.5. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, $z_0=0.03$ m, 50% Reduction in Metal Panel Capacity.




Figure E.6. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, $z_0=0.35$ m, No Reduction in Metal Panel Capacity.




Figure E.7. Damage States vs. Peak Gust Wind Speed – Medium-Sized Metal Building, 100 mph Design Speed, $z_0=0.35$ m, No Reduction in Metal Panel Capacity.




Figure E.8. Damage States vs. Peak Gust Wind Speed – Large Metal Building, 100 mph Design Speed, $z_0=0.35$ m, No Reduction in Metal Panel Capacity.




Figure E.9. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 90 mph Design Speed, $z_0=0.35$ m, No Reduction in Metal Panel Capacity.




Figure E.10. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, $z_0=0.35$ m, 50% Reduction in Metal Panel Capacity.




Figure E.11. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, $z_0=0.70$ m, No Reduction in Metal Panel Capacity.




Figure E.12. Damage States vs. Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, $z_0=1.0$ m, No Reduction in Metal Panel Capacity.

Appendix F.
**Damage State Functions for Engineered Residential
and Commercial Buildings**

Appendix F. Damage State Functions for Engineered Residential and Commercial Buildings

This appendix presents damage state curves for engineered residential and commercial buildings. The damage state curves show the probability of achieving a certain damage state versus storm-maximum peak gust speed (open terrain at 10m above ground). Plots are presented for the overall building damage states and for the individual building component damage states (refer to Table 6.12-1 for damage state definitions).

Table F.1 lists the figures provided in this appendix. Damage state plots for the two-, five- and eight-story buildings are given in Figures F.1 through F.18, F.19 through F.36 and F.37 through F.54, respectively. Two sets of eight figures are given for each of the two-, five- and eight-story engineered buildings. The first set of eight figures are for buildings located in an open terrain ($z_0=0.03$ m) and the second set are for buildings situated in a typical suburban environment ($z_0=0.35$ m). The first figure in each set of eight shows damage state results for the engineered residential building having 33% glazing coverage, a built-up roof cover and situated in Missile Environment A. The remaining seven plots in each set show damage state results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles). The last two figures associated with the two-, five- and eight-story engineered buildings show results of the reference building situated in two additional terrain environments (i.e., $z_0=0.70$ m and 1.0 m).

Table F.1. Sample Damage State Functions for Engineered Residential and Commercial Buildings

Figure	Stories	Occupancy	Roof Cover	Glazing	Missile Environ.	Terrain
F.1	2	Residential	BUR	33%	A	0.03
F.2	2	Residential	BUR	20%	A	0.03
F.3	2	Residential	BUR	50%	A	0.03
F.4	2	Residential	SPM	33%	A	0.03
F.5	2	Residential	BUR	33%	B	0.03
F.6	2	Residential	BUR	33%	C	0.03
F.7	2	Residential	BUR	33%	D	0.03
F.8	2	Commercial	BUR	33%	A	0.03
F.9	2	Residential	BUR	33%	A	0.35
F.10	2	Residential	BUR	20%	A	0.35
F.11	2	Residential	BUR	50%	A	0.35
F.12	2	Residential	SPM	33%	A	0.35
F.13	2	Residential	BUR	33%	B	0.35
F.14	2	Residential	BUR	33%	C	0.35
F.15	2	Residential	BUR	33%	D	0.35
F.16	2	Commercial	BUR	33%	A	0.35
F.17	2	Residential	BUR	33%	A	0.70

Table F.1. Sample Damage State Functions for Engineered Residential and Commercial Buildings (concluded)

Figure	Stories	Occupancy	Roof Cover	Glazing	Missile Environ.	Terrain
F.18	2	Residential	BUR	33%	A	1.00
F.19	5	Residential	BUR	33%	A	0.03
F.20	5	Residential	BUR	20%	A	0.03
F.21	5	Residential	BUR	50%	A	0.03
F.22	5	Residential	SPM	33%	A	0.03
F.23	5	Residential	BUR	33%	B	0.03
F.24	5	Residential	BUR	33%	C	0.03
F.25	5	Residential	BUR	33%	D	0.03
F.26	5	Commercial	BUR	33%	A	0.03
F.27	5	Residential	BUR	33%	A	0.35
F.28	5	Residential	BUR	20%	A	0.35
F.29	5	Residential	BUR	50%	A	0.35
F.30	5	Residential	SPM	33%	A	0.35
F.31	5	Residential	BUR	33%	B	0.35
F.32	5	Residential	BUR	33%	C	0.35
F.33	5	Residential	BUR	33%	D	0.35
F.34	5	Commercial	BUR	33%	A	0.35
F.35	5	Residential	BUR	33%	A	0.70
F.36	5	Residential	BUR	33%	A	1.00
F.37	8	Residential	BUR	33%	A	0.03
F.38	8	Residential	BUR	20%	A	0.03
F.39	8	Residential	BUR	50%	A	0.03
F.40	8	Residential	SPM	33%	A	0.03
F.41	8	Residential	BUR	33%	B	0.03
F.42	8	Residential	BUR	33%	C	0.03
F.43	8	Residential	BUR	33%	D	0.03
F.44	8	Commercial	BUR	33%	A	0.03
F.45	8	Residential	BUR	33%	A	0.35
F.46	8	Residential	BUR	20%	A	0.35
F.47	8	Residential	BUR	50%	A	0.35
F.48	8	Residential	SPM	33%	A	0.35
F.49	8	Residential	BUR	33%	B	0.35
F.50	8	Residential	BUR	33%	C	0.35
F.51	8	Residential	BUR	33%	D	0.35
F.52	8	Commercial	BUR	33%	A	0.35
F.53	8	Residential	BUR	33%	A	0.70
F.54	8	Residential	BUR	33%	A	1.00




Figure F.1. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_{\theta}=0.03$ m.




Figure F.2. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.3. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.4. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.5. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment B, $z_{\theta}=0.03$ m.




Figure F.6. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment C, $z_0=0.03$ m.




Figure F.7. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment D, $z_0=0.03$ m.




Figure F.8. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.9. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.10. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Missile Environment A, $z_{\theta}=0.35$ m.




Figure F.11. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.12. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.13. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment B, $z_{\theta}=0.35$ m.




Figure F.14. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment C, $z_{\theta}=0.35$ m.




Figure F.15. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment D, $z_{\theta}=0.35$ m.




Figure F.16. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.17. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.70$ m.




Figure F.18. Damage States vs. Peak Gust Wind Speed – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=1.0$ m.




Figure F.19. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.20. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.21. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Missile Environment A, $z_{\theta}=0.03$ m.




Figure F.22. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.23. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment B, $z_{\theta}=0.03$ m.




Figure F.24. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment C, $z_0=0.03$ m.




Figure F.25. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment D, $z_{\theta}=0.03$ m.




Figure F.26. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.27. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.28. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.29. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.30. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.31. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment B, $z_{\theta}=0.35$ m.




Figure F.32. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment C, $z_0=0.35$ m.




Figure F.33. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment D, $z_{\theta}=0.35$ m.




Figure F.34. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.35. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.70$ m.




Figure F.36. Damage States vs. Peak Gust Wind Speed – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=1.0$ m.




Figure F.37. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.38. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.39. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.40. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.41. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment B, $z_{\theta}=0.03$ m.




Figure F.42. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment C, $z_{\theta}=0.03$ m.




Figure F.43. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment D, $z_{\theta}=0.03$ m.




Figure F.44. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.03$ m.




Figure F.45. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_{\theta}=0.35$ m.




Figure F.46. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.47. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Missile Environment A, $z_{\theta}=0.35$ m.




Figure F.48. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.49. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment B, $z_{\theta}=0.35$ m.




Figure F.50. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment C, $z_{\theta}=0.35$ m.




Figure F.51. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment D, $z_{\theta}=0.35$ m.




Figure F.52. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.35$ m.




Figure F.53. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_0=0.70$ m.




Figure F.54. Damage States vs. Peak Gust Wind Speed – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Missile Environment A, $z_{\theta}=1.0$ m.

Appendix G.
Damage State Functions for Industrial Buildings

Appendix G. Damage State Functions for Industrial Buildings

This appendix presents damage state curves for industrial buildings. The damage state curves show the probability of achieving a certain damage state versus storm-maximum peak gust speed (open terrain at 10m above ground). Plots are presented for the overall building damage states and for the individual building component damage states (refer to Table 6.13-1 for damage state definitions).

Table G.1 lists the figures provided in this appendix. Two sets of three figures are given for the metal buildings. The first set of three figures (Figures G.1 through G.3) are for buildings located in an open terrain ($z_0=0.03$ m) and the second set (Figures G.4 through G.6) are for buildings situated in a typical suburban environment ($z_0=0.35$ m). The first figure in each set of three shows damage state results for the industrial building constructed with unreinforced masonry walls, having no reduction in the metal roof deck capacity and situated in Missile Environment A. The remaining two plots in each set show damage state results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles). Figures G.7 and G.8 show results of the reference building situated in two additional terrain environments (i.e., $z_0=0.70$ m and 1.0 m).

Table G.1. Sample Damage State Functions for Industrial Buildings

Figure	Walls	Metal Deck Capacity	Missile Environ.	Terrain
G.1	URM	Full	A	0.03
G.2	RM	Full	A	0.03
G.3	URM	50%	A	0.03
G.4	URM	Full	A	0.35
G.5	RM	Full	A	0.35
G.6	URM	50%	A	0.35
G.7	URM	Full	A	0.70
G.8	URM	Full	A	1.00




Figure G.1. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – No Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure G.2. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – No Reduction in Metal Deck Capacity, Reinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure G.3. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – 50% Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.03$ m.




Figure G.4. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – No Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A, $z_{\theta}=0.35$ m.




Figure G.5. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – No Reduction in Metal Deck Capacity, Reinforced Masonry Walls, Missile Environment A, $z_\theta=0.35$ m.




Figure G.6. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – 50% Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A, $z_{\theta}=0.35$ m.




Figure G.7. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – No Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A, $z_0=0.7$ m.




Figure G.8. Damage States vs. Maximum Peak Gust Wind Speed – Industrial Building – No Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A, $z_{\theta}=1.0$ m.

Appendix H.
Loss Functions for Residential Buildings

Appendix H. Loss Functions for Residential Buildings

This appendix presents loss functions for residential buildings (see Section 7.7). The loss functions represent either average building loss normalized by building value or average content loss normalized by content value. Therefore, the loss ratios range between 0 and 1 in both cases. Note that the content value is set to 50% of the building value. For a given simulated storm, the building loss ratio and content loss ratio are estimated based on the modeled damage and the largest gust speed over the entire duration of the simulated storm is saved. The loss functions are then computed by averaging the loss ratios associated with the storms producing a maximum gust speed within 5 mph ranges. The average loss ratios (content or building loss) associated with each 5 mph gust speed range are then plotted at the center of that range. Note that the wind speeds are representative of open terrain at 10 m above ground.

Table H.1 lists the figures provided in this appendix. In each set of sixteen plots, the building parameters varied are: roof deck nails (6d or 8d), roof/wall connections (to E.nail or strap), number of stories (one or two), and roof shape (gable or hip). Plots are presented for the buildings constructed with wood frame walls and for the buildings having no garage.

Table H.1. Sample Loss Functions for Residential Buildings

Figure	Loss Type	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Secondary Water Resistance
H.1	Building	WFR	1	No	Gable	6d	Toe-Nail	No	No	No
H.2	Building	WFR	1	No	Gable	6d	Strap	No	No	No
H.3	Building	WFR	1	No	Gable	8d	Toe-Nail	No	No	No
H.4	Building	WFR	1	No	Gable	8d	Strap	No	No	No
H.5	Building	WFR	1	No	Hip	6d	Toe-Nail	No	No	No
H.6	Building	WFR	1	No	Hip	6d	Strap	No	No	No
H.7	Building	WFR	1	No	Hip	8d	Toe-Nail	No	No	No
H.8	Building	WFR	1	No	Hip	8d	Strap	No	No	No
H.9	Building	WFR	2	No	Gable	6d	Toe-Nail	No	No	No
H.10	Building	WFR	2	No	Gable	6d	Strap	No	No	No
H.11	Building	WFR	2	No	Gable	8d	Toe-Nail	No	No	No
H.12	Building	WFR	2	No	Gable	8d	Strap	No	No	No
H.13	Building	WFR	2	No	Hip	6d	Toe-Nail	No	No	No
H.14	Building	WFR	2	No	Hip	6d	Strap	No	No	No
H.15	Building	WFR	2	No	Hip	8d	Toe-Nail	No	No	No
H.16	Building	WFR	2	No	Hip	8d	Strap	No	No	No
H.17	Content	WFR	1	No	Gable	6d	Toe-Nail	No	No	No
H.18	Content	WFR	1	No	Gable	6d	Strap	No	No	No
H.19	Content	WFR	1	No	Gable	8d	Toe-Nail	No	No	No
H.20	Content	WFR	1	No	Gable	8d	Strap	No	No	No
H.21	Content	WFR	1	No	Hip	6d	Toe-Nail	No	No	No

Table H.1. Sample Loss Functions for Residential Buildings (continued)

Figure	Loss Type	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Secondary Water Resistance
H.22	Content	WFR	1	No	Hip	6d	Strap	No	No	No
H.23	Content	WFR	1	No	Hip	8d	Toe-Nail	No	No	No
H.24	Content	WFR	1	No	Hip	8d	Strap	No	No	No
H.25	Content	WFR	2	No	Gable	6d	Toe-Nail	No	No	No
H.26	Content	WFR	2	No	Gable	6d	Strap	No	No	No
H.27	Content	WFR	2	No	Gable	8d	Toe-Nail	No	No	No
H.28	Content	WFR	2	No	Gable	8d	Strap	No	No	No
H.29	Content	WFR	2	No	Hip	6d	Toe-Nail	No	No	No
H.30	Content	WFR	2	No	Hip	6d	Strap	No	No	No
H.31	Content	WFR	2	No	Hip	8d	Toe-Nail	No	No	No
H.32	Content	WFR	2	No	Hip	8d	Strap	No	No	No
H.33	Building	WFR	1	No	Gable	6d	Toe-Nail	Yes	No	No
H.34	Building	WFR	1	No	Gable	6d	Strap	Yes	No	No
H.35	Building	WFR	1	No	Gable	8d	Toe-Nail	Yes	No	No
H.36	Building	WFR	1	No	Gable	8d	Strap	Yes	No	No
H.37	Building	WFR	1	No	Hip	6d	Toe-Nail	Yes	No	No
H.38	Building	WFR	1	No	Hip	6d	Strap	Yes	No	No
H.39	Building	WFR	1	No	Hip	8d	Toe-Nail	Yes	No	No
H.40	Building	WFR	1	No	Hip	8d	Strap	Yes	No	No
H.41	Building	WFR	2	No	Gable	6d	Toe-Nail	Yes	No	No
H.42	Building	WFR	2	No	Gable	6d	Strap	Yes	No	No
H.43	Building	WFR	2	No	Gable	8d	Toe-Nail	Yes	No	No
H.44	Building	WFR	2	No	Gable	8d	Strap	Yes	No	No
H.45	Building	WFR	2	No	Hip	6d	Toe-Nail	Yes	No	No
H.46	Building	WFR	2	No	Hip	6d	Strap	Yes	No	No
H.47	Building	WFR	2	No	Hip	8d	Toe-Nail	Yes	No	No
H.48	Building	WFR	2	No	Hip	8d	Strap	Yes	No	No
H.49	Content	WFR	1	No	Gable	6d	Toe-Nail	Yes	No	No
H.50	Content	WFR	1	No	Gable	6d	Strap	Yes	No	No
H.51	Content	WFR	1	No	Gable	8d	Toe-Nail	Yes	No	No
H.52	Content	WFR	1	No	Gable	8d	Strap	Yes	No	No
H.53	Content	WFR	1	No	Hip	6d	Toe-Nail	Yes	No	No
H.54	Content	WFR	1	No	Hip	6d	Strap	Yes	No	No
H.55	Content	WFR	1	No	Hip	8d	Toe-Nail	Yes	No	No
H.56	Content	WFR	1	No	Hip	8d	Strap	Yes	No	No
H.57	Content	WFR	2	No	Gable	6d	Toe-Nail	Yes	No	No
H.58	Content	WFR	2	No	Gable	6d	Strap	Yes	No	No
H.59	Content	WFR	2	No	Gable	8d	Toe-Nail	Yes	No	No
H.60	Content	WFR	2	No	Gable	8d	Strap	Yes	No	No
H.61	Content	WFR	2	No	Hip	6d	Toe-Nail	Yes	No	No
H.62	Content	WFR	2	No	Hip	6d	Strap	Yes	No	No
H.63	Content	WFR	2	No	Hip	8d	Toe-Nail	Yes	No	No
H.64	Content	WFR	2	No	Hip	8d	Strap	Yes	No	No

Table H.1. Sample Loss Functions for Residential Buildings (continued)

Figure	Loss Type	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Secondary Water Resistance
H.65	Building	WFR	1	No	Gable	6d	Toe-Nail	No	Yes	No
H.66	Building	WFR	1	No	Gable	6d	Strap	No	Yes	No
H.67	Building	WFR	1	No	Gable	8d	Toe-Nail	No	Yes	No
H.68	Building	WFR	1	No	Gable	8d	Strap	No	Yes	No
H.69	Building	WFR	1	No	Hip	6d	Toe-Nail	No	Yes	No
H.70	Building	WFR	1	No	Hip	6d	Strap	No	Yes	No
H.71	Building	WFR	1	No	Hip	8d	Toe-Nail	No	Yes	No
H.72	Building	WFR	1	No	Hip	8d	Strap	No	Yes	No
H.73	Building	WFR	2	No	Gable	6d	Toe-Nail	No	Yes	No
H.74	Building	WFR	2	No	Gable	6d	Strap	No	Yes	No
H.75	Building	WFR	2	No	Gable	8d	Toe-Nail	No	Yes	No
H.76	Building	WFR	2	No	Gable	8d	Strap	No	Yes	No
H.77	Building	WFR	2	No	Hip	6d	Toe-Nail	No	Yes	No
H.78	Building	WFR	2	No	Hip	6d	Strap	No	Yes	No
H.79	Building	WFR	2	No	Hip	8d	Toe-Nail	No	Yes	No
H.80	Building	WFR	2	No	Hip	8d	Strap	No	Yes	No
H.81	Content	WFR	1	No	Gable	6d	Toe-Nail	No	Yes	No
H.82	Content	WFR	1	No	Gable	6d	Strap	No	Yes	No
H.83	Content	WFR	1	No	Gable	8d	Toe-Nail	No	Yes	No
H.84	Content	WFR	1	No	Gable	8d	Strap	No	Yes	No
H.85	Content	WFR	1	No	Hip	6d	Toe-Nail	No	Yes	No
H.86	Content	WFR	1	No	Hip	6d	Strap	No	Yes	No
H.87	Content	WFR	1	No	Hip	8d	Toe-Nail	No	Yes	No
H.88	Content	WFR	1	No	Hip	8d	Strap	No	Yes	No
H.89	Content	WFR	2	No	Gable	6d	Toe-Nail	No	Yes	No
H.90	Content	WFR	2	No	Gable	6d	Strap	No	Yes	No
H.91	Content	WFR	2	No	Gable	8d	Toe-Nail	No	Yes	No
H.92	Content	WFR	2	No	Gable	8d	Strap	No	Yes	No
H.93	Content	WFR	2	No	Hip	6d	Toe-Nail	No	Yes	No
H.94	Content	WFR	2	No	Hip	6d	Strap	No	Yes	No
H.95	Content	WFR	2	No	Hip	8d	Toe-Nail	No	Yes	No
H.96	Content	WFR	2	No	Hip	8d	Strap	No	Yes	No
H.97	Building	WFR	1	No	Gable	6d	Toe-Nail	No	Yes	Yes
H.98	Building	WFR	1	No	Gable	6d	Strap	No	Yes	Yes
H.99	Building	WFR	1	No	Gable	8d	Toe-Nail	No	Yes	Yes
H.100	Building	WFR	1	No	Gable	8d	Strap	No	Yes	Yes
H.101	Building	WFR	1	No	Hip	6d	Toe-Nail	No	Yes	Yes
H.102	Building	WFR	1	No	Hip	6d	Strap	No	Yes	Yes
H.103	Building	WFR	1	No	Hip	8d	Toe-Nail	No	Yes	Yes
H.104	Building	WFR	1	No	Hip	8d	Strap	No	Yes	Yes
H.105	Building	WFR	2	No	Gable	6d	Toe-Nail	No	Yes	Yes
H.106	Building	WFR	2	No	Gable	6d	Strap	No	Yes	Yes
H.107	Building	WFR	2	No	Gable	8d	Toe-Nail	No	Yes	Yes

Table H.1. Sample Loss Functions for Residential Buildings (continued)

Figure	Loss Type	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Secondary Water Resistance
H.108	Building	WFR	2	No	Gable	8d	Strap	No	Yes	Yes
H.109	Building	WFR	2	No	Hip	6d	Toe-Nail	No	Yes	Yes
H.110	Building	WFR	2	No	Hip	6d	Strap	No	Yes	Yes
H.111	Building	WFR	2	No	Hip	8d	Toe-Nail	No	Yes	Yes
H.112	Building	WFR	2	No	Hip	8d	Strap	No	Yes	Yes
H.113	Content	WFR	1	No	Gable	6d	Toe-Nail	No	Yes	Yes
H.114	Content	WFR	1	No	Gable	6d	Strap	No	Yes	Yes
H.115	Content	WFR	1	No	Gable	8d	Toe-Nail	No	Yes	Yes
H.116	Content	WFR	1	No	Gable	8d	Strap	No	Yes	Yes
H.117	Content	WFR	1	No	Hip	6d	Toe-Nail	No	Yes	Yes
H.118	Content	WFR	1	No	Hip	6d	Strap	No	Yes	Yes
H.119	Content	WFR	1	No	Hip	8d	Toe-Nail	No	Yes	Yes
H.120	Content	WFR	1	No	Hip	8d	Strap	No	Yes	Yes
H.121	Content	WFR	2	No	Gable	6d	Toe-Nail	No	Yes	Yes
H.122	Content	WFR	2	No	Gable	6d	Strap	No	Yes	Yes
H.123	Content	WFR	2	No	Gable	8d	Toe-Nail	No	Yes	Yes
H.124	Content	WFR	2	No	Gable	8d	Strap	No	Yes	Yes
H.125	Content	WFR	2	No	Hip	6d	Toe-Nail	No	Yes	Yes
H.126	Content	WFR	2	No	Hip	6d	Strap	No	Yes	Yes
H.127	Content	WFR	2	No	Hip	8d	Toe-Nail	No	Yes	Yes
H.128	Content	WFR	2	No	Hip	8d	Strap	No	Yes	Yes
H.129	Building	WFR	1	No	Gable	6d	Toe-Nail	Yes	Yes	No
H.130	Building	WFR	1	No	Gable	6d	Strap	Yes	Yes	No
H.131	Building	WFR	1	No	Gable	8d	Toe-Nail	Yes	Yes	No
H.132	Building	WFR	1	No	Gable	8d	Strap	Yes	Yes	No
H.133	Building	WFR	1	No	Hip	6d	Toe-Nail	Yes	Yes	No
H.134	Building	WFR	1	No	Hip	6d	Strap	Yes	Yes	No
H.135	Building	WFR	1	No	Hip	8d	Toe-Nail	Yes	Yes	No
H.136	Building	WFR	1	No	Hip	8d	Strap	Yes	Yes	No
H.137	Building	WFR	2	No	Gable	6d	Toe-Nail	Yes	Yes	No
H.138	Building	WFR	2	No	Gable	6d	Strap	Yes	Yes	No
H.139	Building	WFR	2	No	Gable	8d	Toe-Nail	Yes	Yes	No
H.140	Building	WFR	2	No	Gable	8d	Strap	Yes	Yes	No
H.141	Building	WFR	2	No	Hip	6d	Toe-Nail	Yes	Yes	No
H.142	Building	WFR	2	No	Hip	6d	Strap	Yes	Yes	No
H.143	Building	WFR	2	No	Hip	8d	Toe-Nail	Yes	Yes	No
H.144	Building	WFR	2	No	Hip	8d	Strap	Yes	Yes	No
H.145	Content	WFR	1	No	Gable	6d	Toe-Nail	Yes	Yes	No
H.146	Content	WFR	1	No	Gable	6d	Strap	Yes	Yes	No
H.147	Content	WFR	1	No	Gable	8d	Toe-Nail	Yes	Yes	No
H.148	Content	WFR	1	No	Gable	8d	Strap	Yes	Yes	No
H.149	Content	WFR	1	No	Hip	6d	Toe-Nail	Yes	Yes	No
H.150	Content	WFR	1	No	Hip	6d	Strap	Yes	Yes	No

Table H.1. Sample Loss Functions for Residential Buildings (concluded)

Figure	Loss Type	Walls	Stories	Garage	Roof Shape	Sheathing	Roof/ Wall	Shutters	Upgraded Roof	Secondary Water Resistance
H.151	Content	WFR	1	No	Hip	8d	Toe-Nail	Yes	Yes	No
H.152	Content	WFR	1	No	Hip	8d	Strap	Yes	Yes	No
H.153	Content	WFR	2	No	Gable	6d	Toe-Nail	Yes	Yes	No
H.154	Content	WFR	2	No	Gable	6d	Strap	Yes	Yes	No
H.155	Content	WFR	2	No	Gable	8d	Toe-Nail	Yes	Yes	No
H.156	Content	WFR	2	No	Gable	8d	Strap	Yes	Yes	No
H.157	Content	WFR	2	No	Hip	6d	Toe-Nail	Yes	Yes	No
H.158	Content	WFR	2	No	Hip	6d	Strap	Yes	Yes	No
H.159	Content	WFR	2	No	Hip	8d	Toe-Nail	Yes	Yes	No
H.160	Content	WFR	2	No	Hip	8d	Strap	Yes	Yes	No
H.161	Building	WFR	1	No	Gable	6d	Toe-Nail	Yes	Yes	Yes
H.162	Building	WFR	1	No	Gable	6d	Strap	Yes	Yes	Yes
H.163	Building	WFR	1	No	Gable	8d	Toe-Nail	Yes	Yes	Yes
H.164	Building	WFR	1	No	Gable	8d	Strap	Yes	Yes	Yes
H.165	Building	WFR	1	No	Hip	6d	Toe-Nail	Yes	Yes	Yes
H.166	Building	WFR	1	No	Hip	6d	Strap	Yes	Yes	Yes
H.167	Building	WFR	1	No	Hip	8d	Toe-Nail	Yes	Yes	Yes
H.168	Building	WFR	1	No	Hip	8d	Strap	Yes	Yes	Yes
H.169	Building	WFR	2	No	Gable	6d	Toe-Nail	Yes	Yes	Yes
H.170	Building	WFR	2	No	Gable	6d	Strap	Yes	Yes	Yes
H.171	Building	WFR	2	No	Gable	8d	Toe-Nail	Yes	Yes	Yes
H.172	Building	WFR	2	No	Gable	8d	Strap	Yes	Yes	Yes
H.173	Building	WFR	2	No	Hip	6d	Toe-Nail	Yes	Yes	Yes
H.174	Building	WFR	2	No	Hip	6d	Strap	Yes	Yes	Yes
H.175	Building	WFR	2	No	Hip	8d	Toe-Nail	Yes	Yes	Yes
H.176	Building	WFR	2	No	Hip	8d	Strap	Yes	Yes	Yes
H.177	Content	WFR	1	No	Gable	6d	Toe-Nail	Yes	Yes	Yes
H.178	Content	WFR	1	No	Gable	6d	Strap	Yes	Yes	Yes
H.179	Content	WFR	1	No	Gable	8d	Toe-Nail	Yes	Yes	Yes
H.180	Content	WFR	1	No	Gable	8d	Strap	Yes	Yes	Yes
H.181	Content	WFR	1	No	Hip	6d	Toe-Nail	Yes	Yes	Yes
H.182	Content	WFR	1	No	Hip	6d	Strap	Yes	Yes	Yes
H.183	Content	WFR	1	No	Hip	8d	Toe-Nail	Yes	Yes	Yes
H.184	Content	WFR	1	No	Hip	8d	Strap	Yes	Yes	Yes
H.185	Content	WFR	2	No	Gable	6d	Toe-Nail	Yes	Yes	Yes
H.186	Content	WFR	2	No	Gable	6d	Strap	Yes	Yes	Yes
H.187	Content	WFR	2	No	Gable	8d	Toe-Nail	Yes	Yes	Yes
H.188	Content	WFR	2	No	Gable	8d	Strap	Yes	Yes	Yes
H.189	Content	WFR	2	No	Hip	6d	Toe-Nail	Yes	Yes	Yes
H.190	Content	WFR	2	No	Hip	6d	Strap	Yes	Yes	Yes
H.191	Content	WFR	2	No	Hip	8d	Toe-Nail	Yes	Yes	Yes
H.192	Content	WFR	2	No	Hip	8d	Strap	Yes	Yes	Yes




Figure H.1. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.2. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.3. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.4. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.5. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.6. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.7. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.8. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.9. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.10. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.11. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.12. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Straped Roof Wall Connections, Wood Frame).




Figure H.13. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.14. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.15. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.16. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.17. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.18. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.19. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.20. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.21. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.22. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.23. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.24. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.25. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.26. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.27. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.28. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.29. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.30. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame).




Figure H.31. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame).




Figure H.32. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Straped Roof Wall Connections, Wood Frame).




Figure H.33. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.34. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.35. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.36. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.37. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.38. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.39. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.40. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.41. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.42. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.43. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.44. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.45. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.46. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.47. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.48. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.49. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.50. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.51. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.52. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.53. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.54. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.55. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.56. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.57. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.58. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.59. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.60. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.61. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.62. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.63. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.64. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters).




Figure H.65. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.66. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.67. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.68. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Straped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.69. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.70. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.71. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.72. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.73. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.74. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.75. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.76. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.77. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.78. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.79. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.80. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.81. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.82. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.83. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.84. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.85. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.86. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.87. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.88. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.89. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.90. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.91. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.92. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.93. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.94. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.95. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.96. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof).




Figure H.97. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.98. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.99. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.100. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.101. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.102. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.103. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.104. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.105. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.106. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.107. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.108. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.109. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.110. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.111. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.112. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.113. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.114. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.115. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.116. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.117. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.118. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.119. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.120. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.121. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.122. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.123. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.124. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.125. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.126. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.127. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.128. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Upgraded Roof and Added Secondary Water Resistance).




Figure H.129. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.130. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.131. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.132. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.133. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.134. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.135. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.136. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.137. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.138. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.139. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.140. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.141. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.142. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.143. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.144. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.145. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.146. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.147. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.148. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.149. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.150. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.151. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.152. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.153. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.154. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.155. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.156. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.157. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.158. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.159. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.160. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters and Upgraded Roof).




Figure H.161. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.162. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.163. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.164. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.165. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.166. Building Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.167. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.168. Building Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.169. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.170. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.171. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.172. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.173. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.174. Building Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.175. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.176. Building Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.177. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.178. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.179. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.180. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.181. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.182. Content Loss Function for Single Family Residential Building (One Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.183. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.184. Content Loss Function for Single Family Residential Building (One Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.185. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.186. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.187. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.188. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Gable Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.189. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.190. Content Loss Function for Single Family Residential Building (Two Story, 6d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.191. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Toe-Nailed Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance).




Figure H.192. Content Loss Function for Single Family Residential Building (Two Story, 8d Roof Sheathing Nails, Hip Roof, No Garage, Strapped Roof Wall Connections, Wood Frame, Installed Shutters, Upgraded Roof and Added Secondary Water Resistance)

Appendix I.
Loss Functions for Manufactured Homes

Appendix I. Loss Functions for Manufactured Homes


This appendix presents loss functions for manufactured homes (see Section 7.8). The loss functions represent either average building loss normalized by building value or average content loss normalized by content value. Therefore, the loss ratios range between 0 and 1 in both cases. Note that the content value is set to 50% of the building value. For a given simulated storm, the building loss ratio and content loss ratio are estimated based on the modeled damage and the largest gust speed over the entire duration of the simulated storm is saved. The loss functions are then computed by averaging the loss ratios associated with the storms producing a maximum gust speed within 5 mph ranges. The average loss ratios (content or building loss) associated with each 5 mph gust speed range are then plotted at the center of that range. Note that the wind speeds are representative of open terrain at 10 m above ground.

Table I.1 lists the figures provided in this appendix.


Table I.1. Loss Functions for Manufactured Homes

Figure	Loss Type
I.1	Building
I.2	Content


1994 HUD – Wind Zone III, Tied Down




1994 HUD – Wind Zone II, Tied Down




1994 HUD – Wind Zone II, Tied Down




HUD, Tied Down



HUD, Not Tied Down



Pre-HUD, Tied Down



Pre-HUD, Not Tied Down






Figure I.1. Building Loss Functions for Manufactured Homes.


1994 HUD – Wind Zone III, Tied Down




1994 HUD – Wind Zone II, Tied Down




1994 HUD – Wind Zone II, Tied Down




HUD, Tied Down



HUD, Not Tied Down



Pre-HUD, Tied Down



Pre-HUD, Not Tied Down




Figure I.2. Content Loss Functions for Manufactured Homes.

Appendix J.
Loss Functions for Marginally- or Non-Engineered
Hotel/Motel and Multi-Family Residential Buildings

Appendix J. Loss Functions for Marginally- or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings

This appendix presents loss functions for marginally-engineered hotel/motel and multi-family residential buildings (see Section 7.10). The loss functions represent either average building loss normalized by building value or average content loss normalized by content value. Therefore, the loss ratios range between 0 and 1 in both cases. Note that the content value is set to 50% of the building value. For a given simulated storm, the building loss ratio and content loss ratio are estimated based on the modeled damage and the largest gust speed over the entire duration of the simulated storm is saved. The loss functions are then computed by averaging the loss ratios associated with the storms producing a maximum gust speed within 5mph ranges. The average loss ratios (content or building loss) associated with each 5 mph gust speed range are then plotted at the center of that range. Note that the wind speeds are representative of open terrain at 10 m above ground.

Table J.1 lists the figures provided in this appendix. Two sets of thirteen figures are shown. The first set of thirteen figures (Figures J.1 through J.13) show building loss ratios and the second set (Figures J.14 through J.26) shown content loss ratios. The first figure in each set of thirteen shows loss results for a one-story building with 8d roof sheathing nails, strapped roof-wall connections, wood frame walls and a gable roof with shingles. The remaining twelve plots in each set show loss results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles).

**Table J.1. Sample Loss Functions for Marginally-Engineered or Non-Engineered
Hotel/Motel and Multi-Family Residential Buildings**

Figure	Loss Type	Walls	Stories	Sheathing	Roof/ Wall	Roof Shape	Roof Cover
J.1	Building	WFR	1	8d	Strap	Gable	Shingles
J.2	Building	WFR	1	8d	Strap	Hip	Shingles
J.3	Building	WFR	1	8d	Strap	Flat	BUR, Average
J.4	Building	WFR	1	8d	Strap	Flat	BUR, Poor
J.5	Building	WFR	1	8d	Strap	Flat	EPDM, Average
J.6	Building	WFR	1	8d	Strap	Flat	EPDM, Poor
J.7	Building	WFR	1	6d	Strap	Gable	Shingles
J.8	Building	WFR	1	8d	Toe-Nail	Gable	Shingles
J.9	Building	URM	1	8d	Strap	Gable	Shingles
J.10	Building	RM	1	8d	Strap	Gable	Shingles
J.11	Building	WFR	2	8d	Strap	Gable	Shingles
J.12	Building	WFR	3	8d	Strap	Gable	Shingles
J.13	Building	WFR	4	8d	Strap	Gable	Shingles

Table J.1. Sample Loss Functions for Marginally-Engineered or Non-Engineered Hotel/Motel and Multi-Family Residential Buildings (concluded)

Figure	Loss Type	Walls	Stories	Sheathing	Roof/ Wall	Roof Shape	Roof Cover
J.14	Content	WFR	1	8d	Strap	Gable	Shingles
J.15	Content	WFR	1	8d	Strap	Hip	Shingles
J.16	Content	WFR	1	8d	Strap	Flat	BUR, Average
J.17	Content	WFR	1	8d	Strap	Flat	BUR, Poor
J.18	Content	WFR	1	8d	Strap	Flat	EPDM, Average
J.19	Content	WFR	1	8d	Strap	Flat	EPDM, Poor
J.20	Content	WFR	1	6d	Strap	Gable	Shingles
J.21	Content	WFR	1	8d	Toe-Nail	Gable	Shingles
J.22	Content	URM	1	8d	Strap	Gable	Shingles
J.23	Content	RM	1	8d	Strap	Gable	Shingles
J.24	Content	WFR	2	8d	Strap	Gable	Shingles
J.25	Content	WFR	3	8d	Strap	Gable	Shingles
J.26	Content	WFR	4	8d	Strap	Gable	Shingles




Figure J.1. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.2. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Hip Roof with Shingles.




Figure J.3. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality BUR.




Figure J.4. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality BUR.




Figure J.5. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality EPDM.




Figure J.6. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality EPDM.




Figure J.7. Building Loss Function – One-Story, 6d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.8. Building Loss Function – One-Story, 8d Roof Deck Nails, Toe-Nailed Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.9. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Unreinforced Masonry Walls, Gable Roof with Shingles.




Figure J.10. Building Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Reinforced Masonry Walls, Gable Roof with Shingles.




Figure J.11. Building Loss Function – Two-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.12. Building Loss Function – Three-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.13. Building Loss Function – Four-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.14. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.15. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Hip Roof with Shingles.




Figure J.16. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality BUR.




Figure J.17. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality BUR.




Figure J.18. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Average Quality EPDM.




Figure J.19. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Flat Roof with Poor Quality EPDM.




Figure J.20. Content Loss Function – One-Story, 6d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.21. Content Loss Function – One-Story, 8d Roof Deck Nails, Toe-Nailed Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.22. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Unreinforced Masonry Walls, Gable Roof with Shingles.




Figure J.23. Content Loss Function – One-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Reinforced Masonry Walls, Gable Roof with Shingles.




Figure J.24. Content Loss Function – Two-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.25. Content Loss Function – Three-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.




Figure J.26. Content Loss Function – Four-Story, 8d Roof Deck Nails, Strapped Roof Trusses, Wood Frame Walls, Gable Roof with Shingles.

Appendix K.
Loss Functions for Low Rise Masonry Strip Mall
Buildings

Appendix K. Loss Functions for Low Rise Masonry Strip Mall Buildings

This appendix presents loss functions for low rise masonry strip mall buildings (see Section 7.11). The loss functions represent either average building loss normalized by building value or average content loss normalized by content value. Therefore, the loss ratios range between 0 and 1 in both cases. Note that the content value is set to 50% of the building value. For a given simulated storm, the building loss ratio and content loss ratio are estimated based on the modeled damage and the largest gust speed over the entire duration of the simulated storm is saved. The loss functions are then computed by averaging the loss ratios associated with the storms producing a maximum gust speed within 5 mph ranges. The average loss ratios (content or building loss) associated with each 5 mph gust speed range are then plotted at the center of that range. Note that the wind speeds are representative of open terrain at 10 m above ground.

Table K.1 lists the figures provided in this appendix. Figures K.1 through K.18 give example results for the strip mall buildings modeled with a wood roof system. Figures K.19 through K.42 give example results for the strip mall buildings modeled with a steel roof system.

Two sets of nine figures are given for the buildings modeled with a wood roof system. The first set of nine figures (Figures K.1 through K.9) show building loss functions and the second set (Figures K.10 through K.18) show content loss functions. The first figure in each set of nine shows loss results for the 12' high building with 6 units, 8d roof sheathing nails, strapped roof-wall connections, built-up roof cover, unreinforced masonry walls, and situated in Missile Environment A. The remaining eight plots in each set show loss results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles).

Two sets of twelve figures are given for the buildings modeled with a metal roof system. The first set of twelve figures (Figures K.19 through K.30) show building loss functions and the second set (Figures K.31 through K.42) show content loss functions. The first figure in each set of twelve shows loss results for the 20' high building with 6 units, a joist spacing of 6', metal roof deck fastened with welds, SBCCI roof design criteria, built-up roof cover, unreinforced masonry walls, and situated in Missile Environment A. The remaining eleven plots in each set show loss results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles).

Table K.1. Sample Loss Functions for Low Rise Masonry Strip Mall Buildings

Figure	Loss Type	Walls	Height	Number of Units	Roof Frame	Frame Spacing	Roof/Wall	Deck Mat'l.	Deck Attachment	Design Code	Roof Cover	Missile Environ.
K.1	Building	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A
K.2	Building	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	B
K.3	Building	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	C
K.4	Building	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	D
K.5	Building	URM	12'	6	Wood	2'	Strap	Wood	8d	-	SPM	A
K.6	Building	URM	12'	6	Wood	2'	Strap	Wood	6d	-	BUR	A
K.7	Building	RM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A
K.8	Building	URM	12'	6	Wood	2'	Toe-Nail	Wood	8d	-	BUR	A
K.9	Building	URM	20'	6	Wood	2'	Strap	Wood	8d	-	BUR	A
K.10	Content	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A
K.11	Content	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	B
K.12	Content	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	C
K.13	Content	URM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	D
K.14	Content	URM	12'	6	Wood	2'	Strap	Wood	8d	-	SPM	A
K.15	Content	URM	12'	6	Wood	2'	Strap	Wood	6d	-	BUR	A
K.16	Content	RM	12'	6	Wood	2'	Strap	Wood	8d	-	BUR	A
K.17	Content	URM	12'	6	Wood	2'	Toe-Nail	Wood	8d	-	BUR	A
K.18	Content	URM	20'	6	Wood	2'	Strap	Wood	8d	-	BUR	A
K.19	Building	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A
K.20	Building	URM	20'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A
K.21	Building	URM	20'	1	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A
K.22	Building	URM	12'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A
K.23	Building	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	B
K.24	Building	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	C
K.25	Building	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	D
K.26	Building	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	SPM	A
K.27	Building	URM	20'	6	OWSJ	6'	-	Metal	Weld, 50%	SBCCI, 100	BUR	A
K.28	Building	URM	20'	6	OWSJ	6'	-	Metal	Screw	SBCCI, 100	BUR	A
K.29	Building	URM	20'	6	OWSJ	6'	-	Metal	Weld	ASCE, 100	BUR	A
K.30	Building	RM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A
K.31	Content	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A
K.32	Content	URM	20'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A
K.33	Content	URM	20'	1	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A
K.34	Content	URM	12'	6	OWSJ	4'	-	Metal	Weld	SBCCI, 100	BUR	A
K.35	Content	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	B
K.36	Content	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	C
K.37	Content	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	D
K.38	Content	URM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	SPM	A
K.39	Content	URM	20'	6	OWSJ	6'	-	Metal	Weld, 50%	SBCCI, 100	BUR	A
K.40	Content	URM	20'	6	OWSJ	6'	-	Metal	Screw	SBCCI, 100	BUR	A
K.41	Content	URM	20'	6	OWSJ	6'	-	Metal	Weld	ASCE, 100	BUR	A
K.42	Content	RM	20'	6	OWSJ	6'	-	Metal	Weld	SBCCI, 100	BUR	A




Figure K.1. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.2. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B.




Figure K.3. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C.




Figure K.4. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D.




Figure K.5. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.6. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 6d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.7. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A.




Figure K.8. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Toe-Nailed Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.9. Building Loss Function – Strip Mall Building B – Height=20', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.10. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.11. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B.




Figure K.12. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C.




Figure K.13. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D.




Figure K.14. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.15. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 6d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.16. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A.




Figure K.17. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Wood Deck with 8d Nails, Toe-Nailed Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.18. Content Loss Function – Strip Mall Building B – Height=20', No. of Units=6, Wood Deck with 8d Nails, Strapped Roof-Wall Connections, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.19. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.20. Building Loss Function – Strip Mall Building B – Height=20', No. of Units=6, Joist Spacing=4', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.21. Building Loss Function – Strip Mall Building D – Height=20', No. of Units=1, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.22. Building Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Joist Spacing=4', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.23. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B.




Figure K.24. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C.




Figure K.25. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D.




Figure K.26. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.27. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists with 50% Reduction in Resistance, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.28. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Screwed to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.29. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, ASCE 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.30. Building Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A.




Figure K.31. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.32. Content Loss Function – Strip Mall Building B – Height=20', No. of Units=6, Joist Spacing=4', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.33. Content Loss Function – Strip Mall Building D – Height=20', No. of Units=1, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.34. Content Loss Function – Strip Mall Building A – Height=12', No. of Units=6, Joist Spacing=4', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.35. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment B.




Figure K.36. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment C.




Figure K.37. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment D.




Figure K.38. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Single Ply Membrane Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.39. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists with 50% Reduction in Resistance, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.40. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Screwed to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.41. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, ASCE 100 mph Design Criteria, Built-up Roof Cover, Unreinforced Masonry Walls, Missile Environment A.




Figure K.42. Content Loss Function – Strip Mall Building C – Height=20', No. of Units=6, Joist Spacing=6', Metal Deck Welded to Joists, SBCCI 100 mph Design Criteria, Built-up Roof Cover, Reinforced Masonry Walls, Missile Environment A.

Appendix L.
Loss Functions for Pre-Engineered Metal Buildings

Appendix L. Loss Functions for Pre-Engineered Metal Buildings

This appendix presents loss functions for pre-engineered metal buildings (see Chapter 7.12). The loss functions represent either average building loss normalized by building value or average content loss normalized by content value. Therefore, the loss ratios range between 0 and 1 in both cases. Note that the content value is set to 50% of the building value. For a given simulated storm, the building loss ratio and content loss ratio are estimated based on the modeled damage and the largest gust speed over the entire duration of the simulated storm is saved. The loss functions are then computed by averaging the loss ratios associated with the storms producing a maximum gust speed within 5 mph ranges. The average loss ratios (content or building loss) associated with each 5 mph gust speed range are then plotted at the center of that range. Note that the wind speeds are representative of open terrain at 10 m above ground.

Table L.1 lists the figures provided in this appendix. Two sets of five figures are given for the metal buildings. The first set of five figures (Figures L.1 through L.5) show building loss functions and the second set (Figures L.6 through L.10) show content loss functions. The first figure in each set of five shows loss results for the small metal building designed using a 100 mph design speed and with no reduction in the metal roof panel capacity. The remaining four plots in each set show loss results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles).

Table L.1. Sample Loss Functions for Pre-Engineered Metal Buildings

Figure	Loss Type	Model Building	Design Wind Speed	Metal Panel Capacity
L.1	Building	Small	100 mph	Full
L.2	Building	Medium	100 mph	Full
L.3	Building	Large	100 mph	Full
L.4	Building	Small	90 mph	Full
L.5	Building	Small	100 mph	50%
L.6	Content	Small	100 mph	Full
L.7	Content	Medium	100 mph	Full
L.8	Content	Large	100 mph	Full
L.9	Content	Small	90 mph	Full
L.10	Content	Small	100 mph	50%




Figure L.1. Building Loss Ratios versus Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.2. Building Loss Ratios versus Peak Gust Wind Speed – Medium Metal Building, 100 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.3. Building Loss Ratios versus Peak Gust Wind Speed – Large Metal Building, 100 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.4. Building Loss Ratios versus Peak Gust Wind Speed – Small Metal Building, 90 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.5. Building Loss Ratios versus Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, 50% Reduction in Metal Panel Capacity.




Figure L.6. Content Loss Ratios versus Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.7. Content Loss Ratios versus Peak Gust Wind Speed – Medium Metal Building, 100 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.8. Content Loss Ratios versus Peak Gust Wind Speed – Large Metal Building, 100 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.9. Content Loss Ratios versus Peak Gust Wind Speed – Small Metal Building, 90 mph Design Speed, No Reduction in Metal Panel Capacity.




Figure L.10. Content Loss Ratios versus Peak Gust Wind Speed – Small Metal Building, 100 mph Design Speed, 50% Reduction in Metal Panel Capacity.

Appendix M.
**Loss Functions for Engineered Residential and
Commercial Buildings**

Appendix M. Loss Functions for Engineered Residential and Commercial Buildings

This appendix presents loss functions for engineered residential and commercial buildings (see Section 7.13). The loss functions represent either average building loss normalized by building value or average content loss normalized by content value. Therefore, the loss ratios range between 0 and 1 in both cases. Note that the content value is set to 50% of the building value. For a given simulated storm, the building loss ratio and content loss ratio are estimated based on the modeled damage and the largest gust speed over the entire duration of the simulated storm is saved. The loss functions are then computed by averaging the loss ratios associated with the storms producing a maximum gust speed within 5 mph ranges. The average loss ratios (content or building loss) associated with each 5 mph gust speed range are then plotted at the center of that range. Note that the wind speeds are representative of open terrain at 10 m above ground.

Table M.1 lists the figures provided in this appendix. Loss functions for the two-, five- and eight-story engineered buildings are given in Figures M.1 through M.18, M.19 through M.36 and M.37 through M.54, respectively. Two sets of nine figures are given for each of the two-, five- and eight-story engineered buildings. The first set of nine figures shows building loss functions and the second set shows content loss functions. The first figure in each set of nine shows loss results for the engineered residential building having 33% glazing coverage, a built-up roof cover and situated in Missile Environment A. The remaining eight plots in each set show loss results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles).

Table M.1. Sample Loss Functions for Engineered Residential and Commercial Buildings

Figure	Loss Type	Stories	Occupancy	Roof Deck	Roof Cover	Glazing	Missile Environ.
M.1	Building	2	Residential	Metal	BUR	33%	A
M.2	Building	2	Residential	Metal	BUR	20%	A
M.3	Building	2	Residential	Metal	BUR	50%	A
M.4	Building	2	Residential	Metal	SPM	33%	A
M.5	Building	2	Residential	Metal	BUR	33%	B
M.6	Building	2	Residential	Metal	BUR	33%	C
M.7	Building	2	Residential	Metal	BUR	33%	D
M.8	Building	2	Commercial	Metal	BUR	33%	A
M.9	Building	2	Residential	Concrete	BUR	33%	A
M.10	Content	2	Residential	Metal	BUR	33%	A
M.11	Content	2	Residential	Metal	BUR	20%	A
M.12	Content	2	Residential	Metal	BUR	50%	A
M.13	Content	2	Residential	Metal	SPM	33%	A
M.14	Content	2	Residential	Metal	BUR	33%	B

Table M.1. Sample Loss Functions for Engineered Residential and Commercial Buildings (concluded)

Figure	Loss Type	Stories	Occupancy	Roof Deck	Roof Cover	Glazing	Missile Environ.
M.15	Content	2	Residential	Metal	BUR	33%	C
M.16	Content	2	Residential	Metal	BUR	33%	D
M.17	Content	2	Commercial	Metal	BUR	33%	A
M.18	Content	2	Residential	Concrete	BUR	33%	A
M.19	Building	5	Residential	Metal	BUR	33%	A
M.20	Building	5	Residential	Metal	BUR	20%	A
M.21	Building	5	Residential	Metal	BUR	50%	A
M.22	Building	5	Residential	Metal	SPM	33%	A
M.23	Building	5	Residential	Metal	BUR	33%	B
M.24	Building	5	Residential	Metal	BUR	33%	C
M.25	Building	5	Residential	Metal	BUR	33%	D
M.26	Building	5	Commercial	Metal	BUR	33%	A
M.27	Building	5	Residential	Concrete	BUR	33%	A
M.28	Content	5	Residential	Metal	BUR	33%	A
M.29	Content	5	Residential	Metal	BUR	20%	A
M.30	Content	5	Residential	Metal	BUR	50%	A
M.31	Content	5	Residential	Metal	SPM	33%	A
M.32	Content	5	Residential	Metal	BUR	33%	B
M.33	Content	5	Residential	Metal	BUR	33%	C
M.34	Content	5	Residential	Metal	BUR	33%	D
M.35	Content	5	Commercial	Metal	BUR	33%	A
M.36	Content	5	Residential	Concrete	BUR	33%	A
M.37	Building	8	Residential	Metal	BUR	33%	A
M.38	Building	8	Residential	Metal	BUR	20%	A
M.39	Building	8	Residential	Metal	BUR	50%	A
M.40	Building	8	Residential	Metal	SPM	33%	A
M.41	Building	8	Residential	Metal	BUR	33%	B
M.42	Building	8	Residential	Metal	BUR	33%	C
M.43	Building	8	Residential	Metal	BUR	33%	D
M.44	Building	8	Commercial	Metal	BUR	33%	A
M.45	Building	8	Residential	Concrete	BUR	33%	A
M.46	Content	8	Residential	Metal	BUR	33%	A
M.47	Content	8	Residential	Metal	BUR	20%	A
M.48	Content	8	Residential	Metal	BUR	50%	A
M.49	Content	8	Residential	Metal	SPM	33%	A
M.50	Content	8	Residential	Metal	BUR	33%	B
M.51	Content	8	Residential	Metal	BUR	33%	C
M.52	Content	8	Residential	Metal	BUR	33%	D
M.53	Content	8	Commercial	Metal	BUR	33%	A
M.54	Content	8	Residential	Concrete	BUR	33%	A




Figure M.1. Building Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.2. Building Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.3. Building Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.4. Building Loss Function – Two-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.5. Building Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment B.




Figure M.6. Building Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment C.




Figure M.7. Building Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment D.




Figure M.8. Building Loss Function – Two-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.9. Building Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Concrete Roof Deck, Missile Environment A.




Figure M.10. Content Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.11. Content Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.12. Content Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.13. Content Loss Function – Two-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.14. Content Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment B.




Figure M.15. Content Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment C.




Figure M.16. Content Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment D.




Figure M.17. Content Loss Function – Two-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.18. Content Loss Function – Two-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Concrete Roof Deck, Missile Environment A.




Figure M.19. Building Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.20. Building Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.21. Building Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.22. Building Loss Function – Five-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.23. Building Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment B.




Figure M.24. Building Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment C.




Figure M.25. Building Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment D.




Figure M.26. Building Loss Function – Five-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.27. Building Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Concrete Roof Deck, Missile Environment A.




Figure M.28. Content Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.29. Content Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.30. Content Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.31. Content Loss Function – Five-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.31. Content Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment B.




Figure M.33. Content Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment C.




Figure M.34. Content Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment D.




Figure M.35. Content Loss Function – Five-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.36. Content Loss Function – Five-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Concrete Roof Deck, Missile Environment A.




Figure M.37. Building Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.38. Building Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.39. Building Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.40. Building Loss Function – Eight-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.41. Building Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment B.




Figure M.42. Building Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment C.




Figure M.43. Building Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment D.




Figure M.44. Building Loss Function – Eight-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.45. Building Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Concrete Roof Deck, Missile Environment A.




Figure M.46. Content Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.47. Content Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 20% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.48. Content Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 50% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.49. Content Loss Function – Eight-Story Engineered Residential Building – Single Ply Membrane Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.50. Content Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment B.




Figure M.51. Content Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment C.




Figure M.52. Content Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment D.




Figure M.53. Content Loss Function – Eight-Story Engineered Commercial Building – Built-up Roof Cover, 33% Glazing Coverage, Metal Roof Deck, Missile Environment A.




Figure M.54. Content Loss Function – Eight-Story Engineered Residential Building – Built-up Roof Cover, 33% Glazing Coverage, Concrete Roof Deck, Missile Environment A.

Appendix N.
Loss Functions for Industrial Buildings

Appendix N. Loss Functions for Industrial Buildings

This appendix presents loss functions for industrial buildings (see Section 7.14). The loss functions represent either average building loss normalized by building value or average content loss normalized by content value. Therefore, the loss ratios range between 0 and 1 in both cases. Note that the content value is set to 50% of the building value. For a given simulated storm, the building loss ratio and content loss ratio are estimated based on the modeled damage and the largest gust speed over the entire duration of the simulated storm is saved. The loss functions are then computed by averaging the loss ratios associated with the storms producing a maximum gust speed within 5 mph ranges. The average loss ratios (content or building loss) associated with each 5 mph gust speed range are then plotted at the center of that range. Note that the wind speeds are representative of open terrain at 10 m above ground.

Table N.1 lists the figures provided in this appendix. Two sets of three figures are given for the industrial buildings. The first set of three figures (Figures N.1 through N.3) show building loss functions and the second set (Figures N.4 through N.6) show content loss functions. The first figure in each set of three shows loss results for the industrial building constructed with unreinforced masonry walls, having no reduction in the metal roof deck capacity and situated in Missile Environment A. The remaining two plots in each set show damage state results for buildings which are different by a single variable in comparison to the reference building (note that the changed variable is underlined in the figure titles).

Table N.1. Sample Loss Functions for Industrial Buildings

Figure	Loss Type	Walls	Metal Deck Capacity	Missile Environ.
N.1	Building	URM	Full	A
N.2	Building	RM	Full	A
N.3	Building	URM	50%	A
N.4	Content	URM	Full	A
N.5	Content	RM	Full	A
N.6	Content	URM	50%	A




Figure N.1. Building Loss Function – Industrial Building – No Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A.




Figure N.2. Building Loss Function – Industrial Building – No Reduction in Metal Deck Capacity, Reinforced Masonry Walls, Missile Environment A.




Figure N.3. Building Loss Function – Industrial Building – 50% Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A.




Figure N.4. Content Loss Function – Industrial Building – No Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A.




Figure N.5. Content Loss Function – Industrial Building – No Reduction in Metal Deck Capacity, Reinforced Masonry Walls, Missile Environment A.




Figure N.6. Content Loss Function – Industrial Building – 50% Reduction in Metal Deck Capacity, Unreinforced Masonry Walls, Missile Environment A.

