

of maintenance performed and the person conducting the maintenance.

(h) *Container cooling and cooling water.* (1) Potable water shall be used for cooling except as provided for in paragraphs (h) (2) and (3) of this section.

(2) Cooling canal water shall be chlorinated or treated with a chemical approved by the Administrator as having a bactericidal effect equivalent to chlorination. There shall be a measurable residual of the sanitizer in the water at the discharge point of the canal. Cooling canals shall be cleaned and replenished with potable water to prevent the buildup of organic matter and other materials.

(3) Container cooling waters that are recycled or reused shall be handled in systems that are so designed, operated, and maintained so there is no buildup of microorganisms, organic matter, and other materials in the systems and in the waters. System equipment, such as pipelines, holding tanks and cooling towers, shall be constructed and installed so that they can be cleaned and inspected. In addition, the establishment shall maintain, and make available to Program employees for review, information on at least the following:

- (i) System design and construction;
- (ii) System operation including the rates of renewal with fresh, potable water and the means for treating the water so that there is a measurable residual of an acceptable sanitizer, per paragraph (h)(2) of this section, in the water at the point where the water exits the container cooling vessel;
- (iii) System maintenance including procedures for the periodic cleaning and sanitizing of the entire system; and
- (iv) Water quality standards, such as microbiological, chemical and physical, monitoring procedures including the frequency and site(s) of sampling, and the corrective actions taken when water quality standards are not met.

(i) *Post-process handling of containers.* Containers shall be handled in a manner that will prevent damage to the hermetic seal area. All worn and frayed belting, can retarders, cushions, and the like shall be replaced with non-porous materials. To minimize container abrasions, particularly in the

seal area, containers should not remain stationary on moving conveyors. All post-process container handling equipment should be kept clean so there is no buildup of microorganisms on surfaces in contact with the containers.

(Approved by the Office of Management and Budget under control number 0583-0015)

[51 FR 45634, Dec. 19, 1986, as amended at 65 FR 34390, May 30, 2000]

§ 381.306 Processing and production records.

At least the following processing and production information shall be recorded by the establishment: Date of production; product name and style; container code; container size and type; and the process schedule, including the minimum initial temperature. Measurements made to satisfy the requirements of § 381.303 regarding the control of critical factors shall be recorded. In addition, where applicable, the following information and data shall also be recorded:

(a) *Processing in steam—(1) Batch still retorts.* For each retort batch, record the retort number or other designation, the approximate number of containers or the number of retort crates per retort load, product initial temperature, time steam on, the time and temperature vent closed, the start of process timing, time steam off, and the actual processing time. The indicating temperature device and the temperature recorder shall be read at the same time at least once during process timing and the observed temperatures recorded.

(2) *Batch agitating retorts.* In addition to recording the information required for batch, still steam retorts in paragraph (a)(1) of this section, record the functioning of the condensate bleeders and the retort or reel speed.

(3) *Continuous rotary retorts.* Record the retort system number, the approximate total number of containers retorted, product initial temperature, time steam on, the time and temperature vent closed, time process temperature reached, the time the first can enters and the time the last can exits the retort. The retort or reel speed shall be determined and recorded at intervals not to exceed 4 hours. Readings of the indicating temperature device(s) and

temperature recorder(s) shall be made and recorded at the time the first container enters the retort and thereafter with sufficient frequency to ensure compliance with the process schedule. These observations should be made and recorded at intervals not exceeding 30 minutes of continuous retort operation. Functioning of the condensate bleeder(s) shall be observed and recorded at the time the first container enters the retort and thereafter as specified in § 381.305(b)(3)(v).

(4) *Hydrostatic retorts.* Record the retort system number, the approximate total number of containers retorted, product initial temperature, time steam on, the time and temperature vent(s) closed, time process temperature reached, time first containers enter the retort, time last containers exit the retort, and, if specified in the process schedule, measurements of temperatures in the hydrostatic water legs. Readings of the temperature indicating device, which is located in the steam/water interface, and the temperature recording device shall be observed and the temperatures recorded at the time the first containers enter the steam dome. Thereafter, these instruments shall be read and the temperatures recorded with sufficient frequency to ensure compliance with the temperature specified in the process schedule and should be made at least every hour of continuous retort operation. Container conveyor speed, and for agitating hydrostatic retorts, the rotative chain speed, shall be determined and recorded at intervals of sufficient frequency to ensure compliance with the process schedule and should be performed at least every 4 hours.

(b) *Processing in water—(1) Batch still retorts.* For each retort batch, record the retort number or other designation, the approximate number of containers or number of retort crates per retort load, product initial temperature, time steam on, the start of process timing, water level, water recirculation rate (if critical), overriding pressure maintained, time steam off, and actual processing time. The indicating temperature device and the temperature recorder shall be read at the same time at least once during

process timing and the observed temperatures recorded.

(2) *Batch agitating retorts.* In addition to recording the information required in paragraph (b)(1) of this section, record the retort or reel speed.

(c) *Processing in steam/air mixtures.* For each retort batch, record the retort number or other designation, the approximate number of containers or number of retort crates per retort load, product initial temperature, time steam on, venting procedure, if applicable, the start of process timing, maintenance of circulation of the steam/air mixture, air flow rate or forced recirculation flow rate (if critical), overriding pressure maintained, time steam off, and actual processing time. The indicating temperature device and the temperature recorder shall be read at the same time at least once during process timing and the observed temperatures recorded.

(d) *Atmospheric cookers—(1) Batch-type systems.* For each cooker batch, record the cooker number or other designation and the approximate number of containers. In addition, record all critical factors of the process schedule such as cooker temperature, initial temperature, the time the thermal process cycle begins and ends, hold time, and the final internal product temperature.

(2) *Continuous-type systems.* Record the cooker number or other designation, the time the first containers enter and the last containers exit a cooker, and the approximate total number of containers processed. In addition, record all critical factors of the process schedule such as the initial temperature, cooker speed, and final internal product temperature.

(Approved by the Office of Management and Budget under control number 0583-0015)

§ 381.307 Record review and maintenance.

(a) *Process records.* Charts from temperature/time recording devices shall be identified by production date, container code, processing vessel number or other designation and other data as necessary to enable correlation with the records required in § 381.306. Each entry on a record shall be made at the time the specific event occurs, and the