

(5) Scuttle meets the requirements for location, strength, and height of coaming in subchapter E of this chapter.

(f) Each vertical ladder must—

(1) Have rungs that are—

(i) At least 410 millimeters (16 inches) long;

(ii) At most 300 millimeters (12 inches) apart, uniform for the length of the ladder; and

(iii) At least 180 millimeters (7 inches) from the nearest permanent object in back of the ladder;

(2) Have at least 115 millimeters (4½ inches) of clearance above each rung;

(3) Be made of incombustible materials; and

(4) Have an angle of inclination with the horizontal, greater than 70 degrees but not more than 90 degrees.

(g) No means may be provided for locking any interior door giving access to either of the two required means of escape, except that a crash door or locking-device, capable of being easily forced in an emergency, may be employed if a permanent and conspicuous notice to this effect is attached to both sides of the door. A means may be provided for locking an exterior door to a deckhouse if the door is—

(1) Locked only by a key under the control of one of the OSV's officers; and

(2) Always operable from the inside.

(h) Each passageway or stairway must be wide enough to provide an effective means of escape for the number of persons having access to it even if each person is wearing a lifejacket. There must be no protrusions in the means of escape that could cause injury, ensnare clothing, or damage lifejackets.

(i) No interior stairway, other than within the machinery spaces or cargo holds, may be less than 710 millimeters (28 inches) wide. The angle of inclination of each stairway with the horizontal must not exceed 50 degrees.

(j) No dead-end passageway, or equivalent, may be more than 13.1 meters (40 feet) in length.

(k) Vertical access must be provided between the various weather decks by means of vertical or permanently inclined ladders. The angles of inclination of the inclined ladders with the

horizontal must not exceed 70 degrees, except that vertical ladders may be used for access to pilot-house tops and other house tops used only for weather protection.

(l) Only one means of escape need be provided from each of the spaces stipulated in paragraph (a) of this section, provided the maximum area of each space is less than 28 square meters (300 square feet) and the maximum dimension (length, breadth, or depth) of each space is less than 6 meters (20 feet).

(m) Alternative means of escape from spaces may be provided if acceptable to the cognizant OCMI.

§ 127.250 Ventilation for enclosed spaces.

(a) Each enclosed space within the vessel must be properly vented or ventilated. Means must be provided for closing each vent and ventilator.

(b) Means must be provided for stopping each fan in a ventilation system serving machinery and cargo spaces and for closing, in case of fire, each doorway, ventilator, and annular space around funnels and other openings into such spaces.

§ 127.260 Ventilation for accommodations.

(a) Each accommodation space must be adequately ventilated in a manner suitable for the purpose of the space.

(b) Each vessel of 100 or more gross tons must be provided with a mechanical ventilation system unless the cognizant OCMI is satisfied that a natural system, such as opening windows, portholes, or doors, will accomplish adequate ventilation in ordinary weather.

§ 127.270 Location of accommodations and pilothouse.

(a) Neither quarters for crew members or offshore workers nor the pilot-house may be located forward of the collision bulkhead required by §174.190 of this chapter.

(b) Except as provided in paragraph (c) of this section, no part of any deck with accommodations for crew members or offshore workers may be below the deepest load waterline.

(c) Any deck with accommodations for crew members or offshore workers

§ 127.280

46 CFR Ch. I (10–1–02 Edition)

may be below the deepest load waterline if—

(1) The vessel complies with the damage-stability requirements in §174.205 of this chapter; and

(2) The deck head of the space is not below the deepest load waterline.

(d) No hawse pipe or chain pipe may pass through accommodations for crew members or offshore workers.

(e) There must be no direct access, except through solid, close-fitted doors or hatches, between accommodations and chain lockers, cargo spaces, or machinery spaces.

(f) No sounding tubes, or vents from fuel-oil or cargo-oil tanks may open into accommodations for crew members or offshore workers, except that sounding tubes may open into passageways.

(g) No access openings from fuel-oil or cargo-oil tanks may open into quarters for crew members or offshore workers.

(h) Quarters for crew members must be separate from and independent of those for offshore workers unless the cognizant OCMI approves an alternative arrangement.

§127.280 Construction and arrangement of quarters for crew members and accommodations for offshore workers.

(a) The following requirements apply to quarters for crew members on each vessel of 100 or more gross tons:

(1) Quarters for crew members must be divided into staterooms none of which berths more than four members.

(2) Each stateroom for use by crew members must—

(i) Have clear headroom of at least 1.9 meters (6 feet, 3 inches); and

(ii) Contain at least 2.8 square meters (30 square feet) of deck and at least 6 cubic meters (210 cubic feet) of space for each member accommodated. The presence in a stateroom of equipment for use by the occupants does not diminish the area or volume of the room.

(3) There must be at least one toilet, one washbasin, and one shower or bathtub for every eight or fewer crew members who do not occupy a stateroom to which a private or a semiprivate facility is attached.

(b) The following requirements apply to accommodations for offshore work-

ers on each vessel of 100 or more gross tons:

(1) Each offshore worker aboard must be provided with adequate fixed seating. The width of each seat should be at least 460 millimeters (18 inches). The spacing of fixed seating must be sufficient to allow ready escape in case of fire or other emergency. The following are minimal requirements:

(i) Aisles 4.6 meters (15 feet) in length or less must not be less than 610 millimeters (24 inches) wide.

(ii) Aisles more than 4.6 meters (15 feet) in length must not be less than 760 millimeters (30 inches) wide.

(iii) Where the seating is in rows, the distance from seat front to seat front must not be less than 760 millimeters (30 inches).

(2) If the intended operation of a vessel is to carry offshore workers aboard for more than 24 hours, quarters for them must be provided. Each stateroom for use by them must—

(i) Berth no more than six workers;

(ii) Have clear headroom of at least 1.9 meters (6 feet, 3 inches); and

(iii) Contain at least 1.9 square meters (20 square feet) of deck and at least 4 cubic meters (140 cubic feet) of space for each worker accommodated. The presence in a stateroom of equipment for use by the occupants does not diminish the area or volume of the room.

(3) Toilets and washbasins for use by offshore workers must meet the requirements of paragraph (a)(3) of this section.

(c) Each crew member and offshore worker aboard a vessel of less than 100 gross tons must be provided with accommodations of adequate size and construction, and with equipment for his or her protection and convenience suitable to the size, facilities, and service of the vessel.

(d) For each vessel of 100 or more gross tons, the bulkheads and decks separating accommodations for crew members and offshore workers from machinery spaces must be of "A" Class construction as defined by §92.07–5 of this chapter.

(e) After reviewing the arrangement drawings required by §127.110 of this