

Table E417.25-2

Safe-and-Arm Device Qualification	Section E417.7	Quantity Tested		
		X=1 ⁽⁴⁾	X=6 ⁽⁵⁾	X=3 ⁽⁶⁾
Barrier Alignment	E417.25(o)			
Acceptance Tests ⁽¹⁾	Table E417.25-1	X	X	-
Safety Tests:	E417.25(e)			
Extended Stall	E417.25(e)(3)	X	-	-
Abnormal Drop	E417.9(l)	X	-	-
Containment	E417.25(e)(1)	-	-	1
Barrier Functionality	E417.25(e)(2)	-	-	2
Safing Verification	E417.25(e)(6)	-	X	-
Non-Operating Environment Tests:	E417.9			
Storage Temperature	E417.9(b)	-	X	-
Transportation Shock	E417.9(d)	-	X	-
Bench Handling shock	E417.9(e)	-	X	-
Transportation Vibration	E417.9(f)	-	X	-
Fungus Resistance	E417.9(g)	-	1	-
Salt Fog	E417.9(h)	-	1	-
Fine Sand	E417.9(I)	-	1	-
Handling Drop	E417.9(k)	-	X	-
Performance Verification:	E417.3(d)			
Safe-and-Arm Device Status-of-Health ⁽²⁾	E417.25(b)		X	
Abbreviated Performance Verification:	E417.3(e)			