

CONTENTS

Abstract	1
Introduction	1
Construction/Design issues	2
Materials and methods	3
Quality assurance	4
Experimental results.....	4
Evaluating potential for sample contamination.....	4
Particle-size and concentration-range evaluations for the prototype 14-L Teflon® churn for a single withdrawal	4
Particle-size and concentration-range evaluations for the prototype 14-L Teflon® churn with multiple withdrawals	5
Evaluation of the efficacy of the valve baffle	6
Conclusions and recommendations.....	8
References cited	8
Appendix A: Organic parameters determined in the blank samples and source water.....	9
Appendix B: Inorganic parameters determined in the blank samples and source water.....	12

Tables

Table 1. Concentration and grain-size ranges used to evaluate the prototype 14-L Teflon® churn	3
2. Results for “blind” reference slurries for the U.S. Geological Survey Kentucky District Sediment Laboratory	4
3. Replicate results from the prototype 14-liter Teflon® and polyethylene churn splitters for single withdrawals for a variety of concentrations and grain-size ranges.....	5
4. Replicate results from the prototype 14-liter Teflon® and polyethylene churn splitters for multiple withdrawals for a variety of concentrations and grain-size ranges.....	7
5. Data on the effect of the valve baffle on sediment concentration from the single withdrawal tests.....	8