



U.S. Department  
of Transportation  
**Research and  
Special Programs  
Administration**

MAR 3 2000

400 Seventh Street, S.W.  
Washington, D.C. 20590

DOT-E 8802  
(SECOND REVISION)

EXPIRATION DATE: February 28, 2002

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Eurotainer SA  
Paris France (U.S. Agent: Eurotainer US, Inc.  
Somerset, NJ)
2. PURPOSE AND LIMITATION: This exemption authorizes the use  
of a non-DOT specification IMO type 5 portable tank for the  
transportation of materials listed in paragraph 6 below.  
This exemption provides no relief from any regulation other  
than as specifically stated herein.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-  
180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.315.
5. BASIS: This exemption is based on the application of  
Eurotainer US, Inc. dated February 15, 2000, submitted in  
accordance with § 107.109.
6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous materials description -- proper shipping name	Hazard Class/ Division	Identi- fication Number	Packing Group
Difluoroethane	2.1	UN1030	n/a
Chlorodifluoromethane	2.2	UN1018	n/a
Chloropentafluoroethane	2.2	UN1020	n/a
1,1,1,2-Tetrafluoroethane	2.2	UN3159	n/a

MAR 3 2000

Continuation of DOT-E 8802. (2nd rev.)

Page 2

7. SAFETY CONTROL MEASURES:

a. Packaging prescribed is a non-DOT specification portable tank, mounted in an ISO frame, designed and constructed in accordance with Westerwalder Eisenwerk (WEW) drawings CS-674/Ob, CS-674/3c and list of drawings CS-674, technical specifications and calculations on file with the Office of Hazardous Materials Exemptions and Approvals (OHMEA) and in compliance with the following:

- (1) Code--Complies with ASME Code (not Code stamped);  
IMO Type 5.
- (2) Insulation--None
- (3) Water Capacity (U.S. Gallons)--4,360 (nominal).
- (4) Material--German Steel TT St E 47; yield strength-67,700 psi; tensile strength-86,000 psi; equivalent to ASTM A572 Grade 65.

(5) Tank Size (inches) (outside dia.) x (length) x (thickness)  
78.74 x 225.8 x 0.504

Head Thickness--0.531  
Weld Joint Efficiency--1.0  
Corrosion Allowance--0.0  
Number of Baffles--3

- (6) Design Pressure (PSIG)--275.5  
Note: Design pressure means "maximum allowable working pressure (MAWP)" as used in the ASME Code.
- (7) Test Pressure, Minimum (PSIG)--435
- (8) Openings--One(1), 20 inch diameter manhole on the front head; two(2), safety relief device pads on top, one(1), liquid phase outlet and one(1) gas phase outlet on the bottom.
- (9) Tank surface area (square feet)--411
- (10) Pressure Relief Devices--Two(2), 2 inch diameter spring loaded safety relief valves set at 303 psig. Total relief device capacity is 25,423 SCFM.
- (11) G-Loadings: Vertical down 2; Vertical up 2; longitudinal 2; and Transverse 2.

(12) Maximum Gross Weight (pounds) 57,320.

(13) Maximum Commodity Weight (pounds) 41,115.

(14) Tare Weight (pounds) 16,205.

(15) Design Specific Gravity 1.13.

(16) Design Temperature (!F) 122.

#### 8. SPECIAL PROVISIONS.

a. A person who is not a holder of this exemption who receives a package covered by this exemption may reoffer it for transportation provided no modifications or changes are made to the package and it is reoffered for transportation in conformance with this exemption and the HMR.

b. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

c. Each portable tank must be plainly marked on both sides near the middle, in letters at least two inches high on a contrasting background, "DOT-E 8802".

d. Hydrostatic test certificates for each tank must be maintained by the owner or manufacturer at its principal business office and be made available to any representative of the DOT upon request.

e. No product may be shipped that has venting requirements exceeding 25,423 SCFM, or has a specific gravity greater than 1.41. The venting capacity required for each product must be determined by the flow formulas contained in Compressed Gas Association (CGA) Pamphlet S-1.2.

f. The tank must be filled in accordance with the provisions of § 173.315.

g. Each tank must be (i) visually inspected prior to each trip to ensure that it has not been damaged on the previous trip; and (ii) be retested and reinspected in accordance with the provisions of § 173.32b except the use of an approval agency is not required.

h. Portable tanks may not be transported in container-on-flat car (COFC) or trailer-on-flat car (TOFC) service except under conditions approved by the Associate Administrator for Safety, Federal Railroad Administration.

i. Shippers using the packaging covered by this exemption must comply with all provisions of this exemption, and all other applicable requirements contained in 49 CFR Parts 171-180.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight and cargo vessel.
10. MODAL REQUIREMENTS: A copy of this exemption must be carried aboard each cargo vessel or motor vehicle used to transport packages covered by this exemption.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
  - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued at Washington, D.C.:



**MAR 3 2000**

FOR

Robert A. McGuire  
Acting Associate Administrator  
for Hazardous Materials Safety

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.  
Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Dist: FHWA, FRA, USCG  
PO: AM(00)