

**THE ENVIRONMENTAL TECHNOLOGY VERIFICATION
PROGRAM**



ETV Joint Verification Statement

TECHNOLOGY TYPE: DUST SUPPRESSANT

APPLICATION: CONTROL OF DUST ON UNPAVED ROADS

TECHNOLOGY NAME: DustGard

COMPANY: NORTH AMERICAN SALT COMPANY

ADDRESS: 9900 W. 109th STREET, STE 600
OVERLAND PARK, KS 66210
PHONE: 913-344-9391

WEB SITE: <http://www.nasalt.com/>

E-MAIL: kubalikb@compassminerals.com

The U.S. Environmental Protection Agency (EPA) has created the Environmental Technology Verification (ETV) Program to facilitate the deployment of innovative or improved environmental technologies through performance verification and dissemination of information. The goal of the ETV Program is to further environmental protection by accelerating the acceptance and use of improved and cost-effective technologies. ETV seeks to achieve this goal by providing high-quality, peer-reviewed data on technology performance to those involved in the design, distribution, financing, permitting, purchase, and use of environmental technologies.

ETV works in partnership with recognized standards and testing organizations; stakeholder groups, which consist of buyers, vendor organizations, permittees, and other interested parties; and with the full participation of individual technology developers. The program evaluates the performance of innovative technologies by developing test plans that are responsive to the needs of stakeholders, conducting field or laboratory tests (as appropriate), collecting and analyzing data, and preparing peer-reviewed reports. All evaluations are conducted in accordance with rigorous quality assurance (QA) protocols to ensure that data of known and adequate quality are generated and that the results are defensible.

The Air Pollution Control Technology (APCT) Verification Center, a center under the ETV Program, is operated by RTI International (RTI) in cooperation with EPA's National Risk Management Research Laboratory. The APCT Center has evaluated the performance of a dust suppressant product for control of dust on an unpaved road.

ETV TEST DESCRIPTION

A field test program was designed by RTI and Midwest Research Institute (MRI) to evaluate the performance of dust suppressant products. Five dust suppressants manufactured or distributed by three firms were tested in this program. The field test for North American Salt Company's DustGard was conducted at Fort Leonard Wood, Missouri (FLW). A July 2003 test/QA plan for the field testing was developed and approved by EPA. The test/QA plan describes the procedures and methods used for the tests. The July 2003 version of the test/QA plan was based on an October 2002 version and a subsequent test/QA plan addendum (dated February 19, 2003). The goal of each test was to measure the performance of the products relative to uncontrolled sections of road over a 1-year period. Field testing was planned quarterly over a 1-year period; however, some logistical difficulties related to winter weather and then maintenance activities on the roads of interest arose, and the test/QA plan was revised (Rev 3) to address those issues. Test periods occurred per the test/QA plan for three roughly 6-month periods. Two of those test periods are summarized below and are considered most representative of product performance; the third testing period occurred after unexpected road maintenance, and those data may be seen in the verification report. The verification report also contains 90 percent confidence limits for the data collected during all of the test periods. Emissions measurements were made for total particulate (TP), particulate matter less than or equal to 10 micrometers (μm) in aerodynamic diameter (PM_{10}), and for particulate matter less than or equal to 2.5 μm in aerodynamic diameter ($\text{PM}_{2.5}$).

The host facility for the field test program, FLW, is a U.S. Army base. The test site used unpaved Roads P and PA in training area (TA) 236. Roads P and PA are the main access routes to TA 236 and are traveled by truck convoys, as well as traffic into and out of TA 236. DustGard was applied to test section E, located on Road PA; and test section F, located on Road P, was left untreated as the experimental control. Section 3.1 of the verification report provides a figure showing the test locations. Testing was conducted during October 2002, May 2003, and October 2003.

Table 1 presents test conditions for key parameters that may affect the performance of dust suppressants on unpaved roads.

Table 1. Test Conditions

Parameter	FLW, October 2003	FLW, May 2003
Initial application rate, l/m^2	2.5	2.5
Follow-up application rate, l/m^2	2.5	2.4
Time between application and testing, days	122	79
Precipitation during test week, cm	0.2	3.7
Precipitation during week before testing, cm	1.8	3.2
Precipitation between application and testing, total, cm	39	24
Soil moisture during test weeks, %—uncontrolled road	0.62–1.5	0.01-1.8
Soil moisture during test weeks, %—controlled road	1.9–3.5	0.20-0.42
Soil silt during test weeks, %—uncontrolled road	1.7–5.4	1.6-4.3
Soil silt during test weeks, %—controlled road	1.2 – 1.7	1.2-2.6

The DustGard product was analyzed using an array of chemical and toxicity tests. The results of these tests are included in the appendices to the verification report. A summary of the toxicity data is presented in Table 2.

Table 2. Toxicity Test Results

Species	Acute LC ₅₀ for survival	Chronic LC ₅₀ for survival	Chronic EC ₅₀
<i>Ceriodaphnia dubia</i>	>1,000 mg/L (48-hr)	>1,000 mg/L (7-d)	>1,000 mg/L (7-d), reproduction
Fathead minnow	>1,000 mg/L (96-hr)	>1,000 mg/L (7-d)	>1,000 mg/L (7-d), growth
<i>Americamysis bahia</i>	>1,000 mg/L (96-hr)	>1,000 mg/L (7-d)	>1,000 mg/L (7-d), growth, fecundity

d = day
 EC₅₀ = effective concentration which affects 50% of sample population
 hr = hour
 LC₅₀ = lethal concentration which kills 50% of sample population
 LOEC = lowest observed effective concentration
 mg/L = milligrams per liter
 NOEC = no observed effect concentration

VERIFIED TECHNOLOGY DESCRIPTION

This verification statement is applicable to *North American Salt Company's DustGard*, which is a hygroscopic product made of magnesium chloride. The material safety data sheet (MSDS) for DustGard is retained in the RTI project files and is available at [http://www.nasalt.com/msds/Magnesium%20Chloride%20\(liquid\).pdf](http://www.nasalt.com/msds/Magnesium%20Chloride%20(liquid).pdf) [accessed July 2005].

VERIFICATION OF PERFORMANCE

The overall reduction in particulate matter emissions achieved by the DustGard dust suppressant compared to uncontrolled sections of road is shown in Table 3.

Table 2. Summary of Test Results

Test location and period	Average control efficiency, %			Noted events
	TP	PM ₁₀	PM _{2.5}	
FLW, October 2003	86	>90	59	Rain events the day before test. ^a
FLW, May 2003	75	88	58	Rain events the morning of test. ^b

^a All test sections were wet from rain the previous day. The uncontrolled section was heavily potholed and another section was used for the test. MRI used traffic to dry the road before testing.

^b Rainfall in the morning meant that the uncontrolled section of the road was wet and another section was used for the test.

The APCT Center QA officer has reviewed the test results and quality control data and has concluded that the data quality objectives given in the generic verification protocol and test/QA plan have been attained. EPA and APCT Center QA staff have conducted technical assessments at the test organization and of the data handling. These confirm that the ETV tests were conducted in accordance with the EPA-approved test/QA plan.

This verification statement verifies the effectiveness of *North American Salt Company's DustGard* to control dust on unpaved roads as described above. Extrapolation outside that range should be done with caution and an understanding of the scientific principles that control the performance of the technologies. This verification focused on emissions. Potential technology users may obtain other types of performance information from the manufacturer.

In accordance with the generic verification protocol, this verification statement is valid, commencing on the date below, indefinitely for application of *North American Salt Company's DustGard* to control dust on unpaved roads.

<u>Signed by Sally Gutierrez</u>	<u>9/25/2005</u>	<u>Signed by Andrew Trenholm</u>	<u>9/16/2005</u>
Sally Gutierrez, Director	Date	Andrew R. Trenholm, Director	Date
National Risk Management Research Laboratory		Air Pollution Control Technology Verification Center	
Office of Research and Development			
United States Environmental Protection Agency			