

Environmental Protection Agency

§ 432.15

the provisions of this subpart, in addition to the discharge allowed by § 432.12(a):

| Effluent characteristic | Effluent limitations | |
|-------------------------|--|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kilograms per 1,000 kg ELWK) | |
| BOD5 | 0.04 | 0.02 |
| TSS | 0.08 | 0.04 |
| | English units (pounds per 1,000 lb ELWK) | |
| BOD5 | 0.04 | 0.02 |
| TSS | 0.08 | 0.04 |

(d) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the wet or low temperature rendering of material derived from animals slaughtered at locations other than the slaughterhouse, which may be discharged by a point source subject to the provisions of this subpart, in addition to the discharge allowed by § 432.12(a):

| Effluent characteristic | Effluent limitations | |
|-------------------------|--|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kilograms per 1,000 kg ELWK) | |
| BOD5 | 0.06 | 0.03 |
| TSS | 0.12 | 0.06 |
| | English units (pounds per 1,000 lb ELWK) | |
| BOD5 | 0.06 | 0.03 |
| TSS | 0.12 | 0.06 |

(e) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the dry rendering of material derived from animals slaughtered at locations other than the slaughterhouse, which may be discharged by a point source subject to the provisions of this subpart, in addition to the discharge allowed by § 432.12(a):

| Effluent characteristic | Effluent limitations | |
|-------------------------|--|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kilograms per 1,000 kg ELWK) | |
| BOD5 | 0.02 | 0.01 |
| TSS | 0.04 | 0.02 |
| pH | (¹) | (¹) |
| | English units (pounds per 1,000 lb ELWK) | |
| BOD5 | 0.02 | 0.01 |
| TSS | 0.04 | 0.02 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

[39 FR 7897, Feb. 28, 1974, as amended at 60 FR 33964, June 29, 1995]

§ 432.13 [Reserved]

§ 432.14 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH | No limitation. |
| BOD5 | Do. |
| TSS | Do. |
| Oil and grease | Do. |
| Fecal coliform | Do. |

[40 FR 6446, Feb. 11, 1975, as amended at 60 FR 33964, June 29, 1995]

§ 432.15 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to on-site slaughter or subsequent meat, meat product or by-product processing of carcasses of animals slaughtered on-site which may be discharged by a new source subject to