## §432.16

the provisions of this subpart: the limitations shall be as specified in §432.12(a), with the exception that in addition to the pollutants or pollutant properties controlled by that subsection, discharges of ammonia shall not exceed the limitations set forth below:

	Effluent limitations	
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—
	Metric units (kilograms per 1,000 kg LWK)	
Ammonia	0.34	0.17
	English units (pounds per 1,000 lb LWK)	
Ammonia	0.34	0.17

(b) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the processing of blood derived from animals slaughtered at locations other than the slaughterhouse, which may be discharged by a new source subject to the provisions of this subpart, in addition to the discharge allowed by §§ 432.15(a) and 432.12(c):

•		
	Effluent limitations	
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—
	Metric units (kilograms per 1,000 kg ELWK)	
Ammonia	0.06	0.03
	English units (pounds per 1,000 lb ELWK)	
Ammonia	0.06	0.03

(c) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the wet or low temperature rendering of material derived from animals slaughtered at locations other than slaughterhouse, which may be discharged by a new source subject to the provisions of this subpart, in addition

to the discharge allowed by §§ 432.15(a) and 432.12(d):

	Effluent limitations	
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—
	Metric units (kilograms per 1,000 kg ELWK)	
Ammonia	0.10	0.05
	English units (pounds per 1,000 lb ELWK)	
Ammonia	0.10	0.05

(d) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the dry rendering of material derived from animals slaughtered at locations other than the slaughterhouse which may be discharged by a new source subject to the provisions of this subpart, in addition to the discharge allowed by §§ 432.15(a) and 432.12(e):

	Effluent limitations		
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—	
	Metric units (kilograms per 1,000 kg ELWK)		
Ammonia	0.04	0.02	
	English units (pounds per 1,000 lb ELWK)		
Ammonia	0.04	0.02	

[39 FR 7897, Feb. 28, 1974; 39 FR 26423, July 19, 1974]

## §432.16 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33964, June 29, 1995]