Environmental Protection Agency

	Effluent limitations	
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—
	Metric units (kilograms per 1,000 kg ELWK)	
BOD5	0.02	0.01
TSS	0.04	0.02
	English units (pounds per 1,000 lb ELWK)	
BOD5	0.02	0.01
TSS	0.04	0.02

[39 FR 7897, Feb. 28, 1974; 39 FR 26423, July 19, 1974, as amended at 45 FR 82254, Dec. 15, 1980; 60 FR 33964, June 29, 1995]

§432.23 [Reserved]

§ 432.24 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
pH	No limitation. Do. Do. Do. Do. Do.

[40 FR 6446, Feb. 11, 1975, as amended at 60 FR 33965, June 29, 1995]

§ 432.25 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to on-site slaughter or subsequent meat, meat product or byproduct processing of carcasses of animals slaughtered on-site which may be discharged by a new source subject to the provisions of this subpart: The limitations shall be as specified in

§432.22(a), with the exception that in addition to the pollutants or pollutant properties controlled by that subsection, discharges of ammonia shall not exceed the limitations set forth below:

	Effluent limitations	
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—
	Metric units (kilograms per 1,000 kg LWK)	
Ammonia	0.48	0.24
	English units (pounds per 1,000 lb LWK)	
Ammonia	0.48	0.24

(b) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the processing of blood derived from animals slaughtered at locations other than the slaughterhouse, which may be discharged by a new source subject to the provisions of this subpart, in addition to the discharge allowed by paragraph (a) of this section and §432.22(c):

	Effluent limitations		
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—	
	Metric units (kilograms per 1,000 kg ELWK)		
Ammonia	0.06	0.03	
	English units (pounds per 1,000 lb ELWK)		
Ammonia	0.06	0.03	

(c) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the wet or low temperature rendering of material derived from animals slaughtered at locations other than the slaughterhouse, which may be discharged by a new source subject to the provisions of this subpart, in addition to the discharge allowed by paragraph (a) of this section and §432.22(d):