## §428.14

|                         | Effluent limitations                        |   |  |
|-------------------------|---|---|--|
| Effluent characteristic | Maximum<br>for any 1<br>day                 | Average of daily<br>values for 30<br>consecutive days<br>shall not ex-<br>ceed— |  |
|                         | Metric units (kg/kkg of raw material)       |   |  |
| TSS                     | 0.096                                       | 0.064   |  |
| Oil and grease          | 0.024                                       | .016  |  |
| рН                      | (1)   | (1)   |  |
|                         | English units (lb/1,000 lb of raw material) |   |  |
| TSS                     | 0.096                                       | 0.064   |  |
| Oil and grease          | 0.024                                       | .016  |  |
| рН                      | (1)   | (1)   |  |

<sup>1</sup>Within the range 6.0 to 9.0.

(b) All plants constructed before 1959 shall employ the best available maintenance and housekeeping practices in order to minimize the discharge of oil and grease in nonprocess waste waters. The concentration of oil and grease in discharges of nonprocess waste waters shall meet the following limitations:

(1) The average of daily values for 30 consecutive days shall not exceed 5 mg/ 1.

(2) The maximum for any one day shall not exceed 10 mg/l.

[39 FR 6662, Feb. 21, 1974; 39 FR 26423, July 19, 1974, as amended at 40 FR 18173, Apr. 25, 1975]

#### §428.14 [Reserved]

### §428.15 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

# 40 CFR Ch. I (7-1-03 Edition)

|                         | Effluent limitations                  |   |  |
|-------------------------|---------------------------------------|---|--|
| Effluent characteristic | Maximum<br>for any 1<br>day           | Average of daily<br>values for 30<br>consecutive days<br>shall not ex-<br>ceed— |  |
|                         | Metric units (kg/kkg of raw material) |   |  |
| TSS                     | 0.096                                 | 180.064   |  |
| Oil and grease          | 0.024                                 | .016  |  |
| рН                      | (1)                                   | (1)   |  |

English units (lb/1,000 lb of raw material)

| _              |       | ·     |
|----------------|-------|-------|
| TSS            | 0.096 | 0.064 |
| Oil and grease | 0.024 | .016  |
| рН             | (1)   | (1)   |
|                |       |       |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 6662, Feb. 21, 1974; 39 FR 26423, July 19, 1974]

#### §428.16 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33963, June 29, 1995]

# Subpart B—Emulsion Crumb Rubber Subcategory

### §428.20 Applicability; description of the emulsion crumb rubber subcategory.

The provisions of this subpart are applicable to discharges of pollutants resulting from the manufacture of emulcrumb rubber, other than sion acrylonitrilebutadiene rubber.

[40 FR 18173, Apr. 25, 1975]

## §428.21 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

[39 FR 6662, Feb. 21, 1974, as amended at 40 FR 18173, Apr. 25, 1975]