§86.000-3

tail pipe exhaust emissions and evaporative emissions over the Urban Dynamometer Driving Schedule as described in appendix I to this part.

505 Cycle means the test cycle that consists of the first 505 seconds (seconds 1 to 505) of the EPA Urban Dynamometer Driving Schedule, described in §86.115-00 and listed in appendix I, paragraph (a), of this part.

SC03 means the test cycle, described in §86.160-00 and listed in appendix I, paragraph (h), of this part, which is designed to represent driving immediately following startup.

Supplemental FTP, or SFTP means the additional test procedures designed to measure emissions during aggressive and microtransient driving, as described in §86.159-00 over the US06 cycle, and also the test procedure designed to measure urban driving emissions while the vehicle's air conditioning system is operating, as described in §86.160-00 over the SC03 cycle.

US06 means the test cycle, described in §86.159-00 and listed in appendix I, paragraph (g), of this part, which is designed to evaluate emissions during aggressive and microtransient driving.

[61 FR 54878, Oct. 22, 1996]

§86.000-3 Abbreviations.

The abbreviations in §86.098-3 continue to apply to 1998 and later model year vehicles. The abbreviations in this section apply beginning with the 2000 model year:

A/C—Air conditioning
FTP—Federal Test Procedure
SFTP—Supplemental Federal Test Procedure
WOT—Wide Open Throttle
[61 FR 54878, Oct. 22, 1996]

§ 86.000-7 Maintenance of records; submittal of information; right of entry.

Section 86.000-7 includes text that specifies requirements that differ from \$86.091-7, \$86.094-7 or \$86.096-7. Where a paragraph in \$86.091-7, \$86.094-7 or \$86.096-7 is identical and applicable to \$86.000-7, this may be indicated by specifying the corresponding paragraph and the statement "[Reserved]. For guidance see \$86.091-7." or "[Reserved].

For guidance see §86.094-7." or "[Reserved]. For guidance see §86.096-7."

- (a) introductory text through (a)(2) [Reserved]. For guidance see § 86.091–7.
- (a)(3) [Reserved]. For guidance see §86.094-7.
- (b)-(c)(2) [Reserved]. For guidance see $\S 86.091-7$.
- (c)(3) [Reserved]. For guidance see $\S 86.094-7$.
- (c)(4)-(d)(1)(v) [Reserved]. For guidance see §86.091-7.
- (d)(1)(vi)-(d)(2)(iv) [Reserved]. For guidance see § 86.094-7.
- (d) (3)–(g) [Reserved]. For guidance see $\S 86.091$ –7.
- (h)(1) The manufacturer (or contractor for the manufacturer, if applicable) of any model year 2000 through 2002 light-duty vehicle or light light-duty truck or model year 2002 through 2004 heavy light-duty truck that is certified shall establish, maintain, and retain the following adequately organized and indexed records for each such vehicle:
 - (i) EPA engine family;
 - (ii) Vehicle identification number;
 - (iii) Model year and production date;
 - (iv) Shipment date;
 - (v) Purchaser; and
 - (vi) Purchase contract.
- (h)(2)-(h)(5) [Reserved]. For guidance see §86.094-7.
- (h)(6) Voiding a certificate. (i) EPA may void ab initio a certificate for a vehicle certified to Tier 1 certification standards or to the respective evaporative and/or refueling test procedure and accompanying evaporative and/or refueling standards as set forth or otherwise referenced in §§ 86.000–8, 86.000–9, or 86.098–10 for which the manufacturer fails to retain the records required in this section or to provide such information to the Administrator upon request.
- (h)(6)(ii)-(h)(7)(vi) [Reserved]. For guidance see §86.096-7.
- (h)(7)(vii) EPA evaporative/refueling family.

[61 FR 54878, Oct. 22, 1996]

§ 86.000-8 Emission standards for 2000 and later model year light-duty vehicles.

Section 86.000-8 includes text that specifies requirements that differ from

Environmental Protection Agency

§86.096-8 or §86.099-8. Where a paragraph in §86.096-8 or §86.099-8 is identical and applicable to §86.000-8, this may be indicated by specifying the corresponding paragraph and the statement "[Reserved]. For guidance see §86.096-8." or "[Reserved]. For guidance see §86.099-8."

- (a)(1) introductory text through (a)(1)(ii)(B) [Reserved]. For guidance see \$86.096-8.
- (a)(1)(iii)-(b)(4) [Reserved]. For guidance see §86.099-8.
- (b)(5) [Reserved]. For guidance see §86.096-8.
- (b)(6) [Reserved]. For guidance see $\S 86.099-8$.
- (c) [Reserved]. For guidance see § 86.096-8.
- (d) [Reserved]. For guidance see §86.099-8.
- (e) SFTP Standards. (1) Exhaust emissions from 2000 and later model year light-duty vehicles shall meet the additional SFTP standards of table

A00-2 (defined by useful life, fuel type, and test type) according to the implementation schedule in table A00-1. The standards set forth in table A00-2 refer to exhaust emissions emitted over the Supplemental Federal Test Procedure (SFTP) as set forth in subpart B of this part and collected and calculated in accordance with those procedures. Compliance with these standards are an additional requirement to the required compliance with Tier 1 standards as defined in §8 86.096-8 (a)(1) introductory text through (a)(1)(ii)(B) and 86.099-8 (a)(1)(iii)-(a)(3):

TABLE A00-1—IMPLEMENTATION SCHEDULE FOR LIGHT-DUTY VEHICLES FOR (NMHC=NO $_{\rm X}$) AND CO

Model year	Percentage	
2000	40	
2001	80	
2002	100	

Table A00–2—Useful Life Standards (G/MI) for Light-Duty Vehicles for (NMHC=NO $_{\rm X}$) and CO

Useful life	Fuel type	NMHC=NO _x composite	СО		
			A/C test	US06 test	Composite option
Intermediate	Gasoline	0.65 1.48	3.0 NA	9.0 9.0	3.4 3.4
Full	Gasoline	0.91 2.07	3.7 NA	11.1 11.1	4.2 4.2

- (i) A minimum of the percentage shown in table A00-1 of a manufacturer's sales of the applicable model year's light-duty vehicles shall not exceed the applicable SFTP standards in table A00-2 when tested under the procedures as ubpart B of this part indicated for 2000 and later model year light-duty vehicles.
- (ii) Optionally, a minimum of the percentage shown in table A00–1 of a manufacturer's combined sales of the applicable model year's light-duty vehicles and light light-duty trucks shall not exceed the applicable SFTP standards. Under this option, the light-duty vehicles shall not exceed the applicable SFTP standards in table A00–2, and the light light-duty trucks shall not exceed the applicable SFTP standards in table A00–4 of §86.000–9.
- (iii) Sales percentages for the purposes of determining compliance with this paragraph (e)(1) shall be based on total actual U.S. sales of light-duty vehicles of the applicable model year by a manufacturer to a dealer, distributor, fleet operator, broker, or any other entity which comprises the point of first sale. If the option of paragraph (e)(1)(ii) of this section is taken, such sales percentages shall be based on the total actual combined U.S. sales of light-duty vehicles and light light-duty trucks of the applicable model year by a manufacturer to a dealer, distributor, fleet operator, broker, or any other entity which comprises the point of first sale.
- (iv) The manufacturer may petition the Administrator to allow actual volume produced for U.S. sale to be used in lieu of actual U.S. sales for purposes of determining compliance with the

§ 86.000-9

implementation schedule sales percentages of table A00-1. Such petition shall be submitted within 30 days of the end of the model year to the Vehicle Programs and Compliance Division. For the petition to be granted, the manufacturer must establish to the satisfaction of the Administrator that actual production volume is functionally equivalent to actual sales volume.

- (2) These SFTP standards do not apply to vehicles certified on alternative fuels, but the standards do apply to the gasoline and diesel fuel operation of flexible fuel vehicles and dual fuel vehicles.
- (3) These SFTP standards do not apply to vehicles tested at high altitude.
- (4) The air to fuel ratio shall not be richer at any time than the leanest air to fuel mixture required to obtain maximum torque (lean best torque), plus a tolerance of six (6) percent. The Administrator may approve a manufacturer's request for additional enrichment if it can be shown that additional enrichment is needed to protect the engine or emissions control hardware.
- (5) The requirement to use a single roll dynamometer (or a dynamometer which produces equivalent results), discussed in §§ 86.108-00, 86.118-00, and 86.129-00, applies to all SFTP and FTP test elements as set forth in subpart B of this part for families which are designated as SFTP compliant under the implementation schedule in table A00-1.
- (6) Small volume manufacturers, as defined in $\S 86.094-14(b)(1)$ and (2), are exempt from the requirements of this paragraph (e) until model year 2002, when 100 percent compliance with the standards of this paragraph (e) is required. This exemption does not apply to small volume engine families as defined in $\S 86.094-14(b)(5)$.
- (7) The manufacturer must state at the time of Application for Certification, based on projected U.S. sales or projected production for U.S. sale, which families will be used to attain the required implementation schedule sales percentages for certification purposes.
- (8) A manufacturer cannot use one set of engine families to meet its intermediate useful life standards and an-

other to meet its full useful life standards. The same families which are used to meet the intermediate useful life standards will be required without deviation to meet the corresponding full useful life standards.

- (9) Compliance with composite standards shall be demonstrated using the calculations set forth in §86.164-00.
 - (f) [Reserved]
- (g)–(k) [Reserved]. For guidance see \$86.096-8.

[61 FR 54878, Oct. 22, 1996]

§ 86.000-9 Emission standards for 2000 and later model year light-duty trucks.

Section 86.000-9 includes text that specifies requirements that differ from \$86.097-9 or \$86.099-9. Where a paragraph in \$86.097-9 or \$86.099-9 is identical and applicable to \$86.000-9, this may be indicated by specifying the corresponding paragraph and the statement "[Reserved]. For guidance see \$86.097-9." or "[Reserved]. For guidance see \$86.099-9."

- (a)(1) introductory text through (a)(1)(iii) [Reserved]. For guidance see §86.097-9.
- (a)(1)(iv)-(b)(4) [Reserved]. For guidance see §86.099-9.
 - (b)(5) [Reserved]
- (c) [Reserved]. For guidance see $\S 86.097-9$.
 - (d) [Reserved]
- (e) SFTP Standards. (1) Light lightduty trucks. (i) Exhaust emissions from 2000 and later model year light light-duty trucks shall meet the additional SFTP standards of table A00-4 (defined by useful life, fuel type, truck type, loaded vehicle weight (LVW), and test type) according to the implementation schedule in table A00-3. The standards set forth in table A00-4 refer to exhaust emissions emitted over the Supplemental Federal Test Procedure (SFTP) as set forth in subpart B of this part and collected and calculated in accordance with those procedures. Compliance with these standards are an additional requirement to the required compliance with Tier 1 standards as defined in §§86.097-9(a)(1) introductory text through (a)(1)(iii) and 86.099-9(a)(1)(iv)-(a)(3):