

TABLE 1—PROPERTIES FOR REFERENCE C<sub>16</sub>–C<sub>18</sub> IOS SBF USED IN DISCHARGE SEDIMENT TOXICITY TESTING—Continued

Mud weight of SBF discharged with cuttings (pounds per gallon)	Reference C <sub>16</sub> –C <sub>18</sub> IOS SBF (pounds per gallon)	Reference C <sub>16</sub> –C <sub>18</sub> IOS SBF synthetic to water ratio (%)
11–14 .....	11.5	80/20
>14 .....	14.5	85/15
Plastic Viscosity (PV), centipoise (cP) .....	12–30	
Yield Point (YP), pounds/100 sq. ft .....	10–20	
10-second gel, pounds/100 sq. ft .....	8–15	
10-minute gel, pounds/100 sq. ft .....	12–30	
Electrical stability, V .....	>300	

[66 FR 6901, Jan. 22, 2001]

**Subpart B [Reserved]**

**Subpart C—Onshore Subcategory**

**§ 435.30 Applicability; description of the onshore subcategory.**

The provisions of this subpart are applicable to those facilities engaged in the production, field exploration, drilling, well completion and well treatment in the oil and gas extraction industry which are located landward of the inner boundary of the territorial seas as defined in 40 CFR 125.1(gg) and which are not included within subpart D, E, or F, *Provided, however*, That the applicability of this subpart to (a) facilities in existence on April 13, 1979 or thereafter engaged in the production, field exploration, drilling, well completion and well treatment in the oil and gas extraction industry which are located on land and which would have been considered “coastal” as defined under the interim final regulations for this industry (40 CFR 435.41, 41 FR 44942, October 13, 1976) or which are (b) located in the Santa Maria Basin of California is suspended.

(Secs. 301, 304(b) and 501 of the Clean Water Act as amended, 33 U.S.C. 1251 *et seq.*)

[44 FR 22075, Apr. 13, 1979, as amended at 47 FR 31555, July 21, 1982]

**§ 435.31 Specialized definitions.**

For the purpose of this subpart:

(a) The general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

**§ 435.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): there shall be no discharge of waste water pollutants into navigable waters from any source associated with production, field exploration, drilling, well completion, or well treatment (i.e., produced water, drilling muds, drill cuttings, and produced sand).

[60 FR 33966, June 29, 1995]

**Subpart D—Coastal Subcategory**

SOURCE: 61 FR 66125, Dec. 16, 1996, unless otherwise noted.

**§ 435.40 Applicability; description of the coastal subcategory.**

The provisions of this subpart are applicable to those facilities engaged in field exploration, drilling, well production, and well treatment in the oil and gas industry in areas defined as “coastal.” The term “coastal” shall mean:

(a) Any location in or on a water of the United States landward of the inner boundary of the territorial seas; or

(b)(1) Any location landward from the inner boundary of the territorial seas and bounded on the inland side by the