

**Environmental Protection Agency**

**§ 430.104**

**§ 430.103 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in 40 CFR 401.16) in § 430.102 of this subpart for the best practicable control technology currently available (BPT).

(b) For secondary fiber non-deink facilities where paperboard from wastepaper is produced, non-continuous dischargers shall not be subject to the maximum day and average-of-30-consecutive-days limitations, but shall be subject to annual average effluent limitations determined by dividing the average-of-30-consecutive-days limitations for BOD<sub>5</sub> and TSS by 1.77 and 2.18.

(c) For secondary fiber non-deink facilities where builders' paper and roofing felt from wastepaper are produced, non-continuous dischargers shall not

be subject to the maximum day and average-of-30-consecutive-days limitations, but shall be subject to annual average effluent limitations determined by dividing the average-of-30-consecutive-days limitations for BOD<sub>5</sub> and TSS by 1.90 and 1.90.

**§ 430.104 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart where chlorophenolic-containing biocides are used must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT). Non-continuous dischargers shall not be subject to the maximum day mass limitations in kg/kkg (lb/1000 lb) but shall be subject to concentration limitations. Concentration limitations are only applicable to non-continuous dischargers. Permittees not using chlorophenolic-containing biocides must certify to the permit-issuing authority that they are not using these biocides:

**SUBPART J**

[BAT effluent limitations for secondary fiber non-deink facilities where paperboard from wastepaper is produced]

| Pollutant or pollutant property                       | Maximum for any 1 day                      |                  |
|---|--|------------------|
|   | Kg/kkg (or pounds per 1,000 lb) of product | Milligrams/liter |
| Pentachlorophenol .....                               | 0.00087                                    | (0.029)(7.2)/y   |
| Trichlorophenol .....                                 | 0.00030                                    | (0.010)(7.2)/y   |
| y = wastewater discharged in kgal per ton of product. |  |                  |

**SUBPART J**

[BAT effluent limitations for secondary fiber non-deink facilities where builders' paper and roofing felt from wastepaper are produced]

| Pollutant or pollutant property                       | Maximum for any 1 day                      |                  |
|---|--|------------------|
|   | Kg/kkg (or pounds per 1,000 lb) of product | Milligrams/liter |
| Pentachlorophenol .....                               | 0.0017                                     | (0.029)(14.4)/y  |
| Trichlorophenol .....                                 | 0.00060                                    | (0.010)(14.4)/y  |
| y = wastewater discharged in kgal per ton of product. |  |                  |