

§ 430.10

color for this mill on the basis of best professional judgment.

[63 FR 18635, Apr. 15, 1998, as amended at 65 FR 46108, July 27, 2000]

Subpart A—Dissolving Kraft Subcategory

§ 430.10 Applicability; description of the dissolving kraft subcategory.

The provisions of this subpart apply to discharges resulting from the production of dissolving pulp at kraft mills.

§ 430.11 Specialized definitions.

For the purpose of this subpart, the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 and §430.01 of this part shall apply to this subpart.

40 CFR Ch. I (7–1–04 Edition)

§ 430.12 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT), except that non-continuous dischargers shall not be subject to the maximum day and average of 30 consecutive days limitations but shall be subject to annual average effluent limitations:

SUBPART A
[BPT effluent limitations]

| Pollutant or pollutant property | Kg/kkg (or pounds per 1,000 lb) of product | | |
|---------------------------------|--|---|----------------------------|
| | Continuous dischargers | | Non-continuous dischargers |
| | Maximum for any 1 day | Average of daily values for 30 consecutive days | |
| BOD5 | 23.6 | 12.25 | 6.88 |
| TSS | 37.3 | 20.05 | 11.02 |
| pH | (¹) | (¹) | (¹) |

¹ Within the range of 5.0 to 9.0 at all times.

(b) The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, resulting from the use of wet barking operations, which may be discharged by a point source subject to the provisions of this subpart. These limitations are in addition to the limitations set forth in paragraph (a) of

this section and shall be calculated using the proportion of the mill's total production due to use of logs which are subject to such operations. Non-continuous dischargers shall not be subject to the maximum day and average of 30 consecutive days limitations, but shall be subject to annual average effluent limitations:

SUBPART A
[BPT effluent limitations]

| Pollutant or pollutant property | Kg/kkg (or pounds per 1,000 lb) of product | | |
|---------------------------------|--|---|---|
| | Continuous dischargers | | Non-continuous dischargers (annual average) |
| | Maximum for any 1 day | Average of daily values for 30 consecutive days | |
| BOD5 | 3.2 | 1.7 | 0.95 |
| TSS | 6.9 | 3.75 | 2.0 |