## **Environmental Protection Agency**

SUBPART B

[BPT effluent limitations for bleached kraft facilities where paperboard, coarse paper, and tissue paper are produced]

Pollutant or pollutant parameter	Kg/kkg (or pounds per 1,000 lb) of product		
	Continuous dischargers		Non-contin-
	Maximum for any 1 day	Average of daily values for 30 con- secutive days	uous dis- chargers (annual average)
BOD5	0.45 1.25	0.25 0.7 (¹)	0.10 0.35 (¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 5.0 to 9.0 at all times.

SUBPART B

[BPT effluent limitations for bleached kraft facilities where pulp and fine papers are produced]

Pollutant or pollutant parameter	Kg/kkg (or pounds per 1,000 lb) of product		
	Continuous dischargers		Non contin
	Maximum for any 1 day	Average of daily values for 30 con- secutive days	Non-contin- uous dis- chargers (annual average)
BOD5	0.35 1.15	0.2 0.6	0.10 0.30
pH	(1)	(¹)	( <sup>1</sup> )

<sup>&</sup>lt;sup>1</sup> Within the range of 5.0 to 9.0 at all times.

SUBPART B
[BPT effluent limitations for soda facilities where pulp and papers are produced]

Kg/kkg (or pounds per 1,000 lb) of product		
Continuous dischargers		Non contin
Maximum for any 1 day	Average of daily values for 30 con- secutive days	Non-contin- uous dis- chargers (annual average)
0.3 1.1	0.2 0.55	0.10 0.35
	Continuous  Maximum for any 1 day	Continuous dischargers  Maximum for any 1 day  0.3  Product  Average of daily values for 30 consecutive days

<sup>&</sup>lt;sup>1</sup>Within the range of 5.0 to 9.0 at all times.

## § 430.23 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). The limitations shall be the same as those

specified in §430.22 of this subpart for the best practicable control technology currently available (BPT).

§ 430.24 Effluent limitations representing the degree of effluent reduction attainable by the application of best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must