Environmental Protection Agency

specified for conventional pollutants (which are defined in 40 CFR 401.16) in §430.92 of this subpart for the best practicable control technology currently available (BPT).

§ 430.94 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart where chlorophenolic-containing biocides are

used must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT). Non-continuous dischargers shall not be subject to the maximum day mass limitations in kg/kkg (lb/1000 lb) but shall be subject to concentration limitations. Concentration limitations are only applicable to non-continuous dis-Permittees not chargers. using chlorophenolic-containing biocides must certify to the permit-issuing authority that they are not using these biocides:

SUBPART I [Facilities where fine or tissue paper is produced]

Pollutant or pollutant property	BAT effluent limitations Maximum for any 1 day	
	Pentachlorophenol Trichlorophenol y = wastewater discharged in kgal per ton of product.	

SUBPART I
[Facilities where newsprint is produced]

Pollutant or pollutant property	BAT effluent limitations Maximum for any 1 day	
	Pentachlorophenol Trichlorophenol y = wastewater discharged in kgal per ton of product.	

§ 430.95 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS), except that non-continuous dischargers shall not be subject to the maximum day and average of 30 consecutive days effluent limitations for BOD5 and TSS, but shall be subject to annual average effluent limitations. Also, for non-continuous dischargers, concentration lim-

itations (mg/l) shall apply, where provided. Concentration limitations will only apply to non-continuous dis-Only facilities chargers. where chlorophenolic-containing biocides are used shall be subject pentachlorophenol and trichlorophenol limitations. Permittees not using chlorophenolic-containing biocides must certify to the permit-issuing authority that they are not using these biocides: