

§ 425.65

| Pollutant or pollutant property | BPT limitations | |
|---------------------------------|--|-----------------------------|
| | Maximum for any 1 day | Maximum for monthly average |
| | kg/kg (or pounds per 1,000 pounds) of raw material | |
| BOD5 | 3.2 | 1.5 |
| TSS | 4.7 | 2.1 |
| Oil & Grease | 1.4 | 0.61 |
| Total Chromium | 0.08 | 0.03 |
| pH | (¹) | (¹) |

¹ Within the range of 6.0 to 9.0.

[47 FR 52870, Nov. 23, 1982, as amended at 53 FR 9183, Mar. 21, 1988]

§ 425.65 Pretreatment standards for existing sources (PSES).

Except as provided in § 425.04 and 40 CFR 403.7 and 403.13, any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403, and achieve the following pretreatment standards:

| Pollutant or pollutant property | PSES | |
|---------------------------------|-----------------------------|-----------------------------|
| | Maximum for any 1 day | Maximum for monthly average |
| | Milligrams per liter (mg/l) | |
| Sulfide | 24 | |
| Total chromium | 12 | 8 |
| pH | (¹) | (¹) |

¹ Not less than 7.0.

[47 FR 52870, Nov. 23, 1982, as amended at 61 FR 35685, July 8, 1996]

§ 425.66 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7 and 425.04, any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment must comply with 40 CFR part 403, and must achieve the pretreatment standards contained in § 425.65.

Subpart G—Shearling Subcategory

§ 425.70 Applicability; description of the shearling subcategory.

The provisions of this subpart are applicable to process wastewater discharges resulting from any tannery which processes raw or cured sheep or

40 CFR Ch. I (7-1-04 Edition)

sheep-like skins with the wool or hair retained into finished leather by chrome tanning, and retan-wet finishing.

§ 425.71 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Pollutant or pollutant property | NSPS | |
|---------------------------------|--|-----------------------------|
| | Maximum for any 1 day | Maximum for monthly average |
| | kg/kg (or pounds per 1,000 pounds) of raw material | |
| BOD5 | 3.0 | 1.3 |
| TSS | 4.3 | 1.9 |
| Oil & Grease | 1.2 | 0.55 |
| Total Chromium | 0.08 | 0.03 |
| pH | (¹) | (¹) |

¹ Within the range of 6.0 to 9.0.

[47 FR 52870, Nov. 23, 1982, as amended at 53 FR 9183, Mar. 21, 1988]

§ 425.72 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The effluent limitations are those for BOD5, TSS, Oil and Grease, and pH contained in § 425.71.

§ 425.73 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point